

---

# **A Lot of Effort Documentation**

***Release 0.4.1***

**Audrey Roy**

**Sep 27, 2017**



---

## Contents

---

<b>1</b>	<b>A Lot of Effort</b>	<b>3</b>
1.1	Documentation . . . . .	3
1.2	Quickstart . . . . .	3
1.3	Features . . . . .	3
<b>2</b>	<b>Installation</b>	<b>5</b>
2.1	Install the “alotofeffort” package . . . . .	5
2.2	Configure boto . . . . .	5
<b>3</b>	<b>Usage</b>	<b>7</b>
<b>4</b>	<b>Contributing</b>	<b>9</b>
4.1	Submitting Feedback . . . . .	9
4.2	Getting Started . . . . .	9
4.3	Pull Request Guidelines . . . . .	10
4.4	Tips . . . . .	10
<b>5</b>	<b>Credits</b>	<b>11</b>
5.1	Development Lead . . . . .	11
5.2	Contributors . . . . .	11
<b>6</b>	<b>History</b>	<b>13</b>
6.1	0.4.0 (2015-09-15) . . . . .	13
6.2	0.3 (2013-07-27) . . . . .	13
6.3	0.2 (2013-07-17) . . . . .	13
6.4	0.1 (2013-07-14) . . . . .	13
<b>7</b>	<b>Indices and tables</b>	<b>15</b>



Contents:



# CHAPTER 1

---

## A Lot of Effort

---

Instantly deploy static HTML sites to S3 at the command line.

I created this out of frustration, after spending a lot of effort trying to find a PyPI package that did this without problems.

## Documentation

The full documentation is at <http://alotofeffort.rtd.org>.

## Quickstart

Install it:

```
pip install alotofeffort
```

Configure Boto the standard way in `~/.boto`:

```
[Credentials]
aws_access_key_id = ...
aws_secret_access_key = ...
```

Then use it to deploy a static HTML website to an S3 bucket:

```
$ alotofeffort www/ mybucket
```

## Features

- Uses standard Boto configuration.

- Prints the S3 endpoint URL after deploying.
- Auto-configures the bucket to be a website, with all files public.
- Only files that have changed get uploaded. Files are checked for changes by comparing the local and remote MD5 hashes of the files.
- Never auto-deletes. In fact, it doesn't delete files at all! (In the future, it will check if any files need to be deleted from S3, and prompt you before deleting anything.)



### Install the “alotofeffort” package

At the command line:

```
$ easy_install alotofeffort
```

Or, if you have virtualenvwrapper installed:

```
$ mkvirtualenv alotofeffort
$ pip install alotofeffort
```

### Configure boto

Save the following in *~/.boto*:

```
[Credentials]
aws_access_key_id = ...
aws_secret_access_key = ...
```

Replace ... with your AWS access credentials, of course.



## CHAPTER 3

---

### Usage

---

Deploy a static website with this command:

```
$ alotofeffort www/ mybucket
```

- *www/*: A directory containing the static HTML/JS/CSS to be deployed.
- *mybucket*: The name of your S3 bucket.



Contributions are welcome!

### Submitting Feedback

The best way to send feedback is to file an issue at <https://github.com/audreyr/alotofeffort/issues>.

If you are reporting a bug, please include:

- Your operating system name and version.
- Any details about your local setup that might be helpful in troubleshooting.
- Detailed steps to reproduce the bug.

If you are proposing a feature:

- Explain in detail how it would work.
- Keep the scope as narrow as possible, to make it easier to implement.
- Remember that this is a volunteer-driven project, and that contributions are welcome :)

### Getting Started

Here's how to set up *alotofeffort* for local development.

1. Fork the *alotofeffort* repo on GitHub.
2. Clone your fork locally:

```
$ git clone git@github.com:your_name_here/alotofeffort.git
```

3. Install your local copy into a virtualenv. Assuming you have virtualenvwrapper installed, this is how you set up your fork for local development:

```
$ mkvirtualenv alotofeffort
$ cd alotofeffort/
$ python setup.py develop
```

4. Create a branch for local development:

```
$ git checkout -b name-of-your-bugfix-or-feature
```

Now you can make your changes locally.

5. When you're done making changes, check that your changes pass flake8 and the tests, including testing other Python versions with tox:

```
$ flake8 alotofeffort tests
    $ python setup.py test
$ tox
```

To get flake8 and tox, just pip install them into your virtualenv.

6. Commit your changes and push your branch to GitHub:

```
$ git add .
$ git commit -m "Your detailed description of your changes."
$ git push origin name-of-your-bugfix-or-feature
```

7. Submit a pull request through the GitHub website.

## Pull Request Guidelines

Before you submit a pull request, check that it meets these guidelines:

1. The pull request should include tests.
2. If the pull request adds functionality, the docs should be updated. Put your new functionality into a function with a docstring, and add the feature to the list in README.rst.
3. The pull request should work for Python 2.6+ and 3.3+. Check [https://travis-ci.org/audreyr/alotofeffort/pull\\_requests](https://travis-ci.org/audreyr/alotofeffort/pull_requests) and make sure that the tests pass for all supported Python versions.

## Tips

To run a subset of tests:

```
$ python -m unittest tests.test_alotofeffort
```

## CHAPTER 5

---

### Credits

---

### Development Lead

- Audrey Roy <[audreyr@gmail.com](mailto:audreyr@gmail.com)>

### Contributors

None yet. Why not be the first?





### 0.4.0 (2015-09-15)

- Upgraded boto to 2.38.0.
- Added tox envs for Python 3.3, 3.4, 3.5.
- PEP 8 cleanup.
- README cleanup.
- Improvements to setup.py.

### 0.3 (2013-07-27)

- Only files that have changed get uploaded. Files are checked for changes by comparing the local and remote MD5 hashes of the files.

### 0.2 (2013-07-17)

- It works on Python 2.6 and 2.7.

### 0.1 (2013-07-14)

- First release on PyPI.



## CHAPTER 7

---

### Indices and tables

---

- `genindex`
- `modindex`
- `search`