

---

# **ansible-role-zuul Documentation**

*Release*

**OpenStack Foundation**

August 01, 2018



<b>1</b>	<b>Description</b>	<b>3</b>
<b>2</b>	<b>Requirements</b>	<b>5</b>
2.1	Packages . . . . .	5
2.2	SSH . . . . .	5
<b>3</b>	<b>Role Variables</b>	<b>7</b>
3.1	Zuul Merger Configuration . . . . .	7
<b>4</b>	<b>Dependencies</b>	<b>9</b>
<b>5</b>	<b>Example Playbook</b>	<b>11</b>



Ansible role to manage Zuul

- License: Apache License, Version 2.0
- Documentation: <https://ansible-role-zuul.readthedocs.org>
- Source: <https://git.openstack.org/cgit/openstack/ansible-role-zuul>
- Bugs: <https://bugs.launchpad.net/ansible-role-zuul>



---

**Description**

---

Zuul is a program that is used to gate the source code repository of a project so that changes are only merged if they pass tests.



---

## Requirements

---

- pip3 to be installed if using `zuul_install_method: (git|pip)`

See *bindep.txt* for role dependencies.

## Packages

Package repository index files should be up to date before using this role, we do not manage them.

## SSH

An SSH private key will need to be installed before you can use zuul. The contents of the private key will be used by `zuul_config_gerrit_user` and should be copied to `zuul_config_gerrit_sshkey`.



---

## Role Variables

---

```
# Method used to install zuul. Valid values are git and pip.
# Default: git
zuul_install_method: git

# Git, SSH, or HTTP(s) protocol address of the git repository.
# Default: https://git.openstack.org/openstack-infra/zuul
zuul_git_uri: https://git.openstack.org/openstack-infra/zuul

# What version of the repository to check out.
# Default: master
zuul_git_version: master

# Absolute path of where the repository should be checked out to.
# Default: /opt/ansible-role-zuul/git/openstack-infra/zuul
zuul_git_dest: /opt/ansible-role-zuul/git/openstack-infra/zuul

# The version number to install from the Python Package Index.
# Default: None
zuul_pip_version:

# Name of the user to be created.
# Default: zuul
zuul_user_name: zuul

# Name of the group to be created.
# Default: zuul
zuul_user_group: zuul

# Path of home directory to be created.
# Default: /var/lib/zuul
zuul_user_home: /var/lib/zuul
```

## Zuul Merger Configuration

```
# Value to pass to git config user.email.
# Default: Empty
zuul_config_merger_git_user_email: ""

# Value to pass to git config user.name.
```

```
# Default: Empty  
zuul_config_merger_git_user_name: ""
```

---

**Dependencies**

---



---

## Example Playbook

---

```
- name: Install zuul
  hosts: zuul
  roles:
    - ansible-role-zuul
```