
restfulgrok Documentation

Release 1.3.0b1

Espen Angell Kristiansen

October 01, 2015

1	Install	3
2	Code and issues	5
3	Contribute	7
4	Wiki	9
5	Getting started	11
5.1	Fabric	11
5.2	The awsfab command	11
5.3	Required settings	11
6	Making a fabfile.py and use awsfabtasks	13
6.1	Example fabfile.py	13
6.2	Using the example	14
6.3	Launch/create new EC2 instances	14
7	More task-examples	15
8	Documentation	17
8.1	Tasks	17
8.2	API	19
8.3	awsfab_settings.py — Settings	30
9	Indices and tables	35
	Python Module Index	37

Fabric (<http://fabfile.org>) tasks for Amazon Web Services with some extra utilities for Ubuntu.

Install

```
$ pip install awsfabrictasks
```

Code and issues

Get the sourcecode, and submit issues at our github repo: <https://github.com/espenak/awsfabrictasks>

Contribute

1. Create an [issue](#) describing your problem, improvement, etc (unless you are fixing an existing issue).
2. Fix the issue and create a pull request. This is a perfect example of what a pull request should include: <https://github.com/espenak/awsfabrictasks/pull/9>.

Wiki

Please contribute your tips, tricks and guides to the [Wiki](#).

Getting started

5.1 Fabric

Learn how to use [Fabric](#).

5.2 The awsfab command

Fabric is great for remote execution because it allows you to run a task on any SSH-server with the following syntax:

```
$ fab -H server1,server2,server3 task1 task2
```

The problem with Fabric on AWS EC2 is that we do not have a static dns address to give to `-H`. `awsfab` wraps `fab` and allows us to use:

```
$ awsfab -E <Name-tag of an EC2 instance>,<Name-tag of another....> task1 task2
```

If your instance is not tagged with a name (the tag must be capitalized: `Name`), you can use `--ec2ids` instead.

5.3 Required settings

See *awsfab_settings.py* — *Settings*.

Making a fabfile.py and use awsfabrictasks

6.1 Example fabfile.py

Create a `fabfile.py` just as you would with Fabric, and import tasks from `awsfabrictasks`:

```
from fabric.api import task, run
from awsfabrictasks.decorators import ec2instance

#####
# Add some of our own tasks
#####

@task
def uname():
    """
    Run ``uname -a``
    """
    run('uname -a')

@task
@ec2instance(nametag='tst')
def example_nametag_specific_task():
    """
    Example of using ``@ec2instance``.
    Enables us to run::

        awsfab example_nametag_specific_task``

    and have it automatically use the EC2 instance tagged with ``Name="tst"``.
    """
    run('uname -a')

#####
# Import awsfab tasks
#####
from awsfabrictasks.ec2.tasks import *
from awsfabrictasks.regions import *
from awsfabrictasks.conf import *
```

6.2 Using the example

List basic information about your instances with:

```
$ awsfab ec2_list_instances
```

Start one of your existing EC2 instances (the example assumes it is tagged with Name="mytest"):

```
$ awsfab -E mytest ec2_start_instance
```

Login (SSH) to the instance we just started:

```
$ awsfab -E mytest ec2_login
```

See:

```
$ awsfab -l
```

or [Tasks](#) for more tasks.

6.3 Launch/create new EC2 instances

See [Example `awsfab_settings.py`](#) for an example of how to setup your EC2 launch configurations. After you have added `EC2_LAUNCH_CONFIGS` to your `awsfab_settings.py`, simply run:

```
$ awsfab ec2_launch_instance:<nametag>
```

where `<nametag>` is the name you want to tag your new instance with. You will be asked to choose a config from `EC2_LAUNCH_CONFIGS`, and to confirm all your choices before the instance is created.

More task-examples

The best examples are the provided tasks. Just browse the source, or use the `[source]` links in the *tasks docs*.

8.1 Tasks

8.1.1 `awsfabrictasks.ec2.tasks`

General tasks for AWS management.

`awsfabrictasks.ec2.tasks.ec2_add_tag`

Add tag to EC2 instance. Fails if tag already exists.

Parameters

- **tagname** – Name of the tag to set (required).
- **value** – Value to set the tag to. Default to empty string.

`awsfabrictasks.ec2.tasks.ec2_set_tag`

Set tag on EC2 instance. Overwrites value if tag exists.

Parameters

- **tagname** – Name of the tag to set (required).
- **value** – Value to set the tag to. Default to empty string.

`awsfabrictasks.ec2.tasks.ec2_remove_tag`

Remove tag from EC2 instance. Fails if tag does not exist.

Parameters **tagname** – Name of the tag to remove (required).

`awsfabrictasks.ec2.tasks.ec2_launch_instance`

Launch new EC2 instance.

Parameters

- **name** – The name to tag the EC2 instance with (required)
- **configname** – Name of the configuration in `awsfab_settings.EC2_LAUNCH_CONFIGS`. Prompts for input if not provided as an argument.

`awsfabrictasks.ec2.tasks.ec2_start_instance`

Start EC2 instance.

Parameters **nowait** – Set to `True` to let the EC2 instance start in the background instead of waiting for it to start. Defaults to `False`.

`awsfabrictasks.ec2.tasks.ec2_stop_instance`

Stop EC2 instance.

Parameters `nowait` – Set to `True` to let the EC2 instance stop in the background instead of waiting for it to start. Defaults to `False`.

`awsfabrictasks.ec2.tasks.ec2_list_instances`

List EC2 instances in a region (defaults to `awsfab_settings.DEFAULT_REGION`).

Parameters

- **region** – The region to list instances in. Defaults to `“awsfab_settings.DEFAULT_REGION`.
- **full** – Print all attributes, or just the most useful ones? Defaults to `False`.

`awsfabrictasks.ec2.tasks.ec2_print_instance`

Print EC2 instance info.

Parameters **full** – Print all attributes, or just the most useful ones? Defaults to `False`.

`awsfabrictasks.ec2.tasks.ec2_login`

Log into the host specified by `–hosts`, `–ec2names` or `–ec2ids`.

Aborts if more than one host is specified.

`awsfabrictasks.ec2.tasks.ec2_rsync_download_dir`

Sync the contents of `remote_dir` into `local_dir`. E.g.: if `remote_dir` is `/etc`, and `local_dir` is `/tmp`, the `/tmp/etc` will be created on the local host, and filled with all files in `/etc` on the EC2 instance.

Parameters

- **remote_dir** – The remote directory to download into `local_dir`.
- **local_dir** – The local directory.
- **rsync_args** – Arguments for `rsync`. Defaults to `–av`.
- **noconfirm** – If this is `True`, we will not ask for confirmation before proceeding with the operation. Defaults to `False`.

`awsfabrictasks.ec2.tasks.ec2_rsync_upload_dir`

Sync the contents of `local_dir` into `remote_dir` on the EC2 instance. E.g.: if `local_dir` is `/etc`, and `remote_dir` is `/tmp`, the `/tmp/etc` will be created on the EC2 instance, and filled with all files in `/etc` on the local host.

Parameters

- **local_dir** – The local directory to upload to the EC2 instance.
- **remote_dir** – The remote directory to upload `local_dir` into.
- **rsync_args** – Arguments for `rsync`. Defaults to `–av`.
- **noconfirm** – If this is `True`, we will not ask for confirmation before proceeding with the operation. Defaults to `False`.

8.1.2 `awsfabrictasks.ec2.regions`

`awsfabrictasks.regions.list_regions`

List all regions.

`awsfabrictasks.regions.list_zones`

List zones in the given region.

Parameters **region** – Defaults to `awsfab_settings.DEFAULT_REGION`.

8.2 API

8.2.1 awsfabrictasks.conf

class `awsfabrictasks.conf.Settings`
 Bases: `object`
 Settings object inspired by `django.conf.settings`.

as_dict ()
 Get all settings (uppercase attributes on this object) as a dict.

clear_settings ()
 Clear all settings (intended for testing). Deletes all uppercase attributes.

pprint ()
 Prettyprint the settings.

reset_settings (***settings*)
 Reset settings (intended for testing). Shortcut for:

```
clear_settings()
set_settings(**settings)
```

set_settings (***settings*)
 Set all the given settings as attributes of this object.

Raises ValueError If any of the keys in `settings` is not uppercase.

awsfabrictasks.conf.print_settings
 Pretty-print the settings as they are seen by the system.

8.2.2 awsfabrictasks.utils

exception `awsfabrictasks.utils.InvalidLogLevel`
 Bases: `exceptions.KeyError`
 Raised when `getLogLevelFromString()` gets an invalid `loglevelstring`.

awsfabrictasks.utils.compute_localfile_md5sum (*localfile*)
 Compute the hex-digested md5 checksum of the given *localfile*.

Parameters *localfile* – Path to a file on the local filesystem.

awsfabrictasks.utils.configureStreamLogger (*loggername*, *level*)
 Configure a stdout/stderr logger (`logging.StreamHandler`) with the given *loggername* and *level*. If you are configuring logging for a task, use `configureStreamLoggerForTask()`.

This is suitable for log-configuration for a single task, where the user specifies a loglevel.

Returns The configured logger.

awsfabrictasks.utils.configureStreamLoggerForTask (*modulename*, *taskname*, *loglevel*)
 Configure logging for a task.

Shortcut for:

```
configureStreamLogger(modulename + '.' + taskname, loglevel)
```

Example (note that what you put in the loglevel docs for your task depends on how you use the logger):

```
@task
mytask(loglevel='INFO'):
    """
    Does some task.

    :param loglevel:
        Controls the amount of output:

        QUIET --- No output.
        INFO --- Only produce output for changes.
        DEBUG --- One line of output for each file.

    Defaults to "INFO".
    """
    log = configureStreamLoggerForTask(__name__, 's3_syncupload_dir',
                                       getLogLevelFromString(loglevel))
    log.info('Hello world')
```

`awsfabrictasks.utils.force_noslashend(path)`

Return path with any trailing / removed.

`awsfabrictasks.utils.force_slashend(path)`

Return path suffixed with / (path is unchanged if it is already suffixed with /).

`awsfabrictasks.utils.getLogLevelFromString(loglevelstring)`

Lookup loglevelstring in `loglevel_stringmap`.

Raises InvalidLogLevel If loglevelstring is not in `loglevel_stringmap`.

Returns The loglevel.

Return type int

`awsfabrictasks.utils.guess_contenttype(filename)`

Return the content-type for the given filename. Uses `mimetypes.guess_type()`.

`awsfabrictasks.utils.localpath_to_slashpath(path)`

Replace `os.sep` in path with /.

`awsfabrictasks.utils.parse_bool(data)`

Return True if data is one of: 'true', 'True', True. Otherwise, return False.

`awsfabrictasks.utils.rsyntaxformat_path(source_dir, sync_content=False)`

rsync uses / in the source directory to determine if we should sync a directory or the contents of a directory. How rsync works:

Sync contents: Source path ending with / means sync the contents (just as if we used /* except that * does not include hidden files).

Sync the directory: Source path NOT ending with / means sync the directory. I.e.: If the source is `/etc/init.d`, and the destination is `/tmp`, the contents of `/etc/init.d` is copied into `/tmp/init.d/`.

This is error-prone, and the consequences can be severe if combined with `--delete`. Therefore, we use a boolean to distinguish between these two methods of specifying source directory, and reformat the path using `force_slashend()` and `force_noslashend()`.

Parameters

- **source_dir** – The source directory. May be a remote directory (i.e.: `[USER@]HOSTNAME:PATH`), or a local directory.

- **sync_content** – Normally the function automatically makes sure `local_dir` is not suffixed with `/`, which makes `rsync` copy `local_dir` into `remote_dir`. With `sync_content=True`, the content of `local_dir` is synced into `remote_dir` instead.

`awsfabrictasks.utils.slashpath_to_localpath(path)`

Replace `/` in path with `os.sep`.

`awsfabrictasks.utils.sudo_chattr(remote_path, owner=None, mode=None)`

Run `sudo_chown()` and `sudo_chmod()` on `remote_path`. If owner or mode is `None`, their corresponding function is not called.

`awsfabrictasks.utils.sudo_chmod(remote_path, mode)`

Run `sudo chmod <mode> remote_path`.

`awsfabrictasks.utils.sudo_chown(remote_path, owner)`

Run `sudo chown <owner> remote_path`.

`awsfabrictasks.utils.sudo_mkdir_p(remote_path, **chattr_kw)`

`sudo mkdir -p <remote_path>` followed by `:func:'sudo_chattr'(remote_path, **chattr_kw)`.

`awsfabrictasks.utils.sudo_upload_dir(local_dir, remote_dir, **chattr_kw)`

Upload all files and directories in `local_dir` to `remote_dir`. Directories are created with `sudo_mkdir_p()` and files are uploaded with `sudo_upload_file()`. `chattr_kw` is forwarded in both cases.

`awsfabrictasks.utils.sudo_upload_file(local_path, remote_path, **chattr_kw)`

Use `sudo` to upload a file from `local_path` to `remote_path` and run `sudo_chattr()` with the given `chattr_kw` as arguments.

`awsfabrictasks.utils.sudo_upload_string_to_file(string_to_upload, remote_path, **chattr_kw)`

Create a tempfile containing `string_to_upload`, and use `sudo_upload_file()` to upload the tempfile. Removes the tempfile when the upload is complete or if it fails.

Parameters

- **string_to_upload** – The string to write to the tempfile.
- **remote_path** – See `sudo_upload_file()`.
- **chattr_kw** – See `sudo_upload_file()`.

`awsfabrictasks.utils.loglevel_stringmap = {'INFO': 20, 'QUIET': 50, 'WARN': 30, 'CRITICAL': 50, 'ERROR':`

`Map of strings to loglevels (for the logging module)`

8.2.3 awsfabrictasks.ubuntu

Ubuntu utilities.

`awsfabrictasks.ubuntu.set_locale(locale='en_US')`

Set locale to avoid the warnings from perl and others about locale failures.

8.2.4 awsfabrictasks.ec2.api

exception `awsfabrictasks.ec2.api.Ec2RegionConnectionError(region)`

Bases: `exceptions.Exception`

Raised when we fail to connect to a region.

exception `awsfabrictasks.ec2.api.InstanceLookupError`

Bases: `exceptions.LookupError`

Base class for instance lookup errors.

exception `awsfabrictasks.ec2.api.MultipleInstancesWithSameNameError`

Bases: `awsfabrictasks.ec2.api.InstanceLookupError`

Raised when multiple instances with the same nametag is discovered. (see: `Ec2InstanceWrapper.get_by_nametag()`)

exception `awsfabrictasks.ec2.api.NoInstanceWithNameFound`

Bases: `awsfabrictasks.ec2.api.InstanceLookupError`

Raised when no instace with the requested name is found in `Ec2InstanceWrapper.get_by_nametag()`.

exception `awsfabrictasks.ec2.api.NotExactlyOneInstanceError`

Bases: `awsfabrictasks.ec2.api.InstanceLookupError`

Raised when more than one instance is found when expecting exactly one instance.

exception `awsfabrictasks.ec2.api.WaitForStateError`

Bases: `exceptions.Exception`

Raises when `wait_for_state()` times out.

class `awsfabrictasks.ec2.api.Ec2InstanceWrapper` (*instance*)

Bases: `object`

Wraps a `boto.ec2.instance.Instance` with convenience functions.

Variables `instance` – The `boto.ec2.instance.Instance`.

Parameters `instance` – A `boto.ec2.instance.Instance` object.

add_instance_to_env()

Add self to `fabric.api.env.ec2instances[self.get_ssh_uri()]`, and register the key-pair for the instance in `fabric.api.env.key_filename`.

classmethod `get_by_instanceid` (*instanceid*)

Connect to AWS and get the EC2 instance with the given instance ID.

Parameters `instanceid_with_optional_region` – Parsed with `parse_instanceid()` to find the region and name.

Raises

- **Ec2RegionConnectionError** – If connecting to the region fails.
- **LookupError** – If the requested instance was not found in the region.

Returns A `Ec2InstanceWrapper` contaning the requested instance.

classmethod `get_by_nametag` (*instancename_with_optional_region*)

Connect to AWS and get the EC2 instance with the given Name-tag.

Parameters `instancename_with_optional_region` – Parsed with `parse_instancename()` to find the region and name.

Raises

- **Ec2RegionConnectionError** – If connecting to the region fails.
- **InstanceLookupError** – Or one of its subclasses if the requested instance was not found in the region.

Returns A `Ec2InstanceWrapper` contaning the requested instance.

classmethod `get_by_tagvalue(tags={}, region=None)`

Connect to AWS and get the EC2 instance with the given tag:value pairs.

:param tags A string like 'role=testing,fake=yes' to AND a set of ec2 instance tags

Parameters `region` – optional.

Raises `Ec2RegionConnectionError` If connecting to the region fails.

Returns A list of :class:'Ec2InstanceWrapper's containing the matching instances.

classmethod `get_exactly_one_by_tagvalue(tags, region=None)`

Use `get_by_tagvalue()` to find instances by tags, but raise `LookupError` if not exactly one instance is found.

classmethod `get_from_host_string()`

If an instance has been registered in `fabric.api.env` using `add_instance_to_env()`, this method can be used to get the instance identified by `fabric.api.env.host_string`.

get_ssh_key_filename()

Get the SSH identify filename (.pem-file) for the instance. Searches `awsfab_settings.KEYPAIR_PATH` for "<instance.key_name>.pem".

Raises `LookupError` If the key is not found.

get_ssh_uri()

Get the SSH URI for the instance.

Returns "<instance.tags['awsfab-ssh-user']>@<instance.public_dns_name>"

is_running()

Return True if state=='running'.

is_stopped()

Return True if state=='stopped'.

prettyname()

Return a pretty-formatted name for this instance, using the Name-tag if the instance is tagged with it.

class `awsfabtasks.ec2.api.Ec2LaunchInstance(extra_tags={}, configname=None, configname_help=u'Please select one of the following configurations:', duplicate_name_protection=True)`

Bases: `object`

Launch instances configured in `awsfab_settings.EC2_LAUNCH_CONFIGS`.

Example:

```
launcher = Ec2LaunchInstance(extra_tags={'Name': 'mytest'})
launcher.confirm()
instance = launcher.run_instance()
```

Note that this class is optimized for the following use case:

- Create one or more instances (initialize one or more `Ec2LaunchInstance`).
- Confirm using `confirm()` or `confirm_many()`.
- Launch each instance using `meth:Ec2LaunchInstance.run_instance` or `Ec2LaunchInstance.run_many_instances()`.
- Use `Ec2LaunchInstance.wait_for_running_state_many()` to wait for all instances to launch.

- Do something with the running instances.

Example of launching many instances:

```
a = Ec2LaunchInstance(extra_tags={'Name': 'a'})
b = Ec2LaunchInstance(extra_tags={'Name': 'b'})
Ec2LaunchInstance.confirm_many([a, b])
Ec2LaunchInstance.run_many_instances([a, b])
# Note: that we can start doing stuff with 'a' and 'b' that does not
# require the instances to be running, such as setting tags.
Ec2LaunchInstance.wait_for_running_state_many([a, b])
```

Initialize the launcher. Runs `create_config_ask_if_none()`.

Parameters

- **configname** – Name of a configuration in `awsfab_settings.EC2_LAUNCH_CONFIGS`. If it is `None`, we ask the user for the configfile.
- **configname_help** – The help to show above the prompt for configname input (only used if configname is `None`).

confirm()

Use `prettyprint()` to show the user their choices, and ask for confirmation. Runs `fabric.api.abort()` if the user does not confirm the choices.

classmethod confirm_many (*launchers*)

Loop through Use `prettyprint()` to show the user their choices, and ask for confirmation. Runs `fabric.api.abort()` if the user does not confirm the choices.

create_config_ask_if_none()

Set `kw` and `conf` using `configname`. Prompt the user for a configname if `bool(configname)` is `False`.

get_all_tags()

Merge tags from the `awsfab_settings.EC2_LAUNCH_CONFIGS` config, and the `extra_tags` parameter for `__init__`, and return the resulting dict.

prettyformat()

Prettyformat the configuration.

run_instance()

Run/launch the configured instance, and add the tags to the instance (`get_all_tags()`).

Returns The launched instance.

classmethod run_many_instances (*launchers*)

Loop through `launchers` and run `run_instance()`.

Parameters

- **launchers** – List of `Ec2LaunchInstance` objects.
- **kwargs** – Forwarded to `wait_for_running_state()`.

classmethod wait_for_running_state_many (*launchers*, ****kwargs**)

Loop through `launchers` and run `wait_for_running_state()`.

Parameters

- **launchers** – List of `Ec2LaunchInstance` objects that have been lauched with `Ec2LaunchInstance.run_instance()`.
- **kwargs** – Forwarded to `wait_for_running_state()`.

conf = None

A config dict from `awsfab_settings.EC2_LAUNCH_CONFIGS`.

configname = None

See the docs for the `__init__` parameter.

configname_help = None

See the docs for the `__init__` parameter.

instance = None

The instance launched by `run_instance()`. None when `run_instance()` has not been invoked.

kw = None

Keyword arguments for `run_instances()`.

tag_retry_count = 4

Number of times to retry when adding tags gets `EC2ResponseError`.

tag_retry_sleep = 2

Number of seconds to sleep before retrying when adding tags gets `EC2ResponseError`.

`awsfabrictasks.ec2.api.ec2_rsync(*args, **kwargs)`

Deprecated since version 1.0.13: Use `ec2_rsync_upload()` instead.

`awsfabrictasks.ec2.api.ec2_rsync_download(remote_dir, local_dir, rsync_args=u'-av', sync_content=False)`

`rsync remote_dir` on the current EC2 instance (the one returned by `Ec2InstanceWrapper.get_from_host_string()`) into `local_dir`.

Parameters sync_content – Normally the function automatically makes sure `local_dir` is not suffixed with `/`, which makes `rsync` copy `local_dir` into `remote_dir`. With `sync_content=True`, the content of `local_dir` is synced into `remote_dir` instead.

`awsfabrictasks.ec2.api.ec2_rsync_download_command(instancewrapper, remote_dir, local_dir, rsync_args=u'-av', sync_content=False)`

Returns the `rsync` command used by `ec2_rsync_download()`. Takes the same parameters as `ec2_rsync_download()`, except for the first parameter, `instancewrapper`, which is a `Ec2InstanceWrapper` object.

`awsfabrictasks.ec2.api.ec2_rsync_upload(local_dir, remote_dir, rsync_args=u'-av', sync_content=False)`

`rsync local_dir` into `remote_dir` on the current EC2 instance (the one returned by `Ec2InstanceWrapper.get_from_host_string()`).

Parameters sync_content – Normally the function automatically makes sure `local_dir` is not suffixed with `/`, which makes `rsync` copy `local_dir` into `remote_dir`. With `sync_content=True`, the content of `local_dir` is synced into `remote_dir` instead.

`awsfabrictasks.ec2.api.ec2_rsync_upload_command(instancewrapper, local_dir, remote_dir, rsync_args=u'-av', sync_content=False)`

Returns the `rsync` command used by `ec2_rsync_upload()`. Takes the same parameters as `ec2_rsync_upload()`, except for the first parameter, `instancewrapper`, which is a `Ec2InstanceWrapper` object.

`awsfabrictasks.ec2.api.parse_instanceid(instanceid_with_optional_region)`

Parse instance id with an optional region-name prefixed. Region name is specified by prefixing the instanceid with `<regionname>:`.

Returns (region, instanceid) where region defaults to `awsfab_settings.DEFAULT_REGION` if not prefixed to the id.

`awsfabrictasks.ec2.api.parse_instancename (instancetype_with_optional_region)`

Just like `parse_instanceid()`, however this is for instance names. We keep them as separate functions in case they diverge in the future.

Returns (region, instanceid) where region defaults to `awsfab_settings.DEFAULT_REGION` if not prefixed to the name.

`awsfabrictasks.ec2.api.print_ec2_instance (instance, full=False, indentspaces=3)`

Print attributes of an ec2 instance.

Parameters

- **instance** – A `boto.ec2.instance.Instance` object.
- **full** – Print all attributes? If not, a subset of the attributes are printed.
- **indentspaces** – Number of spaces to indent each line in the output.

`awsfabrictasks.ec2.api.wait_for_running_state (instanceid, **kwargs)`

Shortcut for `wait_for_state(instanceid, 'running', **kwargs)`.

`awsfabrictasks.ec2.api.wait_for_state (instanceid, state_name, sleep_intervals=[15, 5], last_sleep_repeat=40)`

Poll the instance with `instanceid` until its `state_name` matches the desired `state_name`.

The first poll is performed without any delay, and the rest of the polls are performed according to `sleep_intervals`.

Parameters

- **instanceid** – ID of an instance.
- **state_name** – The `state_name` to wait for.
- **sleep_intervals** – List of seconds to wait between each poll for state. The first poll is made immediately, then we wait for `sleep_intervals[0]` seconds before the next poll, and repeat for each item in `sleep_intervals`. Then we repeat for `last_sleep_repeat` using the last item in `sleep_intervals` as the timeout for each wait.
- **last_sleep_repeat** – Number of times to repeat the last item in `sleep_intervals`. If this is 20, we will wait for a maximum of `sum(sleep_intervals) + sleep_intervals[-1]*20`.

`awsfabrictasks.ec2.api.wait_for_stopped_state (instanceid, **kwargs)`

Shortcut for `wait_for_state(instanceid, 'stopped', **kwargs)`.

`awsfabrictasks.ec2.api.zipit (ss)`

Returns a string containing a user_data compatible gzip-file of the zipped `ss` input. Note(using `zlib` alone is not sufficient - we need a zipfile structure)

8.2.5 awsfabrictasks.decorators

`awsfabrictasks.decorators.ec2instance (nametag=None, instanceid=None, tags=None, region=None)`

Wraps the decorated function to execute as if it had been invoked with `--ec2names` or `--ec2ids`.

8.2.6 awsfabrictasks.s3.api

exception `awsfabrictasks.s3.api.S3ConnectionError (msg='Could not connect S3')`

Bases: `exceptions.Exception`

Raised when we fail to connect to S3.

exception `awsfabrictasks.s3.api.S3ErrorBase`

Bases: `exceptions.Exception`

Base class for all S3 errors. Never raised directly.

exception `awsfabrictasks.s3.api.S3FileDoesNotExist` (*s3file*)

Bases: `awsfabrictasks.s3.api.S3FileErrorBase`

Raised when an `S3File` does not exist.

Parameters `s3file` – A `S3File` object.

exception `awsfabrictasks.s3.api.S3FileErrorBase` (*s3file*)

Bases: `awsfabrictasks.s3.api.S3ErrorBase`

Base class for all `S3File` errors. Never raised directly.

Parameters `s3file` – A `S3File` object.

exception `awsfabrictasks.s3.api.S3FileExistsError` (*s3file*)

Bases: `awsfabrictasks.s3.api.S3FileErrorBase`

Raised when trying to overwrite an existing `S3File`, unless overwriting is requested.

Parameters `s3file` – A `S3File` object.

exception `awsfabrictasks.s3.api.S3FileNoInfo` (*s3file*)

Bases: `awsfabrictasks.s3.api.S3FileErrorBase`

Raised when trying to use `S3File` metadata before performing a HEAD request.

Parameters `s3file` – A `S3File` object.

class `awsfabrictasks.s3.api.S3ConnectionWrapper` (*connection*)

Bases: `object`

S3 connection wrapper.

Parameters `bucket` – A `boto.rds.bucket.DBInstance` object.

classmethod `get_bucket` (*bucketname*)

Get the requested bucket.

Shortcut for:

`S3ConnectionWrapper.get_connection().connection.get_bucket(bucketname)`

Parameters `bucketname` – Name of an S3 bucket.

classmethod `get_bucket_using_pattern` (*bucketname*)

Same as `get_bucket()`, however the `bucketname` is filtered through `settingsformat_bucketname()`.

classmethod `get_connection` ()

Connect to S3 using `awsfab_settings.AUTH`.

Returns `S3ConnectionWrapper` object.

class `awsfabrictasks.s3.api.S3File` (*bucket, key*)

Bases: `object`

Simplifies working with keys in S3 buckets.

delete()

Delete the key/file from the bucket.

Raises S3FileDoesNotExist If the key does not exist in the bucket.

etag_matches_localfile(localfile)

Return True if the file at the path given in `localfile` has an md5 hex-digested checksum matching the etag of this S3 key.

exists()

Return True if the key/file exists in the S3 bucket.

get_contents_as_string()

Download the file and return it as a string.

get_contents_to_filename(localfile)

Download the file to the given `localfile`.

get_etag()

Return the etag (the md5sum)

set_contents_from_filename(localfile, overwrite=False)

Upload `localfile`.

Parameters `overwrite` – If True, overwrite if the key/file exists.

Raises S3FileExistsError If `overwrite==True` and the key exists in the bucket.

set_contents_from_string(data, overwrite=False)

Write `data` to the S3 file.

Parameters `overwrite` – If True, overwrite if the key/file exists.

Raises S3FileExistsError If `overwrite==True` and the key exists in the bucket.

class `awsfabrictasks.s3.api.S3Sync(bucket, local_dir, s3prefix)`

Bases: `object`

Makes it easy to sync files to and from S3. This class does not make any changes to the local filesystem, or S3, it only makes it easy to write function that works with hierarkies of files synced locally and on S3.

A good example is the sourcecode for `awsfabrictasks.s3.tasks.s3_syncupload_dir()`.

Parameters

- **bucket** – A `boto.rds.bucket.DBInstance` object.
- **local_dir** – The local directory.
- **local_dir** – The S3 key prefix that corresponds to `local_dir`.

iterfiles()

Iterate over all files both local and within the S3 prefix. Yields `S3SyncIterFile` objects.

How it works:

- Uses `dirlist_absfilenames()` to get all local files in the `local_dir`.
- Uses `s3list_s3filedict()` to get all S3 files in the `s3prefix`.
- Uses these two sets of information to create `S3SyncIterFile` objects.

class `awsfabrictasks.s3.api.S3SyncIterFile`

Bases: `object`

Objects of this class is yielded by `S3Sync.iterfiles()`. Contains info about where the file exists, its local and S3 path (even if it does not exist).

both_exists()

Returns True if `localexists` and `s3exists`.

create_localdir()

Create the directory containing `localpath` if it does not exist.

download_s3file_to_localfile()

`create_localdir()` and download the file at `s3path` to `localpath`.

etag_matches_localfile()

Shortcut for:

```
self.s3file.etag_matches_localfile(self.localpath)
```

localexists = None

Local file exists?

localpath = None

The local path. Always set. Use `localexists` if you want to know if the local file exists.

s3exists = None

S3 file exists?

s3file = None

A `S3File` object. Use `s3exists` if you want to know if the S3 file exists.

s3path = None

The S3 path. Always set. Use `s3exists` if you want to know if the S3 file exists.

`awsfabrictasks.s3.api.dirlist_absfilenames(dirpath)`

Get all the files within the given `dirpath` as a set of absolute filenames.

`awsfabrictasks.s3.api.iter_bucketcontents(bucket, prefix, match, delimiter, formatter=<function <lambda> at 0x7f2612ff06e0>)`

Iterate over items given bucket, yielding items formatted for output.

Parameters

- **bucket** – A class:`boto.s3.bucket.Bucket` object.
- **prefix** – The prefix to list. Defaults to empty string, which lists all items in the root directory.
- **match** – A Unix shell style pattern to match. Matches against the entire key name (in filesystem terms: the absolute path).

Uses the `fnmatch` python module. The match is case-sensitive.

Examples:

```
*.jpg
*2012*example*.log
icon-*.png
```

- **delimiter** – The delimiter to use. Defaults to `/`.
- **formatter** – Formatter callback to use to format each key. Not used on Prefix-keys (directories). The callback should take a key as input, and return a string.

See also:

<http://docs.amazonwebservices.com/AmazonS3/latest/dev/ListingKeysHierarchy.html>

`awsfabrictasks.s3.api.localpath_to_s3path(localdir, localpath, s3prefix)`

Convert a local filepath into a S3 path within the given `s3prefix`.

Parameters

- **localdir** – The local directory that corresponds to `s3prefix`.
- **localpath** – Path to a file within `localdir`.
- **s3prefix** – Prefix to use for the file on S3.

Example:: >>> `localpath_to_s3path('/mydir', '/mydir/hello/world.txt', 'my/test')` `'my/test/hello/world.txt'`

`awsfabrictasks.s3.api.s3list_s3filedict` (*bucket, prefix*)

Get all the keys with the given `prefix` as a dict with key-name as key and the key-object wrapped in a `S3File` as value.

`awsfabrictasks.s3.api.s3path_to_localpath` (*s3prefix, s3path, localdir*)

Convert a s3 filepath into a local filepath within the given `localdir`.

Parameters

- **s3prefix** – Prefix used for the file on S3.
- **s3path** – Path to a file within `s3prefix`.
- **localdir** – The local directory that corresponds to `s3prefix`.

Example:: >>> `s3path_to_localpath('mydir', 'mydir/hello/world.txt', '/my/test')` `'/my/test/hello/world.txt'`

`awsfabrictasks.s3.api.settingsformat_bucketname` (*bucketname*)

Returns `awsfab_settings.S3_BUCKET_PATTERN.format(bucketname=bucketname)`.

See also:

`awsfabrictasks.default_settings.S3_BUCKET_PATTERN`.

8.3 awsfab_settings.py — Settings

8.3.1 Required setup

`awsfabrictasks` uses a settings system similar to the Django settings module. You add your settings to `awsfab_settings.py`.

Required configuration

Create a file named `awsfab_settings.py`, and add your AWS Security credentials:

```
AUTH = {'aws_access_key_id': 'Access Key ID',
        'aws_secret_access_key': 'Secret Access Key'}
```

You find these under My account -> Security Credentials on <http://aws.amazon.com/>.

.pem-key

The `.pem`-keys (key pairs) for you instances (the ones used for SSH login) must be added to `~/ .ssh/` or the current directory. You can change these directories with the `awsfab_settings.KEYPAIR_PATH` variable (see *Default settings*).

8.3.2 Local override

You may override settings in `awsfab_settings_local.py`, which is typically used to store authentication credentials outside your version control system (i.e: with git you would add `awsfab_settings_local.py` to `.gitignore`).

8.3.3 Override name of settings module

`awsfab_settings.py` defines the `awsfab_settings` python module. Importing the module works because `awsfab` adds the current working directory to your `PYTHONPATH`. You can override the name of this module using `--awsfab-settings <modulename>`. When you override the settings module, you also override the name of the corresponding local override. The local override is always `<settings-module-name>_local`.

To sum this up, you do the following to create a custom settings file named `my_awsfab_settings.py` with a local override:

- Create `my_awsfab_settings.py`.
- Create `my_awsfab_settings_local.py` (optional).
- Run with:
\$ `awsfab --awsfab-settings my_awsfab_settings`

Warning: The `--awsfab-settings` module can NOT be a dotted path (it can be `my_test_module`, but NOT `my.test.module`).

8.3.4 Example `awsfab_settings.py`

```
# Config file for awsfabrictasks.
#
# This is a Python module, and it is imported just as a regular Python module.
# Every variable with an uppercase-only name is a setting.

AUTH = {'aws_access_key_id': 'XXXXXXXXXXXXXXXXXXXX',
        'aws_secret_access_key': 'xxxxxxxxxxxxxxxxxxxxxxxxxxxxxxxx'}

DEFAULT_REGION = 'eu-west-1'

#####
# Self documenting map of AMIs
# - You are not required to use this, but it makes it easier to read
#   EC2_LAUNCH_CONFIGS.
#####
ami = {
    'ubuntu-10.04-lts': 'ami-fb665f8f'
}

#####
# Example user_data
# This script will be passed to the new instance at boot
# time and run late in the boot sequence.
# It can be used to do arbitrarily complex setup tasks.
# info: http://ubuntu-smoser.blogspot.co.uk/2010/03/introducing-cloud-inits-cloud-config.html
#####
user_data_example = """#!/bin/sh
```

```
echo ===== Hello World: $(date) =====
echo "I have been up for $(cut -d\ -f 1 < /proc/uptime) sec"
"""
```

```
#####
# Configuration for ec2_launch_instance
#####
EC2_LAUNCH_CONFIGS = {
    'ubuntu-10.04-lts-micro': {
        'description': 'Ubuntu 10.04 on the least expensive instance type.',

        # Ami ID (E.g.: ami-fb665f8f)
        'ami': ami['ubuntu-10.04-lts'],

        # One of: m1.small, m1.large, m1.xlarge, c1.medium, c1.xlarge, m2.xlarge, m2.2xlarge, m2.4xlarge
        'instance_type': 't1.micro',

        # List of security groups
        'security_groups': ['allowssh'],

        # Use the ``list_regions`` task to see all available regions
        'region': DEFAULT_REGION,

        # The name of the key pair to use for instances (See http://console.aws.amazon.com -> EC2 ->
        'key_name': 'awstestkey',

        # The availability zone in which to launch the instances. This is
        # automatically prefixed by ``region``.
        'availability_zone': 'b',

        # Tags to add to the instances. You can use the ``ec2*_tag`` tasks or
        # the management interface to manage tags. Special tags:
        # - Name: Should not be in this dict. It is specified when launching
        #   an instance (needs to be unique for each instance).
        # - awsfab-ssh-user: The ``awsfab`` tasks use this user to log into your instance.
        'tags': {
            'awsfab-ssh-user': 'ubuntu'
        },
        'user_data': user_data_example
    }
}
```

```
#####
# Add your own settings here
#####
```

```
MYCOOLSTUFF_REMOTE_DIR = '/var/www/stuff'
```

8.3.5 Default settings

awsfabrictasks.default_settings.**AUTH** = {}

The AWS access key. Should look something like this:

```
AUTH = {'aws_access_key_id': 'XXXXXXXXXXXXXXXXX',  
        'aws_secret_access_key': 'aaaaaaaaaa\BBBBBBBBB\dsaddad' }
```

`awsfabrictasks.default_settings.DEFAULT_REGION = 'eu-west-1'`

The default AWS region to use with the commands where REGION is supported.

`awsfabrictasks.default_settings.EC2_INSTANCE_DEFAULT_SSHUSER = 'root'`

Default ssh user if the awsfab-ssh-user tag is not set

`awsfabrictasks.default_settings.EC2_LAUNCH_CONFIGS = {}`

Configuration for ec2_launch_instance (see the docs)

`awsfabrictasks.default_settings.EXTRA_SSH_ARGS = '-o StrictHostKeyChecking=no'`

Extra SSH arguments. Used with ssh and rsync.

`awsfabrictasks.default_settings.KEYPAIR_PATH = ['. ', '~/.ssh/']`

Directories to search for "<key_name>.pem". These paths are filtered through `os.path.expanduser`, so paths like `~/.ssh/` works.

`awsfabrictasks.default_settings.S3_BUCKET_PATTERN = '{bucketname}'`

S3 bucket suffix. This is used for all tasks taking bucketname as parameter. The actual bucketname used become:

```
S3_BUCKET_PATTERN.format(bucketname=bucketname)
```

This is typically used to add your domain name or company name to all bucket names, but avoid having to type the entire name for each task. Examples:

```
S3_BUCKET_PATTERN = '{bucketname}.example.com'  
S3_BUCKET_PATTERN = 'example.com.{bucketname}'
```

The default, "`{bucketname}`", uses the bucket name as provided by the user without any changes.

See also:

```
awsfabrictasks.s3.api.S3ConnectionWrapper.get_bucket_using_pattern(),  
awsfabrictasks.s3.api.settingsformat_bucketname()
```

Indices and tables

- *genindex*
- *modindex*
- *search*

a

- `awsfabrictasks.conf`, [19](#)
- `awsfabrictasks.decorators`, [26](#)
- `awsfabrictasks.default_settings`, [32](#)
- `awsfabrictasks.ec2.api`, [21](#)
- `awsfabrictasks.ec2.tasks`, [17](#)
- `awsfabrictasks.regions`, [18](#)
- `awsfabrictasks.s3.api`, [26](#)
- `awsfabrictasks.ubuntu`, [21](#)
- `awsfabrictasks.utils`, [19](#)

A

`add_instance_to_env()` (awsfabric-
tasks.ec2.api.Ec2InstanceWrapper method),
22
`as_dict()` (awsfabrictasks.conf.Settings method), 19
`AUTH` (in module awsfabrictasks.default_settings), 32
`awsfabrictasks.conf` (module), 19
`awsfabrictasks.decorators` (module), 26
`awsfabrictasks.default_settings` (module), 32
`awsfabrictasks.ec2.api` (module), 21
`awsfabrictasks.ec2.tasks` (module), 17
`awsfabrictasks.regions` (module), 18
`awsfabrictasks.s3.api` (module), 26
`awsfabrictasks.ubuntu` (module), 21
`awsfabrictasks.utils` (module), 19

B

`both_exists()` (awsfabrictasks.s3.api.S3SyncIterFile
method), 28

C

`clear_settings()` (awsfabrictasks.conf.Settings method),
19
`compute_localfile_md5sum()` (in module awsfabric-
tasks.utils), 19
`conf` (awsfabrictasks.ec2.api.Ec2LaunchInstance at-
tribute), 24
`configname` (awsfabrictasks.ec2.api.Ec2LaunchInstance
attribute), 25
`configname_help` (awsfabric-
tasks.ec2.api.Ec2LaunchInstance attribute),
25
`configureStreamLogger()` (in module awsfabric-
tasks.utils), 19
`configureStreamLoggerForTask()` (in module awsfabric-
tasks.utils), 19
`confirm()` (awsfabrictasks.ec2.api.Ec2LaunchInstance
method), 24
`confirm_many()` (awsfabric-
tasks.ec2.api.Ec2LaunchInstance class

method), 24
`create_config_ask_if_none()` (awsfabric-
tasks.ec2.api.Ec2LaunchInstance method),
24
`create_localdir()` (awsfabrictasks.s3.api.S3SyncIterFile
method), 29

D

`DEFAULT_REGION` (in module awsfabric-
tasks.default_settings), 33
`delete()` (awsfabrictasks.s3.api.S3File method), 27
`dirlist_absfilenames()` (in module awsfabrictasks.s3.api),
29
`download_s3file_to_localfile()` (awsfabric-
tasks.s3.api.S3SyncIterFile method), 29

E

`ec2_add_tag` (in module awsfabrictasks.ec2.tasks), 17
`EC2_INSTANCE_DEFAULT_SSHUSER` (in module
awsfabrictasks.default_settings), 33
`EC2_LAUNCH_CONFIGS` (in module awsfabric-
tasks.default_settings), 33
`ec2_launch_instance` (in module awsfabric-
tasks.ec2.tasks), 17
`ec2_list_instances` (in module awsfabrictasks.ec2.tasks),
18
`ec2_login` (in module awsfabrictasks.ec2.tasks), 18
`ec2_print_instance` (in module awsfabrictasks.ec2.tasks),
18
`ec2_remove_tag` (in module awsfabrictasks.ec2.tasks), 17
`ec2_rsync()` (in module awsfabrictasks.ec2.api), 25
`ec2_rsync_download()` (in module awsfabric-
tasks.ec2.api), 25
`ec2_rsync_download_command()` (in module awsfabric-
tasks.ec2.api), 25
`ec2_rsync_download_dir` (in module awsfabric-
tasks.ec2.tasks), 18
`ec2_rsync_upload()` (in module awsfabrictasks.ec2.api),
25
`ec2_rsync_upload_command()` (in module awsfabric-
tasks.ec2.api), 25

- `ec2_rsync_upload_dir` (in module `awsfabrictasks.ec2.tasks`), 18
- `ec2_set_tag` (in module `awsfabrictasks.ec2.tasks`), 17
- `ec2_start_instance` (in module `awsfabrictasks.ec2.tasks`), 17
- `ec2_stop_instance` (in module `awsfabrictasks.ec2.tasks`), 17
- `ec2instance()` (in module `awsfabrictasks.decorators`), 26
- `Ec2InstanceWrapper` (class in `awsfabrictasks.ec2.api`), 22
- `Ec2LaunchInstance` (class in `awsfabrictasks.ec2.api`), 23
- `Ec2RegionConnectionError`, 21
- `etag_matches_localfile()` (`awsfabrictasks.s3.api.S3File` method), 28
- `etag_matches_localfile()` (`awsfabrictasks.s3.api.S3SyncIterFile` method), 29
- `exists()` (`awsfabrictasks.s3.api.S3File` method), 28
- `EXTRA_SSH_ARGS` (in module `awsfabrictasks.default_settings`), 33
- ## F
- `force_noslashend()` (in module `awsfabrictasks.utils`), 20
- `force_slashend()` (in module `awsfabrictasks.utils`), 20

G

`get_all_tags()` (`awsfabrictasks.ec2.api.Ec2LaunchInstance` method), 24

`get_bucket()` (`awsfabrictasks.s3.api.S3ConnectionWrapper` class method), 27

`get_bucket_using_pattern()` (`awsfabrictasks.s3.api.S3ConnectionWrapper` class method), 27

`get_by_instanceid()` (`awsfabrictasks.ec2.api.Ec2InstanceWrapper` class method), 22

`get_by_nametag()` (`awsfabrictasks.ec2.api.Ec2InstanceWrapper` class method), 22

`get_by_tagvalue()` (`awsfabrictasks.ec2.api.Ec2InstanceWrapper` class method), 22

`get_connection()` (`awsfabrictasks.s3.api.S3ConnectionWrapper` class method), 27

`get_contents_as_string()` (`awsfabrictasks.s3.api.S3File` method), 28

`get_contents_to_filename()` (`awsfabrictasks.s3.api.S3File` method), 28

`get_etag()` (`awsfabrictasks.s3.api.S3File` method), 28

`get_exactly_one_by_tagvalue()` (`awsfabrictasks.ec2.api.Ec2InstanceWrapper` class method), 23

`get_from_host_string()` (`awsfabrictasks.ec2.api.Ec2InstanceWrapper` class method), 23

`get_ssh_key_filename()` (`awsfabrictasks.ec2.api.Ec2InstanceWrapper` method), 23

`get_ssh_uri()` (`awsfabrictasks.ec2.api.Ec2InstanceWrapper` method), 23

`getLogLevelFromString()` (in module `awsfabrictasks.utils`), 20

`guess_contenttype()` (in module `awsfabrictasks.utils`), 20

I

`instance` (`awsfabrictasks.ec2.api.Ec2LaunchInstance` attribute), 25

`InstanceLookupError`, 21

`InvalidLogLevel`, 19

`is_running()` (`awsfabrictasks.ec2.api.Ec2InstanceWrapper` method), 23

`is_stopped()` (`awsfabrictasks.ec2.api.Ec2InstanceWrapper` method), 23

`iter_bucketcontents()` (in module `awsfabrictasks.s3.api`), 29

`iterfiles()` (`awsfabrictasks.s3.api.S3Sync` method), 28

K

`KEYPAIR_PATH` (in module `awsfabrictasks.default_settings`), 33

`kw` (`awsfabrictasks.ec2.api.Ec2LaunchInstance` attribute), 25

L

`list_regions` (in module `awsfabrictasks.regions`), 18

`list_zones` (in module `awsfabrictasks.regions`), 18

`localexists` (`awsfabrictasks.s3.api.S3SyncIterFile` attribute), 29

`localpath` (`awsfabrictasks.s3.api.S3SyncIterFile` attribute), 29

`localpath_to_s3path()` (in module `awsfabrictasks.s3.api`), 29

`localpath_to_slashpath()` (in module `awsfabrictasks.utils`), 20

`loglevel_stringmap` (in module `awsfabrictasks.utils`), 21

M

`MultipleInstancesWithSameNameError`, 22

N

`NoInstanceWithNameFound`, 22

`NotExactlyOneInstanceError`, 22

P

[parse_bool\(\)](#) (in module `awsfabrictasks.utils`), [20](#)
[parse_instanceid\(\)](#) (in module `awsfabrictasks.ec2.api`), [25](#)
[parse_instancename\(\)](#) (in module `awsfabrictasks.ec2.api`), [25](#)
[pprint\(\)](#) (`awsfabrictasks.conf.Settings` method), [19](#)
[prettyformat\(\)](#) (`awsfabrictasks.ec2.api.Ec2LaunchInstance` method), [24](#)
[prettyname\(\)](#) (`awsfabrictasks.ec2.api.Ec2InstanceWrapper` method), [23](#)
[print_ec2_instance\(\)](#) (in module `awsfabrictasks.ec2.api`), [26](#)
[print_settings](#) (in module `awsfabrictasks.conf`), [19](#)

R

[reset_settings\(\)](#) (`awsfabrictasks.conf.Settings` method), [19](#)
[rsyncformat_path\(\)](#) (in module `awsfabrictasks.utils`), [20](#)
[run_instance\(\)](#) (`awsfabrictasks.ec2.api.Ec2LaunchInstance` method), [24](#)
[run_many_instances\(\)](#) (`awsfabrictasks.ec2.api.Ec2LaunchInstance` class method), [24](#)

S

[S3_BUCKET_PATTERN](#) (in module `awsfabrictasks.default_settings`), [33](#)
[S3ConnectionError](#), [26](#)
[S3ConnectionWrapper](#) (class in `awsfabrictasks.s3.api`), [27](#)
[S3ErrorBase](#), [27](#)
[s3exists](#) (`awsfabrictasks.s3.api.S3SyncIterFile` attribute), [29](#)
[s3file](#) (`awsfabrictasks.s3.api.S3SyncIterFile` attribute), [29](#)
[S3File](#) (class in `awsfabrictasks.s3.api`), [27](#)
[S3FileDoesNotExist](#), [27](#)
[S3FileErrorBase](#), [27](#)
[S3FileExistsError](#), [27](#)
[S3FileNoInfo](#), [27](#)
[s3list_s3filedict\(\)](#) (in module `awsfabrictasks.s3.api`), [30](#)
[s3path](#) (`awsfabrictasks.s3.api.S3SyncIterFile` attribute), [29](#)
[s3path_to_localpath\(\)](#) (in module `awsfabrictasks.s3.api`), [30](#)
[S3Sync](#) (class in `awsfabrictasks.s3.api`), [28](#)
[S3SyncIterFile](#) (class in `awsfabrictasks.s3.api`), [28](#)
[set_contents_from_filename\(\)](#) (`awsfabrictasks.s3.api.S3File` method), [28](#)
[set_contents_from_string\(\)](#) (`awsfabrictasks.s3.api.S3File` method), [28](#)
[set_locale\(\)](#) (in module `awsfabrictasks.ubuntu`), [21](#)

[set_settings\(\)](#) (`awsfabrictasks.conf.Settings` method), [19](#)
[Settings](#) (class in `awsfabrictasks.conf`), [19](#)
[settingsformat_bucketname\(\)](#) (in module `awsfabrictasks.s3.api`), [30](#)
[slashpath_to_localpath\(\)](#) (in module `awsfabrictasks.utils`), [21](#)
[sudo_chattr\(\)](#) (in module `awsfabrictasks.utils`), [21](#)
[sudo_chmod\(\)](#) (in module `awsfabrictasks.utils`), [21](#)
[sudo_chown\(\)](#) (in module `awsfabrictasks.utils`), [21](#)
[sudo_mkdir_p\(\)](#) (in module `awsfabrictasks.utils`), [21](#)
[sudo_upload_dir\(\)](#) (in module `awsfabrictasks.utils`), [21](#)
[sudo_upload_file\(\)](#) (in module `awsfabrictasks.utils`), [21](#)
[sudo_upload_string_to_file\(\)](#) (in module `awsfabrictasks.utils`), [21](#)

T

[tag_retry_count](#) (`awsfabrictasks.ec2.api.Ec2LaunchInstance` attribute), [25](#)
[tag_retry_sleep](#) (`awsfabrictasks.ec2.api.Ec2LaunchInstance` attribute), [25](#)

W

[wait_for_running_state\(\)](#) (in module `awsfabrictasks.ec2.api`), [26](#)
[wait_for_running_state_many\(\)](#) (`awsfabrictasks.ec2.api.Ec2LaunchInstance` class method), [24](#)
[wait_for_state\(\)](#) (in module `awsfabrictasks.ec2.api`), [26](#)
[wait_for_stopped_state\(\)](#) (in module `awsfabrictasks.ec2.api`), [26](#)
[WaitForStateError](#), [22](#)

Z

[zipit\(\)](#) (in module `awsfabrictasks.ec2.api`), [26](#)