

---

# **django2-propeller Documentation**

***Release 2.0.1***

**Adam Radestock**

**May 02, 2019**



---

## Contents:

---

<b>1</b>	<b>Installation</b>	<b>1</b>
<b>2</b>	<b>Quickstart</b>	<b>3</b>
2.1	Example template . . . . .	3
2.2	Template tags and filters . . . . .	4
2.3	Settings . . . . .	4
2.4	Demo application . . . . .	4
<b>3</b>	<b>Template tags and filters</b>	<b>5</b>
3.1	propeller_form . . . . .	5
3.2	propeller_form_errors . . . . .	6
3.3	propeller_formset . . . . .	6
3.4	propeller_formset_errors . . . . .	7
3.5	propeller_field . . . . .	7
3.6	propeller_label . . . . .	9
3.7	propeller_button . . . . .	9
3.8	propeller_icon . . . . .	10
3.9	propeller_bootstrap_icon . . . . .	11
3.10	propeller_alert . . . . .	11
3.11	buttons . . . . .	12
3.12	propeller_messages . . . . .	14
3.13	propeller_pagination . . . . .	15
3.14	propeller_navbar . . . . .	16
3.15	propeller_card . . . . .	16
3.16	propeller_textfilters . . . . .	16
3.17	propeller_jquery_url . . . . .	18
3.18	propeller_javascript_url . . . . .	19
3.19	propeller_css_url . . . . .	19
3.20	propeller_css . . . . .	19
3.21	propeller_javascript . . . . .	20
<b>4</b>	<b>Navbar</b>	<b>21</b>
4.1	NavBarLinkItem . . . . .	21
4.2	NavBarDropDownDivider . . . . .	21
4.3	NavBarDropDownItem . . . . .	21
4.4	CustomItem . . . . .	22
4.5	NavBar . . . . .	22

---

4.6	NavBar Example . . . . .	22
<b>5</b>	<b>Card</b>	<b>25</b>
5.1	CardTitle . . . . .	25
5.2	CardSubtitle . . . . .	25
5.3	CardBody . . . . .	25
5.4	CardHeader . . . . .	26
5.5	CardMediaActions . . . . .	26
5.6	CardActions . . . . .	26
5.7	CardMediaImage . . . . .	26
5.8	CardMedia . . . . .	26
5.9	Card . . . . .	27
5.10	Card Example . . . . .	27
<b>6</b>	<b>Settings</b>	<b>29</b>
<b>7</b>	<b>Templates</b>	<b>31</b>
7.1	propeller/field_help_text_and_errors.html . . . . .	31
7.2	propeller/form_errors.html . . . . .	31
7.3	propeller/messages.html . . . . .	31
7.4	Other . . . . .	32
<b>8</b>	<b>Indices and tables</b>	<b>33</b>

# CHAPTER 1

---

## Installation

---

The preferred way to install `django2-propeller` is pip:

```
$ pip install django2-propeller
```

Alternatively, you can install download or clone this repo and install from its folder with:

```
$ pip install -e .
```

In your project, you should add `django2-propeller` to your `requirements.txt`.

Be sure to use `virtualenv` if you develop python projects.

Add to `INSTALLED_APPS` in your `settings.py`:

```
'django2_propeller',
```

After installation, the [`Quickstart`](#) will get you on your way to using `django2-propeller`.



# CHAPTER 2

---

## Quickstart

---

After [Installation](#), you can use `django-propeller` in your templates.:

Load the `propeller` library and use the `propeller_*` tags:

### 2.1 Example template

```
{# Load the tag library #}
{% load propeller %}

{# Load CSS and JavaScript #}
{% propeller_css %}
{% propeller_javascript %}

{# Display django.contrib.messages as Bootstrap alerts #}
{% propeller_messages %}

{# Display a form #}
<form action="/url/to/submit/" method="post" class="form">
    {% csrf_token %}
    {% propeller_form form %}
    {% buttons %}
        <button type="submit" class="btn btn-primary">
            {% propeller_icon "star" %} Submit
        </button>
    {% endbuttons %}
</form>

{# Read the documentation for more information #}
```

## 2.2 Template tags and filters

Refer to [Template tags and filters](#) for more information.

## 2.3 Settings

You can set defaults for django-propeller in your settings file. Refer to [Settings](#) for more information.

## 2.4 Demo application

The demo application provides a number of useful examples.

clone the repo:

```
$ git clone https://github.com/tfroehlich82/django-propeller.git
```

cd into the cloned directory:

```
$ cd django-propeller
```

run the testserver:

```
$ python manage.py runserver
```

open your browser and browse to:

```
http://127.0.0.1:8000
```

# CHAPTER 3

---

## Template tags and filters

---

**Note:** All the following examples it is understood that you have already loaded the propeller template tag library, placing the code below in the beginning that each template that propeller template tag library will be used. Read the [Installation](#) and [Quickstart](#) sections on how to accomplish this.

---

### 3.1 propeller\_form

`django2_propeller.templatetags.propeller.propeller_form(*args, **kwargs)`  
Render a form

**Tag name:**

```
propeller_form
```

**Parameters:**

**form** The form that is to be rendered

**exclude** A list of field names (comma separated) that should not be rendered E.g. exclude=subject,bcc

See [propeller\\_field](#) for other arguments

**Usage:**

```
{% propeller_form form %}
```

**Example:**

```
{% propeller_form form layout='inline' %}
```

## 3.2 propeller\_form\_errors

```
django2_propeller.templatetags.propeller.propeller_form_errors(*args,  
**kwargs)
```

Render form errors

**Tag name:**

```
propeller_form_errors
```

**Parameters:**

**form** The form that is to be rendered

**type** Control which type of errors should be rendered.

One of the following values:

- 'all'
- 'fields'
- 'non\_fields'

**default** 'all'

**layout** Context value that is available in the template `propeller/form_errors.html` as `layout`.

**Usage:**

```
{% propeller_form_errors form %}
```

**Example:**

```
{% propeller_form_errors form layout='inline' %}
```

## 3.3 propeller\_formset

```
django2_propeller.templatetags.propeller.propeller_formset(*args, **kwargs)
```

Render a formset

**Tag name:**

```
propeller_formset
```

**Parameters:**

**formset** The formset that is being rendered

See [propeller\\_field](#) for other arguments

**Usage:**

```
{% propeller_formset formset %}
```

**Example:**

```
{% propeller_formset formset layout='horizontal' %}
```

## 3.4 propeller\_formset\_errors

`django2_propeller.templatetags.propeller.propeller_formset_errors(*args, **kwargs)`

Render formset errors

**Tag name:**

```
propeller_formset_errors
```

**Parameters:**

**formset** The formset that is being rendered

**layout** Context value that is available in the template `propeller/form_errors.html` as layout.

**Usage:**

```
{% propeller_formset_errors formset %}
```

**Example:**

```
{% propeller_formset_errors formset layout='inline' %}
```

## 3.5 propeller\_field

`django2_propeller.templatetags.propeller.propeller_field(*args, **kwargs)`

Render a field

**Tag name:**

```
propeller_field
```

**Parameters:**

**field** The form field to be rendered

**layout** If set to 'horizontal' then the field and label will be rendered side-by-side, as long as there is no `field_class` set as well.

**form\_group\_class** CSS class of the `div` that wraps the field and label.

**default** 'form-group'

**field\_class** CSS class of the `div` that wraps the field.

**label\_class** CSS class of the `label` element. Will always have `control-label` as the last CSS class.

**show\_help** Show the field's help text, if the field has help text.

**default** True

**show\_label** Whether to show the label of the field.

**default** True

**exclude** A list of field names that should not be rendered

**set\_required** When set to True and the field is required then the `required` attribute is set on the rendered field. This only works up to Django 1.8. Higher Django versions handle `required` natively.

**default** True

**set\_disabled** When set to True then the `disabled` attribute is set on the rendered field. This only works up to Django 1.8. Higher Django versions handle `disabled` natively.

**default** False

**size** Controls the size of the rendered `div.form-group` through the use of CSS classes.

One of the following values:

- 'small'
- 'medium'
- 'large'

**placeholder** Sets the placeholder text of a textbox

**horizontal\_label\_class** Class used on the label when the layout is set to horizontal.

**default** 'col-md-3'. Can be changed in [Settings](#)

**horizontal\_field\_class** Class used on the field when the layout is set to horizontal.

**default** 'col-md-9'. Can be changed in [Settings](#)

**addon\_before** Text that should be prepended to the form field. See the *propeller docs* <<http://getpropeller.com/components/#input-groups-basic>> for an example.

**addon\_after** Text that should be appended to the form field. See the *propeller docs* <<http://getpropeller.com/components/#input-groups-basic>> for an example.

**addon\_before\_class** Class used on the span when `addon_before` is used.

One of the following values:

- 'input-group-addon'
- 'input-group-btn'

**default** input-group-addon

**addon\_after\_class** Class used on the span when `addon_after` is used.

One of the following values:

- 'input-group-addon'
- 'input-group-btn'

**default** input-group-addon

**error\_css\_class** CSS class used when the field has an error

**default** 'has-error'. Can be changed [Settings](#)

**required\_css\_class** CSS class used on the `div.form-group` to indicate a field is required

**default** '' . Can be changed *Settings*

**bound\_css\_class** CSS class used when the field is bound

**default** 'has-success' . Can be changed *Settings*

**Usage:**

```
{% propeller_field field %}
```

**Example:**

```
{% propeller_field field show_label=False %}
```

## 3.6 propeller\_label

django2\_propeller.templatetags.propeller.**propeller\_label**(\*args, \*\*kwargs)

Render a label

**Tag name:**

```
propeller_label
```

**Parameters:**

**content** The label's text

**label\_for** The value that will be in the `for` attribute of the rendered `<label>`

**label\_class** The CSS class for the rendered `<label>`

**label\_title** The value that will be in the `title` attribute of the rendered `<label>`

**Usage:**

```
{% propeller_label content %}
```

**Example:**

```
{% propeller_label "Email address" label_for="exampleInputEmail1" %}
```

## 3.7 propeller\_button

django2\_propeller.templatetags.propeller.**propeller\_button**(\*args, \*\*kwargs)

Render a button

**Tag name:**

```
propeller_button
```

**Parameters:**

**content** The text to be displayed in the button

**button\_type** Optional field defining what type of button this is.

Accepts one of the following values:

- 'submit'
- 'reset'
- 'button'
- 'link'

**style** Optional field defining which style button should have.

Accepts one of the following values:

- 'default'
- 'raised'
- 'flat'
- 'outline'

**icon** Name of an icon to render in the button's visible content. See *propeller\_icon* for acceptable values.

**button\_class** The class of button to use. If none is given, btn-default will be used.

**extra\_classes** Any extra CSS classes that should be added to the button.

**size** Optional field to control the size of the button.

Accepts one of the following values:

- 'xs'
- 'sm'
- 'small'
- 'md'
- 'medium'
- 'lg'
- 'large'

**href** Render the button as an `<a>` element. The `href` attribute is set with this value.

**name** Value of the `name` attribute of the rendered element.

**value** Value of the `value` attribute of the rendered element.

**Usage:**

```
{% propeller_button content %}
```

**Example:**

```
{% propeller_button "Save" button_type="submit" button_class="btn-primary" %}
```

## 3.8 propeller\_icon

`django2_propeller.templatetags.propeller.propeller_icon(icon, **kwargs)`  
Render an icon

**Tag name:**

propeller\_icon

**Parameters:**

**icon** Icon name. See the [Propeller docs](#) for all icons.

**size** Size of the icon. Must be one of ‘xs’, ‘sm’, ‘md’, or ‘lg’. Default: ‘sm’

**extra\_classes** Extra CSS classes to add to the icon HTML. Optional

**title** A title for the icon (HTML title attrivute). Optional

**Usage:**

```
{% propeller_icon icon %}
```

**Example:**

```
{% propeller_icon "star" %}
```

## 3.9 propeller\_bootstrap\_icon

```
django2_propeller.templatetags.propeller.propeller_bootstrap_icon(icon,  
**kwargs)
```

Render an icon

**Tag name:**

propeller\_bootstrap\_icon

**Parameters:**

**icon** Icon name. See the [Bootstrap docs](#) for all icons.

**extra\_classes** Extra CSS classes to add to the icon HTML. Optional

**title** A title for the icon (HTML title attrivute). Optional

**Usage:**

```
{% propeller_bootstrap_icon icon %}
```

**Example:**

```
{% propeller_bootstrap_icon "star" %}
```

## 3.10 propeller\_alert

```
django2_propeller.templatetags.propeller.propeller_alert(content,  
alert_type='info', dismissable=True)
```

Render an alert

**Tag name:**

```
propeller_alert
```

**Parameters:**

**content** HTML content of alert

**alert\_type**

- 'info'
- 'warning'
- 'danger'
- 'success'

**default** 'info'

**dismissable** boolean, is alert dismissable

**default** True

**Usage:**

```
{% propeller_alert content %}
```

**Example:**

```
{% propeller_alert "Something went wrong" alert_type='error' %}
```

## 3.11 buttons

django2\_propeller.templatetags.propeller.**propeller\_button**(\*args, \*\*kwargs)

Render a button

**Tag name:**

```
propeller_button
```

**Parameters:**

**content** The text to be displayed in the button

**button\_type** Optional field defining what type of button this is.

Accepts one of the following values:

- 'submit'
- 'reset'
- 'button'
- 'link'

**style** Optional field defining which style button should have.

Accepts one of the following values:

- 'default'
- 'raised'
- 'flat'
- 'outline'

**icon** Name of an icon to render in the button's visible content. See [propeller\\_icon](#) for acceptable values.

**button\_class** The class of button to use. If none is given, btn-default will be used.

**extra\_classes** Any extra CSS classes that should be added to the button.

**size** Optional field to control the size of the button.

Accepts one of the following values:

- 'xs'
- 'sm'
- 'small'
- 'md'
- 'medium'
- 'lg'
- 'large'

**href** Render the button as an `<a>` element. The `href` attribute is set with this value.

**name** Value of the `name` attribute of the rendered element.

**value** Value of the `value` attribute of the rendered element.

**Usage:**

```
{% propeller_button content %}
```

**Example:**

```
{% propeller_button "Save" button_type="submit" button_class="btn-primary" %}
```

`djang2_propeller.templatetags.propeller.propeller_fab(*args, **kwargs)`

Render a floating action button

**Tag name:**

```
propeller_fab
```

**Parameters:**

**content** The text to be displayed in the button

**button\_type** Optional field defining what type of button this is.

Accepts one of the following values:

- 'submit'
- 'reset'
- 'button'
- 'link'

**style** Optional field defining which style button should have.

Accepts one of the following values:

- 'default'

- 'raised'
- 'flat'
- 'outline'

**icon** Name of an icon to render in the button's visible content. See [propeller\\_icon](#) for acceptable values.

**button\_class** The class of button to use. If none is given, btn-default will be used.

**extra\_classes** Any extra CSS classes that should be added to the button.

**size** Optional field to control the size of the button.

Accepts one of the following values:

- 'xs'
- 'sm'
- 'small'
- 'md'
- 'medium'
- 'lg'
- 'large'

**href** Render the button as an `<a>` element. The `href` attribute is set with this value.

**name** Value of the `name` attribute of the rendered element.

**value** Value of the `value` attribute of the rendered element.

**Usage:**

```
{% propeller_fab content %}
```

**Example:**

```
{% propeller_fab "Save" button_type="submit" button_class="btn-primary" %}
```

## 3.12 propeller\_messages

```
django2_propeller.templatetags.propeller.propeller_messages(context, *args,  
**kwargs)
```

Show django.contrib.messages Messages in propeller alert containers.

In order to make the alerts dismissable (with the close button), we have to set the `jquery` parameter too when using the `propeller_javascript` tag.

Uses the template `propeller/messages.html`.

**Tag name:**

```
propeller_messages
```

**Parameters:**

None.

**Usage:**

{% propeller\_messages %}

**Example:**{% propeller\_javascript jquery=1 %}  
{% propeller\_messages %}

## 3.13 propeller\_pagination

```
django2_propeller.templatetags.propeller.propeller_pagination(page, **kwargs)  
Render pagination for a page
```

**Tag name:**

propeller\_pagination

**Parameters:****page** The page of results to show.**pages\_to\_show** Number of pages in total**default** 11**url** URL to navigate to for pagination forward and pagination back.**default** None**size** Controls the size of the pagination through CSS. Defaults to being normal sized.

One of the following:

• 'small'

• 'large'

**default** None**extra** Any extra page parameters.**default** None**parameter\_name** Name of the paging URL parameter.**default** 'page'**Usage:**

{% propeller\_pagination page %}

**Example:**

{% propeller\_pagination lines url="/pagination?page=1" size="large" %}

## 3.14 propeller\_navbar

---

**Hint:** See also [Navbar](#) for how to create navbar instances

---

`django2_propeller.templatetags.propeller.propeller_navbar(navbar)`  
Render a navbar.

**Tag name:**

```
propeller_navbar
```

**Parameters:**

**navbar** The previously defined navbar instance

**Usage:**

```
{% propeller_navbar navbar_instance %}
```

## 3.15 propeller\_card

---

**Hint:** See also [Card](#) for how to create card instances

---

`django2_propeller.templatetags.propeller.propeller_card(card)`  
Render a propeller card.

**Tag name:**

```
propeller_card
```

**Parameters:**

**card** The previously defined card instance

**Usage:**

```
{% propeller_card card_instance %}
```

## 3.16 propeller\_textfilters

`django2_propeller.templatetags.propeller.pmd_display_text(text, size=1)`  
Render text as a Propeller display text (heading).

**Tag name:**

```
pmd_display_text
```

**Parameters:**

```
size  
    Controls the size of the heading.  
  
    An integer from 1 (normal) to 4 (very large)  
  
    :default: ``1``
```

**Usage:**

```
{% text_variable|pmd_display_text:size %}
```

**Example:**

```
{% my_text|pmd_display_text:3 %}
```

`django2_propeller.templatetags.propeller.pmd_muted_text (text)`  
Render a muted text (secondary heading).

**Tag name:**

```
pmd_muted_text
```

**Usage:**

```
{% text_variable|pmd_muted_text %}
```

`django2_propeller.templatetags.propeller.pmd_lead_text (text)`  
Render text as a Propeller lead text (intro).

**Tag name:**

```
pmd_lead_text
```

**Usage:**

```
{% text_variable|pmd_lead_text %}
```

`django2_propeller.templatetags.propeller.pmd_mark_text (text)`  
Render highlighted text.

**Tag name:**

```
pmd_mark_text
```

**Usage:**

```
{% text_variable|pmd_mark_text %}
```

`django2_propeller.templatetags.propeller.pmd_strike_text (text, autoescape=True)`  
Render striked text.

**Tag name:**

```
pmd_strike_text
```

**Usage:**

```
{% text_variable|pmd_strike_text %}
```

django2\_propeller.templatetags.propeller.**pmd\_underline\_text** (*text*)

Render underlined text.

**Tag name:**

```
pmd_underline_text
```

**Usage:**

```
{% text_variable|pmd_underline_text %}
```

django2\_propeller.templatetags.propeller.**pmd\_bold\_text** (*text*)

Render bold text.

**Tag name:**

```
pmd_bold_text
```

**Usage:**

```
{% text_variable|pmd_bold_text %}
```

django2\_propeller.templatetags.propeller.**pmd\_italic\_text** (*text*)

Render italic text.

**Tag name:**

```
pmd_italic_text
```

**Usage:**

```
{% text_variable|pmd_italic_text %}
```

## 3.17 propeller\_jquery\_url

django2\_propeller.templatetags.propeller.**propeller\_jquery\_url()**

Return the full url to jQuery file to use

Default value: //code.jquery.com/jquery.min.js

This value is configurable, see Settings section

**Tag name:**

```
propeller_jquery_url
```

**Usage:**

```
{% propeller_jquery_url %}
```

**Example:**

```
{% propeller_jquery_url %}
```

## 3.18 propeller\_javascript\_url

`django2_propeller.templatetags.propeller.propeller_javascript_url()`

Return the full url to the Propeller JavaScript library

Default value: None

This value is configurable, see Settings section

**Tag name:**

```
propeller_javascript_url
```

**Usage:**

```
{% propeller_javascript_url %}
```

**Example:**

```
{% propeller_javascript_url %}
```

## 3.19 propeller\_css\_url

`django2_propeller.templatetags.propeller.propeller_css_url()`

Return the full url to the Propeller CSS library

Default value: None

This value is configurable, see Settings section

**Tag name:**

```
propeller_css_url
```

**Usage:**

```
{% propeller_css_url %}
```

**Example:**

```
{% propeller_css_url %}
```

## 3.20 propeller\_css

`django2_propeller.templatetags.propeller.propeller_css()`

Return HTML for Propeller CSS.

Adjust url in settings. If no url is returned, we don't want this statement to return any HTML. This is intended behavior.

Default value: None

This value is configurable, see Settings section

**Tag name:**

```
propeller_css
```

**Usage:**

```
{% propeller_css %}
```

**Example:**

```
{% propeller_css %}
```

## 3.21 propeller\_javascript

`djang2_propeller.templatetags.propeller.propeller_javascript(jquery=None)`

Return HTML for Propeller JavaScript.

Adjust url in settings. If no url is returned, we don't want this statement to return any HTML. This is intended behavior.

Default value: `None`

This value is configurable, see Settings section

**Tag name:**

```
propeller_javascript
```

**Parameters:**

**jquery** Truthy to include jQuery as well as propeller

**Usage:**

```
{% propeller_javascript %}
```

**Example:**

```
{% propeller_javascript jquery=1 %}
```

# CHAPTER 4

---

## Navbar

---

### 4.1 NavBarLinkItem

```
class django2_propeller.navbar.NavBarLinkItem(name="", url=None, icon=None)
```

Generates a Link navbar item or a Link DropDown item.

**Parameters:**

**name** The display name for the item. (for example: ‘Home’)

**url** The address for the link item. Can be a absolute URL or a resolvable Django url. (for example: ‘<http://example.org>’ or ‘home’). Optional.

**icon** not yet supported

### 4.2 NavBarDropDownDivider

```
class django2_propeller.navbar.NavBarDropDownDivider
```

Generates a DropDown Divider item.

### 4.3 NavBarDropDownItem

```
class django2_propeller.navbar.NavBarDropDownItem(name="", items=None, url=None)
```

Generates a DropDown navbar item.

**Parameters:**

**name** The display name for the item. (for example: ‘Home’)

**url** The address for the link item. Can be a absolute URL or a resolvable Django url. (for example: ‘<http://example.org>’ or ‘home’). Optional.

**icon** not yet supported

**items** A list containing NavBarLinkItems and/or NavBarDropDownDivider. Optional.

## 4.4 CustomItem

```
class django2_propeller.navbar.CustomItem(html=')
```

Returns a custom NavBar item.

Just assign some raw HTML code to *html* attribute.

## 4.5 NavBar

```
class django2_propeller.navbar.NavBar
```

NavBar is a class that generates a NavBar.

**Parameters:**

**brandname** The brand shown on the very left of the navbar.

**brandurl** The address for the brand name. Can be a absolute URL or a resolvable Django url. (for example: ‘<http://example.org>’ or ‘home’). Optional.

**items** A list containing NavBarLinkItems and/or NavBarDropDownItems. Optional.

**style\_inverse** Generate a dark navbar if true (default) or a light navbar if false.

**style\_static** Sets the static style for the navbar. Static if true (default) or floating on top if false.

## 4.6 NavBar Example

navbar.py:

```
from django2_propeller.navbar import NavBar, NavBarLinkItem, NavBarDropDownItem,_
 NavBarDropDownDivider

class DemoNavBar(NavBar):
    brandname = "Brand"
    brandurl = "http://example.org"
    items = [
        NavBarLinkItem("Link"),
        NavBarDropDownItem("DropDown", [
            NavBarLinkItem("Action"),
            NavBarLinkItem("Another action"),
            NavBarDropDownDivider(),
            NavBarLinkItem("Separated link"),
            NavBarDropDownDivider(),
            NavBarLinkItem("One more separated link"),
        ])
    ]
```

your\_view.py:

```
from django.views.generic.base import TemplateView
from django2_propeller.views import NavBarMixin
from your_project.navbar import DemoNavBar

class HomePageView(TemplateView, NavBarMixin):
    template_name = 'your_template.html'
    navbar_class = DemoNavBar
```

your\_template.html:

```
{% load propeller %}
{% propeller_navbar navbar %}
```



# CHAPTER 5

---

Card

---

## 5.1 CardTitle

```
class django2_propeller.card.CardTitle
Renders a Card Title.
```

**Parameters:**

**text** The display text for the title.

**size** The size for the title as integer. Works with the h-tag, so size=1 is bigger than size=3. Optional.  
(default=3)

## 5.2 CardSubtitle

```
class django2_propeller.card.CardSubtitle
Renders a Card Subtitle.
```

**Parameters:**

**text** The display text for the subtitle.

## 5.3 CardBody

```
class django2_propeller.card.CardBody
Renders a Card Body.
```

**Parameters:**

**text** The text to display in the body.

## 5.4 CardHeader

```
class django2_propeller.card.CardHeader
    Renders a Card Header.
```

**Parameters:**

**content\_left** A list of items to display on the left of header. May contain Button, FAB, Image, CardTitle, or CardSubtitle.

**content\_middle** A list of items to display in the middle of header. May contain Button, FAB, Image, CardTitle, or CardSubtitle.

## 5.5 CardMediaActions

```
class django2_propeller.card.CardMediaActions
    Renders Card Media Actions.
```

**Parameters:**

**items** A list of items to display in the Card Media Action section. May contain Button or FAB.

## 5.6 CardActions

```
class django2_propeller.card.CardActions
    Renders Card Actions.
```

**Parameters:**

**items** A list of items to display in the Card Action section. May contain Button or FAB.

## 5.7 CardMediaImage

```
class django2_propeller.card.CardMediaImage
    Renders a Card Media Image.
```

**Parameters:**

**image** Must be an instance of an Image.

## 5.8 CardMedia

```
class django2_propeller.card.CardMedia
    Renders Card Media
```

**Parameters:**

**content**

**if style\_inline=True:** A list of items to display in the card media section. May contain CardMediaImage, CardTitle, or CardSubtitle.

**or if style\_inline=False: (default)** A instance of CardMediaImage

**style\_inline** Display card with inline style if true. (Default: False)

## 5.9 Card

```
class django2_propeller.card.Card
    Card is a class that generates a Propeller Card.
```

Parameters:

- primary\_title** An instance of CardTitle. Optional.
- secondary\_title** An instance of CardSubtitle. Optional.
- header** An instance of CardHeader. Optional.
- media** An instance of CardMedia. Optional.
- body** An instance of CardBody. Optional.
- actions** An instance of CardActions. Optional.
- media\_actions** An instance of CardMediaActions. Optional.
- style\_inverse** Display dark style if true. (Default: False)
- style\_inline** Display card with inline style if true. (Default: False)
- width** Width of the card in Bootstrap grid (col-md) as integer. (Default: 4)

## 5.10 Card Example

card.py:

```
from django2_propeller.card import Card, CardHeader, CardActions, CardMediaActions, \
    CardTitle, CardSubtitle, \
CardMediaImage, CardBody, CardMedia
from django2_propeller.components import Image, Button, FAB

class DemoTitle(CardTitle):
    text = "Title goes here"
    size = 2

class DemoSubtitle(CardSubtitle):
    text = "Secondary text"

class DemoMediaImage(CardMediaImage):
    image = Image(source="http://propeller.in/assets/images/profile-pic.png", \
        responsive=True)

class DemoMedia(CardMedia):
    content = [DemoMediaImage(), ]

class DemoBody(CardBody):
    text = "Cards provide context and an entry point to more robust information and \
        views. " \
```

(continues on next page)

(continued from previous page)

```
"Don't overload cards with extraneous information or actions."  
  
class DemoHeader(CardHeader):  
    content_middle = [DemoTitle(), DemoSubtitle()]  
  
class DemoActions(CardActions):  
    items = [  
        Button(content='primary', button_class='btn-primary'),  
        Button('Action'),  
    ]  
  
class DemoMediaActions(CardMediaActions):  
    items = [  
        FAB('', button_class='btn-primary', icon='share', style='flat', size='sm'),  
        FAB('', button_class='btn-primary', icon='thumb_up', style='flat', size='sm'),  
        FAB('', button_class='btn-primary', icon='drafts', style='flat', size='sm')  
    ]  
  
class DemoCard(Card):  
    primary_title = DemoTitle()  
    secondary_title = DemoSubtitle()  
    header = DemoHeader()  
    actions = DemoActions()  
    media_actions = DemoMediaActions()  
    media = DemoMedia()  
    body = DemoBody()
```

your\_template.html:

```
{% load propeller %}  
{% propeller_card card %}
```

# CHAPTER 6

---

## Settings

---

The django-propeller has some pre-configured settings.

They can be modified by adding a dict variable called PROPELLER in your `settings.py` and customizing the values you want;

The PROPELLER dict variable contains these settings and defaults:

```
# Default settings
PROPELLER = {

    # The URL to the jQuery JavaScript file
    'jquery_url': '//code.jquery.com/jquery.min.js',

    # The Bootstrap base URL
    'base_url': '//maxcdn.bootstrapcdn.com/bootstrap/3.3.7/',

    # The complete URL to the Bootstrap CSS file (None means derive it from base_url)
    'css_url': None,

    # The complete URL to the Bootstrap CSS file (None means no theme)
    'theme_url': None,

    # The complete URL to the Bootstrap JavaScript file (None means derive it from base_url)
    'javascript_url': None,

    # Put JavaScript in the HEAD section of the HTML document (only relevant if you use propeller.html)
    'javascript_in_head': False,

    # Include jQuery with Bootstrap JavaScript (affects django-propeller template tags)
    'include_jquery': False,

    # Label class to use in horizontal forms
```

(continues on next page)

(continued from previous page)

```
'horizontal_label_class': 'col-md-3',

# Field class to use in horizontal forms
'horizontal_field_class': 'col-md-9',

# Set HTML required attribute on required fields, for Django <= 1.8 only
'set_required': True,

# Set HTML disabled attribute on disabled fields, for Django <= 1.8 only
'set_disabled': False,

# Set placeholder attributes to label if no placeholder is provided
'set_placeholder': True,

# Class to indicate required (better to set this in your Django form)
'required_css_class': '',

# Class to indicate error (better to set this in your Django form)
'error_css_class': 'has-error',

# Class to indicate success, meaning the field has valid input (better to set this in your Django form)
'success_css_class': 'has-success',

# Renderers (only set these if you have studied the source and understand the inner workings)
'formset_renderers': {
    'default': 'propeller.renderers.FormsetRenderer',
},
'form_renderers': {
    'default': 'propeller.renderers.FormRenderer',
},
'field_renderers': {
    'default': 'propeller.renderers.FieldRenderer',
    'inline': 'propeller.renderers.InlineFieldRenderer',
},
}
```

## Templates

---

Extend `propeller/propeller.html` template to automatically include the needed CSS and JS for Bootstrap and Propeller.

You can customize the output of `django-propeller` by writing your own templates. These templates are available:

### 7.1 propeller/field\_help\_text\_and\_errors.html

This renders the help text and error of each field.

Variable `help_text_and_errors` contains an array of strings.

### 7.2 propeller/form\_errors.html

This renders the non field errors of a form.

Variable `errors` contains an array of strings.

### 7.3 propeller/messages.html

This renders the Django messages variable.

Variable `messages` contains the messages as described in <https://docs.djangoproject.com/en/dev/ref/contrib/messages/#displaying-messages>

`messages` is passed through three built-in filters

`safe <https://docs.djangoproject.com/en/dev/ref/templates/builtins/#std:templatefilter-safe>`

`urlize <https://docs.djangoproject.com/en/dev/ref/templates/builtins/#std:templatefilter-urlize>`

*linebreaksbr <<https://docs.djangoproject.com/en/dev/ref/templates/builtins/#std:templatefilter-linebreaksbr>>*

## 7.4 Other

There are two more templates, `propeller/propeller.html` and `propeller/pagination.html`. You should consider these private for now, meaning you can use them but not modify them.

# CHAPTER 8

---

## Indices and tables

---

- genindex
- modindex
- search



---

## Index

---

### C

Card (*class in django2\_propeller.card*), 27  
CardActions (*class in django2\_propeller.card*), 26  
CardBody (*class in django2\_propeller.card*), 25  
CardHeader (*class in django2\_propeller.card*), 26  
CardMedia (*class in django2\_propeller.card*), 26  
CardMediaActions (*class in django2\_propeller.card*), 26  
CardMediaImage (*class in django2\_propeller.card*), 26  
CardSubtitle (*class in django2\_propeller.card*), 25  
CardTitle (*class in django2\_propeller.card*), 25  
CustomItem (*class in django2\_propeller.navbar*), 22

### N

NavBar (*class in django2\_propeller.navbar*), 22  
NavBarDropDownDivider (*class in django2\_propeller.navbar*), 21  
NavBarDropDownItem (*class in django2\_propeller.navbar*), 21  
NavBarLinkItem (*class in django2\_propeller.navbar*), 21

### P

pmd\_bold\_text () (*in module django2\_propeller.templatetags.propeller*), 18  
pmd\_display\_text () (*in module django2\_propeller.templatetags.propeller*), 16  
pmd\_italic\_text () (*in module django2\_propeller.templatetags.propeller*), 18  
pmd\_lead\_text () (*in module django2\_propeller.templatetags.propeller*), 17  
pmd\_mark\_text () (*in module django2\_propeller.templatetags.propeller*), 17

pmd\_muted\_text () (*in module django2\_propeller.templatetags.propeller*), 17  
pmd\_strike\_text () (*in module django2\_propeller.templatetags.propeller*), 17  
pmd\_underline\_text () (*in module django2\_propeller.templatetags.propeller*), 18  
propeller\_alert () (*in module django2\_propeller.templatetags.propeller*), 11  
propeller\_bootstrap\_icon () (*in module django2\_propeller.templatetags.propeller*), 11  
propeller\_button () (*in module django2\_propeller.templatetags.propeller*), 9, 12  
propeller\_card () (*in module django2\_propeller.templatetags.propeller*), 16  
propeller\_css () (*in module django2\_propeller.templatetags.propeller*), 19  
propeller\_css\_url () (*in module django2\_propeller.templatetags.propeller*), 19  
propeller\_fab () (*in module django2\_propeller.templatetags.propeller*), 13  
propeller\_field () (*in module django2\_propeller.templatetags.propeller*), 7  
propeller\_form () (*in module django2\_propeller.templatetags.propeller*), 5  
propeller\_form\_errors () (*in module django2\_propeller.templatetags.propeller*), 6  
propeller\_formset () (*in module django2\_propeller.templatetags.propeller*),

```
    6
propeller_formset_errors()      (in     module
    django2_propeller.templatetags.propeller), 7
propeller_icon()              (in     module
    django2_propeller.templatetags.propeller),
    10
propeller_javascript()        (in     module
    django2_propeller.templatetags.propeller),
    20
propeller_javascript_url()   (in     module
    django2_propeller.templatetags.propeller), 19
propeller_jquery_url()        (in     module
    django2_propeller.templatetags.propeller),
    18
propeller_label()             (in     module
    django2_propeller.templatetags.propeller),
    9
propeller_messages()          (in     module
    django2_propeller.templatetags.propeller),
    14
propeller_navbar()            (in     module
    django2_propeller.templatetags.propeller),
    16
propeller_pagination()         (in     module
    django2_propeller.templatetags.propeller),
    15
```