
djinfo documentation

Release 0.0.6

Maxime Haineault

Dec 28, 2018

Contents

1	Installation	3
2	Settings	5
3	Integration	7
4	Indices and tables	9

Debugging information page intended for production use.

▼ Settings

Core

ABSOLUTE_URL_OVERRIDES	{},
ADMINS	[]
ALLOWED_HOSTS	['127.0.0.1', 'localhost', '192.168.2.10',]
APPEND_SLASH	True
AUTHENTICATION_BACKENDS	['userena.backends.UserenaAuthenticationBackend', 'guardian.backends.ObjectPermissionBackend', 'django.contrib.auth.backends.ModelBackend',]
AUTH_PASSWORD_VALIDATORS	'*****'
AUTH_USER_MODEL	'users.User'
CACHES	{ 'default': { 'BACKEND': 'django.core.cache.backends.locmem.LocMemCache' } }
CACHE_MIDDLEWARE_ALIAS	'default'
CACHE_MIDDLEWARE_KEY_PREFIX	''
CACHE_MIDDLEWARE_SECONDS	600
CSRF_COOKIE_AGE	31449600
CSRF_COOKIE_DOMAIN	None
CSRF_COOKIE_HTTPONLY	False
CSRF_COOKIE_NAME	'csrftoken'
CSRF_COOKIE_PATH	'/'
CSRF_COOKIE_SECURE	False
CSRF_FAILURE_VIEW	'django.views.csrf.csrf_failure'
CSRF_HEADER_NAME	'HTTP_X_CSRFTOKEN'
CSRF_TRUSTED_ORIGINS	[]

CHAPTER 1

Installation

From Pypi:

```
pip install djinfo
```

Add *djinfo* to your setting's *INSTALLED_APPS*.

Add *djinfo* URL to your project's *urls.py*:

```
from django.conf.urls import url
from django.contrib import admin

urlpatterns = [
    url(r'^admin/', admin.site.urls),
    url(r'^djinfo/', 'djinfo.urls'),
]
```

You can then navigate to <http://127.0.0.1:8000/djinfo/>

Note: Only super user will be able to access this page!

DJINFO_MASK_SETTINGS

Default: `[r'.*PASSPHRASE.*', r'.*PASSWORD.*', r'.*SECRET.*']`

Settings keys matching any of the provided regex list will have their value masked with asterisks.

DJINFO_MASK_ENV

Default: `[r'.*PASSPHRASE.*', r'.*PASSWORD.*', r'.*SECRET.*']`

Environment keys matching any of the provided regex list will have their value masked with asterisks.

DJINFO_EXCLUDE_ENV

Default: `[r'^_fzf.*']`

So far this setting exists solely because fzf is polluting the environment with every single setting it has in bank.

DJINFO_USER_TEST

Default: `lambda u: u.is_superuser`

The function used to test if a user should be allowed to view the djinfo index.

DJINFO_SHOW

Default: `['settings', 'environment']`

An iterable containing blocks to show on the djinfo index.

CHAPTER 3

Integration

If you need to integrate a link to dinfo in a template:

```
{% if request.user.is_superuser %}  
<a href="{% url 'dinfo:index' %}">dinfo</a>  
{% endif %}
```

It is also possible to access the data shown on the page as JSON by adding `?json` to the URL: `{% url 'dinfo:index' %}?json`.

CHAPTER 4

Indices and tables

- `genindex`
- `modindex`
- `search`