
ERPpeek Documentation

Release 1.7.1

Florent Xicluna

Dec 05, 2018

Contents

1	Introduction	3
1.1	Installation	3
1.2	Command line arguments	3
1.3	Interactive use	4
2	ERPpeek API	7
2.1	Client and Services	7
2.2	Model and Records	12
2.3	Utilities	14
3	Tutorial	17
3.1	First connection	17
3.2	Create a database	18
3.3	Clone a database	19
3.4	Find the users	19
3.5	Create a new user	21
3.6	Explore the model	21
3.7	Browse the records	23
4	Developer's notes	25
4.1	Source code	25
4.2	Third-party integration	25
4.3	Changes	25
5	Indices and tables	35
6	Credits	37
	Python Module Index	39

A versatile tool for browsing Odoo / OpenERP data

The ERPpeek library communicates with any Odoo / OpenERP server (>= 5.0) using the standard XML-RPC interface or the new JSON-RPC interface.

It provides both a *fully featured low-level API*, and an encapsulation of the methods on *Active Record objects*. Additional helpers are provided to explore the model and administrate the server remotely.

The [*Introduction*](#) describes its primary uses as a [*command line tool*](#) or within an [*interactive shell*](#).

The [*Tutorial*](#) gives an in-depth look at the capabilities.

Contents:

CHAPTER 1

Introduction

This section gives the bare minimum to use ERPpeek as a *command line tool* or within an *interactive shell*.

1.1 Installation

Download and install the latest release from PyPI:

```
pip install -U erppeek
```

1.2 Command line arguments

There are few arguments to query Odoo models from the command line. Although it is quite limited:

```
$ erppeek --help
Usage: erppeek [options] [search_term_or_id [search_term_or_id ...]]

Inspect data on Odoo objects. Use interactively or query a model (-m)
and pass search terms or ids as positional parameters after the options.

Options:
--version           show program's version number and exit
-h, --help          show this help message and exit
-l, --list          list sections of the configuration
--env=ENV          read connection settings from the given section
-c CONFIG, --config=CONFIG
                  specify alternate config file (default: 'erppeek.ini')
--server=SERVER    full URL of the server (default: http://localhost:8069/xmlrpc)
-d DB, --db=DB      database
-u USER, --user=USER username
-p PASSWORD, --password=PASSWORD
```

(continues on next page)

(continued from previous page)

```
password, or it will be requested on login
-m MODEL, --model=MODEL
    the type of object to find
-f FIELDS, --fields=FIELDS
    restrict the output to certain fields (multiple allowed)
-i, --interact
    use interactively; default when no model is queried
-v, --verbose
    verbose
$ #
```

Example:

```
$ erppeek -d demo -m res.partner -f name -f lang 1
"name", "lang"
"Your Company", "en_US"
```

```
$ erppeek -d demo -m res.groups -f full_name 'id > 0'
"full_name"
"Administration / Access Rights"
"Administration / Configuration"
"Human Resources / Employee"
"Usability / Multi Companies"
"Usability / Extended View"
"Usability / Technical Features"
"Sales Management / User"
"Sales Management / Manager"
"Partner Manager"
```

1.3 Interactive use

Edit `erppeek.ini` and declare the environment(s):

```
[DEFAULT]
scheme = http
host = localhost
port = 8069
database = odoo
username = admin

[demo]
username = demo
password = demo
protocol = xmlrpc

[demo_jsonrpc]
username = demo
password = demo
protocol = jsonrpc

[local]
scheme = local
options = -c /path/to/odoo-server.conf --without-demo all
```

Connect to the Odoo server:

```
erppeek --list  
erppeek --env demo
```

This is a sample session:

```
>>> model('res.users')  
<Model 'res.users'>  
>>> model('res.users').count()  
4  
>>> model('ir.cron').read(['active = False'], 'active function')  
[{'active': False, 'function': 'run_mail_scheduler', 'id': 1},  
 {'active': False, 'function': 'run_bdr_scheduler', 'id': 2},  
 {'active': False, 'function': 'scheduled_fetch_new_scans', 'id': 9}]  
>>> #  
>>> client.modules('delivery')  
{'uninstalled': ['delivery', 'sale_delivery_report']}  
>>> client.upgrade('base')  
1 module(s) selected  
42 module(s) to process:  
 to upgrade account  
 to upgrade account_chart  
 to upgrade account_tax_include  
 to upgrade base  
 ...  
>>> #
```

Note: Use the `--verbose` switch to see what happens behind the scene. Lines are truncated at 79 chars. Use `-vvv` or `-vvvv` to print more.

Note: To preserve the history of commands when closing the session, first create an empty file in your home directory: `touch ~/.erppeek_history`

More details in the [Tutorial](#) section.

CHAPTER 2

ERPpeek API

The library provides few objects to access the OpenObject model and the associated services of the Odoo API.

The signature of the methods mimics the standard methods provided by the `osv.Model` Odoo class. This is intended to help the developer when developing addons. What is experimented at the interactive prompt should be portable in the application with little effort.

- *Client and Services*
 - *Objects*
 - *Advanced methods*
 - *Odoo RPC Services*
 - *Manage addons*
- *Model and Records*
- *Utilities*

2.1 Client and Services

The `Client` object provides thin wrappers around Odoo RPC services and their methods. Additional helpers are provided to explore the models and list or install Odoo add-ons.

```
class erppeek.Client(server, db=None, user=None, password=None, transport=None, verbose=False)
```

Connection to an Odoo instance.

This is the top level object. The `server` is the URL of the instance, like `http://localhost:8069`. If `server` is an `odoo/openerp` Python package, it is used to connect to the local server (≥ 6.1).

The `db` is the name of the database and the `user` should exist in the table `res.users`. If the `password` is not provided, it will be asked on login.

classmethod `Client.from_config(environment, user=None, verbose=False)`

Create a connection to a defined environment.

Read the settings from the section [environment] in the `erppeek.ini` file and return a connected `Client`. See `read_config()` for details of the configuration file format.

`Client.create_database(passwd, database, demo=False, lang='en_US', user_password='admin', login='admin', country_code=None)`

Create a new database.

The superadmin `passwd` and the `database` name are mandatory. By default, `demo` data are not loaded, `lang` is `en_US` and no country is set into the database. Login if successful.

`Client.clone_database(passwd, db_name)`

Clone the current database.

The superadmin `passwd` and `db_name` are mandatory. Login if successful.

Supported since OpenERP 7.

`Client.login(user, password=None, database=None)`

Switch `user` and (optionally) `database`.

If the `password` is not available, it will be asked.

`Client.context`

Default context used for all the methods (default None). In *interactive mode*, this default context contains the language of the shell environment (variable `LANG`). Do not update the context, either copy it or replace it:

```
# Set language to German
client.context = {'lang': 'de_DE', 'preferred_color': 'blue'}
# ... do something

# Switch to Italian
client.context = dict(client.context, lang='it_IT')
# ... do something

# and AVOID (because it changes the context of existing records)
client.context['lang'] = 'fr_FR'
```

Note: In *interactive mode*, a method `Client.connect(env=None)` exists, to connect to another environment, and recreate the `globals()`.

Note: In *interactive mode*, when connected to the local Odoo server, the `get_pool(db_name=None)` function helps to grab a model registry for the current database. The cursor factory is available on the registry as `get_pool().cursor()` (Odoo) or `get_pool().db.cursor()` (OpenERP <= 7).

2.1.1 Objects

`Client.search(obj, domain, offset=0, limit=None, order=None, context=None)`

Filter the records in the `domain`, return the `ids`.

`Client.count(obj, domain, context=None)`

Count the records in the `domain`.

`Client.read(obj, domain, fields=None, offset=0, limit=None, order=None, context=None)`

Wrapper for `client.execute(obj, 'read', [...], ('a', 'b'))`.

The first argument `obj` is the model name (example: "res.partner")

The second argument, `domain`, accepts:

- [('name', '=', 'mushroom'), ('state', '!=', 'draft')]
- ['name = mushroom', 'state != draft']
- []
- a list of ids [1, 2, 3] or a single id 42

The third argument, `fields`, accepts:

- a single field: 'first_name'
- a tuple of fields: ('street', 'city')
- a space separated string: 'street city'
- a format spec: '%(street)s %(city)s'

If `fields` is omitted, all fields are read.

If `domain` is a single id, then:

- return a single value if a single field is requested.
- return a string if a format spec is passed in the `fields` argument.
- else, return a dictionary.

If `domain` is not a single id, the returned value is a list of items. Each item complies with the rules of the previous paragraph.

The optional keyword arguments `offset`, `limit` and `order` are used to restrict the search. The `order` is also used to order the results returned. Note: the low-level RPC method `read` itself does not preserve the order of the results.

`Client.perm_read(obj, ids, context=None, details=True)`

Lookup metadata about the records in the `ids` list. Return a list of dictionaries with the following keys:

- `id`: object id
- `create_uid`: user who created the record
- `create_date`: date when the record was created
- `write_uid`: last user who changed the record
- `write_date`: date of the last change to the record
- `xmjid`: External ID to use to refer to this record (if there is one), in format `module.name` (not available with OpenERP 5)

If `details` is True, the `create_uid` and `write_uid` contain the name of the user.

`Client.write(obj, ids, values, context=None)`

Update the record(s) with the content of the `values` dictionary.

`Client.create(obj, values, context=None)`

Create a new record for the model. The argument `values` is a dictionary of values for the new record. Return the object `id`.

`Client.copy (obj, id, default=None, context=None)`

Copy a record and return the new `id`. The optional argument `default` is a mapping which overrides some values of the new record.

`Client.unlink (obj, ids, context=None)`

Delete records with the given `ids`

`Client.models (name=")`

Return a dictionary of models.

The argument `name` is a pattern to filter the models returned. If omitted, all models are returned. Keys are camel case names of the models. Values are instances of `Model`.

The return value can be used to declare the models in the global namespace:

```
>>> globals().update(client.models('res.'))
```

`Client.model (name, check=True)`

Return a `Model` instance.

The argument `name` is the name of the model. If the optional argument `check` is `False`, no validity check is done.

`Client.keys (obj)`

Wrapper for `Model.keys ()` method.

`Client.fields (obj, names=None)`

Wrapper for `Model.fields ()` method.

`Client.field (obj, name)`

Wrapper for `Model.field ()` method.

`Client.access (obj, mode='read')`

Wrapper for `Model.access ()` method.

2.1.2 Advanced methods

Those methods give more control on the Odoo objects: workflows and reports. Please refer to the Odoo documentation for details.

`Client.execute (obj, method, *params, **kwargs)`

Wrapper around `object.execute` RPC method.

Argument `method` is the name of an `osv.osv` method or a method available on this `obj`. Method `params` are allowed. If needed, keyword arguments are collected in `kwargs`.

`Client.execute_kw (obj, ids, params, kwargs=None)`

Wrapper around `object.execute_kw` RPC method.

Does not exist if server is OpenERP 5.

`Client.exec_workflow (obj, signal, obj_id)`

Wrapper around `object.exec_workflow` RPC method.

Argument `obj` is the name of the model. The `signal` is sent to the object identified by its integer `id` `obj_id`.

`Client.report (obj, ids, datas=None, context=None)`

Wrapper around `report.report` RPC method.

Removed in Odoo 11.

`Client.render_report (obj, ids, datas=None, context=None)`

Wrapper around `report.render_report` RPC method.

Does not exist if server is OpenERP 5.

Removed in Odoo 11.

`Client.report_get (report_id)`

Wrapper around `report.report_get` RPC method.

Removed in Odoo 11.

`Client.wizard (name, datas=None, action='init', context=<object object>)`

Wrapper around `wizard.create` and `wizard.execute` RPC methods.

If only `name` is provided, a new wizard is created and its `id` is returned. If `action` is not "init", then the action is executed. In this case the `name` is either an `id` or a string. If the `name` is a string, the wizard is created before the execution. The optional `datas` argument provides data for the action. The optional `context` argument is passed to the RPC method.

Removed in OpenERP 7.

Removed in OpenERP 7.

2.1.3 Odoo RPC Services

The naked Odoo services are exposed too. The `db` and the `common` services expose few methods which might be helpful for server administration. Use the `dir()` function to introspect them. The `:attr:~Client._object` service should not be used directly because its methods are wrapped and exposed on the `Client` object itself. The two last services are deprecated and removed in recent versions of Odoo. Please refer to the Odoo documentation for more details.

`Client.db`

Expose the `db Service`.

Example: `Client.db.list()` or `Client.db.server_version()` RPC methods.

`Client.common`

Expose the `common Service`.

Example: `Client.common.login_message()` RPC method.

`Client._object`

Expose the `object Service`.

`Client._report`

Expose the `report Service`.

Removed in Odoo 11.

`Client._wizard`

Expose the `wizard Service`.

Removed in OpenERP 7.

`class erppeek.Service (client, endpoint, methods, verbose=False)`

A wrapper around XML-RPC endpoints.

The connected endpoints are exposed on the Client instance. The `server` argument is the URL of the server (scheme+host+port). If `server` is an `odoo` Python package, it is used to connect to the local server. The `endpoint` argument is the name of the service (examples: "object", "db"). The `methods` is the list of methods which should be exposed on this endpoint. Use `dir(...)` on the instance to list them.

2.1.4 Manage addons

These helpers are convenient to list, install or upgrade addons from a Python script or interactively in a Python session.

`Client.modules (name=”, installed=None)`

Return a dictionary of modules.

The optional argument `name` is a pattern to filter the modules. If the boolean argument `installed` is `True`, the modules which are “Not Installed” or “Not Installable” are omitted. If the argument is `False`, only these modules are returned. If argument `installed` is omitted, all modules are returned. The return value is a dictionary where module names are grouped in lists according to their state.

`Client.install (*modules)`

Press the button Install.

`Client.upgrade (*modules)`

Press the button Upgrade.

`Client.uninstall (*modules)`

Press the button Uninstall.

Note: It is not recommended to install or upgrade modules in offline mode when any web server is still running: the operation will not be signaled to other processes. This restriction does not apply when connected through XML-RPC or JSON-RPC.

2.2 Model and Records

In addition to the thin wrapper methods, the `Client` provides a high level API which encapsulates objects into [Active Records](#).

The `Model` is instantiated using the `Client.model()` method or directly through camel case attributes.

Example: both `client.model('res.company')` and `client.ResCompany` return the same `Model`.

`class erppeek.Model (client, model_name)`

The class for Odoo models.

`keys ()`

Return the keys of the model.

`fields (names=None)`

Return a dictionary of the fields of the model.

Optional argument `names` is a sequence of field names or a space separated string of these names. If omitted, all fields are returned.

`field (name)`

Return the field properties for field `name`.

`access (mode='read')`

Check if the user has access to this model.

Optional argument `mode` is the access mode to check. Valid values are `read`, `write`, `create` and `unlink`. If omitted, the `read` mode is checked. Return a boolean.

`browse (domain, offset=0, limit=None, order=None, context=None)`

Return a `Record` or a `RecordList`.

The argument *domain* accepts a single integer *id*, a list of ids or a search domain. If it is a single integer, the return value is a [Record](#). Otherwise, the return value is a [RecordList](#). To get all the records, pass an empty list along with keyword argument *limit=None*.

Note: To enable the unsafe behavior (ERPpeek <= 1.7) of `model.browse([])` (i.e. return all records), this class attribute can be set: `Model._browse_compat = True`.

get (*domain, context=None*)
Return a single [Record](#).

The argument *domain* accepts a single integer *id* or a search domain, or an external ID *xml_id*. The return value is a [Record](#) or None. If multiple records are found, a `ValueError` is raised.

create (*values, context=<object object>*)
Create a [Record](#).

The argument *values* is a dictionary of values which are used to create the record. Relationship fields *one2many* and *many2many* accept either a list of ids or a [RecordList](#) or the extended Odoo syntax. Relationship fields *many2one* and *reference* accept either a [Record](#) or the Odoo syntax.

The newly created [Record](#) is returned.

_get_external_ids (*ids=None*)
Retrieve the External IDs of the records.

Return a dictionary with keys being the fully qualified External IDs, and values the [Record](#) entries.

class `erppeek.RecordList(model, ids)`
A sequence of Odoo [Record](#).

It has a similar API as the [Record](#) class, but for a list of records. The attributes of the [RecordList](#) are read-only, and they return list of attribute values in the same order. The *many2one*, *one2many* and *many2many* attributes are wrapped in [RecordList](#) and list of [RecordList](#) objects. Use the method `RecordList.write` to assign a single value to all the selected records.

read (*fields=None, context=None*)
Wrapper for the `Record.read()` method.

Return a [RecordList](#) if *fields* is the name of a single *many2one* field, else return a list. See `Client.read()` for details.

perm_read (*context=None*)
Wrapper for the `Record.perm_read()` method.

write (*values, context=None*)
Wrapper for the `Record.write()` method.

unlink (*context=None*)
Wrapper for the `Record.unlink()` method.

_external_id
Retrieve the External IDs of the [RecordList](#).

Return the list of fully qualified External IDs of the [RecordList](#), with default value False if there's none. If multiple IDs exist for a record, only one of them is returned.

class `erppeek.Record(model, id)`
A class for all Odoo records.

It maps any Odoo object. The fields can be accessed through attributes. The changes are immediately sent to the server. The *many2one*, *one2many* and *many2many* attributes are wrapped in [Record](#) and [RecordList](#)

objects. These attributes support writing too. The attributes are evaluated lazily, and they are cached in the record. The Record's cache is invalidated if any attribute is changed.

_external_id

Retrieve the External ID of the *Record*.

Return the fully qualified External ID of the *Record*, with default value False if there's none. If multiple IDs exist, only one of them is returned (randomly).

_send(signal)

Trigger workflow *signal* for this *Record*.

copy(default=None, context=<object object>)

Copy a record and return the new *Record*.

The optional argument *default* is a mapping which overrides some values of the new record.

perm_read(context=<object object>)

Read the metadata of the *Record*.

Return a dictionary of values. See *Client.perm_read()* for details.

read(fields=None, context=<object object>)

Read the *fields* of the *Record*.

The argument *fields* accepts different kinds of values. See *Client.read()* for details.

refresh()

Force refreshing the record's data.

unlink(context=<object object>)

Delete the current *Record* from the database.

write(values, context=<object object>)

Write the *values* in the *Record*.

values is a dictionary of values. See *Model.create()* for details.

2.3 Utilities

erppeek.lowercase(s)

Convert to lowercase with dots.

```
>>> lowercase('ResCompany')
'res.company'
```

erppeek.mixedcase(s)

Convert to MixedCase.

```
>>> mixedcase('res.company')
'ResCompany'
```

erppeek.issearchdomain(arg)

Check if the argument is a search domain.

Examples:

- [('name', '=', 'mushroom'), ('state', '!=', 'draft')]
- ['name = mushroom', 'state != draft']
- []

`erppeek.searchargs` (*params*, *kwargs=None*, *context=None*, *api_v9=False*)

Compute the ‘search’ parameters.

`erppeek.format_exception` (*type*, *value*, *tb*, *limit=None*, *chain=True*)

Format a stack trace and the exception information.

This wrapper is a replacement of `traceback.format_exception` which formats the error and traceback received by XML-RPC/JSON-RPC. If *chain* is True, then the original exception is printed too.

`erppeek.read_config` (*section=None*)

Read the environment settings from the configuration file.

The config file `erppeek.ini` contains a *section* for each environment. Each section provides parameters for the connection: host, port, database, username and (optional) password. Default values are read from the [DEFAULT] section. If the password is not in the configuration file, it is requested on login. Return a tuple (server, db, user, password or None). Without argument, it returns the list of configured environments.

`erppeek.start_odoo_services` (*options=None*, *appname=None*)

Initialize the Odoo services.

Import the `odoo` Python package and load the Odoo services. The argument *options* receives the command line arguments for `odoo`. Example:

```
[ '-c', '/path/to/odoo-server.conf', '--without-demo', 'all' ].
```

Return the `odoo` package.

CHAPTER 3

Tutorial

This tutorial demonstrates some features of ERPpeek in the interactive shell.

It assumes an Odoo or OpenERP server is installed. The shell is a true Python shell. We have access to all the features and modules of the Python interpreter.

Steps:

- *First connection*
- *Create a database*
- *Clone a database*
- *Find the users*
- *Create a new user*
- *Explore the model*
- *Browse the records*

3.1 First connection

The server is freshly installed and does not have an Odoo database yet. The tutorial creates its own database `demo` to play with.

Open the ERPpeek shell:

```
$ erppeek
```

It assumes that the server is running locally, and listens on default port 8069.

If our configuration is different, then we use arguments, like:

```
$ erppeek --server http://192.168.0.42:8069
```

It connects using the XML-RPC protocol. If you want to use the JSON-RPC protocol instead, then pass the full URL with /jsonrpc path:

```
$ erppeek --server http://127.0.0.1:8069/jsonrpc
```

On login, it prints few lines about the commands available.

```
$ erppeek
Usage (some commands):
models(name)                      # List models matching pattern
model(name)                        # Return a Model instance
model(name).keys()                 # List field names of the model
model(name).fields(names=None)     # Return details for the fields
model(name).field(name)            # Return details for the field
model(name).browse(domain)         # Return a RecordList

rec = model(name).get(domain)      # Get the Record matching domain
rec.some_field                     # Return the value of this field
rec.read(fields=None)              # Return values for the fields

client.login(user)                 # Login with another user
client.connect(env)                # Connect to another env.
client.modules(name)               # List modules matching pattern
client.upgrade(module1, module2, ...)
                                # Upgrade the modules
```

As we'll see later, the most interesting method here is probably `model()` which returns a `Model` object with nice wrappers.

And it confirms that the default database is not available:

```
...
Error: Database 'odoo' does not exist: []
```

Though, we have a connected client, ready to use:

```
>>> client
<Client 'http://localhost:8069/xmlrpc#()'>
>>> client.server_version
'6.1'
>>> #
```

3.2 Create a database

We create the database "demo" for this tutorial. We need to know the superadmin password before to continue. This is the `admin_passwd` in the `odoo-server.conf` file. Default password is "admin".

Note: This password gives full control on the databases. Set a strong password in the configuration to prevent unauthorized access.

```
>>> client.create_database('super_password', 'demo')
Logged in as 'admin'
>>> client
<Client 'http://localhost:8069/xmlrpc#demo'>
>>> client.db.list()
['demo']
>>> client.user
'admin'
>>> client.modules(installed=True)
{'installed': ['base', 'web', 'web_mobile', 'web_tests']}
>>> len(client.modules()['uninstalled'])
202
>>> #
```

Note: Create an `erppeek.ini` file in the current directory to declare all our environments. Example:

```
[DEFAULT]
host = localhost
port = 8069

[demo]
database = demo
username = joe
```

Then we connect to any environment with `erppeek --env demo` or switch during an interactive session with `client.connect('demo')`.

3.3 Clone a database

It is sometimes useful to clone a database (testing, backup, migration, ...). A shortcut is available for that, the required parameters are the new database name and the superadmin password.

```
>>> client.clone_database('super_password', 'demo_test')
Logged in as 'admin'
>>> client
<Client 'http://localhost:8069/xmlrpc#demo_test'>
>>> client.db.list()
['demo', 'demo_test']
>>> client.user
'admin'
>>> client.modules(installed=True)
{'installed': ['base', 'web', 'web_mobile', 'web_tests']}
>>> len(client.modules()['uninstalled'])
202
>>> #
```

3.4 Find the users

We have created the database "demo" for the tests. We are connected to this database as 'admin'.

Where is the table for the users?

```
>>> client
<Client 'http://localhost:8069/xmlrpc#demo'>
>>> models('user')
{'ResUsers': <Model 'res.users'>, 'ResWidgetUser': <Model 'res.widget.user'>}
```

We've listed two models which matches the name, `res.users` and `res.widget.user`. We reach the `users`' model using the `model()` method and we want to introspect its fields. Fortunately, the `Model` class provides methods to retrieve all the details.

```
>>> model('res.users')
<Model 'res.users'>
>>> print(model('res.users').keys())
['action_id', 'active', 'company_id', 'company_ids', 'context_lang',
 'context_tz', 'date', 'groups_id', 'id', 'login', 'menu_id', 'menu_tips',
 'name', 'new_password', 'password', 'signature', 'user_email', 'view']
>>> model('res.users').field('view')
{'digits': [16, 2],
 'fnct_inv': '_set_interface_type',
 'fnct_inv_arg': False,
 'fnct_search': False,
 'func_obj': False,
 'function': '_get_interface_type',
 'help': 'OpenERP offers a simplified and an extended user interface. If you use OpenERP for the first time we strongly advise you to select the simplified interface, which has less features but is easier to use. You can switch to the other interface from the User/Preferences menu at any time.',
 'selection': [['simple', 'Simplified'], ['extended', 'Extended']],
 'store': False,
 'string': 'Interface',
 'type': 'selection'}
>>> #
```

Let's examine the '`admin`' user in details.

```
>>> model('res.users').count()
1
>>> admin_user = model('res.users').browse(1)
>>> admin_user.groups_id
<RecordList 'res.groups,[1, 2, 3]'>
>>> admin_user.groups_id.name
['Access Rights', 'Configuration', 'Employee']
>>> admin_user.groups_id.full_name
['Administration / Access Rights',
 'Administration / Configuration',
 'Human Resources / Employee']
>>> admin_user.perm_read()
{'create_date': False,
 'create_uid': False,
 'id': 1,
 'write_date': '2012-09-01 09:01:36.631090',
 'write_uid': [1, 'Administrator'],
 'xmlid': 'base.user_admin'}
```

3.5 Create a new user

Now we want a non-admin user to continue the exploration. Let's create Joe.

```
>>> model('res.users').create({'login': 'joe'})
Fault: Integrity Error

The operation cannot be completed, probably due to the following:
- deletion: you may be trying to delete a record while other records still reference it
- creation/update: a mandatory field is not correctly set

[object with reference: name - name]
>>> #
```

It seems we've forgotten some mandatory data. Let's give him a name.

```
>>> model('res.users').create({'login': 'joe', 'name': 'Joe'})
<Record 'res.users,3'>
>>> joe_user = _
>>> joe_user.groups_id.full_name
['Human Resources / Employee', 'Partner Manager']
```

The user Joe does not have a password: we cannot login as joe. We set a password for Joe and we try again.

```
>>> client.login('joe')
Password for 'joe':
Error: Invalid username or password
>>> client.user
'admin'
>>> joe_user.password = 'bar'
>>> client.login('joe')
Logged in as 'joe'
>>> client.user
'joe'
>>> #
```

Success!

3.6 Explore the model

We keep connected as user Joe and we explore the world around us.

```
>>> client.user
'joe'
>>> all_models = sorted(models().values(), key=str)
>>> len(all_models)
92
```

Among these 92 objects, some of them are read-only, others are read-write. We can also filter the non-empty models.

```
>>> # Read-only models
>>> len([m for m in all_models if not m.access('write')])
44
```

(continues on next page)

(continued from previous page)

```

>>> #
>>> # Writable but cannot delete
>>> [m for m in all_models if m.access('write') and not m.access('unlink')]
[<Model 'ir.property'>]
>>> #
>>> # Unreadable models
>>> [m for m in all_models if not m.access('read')]
[<Model 'ir.actions.todo'>,
 <Model 'ir.actions.todo.category'>,
 <Model 'res.payterm'>]
>>> #
>>> # Now print the number of entries in all (readable) models
>>> for m in all_models:
...     mcount = m.access() and m.count()
...     if not mcount:
...         continue
...     print('%4d %s' % (mcount, m))
...
81  <Model 'ir.actions.act_window'>
14   <Model 'ir.actions.act_window.view'>
85   <Model 'ir.actions.act_window_close'>
85   <Model 'ir.actions.actions'>
4    <Model 'ir.actions.report.xml'>
3    <Model 'ir.config_parameter'>
2    <Model 'ir.cron'>
1    <Model 'ir.mail_server'>
92   <Model 'ir.model'>
126  <Model 'ir.model.access'>
1941  <Model 'ir.model.data'>
658   <Model 'ir.model.fields'>
32    <Model 'ir.module.category'>
207   <Model 'ir.module.module'>
432   <Model 'ir.module.module.dependency'>
8    <Model 'ir.rule'>
63    <Model 'ir.ui.menu'>
185   <Model 'ir.ui.view'>
1    <Model 'ir.ui.view_sc'>
72    <Model 'ir.values'>
1    <Model 'res.bank'>
1    <Model 'res.company'>
253   <Model 'res.country'>
51    <Model 'res.country.state'>
48    <Model 'res.currency'>
49    <Model 'res.currency.rate'>
9    <Model 'res.groups'>
1    <Model 'res.lang'>
1    <Model 'res.partner'>
1    <Model 'res.partner.address'>
1    <Model 'res.partner.bank.type'>
1    <Model 'res.partner.bank.type.field'>
5    <Model 'res.partner.title'>
1    <Model 'res.request.link'>
2    <Model 'res.users'>
6    <Model 'res.widget'>
1    <Model 'res.widget.user'>
>>> #
>>> # Show the content of a model

```

(continues on next page)

(continued from previous page)

```
>>> config_params = model('ir.config_parameter').browse([], limit=None)
>>> config_params.read()
[{'id': 1, 'key': 'web.base.url', 'value': 'http://localhost:8069'},
 {'id': 2, 'key': 'database.create_date', 'value': '2012-09-01 09:01:12'},
 {'id': 3,
  'key': 'database.uuid',
  'value': '52fc9630-f49e-2222-e622-08002763afeb'}]
```

3.7 Browse the records

Query the "res.country" model:

```
>>> model('res.country').keys()
['address_format', 'code', 'name']
>>> model('res.country').browse(['name like public'])
<RecordList 'res.country,[41, 42, 57, 62, 116, 144]'>
>>> model('res.country').browse(['name like public']).name
['Central African Republic',
 'Congo, Democratic Republic of the',
 'Czech Republic',
 'Dominican Republic',
 'Kyrgyz Republic (Kyrgyzstan)',
 'Macedonia, the former Yugoslav Republic of']
>>> model('res.country').browse(['code > Y'], order='code ASC').read('code name')
[{'code': 'YE', 'id': 247, 'name': 'Yemen'},
 {'code': 'YT', 'id': 248, 'name': 'Mayotte'},
 {'code': 'YU', 'id': 249, 'name': 'Yugoslavia'},
 {'code': 'ZA', 'id': 250, 'name': 'South Africa'},
 {'code': 'ZM', 'id': 251, 'name': 'Zambia'},
 {'code': 'ZR', 'id': 252, 'name': 'Zaire'},
 {'code': 'ZW', 'id': 253, 'name': 'Zimbabwe'}]
>>> #
```

... the tutorial is done.

Jump to the [ERPeek API](#) for further details.

CHAPTER 4

Developer's notes

4.1 Source code

- Source code and issue tracker on GitHub.
- Continuous tests against Python 2.7 through 3.7 and PyPy, on [Travis-CI](#) platform.

4.2 Third-party integration

This module can be used with other Python libraries to achieve more complex tasks.

For example:

- write unit tests using the standard `unittest` framework.
- write BDD tests using the [Gherkin language](#), and a library like [Behave](#).
- build an interface for Odoo, using a framework like [Flask](#) (HTML, JSON, SOAP, ...).

4.3 Changes

4.3.1 1.7.1 (2018-12-05)

- Add support for the JSON-RPC protocol. It is enabled if the `--server` argument contains the full path to the `/jsonrpc` endpoint. As an alternative, you can specify the `protocol` in the configuration file.
- Change the return value of `Model.browse()` method if search domain is an empty list. It returns an empty `RecordList` except if some other argument is provided (e.g. `all_users = model('res.users').browse([], limit=None)`). Compatibility tip: you can restore the old behavior with `Model._browse_compat = True`.

- Change the return value of `Client.read()` and `Model.read()` methods if search domain is an empty list: it returns `False`.
- Improve error formatting for recent Odoo versions, in interactive mode.
- Refactor the construction of Service proxies.
- Drop compatibility with Python 2.6.

4.3.2 1.7 (2018-11-22)

- Fully support Odoo 10 and Odoo 11.
- New method `Client.clone_database` based on `Client.db.duplicate_database`.
- Optional `login` and `country_code` arguments for `Client.create_database` in Odoo 9+.
- Use the `context` for the search methods.
- Service `Client._report` is removed in Odoo 11. Methods `Client.report`, `Client.report_get` and `Client.render_report` are removed too.
- More robust Python 2 detection logic.

4.3.3 1.6.3 (2015-12-30)

- Do not parse long integers which overflow in XML-RPC.

4.3.4 1.6.2 (2015-09-17)

- Add an optional `t_transport` argument to the `Client` constructor. This is useful for tweaking the SSL context or adding an optional timeout parameter.
- Implement `==` comparison for `RecordList` instances.
- Uninstall dependent add-ons in a single call.
- Do not install/uninstall add-ons if other actions are pending.
- Do not hang when the `Client` constructor receives invalid arguments.
- Fix `str(record)` and `print(record)` with non-ASCII names.

4.3.5 1.6.1 (2014-11-12)

- Support using `--env` and `--user` together to connect with a different user.
- Adapt for Odoo 8.0 after change `cc4fbba6` on October 2014.
- Do not interpret digits with leading 0 as octal in search domain.

4.3.6 1.6 (2014-09-23)

- Compatible with Odoo 8.0.
- New attribute `Client.context` to set the default context for high-level `Model` and `Record` methods.
- Use blocking RPC call in `Client.create_database`. Asynchronous method is removed in Odoo.

- Return the interactive namespace with `main(interact=False)`. It helps to integrate with third-party libraries, such as IPython.
- Remove a duplicate `Logged in as ...` line in interactive mode.
- Remove the `search+name_get` undocumented feature which has wrong behavior when applied to an empty `RecordList`.
- Do not prevent login if access to `Client.db.list()` is denied.

4.3.7 1.6b1 (2014-06-09)

- When a function or a method fails, raise an `erppeek.Error` instead of printing a message and returning `None`.
- Switch to local mode when the command line argument points at the server configuration, like `-c path/to/openerp-server.conf`.
- Local mode compatible with Odoo trunk: support both the old and the new API.
- Use shell-like parsing for `options =` setting in local mode.
- Function `start_openerp_services` is replaced with `start_odoo_services`: it is still compatible with OpenERP 6.1 and 7 and it accepts a list of options in the first argument, similar to `sys.argv[1:]`.
- Search domains require square brackets. Usage without square brackets was deprecated since 0.5, with `UserWarning` alerts.
- Implement addition of `RecordList` of the same model.
- Drop compatibility with Python 2.5.

4.3.8 1.5.3 (2014-05-26)

- Change command line output to CSV format.
- Translate command line output according to `LANG` environment variable.
- Pretty print the list of modules.
- Do not report `Module(s) not found` when trying to install a module already installed.

4.3.9 1.5.2 (2014-04-12)

- Return an appropriate error message when the client is not connected.
- Two similar `Record` from different connections do not compare equal.
- Set the `PGAPPNAME` used for the PostgreSQL connection, in local mode.
- Close PostgreSQL connections on exit, in local mode.
- Implement the context manager protocol.

4.3.10 1.5.1 (2014-03-11)

- When switching to a different environment, with `Client.connect`, invalidate the previous connection to avoid mistakes (interactive mode).

- Avoid cluttering the globals in interactive mode.
- Close socket to avoid `ResourceWarning` on Python 3.
- The `get_pool` helper is only available in interactive mode and if the client is connected locally using the `openerp` package.
- Clear the last exception before entering interactive mode, only needed on Python 2.
- Fix the `searchargs` domain parser for compatibility with Python 3.4.

4.3.11 1.5 (2014-03-10)

- Advertize the `Model` and `Record` paradigm in the `usage` printed in interactive mode: it's far more easier to use, and available since 1.0.
- In interactive mode, only inject four global names: `client`, `models`, `model` and `do`. Other methods are available on `Model` and `Client` instances (read search count keys fields access ...).
- Always clear the `Record` cache when an arbitrary method is called on this `Record`.
- Implement `==` comparison for `Record` instances.
- New computed attributes `Record._external_id` and `RecordList._external_id`, and new method `Model._get_external_ids(ids=None)`.
- Better parsing of dates in search terms.
- Reject invalid `==` operator in search terms.
- Now the `str(...)` of a `Record` is always retrieved with `name_get`. Previously, the output was sometimes inconsistent.
- Fix `TypeError` when browsing duplicate ids.
- Fix error with `Model.get(['field = value'], context={...})`.
- Workaround an issue with some models: always pass a list of ids to `read`.
- Test the behaviour when `read` is called with a `False` id: it happens when browsing a `RecordList` for example.

4.3.12 1.4.5 (2013-03-20)

- Extend `Model.get` to retrieve a record by `xml_id`.
- Fix `AttributeError` when reading a mix of valid and invalid records.
- Fix `dir()` on `Record` and `RecordList` to return all declared fields, and do not report `id` field twice.
- Fix a crash with built-in OS X readline on Python 2.5 or 2.6.

4.3.13 1.4.4 (2013-03-05)

- Remove deprecated `Record.client`.
- Fix compatibility with Python 3.
- Add optional argument `check` to the `Client.model` method to bypass the verification in some cases, used to speed up the read methods.
- Do not crash when mixing non-existing and existing records: return always `False` for non-existing records.

4.3.14 1.4.3 (2013-01-10)

- Compatible with OpenERP 7.
- Set the database name as thread attribute to print it in the log file (local mode only).
- Do not try to access private methods through RPC when resolving attributes of the Client or any Record or RecordList.

4.3.15 1.4.2 (2012-12-19)

- Add the `get_pool` helper when connected using the `openerp` library.
- Remove the leading slash on the `server` option, if present.
- Do not try to access private methods through RPC when reading attributes of the `model` (...).

4.3.16 1.4.1 (2012-10-05)

- Fix reading `many2one` attribute on `RecordList` object in local mode.
- Fix occasional issue on login when switching database on the same server.
- Optimization: do not propagate the call to `RecordList.write` or `RecordList.unlink` if the list is empty.
- Clear the Record cache on `Record._send`.
- Expose the method `Record.refresh` to clear the local cache.

4.3.17 1.4 (2012-10-01)

- New: direct connection to a local server using the `openerp` library. Use `scheme = local` and `options = -c /path/to/openerp-server.conf` in the configuration.

4.3.18 1.3.1 (2012-09-28)

- Fix method `Record._send`.

4.3.19 1.3 (2012-09-27)

- Implement exception chaining in `format_exception` to print the original traceback.
- Return a list of `Record` objects when reading the `reference` field of a `RecordList` object.
- Fix reading attributes on `RecordList` with holes or gaps.
- Accessing an empty `one2many` or `many2many` attribute on a `Record` returns a `RecordList`.
- New method `Model.get` to retrieve a single `Record`. It raises a `ValueError` if multiple records are found.
- New method `Record._send` to send a workflow signal.

4.3.20 1.2.2 (2012-09-24)

- Accept Record and RecordList attribute values when writing or creating records.
- Improve the methods `write` and `create` of Record and RecordList objects to manage one2many and many2many fields.
- Return a Record when reading a reference field. Implement the `create` and `write` methods for these fields.
- Remove undocumented alias `Record.update`.

4.3.21 1.2.1 (2012-09-21)

- Add the special operators `=ilike`, `=ilike`, `=?` and fix parsing of inequality operators `>=` and `<=`.
- Fix the `RecordList.id` attribute, and deprecate `RecordList._ids`.
- Deprecate the `Record.client` attribute: use `Record._model.client`.
- Accessing an empty `many2one` attribute on a RecordList now returns a RecordList.
- Fix `TypeError` when browsing non-existent records.

4.3.22 1.2 (2012-09-19)

- Catch some malformed search domains before sending the RPC request.
- Preserve dictionary response when calling non standard Record methods.
- Expose the helper `format_exception` which formats the errors received through XML-RPC.
- Support XML-RPC through HTTPS with `scheme = https` in the `erppeek.ini` configuration file.
- Print an error message when `client.upgrade(...)` does not find any module to upgrade.

4.3.23 1.1 (2012-09-04)

- When using arbitrary methods on Record, wrap the `id` in a list `[id]`. It fixes a recurring issue with poorly tested methods.
- Do not read all records if the RecordList is empty.
- Fix the bad behaviour when switching to a different database.
- Order the results when using `read` method with `order=` argument.
- Reading attributes of the sequence `<RecordList 'sea.fish,[2, 1, 2]>` will return an ordered sequence of three items. Previously it used to return an unordered sequence of two items.
- Accept the `%(...)%` formatting for the `fields` parameter of the `Record.read` and the `RecordList.read` methods too.
- Add a tutorial to the documentation.

4.3.24 1.0 (2012-08-29)

- Add the test suite for Python 2 and Python 3.
- Implement `len()` for `RecordList` objects.
- Connect to the server even if the database is missing.
- Expose the method `Client.db.get_progress`.
- New method `Client.create_database` which wraps together `Client.db.create` and `Client.db.get_progress`.
- Save the readline history in `~/.erppeek_history`, only if the file already exists.
- Enable auto-completion using `rlcompleter` standard module.
- Raise an `AttributeError` when assigning to a missing or read-only attribute.

4.3.25 0.11 (2012-08-24)

- Enhance the `Model.browse()` method to accept the same keyword arguments as the `Client.search()` method.
- Fix the verbose level on `Client.connect()`.
- Fix the `Record.copy()` method.
- Fix the `Record.perm_read()` method (workaround an OpenERP bug when dealing with single ids).
- Drop the `--search` argument, because the search terms can be passed as positional arguments after the options. Explain it in the description.
- Fix the shell command. Request the password interactively if it's not in the options and not in the configuration file.

4.3.26 0.10 (2012-08-23)

- Add the `--verbose` switch to log the XML-RPC messages. Lines are truncated at 79 chars. Use `-vv` or `-vvv` to truncate at 179 or 9999 chars respectively.
- Removed the `--write` switch because it's not really useful. Use `Record.write()` or `client.write()` for example.
- Stop raising `RuntimeError` when calling `Client.model(name)`. Simply print the message if the name does not match.
- Fix `RecordList.read()` and `Record.read()` methods to accept the same diversity of fields arguments as the `Client.read()` method.
- `RecordList.read()` and `Record.read()` return instances of `RecordList` and `Record` for relational fields.
- Optimize: store the name of the `Record` when a relational field is accessed.
- Fix message wording on module install or upgrade.

4.3.27 0.9.2 (2012-08-22)

- Fix `Record.write()` and `Record.unlink()` methods.
- Fix the caching of the `Model` keys and fields and the `Record` name.

4.3.28 0.9.1 (2012-08-22)

- Fix `client.model()` method. Add `models()` to the `globals()` in interactive mode.

4.3.29 0.9 (2012-08-22)

- Add the Active Record pattern for convenience. New classes `Model`, `RecordList` and `Record`. The `Client.model()` method now returns a single `Model` instance. These models can be reached using camel case attribute too. Example: `client.model('res.company')` and `client.ResCompany` return the same `Model`.
- Refresh the list of modules before install or upgrade.
- List all modules which have state not in ('uninstalled', 'uninstallable') when calling `client.modules(installed=True)`.
- Add documentation.

4.3.30 0.8 (2012-04-24)

- Fix `help(client)` and `repr(...)`.
- Add basic safeguards for argument types.

4.3.31 0.7 (2012-04-04)

- Fix `RuntimeError` on connection.

4.3.32 0.6 (2012-04-03)

- Support Python 3.
- Return `Client` method instead of function when calling `client.write` or similar.
- Fix the case where `read()` is called with a single id.

4.3.33 0.5 (2012-03-29)

- Implement `Client.__getattr__` special attribute to call any object method, like `client.write(obj, values)`. This is somewhat redundant with `client.execute(obj, 'write', values)` and its interactive alias `do(obj, 'write', values)`.
- Add `--write` switch to enable unsafe helpers: `write`, `create`, `copy` and `unlink`.
- Tolerate domain without square brackets, but show a warning.
- Add long options `--search` for `-s`, `--interact` for `-i`.

4.3.34 0.4 (2012-03-28)

- Workaround for `sys.excepthook` ignored, related to a Python issue.

4.3.35 0.3 (2012-03-26)

- Add `--config` and `--version` switches.
- Improve documentation with session examples.
- Move the project from Launchpad to GitHub.

4.3.36 0.2 (2012-03-24)

- Allow to switch user or database: methods `client.login` and `client.connect`.
- Allow `context=` keyword argument.
- Add `access(...)` method.
- Add `%(...)%` s formatting for the `fields` parameter of the `read(...)` method.
- Refactor the interactive mode.
- Many improvements.
- Publish on PyPI.

4.3.37 0.1 (2012-03-14)

- Initial release.
- Online documentation: <http://erppeek.readthedocs.org/>
- Source code and issue tracker: <https://github.com/tinyerp/erppeek>

CHAPTER 5

Indices and tables

- genindex
- search

CHAPTER 6

Credits

Authored and maintained by Florent Xicluna.

Derived from a script by Alan Bell.

Python Module Index

e

erppeek, [7](#)

Symbols

_external_id (erppeek.Record attribute), 14
_external_id (erppeek.RecordList attribute), 13
_get_external_ids() (erppeek.Model method), 13
_report (erppeek.Client attribute), 11
_send() (erppeek.Record method), 14
_wizard (erppeek.Client attribute), 11

A

access() (erppeek.Client method), 10
access() (erppeek.Model method), 12

B

browse() (erppeek.Model method), 12

C

Client (class in erppeek), 7
Client._object (in module erppeek), 11
clone_database() (erppeek.Client method), 8
common (erppeek.Client attribute), 11
context (erppeek.Client attribute), 8
copy() (erppeek.Client method), 9
copy() (erppeek.Record method), 14
count() (erppeek.Client method), 8
create() (erppeek.Client method), 9
create() (erppeek.Model method), 13
create_database() (erppeek.Client method), 8

D

db (erppeek.Client attribute), 11

E

erppeek (module), 7
exec_workflow() (erppeek.Client method), 10
execute() (erppeek.Client method), 10
execute_kw() (erppeek.Client method), 10

F

field() (erppeek.Client method), 10

field() (erppeek.Model method), 12
fields() (erppeek.Client method), 10
fields() (erppeek.Model method), 12
format_exception() (in module erppeek), 15
from_config() (erppeek.Client class method), 7

G

get() (erppeek.Model method), 13

I

install() (erppeek.Client method), 12
issearchdomain() (in module erppeek), 14

K

keys() (erppeek.Client method), 10
keys() (erppeek.Model method), 12

L

login() (erppeek.Client method), 8
lowercase() (in module erppeek), 14

M

mixedcase() (in module erppeek), 14
Model (class in erppeek), 12
model() (erppeek.Client method), 10
models() (erppeek.Client method), 10
modules() (erppeek.Client method), 12

P

perm_read() (erppeek.Client method), 9
perm_read() (erppeek.Record method), 14
perm_read() (erppeek.RecordList method), 13

R

read() (erppeek.Client method), 8
read() (erppeek.Record method), 14
read() (erppeek.RecordList method), 13
read_config() (in module erppeek), 15
Record (class in erppeek), 13

RecordList (class in erppeek), [13](#)
refresh() (erppeek.Record method), [14](#)
render_report() (erppeek.Client method), [10](#)
report() (erppeek.Client method), [10](#)
report_get() (erppeek.Client method), [11](#)

S

search() (erppeek.Client method), [8](#)
searchargs() (in module erppeek), [15](#)
Service (class in erppeek), [11](#)
start_odoo_services() (in module erppeek), [15](#)

U

uninstall() (erppeek.Client method), [12](#)
unlink() (erppeek.Client method), [10](#)
unlink() (erppeek.Record method), [14](#)
unlink() (erppeek.RecordList method), [13](#)
upgrade() (erppeek.Client method), [12](#)

W

wizard() (erppeek.Client method), [11](#)
write() (erppeek.Client method), [9](#)
write() (erppeek.Record method), [14](#)
write() (erppeek.RecordList method), [13](#)