

---

# **RoboticBrain.FlowContextHeader Documentation**

*Release dev-master*

**The author**

March 18, 2016



<b>I</b>	<b>Introduction</b>	<b>3</b>
<b>II</b>	<b>Configuration</b>	<b>7</b>
<b>III</b>	<b>Helpful Snippets</b>	<b>11</b>



---

**Note:** This documentation covering version dev-master has been rendered at: March 18, 2016

---



## **Part I**

# **Introduction**





This package simply adds a HTTP header, which contains the active FlowContext.

---

**Note:** This package is for development purposes only!

---



# **Part II**

# **Configuration**



You can configure the header to be used in your Settings.yaml

```
TYPO3:
  Flow:
    http:
      chain:
        'postprocess':
          chain:
            'RoboticBrain\FlowContextHeader':
              componentOptions:
                'headerName': 'X-ACTUAL_FLOW_CONTEXT' # This is the default value
```



## **Part III**

# **Helpful Snippets**





To enable context selection by the browser, add something like this to the top of your .htaccess file:

```
<IfModule setenvif_module>  
    SetEnvIf X-FLOW_REQUEST_CONTEXT (.*) FLOW_CONTEXT=$1  
</IfModule>
```

**Danger:** This might pose some serious security threats!