# goodreads Documentation

Release 0.1.1

Sefa Kilic

### Contents

1	Dependencies	3
2	Installation	5
3	Getting Started	7
4	Examples         4.1 Books          4.2 Authors          4.3 Users          4.4 Groups          4.5 Events	9 9 10 10 10
5	Contribution	11
6	License	13
	6.1 client 6.2 request 6.3 session 6.4 book 6.5 author 6.6 user 6.7 user_status 6.8 comment 6.9 event 6.10 group 6.11 owned_book	14 14 14 14 14 14 14 14 14
	6.12 review	14

This package provides a Python interface for the Goodreads API. Using it, you can do pretty much anything that Goodreads allows to do with their own data.

Contents 1

2 Contents

## CHAPTER 1

Dependencies

This package depends on the following packages:

- xmltodict
- requests
- rauth

They can be installed using pip.

```
sudo pip install -r requirements.txt
```

If you want to contribute to this package, you will need the nose package as well.

<u> </u>	7
CHAPTER 4	_

Installation

To install, run the following command from the top-level package directory.

sudo python setup.py install

### CHAPTER 3

**Getting Started** 

The first thing is to request an API key from Goodreads here. Once you have it, you can create a client instance to query Goodreads.

```
from goodreads import client
gc = client.GoodreadsClient(<api_key>, <api_secret>)
```

To access some of the methods, you need OAuth for authorization.

```
gc.authenticate(<access_token>, <access_token_secret>)
```

Note that access\_token and access\_token\_secret are different from developer key and secret. For the development step, you can call the same function with no parameters to get authorization. It will open a URL pointing a Goodreads page for OAuth permission. For your application, you can direct the user to that particular URL, ask him/her to authorize your app and save the returning access\_token and access\_token\_secret in your database.

### CHAPTER 4

Examples

This package provides a Python interface for most Goodreads API methods. Here are a few examples demonstrating how to access data on Goodreads.

#### 4.1 Books

Let's access the first book added to Goodreads! It is the book with id 1.

```
book = gc.book(1)
```

Once you have the GoodreadsBook instance for the book, you can access data for the queried book.

```
>>> book.title
u'Harry Potter and the Half-Blood Prince (Harry Potter, #6)'
>>> authors = book.authors
>>> authors[0].name
u'J.K. Rowling'
>>> book.average_rating
u'4.49'
```

#### 4.2 Authors

You can get information about an author as well.

(continued from previous page)

#### 4.3 Users

User data can be retrieved by user id or username.

```
>>> user = gc.user(1)
>>> user.name
u'Otis Chandler'
>>> user.user_name
u'otis'
>>> user.small_image_url
u'http://d.gr-assets.com/users/1189644957p2/1.jpg'
```

### 4.4 Groups

Let's find a group discussing Python and get more information about it.

```
>>> g = gc.find_groups("Python")
>>> g = groups[0]
>>> g['title']
u'The Computer Scientists'
>>> group = gc.group(g['id'])
>>> group.description
u'Only for Committed Self Learners and Computer Scientists Who are Starving for
Information, and Want to Advance their Skills Through: Reading, Practicing and
Discussion Computer Science and Programming Books.'
```

#### 4.5 Events

Goodreads API also allows to list events happening in an area.

```
>>> events = gc.list_events(21229)
>>> event = events[0]
>>> event.title
u'Books and Cocktails'
>>> event.address
u'120 N. Front St.'
>>> event.city
u'Wrightsville'
```

Cŀ	4Δ	рт	-=1	<sub>3</sub> 5
( ) [	-			1 1 1

### Contribution

If you find an API method that is not supported by this package, feel free to create a Github issue. Also, you are more than welcome to submit a pull request for a bug fix or additional feature.

			$\sim$
$\cap$ L	I V D	TER	3 <b>b</b>
$\cup$ $\Gamma$	1AC		1 U

License

MIT License

Contents:

- 6.1 client
- 6.2 request
- 6.3 session
- 6.4 book
- 6.5 author
- 6.6 user
- 6.7 user\_status
- 6.8 comment
- 6.9 event
- 6.10 group
- 6.11 owned\_book
- 6.12 review