
grammarbot-py

Dec 12, 2018

Contents

1 Module contents	1
Python Module Index	3

CHAPTER 1

Module contents

class grammarbot.GrammarBotApiResponse (*json: dict*)
Bases: object

Represents the JSON API returned by the server.

detected_language

Gives the language code for the detected language.

matches

Different matches detected by the GrammarBot API.

raw_json

Returns the raw JSON response that was returned by the server.

result_is_incomplete

States whether these results are complete or incomplete.

class grammarbot.GrammarBotClient (*api_key: str = 'python-default'*)
Bases: object

A GrammarBot-API wrapper client.

check (*text: str, lang: str = 'en-US'*)

Check a given piece of text for grammatical errors.

Parameters

- **text** – Text to be checked using the API.
- **lang** – Language code for the text language.

class grammarbot.GrammarBotMatch (*match_json: dict*)
Bases: object

Represents a GrammarBot match detected by the API.

category

Gives the rule category.

corrections

Gives a list of possibly correct variation of the input text.

message

Returns the message for the given match.

replacement_length

Gives the length of the string that has to be replaced.

replacement_offset

Gives the offset at which the replacement should be made.

replacements

Gives a list of possible replacements.

rule

Gives the rule ID which applies for this match.

type

Gives the type of match.

Python Module Index

g

grammarbot, [1](#)

Index

C

category (grammarbot.GrammarBotMatch attribute), [1](#)
check() (grammarbot.GrammarBotClient method), [1](#)
corrections (grammarbot.GrammarBotMatch attribute), [1](#)

D

detected_language (grammarbot.GrammarBotApiResponse attribute), [1](#)

G
grammarbot (module), [1](#)
GrammarBotApiResponse (class in grammarbot), [1](#)
GrammarBotClient (class in grammarbot), [1](#)
GrammarBotMatch (class in grammarbot), [1](#)

M

matches (grammarbot.GrammarBotApiResponse attribute), [1](#)
message (grammarbot.GrammarBotMatch attribute), [2](#)

R

raw_json (grammarbot.GrammarBotApiResponse attribute), [1](#)
replacement_length (grammarbot.GrammarBotMatch attribute), [2](#)
replacement_offset (grammarbot.GrammarBotMatch attribute), [2](#)
replacements (grammarbot.GrammarBotMatch attribute), [2](#)
result_is_incomplete (grammarbot.GrammarBotApiResponse attribute), [1](#)
rule (grammarbot.GrammarBotMatch attribute), [2](#)

T

type (grammarbot.GrammarBotMatch attribute), [2](#)