
gs.group.member.leave.json **Documentation**

Release 1.0.0

GroupServer.org

April 28, 2016

1	Web hook	3
1.1	Synopsis	3
1.2	Description	3
1.3	Required arguments	3
1.4	Returns	3
1.5	Example	4
2	Changelog	5
2.1	1.0.0 (2015-06-19)	5
3	Indices and tables	7
4	Resources	9

Author [Michael JasonSmith](#)

Contact Michael JasonSmith <mpj17@onlinegroups.net>

Date 2015-06-15

Organization [GroupServer.org](#)

Copyright This document is licensed under a [Creative Commons Attribution-Share Alike 4.0 International License](#) by [OnlineGroups.net](#).

This product provides a web hook that allows a person to be removed from a group by an external system.

Contents:

1.1 Synopsis

`/gs-group-member-leave.json? token =<t> & groupId = <g> & userId =<u> & leave`

1.2 Description

The `gs-group-member-leave.json` page in the **site** context removes a person from the group.

1.3 Required arguments

token

The authentication token ¹.

groupId=<groupId>

The identifier for the group.

userId=<userId>

The identifier for the user.

leave

The “form” action. (No value needs to be set, but the argument must be present)

1.4 Returns

In response a **JSON** object will be returned with the following values:

class LeaveResponse ()

status

The exist status:

- 0: Success, the person has been removed from the group.
- 1: No such group.

¹ See `gs.auth.token` <<https://github.com/groupserver/gs.auth.token/>>

- 2: No such user.
- 4: The user and group exist, but the user is not a member of the group.

message

The plain-text version of the *status*.

groupId

The identifier for the group that the person was removed from.

userId:

The identifier of user-profile of the person that was removed from the group.

1.5 Example

Using **wget** to remove the person with the user-identifier `qK7SgjsTHcLnrJ2ClevcJ0` from the group `test`.

```
$ wget --post-data='token=Fake&groupId=test&userId=qK7SgjsTHcLnrJ2ClevcJ0&leave' \
http://groups.example.com/gs-group-member-leave.json
```

The response will look similar to the following:

```
{
  "status": 0,
  "message": "A Person has left Test",
  "groupId": "test",
  "userId": "qK7SgjsTHcLnrJ2ClevcJ0"
}
```

Changelog

2.1 1.0.0 (2015-06-19)

Initial version. Prior to the creation of this product there was no way to add a person to a group using JSON.

Indices and tables

- `genindex`
- `modindex`
- `search`

Resources

- Documentation: <http://groupserver.readthedocs.io/projects/gsgroupmemberleavejson>
- Code repository: <https://github.com/groupserver/gs.group.member.leave.json/>
- Questions and comments to <http://groupserver.org/groups/development>
- Report bugs at <https://redmine.iopen.net/projects/groupserver>

C

command line option

 groupId=<groupId>, 3

 leave, 3

 token, 3

 userId=<userId>, 3

G

groupId (None attribute), 4

groupId=<groupId>

 command line option, 3

L

leave

 command line option, 3

LeaveResponse() (class), 3

M

message (None attribute), 4

S

status (None attribute), 3

T

token

 command line option, 3

U

userId: (None attribute), 4

userId=<userId>

 command line option, 3