
influxdb*client*

Release 0.0.1

Sep 26, 2019

Contents:

1	User Guide	1
1.1	Query	1
1.2	Write	2
1.2.1	Batching	2
1.2.2	Asynchronous client	3
1.2.3	Synchronous client	3
1.2.4	How to efficiently import large dataset	4
1.3	Gzip support	5
1.4	Debugging	6
2	API Reference	7
2.1	InfluxDBClient	7
2.2	QueryApi	8
2.3	WriteApi	9
2.4	BucketsApi	10
2.5	LabelsApi	12
2.6	OrganizationsApi	13
2.7	UsersApi	14
2.8	TasksApi	15
3	InfluxDB 2.0 client features	19
4	Installation	21
4.1	pip install	21
4.2	SetupTools	21
5	Getting Started	23
6	Indices and tables	25
Index		27

CHAPTER 1

User Guide

- *Query*
- *Write*
 - *Batching*
 - *Asynchronous client*
 - *Synchronous client*
 - *How to efficiently import large dataset*
- *Gzip support*
- *Debugging*

1.1 Query

```
from influxdb_client import InfluxDBClient, Point
from influxdb_client.client.write_api import SYNCHRONOUS

bucket = "my-bucket"

client = InfluxDBClient(url="http://localhost:9999", token="my-token", org="my-org")

write_api = client.write_api(write_options=SYNCHRONOUS)
query_api = client.query_api()

p = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)

write_api.write(bucket=bucket, org="my-org", record=p)
```

(continues on next page)

(continued from previous page)

```

## using Table structure
tables = query_api.query('from(bucket:"my-bucket") |> range(start: -10m)')

for table in tables:
    print(table)
    for row in table.records:
        print (row.values)

## using csv library
csv_result = query_api.query_csv('from(bucket:"my-bucket") |> range(start: -10m)')
val_count = 0
for row in csv_result:
    for cell in row:
        val_count += 1

```

1.2 Write

The WriteApi supports synchronous, asynchronous and batching writes into InfluxDB 2.0. The data should be passed as a [InfluxDB Line Protocol](#), [Data Point](#) or Observable stream.

The default instance of “WriteApi“ use batching.

1.2.1 Batching

The batching is configurable by `write_options`:

Prop- erty	Description	Default Value
<code>batch_size</code>	the number of data pointx to collect in a batch	1000
<code>flush_interval</code>	the number of milliseconds before the batch is written	1000
<code>jitter_interval</code>	the number of milliseconds to increase the batch flush interval by a random amount	0
<code>retry_interval</code>	the number of milliseconds to retry unsuccessful write. The retry interval is used when the InfluxDB server does not specify “Retry-After” header.	1000

```

import rx
from rx import operators as ops

from influxdb_client import InfluxDBClient, Point, WriteOptions
from influxdb_client.client.write_api import SYNCHRONOUS

_client = InfluxDBClient(url="http://localhost:9999", token="my-token", org="my-org")
_write_client = _client.write_api(write_options=WriteOptions(batch_size=500,
                                                               flush_interval=10_000,
                                                               jitter_interval=2_000,
                                                               retry_interval=5_000))

"""
Write Line Protocol
"""

```

(continues on next page)

(continued from previous page)

```

_write_client.write("my-bucket", "my-org", "h2o_feet,location=coyote_creek water_
˓→level=1.0 1")
_write_client.write("my-bucket", "my-org", ["h2o_feet,location=coyote_creek water_
˓→level=2.0 2",
                                         "h2o_feet,location=coyote_creek water_
˓→level=3.0 3"])

"""
Write Data Point
"""

_write_client.write("my-bucket", "my-org", Point("h2o_feet").tag("location", "coyote_
˓→creek").field("water_level", 4.0).time(4))
_write_client.write("my-bucket", "my-org", [Point("h2o_feet").tag("location", "coyote_
˓→creek").field("water_level", 5.0).time(5),
                                         Point("h2o_feet").tag("location", "coyote_
˓→creek").field("water_level", 6.0).time(6)])

"""
Write Observable stream
"""

_data = rx \
    .range(7, 11) \
    .pipe(ops.map(lambda i: "h2o_feet,location=coyote_creek water_level={0}.0 {0}".
˓→format(i)))

_write_client.write("my-bucket", "my-org", _data)

"""

Close client
"""

_write_client.__del__()
client.__del__()

```

1.2.2 Asynchronous client

Data are writes in an asynchronous HTTP request.

```

from influxdb_client import InfluxDBClient
from influxdb_client.client.write_api import ASYNCHRONOUS

client = InfluxDBClient(url="http://localhost:9999", token="my-token", org="my-org")
write_client = client.write_api(write_options=ASYNCHRONOUS)

...
client.__del__()

```

1.2.3 Synchronous client

Data are writes in a synchronous HTTP request.

```
from influxdb_client import InfluxDBClient
from influxdb_client.client.write_api import SYNCHRONOUS

client = InfluxDBClient(url="http://localhost:9999", token="my-token", org="my-org")
write_client = client.write_api(write_options=SYNCHRONOUS)

...
client.__del__()
```

1.2.4 How to efficiently import large dataset

- sources - import_data_set.py

```
"""
Import VIX - CBOE Volatility Index - from "vix-daily.csv" file into InfluxDB 2.0

https://datahub.io/core/finance-vix#data
"""

from collections import OrderedDict
from csv import DictReader
from datetime import datetime

import rx
from rx import operators as ops

from influxdb_client import InfluxDBClient, Point, WriteOptions

def parse_row(row: OrderedDict):
    """Parse row of CSV file into Point with structure:

        financial-analysis,type=ily close=18.47,high=19.82,low=18.28,open=19.82
        ↵11981952000000000000

    CSV format:
        Date,VIX Open,VIX High,VIX Low,VIX Close\n
        2004-01-02,17.96,18.68,17.54,18.22\n
        2004-01-05,18.45,18.49,17.44,17.49\n
        2004-01-06,17.66,17.67,16.19,16.73\n
        2004-01-07,16.72,16.75,15.5,15.5\n
        2004-01-08,15.42,15.68,15.32,15.61\n
        2004-01-09,16.15,16.88,15.57,16.75\n
        ...

    :param row: the row of CSV file
    :return: Parsed csv row to [Point]
    """
    return Point("financial-analysis") \
        .tag("type", "vix-daily") \
        .field("open", float(row['VIX Open'])) \
        .field("high", float(row['VIX High'])) \
        .field("low", float(row['VIX Low'])) \
        .field("close", float(row['VIX Close'])) \
        .time(datetime.strptime(row['Date'], '%Y-%m-%d'))
```

(continues on next page)

(continued from previous page)

```

"""
Converts vix-daily.csv into sequence of data points
"""
data = rx \
    .from_iterable(DictReader(open('vix-daily.csv', 'r'))) \
    .pipe(ops.map(lambda row: parse_row(row)))

client = InfluxDBClient(url="http://localhost:9999", token="my-token", org="my-org", _debug=True)

"""
Create client that writes data in batches with 500 items.
"""
write_api = client.write_api(write_options=WriteOptions(batch_size=500, jitter_interval=1_000))

"""
Write data into InfluxDB
"""
write_api.write(org="my-org", bucket="my-bucket", record=data)
write_api.__del__()

"""
Querying max value of CBOE Volatility Index
"""
query = 'from(bucket:"my-bucket")' \
    '|> range(start: 0, stop: now())' \
    '|> filter(fn: (r) => r.measurement == "financial-analysis")' \
    '|> max()
result = client.query_api().query(org="my-org", query=query)

"""
Processing results
"""
print()
print("== results ==")
print()
for table in result:
    for record in table.records:
        print('max {0:5} = {1}'.format(record.get_field(), record.get_value()))

"""
Close client
"""
client.__del__()

```

1.3 Gzip support

InfluxDBClient does not enable gzip compression for http requests by default. If you want to enable gzip to reduce transfer data's size, you can call:

```
from influxdb_client import InfluxDBClient
```

(continues on next page)

(continued from previous page)

```
_db_client = InfluxDBClient(url="http://localhost:9999", token="my-token", org="my-org"
    ↪, enable_gzip=True)
```

1.4 Debugging

For debug purpose you can enable verbose logging of http requests. Both request header and body will be logged to standard output.

```
_client = InfluxDBClient(url="http://localhost:9999", token="my-token", debug=True,
    ↪org="my-org")
```

CHAPTER 2

API Reference

- *InfluxDBClient*
- *QueryApi*
- *WriteApi*
- *BucketsApi*
- *LabelsApi*
- *OrganizationsApi*
- *UsersApi*
- *TasksApi*

2.1 InfluxDBClient

```
class influxdb_client.InfluxDBClient(url, token, debug=None, timeout=10000, enable_gzip=False, org: str = None)
```

`influxdb_client.InfluxDBClient` is client for HTTP API defined in <https://github.com/influxdata/influxdb/blob/master/http/swagger.yml>.

Parameters

- **url** – InfluxDB server API url (ex. `http://localhost:9999`).
- **token** – auth token
- **debug** – enable verbose logging of http requests
- **timeout** – default http client timeout
- **enable_gzip** – Enable Gzip compression for http requests. Currently only the “Write” and “Query” endpoints supports the Gzip compression.

- **org** – organization name (used as a default in query and write API)

authorizations_api() → influxdb_client.client.authorizations_api.AuthorizationsApi
Creates the Authorizations API instance.

Returns authorizations api

buckets_api() → influxdb_client.client.bucket_api.BucketsApi
Creates the Bucket API instance.

Returns buckets api

close()
Shutdowns the client

health() → influxdb_client.domain.health_check.HealthCheck
Get the health of an instance.

Returns HealthCheck

labels_api() → influxdb_client.client.labels_api.LabelsApi
Creates the Labels API instance.

Returns labels api

organizations_api() → influxdb_client.client.organizations_api.OrganizationsApi
Creates the Organizations API instance.

Returns organizations api

query_api() → influxdb_client.client.query_api.QueryApi
Creates a Query API instance

Returns Query api instance

ready() → influxdb_client.domain.ready.Ready
Gets The readiness of the InfluxDB 2.0.

Returns Ready

tasks_api() → influxdb_client.client.tasks_api.TasksApi
Creates the Tasks API instance.

Returns tasks api

users_api() → influxdb_client.client.users_api.UsersApi
Creates the Users API instance.

Returns users api

write_api (*write_options*=<influxdb_client.client.write_api.WriteOptions object>) → in-fluxdb_client.client.write_api.WriteApi
Creates a Write API instance

Parameters **write_options** – write api configuration

Returns write api instance

2.2 QueryApi

class influxdb_client.QueryApi(*influxdb_client*)
Initializes query client.

Parameters **influxdb_client** – influxdb client

```
query(query: str, org=None, dialect={'annotations': ['datatype', 'group', 'default'], 'comment_prefix': '#', 'date_time_format': 'RFC3339', 'delimiter': ',', 'header': True}) → List[influxdb_client.client.flux_table.FluxTable]
```

Synchronously executes the Flux query and return result as a List['FluxTable']

Parameters

- **query** – the Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)
- **dialect** – csv dialect format

Returns

```
query_csv(query: str, org=None, dialect: influxdb_client.domain.dialect.Dialect = {'annotations': ['datatype', 'group', 'default'], 'comment_prefix': '#', 'date_time_format': 'RFC3339', 'delimiter': ',', 'header': True})
```

Executes the Flux query and return results as a CSV iterator. Each iteration returns a row of the CSV file.

Parameters

- **query** – a Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)
- **dialect** – csv dialect format

Returns The returned object is an iterator. Each iteration returns a row of the CSV file (which can span multiple input lines).

```
query_raw(query: str, org=None, dialect={'annotations': ['datatype', 'group', 'default'], 'comment_prefix': '#', 'date_time_format': 'RFC3339', 'delimiter': ',', 'header': True})
```

Synchronously executes the Flux query and return result as raw unprocessed result as a str

Parameters

- **query** – a Flux query
- **org** – organization name (optional if already specified in InfluxDBClient)
- **dialect** – csv dialect format

Returns str

2.3 WriteApi

```
class influxdb_client.WriteApi(influxdb_client, write_options: influxdb_client.client.write_api.WriteOptions = <influxdb_client.client.write_api.WriteOptions object>)

write(bucket: str, org: str, record: Union[str, List[str], influxdb_client.client.write.point.Point, List[Point], rx.core.observable.observable.Observable], write_precision: influxdb_client.domain.write_precision.WritePrecision = 'ns') → None
```

Writes time-series data into influxdb.

Parameters

- **org** (*str*) – specifies the destination organization for writes; take either the ID or Name interchangeably; if both orgID and org are specified, org takes precedence. (required)
- **bucket** (*str*) – specifies the destination bucket for writes (required)

- **write_precision** (*WritePrecision*) – specifies the precision for the unix timestamps within the body line-protocol
- **record** – Points, line protocol, RxPY Observable to write

2.4 BucketsApi

```
class influxdb_client.BucketsApi(influxdb_client)
```

```
create_bucket(bucket=None, bucket_name=None, org_id=None, retention_rules=None, description=None) → influxdb_client.domain.bucket.Bucket
```

Create a bucket # noqa: E501

Parameters

- **bucket** (`Bucket`) – bucket to create (required)
- **bucket_name** – bucket name
- **description** – bucket description
- **org_id** – org_id
- **bucket_name** – bucket name
- **retention_rules** – retention rules array or single BucketRetentionRules

Returns Bucket If the method is called asynchronously, returns the request thread.

```
delete_bucket(bucket)
```

Delete a bucket # noqa: E501

Parameters **bucket** – bucket id or Bucket

Returns Bucket If the method is called asynchronously, returns the request thread.

```
find_bucket_by_id(id)
```

Find bucket by ID

Parameters **id** –

Returns

```
find_bucket_by_name(bucket_name)
```

Find bucket by name

Parameters **bucket_name** – bucket name

Returns Bucket

```
find_buckets()
```

Gets all buckets

```
class influxdb_client.domain.Bucket(links=None, id=None, name=None, description=None, org_id=None, rp=None, created_at=None, updated_at=None, retention_rules=None, labels=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Bucket - a model defined in OpenAPI

```
created_at
```

Gets the created_at of this Bucket. # noqa: E501

Returns The created_at of this Bucket. # noqa: E501

Return type datetime

description

Gets the description of this Bucket. # noqa: E501

Returns The description of this Bucket. # noqa: E501

Return type str

id

Gets the id of this Bucket. # noqa: E501

Returns The id of this Bucket. # noqa: E501

Return type str

labels

Gets the labels of this Bucket. # noqa: E501

Returns The labels of this Bucket. # noqa: E501

Return type list[Label]

links

Gets the links of this Bucket. # noqa: E501

Returns The links of this Bucket. # noqa: E501

Return type BucketLinks

name

Gets the name of this Bucket. # noqa: E501

Returns The name of this Bucket. # noqa: E501

Return type str

org_id

Gets the org_id of this Bucket. # noqa: E501

Returns The org_id of this Bucket. # noqa: E501

Return type str

retention_rules

Gets the retention_rules of this Bucket. # noqa: E501

rules to expire or retain data. No rules means data never expires. # noqa: E501

Returns The retention_rules of this Bucket. # noqa: E501

Return type list[BucketRetentionRules]

rp

Gets the rp of this Bucket. # noqa: E501

Returns The rp of this Bucket. # noqa: E501

Return type str

to_dict()

Returns the model properties as a dict

to_str()

Returns the string representation of the model

updated_at

Gets the updated_at of this Bucket. # noqa: E501

Returns The updated_at of this Bucket. # noqa: E501

Return type datetime

2.5 LabelsApi

class influxdb_client.LabelsApi (influxdb_client)

The client of the InfluxDB 2.0 that implements Labels HTTP API endpoint.

clone_label (cloned_name: str, label: influxdb_client.domain.label.Label) → influxdb_client.domain.label.Label

Creates the new instance of the label as a copy existing label.

Parameters

- **cloned_name** – new label name
- **label** – existing label

Returns clonned Label

create_label (name: str, org_id: str, properties: Dict[str, str] = None) → influxdb_client.domain.label.Label

Creates a new label.

Parameters

- **name** – label name
- **org_id** – organization id
- **properties** – optional label properties

Returns created label

delete_label (label: Union[str, influxdb_client.domain.label.Label])

Deletes the label.

Parameters **label** – label id or Label

find_label_by_id (label_id: str)

Retrieves the label by id.

Parameters **label_id** –

Returns Label

find_label_by_org (org_id) → List[influxdb_client.domain.label.Label]

Gets the list of all labels for given organization.

Parameters **org_id** – organization id

Returns list of labels

find_labels () → List[influxdb_client.domain.label.Label]

Gets all available labels.

Returns labels

update_label (label: influxdb_client.domain.label.Label)

Updates an existing label name and properties.

Parameters `label` – label

Returns the updated label

2.6 OrganizationsApi

class `influxdb_client.OrganizationsApi(influxdb_client)`

The client of the InfluxDB 2.0 that implements Organizations HTTP API endpoint.

class `influxdb_client.domain.Organization(links=None, id=None, name=None, description=None, created_at=None, updated_at=None, status='active')`

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Organization - a model defined in OpenAPI

created_at

Gets the created_at of this Organization. # noqa: E501

Returns The created_at of this Organization. # noqa: E501

Return type `datetime`

description

Gets the description of this Organization. # noqa: E501

Returns The description of this Organization. # noqa: E501

Return type `str`

id

Gets the id of this Organization. # noqa: E501

Returns The id of this Organization. # noqa: E501

Return type `str`

links

Gets the links of this Organization. # noqa: E501

Returns The links of this Organization. # noqa: E501

Return type `OrganizationLinks`

name

Gets the name of this Organization. # noqa: E501

Returns The name of this Organization. # noqa: E501

Return type `str`

status

Gets the status of this Organization. # noqa: E501

if inactive the organization is inactive. # noqa: E501

Returns The status of this Organization. # noqa: E501

Return type `str`

to_dict()

Returns the model properties as a dict

to_str()
Returns the string representation of the model

updated_at
Gets the updated_at of this Organization. # noqa: E501
Returns The updated_at of this Organization. # noqa: E501
Return type datetime

2.7 UsersApi

```
class influxdb_client.UsersApi(influxdb_client)

class influxdb_client.domain.User(id=None, oauth_id=None, name=None, status='active',
                                 links=None)
NOTE: This class is auto generated by OpenAPI Generator. Ref: https://openapi-generator.tech
Do not edit the class manually.

User - a model defined in OpenAPI

id
    Gets the id of this User. # noqa: E501
    Returns The id of this User. # noqa: E501
    Return type str

links
    Gets the links of this User. # noqa: E501
    Returns The links of this User. # noqa: E501
    Return type UserLinks

name
    Gets the name of this User. # noqa: E501
    Returns The name of this User. # noqa: E501
    Return type str

oauth_id
    Gets the oauth_id of this User. # noqa: E501
    Returns The oauth_id of this User. # noqa: E501
    Return type str

status
    Gets the status of this User. # noqa: E501
    if inactive the user is inactive. # noqa: E501
    Returns The status of this User. # noqa: E501
    Return type str

to_dict()
    Returns the model properties as a dict

to_str()
    Returns the string representation of the model
```

2.8 TasksApi

```
class influxdb_client.TasksApi(influxdb_client)
```

cancel_run(task_id: str, run_id: str)

Cancels a currently running run. :param task_id: :param run_id:

find_tasks(**kwargs)

List tasks.

Parameters

- **name** (*str*) – only returns tasks with the specified name
- **after** (*str*) – returns tasks after specified ID
- **user** (*str*) – filter tasks to a specific user ID
- **org** (*str*) – filter tasks to a specific organization name
- **org_id** (*str*) – filter tasks to a specific organization ID
- **limit** (*int*) – the number of tasks to return

Returns Tasks

get_logs(task_id: str) → List[influxdb_client.domain.log_event.LogEvent]

Retrieve all logs for a task. :param task_id: task id

get_run(task_id: str, run_id: str) → influxdb_client.domain.run.Run

Get run record for specific task and run id :param task_id: task id :param run_id: run id :return: Run for specified task and run id

get_runs(task_id, **kwargs) → List[influxdb_client.domain.run.Run]

Retrieve list of run records for a task

Parameters

- **task_id** – task id
- **after** (*str*) – returns runs after specified ID
- **limit** (*int*) – the number of runs to return
- **after_time** (*datetime*) – filter runs to those scheduled after this time, RFC3339
- **before_time** (*datetime*) – filter runs to those scheduled before this time, RFC3339

retry_run(task_id: str, run_id: str)

Retry a task run. :param task_id: task id :param run_id: run id

run_manually(task_id: str, scheduled_for: <module 'datetime' from

'/home/docs/.pyenv/versions/3.6.8/lib/python3.6/datetime.py'> = None)

Manually start a run of the task now overriding the current schedule.

Parameters

- **task_id** –
- **scheduled_for** – planned execution

```
class influxdb_client.domain.Task(id=None, type=None, org_id=None, org=None,
                                  name=None, description=None, status=None, la-
                                  bels=None, authorization_id=None, flux=None,
                                  every=None, cron=None, offset=None, lat-
                                  est_completed=None, created_at=None, updated_at=None,
                                  links=None)
```

NOTE: This class is auto generated by OpenAPI Generator. Ref: <https://openapi-generator.tech>

Do not edit the class manually.

Task - a model defined in OpenAPI

authorization_id

Gets the authorization_id of this Task. # noqa: E501

The ID of the authorization used when this task communicates with the query engine. # noqa: E501

Returns The authorization_id of this Task. # noqa: E501

Return type str

created_at

Gets the created_at of this Task. # noqa: E501

Returns The created_at of this Task. # noqa: E501

Return type datetime

cron

Gets the cron of this Task. # noqa: E501

A task repetition schedule in the form ‘* * * * *’; parsed from Flux. # noqa: E501

Returns The cron of this Task. # noqa: E501

Return type str

description

Gets the description of this Task. # noqa: E501

An optional description of the task. # noqa: E501

Returns The description of this Task. # noqa: E501

Return type str

every

Gets the every of this Task. # noqa: E501

A simple task repetition schedule; parsed from Flux. # noqa: E501

Returns The every of this Task. # noqa: E501

Return type str

flux

Gets the flux of this Task. # noqa: E501

The Flux script to run for this task. # noqa: E501

Returns The flux of this Task. # noqa: E501

Return type str

id

Gets the id of this Task. # noqa: E501

Returns The id of this Task. # noqa: E501

Return type str**labels**

Gets the labels of this Task. # noqa: E501

Returns The labels of this Task. # noqa: E501

Return type list[Label]

latest_completed

Gets the latest_completed of this Task. # noqa: E501

Timestamp of latest scheduled, completed run, RFC3339. # noqa: E501

Returns The latest_completed of this Task. # noqa: E501

Return type datetime

links

Gets the links of this Task. # noqa: E501

Returns The links of this Task. # noqa: E501

Return type TaskLinks

name

Gets the name of this Task. # noqa: E501

The name of the task. # noqa: E501

Returns The name of this Task. # noqa: E501

Return type str

offset

Gets the offset of this Task. # noqa: E501

Duration to delay after the schedule, before executing the task; parsed from flux, if set to zero it will remove this option and use 0 as the default. # noqa: E501

Returns The offset of this Task. # noqa: E501

Return type str

org

Gets the org of this Task. # noqa: E501

The name of the organization that owns this Task. # noqa: E501

Returns The org of this Task. # noqa: E501

Return type str

org_id

Gets the org_id of this Task. # noqa: E501

The ID of the organization that owns this Task. # noqa: E501

Returns The org_id of this Task. # noqa: E501

Return type str

status

Gets the status of this Task. # noqa: E501

Returns The status of this Task. # noqa: E501

Return type TaskStatusType

to_dict()

Returns the model properties as a dict

to_str()

Returns the string representation of the model

type

Gets the type of this Task. # noqa: E501

The type of task, this can be used for filtering tasks on list actions. # noqa: E501

Returns The type of this Task. # noqa: E501

Return type str

updated_at

Gets the updated_at of this Task. # noqa: E501

Returns The updated_at of this Task. # noqa: E501

Return type datetime

InfluxDB 2.0 python client library. The library covers InfluxDB 2.0

CHAPTER 3

InfluxDB 2.0 client features

- **Querying data**

- using the Flux language
 - into csv, raw data, `flux_table` structure

- **Writing data using**

- Line Protocol
 - Data Point
 - RxPY Observable
 - Not implemented yet - write user types using decorator - write Pandas DataFrame

- **InfluxDB 2.0 API client for management**

- the client is generated from the `swagger` by using the `openapi-generator`
 - organizations & users management
 - buckets management
 - tasks management
 - authorizations
 - health check

CHAPTER 4

Installation

InfluxDB python library uses RxPY - The Reactive Extensions for Python (RxPY).

Python 3.6 or later is required.

4.1 pip install

The python package is hosted on Github, you can install latest version directly:

```
pip3 install git+https://github.com/influxdata/influxdb-client-python.git
```

Then import the package:

```
import influxdb_client
```

4.2 Setuptools

Install via Setuptools.

```
python setup.py install --user
```

(or sudo python setup.py install to install the package for all users)

CHAPTER 5

Getting Started

Please follow the [Installation](#) and then run the following:

```
from influxdb_client import InfluxDBClient, Point
from influxdb_client.client.write_api import SYNCHRONOUS

bucket = "my-bucket"

client = InfluxDBClient(url="http://localhost:9999", token="my-token", org="my-org")

write_api = client.write_api(write_options=SYNCHRONOUS)
query_api = client.query_api()

p = Point("my_measurement").tag("location", "Prague").field("temperature", 25.3)

write_api.write(bucket=bucket, org="my-org", record=p)

## using Table structure
tables = query_api.query('from(bucket:"my-bucket") |> range(start: -10m)')

for table in tables:
    print(table)
    for row in table.records:
        print (row.values)

## using csv library
csv_result = query_api.query_csv('from(bucket:"my-bucket") |> range(start: -10m)')
val_count = 0
for row in csv_result:
    for cell in row:
        val_count += 1
```


CHAPTER 6

Indices and tables

- genindex
- modindex
- search

Index

A

authorization_id (*influxdb_client.domain.Task attribute*), 16
authorizations_api () (*influxdb_client.InfluxDBClient method*), 8

B

Bucket (*class in influxdb_client.domain*), 10
buckets_api () (*influxdb_client.InfluxDBClient method*), 8
BucketsApi (*class in influxdb_client*), 10

C

cancel_run () (*influxdb_client.TasksApi method*), 15
clone_label () (*influxdb_client.LabelsApi method*), 12
close () (*influxdb_client.InfluxDBClient method*), 8
create_bucket () (*influxdb_client.BucketsApi method*), 10
create_label () (*influxdb_client.LabelsApi method*), 12
created_at (*influxdb_client.domain.Bucket attribute*), 10
created_at (*influxdb_client.domain.Organization attribute*), 13
created_at (*influxdb_client.domain.Task attribute*), 16
cron (*influxdb_client.domain.Task attribute*), 16

D

delete_bucket () (*influxdb_client.BucketsApi method*), 10
delete_label () (*influxdb_client.LabelsApi method*), 12
description (*influxdb_client.domain.Bucket attribute*), 11
description (*influxdb_client.domain.Organization attribute*), 13

description (*influxdb_client.domain.Task attribute*), 16

E

every (*influxdb_client.domain.Task attribute*), 16

F

find_bucket_by_id () (*influxdb_client.BucketsApi method*), 10
find_bucket_by_name () (*influxdb_client.BucketsApi method*), 10
find_buckets () (*influxdb_client.BucketsApi method*), 10
find_label_by_id () (*influxdb_client.LabelsApi method*), 12
find_label_by_org () (*influxdb_client.LabelsApi method*), 12
find_labels () (*influxdb_client.LabelsApi method*), 12
find_tasks () (*influxdb_client.TasksApi method*), 15
flux (*influxdb_client.domain.Task attribute*), 16

G

get_logs () (*influxdb_client.TasksApi method*), 15
get_run () (*influxdb_client.TasksApi method*), 15
get_runs () (*influxdb_client.TasksApi method*), 15

H

health () (*influxdb_client.InfluxDBClient method*), 8

I

id (*influxdb_client.domain.Bucket attribute*), 11
id (*influxdb_client.domain.Organization attribute*), 13
id (*influxdb_client.domain.Task attribute*), 16
id (*influxdb_client.domain.User attribute*), 14
InfluxDBClient (*class in influxdb_client*), 7

L

labels (*influxdb_client.domain.Bucket attribute*), 11

labels (*influxdb_client.domain.Task* attribute), 17
labels_api () (*influxdb_client.InfluxDBClient* method), 8
LabelsApi (*class* in *influxdb_client*), 12
latest_completed (*influxdb_client.domain.Task* attribute), 17
links (*influxdb_client.domain.Bucket* attribute), 11
links (*influxdb_client.domain.Organization* attribute), 13
links (*influxdb_client.domain.Task* attribute), 17
links (*influxdb_client.domain.User* attribute), 14

N

name (*influxdb_client.domain.Bucket* attribute), 11
name (*influxdb_client.domain.Organization* attribute), 13
name (*influxdb_client.domain.Task* attribute), 17
name (*influxdb_client.domain.User* attribute), 14

O

oauth_id (*influxdb_client.domain.User* attribute), 14
offset (*influxdb_client.domain.Task* attribute), 17
org (*influxdb_client.domain.Task* attribute), 17
org_id (*influxdb_client.domain.Bucket* attribute), 11
org_id (*influxdb_client.domain.Task* attribute), 17
Organization (*class* in *influxdb_client.domain*), 13
organizations_api () (*influxdb_client.InfluxDBClient* method), 8
OrganizationsApi (*class* in *influxdb_client*), 13

Q

query () (*influxdb_client.QueryApi* method), 8
query_api () (*influxdb_client.InfluxDBClient* method), 8
query_csv () (*influxdb_client.QueryApi* method), 9
query_raw () (*influxdb_client.QueryApi* method), 9
QueryApi (*class* in *influxdb_client*), 8

R

ready () (*influxdb_client.InfluxDBClient* method), 8
retention_rules (*influxdb_client.domain.Bucket* attribute), 11
retry_run () (*influxdb_client.TasksApi* method), 15
rp (*influxdb_client.domain.Bucket* attribute), 11
run_manually () (*influxdb_client.TasksApi* method), 15

S

status (*influxdb_client.domain.Organization* attribute), 13
status (*influxdb_client.domain.Task* attribute), 17
status (*influxdb_client.domain.User* attribute), 14

T

Task (*class* in *influxdb_client.domain*), 15
tasks_api () (*influxdb_client.InfluxDBClient* method), 8
TasksApi (*class* in *influxdb_client*), 15
to_dict () (*influxdb_client.domain.Bucket* method), 11
to_dict () (*influxdb_client.domain.Organization* method), 13
to_dict () (*influxdb_client.domain.Task* method), 17
to_dict () (*influxdb_client.domain.User* method), 14
to_str () (*influxdb_client.domain.Bucket* method), 11
to_str () (*influxdb_client.domain.Organization* method), 13
to_str () (*influxdb_client.domain.Task* method), 18
to_str () (*influxdb_client.domain.User* method), 14
type (*influxdb_client.domain.Task* attribute), 18

U

update_label () (*influxdb_client.LabelsApi* method), 12
updated_at (*influxdb_client.domain.Bucket* attribute), 11
updated_at (*influxdb_client.domain.Organization* attribute), 14
updated_at (*influxdb_client.domain.Task* attribute), 18
User (*class* in *influxdb_client.domain*), 14
users_api () (*influxdb_client.InfluxDBClient* method), 8
UsersApi (*class* in *influxdb_client*), 14

W

write () (*influxdb_client.WriteApi* method), 9
write_api () (*influxdb_client.InfluxDBClient* method), 8
WriteApi (*class* in *influxdb_client*), 9