
libslack Documentation

Release 0.2.0

Nicola Coretti

February 24, 2017

1	libslack	1
1.1	Status	1
1.2	Tickets	1
1.3	Overview	1
1.4	Links	1
1.5	Requirements	1
1.6	Dependencies	1
1.7	Installation	1
1.7.1	From PyPi	1
1.7.2	From Github	2
1.7.3	From Source	2
2	Tools	3
2.1	Slack CMD (scmd)	3
2.1.1	Usage	3
2.1.2	Example	3
2.2	Slack Shell (sls)	3
2.2.1	Usage	4
2.2.2	Screenshot	4
3	API-Reference	5
4	License	7
5	Indices and tables	9
	Python Module Index	11

Status

Tickets

Overview

libslack is a lightweight python wrapper around the [Slack-Web-API](#). As part of libslack a small tool called scmd.py which provides a command line interface for the slack api.

Links

- [Project on Github](#)
- [Documentation](#)

Requirements

- Python 3.4 and newer

Dependencies

- [docopt](#)

Installation

From PyPi

```
pip install libslack
```

From Github

```
pip install git+https://github.com/Nicoretti/libslack.git
```

From Source

```
python3 setup.py install
```

Tools

Slack CMD (scmd)

The Slack CMD enables its user to use the slack web api via the command line.

Usage

```
Usage:
scmd (API_COMMAND | -h | -v ) [<params>] [--auth-token=<token>]

Options:
  -h                Show this screen.
  -v                Show version.
  --auth-token=<token> The authentication token which will be used to access
                    the slack api.
                    As an alternative you can specify it in the .slackrc
                    or set the $SLACK_API_TOKEN environment variable.
```

Example

Call auth.test method

```
User@Host ~ $ scmd auth.test --auth-token xoxb-xxxxxxxxx-xxxxxxxxxxxxxxxxxxxxxxxxxxxx
{'user_id': 'UXXXXXXXX', 'url': 'https://teamname.slack.com/', 'team': 'Teamname', 'user': 'username'}
```

Send a chat message using the web api

```
User@Host ~ $ scmd chat.postMessage '{"channel': 'CXXXXXXXX', 'text': 'this is a message send fd from
{'ok': True, 'message': {'username': 'bot', 'subtype': 'bot_message', 'ts': '1445633421.000121', 'tex
```

Slack Shell (sls)

The Slack Shell provides an interactive shell which enables the user to interactively interact with the slack web api (e.g. query all registered users).

Usage


Usage:

```
sls [--auth-token=<token>]
sls -h | --help
sls -v | --version
```

Options:

```
-h --help          Show this screen.
-v --version       Show version.
--auth-token=<token> The authentication token which will be used to access
                    the slack api.
                    As an alternative you can specify it in the .slackrc
                    or set the $SLACK_API_TOKEN environment variable.
```

Screenshot



```
Slack Shell (SLS)
To get help type help

((SLS)) >>> help

Documented commands (type help <topic>):
=====
help list quit

((SLS)) >>> list help
((SLS)) >>> help list

    The list command can be used to query various information for the slack server.

    Usage:
      list channels [-h]
      list users [-h]

    Options:

      -h prints help for the preceding command.

((SLS)) >>> █
```

API-Reference

class `libslack.slackapi.SlackApi` (*authentication_token*, *request=None*)

A SlackApi object can be used to interact with the slack api.

For further details see [methods](#).

call (*api_call*, *parameters=None*)

Executes a call on the remote slack api and returns an appropriate *SlackApiResponse* object.

Parameters

- **api_call** (*string*) – which identifies the web api endpoint which shall be called.
- **parameters** (*dict*) – which will be supplied to the web api endpoint.

e.g.: `{'channel': 'C1234567890', 'text': 'this message will be sent'}`

Attention: The authentication-token always will be passed to the endpoint implicitly.

Returns an ApiResponse object containing the data provided by the slackapi endpoint.

Raise Exception if an unknown api method is called.

class `libslack.slackapi.SlackApiRequest` (*api_call*, *authentication_token*)

The SlackApiRequest class handles and encapsulates a slack request.

execute (*request_parameters=None*)

Executes an ApiRequest, request an api call.

Parameters

- **request_parameters** (*dict*) – which will be supplied to the web api endpoint.

e.g.: `{'channel': 'C1234567890', 'text': 'this message will be sent'}`

Attention: The authentication-token always will be passed to the endpoint implicitly.

- **authentication_token** – which grants access to the api.

Returns an SlackApiResponse object based on the response of the slackapi endpoint.

Raise Exception if an error occurs while executing the api call.

class `libslack.slackapi.SlackApiResponse` (*response_data*)

The `SlackApiResponse` class handles and encapsulates an response provided by the `slackapi` after an api method was called at the endpoint.

get_error_message ()

If `is_error` returns `True`, this method returns a more detail error message.

Returns a string which provides a more detail error message.

is_error ()

Indicates whether or not the response indicates that an error occurred while trying to execute the associated api call.

Returns `True` if an error has occurred, otherwise `False`.

License

Copyright (c) 2015, Nicola Coretti All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS “AS IS” AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS WARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

Indices and tables

- `genindex`
- `modindex`
- `search`

I

`libslack.slackapi`, [5](#)

C

`call()` (`libslack.slackapi.SlackApi` method), 5

E

`execute()` (`libslack.slackapi.SlackApiRequest` method), 5

G

`get_error_message()` (`libslack.slackapi.SlackApiResponse` method),
6

I

`is_error()` (`libslack.slackapi.SlackApiResponse` method),
6

L

`libslack.slackapi` (module), 5

S

`SlackApi` (class in `libslack.slackapi`), 5

`SlackApiRequest` (class in `libslack.slackapi`), 5

`SlackApiResponse` (class in `libslack.slackapi`), 5