

---

# **matyan Documentation**

***Release 0.3***

**Artur Barseghyan <artur.barseghyan@gmail.com>**

**Nov 19, 2019**



---

## Contents

---

<b>1 Prerequisites</b>	<b>3</b>
<b>2 Documentation</b>	<b>5</b>
<b>3 Installation</b>	<b>7</b>
<b>4 Usage</b>	<b>9</b>
<b>5 Configuration</b>	<b>11</b>
<b>6 Tips and tricks</b>	<b>13</b>
6.1 Write to file . . . . .	13
6.2 Create initial config file . . . . .	13
<b>7 Testing</b>	<b>15</b>
<b>8 Writing documentation</b>	<b>17</b>
<b>9 License</b>	<b>19</b>
<b>10 Support</b>	<b>21</b>
<b>11 Author</b>	<b>23</b>
<b>12 Docs</b>	<b>25</b>
12.1 Use cases and basic concepts . . . . .	25
12.1.1 Sample use-case . . . . .	25
12.1.1.1 The use-case . . . . .	25
12.1.1.2 Sample commits . . . . .	26
12.1.1.3 Sample releases . . . . .	26
12.1.2 Sample changelog output . . . . .	27
12.2 Methodology . . . . .	27
12.3 Release history and notes . . . . .	28
12.3.1 0.3 . . . . .	28
12.3.2 0.2.1 . . . . .	28
12.3.3 0.2 . . . . .	28
12.3.4 0.1 . . . . .	29
12.3.5 0.0.2 . . . . .	29

12.3.6 0.0.1 . . . . .	29
------------------------	----

## **13 Indices and tables**

**31**

Generate changelog from Git commits.



# CHAPTER 1

---

## Prerequisites

---

- Python 3.6, 3.7 and 3.8



# CHAPTER 2

---

## Documentation

---

Documentation is available on [Read the Docs](#).



# CHAPTER 3

---

## Installation

---

Latest stable version on PyPI:

```
pip install matyan
```



# CHAPTER 4

---

## Usage

---

See [Basic concepts](#) section to get impression on possible commit methodology and assumptions taken.

### Generate changelog:

```
generate-changelog
```

### Generate changelog skipping orphaned commits:

In some cases you only want to show what has been done with tickets and skip all non-ticket related commits.

```
generate-changelog --no-other
```

### Generate changelog between two releases:

In some cases you only want to show what has been done since last release. The following example would generate changelog since version 0.0.1 to version 0.0.3.

```
generate-changelog 0.0.1...0.0.3
```

### Generate changelog between two branches:

In some cases you only want to show what has been done since last release. The following example would generate changelog since version 0.0.1 to version 0.0.3.

```
generate-changelog master..dev
```

### Generate changelog with releases info shown

```
generate-changelog --show-releases
```

### Generate changelog between releases with releases info shown

```
generate-changelog 0.0.1...0.0.3 --show-releases
```

### Generate changelog between branches with releases info shown

```
generate-changelog master..dev --show-releases
```

**Generate changelog for the latest release with releases info shown**

```
generate-changelog --latest-release --show-releases
```

# CHAPTER 5

---

## Configuration

---

In order to customize names and texts, add a `.matyan.ini` in your project directory, from which you will be running the `generate-changelog` command.

Sample configuration:

```
[BranchTypes]
feature: Feature
bugfix: Bugfix
hotfix: Hotfix
deprecation: Deprecation

[OtherBranchType]
other: Other

[Unreleased]
unreleased: Unreleased

[IgnoreCommits]
exact: more
    clean up
    code comments
    more on docs
    repo
    working
    more on
    wip
    commit
prefix: more on
        continue on
```



# CHAPTER 6

---

## Tips and tricks

---

### 6.1 Write to file

```
generate-changelog --show-releases 2>&1 | tee changelog.md
```

### 6.2 Create initial config file

```
matyan-create-config
```



# CHAPTER 7

---

## Testing

---

Simply type:

```
./runtests.py
```

Or use tox:

```
tox
```

Or use tox to check specific env:

```
tox -e py36
```



# CHAPTER 8

---

## Writing documentation

---

Keep the following hierarchy.

```
=====
title
=====

header
=====

sub-header
-----
~~~~~

sub-sub-header
~~~~~

sub-sub-sub-header
^^^^^

sub-sub-sub-sub-header
+++++


sub-sub-sub-sub-sub-header
*****
```



# CHAPTER 9

---

## License

---

GPL-2.0-only OR LGPL-2.1-or-later



# CHAPTER 10

---

## Support

---

For any issues contact me at the e-mail given in the *Author* section.



# CHAPTER 11

---

Author

---

Artur Barseghyan <[artur.barseghyan@gmail.com](mailto:artur.barseghyan@gmail.com)>



# CHAPTER 12

---

Docs

---

Contents:

## 12.1 Use cases and basic concepts

If the following applies to you, matyan could help:

- Project releases (tags) are numbered according to the [semantic versioning](#) or [sequence based identifiers](#).
- Project follows the DTAP.
- Testing, acceptance and production branches (hereafter referred as TAP branches) are protected.
- Direct commits to TAP branches are forbidden.
- All commits to TAP branches are made by pull requests.
- JIRA (or a similar tool) is used for handing project tickets.
- Pull requests are merged using GitHub or BitBucket web interface.

### 12.1.1 Sample use-case

#### 12.1.1.1 The use-case

- JIRA is used for issues.
- All commits are prefixed with ID of the JIRA issue: for example, *MSFT-1234* or *NVDA-1234* (where first four letters identify the client commit was done for, it's pattern).
- There are 3 main (protected) branches: *dev*, *staging*, *master*. Direct commits to any of the 3 are forbidden. Any feature/bugfix comes via merge request.
- All branches do have meaningful prefixes. Example, *feature/MSFT-1234-Title-of-the-issue* or *bugfix/MSFT-1236-prevent-duplicate-postal-codes*.

- Release flow is *dev -> staging -> master*.

### 12.1.1.2 Sample commits

Consider the following commits into the dev branch:

*branch: bugfix/MSFT-1240-LinkedIn-authentication-failing*

- MSFT-1240 Fix package configuration.
- MSFT-1240 Update authentication pipeline.

*branch: deprecation/MSFT-1239-Deprecate-Python2*

- MSFT-1239 Deprecate Python2.
- MSFT-1238 Add initial MyPY setup.

*branch: feature/MSFT-1238-Token-authentication*

- MSFT-1238 Implement token authentication.
- MSFT-1238 Update authentication docs.

*branch: feature/MSFT-1237-Improve-document-sharing*

- MSFT-1237 Improve document sharing. Add option to share via GDrive.

*branch: bugfix/MSFT-1236-prevent-duplicate-postal-codes*

- MSFT-1236 Normalise postal codes for German addresses.
- MSFT-1236 Normalise postal codes for US addresses.
- MSFT-1236 Make postal code field unique for the country.

*branch: deprecation/MSFT-1235-deprecate-old-api*

- MSFT-1235 Deprecate API v 2.0.
- MSFT-1235 Update docs.

*branch: feature/MSFT-1234-car-type-suggester*

- MSFT-1234 Initial car type suggester implementation.
- MSFT-1234 Add insurance amount indication based on car weight.

### 12.1.1.3 Sample releases

All commits have been finally merged into master.

Releases have been made in the following way:

*0.1*

- Merged issues MSFT-1234, MSFT-1235 and MSFT-1236

*0.2*

- Merged issues MSFT-1237 and MSFT-1238

*Yet unreleased features/branches*

- MSFT-1239 and

### 12.1.2 Sample changelog output

The generated change log would look as follows:

```
### 0.2

**Features**

*MSFT-1238 Token-authentication*
- Implement token authentication.
- Update authentication docs.

*MSFT-1237 Improve document sharing*
- Improve document sharing. Add option to share via GDrive.

### 0.1

**Bugfixes**

*MSFT-1236 Prevent duplicate postal codes*
- Normalise postal codes for German addresses.
- Normalise postal codes for US addresses.
- Make postal code field unique for the country.

**Deprecations**

*MSFT-1235 Deprecate old api*
- Deprecate API v 2.0.
- Update docs.

**Features**

*MSFT-1234 Car type suggester*
- Initial car type suggester implementation.
- Add insurance amount indication based on car weight.
```

## 12.2 Methodology

- Protect your main (DTAP) branches from direct commits. Commits shall only arrive into these branches via pull request.
- Use feature branches. Make your own prefixes (or use current ones) for classification of the ticket. Add ticket name to the name of the branch, followed by slugified ticket title.
- Prefix commits with ticket number followed by meaningful description.

Sample branch names:

- bugfix/MSFT-1240-LinkedIn-authentication-failing
- deprecation/MSFT-1239-Degenerate-Python2
- feature/MSFT-1238-Token-authentication

Sample commit messages:

- MSFT-1240 Fix package configuration.
- MSFT-1239 Deprecate Python2.
- MSFT-1238 Implement token authentication.

## 12.3 Release history and notes

Sequence based identifiers are used for versioning (schema follows below):

major.minor[.revision]

- It's always safe to upgrade within the same minor version (for example, from 0.3 to 0.3.4).
- Minor version changes might be backwards incompatible. Read the release notes carefully before upgrading (for example, when upgrading from 0.3.4 to 0.4).
- All backwards incompatible changes are mentioned in this document.

### 12.3.1 0.3

2019-11-20

- Most of the functions got optional path parameter to use as path to the repository directory.
- matyan-create-config command renamed to matyan-make-config.
- Next to the commands, functions are tested as well.
- Fix issue with lower edge nog being included when using dotted range.
- Added more tests.

### 12.3.2 0.2.1

2019-11-19

- Minor fixes.

### 12.3.3 0.2

2019-11-19

- Hide empty sections/records.
- Add an option to generate changelog for latest release only.
- Handle multiple merge format commit messages.
- Prevent JSON decoding errors.
- Exclude tests from coverage.

#### 12.3.4 0.1

2019-11-18

---

**Note:** Release dedicated to my mother, who turned 70 yesterday.

---

- Status changed to beta.
- Minor fixes.
- Add *matyan-create-config* command.
- Add initial tests.

#### 12.3.5 0.0.2

2019-11-17

- Minor fixes.

#### 12.3.6 0.0.1

2019-11-17

- Initial alpha release.



# CHAPTER 13

---

## Indices and tables

---

- genindex
- modindex
- search