
Minecraft Region Checker

Jul 08, 2019

CONTENTS

1	Features	3
2	Supported Systems	5
2.1	Using as Python CLI	5
2.2	Using as Container	5
3	Getting Started	7
3.1	Usage	7
3.2	Container Usage	8
4	Indices and tables	11
	Index	13

A Small Tool for rescue and maintenance your Minecraft Worlds, insperated by [Fenixin/Minecraft-Region-Fixer](#), optimized for commandline usage, and integration into a Backup and Recovery Process. Using [twoolie/NBT](#) a Python Parser/Writer for the [NBT](#) file format, for reading and fixing the World Data Files.

For more informations take a look to the [Documentation](#).

FEATURES

- Scanning Region Files, for to many Entities, corrupted or wrong located Chunks. (*repairing planed*)
- Saving the Report as YAML, for later usage.
- Different commandline output formats.
 - YAML, for Script usage.
 - COMMANDLINE, as Human readable commandline Report.
- Configurable over Command Line Parameters (using [click](#)), or Config File (using [anyconfig](#))(*planed*).

SUPPORTED SYSTEMS

For executing you need Python 3.5 or later, or you use the Preconfigured Docker Container from [DockerHub](#). Tested with a Minecraft *1.13.2* World.

2.1 Using as Python CLI

This Tool are published at [pypi.org](#), and be install with [pip](#). It is recommendet to use a [virtualenv](#) to avoid any Dependency correlations.

```
pip install mcworldmanager
```

2.2 Using as Container

The Container is based on [python:3.7-alpine](#), and automatical build on [DockerHub](#).

```
docker run -it \
  --user=${UID}:${(id -g $(whoami))} \
  -w /tmp/worlds \
  -v /tmp/worlds:/tmp/worlds \
  nolte/minecraft-world-manager:latest -v worlds /tmp/worlds
```


GETTING STARTED

3.1 Usage

3.1.1 mcworldmanager

Console script for mcworldmanager.

```
mcworldmanager [OPTIONS] COMMAND [ARGS]...
```

Options

- v, --verbose**
Print debug information
- o, --output_format** <output_format>
Define the STDOUT Output format
- Options** YAML|COMMANDLINE
- r, --report_path** <report_path>
Path for the Report in Yaml Format
- debug-file** <debug_file>
File to be used as a stream for DEBUG logging

region

Analyse a single minecraft region file like r.-1.-2.mca

```
mcworldmanager region [OPTIONS] REGION_FILE_PATH
```

Arguments

REGION_FILE_PATH
Required argument

server

Analyse a all Worlds in a Server Directories

```
mcworldmanager server [OPTIONS] SERVER_DIRECTORY
```

Arguments

SERVER_DIRECTORY

Required argument

version

Display the current version.

```
mcworldmanager version [OPTIONS]
```

worlds

Analyse a List of World Directories

```
mcworldmanager worlds [OPTIONS] [WORLDS_DIRECTORIES]...
```

Arguments

WORLDS_DIRECTORIES

Optional argument(s)

3.2 Container Usage

For easy and quickly usage you can use the Dockerfile from [Dockerhub](#).

```
docker pull nolte/minecraft-world-manager:v0.2.0.dev
```

For wrapping the tool, and checkout to your local FS it is required that you define some additional *Container Run Parameters*.

Listing 1: execute world check

```
docker run -it \
  --user=${UID}:${(id -g ${whoami})} \
  -w /tmp/worlds \
  -v /tmp/worlds:/tmp/worlds \
  nolte/minecraft-world-manager:v0.2.0.dev -v worlds /tmp/worlds
```

3.2.1 Container Run Parameters

- `--user ${UID}:${id -g $(whoami)}` The Container User will mapped to your user and group from the Host System, see [User](#).
- `-w /tmp/worlds` The Container [Workingdir](#).
- `-v /tmp/worlds:/tmp/worlds` Some Folder mounted to your Host System, used as scanning base folder.
- `[mcworldmanager command]` Using the [mcworldmanager](#) commandline parameters.

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

Symbols

-debug-file <debug_file>
 mcworldmanager command line option,
 7

-o, -output_format <output_format>
 mcworldmanager command line option,
 7

-r, -report_path <report_path>
 mcworldmanager command line option,
 7

-v, -verbose
 mcworldmanager command line option,
 7

M

mcworldmanager command line option
 -debug-file <debug_file>,7
 -o, -output_format <output_format>,
 7
 -r, -report_path <report_path>,7
 -v, -verbose,7

mcworldmanager-region command line
 option
 REGION_FILE_PATH,7

mcworldmanager-server command line
 option
 SERVER_DIRECTORY,8

mcworldmanager-worlds command line
 option
 WORLDS_DIRECTORIES,8

R

REGION_FILE_PATH
 mcworldmanager-region command line
 option,7

S

SERVER_DIRECTORY
 mcworldmanager-server command line
 option,8

W

WORLDS_DIRECTORIES

mcworldmanager-worlds command line
 option,8