
rpmdeplint

Release 1.0

July 15, 2016

1	rpmdeplint	3
1.1	Synopsis	3
1.2	Description	3
1.3	Options	3
1.4	Arguments	3
1.5	Commands	3
1.6	Exit status	4
1.7	Examples	4
1.8	Bugs	4
2	API	5
3	Changelog	7
3.1	0.1	7

Rpmdeplint is a tool to find errors in RPM packages in the context of their dependency graph.

rpmdeplint

1.1 Synopsis

```
rpmdeplint check-sat [--repo NAME,PATH] [RMPATH]
rpmdeplint check-conflicts [--repo NAME,PATH] [RMPATH]
rpmdeplint list-deps [--repo NAME,PATH] [RMPATH]
```

1.2 Description

The **rpmdeplint** will test dependency satisfiability of given RPM packages against given repositories.

1.3 Options

--repo NAME, PATH

You can provide multiple repos of each type. The NAME may be anything you choose. The path must either be a filesystem path or a URL. In either case, the path is expected to point at *repodata/repomd.xml*.

1.4 Arguments

RMPATH

Path to an RPM package. This can be a relative or absolute filesystem path.

1.5 Commands

check-sat Checks for unmet dependencies with the given RPM packages against the given repositories. Each unmet dependency is listed.

check-conflicts Checks for undeclared file conflicts in the given RPM packages: that is, when one of the given package contains a file which is also contained in some other package.

This command will not report a file as conflicting between two packages if:

- there is an explicit RPM `Conflicts` between the two packages; or

- the file's checksum, permissions, owner, and group are identical in both packages (RPM allows both packages to own the file in this case); or
- the file's color is different between the two packages (RPM will silently resolve the conflict in favour of the 64-bit file).

list-deps All dependencies will be listed for each given RPM package.

1.6 Exit status

Zero if all dependencies are satisfiable. Non-zero if dependency errors are encountered.

1.7 Examples

Test if an RPM package has unsatisfied dependencies against a remote repository:

```
rpmdeplint check-sat --repo beaker,https://beaker-project.org/yum/client/Fedora23/ my-package.rpm

Problems with dependency set:
nothing provides python(abi) = 2.7 needed by some-package-1.2.3.fc23.noarch
nothing provides TurboGears >= 1.1.3 needed by other-package-33.2-1.fc23.noarch
```

List all dependencies for *my-package.rpm*:

```
rpmdeplint list-deps --repo beaker,https://beaker-project.org/yum/client/Fedora23/ my-package.rpm

my-package has 72 dependencies:
    basesystem-11-1.fc23.noarch
    bash-4.3.42-1.fc23.x86_64
    beaker-common-22.1-1.fc22.noarch
    ....
```

1.8 Bugs

Bug reports can be submitted to <https://bugzilla.redhat.com/>.

Changelog

3.1 0.1

- Initial release. Supports checking dependency satisfiability and undeclared file conflicts.

Symbols

`-repo NAME,PATH`

rpmdeplint-check-sat command line option, 3

R

rpmdeplint-check-sat command line option

`-repo NAME,PATH`, 3

RPMPATH, 3

RPMPATH

rpmdeplint-check-sat command line option, 3