

---

# **SHOW Documentation**

***Release 0.8.2***

**Joseph Durel**

**Jan 30, 2018**



---

## Contents:

---

|          |                                 |           |
|----------|---------------------------------|-----------|
| <b>1</b> | <b>Tutorial</b>                 | <b>3</b>  |
| 1.1      | Including & Compiling . . . . . | 3         |
| 1.2      | Creating a Server . . . . .     | 3         |
| 1.3      | Handling a Connection . . . . . | 4         |
| 1.4      | Reading Requests . . . . .      | 4         |
| 1.5      | Sending Responses . . . . .     | 5         |
| <b>2</b> | <b>Classes &amp; Types</b>      | <b>7</b>  |
| 2.1      | Classes . . . . .               | 7         |
| 2.2      | Types . . . . .                 | 11        |
| 2.3      | Throwables . . . . .            | 12        |
| <b>3</b> | <b>Functions</b>                | <b>15</b> |
| <b>4</b> | <b>Constants</b>                | <b>17</b> |
| 4.1      | Version . . . . .               | 17        |
| <b>5</b> | <b>Separate Utilities</b>       | <b>19</b> |
| 5.1      | Base-64 Encoding . . . . .      | 19        |
| <b>6</b> | <b>Indices and tables</b>       | <b>21</b> |



SHOW is designed to be an idiomatic library for standalone webserver applications written for modern C++. SHOW is simple in the same way the standard library is simple — it doesn't make any design decisions for the programmer, instead giving them a set of primitives for building an HTTP web application.

Both HTTP/1.0 and HTTP/1.1 are supported. SHOW assumes a modern approach to application hosting, and is intended to be run behind a full reverse proxy such as [NGINX](#). As such, SHOW will not support HTTP/2 or TLS (HTTPS). Instead, you should write your applications to serve local HTTP/1.0 and HTTP/1.1 requests.

SHOW uses the [zlib license](#). C++11 support and a POSIX operating system are required.



This shows the basic usage of SHOW; see the [examples](#) for a more thorough introduction.

## 1.1 Including & Compiling

For GCC and Clang, you can either link *show.hpp* to one of your standard include search paths, or use the `-I` flag to tell the compiler where to find the header:

```
clang++ -I "SHOW/src/" ...
```

SHOW is entirely contained in a single header file, you have to do then is include SHOW using `#include <show.hpp>`. With either compiler you'll also need to specify C++11 support with `-std=c++11`.

If you use [CMake](#) and don't have SHOW linked to said include path, you'll need to include the following in your *CMakeLists.txt*:

```
include_directories( "SHOW/src/" )
```

replacing "SHOW/src/" with wherever you've cloned or installed SHOW. Switch to C++11 mode with:

```
set( CMAKE_CXX_STANDARD 11 )  
set( CMAKE_CXX_STANDARD_REQUIRED ON )
```

## 1.2 Creating a Server

To start serving requests, first create a *server* object:

```
show::server my_server(  
    "0.0.0.0", // IP address on which to serve  
    9090,      // Port on which to serve  
);
```

That's it, you've made a server that sits there forever until it gets a connection, then hangs. Not terribly useful, but that's easy to fix.

## 1.3 Handling a Connection

For each call of `my_server.serve()` a single `connection` object will be returned or a `connection_timeout` thrown. You may want to use something like this:

```
while( true )
{
    try
    {
        show::connection connection( my_server.serve() );
        // handle request(s) here
    }
    catch( const show::connection_timeout& ct )
    {
        std::cout
            << "timed out waiting for a connection, looping..."
            << std::endl
            ;
        continue;
    }
}
```

The server listen timeout can be a positive number, 0, or -1. If it is -1, the server will continue listening until interrupted by a signal; if 0, `server::serve()` will throw a `connection_timeout` immediately unless connections are available.

The connection is now independent from the server. You can adjust the connection's timeout independently using `connection::timeout()`. You can also pass it off to a worker thread for processing so your server can continue accepting other connections; this is usually how you'd implement a real web application.

## 1.4 Reading Requests

`request` objects have a number of `const` fields containing the HTTP request's metadata; you can see descriptions of them all in the docs for the class.

Note that these fields do not include the request content, if any. This is because HTTP allows the request content to be streamed to the server. In other words, the server can interpret the headers then wait for the client to send data over a period of time. For this purpose, `request` inherits from `std::streambuf`, implementing the read/get functionality. You can use the raw `std::streambuf` methods to read the incoming data, or create a `std::istream` from the request object for `std::cin`-like behavior.

For example, if your server is expecting the client to *POST* a single integer, you can use:

```
show::request request( test_server.serve() );

std::istream request_content_stream( request );

int my_integer;
request_content_stream >> my_integer;
```

Please note that the above is not terribly safe; production code should include various checks to guard against buggy or malignant clients.

Also note that individual request operations may timeout, so the entire serve code should look like this:



```

while( true )
    try
    {
        show::connection connection( my_server.serve() );
        try
        {
            show::request request( connection );
            std::istream request_content_stream( request );
            int my_integer;
            request_content_stream >> my_integer;
            std::cout << "client sent " << my_integer << "\n";
        }
        catch( const show::connection_timeout& ct )
        {
            std::cout << "got a request, but client disconnected!" << std::endl;
        }
        catch( const show::connection_timeout& ct )
        {
            std::cout << "got a request, but client timed out!" << std::endl;
        }
    }
    catch( const show::connection_timeout& ct )
    {
        std::cout << "timed out waiting for a connection, looping..." << std::endl;
        continue;
    }
}

```

If this feels complicated, it is. Network programming like this reveals the worst parts of distributed programming, as there's a lot that can go wrong between the client and the server.

Another thing to keep in mind is that HTTP/1.1 — and HTTP/1.0 with an extension — allow multiple requests to be pipelined on the same TCP connection. SHOW can't know with certainty where on the connection one request ends and another starts — it's just the nature of pipelined HTTP. Sure, the *Content-Length* header could be used, and [chunked transfer encoding](#) has well-established semantics, but if the client uses neither it is up to your application to figure out the end of the request's content. In general, you should reject requests whose length you can't readily figure out, but SHOW leaves that decision up to the programmer. But you should never try to create a *request* from a *connection* before you've finished reading the content from a previous request.

See also:

- `std::streambuf` on [cppreference.com](#)
- `std::istream` on [cppreference.com](#)
- `std::cin` on [cppreference.com](#)

## 1.5 Sending Responses

Sending responses is slightly more involved than reading basic requests. Say you want to send a “Hello World” message for any incoming request. First, start with a string containing the response message:

```
std::string response_content = "Hello World";
```

Next, create a headers object to hold the content type and length headers (note that header values must be strings):

```
show::headers_t headers = {
    { "Content-Type", { "text/plain" } },
```

```
{ "Content-Length", {  
    std::to_string( response_content.size() )  
} }  
};
```

Since it's a `std::map`, you can also add headers to a `headers_t` like this:

```
headers[ "Content-Type" ].push_back( "text/plain" );
```

Then, set the **HTTP status code** for the response to the generic *200 OK*:

```
show::response_code code = {  
    200,  
    "OK"  
};
```

Creating a response object requires the headers and response code to have been decided already, as they are marshalled (serialized) and buffered for sending as soon as the object is created. A response object also needs to know which request it is in response to. While there's nothing preventing you from creating multiple responses to a single request this way, most of the time that will break your application.

Create a response like this:

```
show::response response(  
    connection,  
    show::http_protocol::HTTP_1_0,  
    code,  
    headers  
);
```

Finally, send the response content. Here, a `std::ostream` is used, as `response` inherits from and implements the write/put functionality of `std::streambuf`:

```
std::ostream response_stream( &response );  
response_stream << response_content;
```

**See also:**

- `std::map` on [cppreference.com](http://cppreference.com)
- `std::ostream` on [cppreference.com](http://cppreference.com)
- `std::streambuf` on [cppreference.com](http://cppreference.com)

## 2.1 Classes

The public interfaces to the main SHOW classes are documented on the following pages:

### 2.1.1 Server

#### **class server**

The server class serves as the basis for writing an HTTP application with SHOW. Creating a server object allows the application to handle HTTP requests on a single IP/port combination.

**server** (**const** std::string &address, unsigned int port, int timeout = -1)

Constructs a new server to serve on the given IP address and port. The IP address will typically be localhost/0.0.0.0/:::. The port should be some random higher-level port chosen for the application.

The timeout is the maximum number of seconds *serve()* will wait for an incoming connection before throwing *connection\_timeout*. A value of 0 means that *serve()* will return immediately if there are no connections waiting to be served; -1 means *serve()* will wait forever (until the program is interrupted).

**~server** ()

Destructor for a server; any existing connections made from this server will continue to function

*connection* **serve** ()

Either returns the next connection waiting to be served or throws *connection\_timeout*.

**const** std::string &**address** () **const**

Get the address this server is servering on

unsigned int **port** () **const**

Get the port this server is servering on

int **timeout** () **const**

Get the current timeout of this server

`int timeout (int)`

Set the timeout of this server to a number of seconds, 0, or -1

## 2.1.2 Connection

**class connection**

Objects of this type represent a connection between a single client and a server. A connection object can be used to generate *request* objects; one in the case of HTTP/1.0 or multiple in the case of HTTP/1.1.

The connection class has no public constructor (besides the move constructor), and can only be created by calling *server::serve()*.

**connection** (*connection&&*)

Explicit *move constructor* as one can't be generated for this class

**~connection** ()

Destructor for a connection, which closes it; any requests or responses created on this connection can no longer be read from or written to

**const** std::string &**client\_address** () **const**

The IP address of the connected client

unsigned int **client\_port** () **const**

The port of the connected client

**const** std::string &**server\_address** () **const**

The address of the server handling the connection

unsigned int **server\_port** () **const**

The port of the server handling the connection

**int timeout** () **const**

Get the current timeout of this connection, initially inherited from the server the connection is created from

**int timeout** (int)

Set the timeout of this connection independently of the server; the argument is a number of seconds, 0, or -1

**See also:**

- *server::timeout()*

## 2.1.3 Request

**class request : public** std::streambuf

Represents a single request sent by a client. Inherits from `std::streambuf`, so it can be used as-is or with a `std::istream`.

**See also:**

- `std::streambuf` on [cppreference.com](http://cppreference.com)
- `std::istream` on [cppreference.com](http://cppreference.com)

**enum content\_length\_flag**

A utility type for *unknown\_content\_length()* with the values:

| Value | Evaluates to |
|-------|--------------|
| NO    | false        |
| YES   | true         |
| MAYBE | true         |

**const** std::string &**client\_address** () **const**

The IP address of the client that sent the request

**const** unsigned int **client\_port** () **const**

The port of the client that sent the request

**bool** **eof** () **const**

Returns whether or not the request, acting as a `std::streambuf`, has reached the end of the request contents. Always returns `false` if the content length is unknown.

**See also:**

- `unknown_content_length()`

**request** (*connection*&)

Constructs a new request on a connection. Blocks until a connection is sent, the connection timeout is reached, or the client disconnects. May also throw `request_parse_error` if the data sent by the client cannot be understood as an HTTP request.

**See also:**

- `connection_timeout`
- `client_disconnected`

**request** (*request*&&)

Explicit `move constructor` as one can't be generated for this class

**void** **flush** ()

Flushes the request contents from the buffer, putting it in a state where the next request can be extracted. It is only safe to call this function if `unknown_content_length()` evaluates to `false`.

*http\_protocol* **protocol** () **const**

The HTTP protocol used by the request. If `NONE`, it's usually safe to assume HTTP/1.0. If `UNKNOWN`, typically either a *400 Bad Request* should be returned, just assume HTTP/1.0 to be permissive, or try to interpret something from `protocol_string()`.

**const** std::string &**protocol\_string** () **const**

The raw protocol string sent in the request, useful if `protocol()` is `UNKNOWN`

**const** std::string &**method** () **const**

The request method as a capitalized ASCII string. While the HTTP protocol technically does not restrict the available methods, typically this will be one of the following:

|         |                             |
|---------|-----------------------------|
| GET     | Common methods              |
| POST    |                             |
| PUT     |                             |
| DELETE  |                             |
| OPTIONS | Useful for APIs             |
| PATCH   | Relatively uncommon methods |
| TRACE   |                             |
| HEAD    |                             |
| CONNECT |                             |

**See also:**

- [List of common HTTP methods on Wikipedia](#) for descriptions of the methods

**const** `std::vector<std::string> &path()` **const**

The request path separated into its elements, each of which has been URL- or percent-decoded. For example:

```
/foo/bar/hello+world/%E3%81%93%E3%82%93%E3%81%AB%E3%81%A1%E3%81%AF
```

becomes:

```
{
    "foo",
    "bar"
    "hello world",
    ""
}
```

**const** `query_args_type &query_args()` **const**

The request query arguments. SHOW is very permissive in how it parses query arguments:

| Query string     | Interpreted as                                 |
|------------------|--|
| ?foo=1&bar=2     | { { "foo", { "1" } }, { "bar", { "2" } } }     |
| ?foo=bar=baz     | { { "foo", { "baz" } }, { "bar", { "baz" } } } |
| ?foo=&bar=baz    | { { "foo", { "" } }, { "bar", { "baz" } } }    |
| ?foo&bar=1&bar=2 | { { "foo", { "" } }, { "bar", { "1", "2" } } } |

**const** `headers_type &headers()` **const**

The request headers

**See also:**

- [List of common HTTP headers on Wikipedia](#)

`content_length_flag` **unknown\_content\_length()** **const**

Whether the content length of the request could be interpreted

This member may be a bit confusing because it is “*un*-known” rather than “know”. It’s convenient for `content_length_flag` to evaluate to a boolean value, but there are two possible reasons the content length would be unknown. Either

1. the request did not send a *Content-Length* header, or
2. the value supplied is not an integer or multiple *Content-Length* headers were sent.

In many languages (including C++), 0 is `false` and any other value is `true`; so the boolean value needs to be `false` for a known content length and `true` for anything else.

unsigned long long `content_length()` **const**

The number of bytes in the request content; only holds a meaningful value if `unknown_content_length()` is YES/true

## 2.1.4 Response

**class response** : public `std::streambuf`

Represents a single response to a request. Inherits from `std::streambuf`, so it can be used as-is or with a `std::ostream`.

SHOW does not prevent multiple response from being created or sent for a single request. Most of the time this is something that would break the application; however, under certain conditions in HTTP/1.1 multiple 100-type responses can be sent before a final 200+ response.

**See also:**

- `std::streambuf` on [cppreference.com](http://en.cppreference.com)
- `std::ostream` on [cppreference.com](http://en.cppreference.com)

**response** (`connection&`, `http_protocol`, **const** `response_code&`, **const** `headers_t&`)

Constructs a new response to the client who made a connection. The protocols, response code, and headers are immediately buffered and cannot be changed after the response is created, so they have to be passed to the constructor.

**~response** ()

Destructor for a response object; ensures the response is flushed

**virtual void flush** ()

Ensure the content currently written to the request is sent to the client

## 2.2 Types

**enum http\_protocol**

Symbolizes the possibly HTTP protocols understood by SHOW. The enum members are:

|          |   |
|----------|---|
| HTTP_1_0 | HTTP/1.0  |
| HTTP_1_1 | HTTP/1.1  |
| NONE     | The request did not specify a protocol version          |
| UNKNOWN  | The protocol specified by the request wasn't recognized |

There is no HTTP\_2 as SHOW is not intended to handle HTTP/2 requests. These are much better handled by a reverse proxy such as [NGINX](http://nginx.org), which will convert them into HTTP/1.0 or HTTP/1.1 requests for SHOW.

**class response\_code**

A simple utility `struct` that encapsulates the numerical code and description for an HTTP status code. An object of this type can easily be statically initialized like so:

```
show::response_code rc = { 404, "Not Found" };
```

See the [list of HTTP status codes](#) on Wikipedia for an easy reference for the standard code & description values.

The two fields are defined as:

unsigned short **code**

std::string **description**

#### **class query\_args\_type**

An alias for `std::map< std::string, std::vector< std::string > >`, and can be statically initialized like one:

```
show::query_args_type args = {
    { "tag", { "foo", "bar" } },
    { "page", { "3" } }
};
```

This creates a variable `args` which represents the query string `?tag=foo&tag=bar&page=3`.

See also:

- `std::map` on [cppreference.com](#)
- `std::vector` on [cppreference.com](#)

#### **class headers\_type**

An alias for `std::map< std::string, std::vector< std::string >, show::_less_ignore_case_ASCII >`, where `show::_less_ignore_case_ASCII` is a case-insensitive [compare](#) for `std::map`.

While HTTP header names are typically given in Dashed-Title-Case, they are technically case-insensitive. Additionally, in general a given header name may appear more than once in a request or response. This type satisfies both these constraints.

Headers can be statically initialized:

```
show::headers_type headers = {
    { "Content-Type", { "text/plain" } },
    { "Set-Cookie", {
        "cookie1=foobar",
        "cookie2=SGVsbG8gV29ybGQh"
    } }
};
```

See also:

- `std::map` on [cppreference.com](#)
- `std::vector` on [cppreference.com](#)

## 2.3 Throwables

Not all of these strictly represent an error state when throw; some signal common situations that should be treated very much in the same way as exceptions. SHOW's throwables are broken into two categories — connection interruptions and exceptions.



### 2.3.1 Connection interruptions

**class connection\_interrupted**

A common base class for both types of connection interruptions

**class connection\_timeout : public *connection\_interrupted***

An object of this type will be thrown in two general situations:

- A server object timed out waiting for a new connection
- A connection, request, or response timed out reading from or sending to a client

In the first situation, generally the application will simply loop and start waiting again. In the second case, the application may want to close the connection or continue waiting with either the same timeout or some kind of falloff. Either way the action will be application-specific.

**class client\_disconnected : public *connection\_interrupted***

This is thrown when SHOW detects that a client has broken connection with the server and no further communication can occur.

### 2.3.2 Exceptions

See also:

- `std::runtime_error` on [cppreference.com](http://cppreference.com)

**class socket\_error : std::runtime\_error**

An unrecoverable, low-level error occurred inside SHOW. If thrown while handling a connection, the connection will no longer be valid but the server should be fine. If thrown while creating or working with a server, the server object itself is in an unrecoverable state and can no longer serve.

The nature of this error when thrown by a server typically implies trying again will not work. If the application is designed to serve on a single IP/port, you will most likely want to exit the program with an error.

**class request\_parse\_error : std::runtime\_error**

Thrown when creating a request object from a connection and SHOW encounters something it can't manage to interpret into a *request*.

As parsing the offending request almost certainly failed midway, garbage data will likely be in the connection's buffer. Currently, the only safe way to handle this exception is to close the connection.

**class url\_decode\_error : std::runtime\_error**

Thrown by *url\_decode()* when the input is not a valid *URL*- or *percent-encoded* string.

---

**Note:** *url\_encode()* shouldn't throw an exception, as any string can be converted to percent-encoding.

---



`std::string url_encode (const std::string &o, bool use_plus_space = true)`

URL-encode a string `o`, escaping all reserved, special, or non-ASCII characters with [percent-encoding](#).

If `use_plus_space` is `true`, spaces will be replaced with `+` rather than `%20`.

`std::string url_decode (const std::string&)`

Decode a [URL-](#) or [percent-encoded](#) string. Throws [url\\_decode\\_error](#) if the input string is not validly encoded.



All constants are `const`-qualified.

### 4.1 Version

The `version` sub-namespace contains information about the current `SHOW` version. It has the following members:

`std::string name`

The proper name of `SHOW` as it should appear referenced in headers, log messages, etc.

`int major`

The major `SHOW` version (`X . 0 . 0`)

`int minor`

The minor `SHOW` version (`0 . X . 0`)

`int revision`

The `SHOW` version revision (`0 . 0 . X`)

`std::string string`

A string representing the major, minor, and revision version numbers



---

Separate Utilities

---

These are some useful utilities included with SHOW, but in their own header files so they're optional.

## 5.1 Base-64 Encoding

These are utilities for handling `base64`-encoded strings, very commonly used for transporting binary data in web applications. They are included in `show/base64.hpp`.

string **base64\_encode** (**const** std::string &o, **const** char \*chars = base64\_chars\_standard)

Base64-encode a string o using the character set chars, which must point to a char array of length 64.

**See also:**

- `base64_chars_standard`
- `base64_chars_urlsafe`

std::string **base64\_decode** (**const** std::string &o, **const** char \*chars = base64\_chars\_standard)

Decode a base64-encoded string o using the character set chars, which must point to a char array of length 64. Throws a `base64_decode_error` if the input is not encoded against chars or has incorrect padding.

**See also:**

- `base64_chars_standard`
- `base64_chars_urlsafe`

**class base64\_decode\_error** : exception

Thrown by `base64_decode()` when the input is not valid base64.

---

**Note:** `base64_encode()` shouldn't throw an exception, as any string can be converted to base-64.

---

char **\*base64\_chars\_standard**

The standard set of base64 characters for use with *base64\_encode()* and *base64\_decode()*

char **\*base64\_chars\_urlsafe**

The URL\_safe set of base64 characters for use with *base64\_encode()* and *base64\_decode()*, making the following replacements:

- + → -
- / → \_



## CHAPTER 6

---

### Indices and tables

---

- `genindex`
- `search`



**S**

- show::base64\_chars\_standard (C++ member), 19
- show::base64\_chars\_urlsaf (C++ member), 20
- show::base64\_decode (C++ function), 19
- show::base64\_decode\_error (C++ class), 19
- show::base64\_encode (C++ function), 19
- show::client\_disconnected (C++ class), 13
- show::connection (C++ class), 8
  - show::connection::~~connection (C++ function), 8
  - show::connection::client\_address (C++ function), 8
  - show::connection::client\_port (C++ function), 8
  - show::connection::connection (C++ function), 8
  - show::connection::server\_address (C++ function), 8
  - show::connection::server\_port (C++ function), 8
  - show::connection::timeout (C++ function), 8
  - show::connection\_interrupted (C++ class), 13
  - show::connection\_timeout (C++ class), 13
- show::headers\_type (C++ class), 12
- show::http\_protocol (C++ enum), 11
- show::query\_args\_type (C++ class), 12
- show::request (C++ class), 8
  - show::request::client\_address (C++ function), 9
  - show::request::client\_port (C++ function), 9
  - show::request::content\_length (C++ function), 11
  - show::request::content\_length\_flag (C++ enum), 8
  - show::request::eof (C++ function), 9
  - show::request::flush (C++ function), 9
  - show::request::headers (C++ function), 10
  - show::request::method (C++ function), 9
  - show::request::path (C++ function), 10
  - show::request::protocol (C++ function), 9
  - show::request::protocol\_string (C++ function), 9
  - show::request::query\_args (C++ function), 10
  - show::request::request (C++ function), 9
  - show::request::unknown\_content\_length (C++ function), 10
- show::request\_parse\_error (C++ class), 13
- show::response (C++ class), 11
  - show::response::~~response (C++ function), 11
  - show::response::flush (C++ function), 11
  - show::response::response (C++ function), 11
- show::response\_code (C++ class), 11
  - show::response\_code::code (C++ member), 12
  - show::response\_code::description (C++ member), 12
- show::server (C++ class), 7
  - show::server::~~server (C++ function), 7
  - show::server::address (C++ function), 7
  - show::server::port (C++ function), 7
  - show::server::serve (C++ function), 7
  - show::server::server (C++ function), 7
  - show::server::timeout (C++ function), 7
- show::socket\_error (C++ class), 13
- show::url\_decode (C++ function), 15
- show::url\_decode\_error (C++ class), 13
- show::url\_encode (C++ function), 15
- show::version::major (C++ member), 17
- show::version::minor (C++ member), 17
- show::version::name (C++ member), 17
- show::version::revision (C++ member), 17
- show::version::string (C++ member), 17