
unitth Documentation

Release 0.0.12

Jonathan Karr

May 08, 2018

Contents

1	Contents	3
1.1	Installation	3
1.1.1	Prerequisites	3
1.1.2	Latest revision from GitHub	3
1.1.3	Latest release From PyPI	3
1.2	Command line interface documentation	3
1.3	Examples	4
1.3.1	Command line	4
1.3.2	Python	4
1.4	About	5
1.4.1	License	5
1.4.2	Development team	6
1.4.3	Acknowledgements	6
1.4.4	Questions and comments	6

This package provides a Python method and command line interface for generating HTML reports of unit test histories. The package is a Python interface for the [UnitTH](#).

CHAPTER 1

Contents

1.1 Installation

1.1.1 Prerequisites

- Python
- Pip

1.1.2 Latest revision from GitHub

Run the following command to install the latest version from GitHub:

```
pip install git+git://github.com/KarrLab/unitth.git#egg=unitth
```

1.1.3 Latest release From PyPI

Run the following command to install the latest release from PyPI:

```
pip install unitth
```

1.2 Command line interface documentation

```
usage: unitth (sub-commands ...) [options ...] {arguments ...}

Generate HTML unit test history report

positional arguments:
```

(continues on next page)

(continued from previous page)

```

xml_report_dir          Parent directory of XML reports of individual builds
                        to generate a history report of

optional arguments:
  -h, --help            show this help message and exit
  --debug              toggle debug output
  --quiet              suppress all output
  --xml-report-filter [XML_REPORT_FILTER]
                        Starts-with filter for individual reports with `xml-
                        report-dir` that should be included in the history
                        report. Set `xml-report-filter` to to include all
                        files/subdirectories in the history report.
  --html-report-path HTML_REPORT_PATH
                        Directory of HTML reports of individual
                        builds(relative to XML directories of individual
                        builds)
  --generate-exec-time-graphs GENERATE_EXEC_TIME_GRAPHS
                        Whether execution time graphs shall be generated
  --html-report-dir HTML_REPORT_DIR
                        directory to store generated HTML history report
  --initial_java_heap_size INITIAL_JAVA_HEAP_SIZE
                        Initial Java heap size
  --maximum_java_heap_size MAXIMUM_JAVA_HEAP_SIZE
                        Maximum Java heap size

```

1.3 Examples

1.3.1 Command line

```

mkdir reports
mkdir reports/nose
mkdir reports/unitth
mkdir reports/html

nosetests tests/test_unitth.py:TestDummy.test_dummy_test --with-xunit --xunit-file_
↳reports/nose/1.xml
nosetests tests/test_unitth.py:TestDummy.test_dummy_test --with-xunit --xunit-file_
↳reports/nose/2.xml

nose2unitth reports/nose/1.xml reports/unitth/1
nose2unitth reports/nose/2.xml reports/unitth/2

junit2html reports/nose/1.xml reports/unitth/1/index.html
junit2html reports/nose/2.xml reports/unitth/2/index.html

unitth --xml_report_filter --html_report_dir reports/html "reports/unitth/*"

```

1.3.2 Python

```

from nose2unitth.core import Converter as nose2unitth
from junit2htmlreport.parser import Junit as JunitParser

```

(continues on next page)

(continued from previous page)

```

from unitth.core import UnitTH
import os
import subprocess

os.mkdir('reports')
os.mkdir('reports/nose')
os.mkdir('reports/unitth')
os.mkdir('reports/html')

subprocess.check_call(['nosetests', 'tests/test_unitth.py:TestDummy.test_dummy_test',
                      '--with-xunit', '--xunit-file', 'reports/nose/1.xml'])
subprocess.check_call(['nosetests', 'tests/test_unitth.py:TestDummy.test_dummy_test',
                      '--with-xunit', '--xunit-file', 'reports/nose/2.xml'])

nose2unitth.run('reports/nose/1.xml', 'reports/unitth/1')
nose2unitth.run('reports/nose/2.xml', 'reports/unitth/2')

with open('reports/unitth/1/index.html', 'wb') as html_file:
    print >> html_file, JunitParser('reports/nose/1.xml').html()
with open('reports/unitth/2/index.html', 'wb') as html_file:
    print >> html_file, JunitParser('reports/nose/2.xml').html()

UnitTH.run('reports/unitth/*', xml_report_filter='', html_report_dir='reports/html')

```

1.4 About

1.4.1 License

The software is released under the MIT license

The MIT License (MIT)

Copyright (c) 2016 Karr Lab

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

1.4.2 Development team

This package was developed by the [Karr Lab](#) at the Icahn School of Medicine at Mount Sinai in New York, USA.

1.4.3 Acknowledgements

This work was supported by a National Institute of Health MIRA award [grant number 1 R35 GM 119771-01].

1.4.4 Questions and comments

Please contact the [Karr Lab](#) with any questions or comments.