

Virtual Micromagnetics Documentation

Release 1.0.2

Mark Vousden

September 16, 2016

1	Contents	3
1.1	Getting Started: As a User	3
1.2	Virtual Micromagnetics Environments and Simulation Software	4
1.3	Virtual Machines and Related Software	5
1.4	Getting Started: As a Poweruser	7
1.5	Developer Notes (valid for version 1.0.2)	7
1.6	Troubleshooting	12
1.7	Glossary	12



Welcome to the *Virtual Micromagnetics* project, where we aim to enable accessible and reproducible micromagnetics simulation, without compromise.

Provided by Mark Vousden, Hans Fangohr, and others at the University of Southampton. Funded by EPSRC's DTC grant EP/G03690X/1. The license for this software is available [here](#).

The *Virtual Micromagnetics* project creates *virtual environments* that run micromagnetic (and in some cases, atomistic) simulations of magnetic behaviour. These environments produce *system virtual machines* which emulate a configured set of software on your computer. This means you as a user only need to manage the software to support the virtual machine, as opposed to the complicated set of dependencies most simulation packages require. As a result, these virtual environments are far simpler to maintain, meaning you have more time to solve the mysteries of the universe instead of:

- wondering why the latest version of a package is incompatible with earlier simulations.
- wondering how to maintain multiple versions of a package to support old simulation software.
- persuading your high-performance computing system administrator to support your long list of software dependencies.
- setting up user accounts and packages for new students to run simulations.

1.1 Getting Started: As a User


To start a *Virtual Micromagnetics* environment, you will need the following software:

- VirtualBox >= 5.0 (<https://www.virtualbox.org/wiki/downloads>)
- Vagrant >= 1.7.4 (<https://www.vagrantup.com/downloads>)


After restarting your machine, command the following in an empty directory:

```
vagrant init virtualmicromagnetics/full
vagrant up --provider virtualbox
```

These commands will download the Full Virtual Micromagnetics environment from the Internet to your computer, and load the environment automatically. When complete, you should be greeted with this window:



This is output from a *virtual machine* running on your computer! Virtual machines produced in this way run Ubuntu GNU/Linux (<https://www.ubuntu.com>) with the XFCE window manager. From here, you can follow instructions in the welcome file on the desktop to run simulations with the installed packages. Never worry about software dependencies again!



Next, see *Virtual Micromagnetics Environments and Simulation Software* for the environments that are available besides the Full Virtual Micromagnetics environment, and the software on these environments.

1.2 Virtual Micromagnetics Environments and Simulation Software

In *Getting Started: As a User*, we created a *virtual machine* based on the Full *Virtual Micromagnetics* environment. Here, we detail the micromagnetic simulation packages and other software supported and used by Virtual Micromagnetics, and we describe the list of available Virtual Micromagnetics environments.

1.2.1 Software

The following micromagnetic simulation packages are supported by Virtual Micromagnetics:

- OOMMF (<http://math.nist.gov/oommf/>)
- MagPar (<http://www.magpar.net/>)
- NMag (<http://nmag.soton.ac.uk/nmag/>)
- Fidimag (<http://computationalmodelling.github.io/fidimag/>)

Each environment that uses a simulation package also contains its examples, and a link to its documentation page which can be opened in the virtual machine. The following infrastructure software is also used in all environments:

- Ubuntu (<http://www.ubuntu.com/>) 14.04
- XFCE4 (<http://www.xfce.org/>)
- Python (<https://www.python.org/>) 2.7, IPython (<http://ipython.org/>)

1.2.2 Environments

The Full environment contains all simulation packages supported by Virtual Micromagnetics, as well as dependencies requested by our users, including:

- Cython(<http://cython.org/>)
- FEniCS (<http://fenicsproject.org/>)
- Gmsh (<http://gmsh.info/>)
- Netgen (<https://sourceforge.net/projects/netgen-mesher/>)
- ParaView (<http://www.paraview.org/>)
- Sundials (<http://acts.nersc.gov/sundials/>)

We recognise that many of our users will not require these tools. To that end, a “Lite” environment can be used instead, which contains all of the simulation packages the Full environment does, without these optional packages. To download and use the Lite Virtual Micromagnetics environment, command:

```
vagrant init virtualmicromagnetics/lite
vagrant up --provider virtualbox
```

Note that this is syntactically similar to the command used in *Getting Started: As a User*, and can be adapted for all other Virtual Micromagnetics environments. Environments exist for specific simulation packages, such as “virtualmicromagnetics/oommf”. The following table shows the list of environments available under Virtual Micromagnetics, and the software they contain:

Software vs. Environment		Full	Lite	OOMMF	Magpar	NMag	Fidimag
Micromagnetic	OOMMF						
	Magpar						
	NMag						
	Fidimag						
Infrastructure	Ubuntu						
	XFCE						
	Python 2						
	IPython						
Other	Cython						
	FEniCS						
	Gmsh						
	Netgen						
	ParaView						
	Sundials						

See *Getting Started: As a Poweruser* if more fine-grained control over your software interests you. However, we firstly recommend reading *Virtual Machines and Related Software* to understand more about *virtual machines*, *virtual environments*, and the software used to create them in the Virtual Micromagnetics project.

1.3 Virtual Machines and Related Software

In *Getting Started: As a User*, we created a *virtual machine* based on the Full *Virtual Micromagnetics* environment using a virtual machine *provider* and *manager*. Here, we detail some of the underlying mechanisms of *virtual machine* creation, what providers, managers, and *provisioners* are, and how virtual machines and *virtual environments* are related through these virtual machine software.

1.3.1 Virtual Machines

A *virtual machine* is a software that imitates a certain other software, usually an operating system or environment, on a certain hardware. For our purposes however, it can be thought of as an operating system running in an operating system. Virtual machines are useful because they allow software tasks to be undertaken in precisely defined environments with little repercussion on the host system they run on. These machines themselves can be described by single files representing the equivalent of a hard disk of the machine, as well as a description of the hardware that the virtual machine emulates. This makes them simple to distribute.

1.3.2 Software Related to Virtual Machines

Virtual machines must be supported by software in order to function. Only provider software is necessary to run a virtual machine, but managers and provisioners are useful for creating virtual machines and virtual environments respectively.

Providers

Virtual machine providers are virtualiser software that supports creating, running, destroying, and other interaction with *virtual machines* on your computer. VirtualBox (<https://www.virtualbox.org>) is an example of a virtual machine provider that is open source and freely available under the GNU GPL (<https://www.gnu.org/copyleft/gpl.html>), and is the provider supported by this project. Other popular provider software includes VMWare, KVM, and Docker. While many cloud computing organisations use virtual machines, they typically use existing provider software.

Managers

While not essential for starting *virtual machines*, specialist software is useful for managing *virtual environments*. Vagrant (<https://www.vagrantup.com>) is an example of a virtual machine manager. It provides a command-line interface to the creation and provision of virtual machines from virtual environments. HashiCorp, the company behind Vagrant, also provides a framework for sharing virtual environments. Most importantly for our purpose, Vagrant can be automated to generate virtual machines containing an environment without user intervention. This environment can then be used to complete our objectives. To specify this environment however, provisioning software is required.

Provisioners

Provisioning is the action of running select commands on a machine, virtual or otherwise, to reach a desired end state. By “state”, here we mean how storage is populated with packages, environment definitions, and more. The user of a provisioner describes the desired state of the system, and the provisioner makes it so. In the absence of a provisioner, shell commands can be executed to specify the state, but this becomes unwieldy for large projects because focus is placed on the instructions needed to obtain the desired state, as opposed to the state itself. Provisioning software, such as Ansible (<https://www.ansible.com>) alleviates this problem. Ansible uses Yet Another Markup Language (YAML) to describe plays to run on a machine to enact the desired end state. Since the focus is on the end state of the system, *idempotency* is essential.

1.3.3 Summary

Virtual machines imitate hardware and software, but must be hosted on a *host machine*. Virtual machines are provided by *provider* software running on the host machine, and can be provisioned for use by a *provisioner* software. *Manager* software links these two concepts, allows the virtual machine to be preserved and distributed as a *virtual environment*, and simplifies the creation of virtual machines.

You are now ready to *get started as a poweruser*, which explains how to create custom environments containing software you choose, as well as instructions for adding new software or configuring your own virtual environment.

1.4 Getting Started: As a Poweruser

In *Virtual Micromagnetics Environments and Simulation Software*, we learned about the different *Virtual Micromagnetics* environments available to users, which bundle sets of configured software. Here we outline how you can create virtual environments yourself, which you can distribute to others. We recommend reading *Virtual Machines and Related Software*, if you have not already.

To create a new, custom *virtual environment*, you will need the following software in addition to the software list in *Getting Started: As a User*:

- A GNU/Linux operating system (we use Ubuntu, <https://www.ubuntu.com>)
- 2.7 <= Python < 3.0 (<https://www.python.org/>)
- 1.9 <= Ansible < 2.0 (<https://www.ansible.com/>)

With this software:

1. Grab a copy of Virtual Micromagnetics. You can do this via Git by cloning our repository with `git clone -b release https://github.com/computationalmodelling/virtualmicromagnetics.git`, or by grabbing a release version at <https://github.com/computationalmodelling/virtualmicromagnetics/releases>
2. Install some sub-packages:
 - Ansible role “blockinfile”; command `ansible-galaxy install yaegashi.blockinfile --proles/` from the Virtual Micromagnetics software directory
 - Vagrant plugin “vagrant-vbguest”; command `vagrant plugin install vagrant-vbguest`
3. Make, with `make` from the Virtual Micromagnetics software directory, with an Internet connection.

After time of the order of hours, you should find a *box file* at `./artefacts/virtualmicromagnetics-full-*.box`. If not, see *Troubleshooting* for more help. If so, congratulations on building your first Virtual Micromagnetics environment! This file represents your virtual environment, which you can share with other users. You can use this environment yourself by commanding the following in an empty directory:

```
vagrant init $PATH_TO_BOX_FILE
vagrant up --provider virtualbox
```


where `$PATH_TO_BOX_FILE` is the aforementioned artefact file. Now that you can create *virtual environments*, see *Developer Notes (valid for version 1.0.2)* to learn how to customise the software you place on them.

1.5 Developer Notes (valid for version 1.0.2)

In *Getting Started: As a Poweruser*, we created a virtual environment from scratch that can be shared with other users. Here, we show how you can completely specify your own environment. Knowledge of Ansible is needed, which can be gleaned from their excellent documentation at <http://docs.ansible.com/ansible/>.

1.5.1 Overview: The Build and Run Processes

This graph shows the operations involved in the build and run processes.



Lets break this down:

- Input Environment -> Developer's Virtual Machine: The input environment is a *virtual environment* containing only the operating system and few convenience tools. In development, Vagrant and VirtualBox create a *virtual machine* from this environment in the `create_vm` role (see *The Build Process*).

- Ansible Provisions: Vagrant commands Ansible to provision this machine using an Ansible playbook.
- Developer's Virtual Machine -> Output Environment: Vagrant then packages the virtual machine into a new virtual environment, which can be distributed to others. Tagged releases are uploaded by administrators to atlas.hashicorp.com, where they become available to all Vagrant users.
- Output Environment -> User's Virtual Machine: The previous steps are run in the build phase by a developer as the build process. This step represents the user following the instructions in *Getting Started: As a User* to create a virtual machine for themselves, which is referred to as the run process.

The run process performed by the user has been documented in *Getting Started: As a User*. Here we introduce the build process, which represents the other section of this diagram.

The Build Process

The build (make) process in step 3 in *Getting Started: As a Poweruser* allowed us to create a virtual environment. The Makefile in the software repository can build multiple targets. Each target runs Ansible on the `master.yml` playbook, which in turn runs the `create_vm` role in the `roles` directory. This creates a virtual machine and provisions it with the playbook passed as a command-line argument in `Makefile`, which lives in the `jobs` directory. It will also do some post-provisioning tasks using the `hookbook`, again passed as a command-line argument. The fundamental difference between the playbook and the hookbook is that the playbook is run on the guest virtual machine by vagrant, and the hookbook is run on the host machine. Different Makefile targets may place different build artefacts in the `artefacts` directory.

Roles add or configure software, playbooks describe the roles that must be enacted to provision the machine, hookbooks describe what to do with that machine (like creating a *box file*), and jobs are Makefile targets that produce certain machines.

To add a new environment, one needs to add a job that follows the pattern of existing jobs.

1.5.2 Where Things Are

In order to add jobs, one should edit `Makefile`. In order to do that, one would need to know where things are, hence the purpose of this section. The *virtual micromagnetics* repository is structured as follows:

- `Makefile`: This is the Makefile through which all jobs are conducted.
- `ansible.cfg` and `inventory.txt`: These files are used by Ansible when the `master.yml` playbook is run. They contain configuration information.
- `roles/`: This directory contains roles (obviously). Each role is given a subdirectory, and should not overlap. Each role directory contains tasks, and may also contain the subdirectories:
 - `vars/` (variable definitions),
 - `templates/` (files to duplicate to the guest virtual machine),
 - `meta/` (metadata, such as role dependencies),
 - `files/` (files used by tasks that aren't covered by the usecases of templates)
- `jobs/`: This directory contains playbooks and directories that can be thought of as jobs in `Makefile`. They are either provisioning playbooks, or post-provisioning hookbooks.
- `machines/`: This directory is created by `Makefile`, and houses the vagrant environment for each individual virtual machine. The provision process is recorded to a log file in the machine's directory (for example, the provision log for the lite build job exists in `machines/virtualmicromagnetics-lite/virtualmicromagnetics-lite.log`)
- `artefacts/`: This directory is created by `Makefile`, and houses build artefacts.

1.5.3 Examples

Create New Machine with Existing Software

Lets create a custom machine called doc-example, that contains Fidimag but no X server. Firstly, we add a target to Makefile (append the following to the Makefile):

```
# This target builds a virtual hard disk file containing an OOMMF and Fidimag
# installation.
doc-example:
    ansible-playbook master.yml -c local -i localhost, -v -k --extra-vars="vm_name=virtualmicromagnetics"
```

Now we need to describe what the state of the machine should be, by writing the playbook `jobs/provision_virtualmicromagnetics_doc-examples.yml`:

```
---
# This Ansible playbook is a provision playbook designed to be used with
# vagrant. This playbook provisions a machine suitable for micromagnetic
# simulation with Fidimag. It is executed by the virtual machine.

- hosts: all

  vars:
    vm_name: virtualmicromagnetics-doc-example

  roles:
    - fidimag
    - fidimag_examples
    - add_super_user
    - { role: set_hostname, HOSTNAME: {{ vm_name }} }
```

Now we are ready to build the environment by commanding (again, from the repository root directory):

```
make doc-example
```

This creates another *virtual environment* in the artefacts directory.

Adding Software

In *The Build Process*, we introduce roles. Roles can add new software to a *virtual environment*. By way of example, we can create a role to install Emacs (<https://www.gnu.org/software/emacs/>) from the Ubuntu software repository. We firstly create a directory structure:

```
# Create a role for Emacs.
mkdir --parents roles/emacs/tasks
```

Now we introduce some content using information from the Ansible documentation (<http://docs.ansible.com/ansible/>, and http://docs.ansible.com/ansible/apt_module.html). Write the following to `roles/emacs/tasks/main.yml`:

```
---
# This Ansible playbook installs Emacs.

- name: Install Emacs.
  apt:
    pkg=emacs
    state=latest
    update_cache=yes
    cache_valid_time=86400
  sudo: yes
```

This role, when run, will ensure that the latest version of Emacs and its dependencies are installed on the virtual machine, and updates the apt cache. Roles can be parameterised and have dependencies, which can cause them to become complicated. By way of example, installing Emacs on the new doc-example environment requires us to append the line:

```
- emacs
```

To clarify, `playbook jobs/provision_virtualmicromagnetics_doc-examples.yml` now looks like:

```
---
# This Ansible playbook is a provision playbook designed to be used with
# vagrant. This playbook provisions a machine suitable for micromagnetic
# simulation with fidimag. It is executed by the virtual machine.

- hosts: all

  vars:
    vm_name: virtualmicromagnetics-doc-example

  roles:
    - fidimag
    - fidimag_examples
    - add_super_user
    - { role: set_hostname, HOSTNAME: {{ vm_name }} }
    - emacs
```

Further Tinkering

We have explored how a new *virtual environment* can be created, and how new software can be added. In this section, we describe how the virtual machine itself can be configured using Vagrant's parameters. Vagrantfiles are files used by Vagrant written using Ruby syntax. These files specify parameters of the *virtual machine* created from a virtual environment. When running the commands in *Getting Started: As a User*, we create a Vagrantfile in the working directory that describes the virtual machine to Vagrant. Vagrantfiles can also be built into a virtual environment. Built-in Vagrantfiles can be found in `guest_resources/vagrantfiles`.

For example, if you wish to specify that 2048MB of memory must be used in the virtual machine created in *Create New Machine with Existing Software* ¹, we can add a builtin Vagrantfile at `guest_resources/vagrantfiles/Vagrantfile_virtualmicromagnetics-doc-example_builtin` with the following content:

```
VAGRANTFILE_API_VERSION = "2"

Vagrant.configure(VAGRANTFILE_API_VERSION) do |config|

  config.vm.provider :virtualbox do |vb|
    vb.memory = 2048
  end
end
```

This Vagrantfile will be detected by the hookbook and included automatically when the environment is packaged. For more information on Vagrantfiles, see the Vagrant documentation (<https://www.vagrantup.com/docs/vagrantfile/>).

1.5.4 Summary and Final Words

To summarise, *virtual environments* are created from an empty Ubuntu virtual machine after being provisioned and packaged. This build process allows the user to create a Virtual Micromagnetics *virtual machine* using Vagrant and

¹ Note that this is not such a good idea if you want to distribute your environment to different users, since they may have a different amount of available memory to you.

VirtualBox. We have also presented how a new environment can be created, how the software of that environment can be controlled, and how the virtual machines can be parameterised.

Thank you for using Virtual Micromagnetics! If you create roles for your favourite software, consider sharing them with the community. You can create a pull request at our GitHub repository at <https://github.com/computationalmodelling/virtualmicromagnetics>, or contacting Mark at mark.vousden@sjtu.ac.uk.

1.6 Troubleshooting

Currently there is not troubleshooting information for Virtual Micromagnetics. If you have an issue, please add it to our issue tracker at <https://github.com/computationalmodelling/virtualmicromagnetics/issues>, or email mark.vousden@sjtu.ac.uk. We will endeavour to resolve the issue and add it here if it is widespread.

1.7 Glossary

Box File A file used by *Vagrant* to create *Vagrant environments*. A box file represents a template from which *Virtual machines* can be created.

Host, Host Machine A machine that uses virtualisation software to host *virtual machines*. Host machines allocate resources, including memory and disk space, to support the running of a virtual machine. Note that a virtual machine can host other virtual machines, making it both a host and virtual machine.

Idempotent, Idempotency Idempotent *provisioning* runs only the commands required to achieve the desired state of the system. Commands that do not change the state are not run. This can save considerable build time when handling dependencies, because a dependency should not be downloaded and reinstalled if it is already in the state it should be in.

Manager, Vagrant Manager software provides an interface for managing *Virtual machines* from *Virtual environments*. Vagrant is an example of manager software, which provides a command-line interface to virtual machine management which can be automated. See *Managers*.

Vagrant Environment The directory structure (including *Vagrantfile*) created by Vagrant when `vagrant init` is commanded. A single virtual machine can be managed in a given environment.

Virtual Environment Virtual environments produce the same *virtual machine* on all virtualisation-capable computers. Virtual environments are also *box files*, but are not *Vagrant environments*.

Provider, Virtualiser, VirtualBox Provider (or virtualiser) software supports the creation of, and interaction with, *virtual machines* from a host machine. VirtualBox is an example of a free provider software. See *Providers*.

Provisioner, Provisioning, Ansible Provisioner software runs a set of commands on a machine, virtual or otherwise, to ensure it is in a particular state. Ansible is an example of provisioner software that enables *idempotent* provisioning. See *Provisioners*.

System Virtual Machine, Virtual Machine “An efficient, isolated duplicate of a real machine.”¹

Software that imitates certain other software on certain hardware. In this project, this includes a complete operating system, and a combination of one or many simulation packages and dependencies. General system virtual machines are described in brief at *Virtual Machines and Related Software*.

More strictly, a virtual machine is a specific instance of a *virtual environment*. When we build *box file* artefacts, we are creating *virtual environments*, not virtual machines. Once *Vagrant* creates a *Vagrant environment* from a

¹ Smith, J., Nair, R. (2005). “The Architecture of Virtual Machines”. *Computer* (IEEE Computer Society) 38 (5): 32–38. doi:10.1109/MC.2005.173

box file and `vagrant up` is commanded, a corresponding virtual machine is created. Virtual machines created on a *host* are managed by virtual machine *providers*, which typically list the machines they are maintaining.

Virtual Micromagnetics “Enabling accessible and reproducible micromagnetic simulation.”

The name of this project, which represents the collection of virtual environments and the software written to create them.

References




Fig. 1.1: OOMMF running in *Virtual Micromagnetics*.

A

Ansible, [12](#)

B

Box File, [12](#)

H

Host, [12](#)

Host Machine, [12](#)

I

Idempotency, [12](#)

Idempotent, [12](#)

M

Manager, [12](#)

P

Provider, [12](#)

Provisioner, [12](#)

Provisioning, [12](#)

S

System Virtual Machine, [12](#)

V

Vagrant, [12](#)

Vagrant Environment, [12](#)

Virtual Environment, [12](#)

Virtual Machine, [12](#)

Virtual Micromagnetics, [13](#)

VirtualBox, [12](#)

Virtualiser, [12](#)