

---

# **ansible-flow Documentation**

***Release 0.2.0***

**John Vrbanac**

**Apr 26, 2017**



---

## Contents

---

<b>1</b>	<b>Contents:</b>	<b>3</b>
1.1	Installing ansible-flow . . . . .	3
1.2	Configuration . . . . .	3
1.3	Using ansible-flow . . . . .	6
<b>2</b>	<b>Links:</b>	<b>7</b>
<b>3</b>	<b>Indices and tables</b>	<b>9</b>



Ansible-flow is a simple utility to help make ansible easier to use with a specific set of production use-cases.

If you need to do the following, then ansible-flow might be for you:

- Use the same playbooks against multiple environments
- Use bastions in your deployment
- Run a collection of playbooks in sequence.



# CHAPTER 1

---

## Contents:

---

## Installing ansible-flow

ansible-flow is available on PyPI and can be installed using:

```
pip install ansible-flow
```

## Configuration

ansible-flow looks for a `project.yml` file within the executing directory.

Each `project.yml` file contains three different sections:

- requirements
- environments
- targets

## Requirements

The requirements section is where you define any python requirements (in a list) that you will need to execute your ansible playbooks. For simple use-cases you should only need to define `ansible` or `ansible==2.1.0`.

Example:

```
requirements:
- ansible==2.1.0
```

## Environments

The environments section is where you define specific for custom variable files, vault keys, and ansible configuration files on a per environment basis.

If you have a number of common values that you'd like to share across environments, then you can specify a `default` environment. If a `default` environment is specified then all other environments will just layer their settings on-top of the `default`.

### Per Environment Options

- `vault-key`: Path to your vault password file
- `custom-var-files`: A list of YAML files to load when executing your playbooks. You can also use file globs in each entry.
- `directory`: A base directory for your `custom-var-files`
- `ansible-config`: Path to a ansible configuration file
- `shell-variables`: Key value pairs of environmental variables to be used when executing ansible

### Example

A environments section containing two different environments each with a file encrypted with two different vault keys.

#### Directory Structure

```
envs/dev/  
  - general.yml  
  - auth.vault.yml  
envs/test/  
  - general.yml  
  - auth.vault.yml  
dev-vault-key  
test-vault-key  
project.yml
```

#### Environments section of `project.yml`

```
environments:  
  default:  
    custom-var-files:  
      - general.yml  
      - auth.vault.yml  
  dev:  
    directory: ./envs/dev  
    vault-key: ./dev-vault-key  
  test:  
    directory: ./envs/test  
    vault-key: ./test-vault-key
```

## Targets

The targets section allows for you to define a set of playbooks to be executed.



## Per Target Options

- `playbooks`: A list of playbooks to be executed in sequential order.
- `inventory`: The inventory script or ini file you wish to use.
- `tags`: Tags you wish to pass to ansible
- `ansible-options`: Custom cli arguments for ansible-playbook

## Example

```
targets:
  ping:
    playbooks:
      - ping.yml
    inventory: ./inventory.ini
  bootstrap:
    playbooks:
      - bootstrap.yml
      - 2fa.yml
    inventory: ./inventory.ini
```

## Example Configuration

```
---
requirements:
  - ansible==2.1.0

environments:
  default:
    custom-var-files:
      - general.yml
      - auth.vault.yml
  dev:
    directory: ./envs/dev
    vault-key: ./dev-vault-key
  test:
    directory: ./envs/test
    vault-key: ./test-vault-key

targets:
  ping:
    playbooks:
      - ping.yml
    inventory: ./inventory.ini
  bootstrap:
    playbooks:
      - bootstrap.yml
      - 2fa.yml
    inventory: ./inventory.ini
```

## Using ansible-flow

### Project virtual environment for ansible-flow

ansible-flow will execute all of its actions under a virtual environment. This allows for you to pin specific versions ansible and any other dependencies. ansible-flow can maintain the virtual environment for you using the venv sub-command.

---

**Note:** The packages installed into the virtual environment are defined in the requirements section of your `project.yml`

---

### Working with ansible-flow's venv sub-command

```
# Create a fresh virtual environment
ansible-flow venv create

# Recreates the virtual environment (commonly used when you change dependencies)
ansible-flow venv recreate

# Completely deletes the virtual environment
ansible-flow venv delete
```

## Running ansible-flow

Assuming you've written your `project.yml` configuration, you can execute a target against a given environment using the following command:

```
ansible-flow run ping --env dev
```

---

**Note:** ansible-flow is not affiliated with the ansible project in any way.

---

## CHAPTER 2

---

Links:

---

- GitHub: <https://github.com/jmvrbanac/ansible-flow>



## CHAPTER 3

---

### Indices and tables

---

- `genindex`
- `modindex`
- `search`