

---

# **Backend.AI Client SDK for Python Documentation**

*Release 20.03.0b1*

**Lablup Inc.**

**Apr 02, 2020**



# GETTING STARTED

<b>1 Quickstart</b>	<b>3</b>
<b>2 Getting Started</b>	<b>5</b>
2.1 Installation	5
2.1.1 Linux/macOS	5
2.1.2 Windows	6
2.1.3 Verification	6
2.2 Client Configuration	6
<b>3 Command-line Interface</b>	<b>9</b>
3.1 Configuration	9
3.1.1 Session Mode	9
3.1.2 API Mode	9
3.1.3 Checking out the current configuration	10
3.2 Compute Sessions	10
3.2.1 Listing sessions	10
3.2.2 Running simple sessions	11
3.2.3 Running sessions with accelerators	12
3.2.4 Terminating or cancelling sessions	12
3.3 Container Applications	13
3.3.1 Starting a session and connecting to its Jupyter Notebook	13
3.3.2 Accessing sessions via a web terminal	13
3.3.3 Accessing sessions via native SSH/SFTP	14
3.4 Storage Management	15
3.4.1 Creating vfolders and managing them	15
3.4.2 File transfers and management	16
3.4.3 Running sessions with storages	16
3.4.4 Creating default files for kernels	17
3.5 Advanced Code Execution	17
3.5.1 Running concurrent experiment sessions	17
3.6 Session Templates	18
3.6.1 Creating and starting session template	18

3.6.2	Full syntax for task template . . . . .	20
<b>4</b>	<b>Developer Reference</b>	<b>21</b>
4.1	Developer Guides . . . . .	21
4.1.1	Client Session . . . . .	21
4.1.2	Examples . . . . .	25
	Synchronous-mode execution . . . . .	25
	Asynchronous-mode Execution . . . . .	27
4.1.3	Testing . . . . .	29
	Unit Tests . . . . .	29
	Integration Tests . . . . .	29
4.2	High-level Function Reference . . . . .	30
4.2.1	Admin Functions . . . . .	30
4.2.2	Agent Functions . . . . .	31
4.2.3	Auth Functions . . . . .	32
4.2.4	Configuration . . . . .	32
4.2.5	KeyPair Functions . . . . .	35
4.2.6	Manager Functions . . . . .	36
4.2.7	Scaling Group Functions . . . . .	37
4.2.8	ComputeSession Functions . . . . .	39
4.2.9	Session Template Functions . . . . .	45
4.2.10	Virtual Folder Functions . . . . .	46
4.3	Low-level SDK Reference . . . . .	47
4.3.1	Base Function . . . . .	47
4.3.2	Request API . . . . .	47
4.3.3	Exceptions . . . . .	50
4.3.4	Miscellaneous Utilities . . . . .	50
<b>5</b>	<b>Indices and tables</b>	<b>51</b>
	<b>Python Module Index</b>	<b>53</b>
	<b>Index</b>	<b>55</b>

This is the documentation for the Python Client SDK which implements [the Backend.AI API](#).



**QUICKSTART**

Python 3.6 or higher is required.

You can download [its official installer from python.org](#), or use a 3rd-party package/version manager such as [homebrew](#), [miniconda](#), or [pyenv](#). It works on Linux, macOS, and Windows.

We recommend to create a virtual environment for isolated, unobtrusive installation of the client SDK library and tools.

```
$ python3 -m venv venv-backend-ai
$ source venv-backend-ai/bin/activate
(venv-backend-ai) $
```

Then install the client library from PyPI.

```
(venv-backend-ai) $ pip install -U pip setuptools
(venv-backend-ai) $ pip install backend.ai-client
```

Set your API keypair as environment variables:

```
(venv-backend-ai) $ export BACKEND_ACCESS_KEY=AKIA...
(venv-backend-ai) $ export BACKEND_SECRET_KEY=...
```

And then try the first commands:

```
(venv-backend-ai) $ backend.ai --help
...
(venv-backend-ai) $ backend.ai ps
...
```

Check out more details about [client configuration](#), the command-line examples, and [SDK code examples](#).





**GETTING STARTED****2.1 Installation****2.1.1 Linux/macOS**

We recommend using [pyenv](#) to manage your Python versions and virtual environments to avoid conflicts with other Python applications.

Create a new virtual environment (Python 3.6 or higher) and activate it on your shell. Then run the following commands:

```
pip install -U pip setuptools
pip install -U backend.ai-client-py
```

Create a shell script `my-backendai-env.sh` like:

```
export BACKEND_ACCESS_KEY=...
export BACKEND_SECRET_KEY=...
export BACKEND_ENDPOINT=https://my-precious-cluster
export BACKEND_ENDPOINT_TYPE=api
```

Run this shell script before using `backend.ai` command.

---

**Note:** The console-server users should set `BACKEND_ENDPOINT_TYPE` to `session`. For details, check out [the client configuration document](#).

---

### 2.1.2 Windows

We recommend using [the Anaconda Navigator](#) to manage your Python environments with a slick GUI app.

Create a new environment (Python 3.6 or higher) and launch a terminal (command prompt). Then run the following commands:

```
python -m pip install -U pip setuptools
python -m pip install -U backend.ai-client-py
```

Create a batch file `my-backendai-env.bat` like:

```
chcp 65001
set PYTHONIOENCODING=UTF-8
set BACKEND_ACCESS_KEY=...
set BACKEND_SECRET_KEY=...
set BACKEND_ENDPOINT=https://my-precious-cluster
set BACKEND_ENDPOINT_TYPE=api
```

Run this batch file before using `backend.ai` command.

Note that this batch file switches your command prompt to use the UTF-8 codepage for correct display of special characters in the console logs.

### 2.1.3 Verification

Run `backend.ai ps` command and check if it says “there is no compute sessions running” or something similar.

If you encounter error messages about “ACCESS\_KEY”, then check if your batch/shell scripts have the correct environment variable names.

If you encounter network connection error messages, check if the endpoint server is configured correctly and accessible.

## 2.2 Client Configuration

The configuration for Backend.AI API includes the endpoint URL prefix, API keypairs (access and secret keys), and a few others.

There are two ways to set the configuration:

1. Setting environment variables before running your program that uses this SDK. This applies to the command-line interface as well.
2. Manually creating *APIConfig* instance and creating sessions with it.

The list of configurable environment variables are:

- `BACKEND_ENDPOINT`
- `BACKEND_ENDPOINT_TYPE`
- `BACKEND_ACCESS_KEY`
- `BACKEND_SECRET_KEY`
- `BACKEND_VFOLDER_MOUNTS`

Please refer the parameter descriptions of *APIConfig*'s constructor for what each environment variable means and what value format should be used.



## COMMAND-LINE INTERFACE

### 3.1 Configuration

---

**Note:** Please consult the detailed usage in the help of each command (use `-h` or `--help` argument to display the manual).

---

Check out [the client configuration](#) for configurations via environment variables.

#### 3.1.1 Session Mode

When the endpoint type is "session", you must explicitly login and logout into/from the console server.

```
$ backend.ai login
Username: myaccount@example.com
Password:
✓ Login succeeded.

$ backend.ai ... # any commands

$ backend.ai logout
✓ Logout done.
```

#### 3.1.2 API Mode

After setting up the environment variables, just run any command:

```
$ backend.ai ...
```

### 3.1.3 Checking out the current configuration

Run the following command to list your current active configurations.

```
$ backend.ai config
```

## 3.2 Compute Sessions

---

**Note:** Please consult the detailed usage in the help of each command (use `-h` or `--help` argument to display the manual).

---

### 3.2.1 Listing sessions

List the session owned by you with various status filters. The most recently status-changed sessions are listed first. To prevent overloading the server, the result is limited to the first 10 sessions and it provides a separate `--all` option to paginate further sessions.

```
backend.ai ps
```

The `ps` command is an alias of the following `admin sessions` command. If you have the administrator privilege, you can list sessions owned by other users by adding `--access-key` option here.

```
backend.ai admin sessions
```

Both commands offer options to set the status filter as follows. For other options, please consult the output of `--help`.

Option	Included Session Status
(no option)	PENDING, PREPARING, RUNNING, RESTARTING, TERMINATING, RESIZING, SUSPENDED, and ERROR.
<code>--running</code>	PREPARING, PULLING, and RUNNING.
<code>--dead</code>	CANCELLED and TERMINATED.

Both commands offer options to specify which fields of sessions should be printed as follows.

Option	Included Session Fields
(no option)	Session ID, Owner, Image, Type, Status, Status Info, Last updated, and Result.
--id-only	Session ID.
--detail	Session ID, Owner, Image, Type, Status, Status Info, Last updated, Result, Tag, Created At, Occupied Resource, Used Memory (MiB), Max Used Memory (MiB), and CPU Using (%).
-f, --format	Specified fields by user.

---

**Note:** Fields for -f/--format option can be displayed by specifying comma-separated parameters.

Available parameters for this option are: id, status, status\_info, created\_at, last\_updated, result, image, type, task\_id, tag, occupied\_slots, used\_memory, max\_used\_memory, cpu\_using.

For example:

```
backend.ai admin session --format id,status,cpu_using
```

---

### 3.2.2 Running simple sessions

The following command spawns a Python session and executes the code passed as -c argument immediately. --rm option states that the client automatically terminates the session after execution finishes.

```
backend.ai run --rm -c 'print("hello world")' python:3.6-ubuntu18.04
```

---

**Note:** By default, you need to specify language with full version tag like python:3.6-ubuntu18.04. Depending on the Backend.AI admin's language alias settings, this can be shortened just as python. If you want to know defined language aliases, contact the admin of Backend.AI server.

---

The following command spawns a Python session and executes the code passed as ./myscript.py file, using the shell command specified in the --exec option.

```
backend.ai run --rm --exec 'python myscript.py arg1 arg2' \  
python:3.6-ubuntu18.04 ./myscript.py
```

Please note that your run command may hang up for a very long time due to queueing when the cluster resource is not sufficiently available.

To avoid indefinite waiting, you may add `--enqueue-only` to return immediately after posting the session creation request.

---

**Note:** When using `--enqueue-only`, the codes are *NOT* executed and relevant options are ignored. This makes the run command to the same of the start command.

---

Or, you may use `--max-wait` option to limit the maximum waiting time. If the session starts within the given `--max-wait` seconds, it works normally, but if not, it returns without code execution like when used `--enqueue-only`.

To watch what is happening behind the scene until the session starts, try `backend.ai events <sessionID>` to receive the lifecycle events such as its scheduling and preparation steps.

### 3.2.3 Running sessions with accelerators

Use one or more `-r` options to specify resource requirements when using `backend.ai run` and `backend.ai start` commands.

For instance, the following command spawns a Python TensorFlow session using a half of virtual GPU device, 4 CPU cores, and 8 GiB of the main memory to execute `./mygpucode.py` file inside it.

```
backend.ai run --rm \  
    -r cpu=4 -r mem=8g -r cuda.shares=2 \  
    python-tensorflow:1.12-py36 ./mygpucode.py
```

### 3.2.4 Terminating or cancelling sessions

Without `--rm` option, your session remains alive for a configured amount of idle timeout (default is 30 minutes). You can see such sessions using the `backend.ai ps` command. Use the following command to manually terminate them via their session IDs. You may specify multiple session IDs to terminate them at once.

```
backend.ai rm <sessionID> [<sessionID>...]
```

If you terminate PENDING sessions which are not scheduled yet, they are cancelled.



## 3.3 Container Applications

---

**Note:** Please consult the detailed usage in the help of each command (use `-h` or `--help` argument to display the manual).

---

### 3.3.1 Starting a session and connecting to its Jupyter Notebook

The following command first spawns a Python session named “mysession” without running any code immediately, and then executes a local proxy which connects to the “jupyter” service running inside the session via the local TCP port 9900. The `start` command shows application services provided by the created compute session so that you can choose one in the subsequent `app` command. In the `start` command, you can specify detailed resource options using `-r` and storage mounts using `-m` parameter.

```
backend.ai start -t mysession python
backend.ai app -b 9900 mysession jupyter
```

Once executed, the `app` command waits for the user to open the displayed address using appropriate application. For the jupyter service, use your favorite web browser just like the way you use Jupyter Notebooks. To stop the `app` command, press `Ctrl+C` or send the `SIGINT` signal.

### 3.3.2 Accessing sessions via a web terminal

All Backend.AI sessions expose an intrinsic application named “ttyd”. It is a web application that embeds xterm.js-based full-screen terminal that runs on web browsers.

```
backend.ai start -t mysession ...
backend.ai app -b 9900 mysession ttyd
```

Then open `http://localhost:9900` to access the shell in a fully functional web terminal using browsers. The default shell is `/bin/bash` for Ubuntu/CentOS-based images and `/bin/ash` for Alpine-based images with a fallback to `/bin/sh`.

**Note:** This shell access does *NOT* grant your root access. All compute session processes are executed as the user privilege.

---

### 3.3.3 Accessing sessions via native SSH/SFTP

Backend.AI offers direct access to compute sessions (containers) via SSH and SFTP, by auto-generating host identity and user keypairs for all sessions. All Backend.AI sessions expose an intrinsic application named "sshd" like "ttyd".

To connect your sessions with SSH, first prepare your session and download an auto-generated SSH keypair named `id_container`. Then start the service port proxy ("app" command) to open a local TCP port that proxies the SSH/SFTP traffic to the compute sessions:

```
$ backend.ai start -t mysess ...
$ backend.ai download mysess id_container
$ mv id_container ~/.ssh
$ backend.ai app mysess sshd -b 9922
```

In another terminal on the same PC, run your ssh client like:

```
$ ssh -o StrictHostKeyChecking=no \
> -o UserKnownHostsFile=/dev/null \
> -i ~/.ssh/id_container \
> work@localhost -p 9922
Warning: Permanently added '[127.0.0.1]:9922' (RSA) to the list of known hosts.
f310e8dbce83:~$
```

This SSH port is also compatible with SFTP to browse the container's filesystem and to upload/download large-sized files.

You could add the following to your `~/.ssh/config` to avoid type extra options every time.

```
Host localhost
  User work
  IdentityFile ~/.ssh/id_container
  StrictHostKeyChecking no
  UserKnownHostsFile /dev/null
```

```
$ ssh localhost -p 9922
```

**Warning:** Since the SSH keypair is auto-generated every time when you launch a new compute session, you need to download and keep it separately for each session.

To use your own SSH private key across all your sessions without downloading the auto-generated one every time, create a vfolder named `.ssh` and put the `authorized_keys` file that includes the public key. The keypair and `.ssh` directory permissions will be automatically updated by Backend.AI when the session launches.

```
$ ssh-keygen -t rsa -b 2048 -f id_container
$ cat id_container.pub > authorized_keys
$ backend.ai vfolder create .ssh
$ backend.ai vfolder upload .ssh authorized_keys
```

## 3.4 Storage Management

---

**Note:** Please consult the detailed usage in the help of each command (use `-h` or `--help` argument to display the manual).

---

Backend.AI abstracts shared network storages into per-user slices called “**virtual folders**” (aka “**vfolders**”), which can be shared between users and user group members.

### 3.4.1 Creating vfolders and managing them

The command-line interface provides a set of subcommands under `backend.ai vfolder` to manage vfolders and files inside them.

To list accessible vfolders including your own ones and those shared by other users:

```
$ backend.ai vfolder list
```

To create a virtual folder named “mydata1”:

```
$ backend.ai vfolder create mydata1 mynas
```

The second argument `mynas` corresponds to the name of a storage host. To list up storage hosts that you are allowed to use:

```
$ backend.ai vfolder list-hosts
```

To delete the vfolder completely:

```
$ backend.ai vfolder delete mydata1
```

### 3.4.2 File transfers and management

To upload a file from the current working directory into the vfolder:

```
$ backend.ai vfolder upload mydata1 ./bigdata.csv
```

To download a file from the vfolder into the current working directory:

```
$ backend.ai vfolder download mydata1 ./bigresult.txt
```

To list files in the vfolder's specific path:

```
$ backend.ai vfolder ls mydata1 .
```

To delete files in the vfolder:

```
$ backend.ai vfolder rm mydata1 ./bigdata.csv
```

**Warning:** All file uploads and downloads overwrite existing files and all file operations are irreversible.

### 3.4.3 Running sessions with storages

The following command spawns a Python session where the virtual folder "mydata1" is mounted. The execution options are omitted in this example. Then, it downloads ./bigresult.txt file (generated by your code) from the "mydata1" virtual folder.

```
$ backend.ai vfolder upload mydata1 ./bigdata.csv  
$ backend.ai run --rm -m mydata1 python:3.6-ubuntu18.04 ...  
$ backend.ai vfolder download mydata1 ./bigresult.txt
```

In your code, you may access the virtual folder via /home/work/mydata1 (where the default current working directory is /home/work) just like a normal directory.

By reusing the same vfolder in subsequent sessions, you do not have to download the result and upload it as the input for next sessions, just keeping them in the storage.

### 3.4.4 Creating default files for kernels

Backend.AI has a feature called 'dotfile', created to all the kernels user spawns. As you can guess, dotfile's path should start with `..`. The following command creates dotfile named `.aws/config` with permission `755`. This file will be created under `/home/work` every time user spawns Backend.AI kernel.

```
$ backend.ai dotfile create .aws/config < ~/.aws/config
```

## 3.5 Advanced Code Execution

---

**Note:** Please consult the detailed usage in the help of each command (use `-h` or `--help` argument to display the manual).

---

### 3.5.1 Running concurrent experiment sessions

In addition to single-shot code execution as described in *Running simple sessions*, the `run` command offers concurrent execution of multiple sessions with different parameters interpolated in the execution command specified in `--exec` option and environment variables specified as `-e` / `--env` options.

To define variables interpolated in the `--exec` option, use `--exec-range`. To define variables interpolated in the `--env` options, use `--env-range`.

Here is an example with environment variable ranges that expands into 4 concurrent sessions.

```
backend.ai run -c 'import os; print("Hello world, {}".format(os.environ["CASENO"]))' \
→ ' \
  -r cpu=1 -r mem=256m \
  -e 'CASENO=$X' \
  --env-range=X=case:1,2,3,4 \
  lablup/python:3.6-ubuntu18.04
```

Both range options accept a special form of argument: "range expressions". The front part of range option value consists of the variable name used for interpolation and an equivalence sign (=). The rest of range expressions have the following three types:

Expression	Interpretation
case:CASE1, CASE2, ..., CASEN	A list of discrete values. The values may be either string or numbers.
linspace:START, STOP,POINTS	An inclusive numerical range with discrete points, in the same way of <code>numpy.linspace()</code> . For example, <code>linspace:1,2,3</code> generates a list of three values: 1, 1.5, and 2.
range:START, STOP,STEP	A numerical range with the same semantics of Python's <code>range()</code> . For example, <code>range:1,6,2</code> generates a list of values: 1, 3, and 5.

If you specify multiple occurrences of range options in the run command, the client spawns sessions for *all possible combinations* of all values specified by each range.

---

**Note:** When your resource limit and cluster's resource capacity cannot run all spawned sessions at the same time, some of sessions may be queued and the command may take a long time to finish.

---

**Warning:** Until all cases finish, the client must keep its network connections to the server alive because this feature is implemented in the client-side. Server-side batch job scheduling is under development!

## 3.6 Session Templates

### 3.6.1 Creating and starting session template

Users may define commonly used set of session creation parameters as reusable templates.

A session template includes common session parameters such as resource slots, vfolder mounts, the kernel iamge to use, and etc. It also support an extra feature that automatically clones a Git repository upon startup as a bootstrap command.

The following sample shows how a session template looks like:

```
---
api_version: v1
kind: taskTemplate
metadata:
  name: template1234
  tag: example-tag
spec:
  kernel:
```

(continues on next page)

(continued from previous page)

```
environ:
  MYCONFIG: XXX
git:
  branch: '19.09'
  commit: 10daee9e328876d75e6d0fa4998d4456711730db
  repository: https://github.com/lablup/backend.ai-agent
  destinationDir: /home/work/baiagent
  image: python:3.6-ubuntu18.04
resources:
  cpu: '2'
  mem: 4g
mounts:
  hostpath-test: /home/work/hostDesktop
  test-vfolder:
sessionType: interactive
```

The `backend.ai sesstpl` command set provides the basic CRUD operations of user-specific session templates.

The `create` command accepts the YAML content either piped from the standard input or read from a file using `-f` flag:

```
$ backend.ai sesstpl create < session-template.yaml
# -- or --
$ backend.ai sesstpl create -f session-template.yaml
```

Once the session template is uploaded, you may use it to start a new session:

```
$ backend.ai start-template <templateId>
```

with substituting `<templateId>` to your template ID.

Other CRUD command examples are as follows:

```
$ backend.ai sesstpl update <templateId> < session-template.yaml
$ backend.ai sesstpl list
$ backend.ai sesstpl get <templateId>
$ backend.ai sesstpl delete <templateId>
```

### 3.6.2 Full syntax for task template

```
---
api_version or apiVersion: str, required
kind: Enum['taskTemplate', 'task_template'], required
metadata: required
  name: str, required
  tag: str (optional)
spec:
  type or sessionType: Enum['interactive', 'batch'] (optional), default=interactive
  kernel:
    image: str, required
    environ: map[str, str] (optional)
    run: (optional)
      bootstrap: str (optional)
      stratup or startup_command or startupCommand: str (optional)
    git: (optional)
      repository: str, required
      commit: str (optional)
      branch: str (optional)
      credential: (optional)
        username: str
        password: str
      destination_dir or destinationDir: str (optional)
  mounts: map[str, str] (optional)
  resources: map[str, str] (optional)
```



**DEVELOPER REFERENCE**

## 4.1 Developer Guides

### 4.1.1 Client Session

This module is the first place to begin with your Python programs that use Backend.AI API functions.

The high-level API functions cannot be used alone – you must initiate a client session first because each session provides *proxy attributes* that represent API functions and run on the session itself.

To achieve this, during initialization session objects internally construct new types by combining the `BaseFunction` class with the attributes in each API function classes, and makes the new types bound to itself. Creating new types every time when creating a new session instance may look weird, but it is the most convenient way to provide *class-methods* in the API function classes to work with specific *session instances*.

When designing your application, please note that session objects are intended to live long following the process' lifecycle, instead of to be created and disposed whenever making API requests.

**class** `ai.backend.client.session.BaseSession(*, config=None)`

The base abstract class for sessions.

**abstractmethod** `close()`

Terminates the session and releases underlying resources.

**closed**

Checks if the session is closed.

**Return type** `bool`

**config**

The configuration used by this session object.

**class** `ai.backend.client.session.Session(*, config=None)`

An API client session that makes API requests synchronously. You may call (almost)

all function proxy methods like a plain Python function. It provides a context manager interface to ensure closing of the session upon errors and scope exits.

**System**

The System function proxy bound to this session.

**Admin**

The Admin function proxy bound to this session.

**Agent**

The Agent function proxy bound to this session.

**AgentWatcher**

The AgentWatcher function proxy bound to this session.

**Auth**

The Auth function proxy bound to this session.

**EtcConfig**

The EtcConfig function proxy bound to this session.

**Domain**

The Domain function proxy bound to this session.

**Group**

The Group function proxy bound to this session.

**Image**

The Image function proxy bound to this session.

**ComputeSession**

The ComputeSession function proxy bound to this session.

**KeyPair**

The KeyPair function proxy bound to this session.

**Manager**

The Manager function proxy bound to this session.

**Resource**

The Resource function proxy bound to this session.

**KeypairResourcePolicy**

The KeypairResourcePolicy function proxy bound to this session.

**User**

The User function proxy bound to this session.

**closed**

Checks if the session is closed.

**Return type** `bool`

**config**

The configuration used by this session object.

**ScalingGroup**

The ScalingGroup function proxy bound to this session.

**SessionTemplate**

The SessionTemplate function proxy bound to this session.

**VFolder**

The VFolder function proxy bound to this session.

**Dotfile**

The Dotfile function proxy bound to this session.

**close()**

Terminates the session. It schedules the `close()` coroutine of the underlying aiohttp session and then enqueues a sentinel object to indicate termination. Then it waits until the worker thread to self-terminate by joining.

**worker\_thread**

The thread that internally executes the asynchronous implementations of the given API functions.

**class** `ai.backend.client.session.AsyncSession(*, config=None)`

An API client session that makes API requests asynchronously using coroutines. You may call all function proxy methods like a coroutine. It provides an async context manager interface to ensure closing of the session upon errors and scope exits.

**closed**

Checks if the session is closed.

**Return type** `bool`

**config**

The configuration used by this session object.

**System**

The System function proxy bound to this session.

**Admin**

The Admin function proxy bound to this session.

**Agent**

The Agent function proxy bound to this session.

**AgentWatcher**

The AgentWatcher function proxy bound to this session.

**Auth**

The Auth function proxy bound to this session.

**EtcConfig**

The EtcConfig function proxy bound to this session.

**Group**

The Group function proxy bound to this session.

**Image**

The Image function proxy bound to this session.

**ComputeSession**

The ComputeSession function proxy bound to this session.

**KeyPair**

The KeyPair function proxy bound to this session.

**Manager**

The Manager function proxy bound to this session.

**Resource**

The Resource function proxy bound to this session.

**KeypairResourcePolicy**

The KeypairResourcePolicy function proxy bound to this session.

**User**

The User function proxy bound to this session.

**ScalingGroup**

The ScalingGroup function proxy bound to this session.

**SessionTemplate**

The SessionTemplate function proxy bound to this session.

**VFolder**

The VFolder function proxy bound to this session.

**Dotfile**

The Dotfile function proxy bound to this session.

**await close()**

Terminates the session and releases underlying resources.

## 4.1.2 Examples

### Synchronous-mode execution

#### Query mode

This is the minimal code to execute a code snippet with this client SDK.

```
import sys
from ai.backend.client import Session

with Session() as session:
    kern = session.ComputeSession.get_or_create('python:3.6-ubuntu18.04')
    code = 'print("hello world")'
    mode = 'query'
    run_id = None
    while True:
        result = kern.execute(run_id, code, mode=mode)
        run_id = result['runId'] # keeps track of this particular run loop
        for rec in result.get('console', []):
            if rec[0] == 'stdout':
                print(rec[1], end='', file=sys.stdout)
            elif rec[0] == 'stderr':
                print(rec[1], end='', file=sys.stderr)
            else:
                handle_media(rec)
        sys.stdout.flush()
        if result['status'] == 'finished':
            break
        else:
            mode = 'continued'
            code = ''
    kern.destroy()
```

You need to take care of `client_token` because it determines whether to reuse kernel sessions or not. Backend.AI cloud has a timeout so that it terminates long-idle kernel sessions, but within the timeout, any kernel creation requests with the same `client_token` let Backend.AI cloud to reuse the kernel.

## Batch mode

You first need to upload the files after creating the session and construct a `opts` struct.

```
import sys
from ai.backend.client import Session

with Session() as session:
    kern = session.ComputeSession.get_or_create('python:3.6-ubuntu18.04')
    kern.upload(['mycode.py', 'setup.py'])
    code = ''
    mode = 'batch'
    run_id = None
    opts = {
        'build': '*', # calls "python setup.py install"
        'exec': 'python mycode.py arg1 arg2',
    }
    while True:
        result = kern.execute(run_id, code, mode=mode, opts=opts)
        opts.clear()
        run_id = result['runId']
        for rec in result.get('console', []):
            if rec[0] == 'stdout':
                print(rec[1], end='', file=sys.stdout)
            elif rec[0] == 'stderr':
                print(rec[1], end='', file=sys.stderr)
            else:
                handle_media(rec)
        sys.stdout.flush()
        if result['status'] == 'finished':
            break
        else:
            mode = 'continued'
            code = ''
    kern.destroy()
```

## Handling user inputs

Inside the while-loop for `kern.execute()` above, change the if-block for `result['status']` as follows:

```
...
if result['status'] == 'finished':
    break
elif result['status'] == 'waiting-input':
```

(continues on next page)

(continued from previous page)

```

mode = 'input'
if result['options'].get('is_password', False):
    code = getpass.getpass()
else:
    code = input()
else:
    mode = 'continued'
    code = ''
...

```

A common gotcha is to miss setting `mode = 'input'`. Be careful!

## Handling multi-media outputs

The `handle_media()` function used above examples would look like:

```

def handle_media(record):
    media_type = record[0] # MIME-Type string
    media_data = record[1] # content
    ...

```

The exact method to process `media_data` depends on the `media_type`. Currently the following behaviors are well-defined:

- For (binary-format) images, the content is a dataURI-encoded string.
- For SVG (scalable vector graphics) images, the content is an XML string.
- For `application/x-sorna-drawing`, the content is a JSON string that represents a set of vector drawing commands to be replayed the client-side (e.g., Javascript on browsers)

## Asynchronous-mode Execution

The `async` version has all `sync`-version interfaces as coroutines but comes with additional features such as `stream_execute()` which streams the execution results via websockets and `stream_ptty()` for interactive terminal streaming.

```

import asyncio
import json
import sys
import aiohttp
from ai.backend.client import AsyncSession

async def main():

```

(continues on next page)

(continued from previous page)

```
async with AsyncSession() as session:
    kern = await session.ComputeSession.get_or_create('python:3.6-ubuntu18.04',
                                                    client_token='mysession')

    code = 'print("hello world")'
    mode = 'query'
    async with kern.stream_execute(code, mode=mode) as stream:
        # no need for explicit run_id since WebSocket connection represents it!
        async for result in stream:
            if result.type != aiohttp.WSMsgType.TEXT:
                continue
            result = json.loads(result.data)
            for rec in result.get('console', []):
                if rec[0] == 'stdout':
                    print(rec[1], end='', file=sys.stdout)
                elif rec[0] == 'stderr':
                    print(rec[1], end='', file=sys.stderr)
                else:
                    handle_media(rec)
            sys.stdout.flush()
            if result['status'] == 'finished':
                break
            elif result['status'] == 'waiting-input':
                mode = 'input'
                if result['options'].get('is_password', False):
                    code = getpass.getpass()
                else:
                    code = input()
                await stream.send_text(code)
            else:
                mode = 'continued'
                code = ''
        await kern.destroy()

loop = asyncio.get_event_loop()
try:
    loop.run_until_complete(main())
finally:
    loop.stop()
```

New in version 1.5.



### 4.1.3 Testing

#### Unit Tests

Unit tests perform function-by-function tests to ensure their individual functionality. This test suite runs without depending on the server-side and thus it is executed in Travis CI for every push.

#### How to run

```
$ python -m pytest -m 'not integration' tests
```

#### Integration Tests

Integration tests combine multiple invocations of high-level interfaces to make underlying API requests to a running gateway server to test the full functionality of the client as well as the manager.

They are marked as “integration” using the `@pytest.mark.integration` decorator to each test case.

**Warning:** The integration tests actually make changes to the target gateway server and agents. If some tests fail, those changes may remain in an inconsistent state and requires a manual recovery such as resetting the database and populating fixtures again, though the test suite tries to clean up them properly.

So, DO NOT RUN it against your production server.

#### Prerequisite

Please refer the README of the manager and agent repositories to set up them. To avoid an indefinite waiting time for pulling Docker images:

- (manager) `python -m ai.backend.manager.cli etcd rescan-images`
- (agent) `docker pull`
  - `lablup/python:3.6-ubuntu18.04`
  - `lablup/lua:5.3-alpine3.8`

The manager must also have at least the following active suerp-admin account in the default domain and the default group.

- Example super-admin account:
  - User ID: admin@lablup.com
  - Password wJalrXUt
  - Access key: AKIAIOSFODNN7EXAMPLE
  - Secret key: wJalrXUtnFEMI/K7MDENG/bPxRfiCYEXAMPLEKEY

One or more testing-XXXX domain, one or more testing-XXXX groups, and one ore more dummy users are created and used during the tests and destroyed after running tests. XXXX will be filled with random identifiers.

---

**Tip:** The *halfstack* configuration and the `example-keypairs.json` fixture is compatible with this integration test suite.

---

### How to run

Execute the gateway and at least one agent in their respective virtualenvs and hosts:

```
$ python -m ai.backend.client.gateway.server
$ python -m ai.backend.client.agent.server
$ python -m ai.backend.client.agent.watcher
```

Then run the tests:

```
$ export BACKEND_ENDPOINT=...
$ python -m pytest -m 'integration' tests
```

## 4.2 High-level Function Reference

### 4.2.1 Admin Functions

**class** `ai.backend.client.func.admin.Admin`

Provides the function interface for making admin GraphQL queries.

---

**Note:** Depending on the privilege of your API access key, you may or may not have access to querying/mutating server-side resources of other users.

---

**session = None**

The client session instance that this function class is bound to.

**classmethod** `await query(query, variables=None)`

Sends the GraphQL query and returns the response.

**Parameters**

- **query** (*str*) – The GraphQL query string.
- **variables** (*Optional[Mapping[str, Any]]*) – An optional key-value dictionary to fill the interpolated template variables in the query.

**Return type** *Any*

**Returns** The object parsed from the response JSON string.

## 4.2.2 Agent Functions

**class** `ai.backend.client.func.agent.Agent`

Provides a shortcut of `Admin.query()` that fetches various agent information.

---

**Note:** All methods in this function class require your API access key to have the *admin* privilege.

---

**session = None**

The client session instance that this function class is bound to.

**classmethod** `await list_with_limit(limit, offset, status='ALIVE', fields=None)`

Fetches the list of agents with the given status with limit and offset for pagination.

**Parameters**

- **limit** – number of agents to get
- **offset** – offset index of agents to get
- **status** (*str*) – An upper-cased string constant representing agent status (one of 'ALIVE', 'TERMINATED', 'LOST', etc.)
- **fields** (*Optional[Iterable[str]]*) – Additional per-agent query fields to fetch.

**Return type** *Sequence[dict]*

**classmethod** `await detail(agent_id, fields=None)`

**Return type** *Sequence[dict]*

### 4.2.3 Auth Functions

**class** ai.backend.client.func.auth.Auth

Provides the function interface for login session management and authorization.

**classmethod** await login(*user\_id*, *password*)

Log-in into the endpoint with the given user ID and password. It creates a server-side web session and return a dictionary with "authenticated" boolean field and JSON-encoded raw cookie data.

**Return type** dict

**classmethod** await logout()

Log-out from the endpoint. It clears the server-side web session.

**Return type** None

**classmethod** await update\_password(*old\_password*, *new\_password*,  
*new\_password2*)

Update user's password. This API works only for account owner.

**Return type** dict

### 4.2.4 Configuration

ai.backend.client.config.get\_env(*key*, *default*=<object object>, \*,  
*clean*=<function <lambda>>)

Retrieves a configuration value from the environment variables. The given *key* is uppercased and prefixed by "BACKEND\_" and then "SORNA\_" if the former does not exist.

#### Parameters

- **key** (str) – The key name.
- **default** (Any) – The default value returned when there is no corresponding environment variable.
- **clean** (Callable[[str], Any]) – A single-argument function that is applied to the result of lookup (in both successes and the default value for failures). The default is returning the value as-is.

**Returns** The value processed by the *clean* function.

ai.backend.client.config.get\_config()

Returns the configuration for the current process. If there is no explicitly set *APIConfig* instance, it will generate a new one from the current environment variables and defaults.

ai.backend.client.config.set\_config(*conf*)

Sets the configuration used throughout the current process.

```
class ai.backend.client.config.APIConfig(*, endpoint=None, endpoint_type=None, domain=None, group=None, version=None, user_agent=None, access_key=None, secret_key=None, hash_type=None, vfolder_mounts=None, skip_sslcert_validation=None, connection_timeout=None, read_timeout=None)
```

Represents a set of API client configurations. The access key and secret key are mandatory – they must be set in either environment variables or as the explicit arguments.

### Parameters

- **endpoint** (`Union[str, URL, None]`) – The URL prefix to make API requests via HTTP/HTTPS. If this is given as `str` and contains multiple URLs separated by comma, the underlying HTTP request-response facility will perform client-side load balancing and automatic fail-over using them, assuming that all those URLs indicates a single, same cluster. The users of the API and CLI will get network connection errors only when all of the given endpoints fail – intermittent failures of a subset of endpoints will be hidden with a little increased latency.
- **endpoint\_type** (`Optional[str]`) – Either "api" or "session". If the endpoint type is "api" (the default if unspecified), it uses the access key and secret key in the configuration to access the manager API server directly. If the endpoint type is "session", it assumes the endpoint is a Backend.AI console server which provides cookie-based authentication with username and password. In the latter, users need to use `backend.ai login` and `backend.ai logout` to manage their sign-in status, or the API equivalent in `login()` and `logout()` methods.
- **version** (`Optional[str]`) – The API protocol version.
- **user\_agent** (`Optional[str]`) – A custom user-agent string which is sent to the API server as a User-Agent HTTP header.
- **access\_key** (`Optional[str]`) – The API access key. If deliberately set to an empty string, the API requests will be made without signatures (anonymously).
- **secret\_key** (`Optional[str]`) – The API secret key.

- **hash\_type** (`Optional[str]`) – The hash type to generate per-request authentication signatures.
- **vfolder\_mounts** (`Optional[Iterable[str]]`) – A list of vfolder names (that must belong to the given access key) to be automatically mounted upon any `Kernel.get_or_create()` calls.

**DEFAULTS** = {'connection\_timeout': 10.0, 'domain': 'default', 'endpoint': 'https://ap

The default values except the access and secret keys.

#### **endpoint**

The currently active endpoint URL. This may change if there are multiple configured endpoints and the current one is not accessible.

**Return type** `URL`

#### **endpoints**

All configured endpoint URLs.

**Return type** `Sequence[URL]`

#### **endpoint\_type**

The configured endpoint type.

**Return type** `str`

#### **domain**

The configured domain.

**Return type** `str`

#### **group**

The configured group.

**Return type** `str`

#### **user\_agent**

The configured user agent string.

**Return type** `str`

#### **access\_key**

The configured API access key.

**Return type** `str`

#### **secret\_key**

The configured API secret key.

**Return type** `str`

#### **version**

The configured API protocol version.

**Return type** `str`

**hash\_type**

The configured hash algorithm for API authentication signatures.

**Return type** `str`

**vfolder\_mounts**

The configured auto-mounted vfolder list.

**Return type** `Tuple[str, ...]`

**skip\_sslcert\_validation**

Whether to skip SSL certificate validation for the API gateway.

**Return type** `bool`

**connection\_timeout**

The maximum allowed duration for making TCP connections to the server.

**Return type** `float`

**read\_timeout**

The maximum allowed waiting time for the first byte of the response from the server.

**Return type** `float`

#### 4.2.5 KeyPair Functions

**class** `ai.backend.client.func.keypair.KeyPair(access_key)`

Provides interactions with keypairs.

**session = None**

The client session instance that this function class is bound to.

**classmethod** **await** `create(user_id, is_active=True, is_admin=False,  
resource_policy=None, rate_limit=None,  
fields=None)`

Creates a new keypair with the given options. You need an admin privilege for this operation.

**Return type** `dict`

**classmethod** **await** `update(access_key, is_active=None, is_admin=None, re-  
source_policy=None, rate_limit=None)`

Creates a new keypair with the given options. You need an admin privilege for this operation.

**Return type** `dict`

**classmethod** `await delete(access_key)`

Deletes an existing keypair with given ACCESSKEY.

**classmethod** `await list(user_id=None, is_active=None, fields=None)`

Lists the keypairs. You need an admin privilege for this operation.

**Return type** `Sequence[dict]`

**await info(fields=None)**

Returns the keypair's information such as resource limits.

**Parameters** `fields (Optional[Iterable[str]])` – Additional per-agent query fields to fetch.

New in version 18.12.

**Return type** `dict`

**classmethod** `await activate(access_key)`

Activates this keypair. You need an admin privilege for this operation.

**Return type** `dict`

**classmethod** `await deactivate(access_key)`

Deactivates this keypair. Deactivated keypairs cannot make any API requests unless activated again by an administrator. You need an admin privilege for this operation.

**Return type** `dict`

#### 4.2.6 Manager Functions

**class** `ai.backend.client.func.manager.Manager`

Provides controlling of the gateway/manager servers.

New in version 18.12.

**session = None**

The client session instance that this function class is bound to.

**classmethod** `await status()`

Returns the current status of the configured API server.

**classmethod** `await freeze(force_kill=False)`

Freezes the configured API server. Any API clients will no longer be able to create new compute sessions nor create and modify vfolders/keypairs/etc. This is used to enter the maintenance mode of the server for unobtrusive manager and/or agent upgrades.

**Parameters** `force_kill (bool)` – If set True, immediately shuts down all running compute sessions forcibly. If not set, clients who have



running compute session are still able to interact with them though they cannot create new compute sessions.

**classmethod** `await unfreeze()`

Unfreezes the configured API server so that it resumes to normal operation.

#### 4.2.7 Scaling Group Functions

**class** `ai.backend.client.func.scaling_group.ScalingGroup(name)`

Provides getting scaling-group information required for the current user.

The scaling-group is an opaque server-side configuration which splits the whole cluster into several partitions, so that server administrators can apply different auto-scaling policies and operation standards to each partition of agent sets.

**session = None**

The client session instance that this function class is bound to.

**classmethod** `await list_available(group)`

List available scaling groups for the current user, considering the user, the user's domain, and the designated user group.

**classmethod** `await list(fields=None)`

List available scaling groups for the current user, considering the user, the user's domain, and the designated user group.

**Return type** `Sequence[dict]`

**classmethod** `await detail(name, fields=None)`

Fetch information of a scaling group by name.

##### Parameters

- **name** (`str`) – Name of the scaling group.
- **fields** (`Optional[Iterable[str]]`) – Additional per-scaling-group query fields.

**Return type** `Sequence[dict]`

**classmethod** `await create(name, description="", is_active=True, driver=None, driver_opts=None, scheduler=None, scheduler_opts=None, fields=None)`

Creates a new scaling group with the given options.

**Return type** `dict`

**classmethod** `await update(name, description="", is_active=True, driver=None, driver_opts=None, scheduler=None, scheduler_opts=None, fields=None)`

Update existing scaling group.

Return type `dict`

**classmethod** `await delete(name)`

Deletes an existing scaling group.

**classmethod** `await associate_domain(scaling_group, domain)`

Associate `scaling_group` with `domain`.

**Parameters**

- `scaling_group` (`str`) – The name of a scaling group.
- `domain` (`str`) – The name of a domain.

**classmethod** `await dissociate_domain(scaling_group, domain)`

Dissociate `scaling_group` from `domain`.

**Parameters**

- `scaling_group` (`str`) – The name of a scaling group.
- `domain` (`str`) – The name of a domain.

**classmethod** `await dissociate_all_domain(domain)`

Dissociate all `scaling_groups` from `domain`.

**Parameters** `domain` (`str`) – The name of a domain.

**classmethod** `await associate_group(scaling_group, group_id)`

Associate `scaling_group` with `group`.

**Parameters**

- `scaling_group` (`str`) – The name of a scaling group.
- `group_id` (`str`) – The ID of a group.

**classmethod** `await dissociate_group(scaling_group, group_id)`

Dissociate `scaling_group` from `group`.

**Parameters**

- `scaling_group` (`str`) – The name of a scaling group.
- `group_id` (`str`) – The ID of a group.

**classmethod** `await dissociate_all_group(group_id)`

Dissociate all `scaling_groups` from `group`.

**Parameters** `group_id` (`str`) – The ID of a group.

## 4.2.8 ComputeSession Functions

**class** ai.backend.client.func.session.**ComputeSession**(*name*,  
*owner\_access\_key=None*)  
Provides various interactions with compute sessions in Backend.AI.

The term 'kernel' is now deprecated and we prefer 'compute sessions'. However, for historical reasons and to avoid confusion with client sessions, we keep the backward compatibility with the naming of this API function class.

For multi-container sessions, all methods take effects to the master container only, except *destroy()* and *restart()* methods. So it is the user's responsibility to distribute uploaded files to multiple containers using explicit copies or virtual folders which are commonly mounted to all containers belonging to the same compute session.

**session = None**

The client session instance that this function class is bound to.

**classmethod** **await** **get\_or\_create**(*image*, \*, *name=None*,  
*type\_='interactive'*, *enqueue\_only=False*,  
*max\_wait=0*, *no\_reuse=False*,  
*mounts=None*, *mount\_map=None*,  
*envs=None*, *startup\_command=None*,  
*resources=None*, *resource\_opts=None*,  
*cluster\_size=1*, *domain\_name=None*,  
*group\_name=None*, *bootstrap\_script=None*,  
*tag=None*,  
*scaling\_group=None*,  
*owner\_access\_key=None*, *pre-open\_ports=None*)

Get-or-creates a compute session. If *name* is None, it creates a new compute session as long as the server has enough resources and your API key has remaining quota. If *name* is a valid string and there is an existing compute session with the same token and the same *image*, then it returns the *ComputeSession* instance representing the existing session.

### Parameters

- **image** (*str*) – The image name and tag for the compute session. Example: python:3.6-ubuntu. Check out the full list of available images in your server using (TODO: new API).
- **name** (*Optional[str]*) – A client-side (user-defined) identifier to distinguish the session among currently running sessions. It may be used to seamlessly reuse the session already created.

Changed in version 19.12.0: Renamed from `clientSessionToken`.

- **type** – Either "interactive" (default) or "batch".

New in version 19.09.0.

- **enqueue\_only** (`bool`) – Just enqueue the session creation request and return immediately, without waiting for its startup. (default: `false` to preserve the legacy behavior)

New in version 19.09.0.

- **max\_wait** (`int`) – The time to wait for session startup. If the cluster resource is being fully utilized, this waiting time can be arbitrarily long due to job queueing. If the timeout reaches, the returned *status* field becomes "TIMEOUT". Still in this case, the session may start in the future.

New in version 19.09.0.

- **no\_reuse** (`bool`) – Raises an explicit error if a session with the same *image* and the same *name* already exists instead of returning the information of it.

New in version 19.09.0.

- **mounts** (`Optional[Iterable[str]]`) – The list of vfolder names that belongs to the current API access key.

- **mount\_map** (`Optional[Mapping[str, str]]`) – Mapping which contains custom path to mount vfolder. Key and value of this map should be vfolder name and custom path. All custom mounts should be under `/home/work`. vFolders which has a dot(.) prefix in its name are not affected.

- **envs** (`Optional[Mapping[str, str]]`) – The environment variables which always bypasses the jail policy.

- **resources** (`Optional[Mapping[str, int]]`) – The resource specification. (TODO: details)

- **cluster\_size** (`int`) – The number of containers in this compute session. Must be at least 1.

- **tag** (`Optional[str]`) – An optional string to annotate extra information.

- **owner** – An optional access key that owns the created session. (Only available to administrators)

**Return type** `ComputeSession`

**Returns** The `ComputeSession` instance.

```
classmethod await create_from_template(template_id, *,
                                       name=<ai.backend.client.utils.Undefined
                                       object>,
                                       type_=<ai.backend.client.utils.Undefined
                                       object>,
                                       en-
                                       queue_only=<ai.backend.client.utils.Undefined
                                       object>,
                                       max_wait=<ai.backend.client.utils.Undefined
                                       object>,
                                       no_reuse=<ai.backend.client.utils.Undefined
                                       object>,
                                       im-
                                       age=<ai.backend.client.utils.Undefined
                                       object>,
                                       mounts=<ai.backend.client.utils.Undefined
                                       object>,
                                       mount_map=<ai.backend.client.utils.Undefined
                                       object>,
                                       envs=<ai.backend.client.utils.Undefined
                                       object>,
                                       startup_command=<ai.backend.client.utils.Undefined
                                       object>,
                                       re-
                                       sources=<ai.backend.client.utils.Undefined
                                       object>,
                                       re-
                                       source_opts=<ai.backend.client.utils.Undefined
                                       object>,
                                       clus-
                                       ter_size=<ai.backend.client.utils.Undefined
                                       object>,
                                       do-
                                       main_name=<ai.backend.client.utils.Undefined
                                       object>,
                                       group_name=<ai.backend.client.utils.Undefined
                                       object>,
                                       boot-
                                       strap_script=<ai.backend.client.utils.Undefined
                                       object>,
                                       tag=<ai.backend.client.utils.Undefined
                                       object>,
                                       scal-
                                       ing_group=<ai.backend.client.utils.Undefined
                                       object>,
                                       owner_access_key=<ai.backend.client.utils.Undefined
                                       object>)
```

Get-or-creates a compute session from template. All other parameters provided will be overwritten to template, including vfolder mounts (not appended!). If *name* is None, it creates a new compute session as long as the server has enough resources and your API key has remaining quota. If *name* is a valid string and

there is an existing compute session with the same token and the same *image*, then it returns the *ComputeSession* instance representing the existing session.

### Parameters

- **template\_id** (*str*) – Task template to apply to compute session.
- **image** (*str*) – The image name and tag for the compute session. Example: `python:3.6-ubuntu`. Check out the full list of available images in your server using (TODO: new API).
- **name** (*str*) – A client-side (user-defined) identifier to distinguish the session among currently running sessions. It may be used to seamlessly reuse the session already created.

Changed in version 19.12.0: Renamed from `clientSessionToken`.

- **type** – Either "interactive" (default) or "batch".  
New in version 19.09.0.
- **enqueue\_only** (*bool*) – Just enqueue the session creation request and return immediately, without waiting for its startup. (default: `false` to preserve the legacy behavior)

New in version 19.09.0.

- **max\_wait** (*int*) – The time to wait for session startup. If the cluster resource is being fully utilized, this waiting time can be arbitrarily long due to job queueing. If the timeout reaches, the returned *status* field becomes "TIMEOUT". Still in this case, the session may start in the future.

New in version 19.09.0.

- **no\_reuse** (*bool*) – Raises an explicit error if a session with the same *image* and the same *name* already exists instead of returning the information of it.

New in version 19.09.0.

- **mounts** (*Iterable[str]*) – The list of vfolder names that belongs to the current API access key.
- **mount\_map** (*Mapping[str, str]*) – Mapping which contains custom path to mount vfolder. Key and value of this map should be vfolder name and custom path. All custom mounts should be under `/home/work`. vFolders which has a dot(.) prefix in its name are not affected.
- **envs** (*Mapping[str, str]*) – The environment variables which always bypasses the jail policy.

- **resources** (`Mapping[str, int]`) – The resource specification. (TODO: details)
- **cluster\_size** (`int`) – The number of containers in this compute session. Must be at least 1.
- **tag** (`str`) – An optional string to annotate extra information.
- **owner** – An optional access key that owns the created session. (Only available to administrators)

**Return type** `ComputeSession`

**Returns** The `ComputeSession` instance.

**await destroy**(*\*, forced=False*)

Destroys the compute session. Since the server literally kills the container(s), all ongoing executions are forcibly interrupted.

**await restart**()

Restarts the compute session. The server force-destroys the current running container(s), but keeps their temporary scratch directories intact.

**await interrupt**()

Tries to interrupt the current ongoing code execution. This may fail without any explicit errors depending on the code being executed.

**await complete**(*code, opts=None*)

Gets the auto-completion candidates from the given code string, as if a user has pressed the tab key just after the code in IDEs.

Depending on the language of the compute session, this feature may not be supported. Unsupported sessions returns an empty list.

**Parameters**

- **code** (`str`) – An (incomplete) code text.
- **opts** (`Optional[dict]`) – Additional information about the current cursor position, such as row, col, line and the remainder text.

**Return type** `Iterable[str]`

**Returns** An ordered list of strings.

**await get\_info**()

Retrieves a brief information about the compute session.

**await get\_logs**()

Retrieves the console log of the compute session container.

**await execute**(*run\_id=None, code=None, mode='query', opts=None*)

Executes a code snippet directly in the compute session or sends a set of

build/clean/execute commands to the compute session.

For more details about using this API, please refer [the official API documentation](#).

### Parameters

- **run\_id** (`Optional[str]`) – A unique identifier for a particular run loop. In the first call, it may be `None` so that the server auto-assigns one. Subsequent calls must use the returned `runId` value to request continuation or to send user inputs.
- **code** (`Optional[str]`) – A code snippet as string. In the continuation requests, it must be an empty string. When sending user inputs, this is where the user input string is stored.
- **mode** (`str`) – A constant string which is one of "query", "batch", "continue", and "user-input".
- **opts** (`Optional[dict]`) – A dict for specifying additional options. Mainly used in the batch mode to specify build/clean/execution commands. See [the API object reference](#) for details.

**Returns** [An execution result object](#)

**await upload**(*files*, *basedir=None*, *show\_progress=False*)

Uploads the given list of files to the compute session. You may refer them in the batch-mode execution or from the code executed in the server afterwards.

### Parameters

- **files** (`Sequence[Union[str, Path]]`) – The list of file paths in the client-side. If the paths include directories, the location of them in the compute session is calculated from the relative path to *basedir* and all intermediate parent directories are automatically created if not exists.

For example, if a file path is `/home/user/test/data.txt` (or `test/data.txt`) where *basedir* is `/home/user` (or the current working directory is `/home/user`), the uploaded file is located at `/home/work/test/data.txt` in the compute session container.

- **basedir** (`Union[str, Path, None]`) – The directory prefix where the files reside. The default value is the current working directory.
- **show\_progress** (`bool`) – Displays a progress bar during uploads.

**await download**(*files*, *dest='.'*, *show\_progress=False*)

Downloads the given list of files from the compute session.

### Parameters



- **files** (`Sequence[Union[str, Path]]`) – The list of file paths in the compute session. If they are relative paths, the path is calculated from `/home/work` in the compute session container.
- **dest** (`Union[str, Path]`) – The destination directory in the client-side.
- **show\_progress** (`bool`) – Displays a progress bar during downloads.

**await list\_files** (`path='.'`)

Gets the list of files in the given path inside the compute session container.

**Parameters** `path` (`Union[str, Path]`) – The directory path in the compute session.

**stream\_events** ()

Opens the stream of the kernel lifecycle events. Only the master kernel of each session is monitored.

**Return type** `SSEResponse`

**Returns** a `StreamEvents` object.

**stream\_ptty** ()

Opens a pseudo-terminal of the kernel (if supported) streamed via websockets.

**Return type** `StreamPty`

**Returns** a `StreamPty` object.

**stream\_execute** (`code='', *, mode='query', opts=None`)

Executes a code snippet in the streaming mode. Since the returned websocket represents a run loop, there is no need to specify `run_id` explicitly.

**Return type** `WebSocketResponse`

**class** `ai.backend.client.func.session.StreamPty` (`session, underlying_ws`)

A derivative class of `WebSocketResponse` which provides additional functions to control the terminal.

#### 4.2.9 Session Template Functions

**class** `ai.backend.client.func.session_template.SessionTemplate` (`template_id, owner_access_key=None`)

`session = None`

**classmethod** **await create** (`template, domain_name=None, group_name=None, owner_access_key=None`)

**Return type** `SessionTemplate`

```
classmethod await list_templates(list_all=False)
```

```
    Return type List[Mapping[str, str]]
```

```
await get(body_format='yaml')
```

```
    Return type str
```

```
await put(template)
```

```
await delete()
```

#### 4.2.10 Virtual Folder Functions

```
class ai.backend.client.func.vfolder.VFolder(name)
```

```
    session = None
```

The client session instance that this function class is bound to.

```
classmethod await create(name, host=None, unmanaged_path=None,
                          group=None)
```

```
classmethod await delete_by_id(oid)
```

```
classmethod await list(list_all=False)
```

```
classmethod await list_hosts()
```

```
classmethod await list_all_hosts()
```

```
classmethod await list_allowed_types()
```

```
await info()
```

```
await delete()
```

```
await rename(new_name)
```

```
await upload(files, basedir=None, show_progress=False)
```

```
await mkdir(path)
```

```
await request_download(filename)
```

```
await delete_files(files, recursive=False)
```

```
await download(files, show_progress=False)
```

```
await list_files(path='.')
```

```
await invite(perm, emails)
```

```
classmethod await invitations()
```

```
classmethod await accept_invitation(inv_id)
```

```
classmethod await delete_invitation(inv_id)
classmethod await get_fstab_contents(agent_id=None)
classmethod await list_mounts()
classmethod await mount_host(name, fs_location, options=None,
                             edit_fstab=False)
classmethod await umount_host(name, edit_fstab=False)
```

## 4.3 Low-level SDK Reference

### 4.3.1 Base Function

This module defines a few utilities that ease complexities to support both synchronous and asynchronous API functions, using some tricks with Python metaclasses.

Unless your are contributing to the client SDK, probably you won't have to use this module directly.

### 4.3.2 Request API

This module provides low-level API request/response interfaces based on aiohttp.

Depending on the session object where the request is made from, [Request](#) and [Response](#) differentiate their behavior: works as plain Python functions or returns awaitables.

```
class ai.backend.client.request.Request(session, method='GET',
                                       path=None, content=None, *, content_type=None,
                                       params=None, reporthook=None)
```

The API request object.

**with async with fetch(\*\*kwargs) as Response**

Sends the request to the server and reads the response.

You may use this method either with plain synchronous Session or AsyncSession.

Both the followings patterns are valid:

```
from ai.backend.client.request import Request
from ai.backend.client.session import Session

with Session() as sess:
    rqst = Request(sess, 'GET', ...)
    with rqst.fetch() as resp:
        print(resp.text())
```

```
from ai.backend.client.request import Request
from ai.backend.client.session import AsyncSession

async with AsyncSession() as sess:
    rqst = Request(sess, 'GET', ...)
    async with rqst.fetch() as resp:
        print(await resp.text())
```

**Return type** *FetchContextManager*

**async with connect\_websocket(\*\*kwargs) as WebSocketResponse or its derivatives**  
Creates a WebSocket connection.

**Warning:** This method only works with *AsyncSession*.

**Return type** *WebSocketContextManager*

#### **content**

Retrieves the content in the original form. Private codes should NOT use this as it incurs duplicate encoding/decoding.

**Return type** *Union[bytes, bytearray, str, StreamReader, IOBase, None]*

**set\_content(value, \*, content\_type=None)**

Sets the content of the request.

**set\_json(value)**

A shortcut for set\_content() with JSON objects.

**attach\_files(files)**

Attach a list of files represented as AttachedFile.

**connect\_events(\*\*kwargs)**

Creates a Server-Sent Events connection.

**Warning:** This method only works with *AsyncSession*.

**Return type** *SSEContextManager*

**class ai.backend.client.request.Response(session, underlying\_response, \*,  
async\_mode=False)**

Represents the Backend.AI API response. Also serves as a high-level wrapper of *aihttp.ClientResponse*.

The response objects are meant to be created by the SDK, not the callers.

`text()`, `json()` methods return the resolved content directly with plain synchronous `Session` while they return the coroutines with `AsyncSession`.

**class** `ai.backend.client.request.WebSocketResponse`(*session*, *underlying\_ws*)

A high-level wrapper of `aiohttp.ClientWebSocketResponse`.

```
class ai.backend.client.request.FetchContextManager(session,
                                                    rqst_ctx_builder,      *,
                                                    response_cls=<class
                                                    'ai.backend.client.request.Response'>,
                                                    check_status=True)
```

The context manager returned by `Request.fetch()`.

It provides both synchronous and asynchronous context manager interfaces.

```
class ai.backend.client.request.WebSocketContextManager(session,
                                                         ws_ctx_builder,
                                                         *, on_enter=None,
                                                         re-
                                                         sponse_cls=<class
                                                         'ai.backend.client.request.WebSocketF
```

The context manager returned by `Request.connect_websocket()`.

```
class ai.backend.client.request.AttachedFile(filename,      stream,      con-
                                              tent_type)
```

A struct that represents an attached file to the API request.

#### Parameters

- **filename** (*str*) – The name of file to store. It may include paths and the server will create parent directories if required.
- **stream** (*Any*) – A file-like object that allows stream-reading bytes.
- **content\_type** (*str*) – The content type for the stream. For arbitrary binary data, use “application/octet-stream”.

#### content\_type

Alias for field number 2

**count**(*value*) → integer -- return number of occurrences of value

#### filename

Alias for field number 0

**index**(*value*[, *start*[, *stop*]]) → integer -- return first index of value.

Raises `ValueError` if the value is not present.

#### stream

Alias for field number 1

### 4.3.3 Exceptions

**class** ai.backend.client.exceptions.**BackendError**

Exception type to catch all ai.backend-related errors.

**with\_traceback()**

Exception.with\_traceback(tb) – set self.\_\_traceback\_\_ to tb and return self.

**class** ai.backend.client.exceptions.**BackendAPIError**(status, reason, data)

Exceptions returned by the API gateway.

**with\_traceback()**

Exception.with\_traceback(tb) – set self.\_\_traceback\_\_ to tb and return self.

**class** ai.backend.client.exceptions.**BackendClientError**

Exceptions from the client library, such as argument validation errors and connection failures.

**with\_traceback()**

Exception.with\_traceback(tb) – set self.\_\_traceback\_\_ to tb and return self.

### 4.3.4 Miscellaneous Utilities

**class** ai.backend.client.utils.**Undefined**

A special type to represent an undefined value.

ai.backend.client.utils.**undefined**

A placeholder to signify an undefined value as a singleton object of *Undefined* and distinguish it from a null (None) value.

**INDICES AND TABLES**

- genindex
- modindex
- search





## PYTHON MODULE INDEX

### a

- `ai.backend.client.base`, 47
- `ai.backend.client.config`, 32
- `ai.backend.client.exceptions`, 50
- `ai.backend.client.func.admin`, 30
- `ai.backend.client.func.agent`, 31
- `ai.backend.client.func.auth`, 32
- `ai.backend.client.func.keypair`, 35
- `ai.backend.client.func.manager`, 36
- `ai.backend.client.func.scaling_group`,  
37
- `ai.backend.client.func.session`, 39
- `ai.backend.client.func.session_template`,  
45
- `ai.backend.client.func.vfolder`, 46
- `ai.backend.client.request`, 47
- `ai.backend.client.session`, 21
- `ai.backend.client.utils`, 50



## INDEX

A

`accept_invitation()` (`ai.backend.client.func.vfolder.VFolder` method), 46

`access_key()` (`ai.backend.client.config.APIConfig` method), 34

`activate()` (`ai.backend.client.func.keypair.KeyPair` method), 36

`Admin` (`ai.backend.client.session.AsyncSession` attribute), 23

`Admin` (`ai.backend.client.session.Session` attribute), 22

`Admin` (class in `ai.backend.client.func.admin`), 30

`Agent` (`ai.backend.client.session.AsyncSession` attribute), 23

`Agent` (`ai.backend.client.session.Session` attribute), 22

`Agent` (class in `ai.backend.client.func.agent`), 31

`AgentWatcher` (`ai.backend.client.session.AsyncSession` attribute), 23

`AgentWatcher` (`ai.backend.client.session.Session` attribute), 22

`ai.backend.client.base` (module), 47

`ai.backend.client.config` (module), 32

`ai.backend.client.exceptions` (module), 50

`ai.backend.client.func.admin` (module), 30

`ai.backend.client.func.agent` (module), 31

`ai.backend.client.func.auth` (module), 32

`ai.backend.client.func.keypair` (module), 35

`ai.backend.client.func.manager` (module), 36

`ai.backend.client.func.scaling_group` (module), 37

`ai.backend.client.func.session` (module), 39

`ai.backend.client.func.session_template` (module), 45

`ai.backend.client.func.vfolder` (module), 46

`ai.backend.client.request` (module), 47

`ai.backend.client.session` (module), 21

`ai.backend.client.utils` (module), 50

`APIConfig` (class in `ai.backend.client.config`), 33

`associate_domain()` (`ai.backend.client.func.scaling_group.ScalingGroup` method), 38

`associate_group()` (`ai.backend.client.func.scaling_group.ScalingGroup` method), 38

`AsyncSession` (class in `ai.backend.client.session`), 23

`attach_files()` (`ai.backend.client.request.Request` method), 48

`AttachedFile` (class in `ai.backend.client.request`), 49

`Auth` (`ai.backend.client.session.AsyncSession` attribute), 23

- Auth (*ai.backend.client.session.Session* attribute), 22
- Auth (class in *ai.backend.client.func.auth*), 32
- ## B
- BackendAPIError (class in *ai.backend.client.exceptions*), 50
- BackendClientError (class in *ai.backend.client.exceptions*), 50
- BackendError (class in *ai.backend.client.exceptions*), 50
- BaseSession (class in *ai.backend.client.session*), 21
- ## C
- close() (*ai.backend.client.session.AsyncSession* method), 24
- close() (*ai.backend.client.session.BaseSession* method), 21
- close() (*ai.backend.client.session.Session* method), 23
- closed() (*ai.backend.client.session.AsyncSession* method), 23
- closed() (*ai.backend.client.session.BaseSession* method), 21
- closed() (*ai.backend.client.session.Session* method), 22
- complete() (*ai.backend.client.func.session.ComputeSession* method), 43
- ComputeSession (*ai.backend.client.session.AsyncSession* attribute), 24
- ComputeSession (*ai.backend.client.session.Session* attribute), 22
- ComputeSession (class in *ai.backend.client.func.session*), 39
- config() (*ai.backend.client.session.AsyncSession* method), 23
- config() (*ai.backend.client.session.BaseSession* method), 21
- config() (*ai.backend.client.session.Session* method), 22
- connect\_events() (*ai.backend.client.request.Request* method), 48
- connect\_websocket() (*ai.backend.client.request.Request* method), 48
- connection\_timeout() (*ai.backend.client.config.APIConfig* method), 35
- content() (*ai.backend.client.request.Request* method), 48
- content\_type() (*ai.backend.client.request.AttachedFile* method), 49
- count() (*ai.backend.client.request.AttachedFile* method), 49
- create() (*ai.backend.client.func.keypair.KeyPair* method), 35
- create() (*ai.backend.client.func.scaling\_group.ScalingGroup* method), 37
- create() (*ai.backend.client.func.session\_template.SessionTemplate* method), 45
- create() (*ai.backend.client.func.vfolder.VFolder* method), 46
- create\_from\_template() (*ai.backend.client.func.session.ComputeSession* method), 40
- deactivate() (*ai.backend.client.func.keypair.KeyPair* method), 36
- DEFAULTS (*ai.backend.client.config.APIConfig* attribute), 34
- delete() (*ai.backend.client.func.keypair.KeyPair* method), 35
- delete() (*ai.backend.client.func.scaling\_group.ScalingGroup* method), 38

`delete()` (`ai.backend.client.func.session_template.SessionTemplate` method), 46  
**E**  
`delete()` (`ai.backend.client.func.vfolder.VFolder` method), 46  
`delete_by_id()` (`ai.backend.client.func.vfolder.VFolder` method), 46  
`delete_files()` (`ai.backend.client.func.vfolder.VFolder` method), 46  
`delete_invitation()` (`ai.backend.client.func.vfolder.VFolder` method), 46  
`destroy()` (`ai.backend.client.func.session.ComputeSession` method), 43  
`detail()` (`ai.backend.client.func.agent.Agent` method), 31  
`detail()` (`ai.backend.client.func.scaling_group.ScalingGroup` method), 37  
`dissociate_all_domain()` (`ai.backend.client.func.scaling_group.ScalingGroup` method), 38  
`dissociate_all_group()` (`ai.backend.client.func.scaling_group.ScalingGroup` method), 38  
`dissociate_domain()` (`ai.backend.client.func.scaling_group.ScalingGroup` method), 38  
`dissociate_group()` (`ai.backend.client.func.scaling_group.ScalingGroup` method), 38  
**Domain** (`ai.backend.client.session.Session` attribute), 22  
`domain()` (`ai.backend.client.config.APIConfig` method), 34  
**Dotfile** (`ai.backend.client.session.AsyncSession` attribute), 24  
**Dotfile** (`ai.backend.client.session.Session` attribute), 23  
`download()` (`ai.backend.client.func.session.ComputeSession` method), 44  
`download()` (`ai.backend.client.func.vfolder.VFolder` method), 46  
`endpoint()` (`ai.backend.client.config.APIConfig` method), 34  
`endpoint_type()` (`ai.backend.client.config.APIConfig` method), 34  
`endpoints()` (`ai.backend.client.config.APIConfig` method), 34  
**EtcdConfig** (`ai.backend.client.session.AsyncSession` attribute), 23  
**EtcdConfig** (`ai.backend.client.session.Session` attribute), 22  
`execute()` (`ai.backend.client.func.session.ComputeSession` method), 43  
**F**  
`fetch()` (`ai.backend.client.request.Request` method), 47  
**FetchContextManager** (class in `ai.backend.client.request`), 49  
`filename()` (`ai.backend.client.request.AttachedFile` method), 49  
`freeze()` (`ai.backend.client.func.manager.Manager` method), 36  
**G**  
`get()` (`ai.backend.client.func.session_template.SessionTemplate` method), 46  
`get_config()` (in module `ai.backend.client.config`), 32  
`get_env()` (in module `ai.backend.client.config`), 32  
`get_fstab_contents()` (`ai.backend.client.func.vfolder.VFolder` method), 47  
`get_info()` (`ai.backend.client.func.session.ComputeSession` method), 43  
`get_logs()` (`ai.backend.client.func.session.ComputeSession` method), 43  
`get_or_create()` (`ai.backend.client.func.session.ComputeSession` method), 39

Group (*ai.backend.client.session.AsyncSessionL*  
*attribute*), 24

Group (*ai.backend.client.session.Session at-*  
*tribute*), 22

group() (*ai.backend.client.config.APIConfig*  
*method*), 34

list() (*ai.backend.client.func.keypair.KeyPair*  
*method*), 36

list() (*ai.backend.client.func.scaling\_group.ScalingGroup*  
*method*), 37

list() (*ai.backend.client.func.vfolder.VFolder*  
*method*), 46

H

list\_all\_hosts()  
 hash\_type() (*ai.backend.client.config.APIConfig*  
*method*), 35

(*ai.backend.client.func.vfolder.VFolder*  
*method*), 46

I

list\_allowed\_types()  
 Image (*ai.backend.client.session.AsyncSession*  
*attribute*), 24

(*ai.backend.client.func.vfolder.VFolder*  
*method*), 46

list\_available()  
 Image (*ai.backend.client.session.Session at-*  
*tribute*), 22

(*ai.backend.client.func.scaling\_group.ScalingGroup*  
*method*), 37

index() (*ai.backend.client.request.AttachedFile*  
*method*), 49

list\_files() (*ai.backend.client.func.session.ComputeSes*  
*method*), 45

info() (*ai.backend.client.func.keypair.KeyPair*  
*method*), 36

list\_files() (*ai.backend.client.func.vfolder.VFolder*  
*method*), 46

info() (*ai.backend.client.func.vfolder.VFolder*  
*method*), 46

list\_hosts() (*ai.backend.client.func.vfolder.VFolder*  
*method*), 46

interrupt() (*ai.backend.client.func.session.ComputeSession*  
*method*), 43

list\_mounts() (*ai.backend.client.func.vfolder.VFolder*  
*method*), 47

invitations() (*ai.backend.client.func.vfolder.VFolder*  
*method*), 46

list\_templates()  
 invite() (*ai.backend.client.func.vfolder.VFolder*  
*method*), 46

(*ai.backend.client.func.session\_template.SessionTe*  
*method*), 45

list\_with\_limit()  
 K

(*ai.backend.client.func.agent.Agent*  
*method*), 31

login() (*ai.backend.client.func.auth.Auth*  
*method*), 32

KeyPair (*ai.backend.client.session.AsyncSession*  
*attribute*), 24

KeyPair (*ai.backend.client.session.Session*  
*attribute*), 22

logout() (*ai.backend.client.func.auth.Auth*  
*method*), 32

KeyPair (class in  
*ai.backend.client.func.keypair*),  
 35

M

Manager (*ai.backend.client.session.AsyncSession*  
*attribute*), 24

Manager (*ai.backend.client.session.Session*  
*attribute*), 22

KeypairResourcePolicy  
 (*ai.backend.client.session.AsyncSession*  
*attribute*), 24

Manager (class in  
 KeypairResourcePolicy  
 (*ai.backend.client.session.Session*  
*attribute*), 22

*ai.backend.client.func.manager*), 36

mkdir() (*ai.backend.client.func.vfolder.VFolder* attribute), 46

mount\_host() (*ai.backend.client.func.vfolder.VFolder* attribute), 47

**P**

put() (*ai.backend.client.func.session\_template.SessionTemplate* attribute), 46

**Q**

query() (*ai.backend.client.func.admin.Admin* attribute), 30

**R**

read\_timeout() (*ai.backend.client.config.APICConfig* attribute), 35

rename() (*ai.backend.client.func.vfolder.VFolder* attribute), 46

Request (*class in ai.backend.client.request*), 47

request\_download() (*ai.backend.client.func.vfolder.VFolder* attribute), 46

Resource (*ai.backend.client.session.AsyncSession* attribute), 24

Resource (*ai.backend.client.session.Session* attribute), 22

Response (*class in ai.backend.client.request*), 48

restart() (*ai.backend.client.func.session.ComputeSession* attribute), 43

**S**

ScalingGroup (*ai.backend.client.session.AsyncSession* attribute), 24

ScalingGroup (*ai.backend.client.session.Session* attribute), 23

ScalingGroup (*class in ai.backend.client.func.scaling\_group*), 37

secret\_key() (*ai.backend.client.config.APICConfig* attribute), 34

session (*ai.backend.client.func.admin.Admin* attribute), 30

session (*ai.backend.client.func.agent.Agent* attribute), 31

session (*ai.backend.client.func.keypair.KeyPair* attribute), 35

session (*ai.backend.client.func.manager.Manager* attribute), 36

session (*ai.backend.client.func.scaling\_group.ScalingGroup* attribute), 37

session (*ai.backend.client.func.session.ComputeSession* attribute), 39

session (*ai.backend.client.func.session\_template.SessionTemplate* attribute), 45

session (*ai.backend.client.func.vfolder.VFolder* attribute), 46

Session (*class in ai.backend.client.session*), 21

SessionTemplate (*ai.backend.client.session.AsyncSession* attribute), 24

SessionTemplate (*ai.backend.client.session.Session* attribute), 23

SessionTemplate (*class in ai.backend.client.func.session\_template*), 45

set\_config() (*in module ai.backend.client.config*), 32

set\_content() (*ai.backend.client.request.Request* attribute), 48

set\_json() (*ai.backend.client.request.Request* attribute), 48

skip\_ssl\_cert\_validation() (*ai.backend.client.config.APICConfig* attribute), 35

status() (*ai.backend.client.func.manager.Manager* attribute), 36

stream() (*ai.backend.client.request.AttachedFile* attribute), 49

stream\_events() (*ai.backend.client.func.session.ComputeSession* attribute), 49

method), 45

stream\_execute() (ai.backend.client.func.session.ComputeSession attribute), 24

method), 45

stream\_ptty() (ai.backend.client.func.session.ComputeSession attribute), 23

method), 45

StreamPty (class in ai.backend.client.func.vfolder), 46

ai.backend.client.func.session), 45

System (ai.backend.client.session.AsyncSession attribute), 23

System (ai.backend.client.session.Session attribute), 22

**U**

umount\_host() (ai.backend.client.func.vfolder.VFolder method), 47

Undefined (class in ai.backend.client.utils), 50

undefined (in module ai.backend.client.utils), 50

unfreeze() (ai.backend.client.func.manager.Manager method), 37

update() (ai.backend.client.func.keypair.KeyPair method), 35

update() (ai.backend.client.func.scaling\_group.ScalingGroup method), 37

update\_password() (ai.backend.client.func.auth.Auth method), 32

upload() (ai.backend.client.func.session.ComputeSession method), 44

upload() (ai.backend.client.func.vfolder.VFolder method), 46

User (ai.backend.client.session.AsyncSession attribute), 24

User (ai.backend.client.session.Session attribute), 22

user\_agent() (ai.backend.client.config.APIConfig method), 34

**V**

version() (ai.backend.client.config.APIConfig