

---

# **cbapi Documentation**

*Release 1.5.1*

**Carbon Black Developer Network**

**Oct 16, 2019**



---

## Contents

---

<b>1</b>	<b>Major Features</b>	<b>3</b>
<b>2</b>	<b>API Credentials</b>	<b>5</b>
<b>3</b>	<b>Backwards &amp; Forwards Compatibility</b>	<b>7</b>
<b>4</b>	<b>User Guide</b>	<b>9</b>
4.1	Installation . . . . .	9
4.2	Getting Started . . . . .	11
4.3	Concepts . . . . .	12
4.4	Logging & Diagnostics . . . . .	16
4.5	CB Response API Examples . . . . .	17
4.6	CbAPI and Live Response . . . . .	25
4.7	CbAPI Changelog . . . . .	27
<b>5</b>	<b>API Documentation</b>	<b>37</b>
5.1	CB Response API . . . . .	37
5.2	CB Protection API . . . . .	54
5.3	CB Defense API . . . . .	70
5.4	CB ThreatHunter API . . . . .	74
5.5	CB LiveQuery API . . . . .	88
5.6	Exceptions . . . . .	93
<b>6</b>	<b>Indices and tables</b>	<b>95</b>
	<b>Python Module Index</b>	<b>97</b>
	<b>Index</b>	<b>99</b>



Release v1.5.1.

cbapi provides a straightforward interface to the Carbon Black products: CB Protection, Response, and Defense. This library provides a Pythonic layer to access the raw power of the REST APIs of all CB products, making it trivial to do the easy stuff and handling all of the “sharp corners” behind the scenes for you. Take a look:

```
>>> from cbapi.response import CbResponseAPI, Process, Binary, Sensor
>>> #
>>> # Create our CbAPI object
>>> #
>>> c = CbResponseAPI()
>>> #
>>> # take the first process that ran notepad.exe, download the binary and read the_
↳first two bytes
>>> #
>>> c.select(Process).where('process_name:notepad.exe').first().binary.file.read(2)
'MZ'
>>> #
>>> # if you want a specific ID, you can put it straight into the .select() call:
>>> #
>>> binary = c.select(Binary, "24DA05ADE2A978E199875DA0D859E7EB")
>>> #
>>> # select all sensors that have ran notepad
>>> #
>>> sensors = set()
>>> for proc in c.select(Process).where('process_name:evil.exe'):
...     sensors.add(proc.sensor)
>>> #
>>> # iterate over all sensors and isolate
>>> #
>>> for s in sensors:
...     s.network_isolation_enabled = True
...     s.save()
```

If you're more a CB Protection fellow, then you're in luck as well:

```
>>> from cbapi.protection.models import FileInstance
>>> from cbapi.protection import CbProtectionAPI
>>> #
>>> # Create our CB Protection API object
>>> #
>>> p = CbProtectionAPI()
>>> #
>>> # Select the first file instance
>>> #
>>> fi = p.select(FileInstance).first()
>>> #
>>> # print that computer's hostname. This automatically "joins" with the Computer_
↳API object.
>>> #
>>> fi.computer.name
u'DOMAIN\MYHOSTNAME'
>>> #
>>> # change the policy ID
>>> #
>>> fi.computer.policyId = 3
>>> fi.computer.save()
```

As of version 1.2, cbapi now provides support for CB Defense too!

```
>>> from cbapi.psc.defense import *
>>> #
>>> # Create our CB Defense API object
>>> #
>>> p = CbDefenseAPI()
>>> #
>>> # Select any devices that have the hostname WIN-IA9NQ1GN8OI and an internal IP_
↳address of 192.168.215.150
>>> #
>>> devices = c.select(Device).where('hostNameExact:WIN-IA9NQ1GN8OI').and_(
↳"ipAddress:192.168.215.150").first()
>>> #
>>> # Change those devices' policy into the Windows_Restrictive_Workstation policy.
>>> #
>>> for dev in devices:
>>>     dev.policyName = "Restrictive_Windows_Workstation"
>>>     dev.save()
```

---

## Major Features

---

- **Enhanced Live Response API** The new cbapi now provides a robust interface to the CB Response Live Response capability. Easily create Live Response sessions, initiate commands on remote hosts, and pull down data as necessary to make your Incident Response process much more efficient and automated.
- **Consistent API for CB Response, Protection and Defense platforms** We now support CB Response, Protection and Defense users in the same API layer. Even better, the object model is the same for both; if you know one API you can easily transition to the other. cbapi hides all the differences between the three REST APIs behind a single, consistent Python-like interface.
- **Enhanced Performance** cbapi now provides a built in caching layer to reduce the query load on the Carbon Black server. This is especially useful when taking advantage of cbapi's new "joining" features. You can transparently access, for example, the binary associated with a given process in CB Response. Since many processes may be associated with the same binary, it does not make sense to repeatedly request the same binary information from the server over and over again. Therefore cbapi now caches this information to avoid unnecessary requests.
- **Reduce Complexity** cbapi now provides a friendly - dare I say "fun" - interface to the data. This greatly improves developer productivity and lowers the bar to entry.
- **Python 3 and Python 2 compatible** Use all the new features and modules available in Python 3 with cbapi. This module is compatible with Python versions 2.6.6 and above, 2.7.x, 3.4.x, and 3.5.x.
- **Better support for multiple CB servers** cbapi now introduces the concept of Credential Profiles; named collections of URL, API keys, and optional proxy configuration for connecting to any number of CB Protection, Defense, or Response servers.





## CHAPTER 2

---

### API Credentials

---

The new `cbapi` as of version 0.9.0 enforces the use of credential files.

In order to perform any queries via the API, you will need to get the API token for your CB user. See the documentation on the Developer Network website on how to acquire the API token for [CB Response](#), [CB Protection](#), or [CB Defense](#).

Once you acquire your API token, place it in one of the default credentials file locations:

- `/etc/carbonblack/credentials.response` (`credentials.protection` for CB Protection, or `credentials.defense` for CB Defense)
- `~/.carbonblack/credentials.response`
- (current working directory) `.carbonblack/credentials.response`

Credentials found in a later path will overwrite earlier ones.

The credentials are stored in INI format. The name of each credential profile is enclosed in square brackets, followed by key-value pairs providing the necessary credential information:

```
[default]
url=https://localhost
token=abcdef0123456789abcdef
ssl_verify=False

[prod]
url=https://cbserver.prod.corp.com
token=aaaaaa
ssl_verify=True

[otheruser]
url=https://localhost
token=bbbbbb
ssl_verify=False
```

The possible options for each credential profile are:

- **url**: The base URL of the CB server. This should include the protocol (https) and the hostname, and nothing else.

- **token:** The API token for the user ID. More than one credential profile can be specified for a given server, with different tokens for each.
- **ssl\_verify:** True or False; controls whether the SSL/TLS certificate presented by the server is validated against the local trusted CA store.
- **org\_key:** The organization key. This is required to access the PSC, and can be found in the console. The format is 123ABC45.
- **proxy:** A proxy specification that will be used when connecting to the CB server. The format is: `http://myusername:mypassword@proxy.company.com:8001/` where the hostname of the proxy is `proxy.company.com`, port 8001, and using `username/password myusername` and `mypassword` respectively.
- **ignore\_system\_proxy:** If you have a system-wide proxy specified, setting this to True will force cbapi to bypass the proxy and directly connect to the CB server.

Future versions of cbapi will also provide the ability to “pin” the TLS certificate so as to provide certificate verification on self-signed or internal CA signed certificates.

### Environment Variable Support

The latest cbapi for python supports specifying API credentials in the following three environment variables:

*CBAPI\_TOKEN* the envvar for holding the CbR/CbP api token or the ConnectorId/APIKEY combination for CB Defense/PSC.

The *CBAPI\_URL* envvar holds the FQDN of the target, a CbR , CBD, or CbD/PSC server specified just as they are in the configuration file format specified above.

The optional *CBAPI\_SSL\_VERIFY* envvar can be used to control SSL validation(True/False or 0/1), which will default to ON when not explicitly set by the user.

---

## Backwards & Forwards Compatibility

---

The previous versions (0.8.x and earlier) of `cbapi` and `bit9Api` are now deprecated and will no longer receive updates. However, existing scripts will work without change as `cbapi` includes both in its legacy package. The legacy package is imported by default and placed in the top level `cbapi` namespace when the `cbapi` module is imported on a Python 2.x interpreter. Therefore, scripts that expect to import `cbapi.CbApi` will continue to work exactly as they had previously.

Since the old API was not compatible with Python 3, the legacy package is not importable in Python 3.x and therefore legacy scripts cannot run under Python 3.

Once `cbapi 1.0.0` is released, the old `cbapi.legacy.CbApi` will be deprecated and removed entirely no earlier than January 2017. New scripts should use the `cbapi.response.rest_api.CbResponseAPI` (for CB Response), `cbapi.protection.rest_api.CbProtectionAPI` (for CB Protection), or `cbapi.defense.rest_api.CbDefenseAPI` API entry points.

The API is frozen as of version 1.0; afterward, any changes in the 1.x version branch will be additions/bug fixes only. Breaking changes to the API will increment the major version number (2.x).



Let's get started with cbapi. Once you've mastered the concepts here, then you can always hop over to the [API Documentation](#) (below) for detailed information on the objects and methods exposed by cbapi.

## 4.1 Installation

Before installing cbapi, make sure that you have access to a working CB Response or CB Protection server. The server can be either on-premise or in the cloud. CB Response clusters are also supported. Once you have access to a working can use the standard Python packaging tools to install cbapi on your local machine.

Feel free to follow along with this document or watch the [Development Environment Setup video](#) on the Developer Network website.

If you already have Python installed, you can skip right down to "Using Pip".

### 4.1.1 Installing Python

Obviously the first thing you'll need to do is install Python on your workstation or server. We recommend using the latest version of Python 3 (as of this writing, 3.6.4) for maximum performance and compatibility. Linux and Mac OS X systems will most likely have Python installed; it will have to be installed on Windows separately.

Note that cbapi is compatible with both Python 2.7 and Python 3.x. If you already have Python 3 installed on your system, you're good to go!


If you believe you have Python installed already, run the following two commands at a command prompt:

```
$ python --version
Python 3.6.4

$ pip --version
pip 9.0.1 from /usr/local/lib/python3.6/site-packages (python 3.6)
```

If “python” reports back a version of 2.6.x, 2.7.x, or 3.x.x, you’re in luck. If “pip” is not found, don’t worry, we’ll install that shortly.

If you’re on Windows, and Python is not installed yet, download the latest Python installer from the [python.org](http://python.org) website. We recommend using the latest version of Python 3. As of this writing, the latest version available is 3.6.4. The direct link for the Python 3.6.4 installer for Windows 64-bit platforms is <https://www.python.org/ftp/python/3.6.4/python-3.6.4-amd64.exe>.



Ensure that the “Add Python to PATH” option is checked.

If for some reason you do not have pip installed, follow the instructions at this [handy guide](#).

### 4.1.2 Using Pip

Once Python and Pip are installed, then open a command prompt and type:

```
$ pip install cbapi
```

This will download and install the latest version of cbapi from the Python PyPI packaging server.

### 4.1.3 Getting the Source Code

cbapi is actively developed on GitHub and the code is available from the [carbonblack GitHub repository](#). The version of cbapi on GitHub will reflect the latest development version of cbapi and may contain bugs not present in the currently released version. On the other hand, it may contain exactly the goodies you’re looking for (or you’d like to contribute back; we are happy to accept pull requests!)

To clone the latest version of the cbapi repository from GitHub:

```
$ git clone https://github.com/carbonblack/cbapi-python.git
```

Once you have a copy of the source, you can install it in “development” mode into your Python site-packages:

```
$ cd cbapi-python
$ python setup.py develop
```

This will link the version of cbapi-python you checked out into your Python site-packages directory. Any changes you make to the checked out version of cbapi will be reflected in your local Python installation. This is a good choice if you are thinking of changing or developing on cbapi itself.

## 4.2 Getting Started

First, let's make sure that your API authentication tokens have been imported into cbapi. Once that's done, then read on for the key concepts that will explain how to interact with Carbon Black APIs via cbapi.

Feel free to follow along with this document or watch the [Development Environment Setup](#) video on the Developer Network website.

### 4.2.1 API Authentication

CB Response and CB Protection use a per-user API secret token to authenticate requests via the API. The API token confers the same permissions and authorization as the user it is associated with, so protect the API token with the same care as a password.

To learn how to obtain the API token for a user, see the Developer Network website: there you will find instructions for obtaining an API token for [CB Response](#) and [CB Protection](#).

Once you have the API token, cbapi helps keep your credentials secret by enforcing the use of a credential file. To encourage sharing of scripts across the community while at the same time protecting the security of our customers, cbapi strongly discourages embedding credentials in individual scripts. Instead, you can place credentials for several CB Response or CB Protection servers inside the API credential file and select which "profile" you would like to use at runtime.

To create the initial credential file, a simple-to-use script is provided. Just run the `cbapi-response`, `cbapi-protection`, or `cbapi-psc` script with the `configure` argument. On Mac OS X and Linux:

```
$ cbapi-response configure
```

Alternatively, if you're using Windows (change `c:\python27` if Python is installed in a different directory):

```
C:\> python c:\python27\scripts\cbapi-response configure
```

This configuration script will walk you through entering your API credentials and will save them to your current user's credential file location, which is located in the `.carbonblack` directory in your user's home directory.

If using `cbapi-psc`, you will also be asked to provide an org key. An org key is required to access the PSC, and can be found in the console under Settings -> API Keys.

### 4.2.2 Your First Query

Now that you have cbapi installed and configured, let's run a simple query to make sure everything is functional:

```
$ python
Python 2.7.10 (default, Jun 22 2015, 12:25:23)
[GCC 4.2.1 Compatible Apple LLVM 6.1.0 (clang-602.0.53)] on darwin
Type "help", "copyright", "credits" or "license" for more information.
>>> from cbapi.response import *
>>> c = CbResponseAPI()
>>> print(c.select(Process).first().cmdline)
C:\Windows\system32\services.exe
```

That's it! Now on to the next step, learning the concepts behind cbapi.

## 4.3 Concepts

There are a few critical concepts that will make understanding and using the cbapi easier. These concepts are explained below, and also covered in a slide deck presented at the Carbon Black regional User Exchanges in 2016. You can see the slide deck [here](#).

At a high level, the cbapi tries to represent data in CB Response or CB Protection as Python objects. If you've worked with SQL Object-relational Mapping (ORM) frameworks before, then this structure may seem familiar – cbapi was designed to operate much like an ORM such as SQLAlchemy or Ruby's ActiveRecord. If you haven't worked with one of these libraries, don't worry! The concepts will become clear after a little practice.

### 4.3.1 Model Objects

Everything in cbapi is represented in terms of “Model Objects”. A Model Object in cbapi represents a single instance of a specific type of data in CB Response or Protection. For example, a process document from CB Response (as seen on an Analyze Process page in the Web UI) is represented as a `cbapi.response.models.Process` Model Object. Similarly, a file instance in CB Protection is represented as a `cbapi.protection.models.FileInstance` Model Object.

Once you have an instance of a Model Object, you can access all of the data contained within as Python properties. For example, if you have a Process Model Object named `proc` and you want to print its command line (which is stored in the `cmdline` property), you would write the code:

```
>>> print(proc.cmdline)
```

This would automatically retrieve the `cmdline` attribute of the process and print it out to your screen.

The data in CB Response and Protection may change rapidly, and so a comprehensive list of valid properties is difficult to keep up-to-date. Therefore, if you are curious what properties are available on a specific Model Object, you can print that Model Object to the screen. It will dump all of the available properties and their current values. For example:

```
>>> print(binary)
cbapi.response.models.Binary:
-> available via web UI at https://cbserver/#binary/08D1631FAF39538A133D94585644D5A8
host_count          : 1
digsig_result       : Signed
observed_filename   : [u'c:\\windows\\syswow64\\appwiz.cpl']
product_version     : 6.2.9200.16384
legal_copyright     : © Microsoft Corporation. All rights reserved.
digsig_sign_time    : 2012-07-26T08:56:00Z
orig_mod_len        : 669696
is_executable_image : False
is_64bit            : False
digsig_publisher    : Microsoft Corporation
...
```

In this example, `host_count`, `orig_mod_len`, etc. are all properties available on this Binary Model Object. Sometimes, properties are not available on every instance of a Model Object. In this case, you can use the `.get()` method to retrieve the property, and return a default value if the property does not exist on the Model Object:

```
>>> print(binary.get("product_version", "<unknown>"))
6.2.9200.16384
```

In summary, Model Objects contain all the data associated with a specific type of API call. In this example, the `cbapi.response.models.Binary` Model Object reflects all the data available via the `/api/v1/binary` API route on a CB Response server.



### 4.3.2 Joining Model Objects

Many times, there are relationships between different Model Objects. To make navigating these relationships easy, cbapi provides special properties to “join” Model Objects together. For example, a `cbapi.response.models.Process` Model Object can reference the `cbapi.response.models.Sensor` or `cbapi.response.models.Binary` associated with this Process.

In this case, special “join” properties are provided for you. When you use one of these properties, cbapi will automatically retrieve the associated Model Object, if necessary.

This capability may sound like a performance killer, causing many unnecessary API calls in order to gather this data. However, cbapi has extensive Model Object caching built-in, so multiple requests for the same data will be eliminated and an API request is only made if the cache does not already contain the requested data.

For example, to print the name of the Sensor Group assigned to the Sensor that ran a specific Process:

```
>>> print(proc.sensor.group.name)
Default Group
```

Behind the scenes, this makes at most two API calls: one to obtain the Sensor associated with the Process, then another to obtain the Sensor Group that Sensor is part of. If either the Sensor or Sensor Group are already present in cbapi’s internal cache, the respective API call is not made and the data is returned directly from the internal cache.

In summary, some Model Objects have special “join” properties that provide easy access to related Model Objects. A list of “join” properties is included as part of the documentation for each Model Object.

### 4.3.3 Queries

Now that we’ve covered how to get data out of a specific Model Object, we now need to learn how to obtain Model Objects in the first place! To do this, we have to create and execute a Query. cbapi Queries use the same query syntax accepted by CB Response or Protection’s APIs, and add a few little helpful features along the way.

To create a query in cbapi, use the `.select()` method on the `CbResponseAPI` or `CbProtectionAPI` object. Pass the Model Object type as a parameter to the `.select()` call and optionally add filtering criteria with `.where()` clauses.

Let’s start with a simple query for CB Response:

```
>>> from cbapi.response import *
>>> cb = CbResponseAPI()
>>> cb.select(Process).where("process_name:cmd.exe")
<cbapi.response.rest_api.Query object at 0x1068815d0>
```

This returns a prepared Query object with the query string `process_name:cmd.exe`. Note that at this point no API calls have been made. The cbapi Query objects are “lazy” in that they are only evaluated when you use them. If you create a Query object but never attempt to retrieve any results, no API call is ever made (I suppose that answers the age-old question; if a Query object is created, but nobody uses it, it does not make a sound, after all).

What can we do with a Query? The first thing we can do is compose new Queries. Most Query types in cbapi can be “composed”; that is, you can create a new query from more than one query string. This can be useful if you have a “base” query and want to add additional filtering criteria. For example, if we take the query above and add the additional filtering criteria (`filemod:*.exe` or `filemod:*.dll`), we can write:

```
>>> base_query = cb.select(Process).where("process_name:cmd.exe")
>>> composed_query = base_query.where("(filemod:*.exe or filemod:*.dll)")
```

Now the `composed_query` is equivalent to a query of `process_name:cmd.exe (filemod:*.exe or filemod:*.dll)`. You can also add sorting criteria to a query:

```
>>> sorted_query = composed_query.sort("last_update asc")
```

Now when we execute the `sorted_query`, the results will be sorted by the last server update time in ascending order.

Ok, now we're ready to actually execute a query and retrieve the results. You can think of a Query as a kind of "infinite" Python list. Generally speaking, you can use all the familiar ways to access a Python list to access the results of a cbapi query. For example:

```
>>> len(base_query)      # How many results were returned for the query?
3

>>> base_query[:2]      # I want the first two results
[<cbapi.response.models.Process: id 00000003-0000-036c-01d2-2efd3af51186-00000001> @_
↪https://cbserver,
<cbapi.response.models.Process: id 00000003-0000-07d4-01d2-2efcd4949dfc-00000001> @_
↪https://cbserver]

>>> base_query[-1:]     # I want the last result
[<cbapi.response.models.Process: id 00000002-0000-0f2c-01d2-2a57625ca0dd-00000001> @_
↪https://cbserver]

>>> for proc in base_query: # Loop over all the results
>>>     print(proc.cmdline)
"C:\Windows\system32\cmd.exe"
"C:\Windows\system32\cmd.exe"
"C:\Windows\system32\cmd.exe"

>>> procs = list(base_query) # Just make a list of all the results
```

In addition to using a Query object as an array, two helper methods are provided as common shortcuts. The first method is `.one()`. The `.one()` method is useful when you know only one result should match your query; it will throw a `MoreThanOneResultError` exception if there are zero or more than one results for the query. The second method is `.first()`, which will return the first result from the result set, or `None` if there are no results.

Every time you access a Query object, it will perform a REST API query to the Carbon Black server. For large result sets, the results are retrieved in batches- by default, 100 results per API request on CB Response and 1,000 results per API request on CB Protection. The search queries themselves are not cached, but the resulting Model Objects are.

### 4.3.4 Retrieving Objects by ID

Every Model Object (and in fact any object addressable via the REST API) has a unique ID associated with it. If you already have a unique ID for a given Model Object, for example, a Process GUID for CB Response, or a Computer ID for CB Protection, you can ask cbapi to give you the associated Model Object for that ID by passing that ID to the `.select()` call. For example:

```
>>> binary = cb.select(Binary, "CA4FAFFA957C71C006B59E29DFE3EB8B")
>>> print(binary.file_desc)
PNRP Name Space Provider
```

Note that retrieving an object via `.select()` with the ID does not automatically request the object from the server via the API. If the Model Object is already in the local cache, the locally cached version is returned. If it is not, a "blank" Model Object is created and is initialized only when an attempt is made to read a property. Therefore, assuming an empty cache, in the example above, the REST API query would not happen until the second line (the `print` statement). If you want to ensure that an object exists at the time you call `.select()`, add the `force_init=True`

keyword parameter to the `.select()` call. This will cause cbapi to force a refresh of the object and if it does not exist, cbapi will throw a `ObjectNotFoundError` exception.

### 4.3.5 Creating New Objects

The CB Response and Protection REST APIs provide the ability to insert new data under certain circumstances. For example, the CB Response REST API allows you to insert a new banned hash into its database. Model Objects that represent these data types can be “created” in cbapi by using the `create()` method:

```
>>> bh = cb.create(BannedHash)
```

If you attempt to create a Model Object that cannot be created, you will receive a `ApiError` exception.

Once a Model Object is created, it’s blank (it has no data). You will need to set the required properties and then call the `.save()` method:

```
>>> bh = cb.create(BannedHash)
>>> bh.text = "Banned from API"
>>> bh.md5sum = "CA4FAFFA957C71C006B59E29DFE3EB8B"
>>> bh.save()
```

If you don’t fill out all the properties required by the API, then you will receive an `InvalidObjectError` exception with a list of the properties that are required and not currently set.

Once the `.save()` method is called, the appropriate REST API call is made to create the object. The Model Object is then updated to the current state returned by the API, which may include additional data properties initialized by CB Response or Protection.

### 4.3.6 Modifying Existing Objects

The same `.save()` method can be used to modify existing Model Objects if the REST API provides that capability. If you attempt to modify a Model Object that cannot be changed, you will receive a `ApiError` exception.

For example, if you want to change the “jgarman” user’s password to “cbisawesome”:

```
>>> user = cb.select(User, "jgarman")
>>> user.password = "cbisawesome"
>>> user.save()
```

### 4.3.7 Deleting Objects

Simply call the `.delete()` method on a Model Object to delete it (again, if you attempt to delete a Model Object that cannot be deleted, you will receive a `ApiError` exception).

Example:

```
>>> user = cb.select(User, "jgarman")
>>> user.delete()
```

### 4.3.8 Tracking Changes to Objects

Internally, Model Objects track all changes between when they were last refreshed from the server up until `.save()` is called. If you’re interested in what properties have been changed or added, simply `print` the Model Object.

You will see a display like the following:

```
>>> user = cb.create(User)
>>> user.username = "jgarman"
>>> user.password = "cbisawesome"
>>> user.first_name = "Jason"
>>> user.last_name = "Garman"
>>> user.teams = []
>>> user.global_admin = False
>>> print(user)
User object, bound to https://cbserver.
Partially initialized. Use .refresh() to load all attributes
-----

(+)          email: jgarman@carbonblack.com
(+)          first_name: Jason
(+)          global_admin: False
              id: None
(+)          last_name: Garman
(+)          password: cbisawesome
(+)          teams: []
(+)          username: jgarman
```

Here, the (+) symbol before a property name means that the property will be added the next time that `.save()` is called. Let's call `.save()` and modify one of the Model Object's properties:

```
>>> user.save()
>>> user.first_name = "J"
>>> print(user)
print(user)
User object, bound to https://cbserver.
Last refreshed at Mon Nov 7 16:54:00 2016
-----

(*)          email: jgarman@carbonblack.com
(*)          first_name: J
              global_admin: False
              id: jgarman
              last_name: Garman
              teams: []
              username: jgarman
```

The (\*) symbol means that a property value will be changed the next time that `.save()` is called. This time, let's forget about our changes by calling `.reset()` instead:

```
>>> user.reset()
>>> print(user.first_name)
Jason
```

Now the user Model Object has been restored to the original state as it was retrieved from the server.

## 4.4 Logging & Diagnostics

The cbapi provides extensive logging facilities to track down issues communicating with the REST API and understand potential performance bottlenecks.

### 4.4.1 Enabling Logging

The cbapi uses Python’s standard logging module for logging. To enable debug logging for the cbapi, you can do the following:

```
>>> import logging
>>> root = logging.getLogger()
>>> root.addHandler(logging.StreamHandler())
>>> logging.getLogger("cbapi").setLevel(logging.DEBUG)
```

All REST API calls, including the API endpoint, any data sent via POST or PUT, and the time it took for the call to complete:

```
>>> user.save()
Creating a new User object
Sending HTTP POST /api/user with {"email": "jgarman@carbonblack.com", "first_name":
↪"Jason", "global_admin": false, "id": null, "last_name": "Garman", "password":
↪"cbisawesome", "teams": [], "username": "jgarman"}
HTTP POST /api/user took 0.079s (response 200)
Received response: {u'result': u'success'}
HTTP GET /api/user/jgarman took 0.011s (response 200)
```

## 4.5 CB Response API Examples

Now that we’ve covered the basics, let’s step through a few examples using the CB Response API. In these examples, we will assume the following boilerplate code to enable logging and establish a connection to the “default” CB Response server in our credential file:

```
>>> import logging
>>> root = logging.getLogger()
>>> root.addHandler(logging.StreamHandler())
>>> logging.getLogger("cbapi").setLevel(logging.DEBUG)

>>> from cbapi.response import *
>>> cb = CbResponseAPI()
```

With that boilerplate out of the way, let’s take a look at a few examples.

### 4.5.1 Download a Binary from CB Response

Let’s grab a binary that CB Response has collected from one of the endpoints. This can be useful if you want to send this binary for further automated analysis or pull it down for manual reverse engineering. You can see a full example with command line options in the examples directory: `binary_download.py`.

Let’s step through the example:

```
>>> import shutil
>>> md5 = "7FB55F5A62E78AF9B58D08AAEEAEF848"
>>> binary = cb.select(Binary, md5)
>>> shutil.copyfileobj(binary.file, open(binary.original_filename, "wb"))
```

First, we select the binary by its primary key: the MD5 hash of the binary contents. The third line requests the binary file data by accessing the `file` property on the Binary Model Object. The `file` property acts as a read-only, Python file-like object. In this case, we use the Python `shutil` library to copy one file object to another. The advantage of

using `shutil` is that the file is copied in chunks, and the full file does not have to be read into memory before saving it to disk.

Another way to use the `file` property is to call `.read()` on it just like any other Python file object. The following code will read the first two bytes from the Binary:

```
>>> binary.file.read(2)
"MZ"
```

## 4.5.2 Ban a Binary

Now let's take this binary and add a Banning rule for it. To do this, we create a new `BannedHash` Model Object:

```
>>> bh = cb.create(BannedHash)
>>> bh.md5hash = binary.md5
>>> bh.text = "Banned from API"
>>> bh.enabled = True
>>> bh.save()
Creating a new BannedHash object
Sending HTTP POST /api/v1/banning/blacklist with {"md5hash":
↳ "7FB55F5A62E78AF9B58D08AAEEAEF848", "text": "banned from API"}
HTTP POST /api/v1/banning/blacklist took 0.035s (response 200)
Received response: {'result': 'success'}
HTTP GET /api/v1/banning/blacklist/7FB55F5A62E78AF9B58D08AAEEAEF848 took 0.039s
↳ (response 200)
```

Note that if the hash is already banned in CB Response, then you will receive a `ServerError` exception with the message that the banned hash already exists.

## 4.5.3 Isolate a Sensor

Switching gears, let's take a Sensor and quarantine it from the network. The CB Response network isolation functionality allows administrators to isolate endpoints that may be actively involved in an incident, while preserving access to perform Live Response on that endpoint and collect further endpoint telemetry.

To isolate a sensor, we first need to acquire its Sensor Model Object:

```
>>> sensor = cb.select(Sensor).where("hostname:HOSTNAME").first()
```

This will select the first sensor that matches the hostname `HOSTNAME`. Now we can isolate that machine:

```
>>> sensor.isolate()
Updating Sensor with unique ID 4
Sending HTTP PUT /api/v1/sensor/4 with {"boot_id": "0", "build_id": 5, "build_version_
↳ string": "005.002.000.61003", ...}
HTTP PUT /api/v1/sensor/4 took 0.129s (response 204)
HTTP GET /api/v1/sensor/4 took 0.050s (response 200)
...
True
```

The `.isolate()` method will keep polling the CB Response server until the sensor has confirmed that it is now isolated from the network. If the sensor is offline or otherwise unreachable, this call could never return. Therefore, there is also a `timeout=` keyword parameter that can be used to set an optional timeout that, if reached, will throw a `TimeoutError` exception. The `.isolate()` function returns `True` when the sensor is successfully isolated.

When you're ready to restore full network connectivity to the sensor, simply call the `.unisolate()` method:

```
>>> sensor.unisolate()
Updating Sensor with unique ID 4
Sending HTTP PUT /api/v1/sensor/4 with {"boot_id": "0", "build_id": 5, "build_version_
↳string": "005.002.000.61003", ...}
HTTP PUT /api/v1/sensor/4 took 0.077s (response 204)
HTTP GET /api/v1/sensor/4 took 0.020s (response 200)
...
True
```

Again, once the sensor is back on the network, the `.unisolate()` method will return `True`. Just like `.isolate()`, you can optionally specify a timeout using the `timeout=` keyword parameter.

#### 4.5.4 Querying Processes and Events

Now, let's do some queries into the CB Response database. The true power of CB Response is its continuous recording and powerful query language that allows you to go back in time and track the root cause of any security incident on your endpoints. Let's start with a simple query to find instances of a specific behavioral IOC, where our attacker used the built-in Windows tool `net.exe` to mount an internal network share. We will iterate over all uses of `net.exe` to mount our target share, printing out the parent processes that led to the execution of the offending command:

```
>>> query = cb.select(Process).where("process_name:net.exe").and_(r
↳"cmdline:\\test\blah").group_by("id")
>>> def print_details(proc, depth):
...     print("%s%s: %s ran %s" % (" " * depth, proc.start, proc.username, proc.
↳cmdline))
...
>>> for proc in query:
...     print_details(proc, 0)
...     proc.walk_parents(print_details)
...
HTTP GET /api/v1/process?cb.urlver=1&facet=false&q=process_name%3Anet.exe+cmdline%3A
↳%5C%5Ctest%5Cblah&rows=100&sort=last_update+desc&start=0 took 0.462s (response 200)
2016-11-11 20:59:31.631000: WIN-IA9NQ1GN8OI\bit9rad ran net use y: \\test\blah
HTTP GET /api/v3/process/00000003-0000-036c-01d2-2efd3af51186/1/event took 0.036s_
↳(response 200)
2016-10-25 20:20:29.790000: WIN-IA9NQ1GN8OI\bit9rad ran "C:\Windows\system32\cmd.exe"
HTTP GET /api/v3/process/00000003-0000-0c34-01d2-2ec94f09cae6/1/event took 0.213s_
↳(response 200)
2016-10-25 14:08:49.651000: WIN-IA9NQ1GN8OI\bit9rad ran C:\Windows\Explorer.EXE
HTTP GET /api/v3/process/00000003-0000-0618-01d2-2ec94edef208/1/event took 0.013s_
↳(response 200)
2016-10-25 14:08:49.370000: WIN-IA9NQ1GN8OI\bit9rad ran_
↳C:\Windows\system32\userinit.exe
HTTP GET /api/v3/process/00000003-0000-02ec-01d2-2ec9412b4b70/1/event took 0.017s_
↳(response 200)
2016-10-25 14:08:26.382000: SYSTEM ran winlogon.exe
HTTP GET /api/v3/process/00000003-0000-02b0-01d2-2ec94115df7a/1/event took 0.012s_
↳(response 200)
2016-10-25 14:08:26.242000: SYSTEM ran \SystemRoot\System32\smss.exe 00000001_
↳00000030
HTTP GET /api/v3/process/00000003-0000-0218-01d2-2ec93f813429/1/event took 0.021s_
↳(response 200)
2016-10-25 14:08:23.590000: SYSTEM ran \SystemRoot\System32\smss.exe
HTTP GET /api/v3/process/00000003-0000-0004-01d2-2ec93f7c7181/1/event took 0.081s_
↳(response 200)
2016-10-25 14:08:23.559000: SYSTEM ran c:\windows\system32\ntoskrnl.exe
```

(continues on next page)

(continued from previous page)

```

HTTP GET /api/v3/process/00000003-0000-0000-01d2-2ec93f6051ee/1/event took 0.011s_
↳ (response 200)
    2016-10-25 14:08:23.374000: ran c:\windows\system32\ntoskrnl.exe
HTTP GET /api/v3/process/00000003-0000-0004-01d2-2ec93f6051ee/1/event took 0.011s_
↳ (response 200)
2016-11-11 20:59:25.667000: WIN-IA9NQ1GN8OI\bit9rad ran net use z: \\test\blah
2016-10-25 20:20:29.790000: WIN-IA9NQ1GN8OI\bit9rad ran "C:\Windows\system32\cmd.exe"
    2016-10-25 14:08:49.651000: WIN-IA9NQ1GN8OI\bit9rad ran C:\Windows\Explorer.EXE
    2016-10-25 14:08:49.370000: WIN-IA9NQ1GN8OI\bit9rad ran_
↳ C:\Windows\system32\userinit.exe
    2016-10-25 14:08:26.382000: SYSTEM ran winlogon.exe
    2016-10-25 14:08:26.242000: SYSTEM ran \SystemRoot\System32\smss.exe 00000001_
↳ 00000030
    2016-10-25 14:08:23.590000: SYSTEM ran \SystemRoot\System32\smss.exe
    2016-10-25 14:08:23.559000: SYSTEM ran c:\windows\system32\ntoskrnl.exe
    2016-10-25 14:08:23.374000: ran c:\windows\system32\ntoskrnl.exe

```

That was a lot in one code sample, so let's break it down part-by-part.

First, we set up the `query` variable by creating a new `Query` object using the `.where()` and `.and_()` methods. Next, we define a function that will get called on each parent process all the way up the chain to the system kernel loading during the boot process. This function, `print_details`, will print a few data points about each process: namely, the local endpoint time when that process started, the user who spawned the process, and the command line for the process.

Finally, we execute our query by looping over the result set with a Python `for` loop. For each process that matches the query, first we print details of the process itself (the process that called `net.exe` with a command line argument of our target share `\\test\blah`), then calls the `.walk_parents()` helper method to walk up the chain of all parent processes. Each level of parent process (the "depth") is represented by an extra space; therefore, reading backwards, you can see that `ntoskrnl.exe` spawned `smss.exe`, which in turn spawned `winlogon.exe`, and so on. You can see the full backwards chain of events that ultimately led to the execution of each of these `net.exe` calls.

Remember that we have logging turned on for these examples, so you see each of the HTTP GET requests to retrieve process event details as they happen. Astute observers will note that walking the parents of the second `net.exe` command, where the `\\test\blah` share was mounted on the `z:` drive, did not trigger additional HTTP GET requests. This is thanks to `cbapi`'s caching layer. Since both `net.exe` commands ran as part of the same command shell session, the parent processes are shared between the two executions. Since the parent processes were already requested as part of the previous walk up the chain of parent processes, `cbapi` did not re-request the data from the server, instead using its internal cache to satisfy the process information requests from this script.

## New Filters: Group By, Time Restrictions

In the query above, there is an extra `.group_by()` method. This method is new in `cbapi` 1.1.0 and is part of five new query filters available when communicating with a CB Response 6.1 server. These filters are accessible via methods on the `Process Query` object. These new methods are:

- `.group_by()` - Group the result set by a field in the response. Typically you will want to group by `id`, which will ensure that the result set only has one result per *process* rather than one result per *event segment*. For more information on processes, process segments, and how segments are stored in CB Response 6.0, see the [Process API Changes for CB Response 6.0](#) page on the Developer Network website.
- `.min_last_update()` - Only return processes that have events after a given date/time stamp (relative to the individual sensor's clock)
- `.max_last_update()` - Only return processes that have events before a given date/time stamp (relative to the individual sensor's clock)



- `.min_last_server_update()` - Only return processes that have events after a given date/time stamp (relative to the CB Response server's clock)
- `.max_last_server_update()` - Only return processes that have events before a given date/time stamp (relative to the CB Response server's clock)

CB Response 6.1 uses a new way of recording process events that greatly increases the speed and scale of collection, allowing you to store and search data for more endpoints on the same hardware. Details on the new database format can be found on the Developer Network website at the [Process API Changes for CB Response 6.0](#) page.

The `Process` Model Object traditionally referred to a single “segment” of events in the CB Response database. In CB Response versions prior to 6.0, a single segment will include up to 10,000 individual endpoint events, enough to handle over 95% of the typical event activity for a given process. Therefore, even though a `Process` Model Object technically refers to a single *segment* in a process, since most processes had less than 10,000 events and therefore were only comprised of a single segment, this distinction wasn't necessary.

However, now that processes are split across many segments, a better way of handling this is necessary. Therefore, CB Response 6.0 introduces the new `.group_by()` method.

## More on Filters

Querying for a process will return *all* segments that match. For example, if you search for `process_name:cmd.exe`, the result set will include *all* segments of *all* `cmd.exe` processes. Therefore, CB Response 6.1 introduced the ability to “group” result sets by a field in the result. Typically you will want to group by the internal process id (the `id` field), and this is what we did in the query above. Grouping by the `id` field will ensure that only one result is returned per *process* rather than per *segment*.

Let's take a look at an example:

```
>>> from datetime import datetime, timedelta
>>> yesterday = datetime.utcnow() - timedelta(days=1) # Get "yesterday" in GMT
>>> for proc in c.select(Process).where("process_name:cmd.exe").min_last_
↳update(yesterday):
...     print proc.id, proc.segment
DEBUG:cbapi.connection:HTTP GET /api/v1/process?cb.min_last_update=2017-05-21T18%3A41
↳%3A58Z&cb.urlver=1&facet=false&q=process_name%3Acmd.exe&rows=100&sort=last_
↳update+desc&start=0 took 2.164s (response 200)
00000001-0000-0e48-01d2-c2a397f4cfe0 1495465643405
00000001-0000-0e48-01d2-c2a397f4cfe0 1495465407157
00000001-0000-0e48-01d2-c2a397f4cfe0 1495463680155
00000001-0000-0e48-01d2-c2a397f4cfe0 1495463807694
00000001-0000-0e48-01d2-c2a397f4cfe0 1495463543944
00000001-0000-0e48-01d2-c2a397f4cfe0 1495463176570
00000001-0000-0e48-01d2-c2a397f4cfe0 1495463243492
```

Notice that the “same” process ID is returned seven times, but with seven different segment IDs. CB Response will return *every* process event segment that matches a given query, in this case, any event segment that contains the process command name `cmd.exe`.

That is, however, most likely not what you wanted. Instead, you'd like a list of the *unique* processes associated with the command name `cmd.exe`. Just add the `.group_by("id")` filter to your query:

```
>>> for proc in c.select(Process).where("process_name:cmd.exe").min_last_
↳update(yesterday).group_by("id"):
...     print proc.id, proc.segment
DEBUG:cbapi.connection:HTTP GET /api/v1/process?cb.group=id&cb.min_last_update=2017-
↳05-21T18%3A41%3A58Z&cb.urlver=1&facet=false&q=process_name%3Acmd.exe&rows=100&
↳sort=last_update+desc&start=0 took 2.163s (response 200)
```

(continues on next page)

```
00000001-0000-0e48-01d2-c2a397f4cfe0 1495465643405
```

## 4.5.5 Feed and Watchlist Maintenance

The cbapi provides several helper functions to assist in creating watchlists and

Watchlists are simply saved Queries that are automatically run on the CB Response server on a periodic basis. Results of the watchlist are tagged in the database and optionally trigger alerts. Therefore, a cbapi Query can easily be converted into a watchlist through the Query `.create_watchlist()` function:

```
>>> new_watchlist = query.create_watchlist("[WARN] Attempts to mount internal share")
Creating a new Watchlist object
Sending HTTP POST /api/v1/watchlist with {"id": null, "index_type": "events", "name":
↳ "[WARN] Attempts to mount internal share", "search_query": "facet=false&q=process_
↳ name%3Anet.exe+cmdline%3A%5C%5Ctest%5Cblah&cb.urlver=1&sort=last_update+desc"}
HTTP POST /api/v1/watchlist took 0.510s (response 200)
Received response: {u'id': 222}
Only received an ID back from the server, forcing a refresh
HTTP GET /api/v1/watchlist/222 took 0.034s (response 200)
```

This helper function will automatically create a watchlist from the Query object with the given name.

If you have a watchlist that already exists, the Watchlist Model Object can help you extract the human-readable query from the watchlist. Just select the watchlist and access the `.query` property on the Watchlist Model Object:

```
>>> my_watchlist = cb.select(Watchlist).where("name:[WARN] Attempts to mount internal_
↳ share").one()
>>> print(my_watchlist.query)
process_name:net.exe cmdline:\\test\blah
```

You can also execute the query straight from the Watchlist Model Object:

```
>>> len(my_watchlist.search())
HTTP GET /api/v1/process?cb.urlver=1&facet=false&q=process_name%3Anet.exe+cmdline%3A
↳ %5C%5Ctest%5Cblah&rows=0&start=0 took 0.477s (response 200)
2
```

And finally, you can of course enable and disable Watchlists:

```
>>> my_watchlist.enabled = False
>>> my_watchlist.save()
Updating Watchlist with unique ID 222
Sending HTTP PUT /api/v1/watchlist/222 with {"alliance_id": null, "date_added": "2016-
↳ 11-15 23:48:27.615993-05:00", "enabled": false, "from_alliance": false, "group_id":
↳ -1, "id": "222", "index_type": "events", "last_hit": "2016-11-15 23:50:08.448685-
↳ 05:00", "last_hit_count": 2, "name": "[WARN] Attempts to mount internal share",
↳ "readonly": false, "search_query": "facet=false&q=process_name%3Anet.exe%20cmdline
↳ %3A%5C%5Ctest%5Cblah&cb.urlver=1", "search_timestamp": "2016-11-16T04:50:01.750240Z
↳ ", "total_hits": "2", "total_tags": "2"}
HTTP PUT /api/v1/watchlist/222 took 0.036s (response 200)
Received response: {u'result': u'success'}
HTTP GET /api/v1/watchlist/222 took 0.029s (response 200)
```

You can see more examples of Feed and Watchlist maintenance in the `feed_operations.py` and `watchlist_operations.py` example scripts.

## 4.5.6 Managing Threat Reports & Alerts

The cbapi provides helper functions to manage alerts and threat reports in bulk. The Query objects associated with the ThreatReport and Alert Model Objects provide a few bulk operations to help manage large numbers of Threat Reports and Alerts, respectively.

To mark a large number of Threat Reports as false positives, create a query that matches the Reports you're interested in. For example, if every Report from the Feed named "SOC" that contains the word "FUZZYWOMBAT" in the report title should be considered a false positive (and no longer trigger Alerts), you can write the following code to do so:

```
>>> feed = c.select(Feed).where("name:SOC").one()
>>> report_query = feed.reports.where("title:FUZZYWOMBAT")
>>> report_query.set_ignored()
```

Similar actions can be taken on Alerts. The AlertQuery object exposes three helper methods to perform bulk operations on sets of Alerts: `.set_ignored()`, `.assign_to()`, and `.change_status()`.

## 4.5.7 Joining Everything Together

Now that we've examined how to request information on binaries, sensors, and processes through cbapi, let's chain this all together using the "join" functionality of cbapi's Model Objects. Let's just tweak the `print_details` function from above to add a few more contextual details. Our new function will now include the following data points for each process:

- The hostname the process was executed on
- The sensor group that host belongs to
- **If the binary was signed, also print out:**
  - The number of days between when the binary was signed and it was executed on the endpoint
  - The verified publisher name from the digital signature

We can transparently "join" between the Process Model Object and the Sensor, Sensor Group, and Binary Model Objects using the appropriately named helper properties. Here's the new function:

```
>>> import pytz

>>> def print_details(proc, depth):
...     print("On host {0} (part of sensor group {1}):".format(proc.hostname, proc.
↳sensor.group.name))
...     print("- At {0}, process {1} was executed by {2}".format(proc.start, proc.
↳cmdline, proc.username))
...     if proc.binary.signed:
...         # force local timestamp into UTC, we're just looking for an estimate here.
...         utc_timestamp = proc.start.replace(tzinfo=pytz.timezone("UTC"))
...         days_since_signed = (utc_timestamp - proc.binary.signing_data.sign_time).
↳days
...         print("- That binary ({0}) was signed by {1} {2} days before it was_
↳executed.".format(proc.process_md5,
...                 proc.binary.signing_data.publisher, days_since_signed))
```

Now if we run our for loop from above again:

```
>>> for proc in query:
...     print_details(proc, 0)
```

(continues on next page)

(continued from previous page)

```

...     proc.walk_parents(print_details)
...
HTTP GET /api/v1/process?cb.urlver=1&facet=false&q=process_name%3Anet.exe+cmdline%3A
↳%5C%5Ctest%5Cblah&rows=100&sort=last_update+desc&start=0 took 0.487s (response 200)
HTTP GET /api/v1/sensor/3 took 0.037s (response 200)
HTTP GET /api/group/1 took 0.022s (response 200)
On host WIN-IA9NQ1GN8OI (part of sensor group Default Group):
- At 2016-11-11 20:59:31.631000, process net use y: \\test\blah was executed by WIN-
↳IA9NQ1GN8OI\bit9rad
HTTP GET /api/v1/binary/79B6D4C5283FC806387C55B8D7C8B762/summary took 0.016s
↳(response 200)
- That binary (79b6d4c5283fc806387c55b8d7c8b762) was signed by Microsoft Corporation
↳1569 days before it was executed.
HTTP GET /api/v3/process/00000003-0000-036c-01d2-2efd3af51186/1/event took 0.045s
↳(response 200)
On host WIN-IA9NQ1GN8OI (part of sensor group Default Group):
- At 2016-10-25 20:20:29.790000, process "C:\Windows\system32\cmd.exe" was executed
↳by WIN-IA9NQ1GN8OI\bit9rad
HTTP GET /api/v1/binary/BF93A2F9901E9B3DFCA8A7982F4A9868/summary took 0.015s
↳(response 200)
- That binary (bf93a2f9901e9b3dfca8a7982f4a9868) was signed by Microsoft Corporation
↳1552 days before it was executed.

```

Those few lines of Python above are jam-packed with functionality. Now for each process execution, we have added contextual information on the source host, the group that host is part of, and details about the signing status of the binary that was executed. The magic is performed behind the scenes when we use the `.binary` and `.sensor` properties on the Process Model Object. Just like our previous example, cbapi's caching layer ensures that we do not overload the CB Response server with duplicate requests for the same data. In this example, multiple redundant requests for sensor, sensor group, and binary data are all eliminated by cbapi's cache.

## 4.5.8 Facets

The cbapi also provides functionality to pull facet information from the database. You can use the `.facet()` method on a Query object to retrieve facet (ie. "group") information for a given query result set. Here's an example that pulls the most common process names for our sample host:

```

>>> def print_facet_histogram(facets):
...     for entry in facets:
...         print("%15s: %5s%% %s" % (entry["name"][:15], entry["ratio"], u"\u25A0
↳"* (int(entry["percent"])/2)))
...
>>> facet_query = cb.select(Process).where("hostname:WIN-IA9NQ1GN8OI").and_(
↳"username:bit9rad")
>>> print_facet_histogram(facet_query.facets("process_name")["process_name"])

HTTP GET /api/v1/process?cb.urlver=1&facet=true&facet.field=process_name&facet.
↳field=username&q=hostname%3AWIN-IA9NQ1GN8OI+username%3Abit9rad&rows=0&start=0 took
↳0.024s (response 200)
    chrome.exe: 23.4% =====
thumbnailextrac: 15.4% =====
    adobearm.exe: 8.6% =====
    taskhost.exe: 6.0% =====
    conhost.exe: 4.7% =====

```

(continues on next page)

(continued from previous page)

```
ping.exe: 4.0% =====
wormgr.exe: 3.5% =====
```

In the above example, we just pulled one facet: the `process_name`; you can ask the server for faceting on multiple fields in one query by simply listing the fields in the call to `.facet()`: for example, `.facet("username", "process_name")` will produce a dictionary with two top-level keys: `username` and `process_name`.

## 4.5.9 Administrative Tasks

In addition to querying data, you can also perform various administrative tasks using `cbapi`.

Let's create a user on our CB Response server:

```
>>> user = cb.create(User)
>>> user.username = "jgarman"
>>> user.password = "cbisawesome"
>>> user.first_name = "Jason"
>>> user.last_name = "Garman"
>>> user.email = "jgarman@carbonblack.com"
>>> user.teams = []
>>> user.global_admin = False
Creating a new User object
Sending HTTP POST /api/user with {"email": "jgarman@carbonblack.com", "first_name":
↳ "Jason", "global_admin": false, "id": null, "last_name": "Garman", "password":
↳ "cbisawesome", "teams": [], "username": null}
HTTP POST /api/user took 0.608s (response 200)
Received response: {'result': 'success'}
```

How about moving a sensor to a new Sensor Group:

```
>>> sg = cb.create(SensorGroup)
>>> sg.name = "Critical Endpoints"
>>> sg.site = 1
>>> sg.save()
Creating a new SensorGroup object
Sending HTTP POST /api/group with {"id": null, "name": "Critical Endpoints", "site_id
↳ ": 1}
HTTP POST /api/group took 0.282s (response 200)
Received response: {'id': 2}
Only received an ID back from the server, forcing a refresh
HTTP GET /api/group/2 took 0.011s (response 200)
>>> sensor = cb.select(Sensor).where("hostname:WIN-IA9NQ1GN8OI").first()
>>> sensor.group = sg
>>> sensor.save()
Updating Sensor with unique ID 3
Sending HTTP PUT /api/v1/sensor/3 with {"boot_id": "2", "build_id": 2, "build_version_
↳ string": "005.002.000.60922", ...}
HTTP PUT /api/v1/sensor/3 took 0.087s (response 204)
HTTP GET /api/v1/sensor/3 took 0.030s (response 200)
```

## 4.6 CbAPI and Live Response

Working with the CB Live Response REST API directly can be difficult. Thankfully, just like the rest of Carbon Black's REST APIs, `cbapi` provides Pythonic APIs to make working with the Live Response API much easier.

In addition to easy-to-use APIs to call into Live Response, cbapi also provides a “job-based” interface that allows cbapi to intelligently schedule large numbers of concurrent Live Response sessions across multiple sensors. Your code can then be notified when the jobs are complete, returning the results of the job if it succeeded or the Exception if it failed.

### 4.6.1 Getting Started with Live Response

The cbapi Live Response API is built around establishing a `cbapi.response.live_response.LiveResponseSession` object from a `cbapi.response.models.Sensor` Model Object. Then you can call methods on the `LiveResponseSession` object to perform Live Response actions on the target host. These calls are synchronous, meaning that they will wait until the action is complete and a result is available, before returning back to your script. Here’s an example:

```
>>> from cbapi.response import *
>>> cb = CbResponseAPI()
>>> sensor = cb.select(Sensor).where("hostname:WIN-IA9NQ1GN8OI").first()
>>> with sensor.lr_session() as session:
...     print(session.get_file(r"c:\test.txt"))

this is a test
```

Since the Live Response API is synchronous, the script will not continue until either the Live Response session is established and the file contents are retrieved, or an exception occurs (in this case, either a timeout error or an error reading the file).

As seen in the example above, the `.lr_session()` method is context-aware. CB Response has a limited number of concurrent Live Response session slots (by default, only ten). By wrapping the `.lr_session()` call within a `with` context, the session is automatically closed at the end of the block and frees that slot for another concurrent Live Response session in another script or user context.

A full listing of methods in the cbapi Live Response API is available in the documentation for the `cbapi.live_response_api.CbLRSessionBase` class.

### 4.6.2 Live Response Errors

There are four classes of errors that you will commonly encounter when working with the Live Response API:

- A `cbapi.errors.TimeoutError` is raised if a timeout is encountered when waiting for a response for a Live Response API request.
- A `cbapi.response.live_response_api.LiveResponseError` is raised if an error is returned during the execution of a Live Response command on an endpoint. The `LiveResponseError` includes detailed information about the error that occurred, including the exact error code that was returned from the endpoint and a textual description of the error.
- A `cbapi.errors.ApiError` is raised if you attempt to execute a command that is not supported by the sensor; for example, attempting to acquire a memory dump from a sensor running a pre-5.1 version of the agent will fail with an `ApiError` exception.
- A `cbapi.errors.ServerError` is raised if any other error occurs; for example, a 500 Internal Server Error is returned from the Live Response API.

### 4.6.3 Job-Based API

The basic Synchronous API described above in the Getting Started section works well for small tasks, targeting one sensor at a time. However, if you want to execute the same set of Live Response commands across a larger number of sensors, the cbapi provides a Job-Based Live Response API. The Job-Based Live Response API provides a straightforward API to submit Live Response jobs to a scheduler, schedule those Live Response jobs on individual endpoints concurrently, and return results and any errors back to you when the jobs complete. The Job-Based Live Response API is a natural fit with the Event-Based API to create IFTTT-style pipelines; if an event is received via the Event API, then perform Live Response actions on the affected endpoint via the Live Response Job-Based API.

The Job-Based API works by first defining a reusable “job” to perform on the endpoint. The Job is simply a class or function that takes a Live Response session object as input and performs a series of commands. Jobs can be as simple as retrieving a registry key, or as complex as collecting the Chrome browser history for any currently logged-in users.

Let’s look at an example Job to retrieve a registry key. This example job is pulled from the `get_reg_autoruns.py` example script:

```
class GetRegistryValue(object):
    def __init__(self, registry_key):
        self.registry_key = registry_key

    def run(self, session):
        reg_info = session.get_registry_value(self.registry_key)
        return time.time(), session.sensor_id, self.registry_key, reg_info["value_data"]
↵"]
```

To submit this job, you instantiate an instance of a `GetRegistryValue` class with the registry key you want to pull back from the endpoint, and submit the `.run()` method to the Live Response Job API:

```
>>> job = GetRegistryValue(regmod_path)
>>> registry_job = cb.live_response.submit_job(job.run, sensor_id)
```

Your script resumes execution immediately after the call to `.submit_job()`. The job(s) that you’ve submitted will be executed in a set of background threads managed by cbapi.

## 4.7 CbAPI Changelog

### 4.7.1 CbAPI 1.5.2 - Released September 9, 2019

#### Updates

- **CB Response**
  - Add support for `max_children` on Process search
- **CB LiveOps**
  - Add LQ device summaries
  - Add faceting for LQ results and LQ device summaries
  - Add LQ run history
- **CB ThreatHunter**
  - Fix an invalid search job creation

## 4.7.2 CbAPI 1.5.1 - Released July 23, 2019

### Updates

- **CB Response**
  - Require CbAPI users to obtain their API token from the CB Response console.
- **CB LiveOps**
  - Fixing a build issue

## 4.7.3 CbAPI 1.5.0 - Released July 23, 2019

### Updates

- **CB LiveOps**
  - Start new LiveQuery (LQ) runs
  - Fetch LQ results
  - View LQ run status
  - Filter on LQ results
- **PSC Org Key Management**
  - Added support for org key management within CbAPI
  - Credentials utility for org keys
  - PR #166, #169, #170

### Examples

- LiveQuery - manage\_run.py
- LiveQuery - run\_search.py

## 4.7.4 CbAPI 1.4.5 - Released July 11, 2019

### Updates

- **CB ThreatHunter**
  - Route updates for process search, feed management, watchlist management
  - Enforce org\_key presence
  - Org-based process search
  - Org-based event search
  - Org-based tree queries
- Minor updates for Python3 Compatibility

### Examples

- Updated CB TH Process Search Example
- Added process\_guid to process\_tree example for ThreatHunter



### 4.7.5 CbAPI 1.4.4 - Released July 3, 2019

#### Updates

- Carbon Black UBS Support PR #142
- CB Response - Fixing bulk update for Alerts to use v1 route
- Updates to use yaml safe\_load #157

#### Examples

- Refactored Carbon Black ThreatHunter examples
- Added process\_guid to process\_tree example for ThreatHunter

### 4.7.6 CbAPI 1.4.3 - Released May 7, 2019

#### Updates

- CB ThreatHunter - Feed fixes #156
- CB Response - Change Alert model object to use v2 route #155
- CB Response - Only view active LR sessions #154
- Removing refs to VT alliance feeds #144

#### Examples

- CB Defense - Create list\_events\_with\_cmdline\_csv.py #152
- CB Defense - Updated import link to proper module #148

### 4.7.7 CbAPI 1.4.2 - Released March 27, 2019

This release introduces additional support for CB PSC's ThreatHunter APIs

- Threat Intelligence APIs

### 4.7.8 CbAPI 1.4.1 - Released January 10, 2019

- Bug fixes
- Adding to authorized error to make it clear that users should check API creds

### 4.7.9 CbAPI 1.4.0 - Released January 10, 2019

This release introduces support for CB PSC's ThreatHunter APIs

- Process, Tree, and Search are supported with more to come

### 4.7.10 CbAPI 1.3.6 - Released February 14, 2018

This release has one critical fix:

- Fix a fatal exception when connecting to CB Response 6.1.x servers

### 4.7.11 CbAPI 1.3.5 - Released February 2, 2018

This release includes bugfixes and contributions from the Carbon Black community.

All products:

- More Python 3 compatibility fixes.
- Fix the `wait_for_completion` and `wait_for_output` options in the Live Response `.create_process()` method. If `wait_for_completion` is `True`, the call to `.create_process()` will block until the remote process has exited. If `wait_for_output` is `True`, then `.create_process()` will additionally wait until the output of the remote process is ready and return that output to the caller. Setting `wait_for_output` to `True` automatically sets `wait_for_completion` to `True` as well.
- The `BaseAPI` constructor now takes three new optional keyword arguments to control the underlying connection pool: `pool_connections`, `pool_maxsize`, and `pool_block`. These arguments are sent to the underlying `HTTPAdapter` used when connecting to the Carbon Black server. For more information on these parameters, see the [Python requests module API documentation for HTTPAdapter](#).

CB Defense:

- Date/time stamps in the Device model object are now represented as proper Python datetime objects, rather than integers.
- The `policy_operations.py` example script's "Replace Rule" command is fixed.
- Add the CB Live Response job-based API.
- Add a new example script `list_devices.py`

CB Response:

- The `Process` and `Binary` model objects now return `None` by default when a non-existent attribute is referenced, rather than throwing an exception.
- Fixes to `walk_children.py` example script.
- Fix exceptions in enumerating child processes, retrieving path and MD5sums from processes.
- Multiple `.where()` clauses can now be used in the `Sensor` model object.
- Workaround implemented for retrieving/managing more than 500 banned hashes.
- Alert bulk operations now work on batches of 500 alerts.
- `.flush_events()` method on `Sensor` model object no longer throws an exception on CB Response 6.x servers.
- `.restart_sensor()` method now available for `Sensor` model object.
- Fix `user_operations.py` example script to eliminate exception when adding a new user to an existing team.
- Add `.remove_team()` method on `User` model object.
- Automatically set `cb.legacy_5x_mode` query parameter for all `Process` queries whenever a legacy Solr core (from CB Response 5.x) is loaded.
- Added `.use_comprehensive_search()` method to enable the "comprehensive search" option on a `Process` query. See the [CB Developer Network documentation on Comprehensive Search](#) for more information on "comprehensive search".
- Add `.all_childprocs()`, `.all_modloads()`, `.all_filemods()`, `.all_regmods()`, `.all_crossprocs()`, and `.all_netconns()` methods to retrieve process events from all segments, rather

than the current process segment. You can also use the special segment “0” to retrieve process events across all segments.

- Fix `cmdline_filters` in the `IngressFilter` model object.

CB Protection:

- Tamper Protection can now be set and cleared in the `Computer` model object.

#### 4.7.12 CbAPI 1.3.4 - Released September 14, 2017

This release includes a critical security fix and small bugfixes.

Security fix:

- The underlying CbAPI connection class erroneously disabled hostname validation by default. This does *not* affect code that uses CbAPI through the public interfaces documented here; it only affects code that accesses the new `CbAPISessionAdapter` class directly. This class was introduced in version 1.3.3. Regardless, it is strongly recommended that all users currently using 1.3.3 upgrade to 1.3.4.

Bug fixes:

- Add rule filename parameter to CB Defense `policy_operations.py` script’s `add-rule` command.
- Add support for `tamperProtectionActive` attribute to CB Protection’s `Computer` object.
- Work around CB Response issue- the `/api/v1/sensor` route incorrectly returns an HTTP 500 if no sensors match the provided query. CbAPI now catches this exception and will instead return an empty set back to the caller.

#### 4.7.13 CbAPI 1.3.3 - Released September 1, 2017

This release includes security improvements and bugfixes.

Security changes:

- CbAPI enforces the use of HTTPS when connecting to on-premise CB Response servers.
- CbAPI can optionally require TLSv1.2 when connecting to Carbon Black servers.
  - Note that some versions of Python and OpenSSL, notably the version of OpenSSL packaged with Mac OS X, do not support TLSv1.2. This will cause CbAPI to fail to connect to CB Response 6.1+ servers which require TLSv1.2 cipher suites.
  - A new command, `cbapi check-tls`, will report the TLS version supported by your platform.
  - To enforce the use of TLSv1.2 when connecting to a server, add `ssl_force_tls_1_2=True` to that server’s credential profile.
- Add the ability to “pin” a specific server certificate to a credential profile.
  - You can now force TLS certificate verification on self-signed, on-premise installations of CB Response or Protection through the `ssl_cert_file` option in the credential profile.
  - To “pin” a server certificate, save the PEM-formatted server certificate to a file, and put the full path to that PEM file in the `ssl_cert_file` option of that server’s credential profile.
  - When using this option with on-premise CB Response servers, you may also have to set `ssl_verify_hostname=False` as the hostname in the certificate generated at install time is `localhost` and will not match the server’s hostname or IP address. This option will still validate that the server’s certificate is valid and matches the copy in the `ssl_cert_file` option.

Changes for CB Protection:

- The API now sets the appropriate “GET” query fields when changing fields such as the `debugFlags` on the `Computer` object.
- The `.template` attribute on the `Computer` model object has been renamed `.templateComputer`.
- Remove `AppCatalog` and `AppTemplate` model objects.

Changes for CB Response:

- Added `.webui_link` property to CB Response Query objects.
- Added `ban_hash.py` example.

Bug Fixes:

- Error handling is improved on Python 3. Live Response auto-reconnect functionality is now fixed on Python 3 as a result.
- Workaround implemented for CB Response 6.1 where `segment_ids` are truncated on Alerts. The `.process` attribute on an Alert now ignores the `segment_id` and links to the first `Process` segment.
- Fixed issue with `Binary.signed` and `CbModLoadEvent.is_signed`.

### 4.7.14 CbAPI 1.3.2 - Released August 10, 2017

This release introduces the Policy API for CB Defense. A sample `policy_operations.py` script is now included in the `examples` directory for CB Defense.

Other changes:

- CB Response
  - Bugfixes to the `User Model Object`.
  - New `user_operations.py` example script to manage users & teams.
  - Additional `Team Model Object` to add/remove/modify user teams.
  - New `check_datasharing.py` example script to check if third party data sharing is enabled for binaries on any sensor groups.
  - Documentation fix for the `User Model Object`.
  - Fix to the `watchlist_operations.py` example script.

### 4.7.15 CbAPI 1.3.1 - Released August 3, 2017

This is a bugfix release with minor changes:

- CB Response
  - Add `partition_operations.py` script to demonstrate the use of the `StoragePartition` model object.
  - Fix errors when accessing the `.start` attribute of child processes.
  - Fix errors generated by the `walk_children.py` example script. The output has been changed as well to indicate the process lifetime, console UI link, and command lines.
  - Add an `.end` attribute to the `Process` model object. This attribute reports back either `None` if the process is still executing, or the last event time associated with the process if it has exited. See the `walk_children.py` script for an example of how to calculate process lifetime.

- Fix errors when using the `.parents` attribute of a `Process`.
- Add `wait_for_completion` flag to `create_process` Live Response method, and default to `True`. The `create_process` method will now wait for the target process to complete before returning.
- CB Defense
  - Add `wait_for_completion` flag to `create_process` Live Response method, and default to `True`. The `create_process` method will now wait for the target process to complete before returning.

#### 4.7.16 CbAPI 1.3.0 - Released July 27, 2017

This release introduces the Live Response API for CB Defense. A sample `cblr_cli.py` script is now included in the `examples` directory for both CB Response and CB Defense.

Other changes:

- CB Protection
  - You can now create new `FileRule` and `Policy` model objects in `cbapi`.
- CB Response
  - Added `watchlist_exporter.py` and `watchlist_importer.py` scripts to the CB Response examples directory. These scripts allow you to export Watchlist data in a human- and machine-readable JSON format and then re-import them into another CB Response server.
  - The `Sensor` Model Object now uses the non-paginated (v1) API by default. This fixes any issues encountered when iterating over all the sensors and receiving duplicate and/or missing sensors.
  - Fix off-by-one error in `CbCrossProcess` object.
  - Fix issue iterating through `Process` Model Objects when accessing processes generated from a 5.2 server after upgrading to 6.1.
  - Reduce number of API requests required when accessing sibling information (parents, children, and siblings) from the `Process` Model Object.
  - Retrieve all events for a process when using `segment ID` of zero on a CB Response 6.1 server.
  - Behavior of `Process.children` attribute has changed:
    - \* Only one entry is present per child (before there were up to two; one for the spawn event, one for the terminate event)
    - \* The timestamp is derived from the start time of the process, not the timestamp from the spawn event. the two timestamps will be off by a few microseconds.
    - \* The old behavior is still available by using the `Process.childprocs` attribute instead. This incurs a performance penalty as another API call will have to be made to collect the `childproc` information.
  - `Binary` Model Object now returns `False` for `.is_signed` attribute if it is set to `(Unknown)`.
- Moved the `six` Python module into `cbapi` and removed the external dependency.

#### 4.7.17 CbAPI 1.2.0 - Released June 22, 2017

This release introduces compatibility with our new product, CB Defense, as well as adding new Model Objects introduced in the CB Protection 8.0 APIs.

Other changes:

- CB Response
  - New method `synchronize()` added to the `Feed Model Object`
- Bug fixes and documentation improvements

#### 4.7.18 CbAPI 1.1.1 - Released June 2, 2017

This release includes compatibility fixes for CB Response 6.1. Changes from 1.0.1 include:

- Substantial changes to the `Process Model Object` for CB Response 6.1. See details below.
- New `StoragePartition Model Object` to control Solr core loading/unloading in CB Response 6.1.
- New `IngressFilter Model Object` to control ingress filter settings in CB Response 6.1.
- Fix issues with `event_export.py` example script.
- Add `.all_events` property to the `Process Model Object` to expose a list of all events across all segments.
- Add example script to perform auto-banning based on watchlist hits from CB Event Forwarder S3 output files.
- Add bulk operations to the `ThreatReport` and `Alert Query` objects:
  - You can now call `.set_ignored()`, `.assign()`, and `.change_status()` on an `Alert Query` object to change the respective fields for every `Alert` that matches the query.
  - You can now call `.set_ignored()` on a `ThreatReport Query` object to set or clear the ignored flag for every `ThreatReport` that matches the query.

#### Changes to `Process Model Object` for CB Response 6.1

CB Response 6.1 uses a new way of recording process events that greatly increases the speed and scale of collection, allowing you to store and search data for more endpoints on the same hardware. Details on the new database format can be found on the Developer Network website at the [Process API Changes for CB Response 6.0](#) page.

The `Process Model Object` traditionally referred to a single “segment” of events in the CB Response database. In CB Response versions prior to 6.0, a single segment will include up to 10,000 individual endpoint events, enough to handle over 95% of the typical event activity for a given process. Therefore, even though a `Process Model Object` technically refers to a single *segment* in a process, since most processes had less than 10,000 events and therefore were only comprised of a single segment, this distinction wasn’t necessary.

However, now that processes are split across many segments, a better way of handling this is necessary. Therefore, CB Response 6.0 introduces the new `.group_by()` method. This method is new in cbapi 1.1.0 and is part of five new query filters available when communicating with a CB Response 6.1 server. These filters are accessible via methods on the `Process Query` object. These new methods are:

- `.group_by()` - Group the result set by a field in the response. Typically you will want to group by `id`, which will ensure that the result set only has one result per *process* rather than one result per *event segment*. For more information on processes, process segments, and how segments are stored in CB Response 6.0, see the [Process API Changes for CB Response 6.0](#) page on the Developer Network website.
- `.min_last_update()` - Only return processes that have events after a given date/time stamp (relative to the individual sensor’s clock)
- `.max_last_update()` - Only return processes that have events before a given date/time stamp (relative to the individual sensor’s clock)
- `.min_last_server_update()` - Only return processes that have events after a given date/time stamp (relative to the CB Response server’s clock)

- `.max_last_server_update()` - Only return processes that have events before a given date/time stamp (relative to the CB Response server's clock)

## Examples for new Filters

Let's take a look at an example:

```
>>> from datetime import datetime, timedelta
>>> yesterday = datetime.utcnow() - timedelta(days=1)      # Get "yesterday" in GMT
>>> for proc in c.select(Process).where("process_name:cmd.exe").min_last_
↳update(yesterday):
...     print proc.id, proc.segment
DEBUG:cbapi.connection:HTTP GET /api/v1/process?cb.min_last_update=2017-05-21T18%3A41
↳%3A58Z&cb.urlver=1&facet=false&q=process_name%3Acmd.exe&rows=100&sort=last_
↳update+desc&start=0 took 2.164s (response 200)
00000001-0000-0e48-01d2-c2a397f4cfe0 1495465643405
00000001-0000-0e48-01d2-c2a397f4cfe0 1495465407157
00000001-0000-0e48-01d2-c2a397f4cfe0 1495463680155
00000001-0000-0e48-01d2-c2a397f4cfe0 1495463807694
00000001-0000-0e48-01d2-c2a397f4cfe0 1495463543944
00000001-0000-0e48-01d2-c2a397f4cfe0 1495463176570
00000001-0000-0e48-01d2-c2a397f4cfe0 1495463243492
```

Notice that the "same" process ID is returned seven times, but with seven different segment IDs. CB Response will return *every* process event segment that matches a given query, in this case, any event segment that contains the process command name `cmd.exe`.

That is, however, most likely not what you wanted. Instead, you'd like a list of the *unique* processes associated with the command name `cmd.exe`. Just add the `.group_by("id")` filter to your query:

```
>>> for proc in c.select(Process).where("process_name:cmd.exe").min_last_
↳update(yesterday).group_by("id"):
...     print proc.id, proc.segment
DEBUG:cbapi.connection:HTTP GET /api/v1/process?cb.group=id&cb.min_last_update=2017-
↳05-21T18%3A41%3A58Z&cb.urlver=1&facet=false&q=process_name%3Acmd.exe&rows=100&
↳sort=last_update+desc&start=0 took 2.163s (response 200)
00000001-0000-0e48-01d2-c2a397f4cfe0 1495465643405
```





Once you've taken a look at the User Guide, read through some of the [examples on GitHub](#), and maybe even written some code of your own, the API documentation can help you get the most out of cbapi by documenting all of the methods available to you.

## 5.1 CB Response API

This page documents the public interfaces exposed by cbapi when communicating with a Carbon Black Enterprise Response server.

### 5.1.1 Main Interface

To use cbapi with Carbon Black Response, you will be using the CbResponseAPI. The CbResponseAPI object then exposes two main methods to access data on the Carbon Black server: `select` and `create`.

**class** `cbapi.response.rest_api.CbResponseAPI` (\*args, \*\*kwargs)

The main entry point into the Carbon Black Enterprise Response API. Note that calling this will automatically connect to the Carbon Black server in order to verify connectivity and get the server version.

#### Parameters

- **profile** (*str*) – (optional) Use the credentials in the named profile when connecting to the Carbon Black server. Uses the profile named 'default' when not specified.
- **url** (*str*) – (optional, discouraged) Instead of using a credential profile, pass URL and API token to the constructor.
- **token** (*str*) – (optional, discouraged) API token
- **ssl\_verify** (*bool*) – (optional, discouraged) Enable or disable SSL certificate verification

Usage:

```
>>> from cbapi import CbEnterpriseResponseAPI
>>> cb = CbEnterpriseResponseAPI(profile="production")
```

**create** (*cls*, *data=None*)

Creates a new object.

**Parameters** *cls* (*class*) – The Model class (only some models can be created, for example, Feed, Notification, ...)

**Returns** An empty instance of the Model class

**Raises** *ApiError* – if the Model cannot be created

**create\_new\_partition** ()

Create a new Solr time partition for event storage. Available in Cb Response 6.1 and above. This will force roll-over current hot partition into warm partition (by renaming it to a time-stamped name) and create a new hot partition (“writer”).

**Returns** Nothing if successful.

**Raises**

- *ApiError* – if there was an error creating the new partition.
- *ServerError* – if there was an error creating the new partition.

**dashboard\_statistics** ()

Retrieve dashboard statistics from the Carbon Black Enterprise Response server.

**Returns** Dictionary with information retrieved from the `/api/v1/dashboard/statistics` API route

**Return type** dict

**from\_ui** (*uri*)

Retrieve a Carbon Black Enterprise Response object based on URL from the Carbon Black Enterprise Response web user interface.

For example, calling this function with `https://server/#/analyze/00000001-0000-0554-01d1-3bc4553b8c9f/1` as the `uri` argument will return a new `py:class: cbapi.response.models.Process` class initialized with the process GUID from the URL.

**Parameters** *uri* (*str*) – Web browser URL from the Cb web interface

**Returns** the appropriate model object for the URL provided

**Raises** *ApiError* – if the URL does not correspond to a recognized model object

**info** ()

Retrieve basic version information from the Carbon Black Enterprise Response server.

**Returns** Dictionary with information retrieved from the `/api/info` API route

**Return type** dict

**license\_request** ()

Retrieve license request block from the Carbon Black Enterprise Response server.

**Returns** License request block

**Return type** str

**select** (*cls*, *unique\_id=None*, *\*args*, *\*\*kwargs*)

Prepares a query against the Carbon Black data store.

**Parameters**

- **cls** (*class*) – The Model class (for example, Computer, Process, Binary, FileInstance) to query
- **unique\_id** – (optional) The unique id of the object to retrieve, to retrieve a single object by ID

**Returns** An instance of the Model class if a unique\_id is provided, otherwise a Query object

**update\_license** (*license\_block*)

Upload new license to the Carbon Black Enterprise Response server.

**Parameters** **license\_block** (*str*) – Licence block provided by Carbon Black support

**Raises** *ServerError* – if the license is not accepted by the Carbon Black server

## 5.1.2 Queries

**class** `cbapi.response.query.Query` (*doc\_class, cb, query=None, raw\_query=None*)

Represents a prepared query to the Carbon Black Enterprise Response server.

This object is returned as part of a `CbEnterpriseResponseAPI.select()` operation on Process and Binary objects from the Carbon Black Enterprise Response server. You should not have to create this class yourself.

The query is not executed on the server until it's accessed, either as an iterator (where it will generate values on demand as they're requested) or as a list (where it will retrieve the entire result set and save to a list). You can also call the Python built-in `len()` on this object to retrieve the total number of items matching the query.

The syntax for query `:py:meth:where` and `:py:meth:sort` methods can be found in the [Query Reference](#) posted on the Carbon Black Developer Network website.

Examples:

```
>>> cb = CbEnterpriseResponseAPI()
>>> query = cb.select(Process) # returns a Query object,
    ↳matching all Processes
>>> query = query.where("process_name:notepad.exe") # add a filter to this Query
>>> query = query.sort("last_update desc") # sort by last update time,
    ↳most recent first
>>> for proc in query: # uses the iterator to,
    ↳retrieve all results
>>>     print("{0} {1}".format(proc.username, proc.hostname))
>>> processes = query[:10] # retrieve the first ten,
    ↳results
>>> len(query) # retrieve the total count
```

**Notes:**

- The slicing operator only supports start and end parameters, but not step. `[1:-1]` is legal, but `[1:2:-1]` is not.
- You can chain where clauses together to create AND queries; only objects that match all where clauses will be returned.

**and\_** (*new\_query*)

Add a filter to this query. Equivalent to calling `where()` on this object.

**Parameters** **new\_query** (*str*) – Query string - see the [Query Reference](#).

**Returns** Query object

**Return type** *Query*

**facets** (*\*args*)

Retrieve a dictionary with the facets for this query.

**Parameters** **args** – Any number of fields to use as facets

**Returns** Facet data

**Return type** dict

**sort** (*new\_sort*)

Set the sort order for this query.

**Parameters** **new\_sort** (*str*) – New sort order - see the [Query Reference](#).

**Returns** Query object

**Return type** *Query*

**where** (*new\_query*)

Add a filter to this query.

**Parameters** **new\_query** (*str*) – Query string - see the [Query Reference](#).

**Returns** Query object

**Return type** *Query*

**class** `cbapi.response.models.ProcessQuery` (*doc\_class, cb, query=None, raw\_query=None*)

**group\_by** (*field\_name*)

Set the group-by field name for this query. Typically, you will want to set this to 'id' if you only want one result per process.

This method is only available for Cb Response servers 6.0 and above. Calling this on a Query object connected to a Cb Response 5.x server will simply result in a no-op.

**Parameters** **field\_name** (*str*) – Field name to group the result set by.

**Returns** Query object

**Return type** *ProcessQuery*

**max\_children** (*num\_children*)

Sets the number of children to fetch with the process

This method is only available for Cb Response servers 6.0 and above. Calling this on a Query object connected to a Cb Response 5.x server will simply result in a no-op.

**Default** 15

**Parameters** **num\_children** (*int*) – Number of children to fetch with process

**Returns** Query object

**Return type** *ProcessQuery*

**max\_last\_server\_update** (*v*)

Set the maximum last update time (relative to server) for this query. The timestamp can be expressed either as a `datetime` like object or as an ISO 8601 string formatted timestamp such as 2017-04-29T04:21:18Z. If a `datetime` like object is provided, it is assumed to be in GMT time zone.

This option will limit the number of Solr cores that need to be searched for events that match the query.

This method is only available for Cb Response servers 6.0 and above. Calling this on a Query object connected to a Cb Response 5.x server will simply result in a no-op.

**Parameters** **v** (*str*) – Timestamp (either string or datetime object).

**Returns** Query object

**Return type** *ProcessQuery*

#### **max\_last\_update** (*v*)

Set the maximum last update time (relative to sensor) for this query. The timestamp can be expressed either as a `datetime` like object or as an ISO 8601 string formatted timestamp such as 2017-04-29T04:21:18Z. If a `datetime` like object is provided, it is assumed to be in GMT time zone.

This option will limit the number of Solr cores that need to be searched for events that match the query.

This method is only available for Cb Response servers 6.0 and above. Calling this on a Query object connected to a Cb Response 5.x server will simply result in a no-op.

**Parameters** **v** (*str*) – Timestamp (either string or datetime object).

**Returns** Query object

**Return type** *ProcessQuery*

#### **min\_last\_server\_update** (*v*)

Set the minimum last update time (relative to server) for this query. The timestamp can be expressed either as a `datetime` like object or as an ISO 8601 string formatted timestamp such as 2017-04-29T04:21:18Z. If a `datetime` like object is provided, it is assumed to be in GMT time zone.

This option will limit the number of Solr cores that need to be searched for events that match the query.

This method is only available for Cb Response servers 6.0 and above. Calling this on a Query object connected to a Cb Response 5.x server will simply result in a no-op.

**Parameters** **v** (*str*) – Timestamp (either string or datetime object).

**Returns** Query object

**Return type** *ProcessQuery*

#### **min\_last\_update** (*v*)

Set the minimum last update time (relative to sensor) for this query. The timestamp can be expressed either as a `datetime` like object or as an ISO 8601 string formatted timestamp such as 2017-04-29T04:21:18Z. If a `datetime` like object is provided, it is assumed to be in GMT time zone.

This option will limit the number of Solr cores that need to be searched for events that match the query.

This method is only available for Cb Response servers 6.0 and above. Calling this on a Query object connected to a Cb Response 5.x server will simply result in a no-op.

**Parameters** **v** (*str*) – Timestamp (either string or datetime object).

**Returns** Query object

**Return type** *ProcessQuery*

#### **use\_comprehensive\_search** ()

Set the `comprehensive_search` flag on the Process query.

**Returns** new Query object

**Return type** *ProcessQuery*

```
class cbapi.response.models.ThreatReportQuery (doc_class, cb, query=None,
                                             raw_query=None)
```

```
class cbapi.response.models.AlertQuery (doc_class, cb, query=None, raw_query=None)
```

### 5.1.3 Models

```
class cbapi.response.models.Process (cb, procguid, segment=None, max_children=15,  
                                     initial_data=None, force_init=False, sup-  
                                     pressed_process=False)
```

#### **all\_events**

Returns a list of all events associated with this process across all segments, sorted by timestamp

**Returns** list of CbEvent objects

#### **all\_events\_segment**

Returns a list of all events associated with this process segment, sorted by timestamp

**Returns** list of CbEvent objects

#### **binary**

Joins this attribute with the *Binary* object associated with this Process object

#### **Example**

```
>>> process_obj = c.select(Process).where('process_name:svch0st.exe')[0]  
>>> binary_obj = process_obj.binary  
>>> print(binary_obj.signed)  
False
```

#### **childprocs**

Generator that returns CbChildProcEvent objects associated with this process

#### **children**

Generator that returns CbChildProcEvent objects associated with this process

#### **cmdline**

**Returns** Returns the command line of the process

**Return type** string

#### **comms\_ip**

Returns ascii representation of the ip address used to communicate with the Cb Response Server

#### **crossprocs**

Generator that returns CbCrossProcEvent objects associated with this process

#### **depth**

Returns the depth of this process from the “root” system process

**Returns** integer representing the depth of the process (0 is the root system process). To prevent infinite recursion, a maximum depth of 500 processes is enforced.

#### **end**

Returns the end time of the process (based on the last event received). If the process has not yet exited, “end” will return None.

**Returns** datetime object of the last event received for the process, if it has terminated. Otherwise, None.

#### **filemods**

Generator that returns CbFileModEvent objects associated with this process

**find\_file\_writes** (*filename*)

Returns a list of file writes with the specified filename

**Parameters** **filename** (*str*) – filename to match on file writes

**Returns** Returns a list of file writes with the specified filename

**Return type** list

**interface\_ip**

Returns ascii representation of the ip address of the interface used to communicate with the Cb Response server. If using NAT, this will be the “internal” IP address of the sensor.

**last\_server\_update**

Returns a pretty version of when this process last updated

**last\_update**

Returns a pretty version of when this process last updated

**max\_last\_server\_update**

Returns a pretty version of the latest event in this process segment

**max\_last\_update**

Returns a pretty version of the latest event in this process segment

**min\_last\_server\_update**

Returns a pretty version of the earliest event in this process segment

**min\_last\_update**

Returns a pretty version of the earliest event in this process segment

**modloads**

Generator that returns `:py:class:CbModLoadEvent` associated with this process

**netconns**

Generator that returns `CbNetConnEvent` objects associated with this process

**parent**

Returns the parent Process object if one exists

**parent\_md5**

Workaround since parent\_md5 silently disappeared in ~Cb Response 6.x

**refresh** ()

Refresh the object from the Carbon Black server.

**regmods**

Generator that returns `CbRegModEvent` objects associated with this process

**sensor**

Joins this attribute with the `Sensor` object associated with this Process object

**Example**

```
>>> process_obj = c.select(Process).where('process_name:svch0st.exe')[0]
>>> sensor_obj = process.sensor
>>> print(sensor_obj.computer_dns_name)
hyperv-win7-x86
```

**start**

Returns the start time of the process

**unsigned\_modloads**

Returns all unsigned module loads. This is useful to filter out all Microsoft signed DLLs

**username**

Returns the username of the owner of this process

**walk\_children** (*callback*, *max\_depth=0*, *depth=0*)

Walk down the execution chain while calling the specified callback function at each depth.

**Example**

```
>>> def proc_callback(parent_proc, depth):
...     print(parent_proc.cmdline, depth)
>>>
>>> process = c.select(Process).where('process_name:svch0st.exe')[0]
>>> process.walk_children(proc_callback, depth=2)
(u'cmd.exe \c ipconfig', 2)
(u'cmd.exe \\c ipconfig', 2)
(u'cmd.exe /c ipconfig', 2)
(u'ipconfig', 3)
(u'cmd.exe /c ipconfig.exe /all', 2)
(u'cmd.exe \c ipconfig', 2)
(u'cmd.exe \\c ipconfig', 2)
(u'cmd.exe /c ipconfig', 2)
(u'ipconfig', 3)
(u'cmd.exe /c ipconfig.exe /all', 2)
```

**Parameters**

- **callback** (*func*) – Callback function used for execution at each depth. This function is executed with the parent process object and depth as parameters.
- **max\_depth** (*int*) – Max number of iterations down the execution chain.
- **depth** (*int*) – Number of iterations down the execution chain

Returns None

**walk\_parents** (*callback*, *max\_depth=0*, *depth=0*)

Walk up the execution chain while calling the specified callback function at each depth.

**Example**

```
>>> def proc_callback(parent_proc, depth):
...     print(parent_proc.cmdline, depth)
>>>
>>> process = c.select(Process).where('process_name:ipconfig.exe')[0]
>>> process.walk_parents(proc_callback)
(u'cmd.exe /c ipconfig.exe', 0)
(u'c:\windows\carbonblack\cb.exe', 1)
(u'C:\Windows\system32\services.exe', 2)
(u'wininit.exe', 3)
(u'\SystemRoot\System32\smss.exe 00000000 00000040 ', 4)
(u'\SystemRoot\System32\smss.exe', 5)
(u'', 6)
```

**Parameters**

- **callback** (*func*) – Callback function used for execution at each depth. This function is executed with the parent process object and depth as parameters.
- **max\_depth** (*int*) – Max number of iterations up the execution chain
- **depth** (*int*) – Number of iterations up the execution chain.



**Returns** None

**webui\_link**

Returns the Cb Response Web UI link associated with this process

**class** `cbapi.response.models.Binary` (*cb, md5sum, initial\_data=None, force\_init=False*)

**class FrequencyData**

Class containing frequency information about a binary

**Parameters**

- **computer\_count** (*int*) – Number of endpoints this binary resides
- **process\_count** (*int*) – Number of executions
- **all\_process\_count** (*int*) – Number of all process documents
- **module\_frequency** (*int*) –  $\text{process\_count} / \text{all\_process\_count}$

Create new instance of `FrequencyData(computer_count, process_count, all_process_count, module_frequency)`

**class SigningData**

Class containing binary signing information

**Parameters**

- **result** (*str*) – Signed or Unsigned
- **publisher** (*str*) – Singnature publisher
- **issuer** (*str*) – Signature issuer
- **subject** (*str*) – Signing subject
- **sign\_time** (*str*) – Binary signed time
- **program\_name** (*str*) – Binary program name

Create new instance of `SigningData(result, publisher, issuer, subject, sign_time, program_name)`

**class VersionInfo**

Class containing versioning information about a binary

**Parameters**

- **file\_desc** (*str*) – File description
- **file\_version** (*str*) – File version
- **product\_name** (*str*) – Product Name
- **product\_version** (*str*) – Product version
- **company\_name** (*str*) – Company Name
- **legal\_copyright** (*str*) – Copyright
- **original\_filename** (*str*) – Original File name of this binary

Create new instance of `VersionInfo(file_desc, file_version, product_name, product_version, company_name, legal_copyright, original_filename)`

**banned**

Returns `BannedHash` object if this Binary's hash has been whitelisted (Banned), otherwise returns `False`

**digsig\_issuer**

Returns the Digital Signature Issuer

**digsig\_prog\_name**

Returns the Digital Signature Program Name

**digsig\_publisher**

Returns the Digital Signature Publisher

**digsig\_sign\_time**

Returns the Digital Signature signing time

**digsig\_subject**

Returns the Digital Signature subject

**endpoints**

Return a list of endpoints this binary resides

**file**

Returns a file pointer to this binary

**Example**

```
>>> process_obj = c.select(Process).where("process_name:svch0st.exe").first()
>>> binary_obj = process_obj.binary
>>> print(binary_obj.file.read(2))
MZ
```

**frequency**

Returns *FrequencyData* information about the binary.

**Example**

```
>>> process_obj = c.select(Process).where('process_name:svch0st.exe').first()
>>> binary_obj = process_obj.binary
>>> print(binary_obj.frequency)
FrequencyData(computer_count=1, process_count=5, all_process_count=4429,
↪module_frequency=0.001128923007450892)
```

**icon**

Returns the raw icon of this Binary. This data is not encoded.

**is\_64bit**

Returns True if the Binary is an AMD64 or x64 (64-bit) Executable

**is\_executable\_image**

Returns True if the Binary is executable

**observed\_filenames**

Returns a list of all observed file names associated with this Binary

**signed**

Returns True if the binary is signed.

**signing\_data**

Returns *SigningData* object which contains: Digital Signature Result, Digital Signature publisher, Issuer, Subject, Signing Time, Program Name

**size**

Returns the size of the Binary

**version\_info**

Returns a *VersionInfo* object containing detailed information: File Description, File Version, Product Name, Product Version, Company Name, Legal Copyright, and Original FileName

**webui\_link**

Returns the Cb Response Web UI link associated with this Binary object

**class** `cbapi.response.models.Sensor(*args, **kwargs)`

Represents a Sensor object in the Carbon Black server.

**class** `NetworkAdapter(macaddr, ipaddr)`

Create new instance of NetworkAdapter(macaddr, ipaddr)

**ipaddr**

Alias for field number 1

**macaddr**

Alias for field number 0

**activity\_stats**

Returns a list of activity statistics from the associated Cb Response Sensor

**dns\_name**

Returns the DNS name associated with this sensor object. This is the same as 'computer\_dns\_name'.

**flush\_events()**

Performs a flush of events for this Cb Response Sensor

**Warning** This may cause a significant amount of network traffic from this sensor to the Cb Response Server

**group****Getter**

Returns the sensor's group id.

**Setter**

Allows access to set the sensor's group id

**hostname**

Returns the hostname associated with this sensor object. This is the same as 'computer\_name'

**isolate(timeout=None)**

Turn on network isolation for this Cb Response Sensor.

This function will block and only return when the isolation is complete, or if a timeout is reached. By default, there is no timeout. You can specify a timeout period (in seconds) in the "timeout" parameter to this function. If a timeout is specified and reached before the sensor is confirmed isolated, then this function will throw a `TimeoutError`.

**Returns** True if sensor is isolated

**Raises** `TimeoutError` – if sensor does not isolate before timeout is reached

**lr\_session()**

Retrieve a Live Response session object for this Sensor.

**Returns** Live Response session object

**Return type** `cbapi.live_response_api.LiveResponseSession`

**Raises** `ApiError` – if there is an error establishing a Live Response session for this Sensor

**network\_interfaces**

Returns a list of networks adapters on the sensor

**os**

Returns the operating system display string of the sensor

**queued\_stats**

Returns a list of status and size of the queued event logs from the associated Cb Response Sensor

**Example**

```
>>> sensor_obj = c.select (Sensor).where ("ip:192.168").first ()
>>> pprint.pprint (sensor_obj.queued_stats)
[{'id': u'355509',
  'num_eventlog_bytes': u'0',
  'num_eventlogs': u'0',
  'num_storefile_bytes': u'0',
  'num_storefiles': 0,
  'sensor_id': 1,
  'timestamp': u'2016-10-17 19:08:09.645294-05:00'}]
```

**resource\_status**

Returns a list of memory statistics used by the Cb Response Sensor

**restart\_sensor ()**

Restarts the Carbon Black sensor (*not* the underlying endpoint operating system).

This simply sets the flag to ask the sensor to restart the next time it checks into the Cb Response server, it does not wait for the sensor to restart.

**sid**

Security Identifier being used by the Cb Response Sensor

**unisolate (timeout=None)**

Turn off network isolation for this Cb Response Sensor.

This function will block and only return when the isolation is removed, or if a timeout is reached. By default, there is no timeout. You can specify a timeout period (in seconds) in the “timeout” parameter to this function. If a timeout is specified and reached before the sensor is confirmed unisolated, then this function will throw a `TimeoutError`.

**Returns** True if sensor is unisolated

**Raises** `TimeoutError` – if sensor does not unisolate before timeout is reached

**webui\_link**

Returns the Cb Response Web UI link associated with this Sensor

```
class cbapi.response.models.Feed (cb, model_unique_id=None, initial_data=None,
                                   force_init=False, full_doc=False)
```

Represents a Feed object in the Carbon Black server.

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

**actions**

**Returns** Returns all `FeedAction` objects associated with this feed

**Return type** `response.rest_api.Query`

**search\_binaries** (*min\_score=None, max\_score=None*)

Perform a *Binary* search within this feed that satisfies `min_score` and `max_score` :param `min_score`: minimum feed score :param `max_score`: maximum feed score :return: Returns a `response.rest_api.Query` object within the appropriate search parameters for binaries :rtype: `response.rest_api.Query`

**search\_processes** (*min\_score=None, max\_score=None*)

Perform a *Process* search within this feed that satisfies `min_score` and `max_score`

#### Parameters

- **min\_score** – minimum feed score
- **max\_score** – maximum feed score

**Returns** Returns a `response.rest_api.Query` object with the appropriate search parameters for processes

**Return type** `response.rest_api.Query`

**class** `cbapi.response.models.BannedHash` (*cb, model\_unique\_id=None, initial\_data=None, force\_init=False, full\_doc=False*)

Represents a BannedHash object in the Carbon Black server.

Base model for :param `cb`: :param `model_unique_id`: :param `initial_data`: :param `force_init`: :param `full_doc`: :return:

#### binary

Joins this attribute with the *Binary* object associated with this Banned Hash object

**class** `cbapi.response.models.Watchlist` (*\*args, \*\*kwargs*)

Represents a Watchlist object in the Carbon Black server.

#### Variables

- **description** – A description of the watchlist.
- **search\_query** – URL encoded search query associated with this watchlist.
- **index\_type** – Index to search for this watchlist. Must be either ‘events’ (Processes) or ‘modules’ (Binaries)

#### facets

Returns facets from the search associated with the watchlist query

**Returns** dictionary of facets as keys

**Return type** `dict`

#### query

##### Getter

Returns the query associated with this watchlist.

##### Setter

Allows access to set the query associated with this watchlist

#### search ()

Creates a search based on the watchlist’s search parameter

**Returns** a *Process* `response.rest_api.Query` or *Binary* `response.rest_api.Query`

**Return type** `response.rest_api.Query`

**class** `cbapi.response.models.Alert` (*cb, alert\_id, initial\_data=None*)  
 Represents a Alert object in the Carbon Black server.

## 5.1.4 Live Response

**class** `cbapi.live_response_api.CbLRSessionBase` (*cblr\_manager, session\_id, sensor\_id, session\_data=None*)

### File Operations

`CbLRSessionBase.get_file` (*file\_name, timeout=None, delay=None*)  
 Retrieve contents of the specified file name

**Parameters** `file_name` (*str*) – Name of the file

**Returns** Content of the specified file name

**Return type** `str`

`CbLRSessionBase.delete_file` (*filename*)  
 Delete the specified file name

**Parameters** `filename` (*str*) – Name of the file

**Returns** `None`

`CbLRSessionBase.put_file` (*infp, remote\_filename*)  
 Create a new file on the remote endpoint with the specified data

#### Example

```
>>> with c.select(Sensor, 1).lr_session() as lr_session:
...     lr_session.put_file(open("test.txt", "rb"), r"C:     est.txt")
```

#### Parameters

- **infp** (*str*) – Python file-like containing data to upload to the remote endpoint
- **remote\_filename** (*str*) – File name to create on the remote endpoint

**Returns** `None`

`CbLRSessionBase.list_directory` (*dir\_name*)  
 List the contents of a directory

#### Example

```
>>> with c.select(Sensor, 1).lr_session() as lr_session:
...     pprint.pprint(lr_session.list_directory('C:\\temp\\'))
[{'attributes': [u'DIRECTORY'],
  u'create_time': 1471897244,
  u'filename': u'.'},
 {u'attributes': [u'DIRECTORY'],
  u'create_time': 1471897244,
  u'filename': u'..'},
 {u'attributes': [u'DIRECTORY'],
  u'create_time': 1471897244,
  u'filename': u'..'},
 {u'attributes': [u'DIRECTORY'],
  u'create_time': 1471897244,
  u'filename': u'..'}
```

(continues on next page)

(continued from previous page)

```

    u'last_write_time': 1476390670,
    u'size': 0},
    {u'attributes': [u'ARCHIVE'],
    u'create_time': 1476390668,
    u'filename': u'test.txt',
    u'last_access_time': 1476390668,
    u'last_write_time': 1476390668,
    u'size': 0}]

```

**Parameters** `dir_name` (*str*) – Directory to list. This parameter should end with “

**Returns** Returns a directory listing

**Return type** list

`CbLRSessionBase.create_directory` (*dir\_name*)

Create a directory on the remote endpoint

**Parameters** `dir_name` (*str*) – New directory name

**Returns** None

`CbLRSessionBase.walk` (*top*, *topdown=True*, *onerror=None*, *followlinks=False*)

Perform a full directory walk with recursion into subdirectories

**Example**

```

>>> with c.select(Sensor, 1).lr_session() as lr_session:
...     for entry in lr_session.walk(directory_name):
...         print(entry)
('C:\temp\', [u'dir1', u'dir2'], [u'file1.txt'])

```

**Parameters**

- `top` (*str*) – Directory to recurse
- `topdown` (*bool*) – if True, start output from top level directory
- `onerror` (*bool*) – Callback if an error occurs. This function is called with one argument (the exception that occurred)
- `followlinks` (*bool*) – Follow symbolic links

**Returns** Returns output in the follow tuple format: (Directory Name, [dirnames], [filenames])

**Return type** tuple

## Registry Operations

`CbLRSessionBase.get_registry_value` (*regkey*)

Returns the associated value of the specified registry key

**Example**

```

>>> with c.select(Sensor, 1).lr_session() as lr_session:
>>>     pprint.pprint(lr_session.get_registry_value(
↪ 'HKLM\SYSTEM\CurrentControlSet\services\ACPI\Start'))
{'u'value_data': 0, u'value_name': u'Start', u'value_type': u'REG_DWORD'}

```

**Parameters** `regkey` (*str*) – The registry key to retrieve

**Returns** Returns a dictionary with keys of: `value_data`, `value_name`, `value_type`

**Return type** `dict`

`CbLRSessionBase.set_registry_value` (*regkey*, *value*, *overwrite=True*, *value\_type=None*)

Set a registry value of the specified registry key

#### Example

```
>>> with c.select(Sensor, 1).lr_session() as lr_session:
...     lr_session.set_registry_value(
↳ 'HKLM\SYSTEM\CurrentControlSet\services\ACPI\testvalue', 1)
```

#### Parameters

- **regkey** (*str*) – The registry key to set
- **value** (*obj*) – The value data
- **overwrite** (*bool*) – Overwrite value if True
- **value\_type** (*str*) – The type of value. Examples: `REG_DWORD`, `REG_MULTI_SZ`, `REG_SZ`

**Returns** `None`

`CbLRSessionBase.delete_registry_value` (*regkey*)

Delete a registry value

**Parameters** `regkey` (*str*) – the registry value to delete

**Returns** `None`

`CbLRSessionBase.create_registry_key` (*regkey*)

Create a new registry

**Parameters** `regkey` (*str*) – The registry key to create

**Returns** `None`

`CbLRSessionBase.delete_registry_key` (*regkey*)

Delete a registry key

**Parameters** `regkey` (*str*) – The registry key to delete

**Returns** `None`

`CbLRSessionBase.list_registry_keys_and_values` (*regkey*)

Enumerate subkeys and values of the specified registry key.

#### Example

```
>>> with c.select(Sensor, 1).lr_session() as lr_session:
>>> pprint.pprint(lr_session.list_registry_keys_and_values(
↳ 'HKLM\SYSTEM\CurrentControlSet\services\ACPI'))
{'sub_keys': [u'Parameters', u'Enum'],
 'values': [{u'value_data': 0,
             u'value_name': u'Start',
             u'value_type': u'REG_DWORD'},
            {u'value_data': 1,
             u'value_name': u'Type',
```

(continues on next page)



(continued from previous page)

```

    u'value_type': u'REG_DWORD'},
    {u'value_data': 3,
     u'value_name': u'ErrorControl',
     u'value_type': u'REG_DWORD'},
    {u'value_data': u'system32\drivers\ACPI.sys',
     u'value_name': u'ImagePath',
     u'value_type': u'REG_EXPAND_SZ'},
    {u'value_data': u'Microsoft ACPI Driver',
     u'value_name': u'DisplayName',
     u'value_type': u'REG_SZ'},
    {u'value_data': u'Boot Bus Extender',
     u'value_name': u'Group',
     u'value_type': u'REG_SZ'},
    {u'value_data': u'acpi.inf_x86_neutral_ddd3c514822f1b21',
     u'value_name': u'DriverPackageId',
     u'value_type': u'REG_SZ'},
    {u'value_data': 1,
     u'value_name': u'Tag',
     u'value_type': u'REG_DWORD'}}}

```

**Parameters** **regkey** (*str*) – The registry key to enumerate

**Returns** returns a dictionary with 2 keys (sub\_keys and values)

**Return type** dict

`CbLRSessionBase.list_registry_keys` (*regkey*)

Enumerate all registry values from the specified registry key.

**Parameters** **regkey** – The registry key to enumerate

**Returns** returns a list of values

**Return type** list

## Process Operations

`CbLRSessionBase.kill_process` (*pid*)

Terminate a process on the remote endpoint

**Parameters** **pid** – Process ID to terminate

**Returns** True if success, False if failure

**Return type** bool

`CbLRSessionBase.create_process` (*command\_string*, *wait\_for\_output=True*, *remote\_output\_file\_name=None*, *working\_directory=None*, *wait\_timeout=30*, *wait\_for\_completion=True*)

Create a new process with the specified command string.

### Example

```

>>> with c.select(Sensor, 1).lr_session() as lr_session:
...     print(lr_session.create_process(r'cmd.exe /c "ping.exe 192.168.1.1"'))
Pinging 192.168.1.1 with 32 bytes of data:
Reply from 192.168.1.1: bytes=32 time<1ms TTL=64

```

**Parameters**

- **command\_string** (*str*) – command string used for the create process operation
- **wait\_for\_output** (*bool*) – Block on output from the new process (execute in foreground). This will also set `wait_for_completion` (below).
- **remote\_output\_file\_name** (*str*) – The remote output file name used for process output
- **working\_directory** (*str*) – The working directory of the create process operation
- **wait\_timeout** (*int*) – Time out used for this live response command
- **wait\_for\_completion** (*bool*) – Wait until the process is completed before returning

**Returns** returns the output of the command string

**Return type** `str`

`CbLRSessionBase.list_processes()`

List currently running processes

**Example**

```
>>> with c.select(Sensor, 1).lr_session() as lr_session:
...     print(lr_session.list_processes()[0])
{'command_line': u'',
 u'create_time': 1476260500,
 u'parent': 0,
 u'parent_guid': u'00000001-0000-0000-0000-000000000000',
 u'path': u'',
 u'pid': 4,
 u'proc_guid': u'00000001-0000-0004-01d2-2461a85e4546',
 u'sid': u's-1-5-18',
 u'username': u'NT AUTHORITY\SYSTEM'}
```

**Returns** returns a list of running processes

**Return type** `list`

## 5.2 CB Protection API

This page documents the public interfaces exposed by `cbapi` when communicating with a Carbon Black Enterprise Protection server.

### 5.2.1 Main Interface

To use `cbapi` with Carbon Black Protection, you will be using the `CbProtectionAPI`. The `CbProtectionAPI` object then exposes two main methods to select data on the Carbon Black server:

**class** `cbapi.protection.rest_api.CbProtectionAPI(*args, **kwargs)`

The main entry point into the Carbon Black Enterprise Protection API.

**Parameters** **profile** (*str*) – (optional) Use the credentials in the named profile when connecting to the Carbon Black server. Uses the profile named ‘default’ when not specified.

Usage:

```
>>> from cbapi import CbEnterpriseProtectionAPI
>>> cb = CbEnterpriseProtectionAPI(profile="production")
```

**create** (*cls*, *data=None*)

Creates a new object.

**Parameters** *cls* (*class*) – The Model class (only some models can be created, for example, Feed, Notification, ...)

**Returns** An empty instance of the Model class

**Raises** *ApiError* – if the Model cannot be created

**select** (*cls*, *unique\_id=None*, *\*args*, *\*\*kwargs*)

Prepares a query against the Carbon Black data store.

**Parameters**

- *cls* (*class*) – The Model class (for example, Computer, Process, Binary, FileInstance) to query
- *unique\_id* – (optional) The unique id of the object to retrieve, to retrieve a single object by ID

**Returns** An instance of the Model class if a *unique\_id* is provided, otherwise a Query object

## 5.2.2 Queries

**class** `cbapi.protection.rest_api.Query` (*doc\_class*, *cb*, *query=None*)

Represents a prepared query to the Carbon Black Enterprise Protection server.

This object is returned as part of a `CbEnterpriseProtectionAPI.select()` operation on models requested from the Carbon Black Enterprise Protection server. You should not have to create this class yourself.

The query is not executed on the server until it's accessed, either as an iterator (where it will generate values on demand as they're requested) or as a list (where it will retrieve the entire result set and save to a list). You can also call the Python built-in `len()` on this object to retrieve the total number of items matching the query.

The syntax for query `:py:meth:where` and `:py:meth:sort` methods can be found in the [Enterprise Protection API reference](#) posted on the Carbon Black Developer Network website.

Examples:

```
>>> from cbapi.protection import CbEnterpriseProtectionAPI, Computer
>>> cb = CbEnterpriseProtectionAPI()
>>> query = cb.select(Computer) # returns a Query object
↳matching all Computers
>>> query = query.where("ipAddress:10.201.2.*") # add a filter to this Query
>>> query = query.sort("processorSpeed DESC") # sort by computer processor
↳speed, descending
>>> for comp in query: # uses the iterator to
↳retrieve all results
>>>     print(comp.name)
>>> comps = query[:10] # retrieve the first ten
↳results
>>> len(query) # retrieve the total count
```

Notes:

- The slicing operator only supports start and end parameters, but not step. `[1:-1]` is legal, but `[1:2:-1]` is not.
- You can chain where clauses together to create AND queries; only objects that match all where clauses will be returned.

**and\_** (*q*)

Add a filter to this query. Equivalent to calling `where()` on this object.

**Parameters** **q** (*str*) – Query string - see the [Enterprise Protection API reference](#).

**Returns** Query object

**Return type** *Query*

**sort** (*new\_sort*)

Set the sort order for this query.

**Parameters** **new\_sort** (*str*) – Sort order - see the [Enterprise Protection API reference](#).

**Returns** Query object

**Return type** *Query*

**where** (*q*)

Add a filter to this query.

**Parameters** **q** (*str*) – Query string - see the [Enterprise Protection API reference](#).

**Returns** Query object

**Return type** *Query*

## 5.2.3 Models

```
class cbapi.protection.models.ApprovalRequest (cb, model_unique_id, initial_data=None)
```

```
ResolutionApproved = 2
ResolutionInstaller = 4
ResolutionNotResolved = 0
ResolutionOther = 7
ResolutionPublisher = 6
ResolutionRejected = 1
ResolutionRuleChange = 3
ResolutionUpdater = 5
StatusClosed = 3
StatusOpen = 2
StatusSubmitted = 1
computer
fileCatalog
installerFileCatalog
processFileCatalog
```

```

    urlobject = '/api/bit9platform/v1/approvalRequest'
class cbapi.protection.models.Certificate(cb, model_unique_id, initial_data=None)

    StateApproved = 2
    StateBanned = 3
    StateMixed = 4
    StateUnapproved = 1
    firstSeenComputer
    parent
    publisher
    urlobject = '/api/bit9platform/v1/certificate'
class cbapi.protection.models.Computer(cb, model_unique_id, initial_data=None)
    Represents a Computer object in the Carbon Black server.

    fileInstances
    policy
    resetCLIPassword()
    templateComputer
    urlobject = '/api/bit9platform/v1/computer'
class cbapi.protection.models.Connector(cb, model_unique_id=None, initial_data=None,
                                         force_init=False, full_doc=False)
    Represents a Connector object in the Carbon Black server.

```

#### Variables

- **id** – Unique connector Id
- **name** – Name of the connector. Note that only non-internal connectors can be renamed
- **analysisName** – Name for analysis component of the connector (can be same as the name field)
- **connectorVersion** – Version of this connector
- **canAnalyze** – True if this connector can analyze files
- **enabled** – True if connector is enabled
- **analysisEnabled** – True if analysis component of this connector is enabled
- **isInternal** – True if this is internal connector
- **analysisTargets** – Array of possible analysis targets. Analysis targets are required when creating new fileAnalysis. They usually represent different OS and configurations and are available only for some internal connectors.

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

```

analysisEnabled = None
analysisName = None
analysisTargets = []

```

```

canAnalyze = None
connectorVersion = None
enabled = None
id = None
isInternal = None
name = None
pendingAnalyses
urlobject = '/api/bit9platform/v1/connector'
class cbapi.protection.models.DriftReport (cb, model_unique_id=None, initial_data=None, force_init=False, full_doc=False)
    Represents a DriftReport object in the Carbon Black server.
    Base model for :param cb: :param model_unique_id: :param initial_data: :param force_init: :param full_doc:
    :return:
urlobject = '/api/bit9platform/v1/driftReport'
class cbapi.protection.models.DriftReportContents (cb, model_unique_id=None, initial_data=None, force_init=False, full_doc=False)
    Represents a DriftReportContents object in the Carbon Black server.
    Base model for :param cb: :param model_unique_id: :param initial_data: :param force_init: :param full_doc:
    :return:
urlobject = '/api/bit9platform/v1/driftReportContents'
class cbapi.protection.models.EnforcementLevel
    LevelHigh = 20
    LevelLow = 40
    LevelMedium = 30
    LevelNone = 80
class cbapi.protection.models.Event (cb, model_unique_id, initial_data=None)
    Represents a Event object in the Carbon Black server.
fileCatalog
urlobject = '/api/bit9platform/v1/event'
class cbapi.protection.models.FileAnalysis (cb, model_unique_id, initial_data=None)
urlobject = '/api/bit9platform/v1/fileAnalysis'
class cbapi.protection.models.FileCatalog (cb, model_unique_id, initial_data=None)
    Represents a FileCatalog object in the Carbon Black server.
certificate
computer
fileHash

```

```

publisher
urlobject = '/api/bit9platform/v1/fileCatalog'
class cbapi.protection.models.FileInstance(cb, model_unique_id, initial_data=None)
Represents a FileInstance object in the Carbon Black server.

computer
fileCatalog
urlobject = '/api/bit9platform/v1/fileInstance'
class cbapi.protection.models.FileInstanceDeleted(cb, model_unique_id, initial_data=None)

urlobject = '/api/bit9platform/v1/fileInstanceDeleted'
class cbapi.protection.models.FileInstanceGroup(cb, model_unique_id, initial_data=None)

urlobject = '/api/bit9platform/v1/fileInstanceGroup'
class cbapi.protection.models.FileRule(cb, model_unique_id=None, initial_data=None, force_init=False, full_doc=False)
Represents a FileRule object in the Carbon Black server.

```

#### Variables

- **id** – Unique id of this fileRule
- **fileCatalogId** – Id of fileCatalog entry associated with this fileRule. Can be null if file hasn't been seen on any endpoints yet. This is foreign key and can be expanded to expose fields from the related fileCatalog object
- **name** – Name of this rule.
- **description** – Description of this rule.
- **fileState** – File state for this rule. Can be one of: 1=Unapproved 2=Approved 3=Banned
- **sourceType** – Mechanism that created this rule. Can be one of: 1 = Manual 2 = Trusted Directory 3 = Reputation 4 = Imported 5 = External (API) 6 = Event Rule 7 = Application Template 8 = Unified Management
- **sourceId** – Id of source of this rule. Can be event rule id or trusted directory id
- **reportOnly** – True if this has a report-only ban
- **reputationApprovalsEnabled** – True if reputation approvals are enabled for this file
- **forceInstaller** – True if this file is forced to act as installer, even if product detected it as 'not installer'
- **forceNotInstaller** – True if this file is forced to act as 'not installer', even if product detected it as installer
- **policyIds** – List of IDs of policies where this rule applies. Value will be empty if this is a global rule
- **hash** – Hash associated with this rule. Note that hash will be available only if rule was created through md5 or sha-1 hash. If rule was created through fileName, fileCatalogId or sha-256 hash that exists in the catalog, this field will be empty.

- **fileName** – File name associated with this rule. Note that file name will be available only if rule was created through file name. If rule was created through fileCatalogId or hash, this field will be empty.
- **lazyApproval** – This field is valid only when creating approvals. When set to true, it will cause approval to be sent to agent only if file is marked as installer or if it blocked on any agent. This is useful when proactively creating lot of approvals that might or might not be required, since it is using less resources. Note that, as soon as lazy approval is sent to agents, this field will be changed to 'false'.
- **platformFlags** – Set of platform flags where this file rule will be valid. combination of: 1 = Windows 2 = Mac 4 = Linux
- **dateCreated** – Date/time when this rule was created (UTC)
- **createdBy** – User that created this object
- **createdByUserId** – Id of user that created this object
- **dateModified** – Date/time when this object was last modified (UTC)
- **modifiedBy** – User that last modified this object
- **modifiedByUserId** – Id of user that last modified this object
- **clVersion** – CL version associated with this file rule
- **idUnique** – Unique GUID of this rule
- **origIdUnique** – Unique GUID of the original rule
- **unifiedFlag** – Local override flag for unified rule (0 - if rule is not unified, 1 - no override allowed, 3 - local override allowed)
- **unifiedSource** – Unified server name that created this rule
- **fileRuleType** – Text description of file rule type
- **version** – Version of this file rule
- **visible** – If rule should be visible in the UI or not

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

```
PlatformLinux = 4
PlatformMac = 2
PlatformWindows = 1
SourceTypeApplicationTemplate = 7
SourceTypeEventRule = 6
SourceTypeExternal = 5
SourceTypeImported = 4
SourceTypeManual = 1
SourceTypeReputation = 3
SourceTypeTrustedDirectory = 2
SourceTypeUnifiedManagement = 8
StateApproved = 2
```



```
StateBanned = 3
StateUnapproved = 1
clVersion = None
createdBy = None
createdByUser
createdByUserId = None
dateCreated = datetime.datetime(1970, 1, 1, 0, 0, tzinfo=tzlocal())
dateModified = datetime.datetime(1970, 1, 1, 0, 0, tzinfo=tzlocal())
description = None
fileCatalog
fileCatalogId = None
fileName = None
fileRuleType = None
fileState = None
forceInstaller = None
forceNotInstaller = None
hash = None
id = None
idUnique = None
lazyApproval = None
modifiedBy = None
modifiedByUserId = None
name = None
origIdUnique = None
platformFlags = None
policyIds = None
reportOnly = None
reputationApprovalsEnabled = None
sourceId = None
sourceType = None
unifiedFlag = None
unifiedSource = None
urlobject = '/api/bit9platform/v1/fileRule'
version = None
visible = None
```

```
class cbapi.protection.models.FileUpload(cb, model_unique_id, initial_data=None)
```

```
    file
```

```
    urlobject = '/api/bit9platform/v1/fileUpload'
```

```
class cbapi.protection.models.GrantedUserPolicyPermission(cb,
                                                         model_unique_id=None,
                                                         initial_data=None,
                                                         force_init=False,
                                                         full_doc=False)
```

Represents a GrantedUserPolicyPermission object in the Carbon Black server.

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

```
    urlobject = '/api/bit9platform/v1/grantedUserPolicyPermission'
```

```
class cbapi.protection.models.InternalEvent(cb, model_unique_id, initial_data=None)
```

```
    urlobject = '/api/bit9platform/v1/internalEvent'
```

```
class cbapi.protection.models.MeteredExecution(cb, model_unique_id, initial_data=None)
```

```
    urlobject = '/api/bit9platform/v1/meteredExecution'
```

```
class cbapi.protection.models.Notification(cb, model_unique_id=None, initial_data=None, force_init=False, full_doc=False)
```

Represents a Notification object in the Carbon Black server.

#### Variables

- **connectorId** – Id of connector object that sent the notification
- **time** – Date/time of the notification (UTC)
- **analysisResult** – Analysis result. Can be one of: 0 = Unknown, 1 = Not malicious, 2 = Potential risk, 3 = Malicious
- **fileAnalysisId** – Id of fileAnalysis object associated with the notification. This should be available if notification came as a result of the file analysis

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

```
ResultClean = 1
```

```
ResultMalicious = 3
```

```
ResultNotAvailable = 0
```

```
ResultPotentialThreat = 2
```

```
analysisResult = None
```

```
anomaly = None
```

```
appliance = None
```

```
connectorId = None
```

```
destIp = None
```

```

destUsername = None
directories = []
externalId = None
externalUrl = None
fileAnalysisId = None
fileName = None
files = []
flags = None
httpHeader = None
malwareName = None
malwareType = None
md5 = None
msgFormat = None
product = None
regKeys = []
severity = None
sha1 = None
sha256 = None
srcHost = None
srcIp = None
srcUsername = None
status = None
targetApp = None
targetOS = None
time = datetime.datetime(1970, 1, 1, 0, 0, tzinfo=tzlocal())
type = None
urlobject = '/api/bit9platform/v1/notification'
version = None

class cbapi.protection.models.Notifier(cb, model_unique_id, initial_data=None)

    urlobject = '/api/bit9platform/v1/notifier'

class cbapi.protection.models.PendingAnalysis(cb, model_unique_id, initial_data=None)

    ResultClean = 1
    ResultMalicious = 3
    ResultNotAvailable = 0
    ResultPotentialThreat = 2

```

```
StatusAnalyzed = 3
StatusCancelled = 5
StatusError = 4
StatusProcessed = 2
StatusScheduled = 0
StatusSubmitted = 1
create_notification (**kwargs)

file
fileCatalog
fileHash
urlobject = '/api/bit9platform/v1/pendingAnalysis'

class cbapi.protection.models.Policy(cb, model_unique_id=None, initial_data=None,
                                     force_init=False, full_doc=False)
    Represents a Policy object in the Carbon Black server.
```

#### Variables

- *id* – Unique id of this policy
- *name* – Name of this policy.
- *description* – Description of this policy.
- *packageName* – Name of installer package for this policy
- *enforcementLevel* – Target enforcement level. Can be one of: 20=High (Block Unapproved) 30=Medium (Prompt Unapproved) 40=Low (Monitor Unapproved) 60=None (Visibility) 80=None (Disabled)
- *disconnectedEnforcementLevel* – Target enforcement level for disconnected computers. Can be one of: 20=High (Block Unapproved) 30=Medium (Prompt Unapproved) 40=Low (Monitor Unapproved) 60=None (Visibility) 80=None (Disabled)
- *helpDeskUrl* – Helpdesk URL for notifiers in this policy
- *imageUrl* – Image logo URL for notifiers in this policy
- *dateCreated* – Date/time when this rule was created (UTC)
- *createdByUserId* – Id of user that created this object
- *dateModified* – Date/time when this object was last modified (UTC)
- *modifiedByUserId* – Id of user that last modified this object
- *readOnly* – True if this policy is read-only
- *hidden* – True if this policy is hidden in the UI
- *automatic* – True if AD mapping is enabled for this policy
- *loadAgentInSafeMode* – True if agents in this policy will be loaded when machine is booted in ‘safe mode’
- *reputationEnabled* – True if reputation approvals are enabled in this policy
- *fileTrackingEnabled* – True if file tracking enabled in this policy
- *customLogo* – True if notifiers in this policy use custom logo

- *automaticApprovalsOnTransition* – True if agents in this policy will automatically locally approve files when transitioning into High Enforcement
- *allowAgentUpgrades* – True if agents can be upgraded for this policy
- *totalComputers* – Total number of computers in this policy
- *connectedComputers* – Number of connected computers in this policy
- *atEnforcementComputers* – Number of computers that are at target enforcement level in this policy
- *clVersionMax* – Max target CL version for agents in this policy

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

```

allowAgentUpgrades = None
atEnforcementComputers = None
automatic = None
automaticApprovalsOnTransition = None
clVersionMax = None
connectedComputers = None
createdByUserId = None
customLogo = None
dateCreated = datetime.datetime(1970, 1, 1, 0, 0, tzinfo=tzlocal())
dateModified = datetime.datetime(1970, 1, 1, 0, 0, tzinfo=tzlocal())
description = None
disconnectedEnforcementLevel = None
enforcementLevel = None
fileTrackingEnabled = None
helpDeskUrl = None
hidden = None
id = None
imageUrl = None
loadAgentInSafeMode = None
modifiedByUserId = None
name = None
packageName = None
readOnly = None
reputationEnabled = None
totalComputers = None
urlobject = '/api/bit9platform/v1/policy'

```

```
class cbapi.protection.models.Publisher (cb, model_unique_id, initial_data=None)
```

```
    urlobject = '/api/bit9platform/v1/publisher'
```

```
class cbapi.protection.models.PublisherCertificate (cb, model_unique_id=None, initial_data=None, force_init=False, full_doc=False)
```

Represents a PublisherCertificate object in the Carbon Black server.

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

```
    urlobject = '/api/bit9platform/v1/publisherCertificate'
```

```
class cbapi.protection.models.ScriptRule (cb, model_unique_id=None, initial_data=None, force_init=False, full_doc=False)
```

Represents a ScriptRule object in the Carbon Black server.

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

```
    urlobject = '/api/bit9platform/v1/scriptRule'
```

```
class cbapi.protection.models.ServerConfig (cb, model_unique_id, initial_data=None)
```

```
    urlobject = '/api/bit9platform/v1/serverConfig'
```

```
class cbapi.protection.models.ServerPerformance (cb, model_unique_id, initial_data=None)
```

```
    urlobject = '/api/bit9platform/v1/serverPerformance'
```

```
class cbapi.protection.models.TrustedDirectory (cb, model_unique_id=None, initial_data=None, force_init=False, full_doc=False)
```

Represents a TrustedDirectory object in the Carbon Black server.

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

```
    urlobject = '/api/bit9platform/v1/trustedDirectory'
```

```
class cbapi.protection.models.TrustedUser (cb, model_unique_id=None, initial_data=None, force_init=False, full_doc=False)
```

Represents a TrustedUser object in the Carbon Black server.

#### Variables

- **id** – Unique id of this trustedUser
- **name** – Name of the user as it will appear on the console. This is not the name that will be enforced on the endpoint
- **userId** – Id of the user that will be trusted on the endpoint. This field can be user name, user SID (Security identifier) on Windows platforms or user’s ID on Linux and Mac platforms
- **description** – Description of this rule
- **platformId** – Platform where this trustedUser will be valid. it is one of: 1 = Windows, 2 = Mac, 4 = Linux

- ***dateCreated*** – Date/time when this object was created (UTC)
- ***createdByUserId*** – Id of user that created this object. This is foreign key and can be expanded to expose fields from the related user object
- ***createdBy*** – User that created this object
- ***dateModified*** – Date/time when this object was last modified (UTC)
- ***modifiedByUserId*** – Id of user that last modified this object. This is foreign key and can be expanded to expose fields from the related user object
- ***modifiedBy*** – User that last modified this object
- ***clVersion*** – CL version associated with this trustedUser

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

```

clVersion = None
createdBy = None
createdByUserId = None
dateCreated = datetime.datetime(1970, 1, 1, 0, 0, tzinfo=tzlocal())
dateModified = datetime.datetime(1970, 1, 1, 0, 0, tzinfo=tzlocal())
description = None
id = None
modifiedBy = None
modifiedByUserId = None
name = None
platformId = None
urlobject = '/api/bit9platform/v1/trustedUser'
userSid = None

```

```
class cbapi.protection.models.Updater(cb, model_unique_id, initial_data=None)
```

```
    urlobject = '/api/bit9platform/v1/updater'
```

```
class cbapi.protection.models.User(cb, model_unique_id=None, initial_data=None,
                                   force_init=False, full_doc=False)
```

Represents a User object in the Carbon Black server.

#### Variables

- ***id*** – Unique id of this user
- ***name*** – Name of the user
- ***userGroupIds*** – Comma-separated list of IDs of corresponding userGroup objects
- ***eMailAddress*** – EMail address of this user
- ***firstName*** – First name of this user
- ***lastName*** – Last name of this user
- ***title*** – Title of this user

- *salutation* – Salutation of this user
- *department* – Department this user belongs to
- *homePhone* – User’s home phone
- *cellPhone* – User’s cell phone
- *backupCellPhone* – User’s secondary cell phone
- *pager* – User’s pager number
- *backupPager* – User’s secondary pager number
- *comments* – Comments for this user
- *adminComments* – Administrator’s comments for this user
- *registrationDate* – Date this user was first registered (UTC)
- *readOnly* – True if this user is one of internal users (System or Cb Collective Defense Cloud Service) or AD user. These users cannot be modified through the API
- *external* – True if this is externally generated user (e.g. from AD)
- *automatic* – True if this user’s roles are assigned automatically through mappings (valid only for external users)
- *unified* – True if this user’s token is already connected to a remote unified environment (token should not be changed)
- *enabled* – True if this user is enabled
- *passwordHash* – Hash of user password
- *passwordSalt* – Salt used to generate password hash
- *apiToken* – API token for this user

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

```
adminComments = None
apiToken = None
automatic = None
backupCellPhone = None
backupPager = None
cellPhone = None
comments = None
department = None
eMailAddress = None
enabled = None
external = None
firstName = None
homePhone = None
id = None
```



```

lastName = None
name = None
pager = None
passwordHash = None
passwordSalt = None
readOnly = None
registrationDate = datetime.datetime(1970, 1, 1, 0, 0, tzinfo=tzlocal())
salutation = None
title = None
unified = None
urlobject = '/api/bit9platform/v1/user'
userGroupIds = None

```

```

class cbapi.protection.models.UserGroup(cb, model_unique_id=None, initial_data=None,
                                         force_init=False, full_doc=False)

```

Represents a UserGroup object in the Carbon Black server.

#### Variables

- *id* – Unique id of this user group
- *name* – Name of the user group
- *description* – Description of this user group
- *permissions* – Permissions associated with users of this user group as a hexadecimal string. See <https://developer.carbonblack.com/reference/enterprise-protection/8.0/rest-api/#usergroup> for more information.
- *policyIds* – List of IDs of policies where this user group applies. Value will be empty if this is a global user group
- *enabled* – True if this userGroup is enabled
- *editable* – True if this userGroup is editable
- *dateCreated* – Date/time when this object was created (UTC)
- *createdByUserId* – Id of user that created this object. This is foreign key and can be expanded to expose fields from the related user object
- *createdBy* – User that created this object
- *dateModified* – Date/time when this object was last modified (UTC)
- *modifiedByUserId* – Id of user that last modified this object. This is foreign key and can be expanded to expose fields from the related user object
- *modifiedBy* – User that last modified this object
- *automaticCount* – Number of users that belong to this group and have been assigned through AD rule (doesn't include internal users)
- *manualCount* – Number of users that belong to this group and have been assigned manually (doesn't include internal users)

Base model for :param cb: :param model\_unique\_id: :param initial\_data: :param force\_init: :param full\_doc:  
:return:

```
automaticCount = None
createdBy = None
createdByUserId = None
dateCreated = datetime.datetime(1970, 1, 1, 0, 0, tzinfo=tzlocal())
dateModified = datetime.datetime(1970, 1, 1, 0, 0, tzinfo=tzlocal())
description = None
editable = None
enabled = None
id = None
manualCount = None
modifiedBy = None
modifiedByUserId = None
name = None
permissions = None
policyIds = None
urlobject = '/api/bit9platform/v1/userGroup'
```

## 5.3 CB Defense API

This page documents the public interfaces exposed by cbapi when communicating with a CB Defense server.

### 5.3.1 Main Interface

To use cbapi with Carbon Black Defense, you will be using the CbDefenseAPI. The CbDefenseAPI object then exposes two main methods to select data on the Carbon Black server:

```
class cbapi.psc.defense.rest_api.CbDefenseAPI(*args, **kwargs)
```

The main entry point into the Cb Defense API.

**Parameters** `profile` (*str*) – (optional) Use the credentials in the named profile when connecting to the Carbon Black server. Uses the profile named ‘default’ when not specified.

Usage:

```
>>> from cbapi import CbDefenseAPI
>>> cb = CbDefenseAPI(profile="production")
```

```
create (cls, data=None)
```

Creates a new object.

**Parameters** `cls` (*class*) – The Model class (only some models can be created, for example, Feed, Notification, ...)

**Returns** An empty instance of the Model class

**Raises** `ApiError` – if the Model cannot be created

**get\_notifications ()**

Retrieve queued notifications (alerts) from the Cb Defense server. Note that this can only be used with a 'SIEM' key generated in the Cb Defense console.

**Returns** list of dictionary objects representing the notifications, or an empty list if none available.

**notification\_listener (interval=60)**

Generator to continually poll the Cb Defense server for notifications (alerts). Note that this can only be used with a 'SIEM' key generated in the Cb Defense console.

**select (cls, unique\_id=None, \*args, \*\*kwargs)**

Prepares a query against the Carbon Black data store.

**Parameters**

- **cls** (*class*) – The Model class (for example, Computer, Process, Binary, FileInstance) to query
- **unique\_id** – (optional) The unique id of the object to retrieve, to retrieve a single object by ID

**Returns** An instance of the Model class if a unique\_id is provided, otherwise a Query object

## 5.3.2 Queries

**class** `cbapi.psc.defense.rest_api.Query (doc_class, cb, query=None)`

Represents a prepared query to the Cb Defense server.

This object is returned as part of a `CbDefenseAPI.select ()` operation on models requested from the Cb Defense server. You should not have to create this class yourself.

The query is not executed on the server until it's accessed, either as an iterator (where it will generate values on demand as they're requested) or as a list (where it will retrieve the entire result set and save to a list). You can also call the Python built-in `len ()` on this object to retrieve the total number of items matching the query.

Examples:

```
>>> from cbapi.psc.defense import CbDefenseAPI
>>> cb = CbDefenseAPI ()
```

**Notes:**

- The slicing operator only supports start and end parameters, but not step. `[1:-1]` is legal, but `[1:2:-1]` is not.
- You can chain where clauses together to create AND queries; only objects that match all where clauses will be returned.

**and\_ (q)**

Add a filter to this query. Equivalent to calling `where ()` on this object.

**Parameters** **q** (*str*) – Query string

**Returns** Query object

**Return type** `Query`

**where (q)**

Add a filter to this query.

**Parameters** *q* (*str*) – Query string

**Returns** Query object

**Return type** *Query*

### 5.3.3 Models

**class** `cbapi.psc.defense.models.DefenseMutableModel` (*cb*, *model\_unique\_id=None*, *initial\_data=None*, *force\_init=False*, *full\_doc=False*)

Represents a DefenseMutableModel object in the Carbon Black server.

**class** `cbapi.psc.defense.models.Device` (*cb*, *model\_unique\_id*, *initial\_data=None*)

Represents a Device object in the Carbon Black server.

`activationCode = None`

`activationCodeExpiryTime`

`assignedToId = None`

`assignedToName = None`

`avEngine = None`

`avLastScanTime`

`avMaster = None`

`avStatus = []`

`avUpdateServers = []`

`createTime`

`deregisteredTime`

`deviceGuid = None`

`deviceId = None`

`deviceOwnerId = None`

`deviceSessionId = None`

`deviceType = None`

`email = None`

`firstName = None`

`firstVirusActivityTime`

`info_key = 'deviceInfo'`

`lastContact`

`lastExternalIpAddress = None`

`lastInternalIpAddress = None`

`lastLocation = None`

`lastName = None`

`lastReportedTime`

```
lastResetTime
lastShutdownTime
lastVirusActivityTime
linuxKernelVersion = None
lr_session()
    Retrieve a Live Response session object for this Device.

    Returns Live Response session object
    Return type cbapi.defense.cblr.LiveResponseSession
    Raises ApiError – if there is an error establishing a Live Response session for this Device

messages = []
middleName = None
name = None
organizationId = None
organizationName = None
osVersion = None
passiveMode = None
policyId = None
policyName = None
primary_key = 'deviceId'
quarantined = None
registeredTime
rootedByAnalytics = None
rootedByAnalyticsTime
rootedBySensor = None
rootedBySensorTime
scanLastActionTime
scanLastCompleteTime
scanStatus = None
sensorStates = []
sensorVersion = None
status = None
targetPriorityType = None
testId = None
uninstalledTime
urlobject = '/integrationServices/v3/device'
vdiBaseDevice = None
```

```
    windowsPlatform = None

class cbapi.psc.defense.models.Event(cb, model_unique_id, initial_data=None)
    Represents a Event object in the Carbon Black server.

    info_key = 'eventInfo'
    primary_key = 'eventId'
    urlobject = '/integrationServices/v3/event'

class cbapi.psc.defense.models.Policy(cb, model_unique_id=None, initial_data=None,
    force_init=False, full_doc=False)
    Represents a Policy object in the Carbon Black server.

    add_rule(new_rule)
    delete_rule(rule_id)
    description = None
    id = None
    info_key = 'policyInfo'
    latestRevision = None
    name = None
    policy = {}
    priorityLevel = None
    replace_rule(rule_id, new_rule)
    rules
    systemPolicy = None
    urlobject = '/integrationServices/v3/policy'
    version = None
```

## 5.4 CB ThreatHunter API

This page documents the public interfaces exposed by cbapi when communicating with a Carbon Black PSC ThreatHunter server.

### 5.4.1 Main Interface

To use cbapi with Carbon Black ThreatHunter, you use CbThreatHunterAPI objects. These objects expose two main methods to access data on the ThreatHunter server: `select` and `create`.

```
class cbapi.psc.threathunter.rest_api.CbThreatHunterAPI(*args, **kwargs)
    The main entry point into the Cb ThreatHunter PSC API.
```

**Parameters** `profile` (*str*) – (optional) Use the credentials in the named profile when connecting to the Carbon Black server. Uses the profile named ‘default’ when not specified.

Usage:

```
>>> from cbapi.psc.threathunter import CbThreatHunterAPI
>>> cb = CbThreatHunterAPI(profile="production")
```

**convert\_query** (*query*)

Converts a legacy CB Response query to a ThreatHunter query.

**Parameters** **query** (*str*) – the query to convert

**Returns** the converted query

**Return type** str

**create** (*cls, data=None*)

Creates a new model.

```
>>> feed = cb.create(Feed, feed_data)
```

**Parameters**

- **cls** – The model being created
- **data** (*dict (str, object)*) – The data to pre-populate the model with

**Returns** an instance of *cls*

**custom\_severities**

Returns a list of active ReportSeverity instances

**Return type** list[ReportSeverity]

**limits** ()

Returns a dictionary containing API limiting information.

Example:

```
>>> cb.limits()
{'status_code': 200, 'time_bounds': {'upper': 1545335070095, 'lower': 1542779216139}}
```

**Returns** a dict of limiting information

**Return type** dict(str, str)

**queries** ()

Retrieves a list of queries, active or complete, known by the ThreatHunter server.

**Returns** a list of query ids

**Return type** list(str)

**select** (*cls, unique\_id=None, \*args, \*\*kwargs*)

Prepares a query against the Carbon Black data store.

**Parameters**

- **cls** (*class*) – The Model class (for example, Computer, Process, Binary, FileInstance) to query
- **unique\_id** – (optional) The unique id of the object to retrieve, to retrieve a single object by ID

**Returns** An instance of the Model class if a unique\_id is provided, otherwise a Query object

**validate\_query** (*query*)  
Validates the given IOC query.

```
>>> cb.validate_query("process_name:chrome.exe") # True
```

**Parameters** *query* (*str*) – the query to validate

**Returns** whether or not the query is valid

**Return type** bool

## 5.4.2 Queries

The ThreatHunter API uses QueryBuilder instances to construct structured or unstructured (i.e., raw string) queries. You can either construct these instances manually, or allow `CbThreatHunterAPI.select()` to do it for you:

**class** `cbapi.psc.threathunter.query.QueryBuilder` (\*\*kwargs)  
Provides a flexible interface for building prepared queries for the CB ThreatHunter backend.

This object can be instantiated directly, or can be managed implicitly through the `CbThreatHunterAPI.select()` API.

Examples:

```
>>> from cbapi.psc.threathunter import QueryBuilder
>>> # build a query with chaining
>>> query = QueryBuilder().where(process_name="malicious.exe").and_(device_name=
↳ "suspect")
>>> # start with an initial query, and chain another condition to it
>>> query = QueryBuilder(device_os="WINDOWS").or_(process_username="root")
```

**and\_** (*q*, \*\*kwargs)  
Adds a conjunctive filter to a query.

**Parameters**

- *q* – string or *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** QueryBuilder object

**Return type** *QueryBuilder*

**not\_** (*q*, \*\*kwargs)  
Adds a negative filter to a query.

**Parameters**

- *q* – *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** QueryBuilder object

**Return type** *QueryBuilder*

**or\_** (*q*, \*\*kwargs)  
Adds a disjunctive filter to a query.

**Parameters**

- *q* – *solrq.Q* object



- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** QueryBuilder object

**Return type** *QueryBuilder*

**where** (*q*, **\*\*kwargs**)

Adds a conjunctive filter to a query.

**Parameters**

- **q** – string or *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** QueryBuilder object

**Return type** *QueryBuilder*

**class** `cbapi.psc.threathunter.query.Query` (*doc\_class*, *cb*)

Represents a prepared query to the Cb ThreatHunter backend.

This object is returned as part of a `CbThreatHunterPI.select()` operation on models requested from the Cb ThreatHunter backend. You should not have to create this class yourself.

The query is not executed on the server until it's accessed, either as an iterator (where it will generate values on demand as they're requested) or as a list (where it will retrieve the entire result set and save to a list). You can also call the Python built-in `len()` on this object to retrieve the total number of items matching the query.

Examples:

```
>>> from cbapi.psc.threathunter import CbThreatHunterAPI
>>> cb = CbThreatHunterAPI()
>>> query = cb.select(Process)
>>> query = query.where(process_name="notepad.exe")
>>> # alternatively:
>>> query = query.where("process_name:notepad.exe")
```

**Notes:**

- The slicing operator only supports start and end parameters, but not step. `[1:-1]` is legal, but `[1:2:-1]` is not.
- You can chain where clauses together to create AND queries; only objects that match all where clauses will be returned.

**and\_** (*q=None*, **\*\*kwargs**)

Add a conjunctive filter to this query.

**Parameters**

- **q** – Query string or *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** *Query*

**not\_** (*q=None*, **\*\*kwargs**)

Adds a negated filter to this query.

**Parameters**

- **q** – *solrq.Q* object

- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** *Query*

**or\_** (*q=None, \*\*kwargs*)

Add a disjunctive filter to this query.

**Parameters**

- **q** – *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** *Query*

**where** (*q=None, \*\*kwargs*)

Add a filter to this query.

**Parameters**

- **q** – Query string, *QueryBuilder*, or *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** *Query*

**class** `cbapi.psc.threathunter.models.AsyncProcessQuery` (*doc\_class, cb*)

Represents the query logic for an asynchronous Process query.

This class specializes *Query* to handle the particulars of process querying.

**and\_** (*q=None, \*\*kwargs*)

Add a conjunctive filter to this query.

**Parameters**

- **q** – Query string or *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** *Query*

**not\_** (*q=None, \*\*kwargs*)

Adds a negated filter to this query.

**Parameters**

- **q** – *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** *Query*

**or\_** (*q=None, \*\*kwargs*)

Add a disjunctive filter to this query.

**Parameters**

- **q** – *solrq.Q* object

- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** Query

**sort\_by** (*key*, *direction*='ASC')

Sets the sorting behavior on a query's results.

Example:

```
>>> cb.select(Process).where(process_name="cmd.exe").sort_by("device_timestamp
↳")
```

**Parameters**

- **key** – the key in the schema to sort by
- **direction** – the sort order, either "ASC" or "DESC"

**Return type** *AsyncProcessQuery*

**timeout** (*msecs*)

Sets the timeout on a process query.

Example:

```
>>> cb.select(Process).where(process_name="foo.exe").timeout(5000)
```

**Param** msecs: the timeout duration, in milliseconds

**Returns** AsyncProcessQuery object

**Return type** *AsyncProcessQuery*

**where** (*q=None*, *\*\*kwargs*)

Add a filter to this query.

**Parameters**

- **q** – Query string, QueryBuilder, or *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** Query

**class** `cbapi.psc.threathunter.query.FeedQuery` (*doc\_class*, *cb*)

Represents the logic for a Feed query.

```
>>> cb.select(Feed)
>>> cb.select(Feed, id)
>>> cb.select(Feed).where(include_public=True)
```

**class** `cbapi.psc.threathunter.query.ReportQuery` (*doc\_class*, *cb*)

Represents the logic for a Report query.

```
>>> cb.select(Report).where(feed_id=id)
```

---

**Note:** Only feed reports can be queried. Watchlist reports should be interacted with via `Watchlist.reports()`.

---

**class** `cbapi.psc.threathunter.query.WatchlistQuery` (*doc\_class*, *cb*)  
Represents the logic for a Watchlist query.

```
>>> cb.select(Watchlist)
```

### 5.4.3 Models

**class** `cbapi.psc.threathunter.models.Process` (*cb*, *model\_unique\_id=None*, *initial\_data=None*, *force\_init=False*, *full\_doc=True*)

Represents a Process object in the Carbon Black server.

**class** `Summary` (*cb*, *model\_unique\_id*)  
Represents a Summary object in the Carbon Black server.

**children**  
Returns a list of child processes for this process.

**Returns** Returns a list of process objects

**Return type** list of *Process*

**events** (*\*\*kwargs*)  
Returns a query for events associated with this process's process GUID.

**Parameters** *kwargs* – Arguments to filter the event query with.

**Returns** Returns a Query object with the appropriate search parameters for events

**Return type** *cbapi.psc.threathunter.query.Query*

Example:

```
>>> [print(event) for event in process.events()]
>>> [print(event) for event in process.events(event_type="modload")]
```

**parents**  
Returns a query for parent processes associated with this process.

**Returns** Returns a Query object with the appropriate search parameters for parent processes, or None if the process has no recorded parent

**Return type** *cbapi.psc.threathunter.query.AsyncProcessQuery* or None

**process\_md5**  
Returns a string representation of the MD5 hash for this process.

**Returns** A string representation of the process's MD5.

**Return type** str

**process\_pids**  
Returns a list of PIDs associated with this process.

**Returns** A list of PIDs

**Return type** list of ints

**process\_sha256**

Returns a string representation of the SHA256 hash for this process.

**Returns** A string representation of the process's SHA256.

**Return type** str

**siblings**

Returns a list of sibling processes for this process.

**Returns** Returns a list of process objects

**Return type** list of *Process*

**summary**

Returns organization-specific information about this process.

**tree()**

Returns a *Tree* of children (and possibly siblings) associated with this process.

**Returns** Returns a *Tree* object

**Return type** *Tree*

Example:

```
>>> tree = process.tree()
```

```
class cbapi.psc.threathunter.models.Event (cb, model_unique_id=None, initial_data=None, force_init=False, full_doc=True)
```

Represents a Event object in the Carbon Black server.

```
class cbapi.psc.threathunter.models.Tree (cb, model_unique_id=None, initial_data=None, force_init=False, full_doc=True)
```

Represents a Tree object in the Carbon Black server.

**children**

Returns all of the children of the process that this tree is centered around.

**Returns** A list of *Process* instances

**Return type** list of *Process*

```
class cbapi.psc.threathunter.models.Feed (cb, model_unique_id=None, initial_data=None)
```

Represents a Feed object in the Carbon Black server.

**Variables**

- **name** – A human-friendly name for this feed
- **owner** – The feed owner's connector ID
- **provider\_url** – A URL supplied by the feed's provider
- **summary** – A human-friendly summary for the feed
- **category** – The feed's category
- **source\_label** – The feed's source label
- **access** – The feed's access (public or private)
- **id** – The feed's unique ID

**append\_reports (reports)**

Append the given reports to this feed's current reports.

**Parameters** `reports` (list(*Report*)) – the reports to append

**Raises** *InvalidObjectError* – if *id* is missing

**delete** ()

Deletes this feed from the ThreatHunter server.

**Raises** *InvalidObjectError* – if *id* is missing

**replace\_reports** (*reports*)

Replace this feed's reports with the given reports.

**Parameters** `reports` (list(*Report*)) – the reports to replace with

**Raises** *InvalidObjectError* – if *id* is missing

**reports**

Returns a list of *Report* associated with this feed.

**Returns** a list of reports

**Return type** list(*Report*)

**save** (*public=False*)

Saves this feed on the ThreatHunter server.

**Parameters** `public` – Whether to make the feed publicly available

**Returns** The saved feed

**Return type** *Feed*

**update** (\*\**kwargs*)

Update this feed's metadata with the given arguments.

```
>>> feed.update(access="private")
```

**Parameters** `kwargs` (*dict*(*str*, *str*)) – The fields to update

**Raises**

- *InvalidObjectError* – if *id* is missing or *validate*() fails
- *ApiError* – if an invalid field is specified

**validate** ()

Validates this feed's state.

**Raises** *InvalidObjectError* – if the feed's state is invalid

```
class cbapi.psc.threathunter.models.Report (cb, model_unique_id=None, initial_data=None, feed_id=None, from_watchlist=False)
```

Represents a Report object in the Carbon Black server.

**Variables**

- *id* – The report's unique ID
- *timestamp* – When this report was created
- *title* – A human-friendly title for this report
- *description* – A human-friendly description for this report
- *severity* – The severity of the IOCs within this report

- **link** – A URL for some reference for this report
- **tags** – A list of tags for this report
- **iocs\_v2** – A list of IOC\_V2 dicts associated with this report
- **visibility** – The visibility of this report

**custom\_severity**

Returns the custom severity for this report.

**Returns** The custom severity for this report, if it exists

**Return type** *ReportSeverity*

**Raises** *InvalidObjectError* – if *id* is missing or this report is from a watchlist

**delete ()**

Deletes this report from the ThreatHunter server.

```
>>> report.delete()
```

**Raises** *InvalidObjectError* – if *id* is missing, or *feed\_id* is missing and this report is a feed report

**ignore ()**

Sets the ignore status on this report.

Only watchlist reports have an ignore status.

**Raises** *InvalidObjectError* – if *id* is missing or this report is not from a watchlist

**ignored**

Returns the ignore status for this report.

Only watchlist reports have an ignore status.

```
>>> if report.ignored:
...     report.unignore()
```

**Returns** whether or not this report is ignored

**Return type** bool

**Raises** *InvalidObjectError* – if *id* is missing or this report is not from a watchlist

**iocs\_**

Returns a list of *IOC\_V2* associated with this report.

```
>>> for ioc in report.iocs_:
...     print(ioc.values)
```

**Returns** a list of IOCs

**Return type** list(*IOC\_V2*)

**save\_watchlist ()**

Saves this report as a watchlist report.

---

**Note:** This method **cannot** be used to save a feed report. To save feed reports, create them with *cb.create* and use `Feed.replace()`.

---

**Raises** *InvalidObjectError* – if *validate()* fails

**unignore()**

Removes the ignore status on this report.

Only watchlist reports have an ignore status.

**Raises** *InvalidObjectError* – if *id* is missing or this report is not from a watchlist

**update(\*\*kwargs)**

Update this report with the given arguments.

---

**Note:** The report's timestamp is always updated, regardless of whether passed explicitly.

---

```
>>> report.update(title="My new report title")
```

**Parameters** *kwargs* (*dict* (*str*, *str*)) – The fields to update

**Returns** The updated report

**Return type** *Report*

**Raises** *InvalidObjectError* – if *id* is missing, or *feed\_id* is missing and this report is a feed report, or *validate()* fails

**validate()**

Validates this report's state.

**Raises** *InvalidObjectError* – if the report's state is invalid

**class** `cbapi.psc.threathunter.models.IOC` (*cb*, *model\_unique\_id=None*, *initial\_data=None*, *report\_id=None*)

Represents a IOC object in the Carbon Black server.

**Variables**

- *md5* – A list of MD5 checksums
- *ipv4* – A list of IPv4 addresses
- *ipv6* – A list of IPv6 addresses
- *dns* – A list of domain names
- *query* – A list of dicts, each containing an IOC query

Creates a new IOC instance.

**Raises** *ApiError* – if *initial\_data* is *None*

**validate()**

Validates this IOC structure's state.

**Raises** *InvalidObjectError* – if the IOC structure's state is invalid



**class** `cbapi.psc.threathunter.models.IOC_V2` (*cb*, *model\_unique\_id=None*, *initial\_data=None*, *report\_id=None*)

Represents a IOC\_V2 object in the Carbon Black server.

#### Variables

- ***id*** – The IOC\_V2’s unique ID
- ***match\_type*** – How IOCs in this IOC\_V2 are matched
- ***values*** – A list of IOCs
- ***field*** – The kind of IOCs contained in this IOC\_V2
- ***link*** – A URL for some reference for this IOC\_V2

Creates a new IOC\_V2 instance.

**Raises** *ApiError* – if *initial\_data* is *None*

**ignore** ()

Sets the ignore status on this IOC.

Only watchlist IOCs have an ignore status.

**Raises** *InvalidObjectError* – if *id* is missing or this IOC is not from a watchlist

**ignored**

Returns whether or not this IOC is ignored

```
>>> if ioc.ignored:
...     ioc.unignore()
```

**Returns** the ignore status

**Return type** bool

**Raises** *InvalidObjectError* – if this IOC is missing an *id* or is not a watchlist IOC

**unignore** ()

Removes the ignore status on this IOC.

Only watchlist IOCs have an ignore status.

**Raises** *InvalidObjectError* – if *id* is missing or this IOC is not from a watchlist

**validate** ()

Validates this IOC\_V2’s state.

**Raises** *InvalidObjectError* – if the IOC\_V2’s state is invalid

**class** `cbapi.psc.threathunter.models.Watchlist` (*cb*, *model\_unique\_id=None*, *initial\_data=None*)

Represents a Watchlist object in the Carbon Black server.

#### Variables

- ***name*** – A human-friendly name for the watchlist
- ***description*** – A short description of the watchlist
- ***id*** – The watchlist’s unique id
- ***tags\_enabled*** – Whether tags are currently enabled
- ***alerts\_enabled*** – Whether alerts are currently enabled

- `create_timestamp` – When this watchlist was created
- `last_update_timestamp` – Report IDs associated with this watchlist
- `report_ids` – Report IDs associated with this watchlist
- `classifier` – A key, value pair specifying an associated feed

**classifier\_**

Returns the classifier key and value, if any, for this watchlist.

**Return type** tuple(str, str) or None

**delete ()**

Deletes this watchlist from the ThreatHunter server.

**Raises** *InvalidObjectError* – if *id* is missing

**disable\_alerts ()**

Disable alerts for this watchlist.

**Raises** *InvalidObjectError* – if *id* is missing

**disable\_tags ()**

Disable tagging for this watchlist.

**Raises** *InvalidObjectError* – if *id* is missing

**enable\_alerts ()**

Enable alerts for this watchlist. Alerts are not retroactive.

**Raises** *InvalidObjectError* – if *id* is missing

**enable\_tags ()**

Enable tagging for this watchlist.

**Raises** *InvalidObjectError* – if *id* is missing

**feed**

Returns the feed linked to this watchlist, if there is one.

**Returns** the feed linked to this watchlist, if any

**Return type** *Feed* or None

**reports**

Returns a list of *Report* instances associated with this watchlist.

---

**Note:** If this watchlist is a classifier (i.e. feed-linked) watchlist, *reports* will be empty. To get the reports associated with the linked feed, use *feed* like:

```
>>> for report in watchlist.feed.reports:
...     print(report.title)
```

**Returns** A list of reports

**Return type** list(*Report*)

**save ()**

Saves this watchlist on the ThreatHunter server.

**Returns** The saved watchlist

**Return type** *Watchlist*

**Raises** *InvalidObjectError* – if *validate()* fails

**update** (*\*\*kwargs*)

Updates this watchlist with the given arguments.

```
>>> watchlist.update(name="New Name")
```

**Parameters** *kwargs* (*dict* (*str*, *str*)) – The fields to update

**Raises**

- *InvalidObjectError* – if *id* is missing or *validate()* fails
- *ApiError* – if *report\_ids* is given and is empty

**validate** ()

Validates this watchlist's state.

**Raises** *InvalidObjectError* – if the watchlist's state is invalid

**class** `cbapi.psc.threathunter.models.ReportSeverity` (*cb*, *initial\_data=None*)

Represents a ReportSeverity object in the Carbon Black server.

**Variables**

- **report\_id** – The unique ID for the corresponding report
- **severity** – The severity level

**class** `cbapi.psc.threathunter.models.Binary` (*cb*, *model\_unique\_id*)

Represents a Binary object in the Carbon Black server.

**Variables**

- **sha256** – The SHA-256 hash of the file
- **md5** – The MD5 hash of the file
- **file\_available** – If true, the file is available for download
- **available\_file\_size** – The size of the file available for download
- **file\_size** – The size of the actual file (represented by the hash)
- **os\_type** – The OS that this file is designed for
- **architecture** – The set of architectures that this file was compiled for
- **lang\_id** – The Language ID value for the Windows VERSIONINFO resource
- **charset\_id** – The Character set ID value for the Windows VERSIONINFO resource
- **internal\_name** – The internal name from FileVersionInformation
- **product\_name** – The product name from FileVersionInformation
- **company\_name** – The company name from FileVersionInformation
- **trademark** – The trademark from FileVersionInformation
- **file\_description** – The file description from FileVersionInformation
- **file\_version** – The file version from FileVersionInformation
- **comments** – Comments from FileVersionInformation

- **original\_filename** – The original filename from FileVersionInformation
- **product\_description** – The product description from FileVersionInformation
- **product\_version** – The product version from FileVersionInformation
- **private\_build** – The private build from FileVersionInformation
- **special\_build** – The special build from FileVersionInformation

**class Summary** (*cb, model\_unique\_id*)

Represents a Summary object in the Carbon Black server.

**download\_url**

Returns a URL that can be used to download the file for this binary. Returns None if no download can be found.

**Parameters** **expiration\_seconds** – How long the download should be valid for

**Raises** *InvalidObjectError* – if URL retrieval should be retried

**Returns** A pre-signed AWS download URL

**Return type** str

**summary**

Returns organization-specific information about this binary.

**class** `cbapi.psc.threathunter.models.Downloads` (*cb, shas, expiration\_seconds=3600*)

Represents a Downloads object in the Carbon Black server.

**class FoundItem** (*cb, item*)

Represents a FoundItem object in the Carbon Black server.

**found**

Returns a list of *Downloads.FoundItem*, one for each binary found in the binary store.

## 5.5 CB LiveQuery API

This page documents the public interfaces exposed by cbapi when communicating with Carbon Black LiveQuery devices.

### 5.5.1 Main Interface

To use cbapi with Carbon Black LiveQuery, you use CbLiveQueryAPI objects.

The LiveQuery API is used in two stages: run submission and result retrieval.

**class** `cbapi.psc.livequery.rest_api.CbLiveQueryAPI` (*\*args, \*\*kwargs*)

The main entry point into the Cb PSC LiveQuery API.

**Parameters** **profile** (*str*) – (optional) Use the credentials in the named profile when connecting to the Carbon Black server. Uses the profile named ‘default’ when not specified.

Usage:

```
>>> from cbapi.psc.livequery import CbLiveQueryAPI
>>> cb = CbLiveQueryAPI(profile="production")
```

**create** (*cls, data=None*)

Creates a new object.

**Parameters** `cls` (*class*) – The Model class (only some models can be created, for example, Feed, Notification, ...)

**Returns** An empty instance of the Model class

**Raises** `ApiError` – if the Model cannot be created

**select** (*cls*, *unique\_id=None*, \**args*, \*\**kwargs*)

Prepares a query against the Carbon Black data store.

**Parameters**

- `cls` (*class*) – The Model class (for example, Computer, Process, Binary, FileInstance) to query
- `unique_id` – (optional) The unique id of the object to retrieve, to retrieve a single object by ID

**Returns** An instance of the Model class if a `unique_id` is provided, otherwise a Query object

## 5.5.2 Queries

The LiveQuery API uses QueryBuilder instances to construct structured or unstructured (i.e., raw string) queries. You can either construct these instances manually, or allow `CbLiveQueryAPI.select()` to do it for you:

**class** `cbapi.psc.livequery.query.QueryBuilder` (\*\**kwargs*)

Provides a flexible interface for building prepared queries for the CB LiveQuery backend.

This object can be instantiated directly, or can be managed implicitly through the `CbLiveQueryAPI.select()` API.

**and\_** (*q*, \*\**kwargs*)

Adds a conjunctive filter to a query.

**Parameters**

- `q` – string or `solrq.Q` object
- `kwargs` – Arguments to construct a `solrq.Q` with

**Returns** QueryBuilder object

**Return type** `QueryBuilder`

**not\_** (*q*, \*\**kwargs*)

Adds a negative filter to a query.

**Parameters**

- `q` – `solrq.Q` object
- `kwargs` – Arguments to construct a `solrq.Q` with

**Returns** QueryBuilder object

**Return type** `QueryBuilder`

**or\_** (*q*, \*\**kwargs*)

Adds a disjunctive filter to a query.

**Parameters**

- `q` – `solrq.Q` object
- `kwargs` – Arguments to construct a `solrq.Q` with

**Returns** QueryBuilder object

**Return type** *QueryBuilder*

**where** (*q*, *\*\*kwargs*)

Adds a conjunctive filter to a query.

**Parameters**

- **q** – string or *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** QueryBuilder object

**Return type** *QueryBuilder*

**class** `cbapi.psc.livequery.query.RunQuery` (*doc\_class*, *cb*)

Represents a query that either creates or retrieves the status of a LiveQuery run.

**device\_ids** (*device\_ids*)

Restricts the devices that this LiveQuery run is performed on to the given IDs.

**Parameters** **device\_ids** – list of ints

**Returns** This instance

**device\_types** (*device\_types*)

Restricts the devices that this LiveQuery run is performed on to the given device types.

**Parameters** **device\_types** – list of str

**Returns** This instance

**name** (*name*)

Sets this LiveQuery run's name. If no name is explicitly set, the run is named after its SQL.

**Parameters** **name** – The run name

**Returns** This instance

**notify\_on\_finish** ()

Sets the notify-on-finish flag on this LiveQuery run.

**Returns** This instance

**policy\_ids** (*policy\_ids*)

Restricts this LiveQuery run to the given policy IDs.

**Parameters** **policy\_ids** – list of ints

**Returns** This instance

**submit** ()

Submits this LiveQuery run.

**Returns** A new Run instance containing the run's status

**where** (*sql*)

Sets this LiveQuery run's underlying SQL.

**Parameters** **sql** – The SQL to execute

**Returns** This instance

**class** `cbapi.psc.livequery.models.ResultQuery` (*doc\_class*, *cb*)

Represents a query that retrieves results from a LiveQuery run.

**and\_** (*q=None, \*\*kwargs*)

Add a conjunctive filter to this query.

**Parameters**

- **q** – Query string or *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** Query

**criteria** (*\*\*kwargs*)

Sets the filter criteria on a query's results.

Example:

```
>>> cb.select(Result).run_id(my_run).criteria(device_id=[123, 456])
```

**not\_** (*q=None, \*\*kwargs*)

Adds a negated filter to this query.

**Parameters**

- **q** – *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** Query

**or\_** (*q=None, \*\*kwargs*)

Add a disjunctive filter to this query.

**Parameters**

- **q** – *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** Query

**run\_id** (*run\_id*)

Sets the run ID to query results for.

Example:

```
>>> cb.select(Result).run_id(my_run)
```

**sort\_by** (*key, direction='ASC'*)

Sets the sorting behavior on a query's results.

Example:

```
>>> cb.select(Result).run_id(my_run).where(username="foobar").sort_by("uid")
```

**Parameters**

- **key** – the key in the schema to sort by
- **direction** – the sort order, either “ASC” or “DESC”

**Return type** *ResultQuery*

**where** (*q=None, \*\*kwargs*)  
 Add a filter to this query.

**Parameters**

- **q** – Query string, *QueryBuilder*, or *solrq.Q* object
- **kwargs** – Arguments to construct a *solrq.Q* with

**Returns** Query object

**Return type** *Query*

### 5.5.3 Models

**class** `cbapi.psc.livequery.models.Run` (*cb, model\_unique\_id=None, initial\_data=None*)  
 Represents a Run object in the Carbon Black server.

**Variables**

- **template\_id** – Placeholder
- **org\_key** – The organization key for this run
- **name** – The name of the LiveQuery run
- **id** – The run’s unique ID
- **sql** – The LiveQuery query
- **created\_by** – Placeholder
- **create\_time** – When this run was created
- **status\_update\_time** – When the status of this run was last updated
- **timeout\_time** – Placeholder
- **cancellation\_time** – Placeholder
- **cancelled\_by** – Placeholder
- **archive\_time** – Placeholder
- **archived\_by** – Placeholder
- **notify\_on\_finish** – Whether or not to send an email on query completion
- **active\_org\_devices** – The number of devices active in the organization
- **status** – The run status
- **device\_filter** – Any device filter rules associated with the run
- **schedule** – Placeholder
- **last\_result\_time** – When the most recent result for this run was reported
- **total\_results** – Placeholder
- **match\_count** – Placeholder
- **no\_match\_count** – Placeholder
- **error\_count** – Placeholder



- **not\_supported\_count** – Placeholder
- **cancelled\_count** – Placeholder

**class** `cbapi.psc.livequery.models.Result` (*cb, initial\_data*)  
 Represents a Result object in the Carbon Black server.

#### Variables

- **id** – The result’s unique ID
- **device** – The device associated with the result
- **status** – The result’s status
- **time\_received** – The time at which this result was received
- **device\_message** – Placeholder
- **fields** – The fields returned by the backing osquery query
- **metrics** – Metrics associated with the result’s host

**class** `Device` (*cb, initial\_data*)  
 Represents a Device object in the Carbon Black server.

**class** `Fields` (*cb, initial\_data*)  
 Represents a Fields object in the Carbon Black server.

**class** `Metrics` (*cb, initial\_data*)  
 Represents a Metrics object in the Carbon Black server.

**device\_**  
 Returns the reified `Result.Device` for this result.

**fields\_**  
 Returns the reified `Result.Fields` for this result.

**metrics\_**  
 Returns the reified `Result.Metrics` for this result.

## 5.6 Exceptions

If an error occurs, the API attempts to roll the error into an appropriate Exception class.

### 5.6.1 Exception Classes

**exception** `cbapi.errors.ApiError` (*message=None, original\_exception=None*)

**exception** `cbapi.errors.CredentialError` (*message=None, original\_exception=None*)

**exception** `cbapi.errors.ServerError` (*error\_code, message, result=None, original\_exception=None*)

A `ServerError` is raised when an HTTP error code is returned from the Carbon Black server.

**exception** `cbapi.errors.ObjectNotFoundError` (*uri, message=None, original\_exception=None*)

The requested object could not be found in the Carbon Black datastore.

**exception** `cbapi.errors.MoreThanOneResultError` (*message=None, original\_exception=None*)

Only one object was requested, but multiple matches were found in the Carbon Black datastore.

**exception** `cbapi.errors.InvalidObjectError` (*message=None, original\_exception=None*)

**exception** `cbapi.errors.TimeoutError` (*uri=None, error\_code=None, message=None, original\_exception=None*)

## CHAPTER 6

---

### Indices and tables

---

- `genindex`
- `modindex`
- `search`



**C**

`cbapi.protection.models`, [56](#)  
`cbapi.psc.defense.models`, [72](#)



## A

- actions (*cbapi.response.models.Feed* attribute), 48
- activationCode (*cbapi.psc.defense.models.Device* attribute), 72
- activationCodeExpiryTime (*cbapi.psc.defense.models.Device* attribute), 72
- activity\_stats (*cbapi.response.models.Sensor* attribute), 47
- add\_rule() (*cbapi.psc.defense.models.Policy* method), 74
- adminComments (*cbapi.protection.models.User* attribute), 68
- Alert (class in *cbapi.response.models*), 49
- AlertQuery (class in *cbapi.response.models*), 41
- all\_events (*cbapi.response.models.Process* attribute), 42
- all\_events\_segment (*cbapi.response.models.Process* attribute), 42
- allowAgentUpgrades (*cbapi.protection.models.Policy* attribute), 65
- analysisEnabled (*cbapi.protection.models.Connector* attribute), 57
- analysisName (*cbapi.protection.models.Connector* attribute), 57
- analysisResult (*cbapi.protection.models.Notification* attribute), 62
- analysisTargets (*cbapi.protection.models.Connector* attribute), 57
- and\_() (*cbapi.protection.rest\_api.Query* method), 56
- and\_() (*cbapi.psc.defense.rest\_api.Query* method), 71
- and\_() (*cbapi.psc.livequery.models.ResultQuery* method), 90
- and\_() (*cbapi.psc.livequery.query.QueryBuilder* method), 89
- and\_() (*cbapi.psc.threathunter.models.AsyncProcessQuery* method), 78
- and\_() (*cbapi.psc.threathunter.query.Query* method), 77
- and\_() (*cbapi.psc.threathunter.query.QueryBuilder* method), 76
- and\_() (*cbapi.response.query.Query* method), 39
- anomaly (*cbapi.protection.models.Notification* attribute), 62
- ApiError, 93
- apiToken (*cbapi.protection.models.User* attribute), 68
- append\_reports() (*cbapi.psc.threathunter.models.Feed* method), 81
- appliance (*cbapi.protection.models.Notification* attribute), 62
- ApprovalRequest (class in *cbapi.protection.models*), 56
- assignedToId (*cbapi.psc.defense.models.Device* attribute), 72
- assignedToName (*cbapi.psc.defense.models.Device* attribute), 72
- AsyncProcessQuery (class in *cbapi.psc.threathunter.models*), 78
- atEnforcementComputers (*cbapi.protection.models.Policy* attribute), 65
- automatic (*cbapi.protection.models.Policy* attribute), 65
- automatic (*cbapi.protection.models.User* attribute), 68
- automaticApprovalsOnTransition (*cbapi.protection.models.Policy* attribute), 65
- automaticCount (*cbapi.protection.models.UserGroup* attribute), 69
- avEngine (*cbapi.psc.defense.models.Device* attribute), 72
- avLastScanTime (*cbapi.psc.defense.models.Device* attribute), 72
- avMaster (*cbapi.psc.defense.models.Device* attribute), 72
- avStatus (*cbapi.psc.defense.models.Device* attribute), 72

avUpdateServers (*cbapi.psc.defense.models.Device attribute*), 72

## B

backupCellPhone (*cbapi.protection.models.User attribute*), 68

backupPager (*cbapi.protection.models.User attribute*), 68

banned (*cbapi.response.models.Binary attribute*), 45

BannedHash (*class in cbapi.response.models*), 49

binary (*cbapi.response.models.BannedHash attribute*), 49

binary (*cbapi.response.models.Process attribute*), 42

Binary (*class in cbapi.psc.threathunter.models*), 87

Binary (*class in cbapi.response.models*), 45

Binary.FrequencyData (*class in cbapi.response.models*), 45

Binary.SigningData (*class in cbapi.response.models*), 45

Binary.Summary (*class in cbapi.psc.threathunter.models*), 88

Binary.VersionInfo (*class in cbapi.response.models*), 45

## C

canAnalyze (*cbapi.protection.models.Connector attribute*), 57

cbapi.protection.models (*module*), 56

cbapi.psc.defense.models (*module*), 72

CbDefenseAPI (*class in cbapi.psc.defense.rest\_api*), 70

CbLiveQueryAPI (*class in cbapi.psc.livequery.rest\_api*), 88

CbLRSessionBase (*class in cbapi.live\_response\_api*), 50

CbProtectionAPI (*class in cbapi.protection.rest\_api*), 54

CbResponseAPI (*class in cbapi.response.rest\_api*), 37

CbThreatHunterAPI (*class in cbapi.psc.threathunter.rest\_api*), 74

cellPhone (*cbapi.protection.models.User attribute*), 68

certificate (*cbapi.protection.models.FileCatalog attribute*), 58

Certificate (*class in cbapi.protection.models*), 57

childprocs (*cbapi.response.models.Process attribute*), 42

children (*cbapi.psc.threathunter.models.Process attribute*), 80

children (*cbapi.psc.threathunter.models.Tree attribute*), 81

children (*cbapi.response.models.Process attribute*), 42

classifier\_ (*cbapi.psc.threathunter.models.Watchlist attribute*), 86

clVersion (*cbapi.protection.models.FileRule attribute*), 61

clVersion (*cbapi.protection.models.TrustedUser attribute*), 67

clVersionMax (*cbapi.protection.models.Policy attribute*), 65

cmdline (*cbapi.response.models.Process attribute*), 42

comments (*cbapi.protection.models.User attribute*), 68

comms\_ip (*cbapi.response.models.Process attribute*), 42

computer (*cbapi.protection.models.ApprovalRequest attribute*), 56

computer (*cbapi.protection.models.FileCatalog attribute*), 58

computer (*cbapi.protection.models.FileInstance attribute*), 59

Computer (*class in cbapi.protection.models*), 57

connectedComputers (*cbapi.protection.models.Policy attribute*), 65

Connector (*class in cbapi.protection.models*), 57

connectorId (*cbapi.protection.models.Notification attribute*), 62

connectorVersion (*cbapi.protection.models.Connector attribute*), 58

convert\_query () (*cbapi.psc.threathunter.rest\_api.CbThreatHunterAPI method*), 75

create () (*cbapi.protection.rest\_api.CbProtectionAPI method*), 55

create () (*cbapi.psc.defense.rest\_api.CbDefenseAPI method*), 70

create () (*cbapi.psc.livequery.rest\_api.CbLiveQueryAPI method*), 88

create () (*cbapi.psc.threathunter.rest\_api.CbThreatHunterAPI method*), 75

create () (*cbapi.response.rest\_api.CbResponseAPI method*), 38

create\_directory () (*cbapi.live\_response\_api.CbLRSessionBase method*), 51

create\_new\_partition () (*cbapi.response.rest\_api.CbResponseAPI method*), 38

create\_notification () (*cbapi.protection.models.PendingAnalysis method*), 64

create\_process () (*cbapi.live\_response\_api.CbLRSessionBase method*), 53

create\_registry\_key () (*cbapi.live\_response\_api.CbLRSessionBase method*), 52

createdBy (*cbapi.protection.models.FileRule attribute*), 61



- tribute), 61
- createdBy (*cbapi.protection.models.TrustedUser attribute*), 67
- createdBy (*cbapi.protection.models.UserGroup attribute*), 70
- createdByUser (*cbapi.protection.models.FileRule attribute*), 61
- createdByUserId (*cbapi.protection.models.FileRule attribute*), 61
- createdByUserId (*cbapi.protection.models.Policy attribute*), 65
- createdByUserId (*cbapi.protection.models.TrustedUser attribute*), 67
- createdByUserId (*cbapi.protection.models.UserGroup attribute*), 70
- createTime (*cbapi.psc.defense.models.Device attribute*), 72
- CredentialError, 93
- criteria() (*cbapi.psc.livequery.models.ResultQuery method*), 91
- crossprocs (*cbapi.response.models.Process attribute*), 42
- custom\_severities (*cbapi.psc.threathunter.rest\_api.CbThreatHunterAPI attribute*), 75
- custom\_severity (*cbapi.psc.threathunter.models.Report attribute*), 83
- customLogo (*cbapi.protection.models.Policy attribute*), 65
- ## D
- dashboard\_statistics() (*cbapi.response.rest\_api.CbResponseAPI method*), 38
- dateCreated (*cbapi.protection.models.FileRule attribute*), 61
- dateCreated (*cbapi.protection.models.Policy attribute*), 65
- dateCreated (*cbapi.protection.models.TrustedUser attribute*), 67
- dateCreated (*cbapi.protection.models.UserGroup attribute*), 70
- dateModified (*cbapi.protection.models.FileRule attribute*), 61
- dateModified (*cbapi.protection.models.Policy attribute*), 65
- dateModified (*cbapi.protection.models.TrustedUser attribute*), 67
- dateModified (*cbapi.protection.models.UserGroup attribute*), 70
- DefenseMutableModel (class in *cbapi.psc.defense.models*), 72
- delete() (*cbapi.psc.threathunter.models.Feed method*), 82
- delete() (*cbapi.psc.threathunter.models.Report method*), 83
- delete() (*cbapi.psc.threathunter.models.Watchlist method*), 86
- delete\_file() (*cbapi.live\_response\_api.CbLRSessionBase method*), 50
- delete\_registry\_key() (*cbapi.live\_response\_api.CbLRSessionBase method*), 52
- delete\_registry\_value() (*cbapi.live\_response\_api.CbLRSessionBase method*), 52
- delete\_rule() (*cbapi.psc.defense.models.Policy method*), 74
- department (*cbapi.protection.models.User attribute*), 68
- depth (*cbapi.response.models.Process attribute*), 42
- deregisteredTime (*cbapi.psc.defense.models.Device attribute*), 72
- description (*cbapi.protection.models.FileRule attribute*), 61
- description (*cbapi.protection.models.Policy attribute*), 65
- description (*cbapi.protection.models.TrustedUser attribute*), 67
- description (*cbapi.protection.models.UserGroup attribute*), 70
- description (*cbapi.psc.defense.models.Policy attribute*), 74
- destIp (*cbapi.protection.models.Notification attribute*), 62
- destUsername (*cbapi.protection.models.Notification attribute*), 62
- Device (class in *cbapi.psc.defense.models*), 72
- device\_ (*cbapi.psc.livequery.models.Result attribute*), 93
- device\_ids() (*cbapi.psc.livequery.query.RunQuery method*), 90
- device\_types() (*cbapi.psc.livequery.query.RunQuery method*), 90
- deviceGuid (*cbapi.psc.defense.models.Device attribute*), 72
- deviceId (*cbapi.psc.defense.models.Device attribute*), 72
- deviceId (*cbapi.psc.defense.models.Device attribute*), 72
- deviceOwnerId (*cbapi.psc.defense.models.Device attribute*), 72
- deviceSessionId (*cbapi.psc.defense.models.Device attribute*), 72
- deviceType (*cbapi.psc.defense.models.Device attribute*), 72
- digsig\_issuer (*cbapi.response.models.Binary attribute*), 45
- digsig\_prog\_name (*cbapi.response.models.Binary attribute*), 46

digsig\_publisher (*cbapi.response.models.Binary attribute*), 46  
 digsig\_sign\_time (*cbapi.response.models.Binary attribute*), 46  
 digsig\_subject (*cbapi.response.models.Binary attribute*), 46  
 directories (*cbapi.protection.models.Notification attribute*), 63  
 disable\_alerts() (*cbapi.psc.threathunter.models.Watchlist method*), 86  
 disable\_tags() (*cbapi.psc.threathunter.models.Watchlist method*), 86  
 disconnectedEnforcementLevel (*cbapi.protection.models.Policy attribute*), 65  
 dns\_name (*cbapi.response.models.Sensor attribute*), 47  
 download\_url (*cbapi.psc.threathunter.models.Binary attribute*), 88  
 Downloads (*class in cbapi.psc.threathunter.models*), 88  
 Downloads.FoundItem (*class in cbapi.psc.threathunter.models*), 88  
 DriftReport (*class in cbapi.protection.models*), 58  
 DriftReportContents (*class in cbapi.protection.models*), 58

**E**

editable (*cbapi.protection.models.UserGroup attribute*), 70  
 email (*cbapi.psc.defense.models.Device attribute*), 72  
 emailAddress (*cbapi.protection.models.User attribute*), 68  
 enable\_alerts() (*cbapi.psc.threathunter.models.Watchlist method*), 86  
 enable\_tags() (*cbapi.psc.threathunter.models.Watchlist method*), 86  
 enabled (*cbapi.protection.models.Connector attribute*), 58  
 enabled (*cbapi.protection.models.User attribute*), 68  
 enabled (*cbapi.protection.models.UserGroup attribute*), 70  
 end (*cbapi.response.models.Process attribute*), 42  
 endpoints (*cbapi.response.models.Binary attribute*), 46  
 enforcementLevel (*cbapi.protection.models.Policy attribute*), 65  
 EnforcementLevel (*class in cbapi.protection.models*), 58  
 Event (*class in cbapi.protection.models*), 58  
 Event (*class in cbapi.psc.defense.models*), 74  
 Event (*class in cbapi.psc.threathunter.models*), 81  
 events() (*cbapi.psc.threathunter.models.Process method*), 80  
 external (*cbapi.protection.models.User attribute*), 68

externalId (*cbapi.protection.models.Notification attribute*), 63  
 externalUrl (*cbapi.protection.models.Notification attribute*), 63

**F**

facets (*cbapi.response.models.Watchlist attribute*), 49  
 facets() (*cbapi.response.query.Query method*), 40  
 Feed (*cbapi.psc.threathunter.models.Watchlist attribute*), 86  
 Feed (*class in cbapi.psc.threathunter.models*), 81  
 Feed (*class in cbapi.response.models*), 48  
 FeedQuery (*class in cbapi.psc.threathunter.query*), 79  
 fields\_ (*cbapi.psc.livequery.models.Result attribute*), 93  
 file (*cbapi.protection.models.FileUpload attribute*), 62  
 file (*cbapi.protection.models.PendingAnalysis attribute*), 64  
 file (*cbapi.response.models.Binary attribute*), 46  
 FileAnalysis (*class in cbapi.protection.models*), 58  
 fileAnalysisId (*cbapi.protection.models.Notification attribute*), 63  
 fileCatalog (*cbapi.protection.models.ApprovalRequest attribute*), 56  
 fileCatalog (*cbapi.protection.models.Event attribute*), 58  
 fileCatalog (*cbapi.protection.models.FileInstance attribute*), 59  
 fileCatalog (*cbapi.protection.models.FileRule attribute*), 61  
 fileCatalog (*cbapi.protection.models.PendingAnalysis attribute*), 64  
 FileCatalog (*class in cbapi.protection.models*), 58  
 fileCatalogId (*cbapi.protection.models.FileRule attribute*), 61  
 fileHash (*cbapi.protection.models.FileCatalog attribute*), 58  
 fileHash (*cbapi.protection.models.PendingAnalysis attribute*), 64  
 FileInstance (*class in cbapi.protection.models*), 59  
 FileInstanceDeleted (*class in cbapi.protection.models*), 59  
 FileInstanceGroup (*class in cbapi.protection.models*), 59  
 fileInstances (*cbapi.protection.models.Computer attribute*), 57  
 filemods (*cbapi.response.models.Process attribute*), 42  
 fileName (*cbapi.protection.models.FileRule attribute*), 61  
 fileName (*cbapi.protection.models.Notification attribute*), 63  
 FileRule (*class in cbapi.protection.models*), 59

fileRuleType (*cbapi.protection.models.FileRule attribute*), 61

files (*cbapi.protection.models.Notification attribute*), 63

fileState (*cbapi.protection.models.FileRule attribute*), 61

fileTrackingEnabled (*cbapi.protection.models.Policy attribute*), 65

FileUpload (*class in cbapi.protection.models*), 61

find\_file\_writes() (*cbapi.response.models.Process method*), 42

firstName (*cbapi.protection.models.User attribute*), 68

firstName (*cbapi.psc.defense.models.Device attribute*), 72

firstSeenComputer (*cbapi.protection.models.Certificate attribute*), 57

firstVirusActivityTime (*cbapi.psc.defense.models.Device attribute*), 72

flags (*cbapi.protection.models.Notification attribute*), 63

flush\_events() (*cbapi.response.models.Sensor method*), 47

forceInstaller (*cbapi.protection.models.FileRule attribute*), 61

forceNotInstaller (*cbapi.protection.models.FileRule attribute*), 61

found (*cbapi.psc.threathunter.models.Downloads attribute*), 88

frequency (*cbapi.response.models.Binary attribute*), 46

from\_ui() (*cbapi.response.rest\_api.CbResponseAPI method*), 38

## G

get\_file() (*cbapi.live\_response\_api.CbLRSessionBase method*), 50

get\_notifications() (*cbapi.psc.defense.rest\_api.CbDefenseAPI method*), 70

get\_registry\_value() (*cbapi.live\_response\_api.CbLRSessionBase method*), 51

GrantedUserPolicyPermission (*class in cbapi.protection.models*), 62

group (*cbapi.response.models.Sensor attribute*), 47

group\_by() (*cbapi.response.models.ProcessQuery method*), 40

## H

hash (*cbapi.protection.models.FileRule attribute*), 61

helpDeskUrl (*cbapi.protection.models.Policy attribute*), 65

hidden (*cbapi.protection.models.Policy attribute*), 65

homePhone (*cbapi.protection.models.User attribute*), 68

hostname (*cbapi.response.models.Sensor attribute*), 47

httpHeader (*cbapi.protection.models.Notification attribute*), 63

## I

icon (*cbapi.response.models.Binary attribute*), 46

id (*cbapi.protection.models.Connector attribute*), 58

id (*cbapi.protection.models.FileRule attribute*), 61

id (*cbapi.protection.models.Policy attribute*), 65

id (*cbapi.protection.models.TrustedUser attribute*), 67

id (*cbapi.protection.models.User attribute*), 68

id (*cbapi.protection.models.UserGroup attribute*), 70

id (*cbapi.psc.defense.models.Policy attribute*), 74

idUnique (*cbapi.protection.models.FileRule attribute*), 61

ignore() (*cbapi.psc.threathunter.models.IOC\_V2 method*), 85

ignore() (*cbapi.psc.threathunter.models.Report method*), 83

ignored (*cbapi.psc.threathunter.models.IOC\_V2 attribute*), 85

ignored (*cbapi.psc.threathunter.models.Report attribute*), 83

imageUrl (*cbapi.protection.models.Policy attribute*), 65

info() (*cbapi.response.rest\_api.CbResponseAPI method*), 38

info\_key (*cbapi.psc.defense.models.Device attribute*), 72

info\_key (*cbapi.psc.defense.models.Event attribute*), 74

info\_key (*cbapi.psc.defense.models.Policy attribute*), 74

installerFileCatalog (*cbapi.protection.models.ApprovalRequest attribute*), 56

interface\_ip (*cbapi.response.models.Process attribute*), 43

InternalEvent (*class in cbapi.protection.models*), 62

InvalidObjectError, 93

IOC (*class in cbapi.psc.threathunter.models*), 84

IOC\_V2 (*class in cbapi.psc.threathunter.models*), 84

iocs\_ (*cbapi.psc.threathunter.models.Report attribute*), 83

ipaddr (*cbapi.response.models.Sensor.NetworkAdapter attribute*), 47

is\_64bit (*cbapi.response.models.Binary attribute*), 46

is\_executable\_image (cbapi.response.models.Binary attribute), 46

isInternal (cbapi.protection.models.Connector attribute), 58

isolate() (cbapi.response.models.Sensor method), 47

## K

kill\_process() (cbapi.live\_response\_api.CbLRSessionBase method), 53

## L

last\_server\_update (cbapi.response.models.Process attribute), 43

last\_update (cbapi.response.models.Process attribute), 43

lastContact (cbapi.psc.defense.models.Device attribute), 72

lastExternalIpAddress (cbapi.psc.defense.models.Device attribute), 72

lastInternalIpAddress (cbapi.psc.defense.models.Device attribute), 72

lastLocation (cbapi.psc.defense.models.Device attribute), 72

lastName (cbapi.protection.models.User attribute), 68

lastName (cbapi.psc.defense.models.Device attribute), 72

lastReportedTime (cbapi.psc.defense.models.Device attribute), 72

lastResetTime (cbapi.psc.defense.models.Device attribute), 72

lastShutdownTime (cbapi.psc.defense.models.Device attribute), 73

lastVirusActivityTime (cbapi.psc.defense.models.Device attribute), 73

latestRevision (cbapi.psc.defense.models.Policy attribute), 74

lazyApproval (cbapi.protection.models.FileRule attribute), 61

LevelHigh (cbapi.protection.models.EnforcementLevel attribute), 58

LevelLow (cbapi.protection.models.EnforcementLevel attribute), 58

LevelMedium (cbapi.protection.models.EnforcementLevel attribute), 58

LevelNone (cbapi.protection.models.EnforcementLevel attribute), 58

license\_request() (cbapi.response.rest\_api.CbResponseAPI method), 38

limits() (cbapi.psc.threathunter.rest\_api.CbThreatHunterAPI method), 75

linuxKernelVersion (cbapi.psc.defense.models.Device attribute), 73

list\_directory() (cbapi.live\_response\_api.CbLRSessionBase method), 50

list\_processes() (cbapi.live\_response\_api.CbLRSessionBase method), 54

list\_registry\_keys() (cbapi.live\_response\_api.CbLRSessionBase method), 53

list\_registry\_keys\_and\_values() (cbapi.live\_response\_api.CbLRSessionBase method), 52

loadAgentInSafeMode (cbapi.protection.models.Policy attribute), 65

lr\_session() (cbapi.psc.defense.models.Device method), 73

lr\_session() (cbapi.response.models.Sensor method), 47

## M

macaddr (cbapi.response.models.Sensor.NetworkAdapter attribute), 47

malwareName (cbapi.protection.models.Notification attribute), 63

malwareType (cbapi.protection.models.Notification attribute), 63

manualCount (cbapi.protection.models.UserGroup attribute), 70

max\_children() (cbapi.response.models.ProcessQuery method), 40

max\_last\_server\_update (cbapi.response.models.Process attribute), 43

max\_last\_server\_update() (cbapi.response.models.ProcessQuery method), 40

max\_last\_update (cbapi.response.models.Process attribute), 43

max\_last\_update() (cbapi.response.models.ProcessQuery method), 41

md5 (cbapi.protection.models.Notification attribute), 63

messages (cbapi.psc.defense.models.Device attribute), 73

MeteredExecution (class in cbapi.protection.models), 62

metrics\_ (cbapi.psc.livequery.models.Result attribute), 93

middleName (cbapi.psc.defense.models.Device attribute), 73

min\_last\_server\_update (cbapi.response.models.Process attribute), 43

- min\_last\_server\_update() (cbapi.response.models.ProcessQuery method), 41  
 min\_last\_update (cbapi.response.models.Process attribute), 43  
 min\_last\_update() (cbapi.response.models.ProcessQuery method), 41  
 modifiedBy (cbapi.protection.models.FileRule attribute), 61  
 modifiedBy (cbapi.protection.models.TrustedUser attribute), 67  
 modifiedBy (cbapi.protection.models.UserGroup attribute), 70  
 modifiedByUserId (cbapi.protection.models.FileRule attribute), 61  
 modifiedByUserId (cbapi.protection.models.Policy attribute), 65  
 modifiedByUserId (cbapi.protection.models.TrustedUser attribute), 67  
 modifiedByUserId (cbapi.protection.models.UserGroup attribute), 70  
 modloads (cbapi.response.models.Process attribute), 43  
 MoreThanOneResultError, 93  
 msgFormat (cbapi.protection.models.Notification attribute), 63
- ## N
- name (cbapi.protection.models.Connector attribute), 58  
 name (cbapi.protection.models.FileRule attribute), 61  
 name (cbapi.protection.models.Policy attribute), 65  
 name (cbapi.protection.models.TrustedUser attribute), 67  
 name (cbapi.protection.models.User attribute), 69  
 name (cbapi.protection.models.UserGroup attribute), 70  
 name (cbapi.psc.defense.models.Device attribute), 73  
 name (cbapi.psc.defense.models.Policy attribute), 74  
 name() (cbapi.psc.livequery.query.RunQuery method), 90  
 netconns (cbapi.response.models.Process attribute), 43  
 network\_interfaces (cbapi.response.models.Sensor attribute), 47  
 not\_() (cbapi.psc.livequery.models.ResultQuery method), 91  
 not\_() (cbapi.psc.livequery.query.QueryBuilder method), 89  
 not\_() (cbapi.psc.threathunter.models.AsyncProcessQuery method), 78  
 not\_() (cbapi.psc.threathunter.query.Query method), 77  
 not\_() (cbapi.psc.threathunter.query.QueryBuilder method), 76  
 Notification (class in cbapi.protection.models), 62  
 notification\_listener() (cbapi.psc.defense.rest\_api.CbDefenseAPI method), 71  
 Notifier (class in cbapi.protection.models), 63  
 notify\_on\_finish() (cbapi.psc.livequery.query.RunQuery method), 90
- ## O
- ObjectNotFoundError, 93  
 observed\_filenames (cbapi.response.models.Binary attribute), 46  
 or\_() (cbapi.psc.livequery.models.ResultQuery method), 91  
 or\_() (cbapi.psc.livequery.query.QueryBuilder method), 89  
 or\_() (cbapi.psc.threathunter.models.AsyncProcessQuery method), 78  
 or\_() (cbapi.psc.threathunter.query.Query method), 78  
 or\_() (cbapi.psc.threathunter.query.QueryBuilder method), 76  
 organizationId (cbapi.psc.defense.models.Device attribute), 73  
 organizationName (cbapi.psc.defense.models.Device attribute), 73  
 origIdUnique (cbapi.protection.models.FileRule attribute), 61  
 os (cbapi.response.models.Sensor attribute), 48  
 osVersion (cbapi.psc.defense.models.Device attribute), 73
- ## P
- packageName (cbapi.protection.models.Policy attribute), 65  
 pager (cbapi.protection.models.User attribute), 69  
 parent (cbapi.protection.models.Certificate attribute), 57  
 parent (cbapi.response.models.Process attribute), 43  
 parent\_md5 (cbapi.response.models.Process attribute), 43  
 parents (cbapi.psc.threathunter.models.Process attribute), 80  
 passiveMode (cbapi.psc.defense.models.Device attribute), 73  
 passwordHash (cbapi.protection.models.User attribute), 69  
 passwordSalt (cbapi.protection.models.User attribute), 69  
 pendingAnalyses (cbapi.protection.models.Connector attribute), 58

- PendingAnalysis (class in *cbapi.protection.models*), 63
  - permissions (*cbapi.protection.models.UserGroup* attribute), 70
  - platformFlags (*cbapi.protection.models.FileRule* attribute), 61
  - platformId (*cbapi.protection.models.TrustedUser* attribute), 67
  - PlatformLinux (*cbapi.protection.models.FileRule* attribute), 60
  - PlatformMac (*cbapi.protection.models.FileRule* attribute), 60
  - PlatformWindows (*cbapi.protection.models.FileRule* attribute), 60
  - policy (*cbapi.protection.models.Computer* attribute), 57
  - policy (*cbapi.psc.defense.models.Policy* attribute), 74
  - Policy (class in *cbapi.protection.models*), 64
  - Policy (class in *cbapi.psc.defense.models*), 74
  - policy\_ids() (*cbapi.psc.livequery.query.RunQuery* method), 90
  - policyId (*cbapi.psc.defense.models.Device* attribute), 73
  - policyIds (*cbapi.protection.models.FileRule* attribute), 61
  - policyIds (*cbapi.protection.models.UserGroup* attribute), 70
  - policyName (*cbapi.psc.defense.models.Device* attribute), 73
  - primary\_key (*cbapi.psc.defense.models.Device* attribute), 73
  - primary\_key (*cbapi.psc.defense.models.Event* attribute), 74
  - priorityLevel (*cbapi.psc.defense.models.Policy* attribute), 74
  - Process (class in *cbapi.psc.threathunter.models*), 80
  - Process (class in *cbapi.response.models*), 42
  - Process.Summary (class in *cbapi.psc.threathunter.models*), 80
  - process\_md5 (*cbapi.psc.threathunter.models.Process* attribute), 80
  - process\_pids (*cbapi.psc.threathunter.models.Process* attribute), 80
  - process\_sha256 (*cbapi.psc.threathunter.models.Process* attribute), 80
  - processFileCatalog (*cbapi.protection.models.ApprovalRequest* attribute), 56
  - ProcessQuery (class in *cbapi.response.models*), 40
  - product (*cbapi.protection.models.Notification* attribute), 63
  - publisher (*cbapi.protection.models.Certificate* attribute), 57
  - publisher (*cbapi.protection.models.FileCatalog* attribute), 58
  - Publisher (class in *cbapi.protection.models*), 65
  - PublisherCertificate (class in *cbapi.protection.models*), 66
  - put\_file() (*cbapi.live\_response\_api.CbLRSessionBase* method), 50
- ## Q
- quarantined (*cbapi.psc.defense.models.Device* attribute), 73
  - queries() (*cbapi.psc.threathunter.rest\_api.CbThreatHunterAPI* method), 75
  - query (*cbapi.response.models.Watchlist* attribute), 49
  - Query (class in *cbapi.protection.rest\_api*), 55
  - Query (class in *cbapi.psc.defense.rest\_api*), 71
  - Query (class in *cbapi.psc.threathunter.query*), 77
  - Query (class in *cbapi.response.query*), 39
  - QueryBuilder (class in *cbapi.psc.livequery.query*), 89
  - QueryBuilder (class in *cbapi.psc.threathunter.query*), 76
  - queued\_stats (*cbapi.response.models.Sensor* attribute), 48
- ## R
- readOnly (*cbapi.protection.models.Policy* attribute), 65
  - readOnly (*cbapi.protection.models.User* attribute), 69
  - refresh() (*cbapi.response.models.Process* method), 43
  - registeredTime (*cbapi.psc.defense.models.Device* attribute), 73
  - registrationDate (*cbapi.protection.models.User* attribute), 69
  - regKeys (*cbapi.protection.models.Notification* attribute), 63
  - regmods (*cbapi.response.models.Process* attribute), 43
  - replace\_reports() (*cbapi.psc.threathunter.models.Feed* method), 82
  - replace\_rule() (*cbapi.psc.defense.models.Policy* method), 74
  - Report (class in *cbapi.psc.threathunter.models*), 82
  - reportOnly (*cbapi.protection.models.FileRule* attribute), 61
  - ReportQuery (class in *cbapi.psc.threathunter.query*), 79
  - reports (*cbapi.psc.threathunter.models.Feed* attribute), 82
  - reports (*cbapi.psc.threathunter.models.Watchlist* attribute), 86
  - ReportSeverity (class in *cbapi.psc.threathunter.models*), 87
  - reputationApprovalsEnabled (*cbapi.protection.models.FileRule* attribute),

- 61
- reputationEnabled  
(*cbapi.protection.models.Policy* attribute), 65
- resetCLIPassword()  
(*cbapi.protection.models.Computer* method), 57
- ResolutionApproved  
(*cbapi.protection.models.ApprovalRequest* attribute), 56
- ResolutionInstaller  
(*cbapi.protection.models.ApprovalRequest* attribute), 56
- ResolutionNotResolved  
(*cbapi.protection.models.ApprovalRequest* attribute), 56
- ResolutionOther (*cbapi.protection.models.ApprovalRequest* attribute), 56
- ResolutionPublisher  
(*cbapi.protection.models.ApprovalRequest* attribute), 56
- ResolutionRejected  
(*cbapi.protection.models.ApprovalRequest* attribute), 56
- ResolutionRuleChange  
(*cbapi.protection.models.ApprovalRequest* attribute), 56
- ResolutionUpdater  
(*cbapi.protection.models.ApprovalRequest* attribute), 56
- resource\_status (*cbapi.response.models.Sensor* attribute), 48
- restart\_sensor() (*cbapi.response.models.Sensor* method), 48
- Result (class in *cbapi.psc.livequery.models*), 93
- Result.Device (class in *cbapi.psc.livequery.models*), 93
- Result.Fields (class in *cbapi.psc.livequery.models*), 93
- Result.Metrics (class in *cbapi.psc.livequery.models*), 93
- ResultClean (*cbapi.protection.models.Notification* attribute), 62
- ResultClean (*cbapi.protection.models.PendingAnalysis* attribute), 63
- ResultMalicious (*cbapi.protection.models.Notification* attribute), 62
- ResultMalicious (*cbapi.protection.models.PendingAnalysis* attribute), 63
- ResultNotAvailable  
(*cbapi.protection.models.Notification* attribute), 62
- ResultNotAvailable  
(*cbapi.protection.models.PendingAnalysis* attribute), 63
- ResultPotentialThreat  
(*cbapi.protection.models.Notification* attribute), 62
- ResultPotentialThreat  
(*cbapi.protection.models.PendingAnalysis* attribute), 63
- ResultQuery (class in *cbapi.psc.livequery.models*), 90
- rootedByAnalytics  
(*cbapi.psc.defense.models.Device* attribute), 73
- rootedByAnalyticsTime  
(*cbapi.psc.defense.models.Device* attribute), 73
- rootedBySensor (*cbapi.psc.defense.models.Device* attribute), 73
- rootedBySensorTime  
(*cbapi.psc.defense.models.Device* attribute), 73
- Roots (*cbapi.psc.defense.models.Policy* attribute), 74
- Run (class in *cbapi.psc.livequery.models*), 92
- run\_id() (*cbapi.psc.livequery.models.ResultQuery* method), 91
- RunQuery (class in *cbapi.psc.livequery.query*), 90
- ## S
- salutation (*cbapi.protection.models.User* attribute), 69
- save() (*cbapi.psc.threathunter.models.Feed* method), 82
- save() (*cbapi.psc.threathunter.models.Watchlist* method), 86
- save\_watchlist() (*cbapi.psc.threathunter.models.Report* method), 83
- scanLastActionTime  
(*cbapi.psc.defense.models.Device* attribute), 73
- scanLastCompleteTime  
(*cbapi.psc.defense.models.Device* attribute), 73
- scanStatus (*cbapi.psc.defense.models.Device* attribute), 73
- ScriptRule (class in *cbapi.protection.models*), 66
- search() (*cbapi.response.models.Watchlist* method), 49
- search\_binaries() (*cbapi.response.models.Feed* method), 48
- search\_processes() (*cbapi.response.models.Feed* method), 49
- select() (*cbapi.protection.rest\_api.CbProtectionAPI* method), 55
- select() (*cbapi.psc.defense.rest\_api.CbDefenseAPI* method), 71
- select() (*cbapi.psc.livequery.rest\_api.CbLiveQueryAPI* method), 89
- select() (*cbapi.psc.threathunter.rest\_api.CbThreatHunterAPI* method), 75
- select() (*cbapi.response.rest\_api.CbResponseAPI* method), 38

- sensor (*cbapi.response.models.Process* attribute), 43
- Sensor (*class in cbapi.response.models*), 47
- Sensor.NetworkAdapter (*class in cbapi.response.models*), 47
- sensorStates (*cbapi.psc.defense.models.Device* attribute), 73
- sensorVersion (*cbapi.psc.defense.models.Device* attribute), 73
- ServerConfig (*class in cbapi.protection.models*), 66
- ServerError, 93
- ServerPerformance (*class in cbapi.protection.models*), 66
- set\_registry\_value () (*cbapi.live\_response\_api.CbLRSessionBase* method), 52
- severity (*cbapi.protection.models.Notification* attribute), 63
- sha1 (*cbapi.protection.models.Notification* attribute), 63
- sha256 (*cbapi.protection.models.Notification* attribute), 63
- siblings (*cbapi.psc.threathunter.models.Process* attribute), 81
- sid (*cbapi.response.models.Sensor* attribute), 48
- signed (*cbapi.response.models.Binary* attribute), 46
- signing\_data (*cbapi.response.models.Binary* attribute), 46
- size (*cbapi.response.models.Binary* attribute), 46
- sort () (*cbapi.protection.rest\_api.Query* method), 56
- sort () (*cbapi.response.query.Query* method), 40
- sort\_by () (*cbapi.psc.livequery.models.ResultQuery* method), 91
- sort\_by () (*cbapi.psc.threathunter.models.AsyncProcessQuery* method), 79
- sourceId (*cbapi.protection.models.FileRule* attribute), 61
- sourceType (*cbapi.protection.models.FileRule* attribute), 61
- SourceTypeApplicationTemplate (*cbapi.protection.models.FileRule* attribute), 60
- SourceTypeEventRule (*cbapi.protection.models.FileRule* attribute), 60
- SourceTypeExternal (*cbapi.protection.models.FileRule* attribute), 60
- SourceTypeImported (*cbapi.protection.models.FileRule* attribute), 60
- SourceTypeManual (*cbapi.protection.models.FileRule* attribute), 60
- SourceTypeReputation (*cbapi.protection.models.FileRule* attribute), 60
- SourceTypeTrustedDirectory (*cbapi.protection.models.FileRule* attribute), 60
- SourceTypeUnifiedManagement (*cbapi.protection.models.FileRule* attribute), 60
- srcHost (*cbapi.protection.models.Notification* attribute), 63
- srcIp (*cbapi.protection.models.Notification* attribute), 63
- srcUsername (*cbapi.protection.models.Notification* attribute), 63
- start (*cbapi.response.models.Process* attribute), 43
- StateApproved (*cbapi.protection.models.Certificate* attribute), 57
- StateApproved (*cbapi.protection.models.FileRule* attribute), 60
- StateBanned (*cbapi.protection.models.Certificate* attribute), 57
- StateBanned (*cbapi.protection.models.FileRule* attribute), 60
- StateMixed (*cbapi.protection.models.Certificate* attribute), 57
- StateUnapproved (*cbapi.protection.models.Certificate* attribute), 57
- StateUnapproved (*cbapi.protection.models.FileRule* attribute), 61
- status (*cbapi.protection.models.Notification* attribute), 63
- status (*cbapi.psc.defense.models.Device* attribute), 73
- StatusAnalyzed (*cbapi.protection.models.PendingAnalysis* attribute), 63
- StatusCancelled (*cbapi.protection.models.PendingAnalysis* attribute), 64
- StatusClosed (*cbapi.protection.models.ApprovalRequest* attribute), 56
- StatusError (*cbapi.protection.models.PendingAnalysis* attribute), 64
- StatusOpen (*cbapi.protection.models.ApprovalRequest* attribute), 56
- StatusProcessed (*cbapi.protection.models.PendingAnalysis* attribute), 64
- StatusScheduled (*cbapi.protection.models.PendingAnalysis* attribute), 64
- StatusSubmitted (*cbapi.protection.models.ApprovalRequest* attribute), 56
- StatusSubmitted (*cbapi.protection.models.PendingAnalysis* attribute), 64
- submit () (*cbapi.psc.livequery.query.RunQuery* method), 90
- summary (*cbapi.psc.threathunter.models.Binary* attribute), 88
- summary (*cbapi.psc.threathunter.models.Process* attribute), 81



systemPolicy (*cbapi.psc.defense.models.Policy* attribute), 74

## T

targetApp (*cbapi.protection.models.Notification* attribute), 63

targetOS (*cbapi.protection.models.Notification* attribute), 63

targetPriorityType (*cbapi.psc.defense.models.Device* attribute), 73

templateComputer (*cbapi.protection.models.Computer* attribute), 57

testId (*cbapi.psc.defense.models.Device* attribute), 73

ThreatReportQuery (class in *cbapi.response.models*), 41

time (*cbapi.protection.models.Notification* attribute), 63

timeout () (*cbapi.psc.threathunter.models.AsyncProcessQuery* method), 79

TimeoutError, 94

title (*cbapi.protection.models.User* attribute), 69

totalComputers (*cbapi.protection.models.Policy* attribute), 65

Tree (class in *cbapi.psc.threathunter.models*), 81

tree () (*cbapi.psc.threathunter.models.Process* method), 81

TrustedDirectory (class in *cbapi.protection.models*), 66

TrustedUser (class in *cbapi.protection.models*), 66

type (*cbapi.protection.models.Notification* attribute), 63

## U

unified (*cbapi.protection.models.User* attribute), 69

unifiedFlag (*cbapi.protection.models.FileRule* attribute), 61

unifiedSource (*cbapi.protection.models.FileRule* attribute), 61

unignore () (*cbapi.psc.threathunter.models.IOC\_V2* method), 85

unignore () (*cbapi.psc.threathunter.models.Report* method), 84

uninstalledTime (*cbapi.psc.defense.models.Device* attribute), 73

unisolate () (*cbapi.response.models.Sensor* method), 48

unsigned\_modloads (*cbapi.response.models.Process* attribute), 43

update () (*cbapi.psc.threathunter.models.Feed* method), 82

update () (*cbapi.psc.threathunter.models.Report* method), 84

update () (*cbapi.psc.threathunter.models.Watchlist* method), 87

update\_license () (*cbapi.response.rest\_api.CbResponseAPI* method), 39

Updater (class in *cbapi.protection.models*), 67

urlobject (*cbapi.protection.models.ApprovalRequest* attribute), 57

urlobject (*cbapi.protection.models.Certificate* attribute), 57

urlobject (*cbapi.protection.models.Computer* attribute), 57

urlobject (*cbapi.protection.models.Connector* attribute), 58

urlobject (*cbapi.protection.models.DriftReport* attribute), 58

urlobject (*cbapi.protection.models.DriftReportContents* attribute), 58

urlobject (*cbapi.protection.models.Event* attribute), 58

urlobject (*cbapi.protection.models.FileAnalysis* attribute), 58

urlobject (*cbapi.protection.models.FileCatalog* attribute), 59

urlobject (*cbapi.protection.models.FileInstance* attribute), 59

urlobject (*cbapi.protection.models.FileInstanceDeleted* attribute), 59

urlobject (*cbapi.protection.models.FileInstanceGroup* attribute), 59

urlobject (*cbapi.protection.models.FileRule* attribute), 61

urlobject (*cbapi.protection.models.FileUpload* attribute), 62

urlobject (*cbapi.protection.models.GrantedUserPolicyPermission* attribute), 62

urlobject (*cbapi.protection.models.InternalEvent* attribute), 62

urlobject (*cbapi.protection.models.MeteredExecution* attribute), 62

urlobject (*cbapi.protection.models.Notification* attribute), 63

urlobject (*cbapi.protection.models.Notifier* attribute), 63

urlobject (*cbapi.protection.models.PendingAnalysis* attribute), 64

urlobject (*cbapi.protection.models.Policy* attribute), 65

urlobject (*cbapi.protection.models.Publisher* attribute), 66

urlobject (*cbapi.protection.models.PublisherCertificate* attribute), 66

urlobject (*cbapi.protection.models.ScriptRule* attribute), 66

urlobject (*cbapi.protection.models.ServerConfig* attribute), 66

urlobject (*cbapi.protection.models.ServerPerformance*

*attribute*), 66  
 urlobject (*cbapi.protection.models.TrustedDirectory attribute*), 66  
 urlobject (*cbapi.protection.models.TrustedUser attribute*), 67  
 urlobject (*cbapi.protection.models.Updater attribute*), 67  
 urlobject (*cbapi.protection.models.User attribute*), 69  
 urlobject (*cbapi.protection.models.UserGroup attribute*), 70  
 urlobject (*cbapi.psc.defense.models.Device attribute*), 73  
 urlobject (*cbapi.psc.defense.models.Event attribute*), 74  
 urlobject (*cbapi.psc.defense.models.Policy attribute*), 74  
 use\_comprehensive\_search() (*cbapi.response.models.ProcessQuery method*), 41  
 User (*class in cbapi.protection.models*), 67  
 UserGroup (*class in cbapi.protection.models*), 69  
 userGroupIds (*cbapi.protection.models.User attribute*), 69  
 username (*cbapi.response.models.Process attribute*), 43  
 userSid (*cbapi.protection.models.TrustedUser attribute*), 67

## V

validate() (*cbapi.psc.threathunter.models.Feed method*), 82  
 validate() (*cbapi.psc.threathunter.models.IOC method*), 84  
 validate() (*cbapi.psc.threathunter.models.IOC\_V2 method*), 85  
 validate() (*cbapi.psc.threathunter.models.Report method*), 84  
 validate() (*cbapi.psc.threathunter.models.Watchlist method*), 87  
 validate\_query() (*cbapi.psc.threathunter.rest\_api.CbThreatHunterAPI method*), 75  
 vdiBaseDevice (*cbapi.psc.defense.models.Device attribute*), 73  
 version (*cbapi.protection.models.FileRule attribute*), 61  
 version (*cbapi.protection.models.Notification attribute*), 63  
 version (*cbapi.psc.defense.models.Policy attribute*), 74  
 version\_info (*cbapi.response.models.Binary attribute*), 46  
 visible (*cbapi.protection.models.FileRule attribute*), 61

## W

walk() (*cbapi.live\_response\_api.CbLRSessionBase method*), 51  
 walk\_children() (*cbapi.response.models.Process method*), 44  
 walk\_parents() (*cbapi.response.models.Process method*), 44  
 Watchlist (*class in cbapi.psc.threathunter.models*), 85  
 Watchlist (*class in cbapi.response.models*), 49  
 WatchlistQuery (*class in cbapi.psc.threathunter.query*), 80  
 webui\_link (*cbapi.response.models.Binary attribute*), 47  
 webui\_link (*cbapi.response.models.Process attribute*), 45  
 webui\_link (*cbapi.response.models.Sensor attribute*), 48  
 where() (*cbapi.protection.rest\_api.Query method*), 56  
 where() (*cbapi.psc.defense.rest\_api.Query method*), 71  
 where() (*cbapi.psc.livequery.models.ResultQuery method*), 92  
 where() (*cbapi.psc.livequery.query.QueryBuilder method*), 90  
 where() (*cbapi.psc.livequery.query.RunQuery method*), 90  
 where() (*cbapi.psc.threathunter.models.AsyncProcessQuery method*), 79  
 where() (*cbapi.psc.threathunter.query.Query method*), 78  
 where() (*cbapi.psc.threathunter.query.QueryBuilder method*), 77  
 where() (*cbapi.response.query.Query method*), 40  
 windowsPlatform (*cbapi.psc.defense.models.Device attribute*), 73