

---

# **certbot-dns-ovh Documentation**

***Release 0***

**Certbot Project**

**Apr 10, 2024**



**CONTENTS:**

<b>1</b>	<b>Named Arguments</b>	<b>3</b>
<b>2</b>	<b>Credentials</b>	<b>5</b>
<b>3</b>	<b>Examples</b>	<b>7</b>
<b>4</b>	<b>API Documentation</b>	<b>9</b>
<b>5</b>	<b>Indices and tables</b>	<b>11</b>
	<b>Python Module Index</b>	<b>13</b>
	<b>Index</b>	<b>15</b>



The `dns_ovh` plugin automates the process of completing a `dns-01` challenge ([DNS01](#)) by creating, and subsequently removing, TXT records using the OVH API.

---

**Note:** The plugin is not installed by default. It can be installed by heading to [certbot.eff.org](https://certbot.eff.org), choosing your system and selecting the Wildcard tab.

---



## NAMED ARGUMENTS

---

<code>--dns-ovh-credentials</code>	OVH <i>credentials</i> INI file. (Required)
<code>--dns-ovh-propagation</code>	The number of seconds to wait for DNS to propagate before asking the ACME server to verify the DNS record. (Default: 30)

---





**CREDENTIALS**

Use of this plugin requires a configuration file containing OVH API credentials for an account with the following access rules (allowing all domains):

- GET /domain/zone/\*
- PUT /domain/zone/\*
- POST /domain/zone/\*
- DELETE /domain/zone/\*

Alternatively, to allow a single domain only, the following access rules apply:

- GET /domain/zone/
- GET /domain/zone/<REQUIRED\_DOMAIN>/\*
- PUT /domain/zone/<REQUIRED\_DOMAIN>/\*
- POST /domain/zone/<REQUIRED\_DOMAIN>/\*
- DELETE /domain/zone/<REQUIRED\_DOMAIN>/\*

These credentials can be obtained at the following links:

- OVH Europe (endpoint: `ovh-eu`)
- OVH North America (endpoint: `ovh-ca`)

Listing 1: Example credentials file:

```
# OVH API credentials used by Certbot
dns_ovh_endpoint = ovh-eu
dns_ovh_application_key = MDAwMDAwMDAwMDAw
dns_ovh_application_secret = MDAwMDAwMDAwMDAwMDAwMDAwMDAwMDAwMDAw
dns_ovh_consumer_key = MDAwMDAwMDAwMDAwMDAwMDAwMDAwMDAwMDAw
```

The path to this file can be provided interactively or using the `--dns-ovh-credentials` command-line argument. Certbot records the path to this file for use during renewal, but does not store the file's contents.

**Caution:** You should protect these API credentials as you would the password to your OVH account. Users who can read this file can use these credentials to issue arbitrary API calls on your behalf. Users who can cause Certbot to run using these credentials can complete a `dns-01` challenge to acquire new certificates or revoke existing certificates for associated domains, even if those domains aren't being managed by this server.

Certbot will emit a warning if it detects that the credentials file can be accessed by other users on your system. The warning reads “Unsafe permissions on credentials configuration file”, followed by the path to the credentials file. This

warning will be emitted each time Certbot uses the credentials file, including for renewal, and cannot be silenced except by addressing the issue (e.g., by using a command like `chmod 600` to restrict access to the file).

## EXAMPLES

Listing 1: To acquire a certificate for `example.com`

```
certbot certonly \  
--dns-ovh \  
--dns-ovh-credentials ~/.secrets/certbot/ovh.ini \  
-d example.com
```

Listing 2: To acquire a single certificate for both `example.com` and `www.example.com`

```
certbot certonly \  
--dns-ovh \  
--dns-ovh-credentials ~/.secrets/certbot/ovh.ini \  
-d example.com \  
-d www.example.com
```

Listing 3: To acquire a certificate for `example.com`, waiting 60 seconds for DNS propagation

```
certbot certonly \  
--dns-ovh \  
--dns-ovh-credentials ~/.secrets/certbot/ovh.ini \  
--dns-ovh-propagation-seconds 60 \  
-d example.com
```



## **API DOCUMENTATION**

Certbot plugins implement the Certbot plugins API, and do not otherwise have an external API.



## INDICES AND TABLES

- genindex
- modindex
- search





## PYTHON MODULE INDEX

### C

`certbot_dns_ovh`, [1](#)



## INDEX

### C

certbot\_dns\_ovh  
    module, 1

### M

module  
    certbot\_dns\_ovh, 1