
coalaipapi Documentation

Release 0.1

BigchainDB

August 10, 2016

1	Install	3
2	Settings	5
3	Deploy	7
4	Developing with Docker	9
4.1	Setting up	9
4.2	Deployment	11
4.3	Building and running your app on EC2	11
4.4	Security advisory	12
5	Indices and tables	13

Contents:

Install

This is where you write how to get a new laptop to run this project.

Settings

List project settings

Deploy

This is where you describe how the project is deployed in production.

Developing with Docker

You can develop your application in a [Docker](#) container for simpler deployment onto bare Linux machines later. This instruction assumes an [Amazon Web Services](#) EC2 instance, but it should work on any machine with Docker > 1.3 and [Docker compose](#) installed.

4.1 Setting up

Docker encourages running one container for each process. This might mean one container for your web server, one for Django application and a third for your database. Once you're happy composing containers in this way you can easily add more, such as a [Redis](#) cache.

The Docker compose tool (previously known as [fig](#)) makes linking these containers easy. An example set up for your Cookiecutter Django project might look like this:

```
webapp/ # Your cookiecutter project would be in here
  Dockerfile
  ...
database/
  Dockerfile
  ...
webserver/
  Dockerfile
  ...
docker-compose.yml
```

Each component of your application would get its own [Dockerfile](#). The rest of this example assumes you are using the [base postgres image](#) for your database. Your database settings in *config/common.py* might then look something like:

```
DATABASES = {
    'default': {
        'ENGINE': 'django.db.backends.postgresql_psycopg2',
        'NAME': 'postgres',
        'USER': 'postgres',
        'HOST': 'database',
        'PORT': 5432,
    }
}
```

The [Docker compose documentation](#) explains in detail what you can accomplish in the *docker-compose.yml* file, but an example configuration might look like this:

```
database:
  build: database
webapp:
  build: webapp:
  command: /usr/bin/python3.4 manage.py runserver 0.0.0.0:8000 # dev setting
  # command: gunicorn -b 0.0.0.0:8000 wsgi:application # production setting
  volumes:
    - webapp/your_project_name:/path/to/container/workdir/
  links:
    - database
webserver:
  build: webserver
  ports:
    - "80:80"
    - "443:443"
  links:
    - webapp
```

We'll ignore the webserver for now (you'll want to comment that part out while we do). A working Dockerfile to run your cookiecutter application might look like this:

```
FROM ubuntu:14.04
ENV REFRESHED_AT 2015-01-13

# update packages and prepare to build software
RUN ["apt-get", "update"]
RUN ["apt-get", "-y", "install", "build-essential", "vim", "git", "curl"]
RUN ["locale-gen", "en_GB.UTF-8"]

# install latest python
RUN ["apt-get", "-y", "build-dep", "python3-dev", "python3-imaging"]
RUN ["apt-get", "-y", "install", "python3-dev", "python3-imaging", "python3-pip"]

# prepare postgresQL support
RUN ["apt-get", "-y", "build-dep", "python3-psycopg2"]

# move into our working directory
# ADD must be after chown see http://stackoverflow.com/a/26145444/1281947
RUN ["groupadd", "python"]
RUN ["useradd", "python", "-s", "/bin/bash", "-m", "-g", "python", "-G", "python"]
ENV HOME /home/python
WORKDIR /home/python
RUN ["chown", "-R", "python:python", "/home/python"]
ADD ./ /home/python

# manage requirements
ENV REQUIREMENTS_REFRESHED_AT 2015-02-25
RUN ["pip3", "install", "-r", "requirements.txt"]

# uncomment the line below to use container as a non-root user
USER python:python
```

Running `sudo docker-compose build` will follow the instructions in your `docker-compose.yml` file and build the database container, then your webapp, before mounting your cookiecutter project files as a volume in the webapp container and linking to the database. Our example yaml file runs in development mode but changing it to production mode is as simple as commenting out the line using `runserver` and uncommenting the line using `gunicorn`.

Both are set to run on port `0.0.0.0:8000`, which is where the Docker daemon will discover it. You can now run `sudo docker-compose up` and browse to `localhost:8000` to see your application running.

Be careful with Elastic IPs because, on the AWS free tier, if you assign one and then stop the machine you will incur charges while the machine is down (presumably because you're preventing them allocating the IP to someone else).

4.4 Security advisory

The setup described in this instruction will get you up-and-running but it hasn't been audited for security. If you are running your own setup like this it is always advisable to, at a minimum, examine your application with a tool like [OWASP ZAP](#) to see what security holes you might be leaving open.

Indices and tables

- `genindex`
- `modindex`
- `search`