
dask-ndinterp Documentation

Release 0+untagged.6.g301299b.dirty

John Kirkham

May 16, 2017

Contents

1	dask-ndinterp	3
2	Installation	5
3	Usage	7
4	API	9
5	Contributing	11
6	Credits	15
7	Indices and tables	17
	Python Module Index	19

Contents:

CHAPTER 1

dask-ndinterp

A library for finding N-D interpolations of Dask Arrays

- Free software: BSD 3-Clause
- Documentation: <https://dask-ndinterp.readthedocs.io>.

Features

- TODO

Credits

This package was created with [Cookiecutter](#) and the [dask-image/dask-image-cookiecutter](#) project template.

Stable release

To install `dask-ndinterp`, run this command in your terminal:

```
$ pip install dask-ndinterp
```

This is the preferred method to install `dask-ndinterp`, as it will always install the most recent stable release.

If you don't have `pip` installed, this [Python installation guide](#) can guide you through the process.

From sources

The sources for `dask-ndinterp` can be downloaded from the [Github repo](#).

You can either clone the public repository:

```
$ git clone git://github.com/dask-image/dask-ndinterp
```

Or download the [tarball](#):

```
$ curl -OL https://github.com/dask-image/dask-ndinterp/tarball/master
```

Once you have a copy of the source, you can install it with:

```
$ python setup.py install
```


CHAPTER 3

Usage

To use dask-ndinterp in a project:

```
import dask_ndinterp
```


dask_ndinterp package

Submodules

dask_ndinterp.core module

Contributions are welcome, and they are greatly appreciated! Every little bit helps, and credit will always be given. You can contribute in many ways:

Types of Contributions

Report Bugs

Report bugs at <https://github.com/dask-image/dask-ndinterp/issues>.

If you are reporting a bug, please include:

- Your operating system name and version.
- Any details about your local setup that might be helpful in troubleshooting.
- Detailed steps to reproduce the bug.

Fix Bugs

Look through the GitHub issues for bugs. Anything tagged with “bug” and “help wanted” is open to whoever wants to implement it.

Implement Features

Look through the GitHub issues for features. Anything tagged with “enhancement” and “help wanted” is open to whoever wants to implement it.

Write Documentation

dask-ndinterp could always use more documentation, whether as part of the official dask-ndinterp docs, in docstrings, or even on the web in blog posts, articles, and such.

Submit Feedback

The best way to send feedback is to file an issue at <https://github.com/dask-image/dask-ndinterp/issues>.

If you are proposing a feature:

- Explain in detail how it would work.
- Keep the scope as narrow as possible, to make it easier to implement.
- Remember that this is a volunteer-driven project, and that contributions are welcome :)

Get Started!

Ready to contribute? Here's how to set up *dask-ndinterp* for local development.

1. Fork the *dask-ndinterp* repo on GitHub.
2. Clone your fork locally:

```
$ git clone git@github.com:your_name_here/dask-ndinterp.git
```

3. Install your local copy into an environment. Assuming you have conda installed, this is how you set up your fork for local development (on Windows drop *source*). Replace “<some version>” with the Python version used for testing.:

```
$ conda create -n dask-ndinterpenv python="<some version>"
$ source activate dask-ndinterpenv
$ python setup.py develop
```

4. Create a branch for local development:

```
$ git checkout -b name-of-your-bugfix-or-feature
```

Now you can make your changes locally.

5. When you're done making changes, check that your changes pass flake8 and the tests, including testing other Python versions:

```
$ flake8 dask_ndinterp tests
$ python setup.py test or py.test
```

To get flake8, just conda install it into your environment.

6. Commit your changes and push your branch to GitHub:

```
$ git add .
$ git commit -m "Your detailed description of your changes."
$ git push origin name-of-your-bugfix-or-feature
```

7. Submit a pull request through the GitHub website.

Pull Request Guidelines

Before you submit a pull request, check that it meets these guidelines:

1. The pull request should include tests.
2. If the pull request adds functionality, the docs should be updated. Put your new functionality into a function with a docstring, and add the feature to the list in README.rst.
3. The pull request should work for Python 2.7, 3.4, 3.5, and 3.6. Check https://travis-ci.org/dask-image/dask-ndinterp/pull_requests and make sure that the tests pass for all supported Python versions.

Tips

To run a subset of tests:

```
$ py.test tests/test_core.py
```


CHAPTER 6

Credits

Development Lead

- John Kirkham, Howard Hughes Medical Institute <kirkhamj@janelia.hhmi.org>

Contributors

None yet. Why not be the first?

CHAPTER 7

Indices and tables

- `genindex`
- `modindex`
- `search`

d

dask_ndinterp, 9

dask_ndinterp.core, 9

D

`dask_ndinterp` (module), 9

`dask_ndinterp.core` (module), 9