dblapi Documentation

Release 0.1.0b

AndyTempel

Sep 15, 2018

Contents:

1 Documentation Contents **3**
- 1.1 API Reference . . . 3
  - 1.1.1 Version Related Info . . . 3
  - 1.1.2 Client . . . 3
  - 1.1.3 Models . . . 3
    - 1.1.3.1 DBLBot . . . 4
    - 1.1.3.2 Avatar . . . 4
    - 1.1.3.3 Description . . . 4
    - 1.1.3.4 DBLStats . . . 4
  - 1.1.4 Exceptions . . . 4
- 1.2 Examples . . . 4

2 Indices and tables **5**

dblapi is improved and easy-to-use API wrapper for Discord Bot List API. Most importantly it features native discord.py integration, plug it in and leave it. It does all the work for you.

Features:

- Uses pythonic way of `async`/`await` syntax
- Uses caching to avoid ratelimiting.
- Plugs directly into discord.py
- Easy to use with object oriented design

To see usage examples select Examples from the menu.

CHAPTER 1

Documentation Contents

1.1 API Reference

The following section outlines the API of dblapi.

Note: This module uses the Python logging module to log diagnostic and errors in an output independent way. If the logging module is not configured, these logs will not be output anywhere.

1.1.1 Version Related Info

There are two main ways to query version information about the library.

version_info
A named tuple that is similar to sys.version_info.

Just like sys.version_info the valid values for `releaselevel` are 'alpha', 'beta', 'candidate' and 'final'.

__version__
A string representation of the version. e.g. `'0.1.0-alpha0'`.

1.1.2 Client

1.1.3 Models

Here is collection of models used by dblapi.

1.1.3.1 DBLBot

1.1.3.2 Avatar

1.1.3.3 Description

1.1.3.4 DBLStats

1.1.4 Exceptions

1.2 Examples

CHAPTER 2

Indices and tables

- genindex
- modindex
- search

Index

Symbols

__version__ (built-in variable), 3

V

version_info (built-in variable), 3