

---

# **Django statsd Documentation**

***Release 2.1.1***

**Rick van Hattem**

**Apr 05, 2018**



---

## Contents

---

|          |                                 |           |
|----------|---------------------------------|-----------|
| <b>1</b> | <b>Introduction</b>             | <b>3</b>  |
| <b>2</b> | <b>Install</b>                  | <b>5</b>  |
| <b>3</b> | <b>Usage</b>                    | <b>7</b>  |
| 3.1      | Advanced Usage . . . . .        | 7         |
| <b>4</b> | <b>django_statsd Package</b>    | <b>9</b>  |
| 4.1      | django_statsd Package . . . . . | 9         |
| 4.2      | settings Module . . . . .       | 9         |
| 4.3      | celery Module . . . . .         | 10        |
| 4.4      | database Module . . . . .       | 10        |
| 4.5      | json Module . . . . .           | 10        |
| 4.6      | middleware Module . . . . .     | 10        |
| 4.7      | redis Module . . . . .          | 12        |
| 4.8      | templates Module . . . . .      | 12        |
| 4.9      | urls Module . . . . .           | 12        |
| 4.10     | utils Module . . . . .          | 12        |
| <b>5</b> | <b>Indices and tables</b>       | <b>13</b> |
|          | <b>Python Module Index</b>      | <b>15</b> |



Contents:



*django\_statsd* is a middleware that uses *python-statsd* to log query and view durations to statsd.

- **Documentation**
  - <http://django-stats.readthedocs.org/en/latest/>
- **Source**
  - <https://github.com/WoLpH/django-statsd>
- **Bug reports**
  - <https://github.com/WoLpH/django-statsd/issues>
- **Package homepage**
  - <https://pypi.python.org/pypi/django-statsd>
- **Python Statsd**
  - <https://github.com/WoLpH/python-statsd>
- **Graphite**
  - <http://graphite.wikidot.com>
- **Statsd**
  - code: <https://github.com/etsy/statsd>
  - blog post: <http://codeascraft.etsy.com/2011/02/15/measure-anything-measure-everything/>





## CHAPTER 2

---

### Install

---

To install simply execute *python setup.py install*. If you want to run the tests first, run *python setup.py test*



To install, add the following to your `settings.py`:

1. `django_statsd` to the `INSTALLED_APPS` setting.
2. `django_statsd.middleware.StatsdMiddleware` to the top of your `MIDDLEWARE_CLASSES`
3. `django_statsd.middleware.StatsdMiddlewareTimer` to the bottom of your `MIDDLEWARE_CLASSES`

## 3.1 Advanced Usage

```
>>> def some_view(request):
...     with request.timings('something_to_time'):
...         # do something here
...         pass
>>>
>>> def some_view(request):
...     request.timings.start('something_to_time')
...     # do something here
...     request.timings.stop('something_to_time')
```



---

## django\_statsd Package

---

### 4.1 django\_statsd Package

`django_statsd.__init__.decr` (*key*, *value=1*)  
`django_statsd.__init__.incr` (*key*, *value=1*)  
`django_statsd.__init__.start` (*key*)  
`django_statsd.__init__.stop` (*key*)  
`django_statsd.__init__.with_` (*key*)  
`django_statsd.__init__.wrapper` (*prefix*, *f*)  
`django_statsd.__init__.named_wrapper` (*name*, *f*)  
`django_statsd.__init__.decorator` (*prefix*)

### 4.2 settings Module

`django_statsd.settings.STATSD_DEBUG = True`  
Enable warnings such as timers which are started but not finished. Defaults to DEBUG if not configured

`django_statsd.settings.STATSD_HOST = '127.0.0.1'`  
Statsd host, defaults to 127.0.0.1

`django_statsd.settings.STATSD_PORT = '8125'`  
Statsd port, defaults to 8125

`django_statsd.settings.STATSD_PREFIX = 'some_key_prefix'`  
Set the global statsd prefix if needed. Otherwise use the root

`django_statsd.settings.STATSD_SAMPLE_RATE = 1.0`  
Statsd sample rate, lowering this decreases the (random) odds of actually submitting the data. Between 0 and 1 where 1 means always

```
django_statsd.settings.STATSD_TAGS_LIKE = None
    Enable creating tags as well as the bare version. This causes an ajax view to be stored both as the regular view
    name and as the ajax tag. Supported separators are _is_ and =

django_statsd.settings.STATSD_TRACK_MIDDLEWARE = True
    Enable tracking all requests using the middleware

django_statsd.settings.get_setting(key, default=None)
```

## 4.3 celery Module

## 4.4 database Module

```
class django_statsd.database.TimingCursorWrapper
    Bases: object

    execute(*args, **kwargs)
    executemany(*args, **kwargs)
```

## 4.5 json Module

## 4.6 middleware Module

```
class django_statsd.middleware.Client(prefix='view')
    Bases: object

    class_
        alias of statsd.client.Client

    get_client(*args)
    submit(*args)

class django_statsd.middleware.Counter(prefix='view')
    Bases: django_statsd.middleware.Client

    class_
        alias of statsd.counter.Counter

    decrement(key, delta=1)
    increment(key, delta=1)
    submit(*args)

class django_statsd.middleware.DummyWith
    Bases: object

class django_statsd.middleware.StatsdMiddleware(get_response)
    Bases: django.utils.deprecation.MiddlewareMixin

    cleanup(request)
    process_exception(request, exception)
    process_request(request)
```

```
    process_response (request, response)
    process_template_response (request, response)
    process_view (request, view_func, view_args, view_kwargs)
    scope = <thread._local object>
    classmethod start (prefix='view')
    classmethod stop (*key)

class django_statsd.middleware.StatsdMiddlewareTimer (get_response=None)
    Bases: django.utils.deprecation.MiddlewareMixin
    process_exception (request, exception)
    process_request (request)
    process_response (request, response)
    process_template_response (request, response)
    process_view (request, view_func, view_args, view_kwargs)

class django_statsd.middleware.Timer (prefix='view')
    Bases: django_statsd.middleware.Client
    class_
        alias of statsd.timer.Timer
    start (key)
    stop (key)
    submit (*args)

class django_statsd.middleware.WithTimer (timer, key)
    Bases: object

django_statsd.middleware.decorator (prefix)
django_statsd.middleware.decr (key, value=1)
django_statsd.middleware.incr (key, value=1)
django_statsd.middleware.named_wrapper (name, f)
django_statsd.middleware.start (key)
django_statsd.middleware.stop (key)
django_statsd.middleware.with_ (key)
django_statsd.middleware.wrapper (prefix, f)
```

## 4.7 redis Module

## 4.8 templates Module

## 4.9 urls Module

```
class django_statsd.urls.StatsdHTTPConnection(*args, **kwargs)
    Bases: httpplib.HTTPConnection

    close(*args, **kwargs)

    connect(*args, **kwargs)
```

## 4.10 utils Module

```
django_statsd.utils.get_client(name, connection=None, class_=<class 'statsd.client.Client'>)
django_statsd.utils.get_connection(host=None, port=None, sample_rate=None)
django_statsd.utils.get_counter(name, connection=None)
django_statsd.utils.get_timer(name, connection=None)
```



## CHAPTER 5

---

### Indices and tables

---

- `genindex`
- `search`



### d

- `django_statsd.__init__`, 9
- `django_statsd.celery`, 10
- `django_statsd.database`, 10
- `django_statsd.json`, 10
- `django_statsd.middleware`, 10
- `django_statsd.redis`, 12
- `django_statsd.settings`, 9
- `django_statsd.templates`, 12
- `django_statsd.urls`, 12
- `django_statsd.utils`, 12



## C

class\_ (django\_statsd.middleware.Client attribute), 10  
class\_ (django\_statsd.middleware.Counter attribute), 10  
class\_ (django\_statsd.middleware.Timer attribute), 11  
cleanup() (django\_statsd.middleware.StatsdMiddleware method), 10  
Client (class in django\_statsd.middleware), 10  
close() (django\_statsd.urls.StatsdHTTPConnection method), 12  
connect() (django\_statsd.urls.StatsdHTTPConnection method), 12  
Counter (class in django\_statsd.middleware), 10

## D

decorator() (in module django\_statsd.\_\_init\_\_), 9  
decorator() (in module django\_statsd.middleware), 11  
decr() (in module django\_statsd.\_\_init\_\_), 9  
decr() (in module django\_statsd.middleware), 11  
decrement() (django\_statsd.middleware.Counter method), 10  
django\_statsd.\_\_init\_\_ (module), 9  
django\_statsd.celery (module), 10  
django\_statsd.database (module), 10  
django\_statsd.json (module), 10  
django\_statsd.middleware (module), 10  
django\_statsd.redis (module), 12  
django\_statsd.settings (module), 9  
django\_statsd.templates (module), 12  
django\_statsd.urls (module), 12  
django\_statsd.utils (module), 12  
DummyWith (class in django\_statsd.middleware), 10

## E

execute() (django\_statsd.database.TimingCursorWrapper method), 10  
executemany() (django\_statsd.database.TimingCursorWrapper method), 10

## G

get\_client() (django\_statsd.middleware.Client method), 10  
get\_client() (in module django\_statsd.utils), 12  
get\_connection() (in module django\_statsd.utils), 12  
get\_counter() (in module django\_statsd.utils), 12  
get\_setting() (in module django\_statsd.settings), 10  
get\_timer() (in module django\_statsd.utils), 12

## I

incr() (in module django\_statsd.\_\_init\_\_), 9  
incr() (in module django\_statsd.middleware), 11  
increment() (django\_statsd.middleware.Counter method), 10

## N

named\_wrapper() (in module django\_statsd.\_\_init\_\_), 9  
named\_wrapper() (in module django\_statsd.middleware), 11

## P

process\_exception() (django\_statsd.middleware.StatsdMiddleware method), 10  
process\_exception() (django\_statsd.middleware.StatsdMiddlewareTimer method), 11  
process\_request() (django\_statsd.middleware.StatsdMiddleware method), 10  
process\_request() (django\_statsd.middleware.StatsdMiddlewareTimer method), 11  
process\_response() (django\_statsd.middleware.StatsdMiddleware method), 10  
process\_response() (django\_statsd.middleware.StatsdMiddlewareTimer method), 11  
process\_template\_response() (django\_statsd.middleware.StatsdMiddleware method), 11  
process\_template\_response() (django\_statsd.middleware.StatsdMiddlewareTimer method), 11

`process_view()` (`django_statsd.middleware.StatsdMiddleware` method), 11  
`process_view()` (`django_statsd.middleware.StatsdMiddlewareTimer` method), 11

## S

`scope` (`django_statsd.middleware.StatsdMiddleware` attribute), 11  
`start()` (`django_statsd.middleware.StatsdMiddleware` class method), 11  
`start()` (`django_statsd.middleware.Timer` method), 11  
`start()` (in module `django_statsd.__init__`), 9  
`start()` (in module `django_statsd.middleware`), 11  
`STATSD_DEBUG` (in module `django_statsd.settings`), 9  
`STATSD_HOST` (in module `django_statsd.settings`), 9  
`STATSD_PORT` (in module `django_statsd.settings`), 9  
`STATSD_PREFIX` (in module `django_statsd.settings`), 9  
`STATSD_SAMPLE_RATE` (in module `django_statsd.settings`), 9  
`STATSD_TAGS_LIKE` (in module `django_statsd.settings`), 9  
`STATSD_TRACK_MIDDLEWARE` (in module `django_statsd.settings`), 10  
`StatsdHTTPConnection` (class in `django_statsd.urls`), 12  
`StatsdMiddleware` (class in `django_statsd.middleware`), 10  
`StatsdMiddlewareTimer` (class in `django_statsd.middleware`), 11  
`stop()` (`django_statsd.middleware.StatsdMiddleware` class method), 11  
`stop()` (`django_statsd.middleware.Timer` method), 11  
`stop()` (in module `django_statsd.__init__`), 9  
`stop()` (in module `django_statsd.middleware`), 11  
`submit()` (`django_statsd.middleware.Client` method), 10  
`submit()` (`django_statsd.middleware.Counter` method), 10  
`submit()` (`django_statsd.middleware.Timer` method), 11

## T

`Timer` (class in `django_statsd.middleware`), 11  
`TimingCursorWrapper` (class in `django_statsd.database`), 10

## W

`with_()` (in module `django_statsd.__init__`), 9  
`with_()` (in module `django_statsd.middleware`), 11  
`WithTimer` (class in `django_statsd.middleware`), 11  
`wrapper()` (in module `django_statsd.__init__`), 9  
`wrapper()` (in module `django_statsd.middleware`), 11