

---

# **djed.static Documentation**

***Release 0.2***

**Djed developers**

January 08, 2015



<b>1</b>	<b>Contents</b>	<b>3</b>
1.1	Getting Started . . . . .	3
1.2	Local Components . . . . .	3
1.3	Configuration . . . . .	4
1.4	Support and Development . . . . .	4
1.5	Change History . . . . .	4
<b>2</b>	<b>Indices and tables</b>	<b>5</b>



djed.static integrates [BowerStatic](#) into the [Pyramid Web Framework](#). BowerStatic is a WSGI component that can serve static resources from front-end packages (JavaScript, CSS) that you install through the [Bower](#) package manager.



## 1.1 Getting Started

Install the package into your python environment:

```
pip install djed.static
```

Include it in your Pyramid application:

```
config.include('djed.static')
```

Initialize a `bower_components` directory:

```
config.init_bower_components('myapp:static/bower_components')
```

Include desired Bower packages on your page. You can do this in templates or somewhere else in your code:

```
request.include('bootstrap')
```

All required dependencies are also included on the page.

## 1.2 Local Components

If you develop your own front-end-code (so called “local components”), you can add them as follows:

```
config.add_bower_component('myapp:static/my_component', version='1.0.0')
```

You can retrieve the version of your Pyramid application like this:

```
import pkg_resources
```

```
version = pkg_resources.get_distribution('myproject').version
```

You can include local components on page like any other component:

```
request.include('my_component')
```

This includes your front-end-code on the page and all dependencies that are defined in the `bower.json` file.

## 1.3 Configuration

You can configure djed.static via your ini-file:

```
[app:myapp]
djed.static.components_name = lib
...
```

To understand the ini-setting options, let's take a look at the URL structure that is generated by BowerStatic:

```
/bowerstatic/components/jquery/2.1.1/dist/jquery.js
```

Or for local components:

```
/bowerstatic/local/mycomponent/1.0.0/mycomponent.js
```

The setting options allow you to change the first two parts of the URLs:

**djed.static.publisher\_signature** The first part of the components and local URLs.

default: `bowerstatic`

**djed.static.components\_name** The second part of the components URLs.

default: `components`

**djed.static.local\_components\_name** The second part of the local URLs.

default: `local`

## 1.4 Support and Development

If you've got questions, contact the [djedproject mailling list](#).

To report bugs, use the [issue tracker](#).

Check out trunk version via the [Github repository](#):

```
git clone git@github.com:djedproject/djed.static.git
```

## 1.5 Change History

### 1.5.1 0.2 (2015-01-09)

- Added documentation
- Added `ini` setting options

### 1.5.2 0.1 (2015-01-06)

- Initial release



---

## Indices and tables

---

- *genindex*
- *modindex*
- *search*