
eth-rlp Documentation

Release 2.1.0

The Ethereum Foundation

Apr 22, 2024

CONTENTS

| | | |
|----------|---------------------------------------|-----------|
| 1 | Contents | 3 |
| 1.1 | eth_rlp package | 3 |
| 1.1.1 | HashableRLP | 3 |
| 1.2 | Release Notes | 4 |
| 1.2.1 | eth-rlp v2.1.0 (2024-03-19) | 4 |
| 1.2.2 | eth-rlp v2.0.0 (2024-03-04) | 4 |
| 1.2.3 | eth-rlp v1.0.1 (2024-01-25) | 5 |
| 1.2.4 | eth-rlp v1.0.0 (2023-12-06) | 5 |
| 1.2.5 | eth-rlp v0.3.0 (2022-01-19) | 5 |
| 1.2.6 | Eth_Rlp 0.3.0 (2022-01-19) | 5 |
| 1.2.7 | eth-rlp v0.2.0 (2020-09-01) | 6 |
| 1.2.8 | v0.1.2 | 6 |
| 1.2.9 | v0.1.1 | 6 |
| 1.2.10 | v0.1.0 | 6 |
| 1.2.11 | v0.1.0-alpha.2 | 6 |
| 1.2.12 | v0.1.0-alpha.1 | 7 |
| 2 | Indices and tables | 9 |
| | Python Module Index | 11 |
| | Index | 13 |

RLP definitions for common Ethereum objects in Python

Install with

```
pip install eth_rlp
```

Import with

```
from eth_rlp import HashableRLP
```


CONTENTS

1.1 eth_rlp package

1.1.1 HashableRLP

class `eth_rlp.main.HashableRLP(*args, **kwargs)`

An extension of `rlp.Serializable`. In addition to the below functions, the class is iterable.

Use like:

```
class MyRLP(HashableRLP):
    fields = (
        ('name1', rlp.sedes.big_endian_int),
        ('name2', rlp.sedes.binary),
        etc...
    )

my_obj = MyRLP(name2=b'\xff', name1=1)
list(my_obj) == [1, b'\xff']
# note that the iteration order is always in RLP-defined order
```

as_dict() → `Dict[str, Any]`

Convert rlp object to a dict

Returns

mapping of RLP field names to field values

Return type

dict

classmethod **from_bytes**(*serialized_bytes: bytes | bytearray*) → `Self`

Shorthand invocation for `rlp.decode()` using this class.

Parameters

serialized_bytes (*bytes*) – the byte string to decode

Returns

the decoded object

Return type

HashableRLP

classmethod **from_dict**(*field_dict: Dict[str, Any]*) → `Self`

In addition to the standard initialization of.

```
my_obj = MyRLP(name1=1, name2=b'\xff')
```

This method enables initialization with.

```
my_obj = MyRLP.from_dict({'name1': 1, 'name2': b'\xff'})
```

In general, the standard initialization is preferred, but some approaches might favor this API, like when using `toolz.functoolz.pipe()`.

```
return eth_utils.toolz.pipe(  
    my_dict,  
    normalize,  
    validate,  
    MyRLP.from_dict,  
)
```

Parameters

field_dict (*dict*) – the dictionary of values to initialize with

Returns

the new rlp object

Return type

HashableRLP

hash() → *HexBytes*

Returns

the hash of the encoded bytestring

Return type

HexBytes

1.2 Release Notes

1.2.1 eth-rlp v2.1.0 (2024-03-19)

Internal Changes - for eth-rlp Contributors

- Bump to hexbytes>=1.2.0 and add blocklint to linting (#22)

1.2.2 eth-rlp v2.0.0 (2024-03-04)

Breaking Changes

- Bump hexbytes dependency to >=1.0.0 (#21)

Features

- Add Python 3.12 support (#18)

Internal Changes - for eth-rlp Contributors

- Add windows-wheel CI job for py312, set both py311 and py312 to use latest patch version (#20)
- Add `py.typed` file, move misplaced newsfragment, correct py version pins for `typing-extensions` (#21)

1.2.3 eth-rlp v1.0.1 (2024-01-25)

Bugfixes

- Add the missing `typing_extensions` module requirement for Python ≤ 3.11 (#19)

1.2.4 eth-rlp v1.0.0 (2023-12-06)

Breaking Changes

- Drop python 3.7 support (#16)

Features

- Add python 3.11 support (#16)

Internal Changes - for eth-rlp Contributors

- Merge updates from template, including use `pre-commit` for linting, and changing the name of the master branch to `main` (#16)

1.2.5 eth-rlp v0.3.0 (2022-01-19)

1.2.6 Eth_Rlp 0.3.0 (2022-01-19)

Features

- Add support for python 3.8-3.10 (#12)
- Require `eth-utils` $\geq 2.0, < 3$ (#14)

Deprecations and Removals

- Remove support for Python 3.6 (#13)

1.2.7 eth-rlp v0.2.0 (2020-09-01)

Features

- Add support for pyrlp v2.0.0-alpha.1 (as long as you don't use pypy) (#8)

Deprecations and Removals

- Dropped py3.5 support (#7)

Miscellaneous changes

- Merge updates from the project template (#7)

1.2.8 v0.1.2

Released April 25, 2018

- Add `as_dict()` as a shim for joint v0/v1 compatibility

1.2.9 v0.1.1

Released April 25, 2018

- Add support for rlp version 1 (but still backwards-compatible with v0)

1.2.10 v0.1.0

Released Mar 1, 2018

- Marked stable
- Upgraded eth-utils and hexbytes to stable versions
- Add pypy3 support

1.2.11 v0.1.0-alpha.2

Released Jan 30, 2018

- First working version
- Some docs
- New basic tests, that pass

1.2.12 v0.1.0-alpha.1

- Launched repository, claimed names for pip, RTD, github, etc

INDICES AND TABLES

- genindex
- modindex

PYTHON MODULE INDEX

e

`eth_rlp.main`, 3

INDEX

A

`as_dict()` (*eth_rlp.main.HashableRLP method*), 3

E

`eth_rlp.main`
module, 3

F

`from_bytes()` (*eth_rlp.main.HashableRLP class method*), 3

`from_dict()` (*eth_rlp.main.HashableRLP class method*), 3

H

`hash()` (*eth_rlp.main.HashableRLP method*), 4

`HashableRLP` (*class in eth_rlp.main*), 3

M

module
`eth_rlp.main`, 3