

---

# **Hammr Guide**

***Release 3.6***

**UShareSoft**

**Mar 06, 2018**



---

## Contents

---

<b>1</b>	<b>Introduction</b>	<b>3</b>
<b>2</b>	<b>Getting Started</b>	<b>5</b>
2.1	Template Configuration File . . . . .	5
2.2	Installation . . . . .	6
2.3	Launching hammr . . . . .	9
2.4	Creating Your First Machine Image . . . . .	11
<b>3</b>	<b>Authentication</b>	<b>17</b>
3.1	Command-line Parameters . . . . .	17
<b>4</b>	<b>Using a Credential File</b>	<b>19</b>
<b>5</b>	<b>Command-Line</b>	<b>21</b>
5.1	account . . . . .	21
5.2	bundle . . . . .	22
5.3	format . . . . .	22
5.4	platform . . . . .	23
5.5	image . . . . .	23
5.6	os . . . . .	24
5.7	quota . . . . .	24
5.8	scan . . . . .	25
5.9	template . . . . .	26
<b>6</b>	<b>Your Account</b>	<b>29</b>
6.1	Operating Systems . . . . .	29
6.2	Quotas . . . . .	30
6.3	Setting Your Cloud Accounts . . . . .	31
<b>7</b>	<b>Creating and Managing Templates</b>	<b>33</b>
7.1	Creating a Template . . . . .	33
7.2	Validating Your Template . . . . .	34
7.3	Adding Packages to Your Template . . . . .	34
7.4	Searching for Packages . . . . .	35
7.5	Understanding Package Updates . . . . .	35
7.6	Package Dependencies and Updates . . . . .	36
7.7	Using Advanced Partitioning . . . . .	39

<b>8</b>	<b>Building and Publishing Machine Images</b>	<b>47</b>
8.1	Building a Machine Image . . . . .	47
8.2	Listing the Images Generated . . . . .	48
8.3	Publishing a Machine Image . . . . .	48
8.4	Downloading a Machine Image . . . . .	50
<b>9</b>	<b>Importing and Exporting</b>	<b>51</b>
9.1	Exporting a Template . . . . .	51
9.2	Importing a Template . . . . .	52
<b>10</b>	<b>Templates Specification</b>	<b>55</b>
10.1	Stack . . . . .	55
10.2	Builders . . . . .	93
<b>11</b>	<b>Migrating a Live System</b>	<b>153</b>
11.1	Updating a Template Before Migrating . . . . .	154
<b>12</b>	<b>Changelog</b>	<b>157</b>
12.1	hammr-3.6 1.1 (2016-16-12) . . . . .	157
12.2	hammr-3.6 0.1 (2016-07-01) . . . . .	157
12.3	0.2.5.10 (2016-04-29) . . . . .	158
12.4	0.2.5.9 (2015-12-18) . . . . .	158
12.5	0.2.5.8 (2015-11-20) . . . . .	158
12.6	0.2.5.7 (2015-09-21) . . . . .	158
12.7	0.2.5.6 (2015-08-29) . . . . .	159
12.8	0.2.5.5 (2015-08-04) . . . . .	159

This guide contains a complete reference of all features provided by hammr. If you are completely new to hammr, we recommend that you read the [Introduction](#) and walk through the [Getting Started](#) section which guides you through how to create your first template, generate a machine image and publish it to a target cloud environment.

Any questions or comments, please get in touch by using the [mailing list](#).

Contents:



# CHAPTER 1

---

## Introduction

---

Hammr is an open source tool for creating machine images for different environments from a single configuration file, or migrating live systems from one environment to another. Hammr is a lightweight client-side tool based on Python, and can be installed on all major operating systems.

A machine image contains a set of operating system packages and other 3rd party software required to run a particular service. Once a machine image is created, it can be used to provision one or more identical running instances. The format of the machine image varies depending on whether you want to run your service on a physical machine (e.g ISO) a virtual datacenter (e.g OVF for VMware vCenter) or cloud environment (e.g. AMI for Amazon EC2).

Hammr can be used as part of your “DevOps tool chain” and in conjunction with other tools such as Jenkins, Chef, Puppet and SaltStack, allowing you to easily build your machine images and maintain your live running instances. Hammr also has migration capabilities, allowing you to scan a live system, generate a machine image for a different environment as well as export it back to a configuration file for sharing.






Hammr is a client command-line tool for a UForge Server. A UForge server can be deployed onsite in your own datacenter, or provided in SaaS by a growing number of hosting providers and UShareSoft.

If you don't have your own UForge Server, you can get a free online account [here](#) from UShareSoft. Once you have signed up for an account, hammr uses your account to create and manage templates; build machine images; or migrate live systems from one environment to another.

## 2.1 Template Configuration File

All machine images are created from a JSON configuration file, known as the `template`. Templates provide all the information (os packages, software files, configuration) to describe the machine image you wish to build. This template is used by hammr to create the template (in meta-data) into the UForge Server and build one or more identical machine images. These images can then be registered to the respective environment ready for provisioning. Once a template is created in the UForge Server, hammr can be used to track and apply package updates for the template. Hammr can also export a template registered in the UForge Server to an archive that includes all the software and the original template configuration file.



## 2.2 Installation

To use hammr, you require to install it on the machine you wish to run it. Hammr is based on python, and is supported all major operating systems. The easiest way to install hammr is using `pip` the widely used package management system for installing and managing software packages written in python.

### 2.2.1 Installing pip

If you already have pip installed on your system, you can skip this step.

To install or upgrade pip, download [get-pip.py](#)

Now run the command:

```
$ python get-pip.py
```

For more information on installing pip, please refer to the official pip documentation: <http://www.pip-installer.org/en/latest/installing.html>

### 2.2.2 Installing Hammr

Once pip has been installed, you can now install the hammr packages (note, you may have to run this command as `sudo` or `administrator`). Please refer to the installation instructions depending upon your desktop type:

#### For Linux

First of all, you need to install extra packages on your system

Debian based system:

```
$ apt-get install python-dev gcc libxslt1-dev
```

Red-hat based system:

```
$ yum install gcc python-devel libxml2-devel libxslt-devel
```

Now, you are ready to install Hammr:

```
$ easy_install progressbar==2.3
$ pip install hammr-3.6
```

If you already have hammr installed and want to upgrade to the latest version you can run:

```
$ pip install --upgrade hammr
```

#### For Mac

For Mac users, you need to have XCode installed (or any other C compiler).

You can download the latest version of Xcode from the Apple developer website or get it using the Mac App Store

Run the following command:

```
$ xcode-select --install
$ sudo easy_install pip
$ sudo easy_install readline
$ sudo easy_install progressbar==2.3
$ sudo pip install hammr-3.6
```

If you already have hammr installed and want to upgrade to the latest version you can run:

```
$ pip install --upgrade hammr
```

## For Windows

For Windows users, first install Python 2.7, which can be found [here](#). Download the msi file, and install Python 2.7 by executing the msi file. In the instructions below, we assume that the installation path for Python 2.7 is C:\Python27.

Once Python 2.7 is installed, run the command:

```
c:\Python27> .\Scripts\easy_install.exe hammr
```

If your Windows does not have a compilation environment, pycrypto installation may fail. You can install a pycrypto windows binary with this command (change your python version if needed):


```
c:\Python27> .\Scripts\easy_install.exe http://www.voidspace.org.uk/downloads/
↳pycrypto26/pycrypto-2.6.win32-py2.7.exe
```

If you already have hammr installed and want to upgrade to the latest version you can run:

```
c:\Python27\Scripts> easy_install.exe --upgrade hammr
```

Add Python and hammr to system path: Go to “My Computer > (right click) Properties > Advanced System Settings > Environment Variables”

You will get this configuration window:



In System Variables, search for the Path variable and click Edit. Add the following at the end (replace C:\Python27 with your Python installation path if it differs):

```
;C:\Python27;C:\Python27\Scripts;
```

## From Source

Hammr has a dependency to `uforge_python_sdk`. First, you need to install it:

```
$ pip install uforge_python_sdk
```

or download sources from pypi: [https://pypi.python.org/pypi/uforge\\_python\\_sdk](https://pypi.python.org/pypi/uforge_python_sdk)

Go to the source directory where the `setup.py` file is located. To compile and install, run (as sudo):

```
$ python setup.py build; sudo python setup.py install
```

Now clone the Hammr git repository to get all the source files. Next go to the source directory where the `setup.py` file is located. To compile and install, run (as sudo):

```
$ python setup.py build; sudo python setup.py install
```

This will automatically create the hammr executable and install it properly on your system.

## Verifying the Installation

After completing the installation process, to verify that the installation was successful and hammr is available to use, open up a new terminal window and run the command:

```
$ hammr -v
hammr version '0.2.0'
```

## 2.3 Launching hammr

Hammr is a command-line tool, allowing you to specify commands that get executed by hammr. Each command may have one or more sub-commands and optional parameters. Hammr provides inbuilt help. To list all the main options, use the `-h`, `--help` flags or `TAB`.

```
$ hammr -h
usage: hammr [-h] [-a URL] [-u USER] [-p PASSWORD] [-v] [cmds [cmds ...]]
To get more information on a sub-command, use the -h, --help flags or TAB for more_
↳information

$ hammr template -h
=====
Template help
=====
build                | Builds a machine image from the template
clone                | Clones the template. The clone is copying the meta-
↳data of the template
create               | Create a new template and save to the UForge server
delete              | Deletes an existing template
export              | Exports a template by creating an archive (compressed_
↳tar file)
help                 | List available commands with "help" or detailed help_
↳with "help cmd".
import               | Creates a template from an archive
list                 | Displays all the created templates
validate             | Validates the syntax of a template configuration file
```

### 2.3.1 Modes

There are three different modes when launching hammr:

- Classic command-line: used in shell scripts or via a terminal
- Interactive mode: where hammr is launched once, providing you a prompt to execute hammr commands
- Batch mode: allowing hammr to execute a series of commands from a file

When using the classic mode, the command `hammr` is used, followed by a command, sub-command and any options. For example:

```
$ hammr os list --url https://uforge.usharesoft.com/api -u username -p password
```

To enter interactive mode, launch the `hammr` command on its own. This provides a prompt, allowing you to enter commands and sub-commands the same way as you would in classic mode.

To use batch mode, create a file containing the list of commands you wish to launch in sequence and then provide this file to hammr via the batch command. For example if you wanted to list all the operating system available to you in batch mode, firstly create a file with the commands to launch, in this case `os list`:

```
$ vi batchfile
os list
```

Launch hammr providing the batch file:

```
$ hammr batch --file batchfile --url https://uforge.usharesoft.com/api -u username -p password
os list
Getting distributions for [root] ...
```

Id	Name	Version	Architecture	Release Date	Profiles
121	CentOS	6.4	x86_64	2013-03-01 14:01:26	Server No X Server Minimal
87	Ubuntu	12.04	x86_64	2012-02-24 19:04:45	Minimal Desktop Server Minimal

### 2.3.2 Authentication

Communication between hammr and the UForge server is done via HTTPS. To send requests to the UForge server, hammr requires the following information:

- UForge Server URL endpoint
- Your account user name
- Your password

This information can be passed to hammr either from command-line options or from a file.

### 2.3.3 Command-line Parameters

Authentication information can be passed to hammr via command-line options. These options are:

- `-a` or `--url`: the UForge Server URL endpoint. If the URL uses HTTPS, then the connection will be done securely (recommended), otherwise connection will be done via HTTP
- `-u` or `--user`: the user name to use for authentication
- `-p` or `--password`: the password to use for authentication

For example

```
$ hammr os list --url https://uforge.usharesoft.com/api -u username -p password
```

These parameters need to be passed each time you wish to use the command-line.

### 2.3.4 Using a Credential File

Rather than passing the authentication information as part of the command-line, you can instead store this information in a credential file (`credentials.json`) that will be used every time hammr is launched. Hammr searches for this file in a sub-directory named `.hammr` located in the home directory of the user launching hammr.

---

**Note:** If your AppCenter has a self-signed certificate, in order to use hammr with your AppCenter you must use a credentials file.

---

To use a credential file, go to the `.hammr` sub-directory and create the file `credentials.json`.

```
$ cd ~/.hammr
$ vi credentials.json
```

Add the authentication and UForge URL endpoint to this file, using the following format:

```
{
  "user" : "root",
  "password" : "password",
  "url" : "http://10.1.2.24/ufws-3.3",
  "acceptAutoSigned": false
}
```

As this file contains security information, it is recommended to change the permissions on this file, so only you can read or write to it:

```
$ chmod 600 credentials.json
```

Now every time hammr is launched, you no longer need to provide the authentication information as part of the command-line. Hammr will automatically use the information contained in this file.

---

**Note:** The key `acceptAutoSigned` is to accept or not self-signed SSL certificates. Default value is `false`.

---

## 2.4 Creating Your First Machine Image

Now that hammr is installed, let's build our first machine image. Hammr can be used to build machine images containing pretty much any software for many different environments – from a trusty ISO image for physical machine deployments; to virtual and cloud environments.

In this example we are going to create a nginx machine image for Amazon EC2 based on Ubuntu 12.04 (64 bit).

---

**Note:** To go through this tutorial, you are going to need an AWS account. If you don't have one, create a free account [here](#). If you do not wish to create an AWS account, then you can still follow the tutorial, as creating machine images for other environments follows the same basic principles.

---

There are three phases when creating your machine image:

- Defining the contents of the machine image in a template configuration file
- Generating the machine image from the template to the required environment, in our case Amazon EC2.

- Publishing and registering the image in AWS, ready to provision one or more machine instances from the machine image

The rest of this section highlights these steps to create your first machine image.

### 2.4.1 Creating the Template

A configuration file, named the template, defines the contents of the machine image and any credential information required to generate and publish the image to the target environment.

Lets create a template for the nginx machine image. Create a file `nginx-template.json` with the following content:

```
{
  "stack": {
    "name": "nginx",
    "version": "1.0",
    "os": {
      "name": "Ubuntu",
      "version": "12.04",
      "arch": "x86_64",
      "profile": "Minimal",
      "pkgs": [{
        "name": "nginx"
      }]
    },
    "installation": {
      "diskSize": 12288
    }
  }
}
```

A couple of things to point out at this stage. The `stack` section defines the content of the machine you want to build. There are many sub-sections (see the Stack glossary), the:

- `os`: defines the operating system you want to use (in this case Ubuntu 12.04 64bit); the profile type (minimal); and any specific packages to install (nginx)
- `installation`: defines lower level installation parameters. In this example a disk size of 8GB

Now lets create the template using `hammr`. First lets validate that the configuration file does not have any syntax errors or missing mandatory values, by using the command `template validate` and passing in our template file `nginx-template.json`.

```
$ hammr template validate --file nginx-template.json
Validating the template file [/Users/james/nginx-template.json] ...
OK: Syntax of template file [/Users/james/nginx-template.json] is ok
```

Now run the command `template create`.

```
$ hammr template create --file nginx-template.json
Validating the template file [/Users/james/nginx-template.json] ...
OK: Syntax of template file [/Users/james/nginx-template.json] is ok
Creating template from temporary [/var/folders/f6/8kljm7cx3h7fvb26tq18kw4m0000gn/T/
↪hammr-15888/archive.tar.gz] archive ...
100%|#####|
OK: Template create: DONE
Template URI: users/root/appliances/898
Template Id : 898
```



This takes the information in the `stack` section of the template configuration file and stores this in the UForge server. You can display all the templates created by using `template list`.

```
$ hammr template list
# to do, add output:
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Id | Name | Version | OS | Created |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| 683 | nginx | 1.0 | Ubuntu 12.04 x86_64 | 2014-05-02 13:59:25 |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+
Found 1 templates
```

You can create one or more machine images from this template.

## 2.4.2 Building a Machine Image

Once a template has been created, you can create a machine image from it. You can build as many machine images as you like for different platforms and environments. The result will be near identical machine images every time you build from the template. There will be minor differences depending upon the target platform. For example, building an Amazon EC2 image will automatically include the mandatory Amazon libraries required by EC2 to correctly provision an instance, while for OpenStack or VMware vCloud Director, these libraries are not required.

To build a machine image, you need to add the `builders` section to your file. The `builder` section provides mandatory parameters to build (and for some environments register) the machine image. Each target environment requires different `builders` parameters. Refer to the documentation for more information.

For security reasons, it is recommended not to add any cloud account information into the template file. Hammr provides various mechanisms to provide this cloud account information. The method we will use in this tutorial will be to register the cloud account information to the UForge server, then reference the cloud account tag name in the template. So create a file `aws-account.json` and add the following content:

```
{
  "accounts": [
    {
      "type": "Amazon",
      "name": "James AWS Account",
      "accountNumber": "11111-111111-1111",
      "accessKeyId": "myaccesskeyid",
      "secretAccessKeyId": "mysecretaccesskeyid",
      "x509Cert": "/home/developer/UShareSoft/WKS/Hammr/tests/certs/aws/aws.cert.pem",
      "x509PrivateKey": "/home/developer/UShareSoft/WKS/Hammr/tests/certs/aws/aws.key.pem"
    }
  ]
}
```

To create the cloud account, use the command `account create`

```
$ hammr account create --file aws-account.json
Validating the template file [aws-account.json] ...
OK: Syntax of template file [aws-account.json] is ok
```



### 2.4.3 Publishing and Registering the Machine Image

Once the machine image is generated, you can upload and register the machine image to the target environment, in this case AWS.

**Warning:** The image uploaded will be stored in AWS S3 storage. AWS does not charge you for any inbound data, however they will charge you for the storage used.

To get the id of the machine image generated, use the command `image list`

```
$ hammr image list
Getting all images and publications for [root] ...
Images:
```

Id	Name	Version	Rev.	Format	Created	Size
1042	generation	1.0	1	kvm	2014-05-21 09:29:36	0B
	Done					X
981	wordpress	1.0	1	vbox	2014-05-19 17:08:06	0B
	Canceled					X
960	nginx-muppets	1.0	1	vbox	2014-05-15 13:33:43	0B
	Done					X

```
Found 3 images
No publication available
```

Now use the command `publish` to start the registration process

[illegible]

## 2.4.4 Next Steps

And that's it! You have just built and published your first machine image with hammr. You should now have a grasp of the basics of hammr; how to create a template; use it to generate a machine image and publish it to the target environment ready for provisioning.

You should now be ready to start using hammr in real world scenarios. For more detailed information of hammr and the features it provides, please use the documentation section.

Any questions or comments, please get in touch by using the [mailing list](#). If you find any bugs, please post them on the [issue tracker](#) in GitHub.

Communication between hammr and the UForge server is done via HTTPS. To send requests to the UForge server, hammr needs the following information:

- UForge Server URL endpoint
- Your account user name
- Your password

This information can be passed to hammr either from command-line options or from a file.

### 3.1 Command-line Parameters

Authentication information can be passed to hammr via command-line options. These options are:

- `-a` or `--url`: the UForge Server URL endpoint. If the URL uses HTTPS, then the connection will be done securely (recommended), otherwise connection will be done via HTTP
- `-u` or `--user`: the user name to use for authentication
- `-p` or `--password`: the password to use for authentication

For example

```
$ hammr os list --url https://uforge.usharesoft.com/api -u username -p password
```

These parameters need to be passed each time you want to use the command-line.



## CHAPTER 4

---

### Using a Credential File

---

Rather than passing the authentication information as part of the command-line, you can instead store this information in a credential file (`credentials.json`) that will be used every time `hammr` is launched. `hammr` searches for this file in a sub-directory named `.hammr` located in the home directory of the user launching `hammr`.

For more information, refer to *Using a Credential File*.





# CHAPTER 5

---

## Command-Line

---

Hammr is launched by using the main command-line tool `hammr`. The `hammr` tool can be launched with other commands, sub-commands and options. The usage for the tool, can be shown by running `hammr` with the help options `-h` or `--help`:

```
$ hammr --help
usage: hammr [-h] [-a URL] [-u USER] [-p PASSWORD] [-v] [cmds [cmds ...]]
```

The global options are:

- `-h, --help`: displays the usage
- `-a URL, --url URL`: the UForge server URL endpoint to use
- `-u USER, --user USER`: the user name used to authenticate to the UForge server
- `-p PASSWORD, --password PASSWORD`: the password used to authenticate to the UForge server
- `-v`: displays the current version of the `hammr` tool

Hammr communicates with a UForge server instance, requiring authentication information as part of this authentication. The authentication information may be passed to `hammr` via the global options, however, there are other ways to pass this information. For more information, please refer to [Authentication](#) section of the documentation.

Below provides a list of the available commands:

## 5.1 account

Manages all of your different cloud accounts used when either building or publishing machine images. The usage is:

```
usage: hammr account [sub-command] [options]
```

### 5.1.1 Sub Commands

#### **create sub-command**

Creates a new cloud account. The options are:

- `--file` (mandatory): json file providing the cloud account parameters

#### **delete sub-command**

Deletes an existing cloud account. The options are:

- `--id` (mandatory): the ID of the cloud account to delete

#### **list sub-command**

Displays all the cloud accounts for the user.

## 5.2 bundle

Manages all the bundles that have been registered in UForge. A bundle is group of software that is uploaded during the creation of a template. The usage is:

```
usage: hammr bundle [sub-command] [options]
```

### 5.2.1 Sub Commands

#### **delete sub-command**

Deletes an existing bundle. The options are:

- `--id` (mandatory): the ID of the bundle to delete

#### **list sub-command**

Lists all the bundles that have been registered in the UForge server.

## 5.3 format

Displays all the machine image formats the user has access to when building a machine image. The usage is:

```
usage: hammr format [sub-command]
```

### 5.3.1 Sub Commands

#### **list sub-command**

Displays all the machine image formats for the user.

## 5.4 platform

Displays all the platform types the user has access to for creating cloud accounts. The usage is:

```
usage: hammr platform [sub-command]
```

### 5.4.1 Sub Commands

#### **list sub-command**

Displays all the platform types available for the user.

## 5.5 image

Manages all of the machine images you have built and/or published. The usage is:

```
usage: hammr image [sub-command] [options]
```

### 5.5.1 Sub Commands

#### **cancel sub-command**

Cancels a machine image build or publish. The options are:

- `--id` (mandatory): the ID of the machine image to cancel

#### **delete sub-command**

Deletes a machine image or publish information. The options are:

- `--id` (mandatory): the ID of the machine image to delete

#### **download sub-command**

Downloads a machine image to the local filesystem. The options are:

- `--id` (mandatory): the ID of the machine image to download
- `--file` (mandatory): the pathname where to store the machine image

#### **list sub-command**

Displays all the machine images built and publish information of those machine images to their respective target platforms.

### **publish sub-command**

Publish (upload and register) a built machine image to a target environment. The options are:

- **--file** (mandatory): json file providing the cloud account parameters required for upload and registration

## 5.6 os

Displays all the operating systems available to use when creating templates. The usage is:

```
usage: hammr os [sub-command] [options]
```

### 5.6.1 Sub Commands

#### **list sub-command**

Displays all the operating systems available to use by the user.

#### **search sub-command**

Operating System package search.

- **--id** (mandatory): the ID of the OS
- **--pkg** (mandatory): **Regular expression of the package:**
  - “string” : search all packages wich contains “string”
  - “^string”: search all packages wich start with “string”
  - “string\$”: search all packages wich end with “string”

## 5.7 quota

Displays the current user quota for the user. This includes all of your different cloud accounts used when either building or publishing machine images. The usage is:

```
usage: hammr quota [sub-command]
```

### 5.7.1 Sub Commands

#### **list sub-command**

Displays the user’s quota information.

## 5.8 scan

Manages all the scans executed on live systems. The usage is:

```
usage: hammr scan [sub-command] [options]
```

### 5.8.1 Sub Commands

#### **build sub-command**

Builds a machine image from a scan. The options are:

- `--id` (mandatory): the ID of the scan to generate the machine image from
- `--file` (mandatory): json file providing the builder parameters

#### **delete sub-command**

Deletes an existing scan. The options are:

- `--id` (mandatory): the ID of the scan to delete

#### **import sub-command**

Imports (or transforms) the scan to a template.

- `--id` (mandatory): the ID of the scan to import
- `--name` (mandatory): the name to use for the template created from the scan
- `--version` (mandatory): the version to use for the template created from the scan

#### **list sub-command**

Displays all the scans for the user.

#### **run sub-command**

Executes a deep scan of a running system.

- `--ip` (mandatory): the IP address or fully qualified hostname of the running system
- `--scan-login` (mandatory): the root user name (normally root)
- `--name` (mandatory): the scan name to use when creating the scan meta-data
- `--scan-password` (optional): the root password to authenticate to the running system
- `--dir` (optional): the directory where to install the uforge-scan.bin binary used to execute the deep scan
- `--exclude` (optional): a list of directories or files to exclude during the deep scan

## 5.9 template

Manages all the templates created by the user. The usage is:

```
usage: hammr template [sub-command] [options]
```

### 5.9.1 Sub Commands

#### **build sub-command**

Builds a machine image from the template. The options are:

- `--file` (mandatory): json file providing the builder parameters

#### **clone sub-command**

Clones the template. The clone is copying the meta-data of the template. The options are:

- `--id` (mandatory): the ID of the template to clone
- `--name` (mandatory): the name to use for the new cloned template
- `--version` (mandatory): the version to use for the cloned template

#### **create sub-command**

Creates a new template and saves it to the UForge server. Hammr creates a tar.gz archive which includes the .json file and binaries and imports it to UForge. The options are:

- `--file` (mandatory): json file containing the template content
- `--archive-path` (optional): path of where to store the archive (tar.gz) of the created template. If provided, hammr creates an archive of the created template, equivalent to running `template export`
- `--force` (optional): force template creation (delete template/bundle if already exist)
- `--rbundles` (optional): if a bundle already exists, use it in the new template. Warning: this option ignore the content of the bundle described in the template file
- `--usemajor` (optional): use distribution major version if exit

#### **delete sub-command**

Deletes an existing template. The options are:

- `--id` (mandatory): the ID of the template to delete

#### **export sub-command**

Exports a template by creating an archive (compressed tar file) that includes the json template configuration file. The options are:

- `--id` (mandatory): the ID of the template to export
- `--file` (optional): destination path where to store the template configuration file on the local filesystem

**import sub-command**

Creates a template from an archive. The archive file must be a tar.gz (which includes the .json and binaries). The options are:

- `--file` (mandatory): the path of the archive
- `--force` (optional): force template creation (delete template/bundle if already exist)
- `--usemajor` (optional): use distribution major version if exit

**list sub-command**

Displays all the created templates.

**validate sub-command**

Validates the syntax of a template configuration file. The options are:

- `--file` (mandatory): the json template configuration file





# CHAPTER 6

## Your Account

As you discovered in the Introduction, `hammr` allows you to communicate with and use the UForge server to create, build and publish machine images. Since you are communicating with UForge, a number of actions are managed by your UForge Account, such as the operating systems you have access to, any quotas set (on the number of images you can create, for example), as well as managing your cloud account. The following sections will help you use `hammr` to access information from your UForge cloud account.

## 6.1 Operating Systems

`Hammr` allows you to create machine images for a number of OSes. The type of OS you want to use needs to be defined in the `os` section of the configuration file, as described in.

For a list of the OSes that can be added to your template, run `os list`, for example

```
$ hammr os list
Getting distributions for [root] ...
+-----+-----+-----+-----+-----+-----+
↪-----+
| Id | Name | Version | Architecture | Release Date |
↪Profiles |
+-----+-----+-----+-----+-----+-----+-----+
| 120 | CentOS | 6 | x86_64 | 2011-07-03 02:06:43 | Server |
↪ | | | | | Minimal |
↪ | | | | | Minimal Desktop |
↪ | | | | |
+-----+-----+-----+-----+-----+-----+
↪-----+
| 121 | CentOS | 6 | i386 | 2011-07-03 04:02:09 | Minimal |
↪ | | | | | Server |
↪ | | | | | Minimal Desktop |
↪ | | | | |
```

+-----+						
+-----+						
122	CentOS	5	x86_64	2008-06-19 13:56:25	Minimal Desktop	U
					Minimal	U
					Server	U
+-----+						
+-----+						
123	CentOS	5	i386	2008-06-19 14:01:21	Minimal	U
					Minimal Desktop	U
					Server	U
+-----+						
+-----+						
42	Debian	6	x86_64	2010-04-20 00:18:34	Minimal Desktop	U
					Server	U
					Minimal	U
+-----+						
+-----+						
125	Debian	7	x86_64	2012-11-05 11:17:46	Minimal Desktop	U
					Server	U
					Minimal	U
+-----+						
+-----+						
124	Debian	7	i386	2012-11-05 11:17:46	Server	U
					Minimal	U
					Minimal Desktop	U
+-----+						
+-----+						
Found 7 distributions						

## 6.2 Quotas

There are a number of quotas that can be set on a UForge account. For example, a free account has the following limitations:

Quotas can be set for the following:

- Disk usage: diskusage in bytes (includes storage of bundle uploads, bootscripts, image generations, scans)
- Templates: number of templates created
- Generations: number of machine images generated

- Scans: number of scans for migration

To view the quotas that have been set on your account, run `quota list`:

```
$ hammr quota list
Getting quotas for [root] ...
Scans (25) -----UNLIMITED-----
Templates (26) -----UNLIMITED-----
Generations (72/100) |||||-----
Disk usage (30GB) -----UNLIMITED-----
```

The output not only lists any quotas that are set, but it also shows you the limit you are at, even if your account is set to unlimited.

## 6.3 Setting Your Cloud Accounts

For security reasons, it is recommended not to add any cloud account information into the template file. Hammr allows you to register your cloud account information to the UForge server, then reference the cloud account tag name in the template.

To do this, you need to create a JSON file which contains all the necessary cloud credentials. This will depend on your cloud type. For more information, refer to the [Builders](#) section of the documentation.

Once this file is ready, you create the cloud account on UForge by running the command `account create`.

```
$ hammr account create --file aws-account.json
Validating the template file [aws-account.json] ...
OK: Syntax of template file [aws-account.json] is ok
Create account for 'ami'...
OK: Account create successfully for [ami]
```

Once the cloud account is created, you can safely reference the cloud credentials in all the template files by using the account name.



---

## Creating and Managing Templates

---

If you have read the Introduction and gone through the step by step tutorial in the Getting Started section, you now have an operational configuration template and have built an image. However, the example probably doesn't match with the type of machine image you want to create. This section will help you with the basics for creating and managing your template, including how to manage package updates.

You should refer to the section for all the possible parameters you can add to define your template.

### 7.1 Creating a Template

A template is a configuration file which defines the machine image you want to build. The format of this file is simple JSON. Note that the template can be saved locally or stored on a server, in which case hammr will access it via a URL. For security reasons we recommend that you save your UForge credentials in a separate credentials file, saved at the same location as your template.

The mandatory values when creating a template are:

- `name`: the name of the template to create. You can easily make the name unique by using the timestamp keyword (surrounded by curly brackets).
- `version`: the version of the template.
- `os`: the operating system details to use in your images. You must include the OS family name, version and architecture type. For more information regarding OS and package parameters, see [Adding Packages to Your Template](#)

For more details about the various parameters you can set in your template to define the machine image you want to create, refer to the [Templates Specification](#) section.

The following is an example of the minimum information needed in your configuration file to define a template. It includes the name, version, a few installation parameter and the OS. This example describes a CentOS 6.4 32-bit template.

```
{  
  "stack" : {
```

```
"name" : "myTemplate",
"version" : "1.0",
"installation" : {
  "internetSettings" : "dhcp",
  "diskSize" : 12288,
  "swapSize" : 512
},
"os" : {
  "name" : "CentOS",
  "version" : "6.4",
  "arch" : "x86_64",
  "profile" : "Minimal"
}
}
```

Once you have written and saved this minimal template you can then create the template using `template create`:

```
$ hammr template create --file <blueprint>.json
Validating the template file [/Users/james/nginx-template.json] ...
OK: Syntax of template file [/Users/james/nginx-template.json] is ok
Creating template from temporary [/var/folders/f6/8kljm7cx3h7fvb26tq18kw4m0000gn/T/
↳hammr-15888/archive.tar.gz] archive ...
100%|#####|
OK: Template create: DONE
Template URI: users/root/appliances/898
Template Id : 898
```

## 7.2 Validating Your Template

Once you have created and modified your template file, it is best practice to validate your template before you build or publish it. In order to check that your template does not have any syntax errors or missing mandatory values, run the command `validate`.

```
$ hammr template validate --file <path/filename>.json
Validating the template file [/Users/james/nginx-template.json] ...
OK: Syntax of template file [/Users/james/nginx-template.json] is ok
```

If there are any errors, this command will tell you.

## 7.3 Adding Packages to Your Template

When defining your machine image you set the OS and profile. UForge automatically pulls in all the necessary packages required for the chosen OS. You do not need to list them separately. However, you may want to add other packages to your machine image. These additional packages are listed in the `pkgs` section of your template.

---

**Note:** If the packages you choose to add to your template have any dependencies, all the required packages will be added automatically. You do not have to search and list all the dependencies in your template.

---

The following is a basic example for a CentOS 6.4 32-bit template with package for `iotop` added.

```
{
  "os" : {
    "name" : "CentOS",
    "version" : "6.4",
    "arch" : "x86_64",
    "profile" : "Minimal"
    "pkgs" : {
      "name" : "iotop"
    }
  }
}
```

## 7.4 Searching for Packages

You can search for the available packages as follows:

```
$ hammr os search
```

When running a search you will need to specify the OS id and a search string.

```
$ hammr os search --id 121 --pkg ntpdate
Search package 'ntpdate' ...
for OS 'CentOS', version 6
```

Name	Version	Arch	Release	Build date	Size
ntpdate	4.2.4p8	i686	3.el6.centos	2013-02-22 11:22:14	56K
ntpdate	4.2.4p8	i686	2.el6.centos	2011-11-29 12:06:40	56K
ntpdate	4.2.4p8	i686	2.el6	2010-08-25 01:51:27	56K
ntpdate	4.2.6p5	i686	1.el6.centos	2013-11-23 06:20:19	74K

```
Found 4 packages
```

To get the OS id, list the OS information by running:

```
$ hammr os list
```

## 7.5 Understanding Package Updates

A more complete example for adding CentOS is provided below. You will notice the following optional information has been added:

- `updateTo`: This is the date up until which the packages should be updated
- `profile`: The OS profile. The options are listed under `os list`

```
{
  "os" : {
    "name" : "CentOS",
```

```
"version" : "6.4",
"arch" : "x86_64",
"updateTo" : "01-30-2014",
"profile" : "Minimal",
"pkgs" : [ {
  "name" : "iotop"
},
{
  "name" : "httpd",
  "version" : "2.2.15",
  "release" : "28.el6.centos",
  "arch" : "x86_64"
}]
}
```

In the example above you can see that for the package `httpd` a specific version and release are specified. When no version or release is specified, the latest release is used.

## 7.6 Package Dependencies and Updates

Hammr via the build mechanism calculates determines the complete list packages that require to be installed by checking the dependencies of the packages you have listed in the `os` sub-section of the stack (via the profile and pkgs) and any native packages listed in a `bundle`. Hammr also provides a mechanism to track any available updates on these packages and allow you to update or roll-back your template.

### 7.6.1 What is a Dependency

A dependency is a piece of information in a software package that describes which other packages it requires to function correctly. Many packages require operating system libraries as they provide common services that just about every program uses (filesystem, network, memory etc).

For example, network applications typically depend on lower-level networking libraries provided by the operating system. The principle behind package dependencies is to share software, allowing software developers to write and maintain less code at a higher quality. Operating systems have thousands of packages.

In the world of virtualization and cloud computing, it is becoming imperative to strip down the number of operating system packages to just the required packages to run a particular application. This process, known as JeOS (pronounced “juice”) standing for “Just Enough Operating System” is a very painful manual process. So much so that many operating system vendors now supply a core operating system ISO with the minimum set of packages required to boot the system. The fun then begins as you manually install only the packages (and their dependencies) required to run your application.

### 7.6.2 Calculating Package Dependencies

Package dependency checking occurs when you build (or generating) a new machine image. During the first phase of generation, the backend UForge Server calculates automatically all the dependencies of each package in the `os` section (profile and pkgs list) as well as any packages contained elsewhere in your stack (native packages declared in one or more bundles).


All missing packages are automatically added. For each package added, this package’s dependencies are also checked. This process continues until all the dependencies have been met. The end result is a complete dependency tree of all the packages you require to run your application. All these packages are added to the machine image. Consequently



don't be surprised if the number of packages that are actually installed are larger than the packages lists in the stack section of the template.

Each package has meta-data on what the package requires (that is, what the package depends on) and what it provides in terms of functionality. This meta-data varies on the package type (RPM, DEB etc).

The dependency calculation is done using a specific moment in time. This date is determined by the `updateTo` key in your stack. If this key does not exist, then the date the template was created (via the command `template create`) is used. Chosen package versions and dependencies are calculated by ensuring that they are equal to or less than this date. Let's take an example. Imagine you create a new stack on June 17th 2013, 17:00 GMT+1, and you choose package A, B and C. Packages A, B and C may have more than one version (updates added to the repository due to bug fixing and or new features). The versions displayed for A, B and C will be dates of each of these packages closest (but inferior) to our date.




### 7.6.3 Package Updates

As you probably know, packages evolve as bugs are fixed and new features are added. These new packages become available in the operating system repository. The UForge Server uses an internal mechanism to check for any new package update available in the repository, and, if found, adds the meta-data of this package to its own database. Using this process, the UForge Server builds a history of the operating system, as it keeps references to the old packages that are being replaced by the update.

These updates do not get taken into account for your current template when generating a new image. By calculating packages by the same date ensures when you build your machine image, the same image is generated time after time. This is due to always using the `updateTo` date (or the creation date) of the template in question.

Ok great, but what if you actually wanted to include these updates in the next generation? Well, it's a simple matter of updating the `updateTo` key of the stack section.

```
{
  "stack": {
    "name": "CentOS Base Template",
    "version": "6.4",
    "description": "This is a CentOS core template.",
    "os": {
      "name": "CentOS",
      "version": "6.4",
      "arch": "x86_64",
      "profile": "Minimal",
      "updateTo": "2013-06-15"
    }
  }
}
```



In this case, UForge will notify you that three updates are available. Note, that for package B even if there is an intermediary package (version 7.3), only the last one is taken into account.

### 7.6.4 Making a Package “Sticky”

Being able to roll-forward or roll-back the packages is all well and good, but what if we wanted to force a particular version of a package to be part of the machine image?

Due to the current package version calculation being based on a particular date it is impossible to specify a particular package version to be part of the generation, as depending upon the build date of the package, potentially an earlier or more up to date version of the package may be chosen instead. To get around this issue, Hammr provides a mechanism to enforce a particular package version. This is known as making a package “sticky”. To do this, specify the fullname of the package, or its version, revision and architecture.

For example:

```
{
  "stack": {
    "name": "CentOS Base Template",
    "version": "6.4",
    "description": "This is a CentOS core template.",
    "os": {
      "name": "CentOS",
      "version": "6.4",
      "arch": "x86_64",
      "profile": "Minimal",
      "updateTo": "2013-06-15",
      "pkgs": [
        {
          "name": "php",
          "version": "5.5.3",
          "release": "23.el6_4",
          "arch": "i686"
        },
        {
          "name": "php-common",
          "fullName": "php-common-5.5.3-23.el6_4-i686.rpm"
        }
      ]
    }
  }
}
```

## 7.7 Using Advanced Partitioning

Hammr supports the ability to describe partitioning schemas as part of the stack used to build machine images. Partitioning is the act of dividing one or more physical disks into logical sections with the goal to treat each physical disk drive as if it were multiple disks.

Partitioning is used frequently in production systems. Benefits include:

- Isolating data from programs
- Keeping frequently used programs and data near each other
- Having cache and log files separate from other files. These can change size dynamically and rapidly, potentially making a file system full.
- Having a separate area for operating system virtual memory swapping/paging

**Warning:** Some cloud platforms do not support all the features of partitioning, or limit the number of partitions you may have in your machine image. When building a machine image for a particular cloud platform, hammr will return an error if the partitioning table in the stack if the partitioning setup is not supported. This helps you save time and effort down the road when an instance of the machine image does not boot.

The rest of this section, provides examples of:

### 7.7.1 Disks

The first thing a partitioning table needs is to declare one or more disks that will be used to partition. Each disk declared in the partitioning table has the name `sd` followed by a letter, starting at `a`, namely: 1st disk `sda`, 2nd disk `sdb` and so on. A disk may have one of two types, either `MSDOS` or `LVM` and provide a total disk size available. `LVM` disks cannot have any physical partitions, however can be used in logical volumes (we will touch on this subject later).

The example below describes 1 disk of 20GB.

```
{
  "installation": {
    "partitioning": {
      "disks": [
        {
          "name": "sda",
          "type": "msdos",
          "size": 20480
        }
      ]
    }
  }
}
```

#### Example

The following example describes 2 disks of 20GB each.

```
{
  "installation": {
    "partitioning": {
      "disks": [
        {
          "name": "sda",
          "type": "msdos",
          "size": 20480
        },
        {
          "name": "sdb",
          "type": "msdos",
          "size": 20480
        }
      ]
    }
  }
}
```

### 7.7.2 Physical Partitions

Each disk declared may be partitioned, i.e. the act of dividing the physical disk into logical sections with the goal to treat one physical disk drive as if it were multiple disks. These are called physical partitions.

---

**Note:** A disk may have a maximum of 4 physical partitions.

---

Each physical partition has a unique number: 1,2,3 and 4; declare a filesystem type and size. All filesystem types with the exception of `lvm2`, `extended` and `linux-swap` require a mount point. LVM physical partitions are used in logical volumes (which will be covered later).

### Example

The following example shows 3 physical partitions of a disk: `/boot`, `swap`, and `/space`.



```
{
  "partitioning": {
    "disks": [
      {
        "name": "sda",
        "type": "msdos",
        "size": 20480,
        "partitions": [
          {
            "number": 1,
            "fstype": "ext3",
            "size": 2048,
            "mountPoint": "/boot"
          },
          {
            "number": 2,
            "fstype": "linux-swap",
            "size": 1024
          },
          {
            "number": 3,
            "fstype": "ext3",
            "size": 17408,
            "label": "space",
            "mountPoint": "/space"
          }
        ]
      }
    ]
  }
}
```

**Note:** In a partitioning table, at least one partition must be the `/boot` partition. In the above example this is one of the physical partitions. Furthermore, the sum of the physical partition sizes must be smaller or equal to the disk size.

### 7.7.3 Logical Partitions

Due to the restriction of only having 4 physical partitions for disk, you can further partition a physical partition. This is known as logical partitioning. To partition a physical partition, use the filesystem type `extended`.

**Note:** You can only use the `extended` filesystem ONCE for a disk i.e. you can only partition one physical partition in a disk. When using extended you cannot declare a mount point or label. These will be ignored by hammr.

Like a physical partition, each logical partition has a unique number starting at 5: 5,6,7,8 etc; declare a filesystem type and size. You cannot further partition a logical partition (extended filesystem type cannot be used). There is no limit to the number of logical partitions you may have, however the sum of the logical partitions cannot exceed the size of the physical partition.

## Example

The following example shows 3 physical partitions of a disk, where the last physical partition has 3 logical partitions : `/space`, `/home` and `/tmp`.



```
{
  "partitioning": {
    "disks": [
      {
        "name": "sda",
        "type": "msdos",
        "size": 20480,
        "partitions": [
          {
            "number": 1,
            "fstype": "ext3",
            "size": 2048,
            "mountPoint": "/boot"
          },
          {
            "number": 2,
            "fstype": "linux-swap",
            "size": 1024
          },
          {
            "number": 3,
            "fstype": "Extended",
            "size": 17408,
            "partitions": [
              {
                "number": 5,
                "fstype": "ext3",
                "size": 8192,
                "mountPoint": "/space",
                "label": "space"
              }
            ]
          }
        ]
      }
    ]
  }
}
```

```

    },
    {
      "number": 6,
      "fstype": "ext3",
      "size": 8192,
      "mountPoint": "/home",
      "label": "home"
    },
    {
      "number": 7,
      "fstype": "ext3",
      "size": 1024,
      "mountPoint": "/tmp",
      "label": "tmp"
    }
  ]
}

```

### 7.7.4 Growable Partitions

Physical and Logical Partitions can be marked as growable by using the `grow` flag. This declares that the particular partition takes all remaining disk space available after the other partition sizes of been satisfied.

You can only declare one physical partition to be growable in a disk, and one logical partition to be growable for a physical partition.

#### Example

In this example we mark the “space” physical partition as growable, i.e. the “space” partition takes up the rest of the disk (rather than us having to calculate the space left after creating the first two partitions). We must specify though a size for the “space” partition (the minimum partition size is 64MB).



```

{
  "partitioning": {
    "disks": [
      {
        "name": "sda",
        "type": "msdos",
        "size": 20480,
        "partitions": [
          {
            "number": 1,
            "fstype": "ext3",

```

```
        "size": 2048,  
        "mountPoint": "/boot"  
      },  
      {  
        "number": 2,  
        "fstype": "linux-swapon",  
        "size": 1024  
      },  
      {  
        "number": 3,  
        "fstype": "ext3",  
        "size": 64,  
        "grow": true,  
        "label": "space",  
        "mountPoint": "/space"  
      }  
    ]  
  }  
]  
}
```

### 7.7.5 Volume Groups and Logical Volumes

Volume groups and logical volumes allows more creative and flexible partitioning schemas to be created than conventional partitioning schemas we have already discussed.

A volume group allows us to gather disks, physical and logical partitions into a single logical pool of storage. This pool of storage can then be partitioned (like a disk) by using a logical volume.

Only disks that have the type `lvm`, and physical partitions or logical partitions that have filesystem types `lvm2` can be grouped together in a volume group.


---

**Note:** Once a physical or logical partition is grouped together into a volume group, they cannot be declared in another volume group.

---

In this example, an extended physical partition that has two logical partitions that have `lvm` filesystems; and a disk of type `lvm` are pooled together via a volume group `grp1`. A logical volume is used to partition further this volume group.





```
{
  "partitioning": {
    "disks": [
      {
        "name": "sda",
        "type": "msdos",
        "size": 20480,
        "partitions": [
          {
            "number": 1,
            "fstype": "ext3",
            "mountPoint": "/boot",
            "size": 1024
          },
          {
            "number": 2,
            "fstype": "linux-swaps",
            "size": 1024
          },
          {
            "number": 3,
            "fstype": "extended",
            "size": 18432,
            "partitions": [
              {
                "number": 5,
                "fstype": "lvm2",
                "size": 9216
              },
              {
                "number": 6,
                "fstype": "lvm2",
                "size": 9216
              }
            ]
          }
        ]
      }
    ]
  }
}
```

```
    },
    {
      "name": "sdb",
      "type": "lvm",
      "size": 122880
    }
  ],
  "volumeGroups": [
    {
      "name": "grp1",
      "physicalVolumes": [
        {
          "name": "sda5"
        },
        {
          "name": "sda6"
        },
        {
          "name": "sdb"
        }
      ]
    }
  ],
  "logicalVolumes": [
    {
      "name": "vol1",
      "vg_name": "grp1",
      "fstype": "ext3",
      "mountPoint": "/home",
      "size": 4096
    },
    {
      "name": "vol2",
      "vg_name": "grp1",
      "fstype": "ext3",
      "mountPoint": "/space",
      "size": 64,
      "grow": true
    }
  ]
}
```

## Building and Publishing Machine Images

Templates allow you to generate and publish identical machine images for physical, virtual and cloud environments. The rest of this section highlights how to build, publish and manage machine images with `hammer`.

## 8.1 Building a Machine Image

In order to generate a machine image based on the template you created, you must update the template with the information for each type of image you want to generate (physical, virtual or cloud). This is done in the `builders` section of the configuration file.

The parameters you need to enter will depend on the type of image you want to generate. For a complete list of the mandatory and optional fields, see the builders list. Note that you can define several types of images in the same template.

When you run the `hammr` command to generate the images, all image formats defined in the `builders` section will be built at the same time.

Once the template is updated, build the images by running the command `template build`:

[illegible]

**Note:** This may take some time. A progress report is be shown.

## 8.2 Listing the Images Generated

You can check that the machine images have been created by running `image list`:

```
$ hammr image list
Getting all images and publications for [root] ...
Images:
+-----+-----+-----+-----+-----+-----+-----+-----+
| Id | Name | Version | Rev. | Format | Created | Size | X |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 1042 | generation | 1.0 | 1 | kvm | 2014-05-21 09:29:36 | 0B | X |
| | Done | | | | | | |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 981 | wordpress | 1.0 | 1 | vbox | 2014-05-19 17:08:06 | 0B | X |
| | Canceled | | | | | | |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 960 | nginx-muppets | 1.0 | 1 | vbox | 2014-05-15 13:33:43 | 0B | X |
| | Done | | | | | | |
+-----+-----+-----+-----+-----+-----+-----+-----+
Found 3 images
No publication available
```

The table lists the image ID number, which you will need to publish the image, the name, version, revision (this is automatically increased everytime you modify the template and run `template build`), the format of the image, when it was created (date and time of the creation), if the image is compressed (not possible for all formats) and the status.

## 8.3 Publishing a Machine Image

In order to publish a machine image of the template you created, you must make sure that the `builders` section of the template has the necessary info for each machine image you want to publish to. This includes defining the machine image you want to build as well the information for the cloud platform you want to publish you.

You will also need to set the information for your cloud account. We recommend that this information not be included in the template file, but rather set as a value that hammr will access in a separate read-only file. For more information on creating a credential file with your cloud account information refer to the details in [Setting Your Cloud Accounts](#).

The following is an example of the `builders` section illustrating the publication to OpenStack. Note that you can incorporate details for several cloud platforms in the same configuration file. For details of the required parameters for each of the image types, refer to the documentation.

```
{
  "builders": [
    {
      "type": "openstack",
      "hardwareSettings": {
        "memory": 1024
      },
      "installation": {
```

```

    "diskSize": 2000
  },
  "account": "Openstack OW2",
  "tenant": "opencloudware",
  "imageName": "openstack-test",
  "publicImage": "no",
  "endpoint": "http://ow2-04.xsalto.net:9292/v1",
  "keystoneEndpoint": "http://ow2-04.xsalto.net:5000/v2.0",
  "username": "test",
  "password": "password"
}
]
}

```

Publish the image(s) by running the command `image publish`:

[illegible]

**Note:** This may take some time. A progress report will be shown.

To get the id of the machine image generated, use the command `image list`:

```
$ hammer image list
Getting all images and publications for [root] ...
Images:
```

Id	Name	Version	Rev.	Format	Created	Size
1042	generation   Done	1.0	1	kvm	2014-05-21 09:29:36	0B X
1049	generation   In progress (2%)	1.0	1	ovf	2014-05-21 12:17:21	0B X
981	wordpress   Canceled	1.0	1	vbox	2014-05-19 17:08:06	0B X
960	nginx-muppets   Done	1.0	1	vbox	2014-05-15 13:33:43	0B X

```
Found 4 images
No publication available
```

## 8.4 Downloading a Machine Image

You can only download images that have been compressed. You will need the image `Id` number in order to download it as follows. You must also set the location where the image should be saved. To download a machine image, use the command `image download`.

[illegible]

---

## Importing and Exporting

---

Hammr has a notion of importing and exporting templates. After creating a template from a JSON configuration file; this template can be exported as an archive. The archive will include the template JSON file as well as any bundled software that was initially uploaded as part of the template creation.

The archive can then be used to import the template into another UForge Server instance.

The `stack` section of a template can include bundles of software and configuration information. This information may be stored locally on a filesystem or available via URLs. In some cases, when another user creates a template from the same template JSON file, the custom software and/or configuration files may not be reachable or present. By creating an archive (using export) ensure that all relevant software for creating the template is available.

### 9.1 Exporting a Template

To illustrate exporting a template, let's start from scratch. We will create a template, get the ID and export it with `hammr`.

So first let's create a new template with the JSON file `centoscore-template.json`.

```
{
  "stack" : {
    "name" : "CentOS Core",
    "version" : "6.4",
    "os" : {
      "name" : "CentOS",
      "version" : "6.4",
      "arch" : "x86_64",
      "profile" : "Minimal"
    },
  },
  "config" : [ {
    "name" : "firstboot1.sh",
    "source" : "http://myconfig.site.com/config/firstboot1.sh",
    "type" : "bootscript",
    "frequency" : "firstboot"
  } ]
}
```

```

    }, {
      "name" : "firstboot0.sh",
      "source" : "http://myconfig.site.com/config/firstboot1.sh",
      "type" : "bootscript",
      "frequency" : "firstboot"
    } ]
  }
}

```

```
$ hammr template create --file centoscore-template.json
```

Now that the template is created we need to get the Id of the template you want to export. To do so, list the templates with the command `template list`:

```
$ hammr template list
```

Id	Name	Version	OS	Created
669	CentOS Core	1.0	CentOS 6.4 x86_64	2014-04-25

In this case the Id is 669. To export the template, run the command `template export`:

```
$ hammr template export --id 669 --file /tmp/centos-core-archive.tar.gz
Exporting template with id [669] :
100%|#####|
#|
Downloading archive...
OK: Download complete of file [/tmp/centos-core-archive.tar.gz]
```

Now if you uncompress the archive, you will find a file `template.json`, which is the template JSON configuration file and a sub-directory `config` containing the two boot scripts.

If you open the `template.json` file, then you will notice that there is additional information added, including:

- `pkgs`: this contains all the packages that are added by the os profile `Minimal`
- `updateTo`: this is the date that the template initially created. This ensure that if you re-import this template (the creation date might be different) and build a machine image, the machine image will be identical to any machine image built from the original template
- `installation`: adds the default installation parameters.

## 9.2 Importing a Template

You can import a template based on a `tar.gz` archive file by using the command `template import`. This will import the archive, which contains the `.json` and binaries of the template.

```
$ hammr template import --file /tmp/centos-core-archive.tar.gz
Importing template from [/tmp/centos-core-archive.tar.gz] archive ...
100%|#####|
#|
```



```
OK: Template import: DONE  
Template URI: users/root/appliances/22  
Template Id : 22
```



---

## Templates Specification

---

Templates contain all the information used to create stacks; build machine images and publish them to the target platform. They are JSON files, passed as a parameter to the `hammr` command-line.

A template has two main parts:

- `stack`: defines the packages, files and configuration scripts of the machine image to build.
- `builders`: an array defining the format of the machine images to build.

### 10.1 Stack

Within a template, the `stack` section describes the packages, files and configuration information required to be added when building a machine image. It can also contain low level installation information (for example keyboard settings, partitioning, timezone etc) to be configured as part of the build or prompted during the first boot of an instance using the machine image.

The definition of a `stack` section is:

```
{
  "stack": {
    ...the stack definition goes here.
  }
}
```

The valid keys to use within a stack are:

- `name` (mandatory): a string providing the name of the stack
- `version` (mandatory): a string providing the version of the stack
- `description` (optional): a string providing a description of what the stack does
- `os` (mandatory): an object providing the operating system to use when building the machine image. You must have access to this operating system in UForge. This object may include specific packages to install from the operating system repository. For more information, refer to the [os](#) sub-section.

- `bundles` (optional): an array of objects describing any software bundles (can be native packages, tarballs, jars, wars etc) to upload and use when building the machine image. For more information, refer to the [bundles](#) sub-section.
- `installation` (optional): an object providing low-level installation or first boot options. Some options can be pre-configured as part of the build or prompted by the end-user to provide when provisioning an instance from the machine image. For more information, refer to the [installation](#) sub-section.
- `config` (optional): an array of objects describing any configuration scripts to execute when an instance is booted from the machine image. For more information, refer to the [config](#) sub-section.

Stack sub-sections are:

### 10.1.1 `os`

Within a `stack`, the `os` sub-section describes the operating system to use when building the machine image. This includes the operating system version, architecture and the `os` profile to use. The `os` profile is a pre-determined group of packages that will be installed as part of the machine image build. Extra packages can be specified to include in the build that are available in the operating system repository, and the build date can be set to get the latest updates, or roll-back. For more information on `os` package updates, refer to [Package Updates](#).

To use a particular operating system, you must have access to it in the UForge server you are using. To determine which operating systems are available, use the `os list` command (please refer [Command-Line](#) for more information).

The definition of an `os` section is:

```
"os": {  
  ...the os definition goes here.  
}
```

The valid keys to use within the `os` object are:

- `arch` (mandatory): a string providing the architecture to use
- `name` (mandatory): a string providing the name of the operating system to use
- `pkgs` (optional): an array providing any extra packages to install (see `pkgs` key sub-section for more information)
- `profile` (mandatory): a string providing which operating system profile to use
- `updateTo` (optional): a string providing the date and time where package versions should be calculated (determines which package versions to use to \* calculate the package dependency tree)
- `version` (mandatory): a string providing the version of the operating system to use

### Sub-Sections

The `os` sub-sections are:

#### `pkgs`

Within the `os` section, the `pkgs` sub-section is an array of objects describing any extra packages that should be installed as part of the machine image build. Any package information provided in this section must exist in the corresponding operating system repository, otherwise this will result in a build failure.

The definition of a `pkgs` section is:

```
"pkgs": [
  ...the list of packages goes here.
]
```

The valid keys to use within the pkgs object are:

- **arch** (optional): a string providing architecture to use
- **fullName** (optional): a string providing the name, version, release and architecture information. If used, the mandatory name key is not required.
- **name** (mandatory): a string providing the name of the package to use
- **release** (optional): a string providing the release of the package to use
- **version** (optional): a string providing the version of the package to use

When **name** is used on its own, the version, release and arch is determined when the machine image is being built. This information is determined during the package dependency phase of the build. The package dependency phase uses the created date of the stack within the UForge server to calculate the correct versions of packages. This date can be overridden by the **updateTo** key in the **os** section. Any missing packages required by the stack are also added to ensure any dependencies are met.

In the case where **version**, **release** and **arch** (or **fullName**) is used, then the version determined by the created stack date (or **updateTo** date) is overridden by the version details provided. This is known as making the package sticky. Note, that any updates available for this package will NOT be used in this case.

## Examples

### Basic Example

The following example uses CentOS 6.4 64 bit operating system for the template and adding the packages **php**, **php-cli**, **php-common** and **php-mysql**. Note that only the name is provided. The final version and release of these packages is determined during the build of the machine image.

```
{
  "os": {
    "name": "CentOS",
    "version": "6.4",
    "arch": "x86_64",
    "profile": "Minimal",
    "pkgs": [
      {
        "name": "php"
      },
      {
        "name": "php-cli"
      },
      {
        "name": "php-common"
      },
      {
        "name": "php-mysql"
      }
    ]
  }
}
```

## Adding a Version and Release

By adding version, release and arch or fullName, during the build this specific version is used regardless of any build date (updateTo) set in the os section. This is called making the package “sticky”.

```
{
  "os": {
    "name": "CentOS",
    "version": "6.4",
    "arch": "x86_64",
    "profile": "Minimal",
    "pkgs": [
      {
        "name": "php",
        "version": "5.5.3",
        "release": "23.el6_4",
        "arch": "i686"
      },
      {
        "name": "php-cli",
        "version": "5.5.3",
        "release": "23.el6_4",
        "arch": "i686"
      },
      {
        "fullName": "php-common-5.5.3-23.el6_4-i686.rpm"
      },
      {
        "fullName": "php-mysql-5.5.3-23.el6_4-i686.rpm"
      }
    ]
  }
}
```

## Examples

### Basic Example

The following example describes using CentOS 6.4 64 bit operating system for the template. The profile `Minimal` is used, which automatically adds a pre-determined group of packages to the template.

```
{
  "os": {
    "name": "CentOS",
    "version": "6.4",
    "arch": "x86_64",
    "profile": "Minimal"
  }
}
```

The name, version, arch and profile values for an operating system can be found by using the command `os list`. This lists all the operating systems you have access to.

## Specifying a Build Date/Time

By using the `updateTo` key will specify the date and time to calculate the version and release of all the packages to use in the template during the build phase of a machine image. This allows you to roll-back or update the operating system packages used. If no date is provided, then the date the template is created is used. The example below sets the date to 14 May 2014 00:00 UTC. Note that timezone must respect [General Time Zone](#) format.

```
{
  "os": {
    "name": "CentOS",
    "version": "6.4",
    "arch": "x86_64",
    "profile": "Minimal"
    "updateTo": "2014-05-14 00:00 UTC"
  }
}
```

You can still use a date without time information, in such case time will be interpreted by server as midnight in server's own timezone (UTC by default).

```
{
  "os": {
    "name": "CentOS",
    "version": "6.4",
    "arch": "x86_64",
    "profile": "Minimal"
    "updateTo": "2014-05-14"
  }
}
```

### 10.1.2 bundles

Within a `stack`, the `bundles` sub-section describes any custom software to be added to the filesystem of the machine image during the build phase. Software bundles can contain any file, archive or native package. Native packages can be installed and archives can be uncompressed as part of this process.

The definition of a bundles section is:

```
"bundles": [
  ...the list of bundles goes here.
]
```

The valid keys to use within a bundle are:

- `description` (optional): a string describing what the bundle does or contains.
- `destination` (mandatory): a string providing the target directory where to add the files in the filesystem.
- `files` (mandatory): an array of objects describing the files, archives or packages contained in the bundle. See the [files](#) sub-section for available keys.
- `license` (optional): an object providing the license information for the bundle. See the [license](#) sub-section for available keys.
- `name` (mandatory): a string providing the name of the bundle.
- `version` (mandatory): a string providing the version of the bundle.

The destination string that describes where to add the files in the bundle is ignored for native packages that have the option to be installed during the build process.

### Sub-sections

Bundle sub-sections are:

#### files

Within a bundle, the `files` sub-section describes the list of files, binaries, archives or native packages that are part of the bundle. Within the `files` you can also list a folder.

The definition of a files section is:

```
{
  "files": [
    ...the list of files goes here.
  ]
}
```

The valid keys to use within a file are:

- `destination` (optional): a string providing the destination path where to install the file on the machine image filesystem. This overrides any destination install path provided in the bundle section.
- `extract` (optional): a boolean describing whether to uncompress/extract the archive file during the build process. This flag can only be used if the file is an archive, otherwise this flag is ignored.
- `install` (optional): a boolean describing whether to install the native package as part of the build. It can only be used for native packages. If false, then the native package will be added to the filesystem as a file described by the destination. Otherwise the package will be treated like any other native package – package dependencies will be verified and installed. If the file is not a native package then this flag is ignored.
- `md5sum` (optional): a string providing a md5sum checksum.
- `name` (mandatory): a string providing the name of the bundle.
- `params` (optional): a string providing any parameters to execute with the binary file as part of the generation process. These parameters are ignored if the file is not a binary (.msi, .exe etc)
- `source` (mandatory): a string providing the location of where to get the file. This can be a filesystem path (absolute or relative) or an URL.

### Examples

#### Basic Example

The following example shows how to declare a set of files to uploaded as part of a bundle.

---

**Note:** If you declare the same file twice, the second file will overwrite the first one.

---

```
{
  "files": [
    {
```



```

    "name": "wordpress.zip",
    "source": "http://wordpress.org/wordpress-3.5.zip"
  }
]
}

```

### Example of a Folder in Files Sub-section

The following example shows how to declare a folder to be uploaded as part of a bundle. All the files within the declared bundle will be uploaded.

**Note:** You cannot upload the same source folder with two different names. In the end, the source folder and files will only be uploaded once.

```

{
  "files": [
    {
      "name": "folder",
      "source": "/usr/local/folder"
    }
  ]
}

```

### Overriding Bundle Destination

The bundle via destination provides the global install path for all the files. This example shows how you can add a file to another directory in the filesystem, effectively overriding the default destination directory.

```

{
  "files": [
    {
      "name": "wordpress.zip",
      "source": "http://wordpress.org/wordpress-3.5.zip",
      "destination": "/usr/local/wordpress"
    }
  ]
}

```

### Extracting Archives

The example uses the `extract` key to automatically extract the archive file:

```

{
  "files": [
    {
      "name": "wordpress.zip",
      "source": "http://wordpress.org/wordpress-3.5.zip",
      "destination": "/usr/local/wordpress",
      "extract": true
    }
  ]
}

```

```
]
}
```

## Installing or Placing Native Packages

The example declares a native package to be added to the bundle. The `install` key is used to tell the build process not to install the package, but to add it to the filesystem in the destination directory.

```
{
  "files": [{
    "name": "mypackage.rpm",
    "source": "/home/joris/demo/mypackage-3.1.rpm",
    "destination": "/usr/local/rpms",
    "install": false
  }]
}
```

If `install` is set to `true`, then the package is installed as a native package (including package dependency checking) and then destination information is ignored.

## Using Parameters for Binaries

The example declares a binary file to be added to the bundle. The `params` key is used to provide a set of parameters that are used to execute the binary.

```
{
  "files": [
    {
      "name": "mybinary.exe",
      "source": "/home/joris/demo/mybinary.exe",
      "params": "--silent"
    }
  ]
}
```

**Warning:** Hammr only supports windows binaries to be executed with parameters (.exe and .msi). For linux, use the *config* section to declare boot scripts.

## license

Within a bundle, the `license` sub-section describes the license information or EULA for the files that make up the bundle.

The definition of a license section is:

```
"license": {
  ...the license declaration goes here.
}
```

The valid keys to use within a license are:

- **name** (mandatory): a string providing the name of the license.
- **source** (mandatory): a string providing the location of where to get the license. This can be a filesystem path or URL.

## Example

The following example shows how to declare a license for a bundle.

```
{
  "license": {
    "name": "license.html",
    "source": "/home/joris/demo/apache-license.html"
  }
}
```

## Examples

### Basic Example

The following example describes the mandatory information in a bundle to be uploaded and used in the template. All the files described in the bundle are placed in the `/tmp/wordpress` directory.

```
{
  "bundles": [
    {
      "name": "wordpress",
      "version": "3.5",
      "destination": "/tmp/wordpress",
      "files": [
        ...add files definition here.
      ]
    },
    {
      "name": "wordpress language pack",
      "version": "3.5",
      "destination": "/tmp/wordpress",
      "files": [
        ...add files definition here.
      ]
    }
  ]
}
```

### Adding a Description and License

The following example show how you can add license information and a description to the bundle.

```
{
  "bundles": [
    {
      "name": "wordpress",
      "version": "3.5",
```

```
"description": "The wordpress files from wordpress.org",
"destination": "/tmp/wordpress",
"files": [
  ...add files definition here (see files sub section)
],
"license": {
  ...add license definition here (see license sub section)
}
}
]
```

### 10.1.3 installation

Within a *Stack*, the `installation` sub-section describes questions that are normally related to the installation of an operating system. This includes root password, keyboard settings, timezone, and partitioning. These questions are only asked once as part of the operating system installation; consequently decided by the person when building machine images manually. Hammr provides a mechanism that allows some of the installation questions to be asked as part of the first-boot when provisioning an instance from the machine image. This makes any machine image built by hammr to be more flexible, for example if you have a team in the UK and another team in France then their keyboard settings are most likely to be QWERTY and AZERTY respectively. By allowing the end-user to choose the keyboard settings as part of first-boot can help resolve hours of frustration.

The definition of a `pkgs` section is:

```
"installation": {
  ...the installation definition goes here.
}
```

The valid keys to use within an installation are:

- `diskSize` (optional): an integer value (in MB) providing the disk size of the machine image. This value is ignored if an advanced partitioning table is provided (see *partitioning*)
- `displayLicense` (optional): a boolean value to display any EULA during the first boot of a provisioned instance (includes operating system EULA and any license information provided in the *bundles* section of the stack). If the value is `false` then no license information is displayed. If `displayLicense` is not used, then by default all license information is displayed during first boot.
- `internetSettings` (optional): a string providing the network settings. Only two possible values `dhcp` or `static`. If no value is provided, `dhcp` is set by default.
- `kernelParams` (optional): an array of strings providing the kernel parameters to use. These parameters are used when provisioning an instance from the machine image. If no kernel parameters are provided, the `rhbg` and `quiet` parameters are set by default
- `keyboard` (optional): a string providing the keyboard layout to use. If no keyboard setting is provided, then during first boot the keyboard setting is prompted. See *keyboard* sub-section for all available values for keyboard
- `partitioning` (optional): an array of objects describing an advanced partitioning table. Refer to *partitioning* sub-section for more information.
- `rootUser` (optional): an object describing the configuration information of the root user (or primary administrator). If `rootUser` is not provided, then during first boot the root user password is prompted
- `swapSize` (optional): an integer value (in MB) providing the swap size to be allocated. This value is ignored if an advanced partitioning table is provided (see *partitioning*)

- `timezone` (optional): a string providing the timezone to use. If no timezone is provided, then during first boot the timezone is prompted. See [timezone](#) sub-section for all available values for timezone.
- `firewall` (optional): a boolean to enable or disable the firewall service. If no firewall is given, then the firewall is asked during installation.
- `welcomeMessage` (optional): a string providing a welcome message displayed during the first boot of a provisioned instance

## Sub-sections

The installation sub-sections are:

### keyboard

The following is a list of all the accepted keyboard values that can be used for the keyboard key in an [installation](#) sub-section of the stack.

You do not need to enter the full name; only the short form is required. For example, for Danish use:

```
{
  "installation": {
    "keyboard": "dk"
  }
}
```

### Available Keyboard Values

- Arabic (azerty) `ar-azerty`
- Arabic (azerty/digits) `ar-azerty-digits`
- Arabic (digits) `ar-digits`
- Arabic (qwerty) `ar-qwerty`
- Arabic (qwerty/digits) `ar-qwerty-digits`
- Belgian (be-latin1) `be-latin1`
- Bengali (Inscript) `ben`
- Bengali (Probhat) `ben-probhat`
- Brazilian (ABNT2) `br-abnt2`
- Bulgarian (Phonetic) `bg_pho-utf8`
- Bulgarian `bg_bds-utf8`
- Croatian `croat`
- Czech (qwerty) `cz-lat2`
- Czech `cz-us-qwertz`
- Danish `dk`
- Danish (latin1) `dk-latin1`
- Devanagari (Inscript) `dev`

- Dutch `nl`
- Dvorak `dvorak`
- Estonian `et`
- Finnish (latin1) `fi-latin1`
- Finnish `fi`
- French (latin1) `fr-latin1`
- French (latin9) `fr-latin9`
- French (pc) `fr-pc`
- French Canadian `cf`
- French `fr`
- German (latin1 w/ no deadkeys) `de-latin1-nodeadkeys`
- German (latin1) `de-latin1`
- German `de`
- Greek `gr`
- Gujarati (Inscript) `guj`
- Hungarian (101 key) `hu101`
- Hungarian `hu`
- Icelandic `is-latin1`
- Irish `ie`
- Italian (IBM) `it-ibm`
- Italian (it2) `it2`
- Italian `it`
- Japanese `jp106`
- Korean `ko`
- Latin American `la-latin1`
- Macedonian `mk-utf`
- Norwegian `no`
- Polish `pl2`
- Portuguese `pt-latin1`
- Punjabi (Inscript) `gur`
- Romanian Cedilla `ro-cedilla`
- Romanian `ro`
- Romanian Standard Cedilla `ro-std-cedilla`
- Romanian Standard `ro-std`
- Russian `ru`
- Serbian (latin) `sr-latin`

- Serbian `sr-cy`
- Slovak (qwerty) `sk-qwerty`
- Slovenian `slovene`
- Spanish `es`
- Swedish `sv-latin1`
- Swiss French (latin1) `fr_CH-latin1`
- Swiss French `fr_CH`
- Swiss German (latin1) `sg-latin1`
- Swiss German `sg`
- Tajik `tj`
- Tamil (Inscript) `tml-inscript`
- Tamil (Typewriter) `tml-uni`
- Turkish `trq`
- U.S. English `us`
- U.S. International `us-acentos`
- Ukrainian `ua-utf`
- United Kingdom `uk`

## groups

Within an *installation* section, the `groups` sub-section describes extra operating system groups to create as part of the machine image build process.

The definition of a groups section is:

```
"groups": [
  ...the list of groups goes here.
]
```

The valid keys to use within a group are:

- `name` (mandatory): a string providing the name of the group. The name cannot contain any spaces.
- `systemGroup` (optional): a boolean determining if the group is a system user.
- `groupId` (optional): an integer providing the unique Id of the group. This number must be greater than 1000. If the group is a system group, then this number must be greater than 201.

## Examples

### Basic Example

The following example describes groups to be created during the build. As no `groupId` is specified, the next available group Id numbers are used automatically during the build of the machine image.

```
{
  "groups": [
    {
      "name": "nginx"
    },
    {
      "name": "mongoDb"
    }
  ]
}
```

## System Groups and Group Ids

This example shows how you can pre-determine the `groupId` of the group to be created as well as making the group a system group.

**Warning:** A normal group's Id must be greater than 1000. If the group is a system group, then this Id can start at 201.

```
{
  "groups": [
    {
      "name": "nginx",
      "groupId": 1033
    },
    {
      "name": "mongoDb",
      "systemGroup": true,
      "groupId": 245
    }
  ]
}
```

## partitioning

Within an *installation* section, the partitioning sub-section allows you to describe an advanced partitioning table.

**Warning:** not all clouds support advanced partitioning. When building a machine image for an environment that does not support advanced partitioning, the build will fail with an appropriate error message.

The definition of a partitioning section is:

```
"partitioning": {
  ...the partitioning definition goes here.
}
```

The valid keys to use within partitioning are:

- **disks** (mandatory): an array of objects describing the physical disks that make up the advanced partitioning table. A disk may include up to four partitions, one of which can be of type extended that may hold one or more logical partitions. For more information, refer to the *disks* sub-section.



- `volumeGroups` (optional): an array objects describing any volume groups that make up the advanced partitioning table. If used, you must have one or more logical volumes using this volume group. For more information, refer to the *volumeGroups* sub-section.
- `logicalVolumes` (optional): an array of objects describing any logical volumes that make up the partitioning table. If used, you must have one or more volume groups that are used in creating the logical volume. For more information, refer to the *logical volumes* sub-section.

## Sub-sections

The partitioning sub-sections are:

### disks

Within a *partitioning* section, the `disks` sub-section describes all the physical disks for an advanced partitioning table. Each disk may be partitioned, i.e. the act of dividing the physical disk into logical sections with the goal to treat one physical disk drive as if it were multiple disks. These are called physical partitions. A disk may have a maximum of 4 physical partitions.

The definition of a disks section is:

```
"disks": [
  ...the list of disks goes here.
]
```

The valid keys to use within a disk are:

- `name` (mandatory): a string providing the name of the disk. Currently only the following values are valid: `sd` followed by a letter. The first disk must use the letter `a` (i.e. `sda`), the second disk `b` and so forth.
- `partitions` (optional): an array of objects describing the partitions for this disk. For more information, refer to the *partitions* sub-section. A maximum of 4 partitions is allowed.
- `size` (mandatory): an integer providing the size of the disk (in MB)
- `type` (mandatory): a string providing the disk type. The valid values are `MSDOS` or `LVM`

## Sub-sections

The disks sub-sections are:

### partitions

Within a *disks* section, the `partitions` sub-section describes all the partitions to create for the disk. Disk partitioning is the act of dividing the physical disk into logical sections with the goal to treat one physical disk drive as if it were multiple disks.

**Warning:** A disk may have a maximum of 4 partitions.

The definition of a partitions section is:

```
"partitions": [  
  ...the list of partitions goes here.  
]
```

The valid keys to use within a partition are:

- `fstype` (mandatory): a string providing the filesystem type. See below for valid values.
- `grow` (optional): a boolean marking this partition as growable. When a partition is growable it will take any available space left on the disk after all the other partitions catered for. You can only have 1 growable partition in a disk.
- `label` (optional): a string providing a label for this partition
- `partitions` (optional): an array of objects `partition` describing any logical partitions this partition may contain. To use logical partitions, this partition must use the `Extended` filesystem type.
- `mountPoint` (optional): a string providing the mount point of the partition. If the `fstype` is NOT `lvm` then the mount point is mandatory.
- `number` (mandatory): an integer providing the partition number. Starting at 1
- `size` (mandatory): an integer providing the size of the partition. Note that the sum of all the partitions cannot be greater than the total disk size provided in the `disk`. The minimum size is 64MB.

### Available Filesystem Types

The following are valid filesystem types used with the `fstype` key:

- `Extended`
- `ext2`
- `ext3`
- `ext4`
- `NTFS`
- `FAT16`
- `FAT32`
- `jfs`
- `linux-swaps`
- `lvm2`
- `unformatted`
- `xfs`

### logical volumes

Within a *partitioning* section, the `logicalVolumes` sub-section describes the way a volume group should be partitioned.

The definition of a `logicalVolumes` section is:

```
"disks": [
  ...the list of logical volumes goes here.
]
```

The valid keys to use within a logical volume are:

- `fstype` (mandatory): a string providing the filesystem type. See below for valid values.
- `grow` (optional): a boolean marking this volume (partition) as growable. When a volume is growable it will take any available space remaining in the volume group after all the other volumes catered for. You can only have 1 growable partition in the logical volume.
- `label` (optional): a string providing a label for this volume
- `mountPoint` (mandatory): a string providing the mount point of the volume.
- `name` (mandatory): a string providing the name of the volume.
- `size` (mandatory): an integer providing the size of the volume. Note that the sum of all the volumes cannot be greater than the total size provided in the *volumeGroups*.
- `vg_name` (mandatory): a string providing the name of the volume group this logical volume is using

## Available Filesystem Types

The following are valid filesystem types used with the `fstype` key:

- `Extended`
- `ext2`
- `ext3`
- `ext4`
- `NTFS`
- `FAT16`
- `FAT32`
- `jfs`
- `linux-swaps`
- `lvm2`
- `unformatted`
- `xfs`

## volumeGroups

Within a *partitioning* section, the `volumeGroups` sub-section describes a volume group in the partitioning table. A volume group creates a pool of disk space from a collection of disks or partitions. This volume group can then be partitioned via a *logical volumes*.

**Warning:** Only disks and partitions of type `lvm` and logical partitions can be added to a volume group.

The definition of a volumeGroups section is:

```
"disks": [
  ...the list of volume groups goes here.
]
```

The valid keys to use within a volumeGroup are:

- **name** (mandatory): a string providing the name of the volume group
- **physicalVolumes** (optional): an array of strings describing the names of the disks or partitions to include in this group. The sum of all the disks and partitions added will be the total size of this volume group. This logical pool of disk can then be partitioned via a logical volume. You cannot add a disk and one of its partitions into the same volume group, furthermore you cannot use a disk or partition more than once if 2 or more volume groups are declared.

## Examples

### Basic Example

The following example describes a partitioning table with one disk that has three partitions: the `boot` partition, a swap partition and a third partition called `space`.



```
{
  "partitioning": {
    "disks": [
      {
        "name": "sda",
        "type": "msdos",
        "size": 12288,
        "partitions": [
          {
            "number": 1,
            "fstype": "ext3",
            "size": 2048,
            "mountPoint": "/boot"
          },
          {
            "number": 2,
            "fstype": "linux-swaps",
            "size": 1024
          },
          {
            "number": 3,
            "fstype": "ext3",
            "size": 9216,
            "label": "space",
            "mountPoint": "/space"
          }
        ]
      }
    ]
  }
}
```

```

    }
  ]
}

```

## Using Growable Example

The same partitioning table as shown in *Basic Example* can be written slightly differently using the `grow` flag. A growable partition is partition that takes up the rest of the available disk space after the other partition sizes have been satisfied. In this case, we say that the “space” partition takes up the rest of the disk (rather than us having to calculate the space left after creating the first two partitions). We must specify though a size for the third partition (the minimum partition size is 64MB).



```

{
  "partitioning": {
    "disks": [
      {
        "name": "sda",
        "type": "msdos",
        "size": 12288,
        "partitions": [
          {
            "number": 1,
            "fstype": "ext3",
            "size": 2048,
            "mountPoint": "/boot"
          },
          {
            "number": 2,
            "fstype": "linux-swap",
            "size": 1024
          },
          {
            "number": 3,
            "fstype": "ext3",
            "size": 64,
            "grow": true,
            "label": "space",
            "mountPoint": "/space"
          }
        ]
      }
    ]
  }
}

```

## Creating Logical Partitions Example

In this example the, logical partitions are created inside the `space` partition. The `space` partition now has the filesystem type `Extended`.

**Warning:** only one partition within a disk can have logical partitions. When a partition is extended, you cannot specify a mount point or a label. Logical partitions must start with number 5



```
{
  "partitioning": {
    "disks": [
      {
        "name": "sda",
        "type": "msdos",
        "size": 12288,
        "partitions": [
          {
            "number": 1,
            "fstype": "ext3",
            "size": 2048,
            "mountPoint": "/boot"
          },
          {
            "number": 2,
            "fstype": "linux-swap",
            "size": 1024
          },
          {
            "number": 3,
            "fstype": "Extended",
            "size": 9216,
            "partitions": [
              {
                "number": 5,
                "fstype": "ext3",
                "size": 4098,
                "mountPoint": "/space",
                "label": "space"
              },
              {
                "number": 6,
                "fstype": "ext3",
                "size": 4098,

```


```

        "mountPoint": "/home",
        "label": "home"
      },
      {
        "number": 7,
        "fstype": "ext3",
        "size": 64,
        "mountPoint": "/tmp",
        "label": "tmp",
        "grow": true
      }
    ]
  }
}
}
}
}

```

### Volume Groups and Logical Volumes Example

The following example shows how disks and partitions that have lvm filesystem types can be regrouped together – volume group then re-partitioned differently – a logical volume.



```

{
  "partitioning": {
    "disks": [
      {
        "name": "sda",
        "type": "msdos",
        "size": 12288,
        "partitions": [
          {
            "number": 1,
            "fstype": "ext3",

```

```
    "mountPoint": "/boot",
    "size": 1024
  },
  {
    "number": 2,
    "fstype": "linux-swap",
    "size": 1024
  },
  {
    "number": 3,
    "fstype": "extended",
    "size": 64,
    "grow": true,
    "partitions": [
      {
        "number": 5,
        "fstype": "lvm2",
        "size": 5120
      },
      {
        "number": 6,
        "fstype": "lvm2",
        "size": 5120
      }
    ]
  }
]
},
{
  "name": "sdb",
  "type": "lvm",
  "size": 122880
}
],
"volumeGroups": [
  {
    "name": "grp1",
    "physicalVolumes": [
      {
        "name": "sda5"
      },
      {
        "name": "sda6"
      },
      {
        "name": "sdb"
      }
    ]
  }
]
},
"logicalVolumes": [
  {
    "name": "vol1",
    "vg_name": "grp1",
    "fstype": "ext3",
    "mountPoint": "/home",
    "size": 4098
  },
],
```



```

    {
      "name": "vol2",
      "vg_name": "grp1",
      "fstype": "ext3",
      "mountPoint": "/space",
      "size": 64,
      "grow": true
    }
  ]
}

```

## rootUser

Within an *installation*, the `rootUser` sub-section describes information for the root user to be created as part of the machine image build. If no root user information is provided, when an instance is provisioned from the machine image, the root user password is prompted.

The definition of a `rootUser` section is:

```

"rootUser": {
  ...the root user definition goes here.
}

```

The valid keys to use within a `rootUser` are:

- `disablePasswordLogin` (optional): a boolean to determine whether to disable the ability for the root user to login into a running instance using the root password.
- `password` (optional): a string providing the root user password. A blank password "" is valid.
- `setPassword` (mandatory): a boolean to determine whether to preset a password during the build or prompt the user to add a password during first boot of the instance.
- `sshKeys` (optional): an array of objects providing one or more public ssh keys for the root user. For more information, refer to the *sshKeys* sub-section.

## Sub-sections

The root user sub-sections are:

### sshKeys

The `sshKeys` sub-section describes one or more public SSH keys that can be used for a particular user.

The definition of a `sshKeys` section is:

```

"sshKeys": [
  ...the list of ssh keys goes here.
]

```

The valid keys to use within a `sshKey` are:

- `name` (mandatory): a string providing the name of the public SSH key

- `publicKey` (mandatory): a string providing the public key content. A public key must begin with string `ssh-rsa` or `ssh-dss`

### Example

This example shows how to provide an ssh key for the root user of the operating system.

```
{
  "sshKeys": [
    {
      "name": "admin-public",
      "publicKey": "ssh-rsa_
↪AAAAB3NzaClyc2EAAAABIwAAAQEA6NF8iallvQVp22WDkTkyrtvp9eWW6A8YVr+kz4TjGYe7gHzIw+niNltGEEHxD8+v1I2YJ6
↪"
    }
  ]
}
```

### Examples

#### Basic Example

The following example describes the basic root user information.

```
{
  "rootUser": {
    "password": "welcome-not-a-good-password"
  }
}
```

#### Disabling Password Login

You can easily disable root password login as a security measure by doing the following:

```
{
  "rootUser": {
    "password": "welcome-not-a-good-password",
    "disablePasswordLogin": true
  }
}
```

#### timezone

The following is a list of all the accepted timezone values that can be used for the `timezone` key in an *installation* sub-section of the stack.

For example:

```
{
  "installation": {
    "timezone": "Europe/Paris"
  }
}
```

```
}  
}
```

### Available Keyboard Values

- Africa/Abidjan
- Africa/Accra
- Africa/Addis\_Ababa
- Africa/Algiers
- Africa/Asmara
- Africa/Bamako
- Africa/Bangui
- Africa/Banjul
- Africa/Bissau
- Africa/Blantyre
- Africa/Brazzaville
- Africa/Bujumbura
- Africa/Cairo
- Africa/Casablanca
- Africa/Ceuta
- Africa/Conakry
- Africa/Dakar
- Africa/Dar\_es\_Salaam
- Africa/Djibouti
- Africa/Douala
- Africa/El\_Aaiun
- Africa/Freetown
- Africa/Gaborone
- Africa/Harare
- Africa/Johannesburg
- Africa/Kampala
- Africa/Khartoum
- Africa/Kigali
- Africa/Kinshasa
- Africa/Lagos
- Africa/Libreville

- Africa/Lome
- Africa/Luanda
- Africa/Lubumbashi
- Africa/Lusaka
- Africa/Malabo
- Africa/Maputo
- Africa/Maseru
- Africa/Mbabane
- Africa/Mogadishu
- Africa/Monrovia
- Africa/Nairobi
- Africa/Ndjamena
- Africa/Niamey
- Africa/Nouakchott
- Africa/Ouagadougou
- Africa/Porto-Novo
- Africa/Sao\_Tome
- Africa/Tripoli
- Africa/Tunis
- Africa/Windhoek
- America/Adak
- America/Anchorage
- America/Anguilla
- America/Antigua
- America/Araguaina
- America/Argentina/Buenos\_Aires
- America/Argentina/Catamarca
- America/Argentina/Cordoba
- America/Argentina/Jujuy
- America/Argentina/La\_Rioja
- America/Argentina/Mendoza
- America/Argentina/Rio\_Gallegos
- America/Argentina/Salta
- America/Argentina/San\_Juan
- America/Argentina/San\_Luis
- America/Argentina/Tucuman

- America/Argentina/Ushuaia
- America/Aruba
- America/Asuncion
- America/Atikokan
- America/Bahia
- America/Bahia\_Banderas
- America/Barbados
- America/Belize
- America/Blanc-Sablon
- America/Boa\_Vista
- America/Bogota
- America/Boise
- America/Cambridge\_Bay
- America/Campo\_Grande
- America/Cancun
- America/Caracas
- America/Cayenne
- America/Cayman
- America/Chicago
- America/Chihuahua
- America/Costa\_Rica
- America/Cuiaba
- America/Curacao
- America/Danmarkshavn
- America/Dawson
- America/Dawson\_Creek
- America/Denver
- America/Detroit
- America/Dominica
- America/Edmonton
- America/Eirunepe
- America/El\_Salvador
- America/Fortaleza
- America/Glace\_Bay
- America/Godthab
- America/Goose\_Bay

- America/Grand\_Turk
- America/Grenada
- America/Guadeloupe
- America/Guatemala
- America/Guayaquil
- America/Guyana
- America/Halifax
- America/Havana
- America/Hermosillo
- America/Indiana/Indianapolis
- America/Indiana/Knox
- America/Indiana/Marengo
- America/Indiana/Petersburg
- America/Indiana/Tell\_City
- America/Indiana/Vevay
- America/Indiana/Vincennes
- America/Indiana/Winamac
- America/Inuvik
- America/Iqaluit
- America/Jamaica
- America/Juneau
- America/Kentucky/Louisville
- America/Kentucky/Monticello
- America/La\_Paz
- America/Lima
- America/Los\_Angeles
- America/Maceio
- America/Managua
- America/Manaus
- America/Marigot
- America/Martinique
- America/Matamoros
- America/Mazatlan
- America/Menominee
- America/Merida
- America/Mexico\_City

- America/Miquelon
- America/Moncton
- America/Monterrey
- America/Montevideo
- America/Montreal
- America/Montserrat
- America/Nassau
- America/New\_York
- America/Nipigon
- America/Nome
- America/Noronha
- America/North\_Dakota/Beulah
- America/North\_Dakota/Center
- America/North\_Dakota/New\_Salem
- America/Ojinaga
- America/Panama
- America/Pangnirtung
- America/Paramaribo
- America/Phoenix
- America/Port-au-Prince
- America/Port\_of\_Spain
- America/Porto\_Velho
- America/Puerto\_Rico
- America/Rainy\_River
- America/Rankin\_Inlet
- America/Recife
- America/Regina
- America/Resolute
- America/Rio\_Branco
- America/Santa\_Isabel
- America/Santarem
- America/Santiago
- America/Santo\_Domingo
- America/Sao\_Paulo
- America/Scoresbysund
- America/Shiprock

- America/St\_Barthelemy
- America/St\_Johns
- America/St\_Kitts
- America/St\_Lucia
- America/St\_Thomas
- America/St\_Vincent
- America/Swift\_Current
- America/Tegucigalpa
- America/Thule
- America/Thunder\_Bay
- America/Tijuana
- America/Toronto
- America/Tortola
- America/Vancouver
- America/Whitehorse
- America/Winnipeg
- America/Yakutat
- America/Yellowknife
- Antarctica/Casey
- Antarctica/Davis
- Antarctica/DumontDUrville
- Antarctica/Macquarie
- Antarctica/Mawson
- Antarctica/McMurdo
- Antarctica/Palmer
- Antarctica/Rothera
- Antarctica/South\_Pole
- Antarctica/Syowa
- Antarctica/Vostok
- Arctic/Longyearbyen
- Asia/Aden
- Asia/Almaty
- Asia/Amman
- Asia/Anadyr
- Asia/Aqtau
- Asia/Aqtobe



- Asia/Ashgabat
- Asia/Baghdad
- Asia/Bahrain
- Asia/Baku
- Asia/Bangkok
- Asia/Beirut
- Asia/Bishkek
- Asia/Brunei
- Asia/Choibalsan
- Asia/Chongqing
- Asia/Colombo
- Asia/Damascus
- Asia/Dhaka
- Asia/Dili
- Asia/Dubai
- Asia/Dushanbe
- Asia/Gaza
- Asia/Harbin
- Asia/Ho\_Chi\_Min
- Asia/Hong\_Kong
- Asia/Hovd
- Asia/Irkutsk
- Asia/Jakarta
- Asia/Jayapura
- Asia/Jerusalem
- Asia/Kabul
- Asia/Kamchatka
- Asia/Karachi
- Asia/Kashgar
- Asia/Kathmandu
- Asia/Kolkata
- Asia/Krasnoyarsk
- Asia/Kuala\_Lumpur
- Asia/Kuching
- Asia/Kuwait
- Asia/Macau

- Asia/Magadan
- Asia/Makassar
- Asia/Manila
- Asia/Muscat
- Asia/Nicosia
- Asia/Novokuznetsk
- Asia/Novosibirsk
- Asia/Omsk
- Asia/Oral
- Asia/Phnom\_Penh
- Asia/Pontianak
- Asia/Pyongyang
- Asia/Qatar
- Asia/Qyzylorda
- Asia/Rangoon
- Asia/Riyadh
- Asia/Sakhalin
- Asia/Samarkand
- Asia/Seoul
- Asia/Shanghai
- Asia/Singapore
- Asia/Taipei
- Asia/Tashkent
- Asia/Tbilisi
- Asia/Tehran
- Asia/Thimphu
- Asia/Tokyo
- Asia/Ulaanbaatar
- Asia/Urumqi
- Asia/Vientiane
- Asia/Vladivostok
- Asia/Yakutsk
- Asia/Yekaterinburg
- Asia/Yerevan
- Atlantic/Azores
- Atlantic/Bermuda

- Atlantic/Canary
- Atlantic/Cape\_Verde
- Atlantic/Faroe
- Atlantic/Madeira
- Atlantic/Reykjavik
- Atlantic/South\_Georgia
- Atlantic/St\_Helena
- Atlantic/Stanley
- Australia/Adelaide
- Australia/Brisbane
- Australia/Broken\_Hill
- Australia/Currie
- Australia/Darwin
- Australia/Eucla
- Australia/Hobart
- Australia/Lindeman
- Australia/Lord\_Howe
- Australia/Melbourne
- Australia/Perth
- Australia/Sydney
- Europe/Amsterdam
- Europe/Athens
- Europe/Belgrade
- Europe/Berlin
- Europe/Bratislava
- Europe/Brussels
- Europe/Bucharest
- Europe/Budapest
- Europe/Chisinau
- Europe/Copenhagen
- Europe/Dublin
- Europe/Gibraltar
- Europe/Guernsey
- Europe/Helsinki
- Europe/Isle\_of\_Man
- Europe/Istanbul

- Europe/Jersey
- Europe/Kaliningrad
- Europe/Kiev
- Europe/Lisbon
- Europe/Ljubljana
- Europe/London
- Europe/Luxembourg
- Europe/Madrid
- Europe/Malta
- Europe/Mariehamn
- Europe/Minsk
- Europe/Monaco
- Europe/Moscow
- Europe/Oslo
- Europe/Paris
- Europe/Podgorica
- Europe/Prague
- Europe/Riga
- Europe/Rome
- Europe/Samara
- Europe/San\_Marino
- Europe/Sarajevo
- Europe/Simferopol
- Europe/Skopje
- Europe/Sofia
- Europe/Stockholm
- Europe/Tallinn
- Europe/Tirane
- Europe/Uzhgorod
- Europe/Vaduz
- Europe/Vatican
- Europe/Vienna
- Europe/Vilnius
- Europe/Volgograd
- Europe/Warsaw
- Europe/Zagreb

- Europe/Zaporozhye
- Europe/Zurich
- Indian/Antananarivo
- Indian/Chagos
- Indian/Christmas
- Indian/Cocos
- Indian/Comoro
- Indian/Kerguelen
- Indian/Mahe
- Indian/Maldives
- Indian/Mauritius
- Indian/Mayotte
- Indian/Reunion
- Pacific/Apia
- Pacific/Auckland
- Pacific/Chatham
- Pacific/Chuuk
- Pacific/Easter
- Pacific/Efate
- Pacific/Enderbury
- Pacific/Fakaofu
- Pacific/Fiji
- Pacific/Funafuti
- Pacific/Galapagos
- Pacific/Gambier
- Pacific/Guadalcanal
- Pacific/Guam
- Pacific/Honolulu
- Pacific/Johnston
- Pacific/Kiritimati
- Pacific/Kosrae
- Pacific/Kwajalein
- Pacific/Majuro
- Pacific/Marquesas
- Pacific/Midway
- Pacific/Nauru

- Pacific/Niue
- Pacific/Norfolk
- Pacific/Noumea
- Pacific/Pago\_Pago
- Pacific/Palau
- Pacific/Pitcairn
- Pacific/Pohnpei
- Pacific/Port\_Moresby
- Pacific/Rarotonga
- Pacific/Saipan
- Pacific/Tahiti
- Pacific/Tarawa
- Pacific/Tongatapu
- Pacific/Wake
- Pacific/Wallis

### users

Within an *installation* section, the `users` sub-section describes extra operating system users to create as part of the machine image build process.

The definition of a users section is:

```
"users": [  
  ...the list of users goes here.  
]
```

The valid keys to use within a user are:

- `fullName` (mandatory): a string providing the full name of the user. The same value as `name` can be used.
- `homeDir` (mandatory): a string providing the home directory of the user. Recommended default: `/home/username` where `username` is the same value as `name`
- `name` (mandatory): a string providing the name of the user. The name cannot contain any spaces.
- `password` (optional): a string providing the user password.
- `primaryGroup` (optional): a string providing the user's primary group. If no primary group is given, then the primary group is the same as `name`.
- `shell` (mandatory): a string providing the default shell environment for the user. Recommended default is `/bin/bash`.
- `secondaryGroups` (optional): a string providing one or more group names separated by a comma (,).
- `systemUser` (optional): a boolean determining if the user is a system user.
- `userId` (optional): an integer providing the unique Id of the user. This number must be greater than 1000. If the user is a system user, then this number must be greater than 201.

## Examples

### Basic Example

The following example provides the minimal information to create users during a build. As no `userId` is specified, the next available user Id numbers are used automatically during the build of the machine image. Furthermore, as no primary group is provided, the primary group will have the same name as the user name.

```
{
  "users": [
    {
      "name": "joris",
      "fullName": "joris",
      "homeDir": "/home/joris",
      "shell": "/bin/bash"
    },
    {
      "name": "yann",
      "fullName": "yann dorcet",
      "homeDir": "/home/ydorcet",
      "shell": "/bin/bash"
    }
  ]
}
```

### More Complex Example

This example shows how you can provide group information, set a user Id and make a user a system user.

```
{
  "users": [
    {
      "name": "joris",
      "fullName": "joris",
      "userId": 2222,
      "primaryGroup": "joris",
      "secondaryGroups": "dev,france",
      "homeDir": "/home/joris",
      "shell": "/bin/bash"
    },
    {
      "name": "yann",
      "fullName": "yann dorcet",
      "systemUser": true,
      "userId": 400,
      "primaryGroup": "yann",
      "secondaryGroups": "admin,dev,france",
      "homeDir": "/home/ydorcet",
      "shell": "/sbin/nologin"
    }
  ]
}
```

**Warning:** By setting `/sbin/nologin` the user will not be able to log via the machine's console.

### Example

The following example sets the timezone, disk size, swap size, kernel parameters and automatically accepts all the licenses on the end-user's behalf (license information not displayed on boot).

---

**Note:** By default without any installation information specified, the internet settings is set to `dhcp`; kernel parameters `rhgb` and `quiet` are set and display licenses is set to `true`.

---

```
{
  "installation": {
    "timezone": "Europe/London",
    "internetSettings": "dhcp",
    "kernelParams": [
      "rhgb",
      "quiet"
    ],
    "diskSize": 12288,
    "swapSize": 512,
    "displayLicenses": false
  }
}
```

### 10.1.4 config

Within a `stack`, the `config` sub-section describes boot scripts to be added to the template and executed as part of the boot sequence of an instance.

The definition of a config section is:

```
"config": [
  ...the list of configuration file definitions goes here.
]
```

The valid keys to use within a config are:

- `frequency` (mandatory): a string to determine when the boot script should be executed. There are only two valid values, `firstboot` to specify the script should only be executed once on the first time the instance is booted; `everyboot` to specify the script should be executed every time the instance is booted.
- `name` (mandatory): a string providing the name of the boot script.
- `source` (mandatory): a string providing the location of the boot script. This can be a filesystem pathname (relative or absolute) or an URL.
- `type` (mandatory): a string providing the script type. For the moment the only valid value is `bootsript`
- `order` (optional): an integer providing the boot order.



## Example

The following example shows the declaration of two boot scripts, one to be execute only once the first time the machine is instantiated; the second to be executed every time the instance is rebooted.

```
{
  "config": [
    {
      "name": "configure-mysql.sh",
      "source": "/home/joris/demo/configure-mysql.sh",
      "type": "bootscrip",
      "frequency": "firstboot"
    },
    {
      "name": "check-stats.sh",
      "source": "http://downloads.mysite.com/config/check-stats.sh",
      "type": "bootscrip",
      "frequency": "everyboot",
      "order": "1"
    }
  ]
}
```

## Example

The following example shows a simple stack definition.

```
{
  "stack": {
    "name": "CentOS Base Template",
    "version": "6.4",
    "description": "This is a CentOS core template.",
    "os": {
      "name": "CentOS",
      "version": "6.4",
      "arch": "x86_64",
      "profile": "Minimal"
    }
  }
}
```

## 10.2 Builders

Within a template, the `builders` section is an array of objects, describing the list of machine images to build (and where possible publish). For example if you wished to build an AMI image for Amazon EC2 and another for Microsoft Azure, you would specify a builder for each.

The information may include H/W requirements, authentication information (known as a cloud account) or where to upload and register the machine image after the build is complete.

Please refer to the specific machine image format for the mandatory and optional attributes.

## A Word on Cloud Accounts

For “cloud” machine images, for example Amazon EC2, Azure CloudStack, OpenStack, Flexiant and Eucalyptus, the `builder` requires account information to the cloud environment. Information from the builder is used to correctly generate the machine image (for example AMI images for Amazon EC2 requires to have certain certificates embedded into the machine image) and to upload and register the machine image into the correct region, zone or datacenter.

The cloud account information can be part of the builder section, however as this includes sensitive information, `hammr` provides other mechanisms to include this information in the builder section. A safer way is to store this information in a separate JSON file and create the cloud account using `account create`; then reference the account name in the builder.

Please refer to the specific machine image format for the cloud account options and examples.

### 10.2.1 Cloud Targets

#### Abiquo

Default builder type: `Abiquo`

Require Cloud Account: Yes

[www.abiquo.com](http://www.abiquo.com)

The `Abiquo` builder provides information for building and publishing the machine image for the Abiquo cloud platform. The Abiquo builder requires cloud account information to upload and register the machine image to the Abiquo platform. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The Abiquo builder section has the following definition:

```
{
  "builders": [
    {
      "type": "Abiquo",
      ...the rest of the definition goes here.
    }
  ]
}
```

#### Building a Machine Image

For building an image, the valid keys are:

- `type` (mandatory): a string providing the machine image type to build. Default builder type for Abiquo: `Abiquo`. To get the available builder type, please refer to *format*
- **`hardwareSettings` (mandatory): an object providing hardware settings to be used for the machine image. The following**
  - `memory` (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).

- `hwType` (optional): an integer providing the hardware type for the machine image. This is the VMware hardware type: 4 (ESXi>3.x), 7 (ESXi>4.x) or 9 (ESXi>5.x)
- `installation` (optional): an object providing low-level installation or first boot options. These override any installation options in the *Stack* section. The following valid keys for installation are:
- `diskSize` (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Publishing a Machine Image

To publish an image, the valid keys are:

- `type` (mandatory): a string providing the machine image type to build. Default builder type for Abiquo, Abiquo. To get the available builder type, please refer to *format*
- `account` (mandatory): an object providing the abiquo cloud account information required to publish the built machine image.
- `category` (mandatory): a string providing the category this machine image. The category name must already be present in the abiquo platform.
- `datacenter` (mandatory): a string providing the datacenter name. The datacenter must already be present in the abiquo platform, and the cloud account must have access to the datacenter.
- `description` (mandatory): a string providing the description of what the machine image does.
- `enterprise` (mandatory): a string providing the enterprise resource name where to publish the machine image to. The enterprise resource must already exist in the abiquo platform, and the cloud account must have access to the enterprise resource.
- `productName` (mandatory): a string providing the name to be displayed for machine image. The name cannot exceed 32 characters

## Abiquo Cloud Account

Key: `account`

Used to authenticate the abiquo platform.

The Abiquo cloud account has the following valid keys:

- `type` (mandatory): a string providing the cloud account type. Default platform type for Abiquo: Abiquo. To get the available platform type, please refer to *platform*
- `file` (optional): a string providing the location of the account information. This can be a pathname (relative or absolute) or an URL.
- `hostname` (mandatory): a string providing the hostname or IP address where the abiquo cloud platform is running
- `name` (mandatory): a string providing the name of the cloud account. This name can be used in a builder section to reference the rest of the cloud account information.
- `password` (mandatory): a string providing the password to use to authenticate
- `username` (mandatory): a string providing the username to use to authenticate

---

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

---

## Examples

### Basic Example

The following example shows an abiquo builder with all the information to build and publish a machine image to the Abiquo Cloud platform.

```
{
  "builders": [
    {
      "type": "Abiquo",
      "account": {
        "type": "Abiquo",
        "name": "My Abiquo Account",
        "hostname": "test.abiquo.com",
        "username": "myLogin",
        "password": "myPassWD"
      },
      "hardwareSettings": {
        "memory": 1024
      },
      "installation": {
        "diskSize": 2000
      },
      "enterprise": "UShareSoft",
      "datacenter": "London",
      "productName": "CentOS Core",
      "category": "OS",
      "description": "CentOS Core template."
    }
  ]
}
```

### Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `abiquo-account.json`.

```
{
  "accounts": [
    {
      "type": "Abiquo",
      "name": "My Abiquo Account",
      "hostname": "test.abiquo.com",
      "username": "myLogin",
      "password": "myPassWD"
    }
  ]
}
```

```
]
}
```

The builder section can either reference by using `file` or `name`.

Reference by file:

```
{
  "builders": [
    {
      "type": "Abiquo",
      "account": {
        "file": "/home/joris/accounts/abiquo-account.json"
      },
      "hardwareSettings": {
        "memory": 1024
      },
      "installation": {
        "diskSize": 2000
      },
      "enterprise": "UShareSoft",
      "datacenter": "London",
      "productName": "CentOS Core",
      "category": "OS",
      "description": "CentOS Core template."
    }
  ]
}
```

Reference by name, note the cloud account must already be created by using `account create`.

```
{
  "builders": [
    {
      "type": "Abiquo",
      "account": {
        "name": "My Abiquo Account"
      },
      "hardwareSettings": {
        "memory": 1024
      },
      "installation": {
        "diskSize": 2000
      },
      "enterprise": "UShareSoft",
      "datacenter": "London",
      "productName": "CentOS Core",
      "category": "OS",
      "description": "CentOS Core template."
    }
  ]
}
```

## Amazon EC2

Default builder type: `Amazon AWS`

Require Cloud Account: Yes

[aws.amazon.com](https://aws.amazon.com)

The Amazon builder provides information for building and publishing machine images for Amazon EC2. The Amazon builder requires cloud account information to upload and register the machine image to AWS (Amazon Web Services) public cloud. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The Amazon builder section has the following definition:

```
{
  "builders": [
    {
      "type": "Amazon AWS",
      ...the rest of the definition goes here.
    }
  ]
}
```

### Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Amazon: Amazon AWS. To get the available builder type, please refer to *format*
- **disableRootLogin** (optional): a boolean flag to determine if root login access should be disabled for any instance provisioned from the machine image.
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. As EBS-backed machine image is created, the maximum disk size is 1TB.

### Publishing a Machine Image

To publish an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Amazon: Amazon AWS. To get the available builder type, please refer to *format*
- **account** (mandatory): an object providing the AWS cloud account information required to publish the built machine image.
- **region** (mandatory): a string providing the region where to publish the machine image. See below for valid regions.
- **bucket** (mandatory): a string providing the bucket name where to store the machine image. Bucket names are global to everyone, so you must choose a unique bucket name that does not already exist (or belongs to you). A bucket name cannot include spaces. Note, that if the bucket exists already in one region (for example Europe) and you wish to upload the same machine image to another region, then you must provide a new bucket name.

## Valid Regions

The following regions are supported:

- `ap-northeast-1`: Asia Pacific (Tokyo) Region
- `ap-southeast-1`: Asia Pacific (Singapore) Region
- `eu-west-1`: EU (Ireland) Region
- `sa-east-1`: South America (Sao Paulo) Region
- `us-east-1`: US East (North Virginia) Region
- `us-west-1`: US West (North california) Region
- `us-west-2`: US West (Oregon) Region

## Amazon Cloud Account

Key: `account`

Used to authenticate to AWS.

The Amazon cloud account has the following valid keys:

- `type` (mandatory): a string providing the cloud account type. Default platform type for Amazon: `Amazon`. To get the available platform type, please refer to [platform](#)
- `name` (mandatory): a string providing the name of the cloud account. This name can be used in a builder section to reference the rest of the cloud account information.
- `accountNumber` (mandatory): A string providing your AWS account number. This number can be found at the top right hand side of the Account > Security Credentials page after signing into Amazon Web Services
- `accessKeyId` (mandatory): A string providing your AWS access key id. To get your access key, sign into AWS ([aws.amazon.com](#)), click on Security Credentials > Access Credentials > Access Keys. Your access key id should be displayed, otherwise create a new one. Note, for security purposes, we recommend you change your access keys every 90 days
- `secretAccessKeyId` (mandatory): A string providing you AWS secret access key. To get your secret access key, sign into AWS ([aws.amazon.com](#)), click on Security Credentials > Access Credentials > Access Keys. Click on the Show button to reveal your secret key
- `x509Cert` (mandatory): A string providing the pathname or URL where to retrieve the X.509 certificate public key. To create a X.509 certificate, sign into AWS ([aws.amazon.com](#)), click on Security Credentials > Access Credentials > X.509 Certificates. Download the X.509 certificate or create a new one. This should be a (.pem) file.
- `x509PrivateKey` (mandatory): A string providing the pathname or URL where to retrieve the X.509 certificate private key. This private key is provided during the X.509 creation process. AWS does not store this private key, so you must download it and store it during this creation process. To create a X.509 certificate, sign into AWS ([aws.amazon.com](#)), click on Security Credentials > Access Credentials > X.509 Certificates and create a new certificate. Download and save the Private Key. This should be a (.pem) file
- `file` (optional): a string providing the location of the account information. This can be a pathname (relative or absolute) or an URL.

---

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

---

## Example

The following example shows an amazon builder with all the information to build and publish a machine image to Amazon EC2.

```
{
  "builders": [
    {
      "type": "Amazon AWS",
      "account": {
        "type": "Amazon",
        "name": "My AWS account",
        "accountNumber": "11111-111111-1111",
        "accessKeyId": "myaccessKeyId",
        "secretAccessKeyId": "mysecretaccesskeyid",
        "x509Cert": "/path/to/aws.cert.pem",
        "x509PrivateKey": "/path/to/aws.key.pem"
      },
      "installation": {
        "diskSize": 10240
      },
      "region": "eu-central-1",
      "bucket": "testsohammr"
    }
  ]
}
```

## Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `aws-account.json`.

```
{
  "accounts": [
    {
      "type": "Amazon",
      "accountNumber": "11111-111111-1111",
      "name": "My AWS account",
      "accessKeyId": "myaccessKeyId",
      "secretAccessKeyId": "mysecretaccesskeyid",
      "x509Cert": "/path/to/aws.cert.pem",
      "x509PrivateKey": "/path/to/aws.key.pem"
    }
  ]
}
```

The builder section can either reference by using file or name.

Reference by file:

```
{
  "builders": [
    {
      "type": "Amazon AWS",
      "account": {
        "file": "/path/to/aws-account.json"
      }
    }
  ]
}
```



```

    },
    "installation": {
      "diskSize": 10240
    },
    "region": "eu-central-1",
    "bucket": "test-so-hammr"
  }
]
}

```

Reference by name, note the cloud account must already be created by using `account create`.

```

{
  "builders": [
    {
      "type": "Amazon AWS",
      "account": {
        "name": "My AWS Account"
      },
      "installation": {
        "diskSize": 10240
      },
      "region": "eu-central-1",
      "bucket": "test-so-hammr"
    }
  ]
}

```

## CloudStack

Default builder type: CloudStack VMware (OVA), CloudStack KVM (QCOW2) or CloudStack Citrix Xen (VHD)

Require Cloud Account: Yes

[cloudstack.apache.org](http://cloudstack.apache.org)

The CloudStack builder provides information for building and publishing the machine image to the CloudStack cloud platform. This builder supports KVM (CloudStack KVM (QCOW2)), Xen (CloudStack Citrix Xen (VHD)) or VMware (CloudStack VMware (OVA)) based images for CloudStack. These builder types are the default names provided by UForge AppCenter.

---

**Note:** These builder type names can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The CloudStack builder requires cloud account information to upload and register the machine image to the CloudStack platform.

The CloudStack builder section has the following definition:

```

{
  "builders": [
    {
      "type": "CloudStack KVM (QCOW2)",
      ...the rest of the definition goes here.
    }
  ]
}

```

```

    ]
  }

```

## Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for CloudStack: CloudStack VMware (OVA), CloudStack KVM (QCOW2) or CloudStack Citrix Xen (VHD). To get the available builder type, please refer to [format](#)
- **hardwareSettings** (mandatory): an object providing hardware settings to be used for the machine image. If an OVF machine image is being built, then the hardware settings are mandatory. The following valid keys for hardware settings are:
- **memory** (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation options in the [Stack](#) section. The following valid keys for installation are:
- **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Publishing a Machine Image

To publish an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for CloudStack: CloudStack VMware (OVA), CloudStack KVM (QCOW2) or CloudStack Citrix Xen (VHD). To get the available builder type, please refer to [format](#)
- **account** (mandatory): an object providing the CloudStack cloud account information required to publish the built machine image.
- **imageName** (mandatory): a string providing the displayed name of the machine image.
- **zone** (mandatory): a string providing the zone to publish the machine image
- **publicImage** (optional): a boolean flag to determine in the machine image is to be public
- **featured** (optional): a boolean flag to determine in the machine image is to be “featured”

## CloudStack Cloud Account

**Key:** `account` Used to authenticate the CloudStack platform.

The CloudStack cloud account has the following valid keys:

- **type** (mandatory): a string providing the cloud account type. Default platform type for CloudStack is CloudStack. To get the available platform type, please refer to [platform](#)
- **name** (mandatory): a string providing the name of the cloud account. This name can be used in a builder section to reference the rest of the cloud account information.
- **publicApiKey** (mandatory): a string providing your public API key. If you do not have a public/secret key pair, please refer to the CloudStack documentation to generate them, or contact your cloud administrator

- `secretApiKey` (mandatory): a string providing your secret API key. If you do not have a public/secret key pair, please refer to the CloudStack documentation to generate them, or contact your cloud administrator
- `endpointUrl` (mandatory): a string providing the API URL endpoint of the cloudstack management console to upload the machine image to. For example: <http://cloudstackhostname:8080/client/api>
- `file` (optional): a string providing the location of the account information. This can be a pathname (relative or absolute) or an URL.

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

## Example

The following example shows a CloudStack builder with all the information to build and publish a machine image to CloudStack.

```
{
  "builders": [
    {
      "type": "CloudStack KVM (QCOW2)",
      "account": {
        "type": "CloudStack",
        "name": "My CloudStack account",
        "publicApiKey": "mypublicapikey",
        "secretApiKey": "mysecretapikey",
        "endpointUrl": "myendpointurl"
      },
      "imageName": "CentOS Core",
      "zone": "zone1"
    }
  ]
}
```

## Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `cloudstack-account.json`.

```
{
  "accounts": [
    {
      "type": "CloudStack",
      "name": "My CloudStack account",
      "publicApiKey": "mypublicapikey",
      "secretApiKey": "mysecretapikey",
      "endpointUrl": "myendpointurl"
    }
  ]
}
```

The builder section can either reference by using `file` or `name`.

Reference by file:

```
{
  "builders": [
    {
      "type": "CloudStack KVM (QCOW2)",
      "account": {
        "file": "/path/to/cloudstack-account.json"
      },
      "imageName": "CentOS Core",
      "zone": "zone1"
    }
  ]
}
```

Reference by name, note the cloud account must already be created by using `account create`.

```
{
  "builders": [
    {
      "type": "CloudStack KVM (QCOW2)",
      "account": {
        "name": "My CloudStack Account"
      },
      "imageName": "CentOS Core",
      "zone": "zone1"
    }
  ]
}
```

## Eucalyptus

Default builder type: `Eucalyptus KVM` or `Eucalyptus XEN`

Require Cloud Account: Yes

[www.eucalyptus.com](http://www.eucalyptus.com)

The Eucalyptus builder provides information for building and publishing the machine image for Eucalyptus. This builder supports KVM (`Eucalyptus KVM`) and Xen (`Eucalyptus XEN`) based images for Eucalyptus. These builder types are the default names provided by UForge AppCenter.

---

**Note:** These builder type names can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The Eucalyptus builder requires cloud account information to upload and register the machine image to an Eucalyptus cloud platform.

The Eucalyptus builder section has the following definition:

```
{
  "builders": [
    {
      "type": "Eucalyptus KVM",
      ...the rest of the definition goes here.
    }
  ]
}
```

```
]
}
```

## Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Eucalyptus: `Eucalyptus KVM` or `Eucalyptus XEN`. To get the available builder type, please refer to [format](#)
- **account** (mandatory): an object providing the Eucalyptus cloud account information required to publish the built machine image.
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.
- **disableRootLogin** (optional): a boolean flag to determine if root login access should be disabled for any instance provisioned from the machine image.

## Publishing a Machine Image

To publish an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Eucalyptus: `Eucalyptus KVM` or `Eucalyptus XEN`. To get the available builder type, please refer to [format](#)
- **account** (mandatory): an object providing the Eucalyptus cloud account information required to publish the built machine image.
- **bucket** (mandatory): a string providing the bucket where to store the machine image. Note, bucket names are global to everyone, so you must choose a unique bucket name that is not used by another user. The bucket name should not include spaces.
- **description** (mandatory): a string providing a description of what the machine image does. The description of the machine image is displayed in the console. The description can only be up to 255 characters long. Descriptions longer than 255 characters will be truncated.
- **imageName** (mandatory): a string providing the displayed name for the machine image.
- **kernelId** (optional): a string providing the kernel Id when booting an instance from the machine image. Note that the kernel id must be already present on the cloud environment. If a kernel Id is not specified, then the default kernel Id registered on the cloud platform will be used.
- **ramdisk** (optional): a string providing the ramdisk Id when booting an instance from the machine image. Note that the ramdisk Id must be already present on the cloud environment. If a ramdisk Id is not specified, then the default ramdisk Id registered on the cloud platform will be used.

## Eucalyptus Cloud Account

Key: `account` Used to authenticate to Eucalyptus.

The Eucalyptus cloud account has the following valid keys:

- `type` (mandatory): a string providing the cloud account type. Default platform type for Eucalyptus is Eucalyptus. To get the available platform type, please refer to *platform*
- `accountNumber` (mandatory): a string providing the User ID or Eucalyptus account number of the user who is bundling the image. This value can be found in the `euarc` file.
- `cloudCert` (mandatory): a string providing the location of the cloud certificate. This may be a path or URL. To get the cloud certificate, login into your Eucalyptus admin console (for example <https://myserver.domain.com:8443>). Go to the Credentials ZIP-file and click on the button Download credentials. Unzip this file, you should find the certificate with the name `cloud-cert.pem`
- `file` (optional): a string providing the location of the account information. This can be a pathname (relative or absolute) or an URL.
- `endpoint` (mandatory): a string providing the URL of the Eucalyptus Walrus server. To get the walrus server information, login into your Eucalyptus admin console and click on the Configuration tab
- `name`: (mandatory) a string providing the name of the cloud account. This name can be used in a builder section to reference the rest of the cloud account information.
- `queryId` (mandatory): a string providing your Eucalyptus query id. To get this key, login into your Eucalyptus admin console (for example <https://myserver.domain.com:8443>). Go to Query Interface Credentials > Show keys, the query id will be displayed.
- `secretKey` (mandatory): a string of your your Eucalyptus secret key. To get this key, login into your Eucalyptus admin console (for example <https://myserver.domain.com:8443>). Go to Query Interface Credentials > Show keys, the secret key will be displayed
- `x509PrivateKey` (mandatory): a string providing the location of the X.509 certificate private key. This may be a path or URL. This is the private key of the X.509 certificate. To get an X.509 private key, login into your Eucalyptus admin console, go to Credentials ZIP-file and click on the button Download credentials. Unzip this file, you should find the private key with the name `XXXX-XXXX-XXXX-pk.pem`.
- `x509Cert` (mandatory): a string providing the location of the X.509 certificate public key. This may be a path or URL. To get a X.509 certificate, login into your Eucalyptus admin console, go to the Credentials ZIP-file and click on the button Download credentials. Unzip this file, you should find the certificate with the name `XXXX-XXXX-XXXX-cert.pem`

---

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

---

## Example

The following example shows an Eucalyptus builder with all the information to build and publish a machine image to Eucalyptus.

```
{
  "builders": [
    {
      "type": "Eucalyptus KVM",
      "account": {
        "type": "Eucalyptus",
        "name": "My Eucalyptus Account",
        "accountNumber": "111122223333",
        "x509PrivateKey": "/home/joris/accounts/euca/euca-pk.pem",
        "x509Cert": "/home/joris/accounts/euca/euca-cert.pem",
        "cloudCert": "/home/joris/accounts/euca/cloud-cert.pem",
```

```

    "endpoint": "http://127.0.0.1/8773",
    "queryId": "WkVpyXXZ77rXcdeSbds3lkXcr5Jc4GeUtkA",
    "secretKey": "ir9CKRvOXXTHJXXj8VPRXX7PgxxY9DY0VLng"
  },
  "imageName": "CentOS Core",
  "description": "CentOS Base Image",
  "bucket": "ussprodbucket"
}
]
}

```

## Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `euca-account.json`.

```

{
  "accounts": [
    {
      "type": "Eucalyptus",
      "name": "My Eucalyptus Account",
      "accountNumber": "111122223333",
      "x509PrivateKey": "/home/joris/accounts/euca/euca-pk.pem",
      "x509Cert": "/home/joris/accounts/euca/euca-cert.pem",
      "cloudCert": "/home/joris/accounts/euca/cloud-cert.pem",
      "endpoint": "http://127.0.0.1/8773",
      "queryId": "WkVpyXXZ77rXcdeSbds3lkXcr5Jc4GeUtkA",
      "secretKey": "ir9CKRvOXXTHJXXj8VPRXX7PgxxY9DY0VLng"
    }
  ]
}

```

The builder section can either reference by using file or name.

Reference by file:

```

{
  "builders": [
    {
      "type": "Eucalyptus KVM",
      "account": {
        "file": "/home/joris/accounts/euca-account.json"
      },
      "imageName": "CentOS Core",
      "description": "CentOS Base Image",
      "bucket": "ussprodbucket"
    }
  ]
}

```

Reference by name, note the cloud account must already be created by using `account create`.

```

{
  "builders": [
    {
      "type": "Eucalyptus KVM",

```

```
"account": {
  "name": "My Eucalytpus Account"
},
"imageName": "CentOS Core",
"description": "CentOS Base Image",
"bucket": "ussprodbucket"
}
]
```

## Flexiant

Default builder type: Flexiant QCOW2 - KVM/Xen/VMware, Flexiant OVA - VMware or Flexiant RAW - KVM/Xen

Require Cloud Account: Yes

[flexiant.com](http://flexiant.com)

The Flexiant builder provides information for building and publishing the machine image to a Flexiant cloud platform. This builder supports KVM (Flexiant QCOW2 - KVM/Xen/VMware), VMware (Flexiant OVA - VMware) or Raw (Flexiant RAW - KVM/Xen) based images for Flexiant.

These builder types are the default names provided by UForge AppCenter.

---

**Note:** These builder type names can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The Flexiant builder requires cloud account information to upload and register the machine image to the Flexiant platform.

The Flexiant builder section has the following definition:

```
{
  "builders": [
    {
      "type": "Flexiant OVA - VMware",
      ...the rest of the definition goes here.
    }
  ]
}
```

## Building a Machine Image

For building an image, the valid keys are:

- **type (mandatory):** a string providing the machine image type to build. Default builder type for Flexiant: Flexiant QCOW2 - KVM/Xen/VMware, Flexiant OVA - VMware or Flexiant RAW - KVM/Xen. To get the available builder type, please refer to *format*
- **hardwareSettings (mandatory):** an object providing hardware settings to be used for the machine image. If an OVF n
  - **memory (mandatory):** an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).



- **installation (optional):** an object providing low-level installation or first boot options. These override any installation options.
- **diskSize (mandatory):** an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Publishing a Machine Image

To publish an image, the valid keys are:

- **type (mandatory):** a string providing the machine image type to build. Default builder type for Flexiant: Flexiant QCOW2 – KVM/Xen/VMware, Flexiant OVA – VMware or Flexiant RAW – KVM/Xen. To get the available builder type, please refer to *format*
- **account (mandatory):** an object providing the Flexiant cloud account information required to publish the built machine image.
- **virtualDatacenterName (mandatory):** a string providing the datacenter name where to register the machine image. Note, the user must have access to this datacenter.
- **machineImageName (mandatory):** a string providing the name of the machine image to displayed.
- **diskOffering (mandatory):** a string providing the disk offering to register the machine image under.

## Flexiant Cloud Account

Key: `account` Used to authenticate the Flexiant platform.

The Flexiant cloud account has the following valid keys:

- **type (mandatory):** a string providing the cloud account type. Default platform type for Flexiant is `Flexiant`. To get the available platform type, please refer to *platform*
- **name (mandatory):** a string providing the name of the cloud account. This name can be used in a builder section to reference the rest of the cloud account information.
- **apiUsername (mandatory):** a string providing your API username. To get your api username, log in to Flexiant cloud orchestrator, click on Settings > Your API Details
- **password (mandatory):** a string providing your Flexiant cloud orchestrator account password
- **wsdlUrl (mandatory):** a string providing the wsdl URL of the Flexiant cloud orchestrator, for example: <https://myapi.example2.com:4442/?wsdl>
- **file (optional):** a string providing the location of the account information. This can be a pathname (relative or absolute) or an URL.

---

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

---

## Example

The following example shows a Flexiant builder with all the information to build and publish a machine image to the Flexiant.

```
{
  "builders": [
    {
      "type": "Flexiant RAW - KVM/Xen",
      "account": {
        "type": "Flexiant",
        "name": "My Flexiant account",
        "apiUsername": "name@domain.com/mykey1111",
        "password": "mypassword",
        "wsdlUrl": "myWsdlurl"
      },
      "hardwareSettings": {
        "memory": 1024
      },
      "installation": {
        "diskSize": 2000
      },
      "virtualDatacenterName": "KVM (CEPH Cluster)",
      "machineImageName": "test_hammr",
      "diskOffering": "21 GB"
    }
  ]
}
```

## Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `Flexiant-account.json`.

```
{
  "accounts": [
    {
      "type": "Flexiant",
      "name": "My Flexiant account",
      "apiUsername": "name@domain.com/mykey1111",
      "password": "mypassword",
      "wsdlUrl": "myWsdlurl"
    }
  ]
}
```

The builder section can either reference by using file or name.

Reference by file:

```
{
  "builders": [
    {
      "type": "Flexiant RAW - KVM/Xen",
      "account": {
        "file": "/path/to/flexiant-account.json"
      },
      "hardwareSettings": {
        "memory": 1024
      },
    },
  ]
}
```

```

    "installation": {
      "diskSize": 2000
    },
    "virtualDatacenterName": "KVM (CEPH Cluster)",
    "machineImageName": "test_hammr",
    "diskOffering": "21 GB"
  }
]
}

```

Reference by name, note the cloud account must already be created by using `account create`.

```

{
  "builders": [
    {
      "type": "Flexiant RAW - KVM/Xen",
      "account": {
        "name": "My Flexiant Account"
      },
      "hardwareSettings": {
        "memory": 1024
      },
      "installation": {
        "diskSize": 2000
      },
      "virtualDatacenterName": "KVM (CEPH Cluster)",
      "machineImageName": "test_hammr",
      "diskOffering": "21 GB"
    }
  ]
}

```

## Google Compute Engine

Default builder type: Google Compute Engine

Require Cloud Account: Yes

### Google Compute Engine

The GCE builder provides information for building and publishing the machine image for Google Compute Engine. The GCE builder requires cloud account information to upload and register the machine image to Google Compute Engine public cloud. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The GCE builder section has the following definition:

```

{
  "builders": [
    {
      "type": "Google Compute Engine",
      ...the rest of the definition goes here.
    }
  ]
}

```

```
]
}
```

### Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Google compute Engine: Google Compute Engine. To get the available builder type, please refer to [format](#)
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create.

### Publishing a Machine Image

To publish an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Google compute Engine: Google Compute Engine. To get the available builder type, please refer to [format](#)
- **account** (mandatory): an object providing the GCE cloud account information required to publish the built machine image.
- **bucket** (mandatory): a string providing the bucket name where to store the machine image. The bucket name can only contain lower case alpha characters [a-z] and the special character “-”.
- **bucketLocation** (mandatory): a string providing the bucket location where to store the machine image. See below for valid values.
- **computeZone** (mandatory): a string providing the compute zone where this machine image will be used. See below for valid compute zone values.
- **description** (optional): a string providing the description for the machine image.
- **diskNamePrefix** (mandatory): a string providing the disk name prefix used when creating the disks for the running machine (note the prefix name can only contain lower case alpha characters [a-z] and the special character “-”)
- **projectId** (mandatory): a string providing the project Id to associate this machine image with.
- **storageClass** (mandatory): a string providing the storage type to use with this machine image. See below for valid storage class values

### Valid Compute Zones

The following zones are supported:

- **us-central1-a**: US (availability zone: a)
- **us-central1-b**: US (availability zone: b)
- **europa-west1-a**: Europe (availability zone: a)
- **europa-west1-b**: Europe (availability zone: b)

## Valid Bucket Locations

The following bucket locations are supported:

- EU
- US

## Valid Storage Classes

The following storage classes are supported:

- STANDARD
- DURABLE\_REDUCED\_AVAILABILITY

## GCE Cloud Account

Key: `account` Used to authenticate to GCE.

The GCE cloud account has the following valid keys:

- `type` (mandatory): a string providing the cloud account type. Default platform type for Google Compute Engine: Google Compute Engine. To get the available platform type, please refer to [platform](#)
- `certPassword` (mandatory): A string providing the password to decrypt the GCE certificate. This password is normally provided along with the certificate.
- `cert` (mandatory): A string providing the pathname or URL where to retrieve your GCE certificate. This should be a (.pem) file.
- `name` (mandatory): a string providing the name of the cloud account. This name can be used in a builder section to reference the rest of the cloud account information.

---

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

---

## Example

The following example shows a GCE builder with all the information to build and publish a machine image to Google Compute Engine.

```
{
  "builders": [
    {
      "type": "Google Compute Engine",
      "account": {
        "type": "Google Compute Engine",
        "name": "My GCE Account",
        "username": "joris",
        "certPassword": "myCertPassword",
        "cert": "/home/joris/certs/gce.pem"
      },
      "computeZone": "europe-west1-a",
      "bucketLocation": "EU",
```

```
    "bucket": "jorisbucketname",
    "projectId": "jorisproject",
    "storageClass": "STANDARD",
    "diskNamePrefix": "uss-",
    "description": "CentOS Core machine image"
  }
]
```

## Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `gce-account.json`.

```
{
  "accounts": [
    {
      "type": "Google Compute Engine",
      "name": "My GCE Account",
      "username": "joris",
      "certPassword": "myCertPassword",
      "cert": "/home/joris/certs/gce.pem"
    }
  ]
}
```

The builder section can either reference by using `file` or `name`.

Reference by file:

```
{
  "builders": [
    {
      "type": "Google Compute Engine",
      "account": {
        "file": "/home/joris/accounts/gce-account.json"
      },
      "computeZone": "europe-west1-a",
      "bucketLocation": "EU",
      "bucket": "jorisbucketname",
      "projectId": "jorisproject",
      "storageClass": "STANDARD",
      "diskNamePrefix": "uss-",
      "description": "CentOS Core machine image"
    }
  ]
}
```

Reference by name, note the cloud account must already be created by using `account create`.

```
{
  "builders": [
    {
      "type": "Google Compute Engine",
      "account": {
        "name": "My GCE Account"
      }
    }
  ]
}
```

```

    },
    "computeZone": "europe-west1-a",
    "bucketLocation": "EU",
    "bucket": "jorisbucketname",
    "projectId": "jorisproject",
    "storageClass": "STANDARD",
    "diskNamePrefix": "uss-",
    "description": "CentOS Core machine image"
  }
]
}

```

## Microsoft Azure

Default builder type: Microsoft Azure

Require Cloud Account: Yes

[azure.microsoft.com](https://azure.microsoft.com)

The Azure builder provides information for building and publishing the machine image to the Microsoft Azure cloud platform. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The Azure builder section has the following definition:

```

{
  "builders": [
    {
      "type": "Microsoft Azure",
      ...the rest of the definition goes here.
    }
  ]
}

```

## Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Azure: Microsoft Azure. To get the available builder type, please refer to *format*
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the *Stack*. This cannot be used if an advanced partitioning table is defined in the stack.

## Publishing a Machine Image

To publish an image, the valid keys are:

- `type` (mandatory): a string providing the machine image type to build. Default builder type for Azure: `Microsoft Azure`. To get the available builder type, please refer to [format](#)
- `account` (mandatory): an object providing all the cloud account information to authenticate and publish a machine image to Azure.
- `region` (mandatory): a string providing the region where to create the storage account. If the storage account already exists, then you should not specify a region. See below for valid regions.
- `storageAccount` (mandatory): a string providing the storage account to use for uploading and storing the machine image. The storage account is the highest level of the namespace for accessing each of the fundamental services.

### Valid Azure Regions

- North Central US
- South Central US
- East US
- West US
- North Europe
- West Europe
- East Asia

### Azure Cloud Account

Key: `account`

Used to authenticate the Azure platform. The Azure cloud account has the following valid keys:

- `type` (mandatory): a string providing the cloud account type. Default platform type for Microsoft Azure: `Microsoft Azure`. To get the available platform type, please refer to [platform](#)
- `name` (mandatory): a string providing the name of the cloud account. This name can be used in a builder section to reference the rest of the cloud account information.
- `publishsettings` (mandatory): A string providing the pathname where to retrieve the publish settings and subscription information file. This should be a `(.publishsettings)` file.
- `file` (optional): a string providing the location of the account information. This can be a pathname (relative or absolute) or an URL.

---

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

---

### Example

The following example shows an Azure builder with all the information to build and publish a machine image to Azure.



```
{
  "builders": [
    {
      "type": "Microsoft Azure",
      "account": {
        "type": "Microsoft Azure",
        "name": "My Azure account",
        "publishsettings": "/path/to/Pay-As-You-Go-4-25-2016-credentials.
↪publishsettings"
      },
      "storageAccount": "mystorageaccount",
      "region": "Central US"
    }
  ]
}
```

## Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `azure-account.json`.

```
{
  "accounts": [
    {
      "type": "Microsoft Azure",
      "name": "My Azure account",
      "publishsettings": "/path/to/Pay-As-You-Go-date-credentials.publishsettings"
    }
  ]
}
```

The builder section can either reference by using file or name.

Reference by file:

```
{
  "builders": [
    {
      "type": "Microsoft Azure",
      "account": {
        "file": "/home/joris/accounts/azure-account.json"
      },
      "storageAccount": "mystorageaccount",
      "region": "Central US"
    }
  ]
}
```

Reference by name, note the cloud account must already be created by using `account create`.

```
{
  "builders": [
    {
      "type": "Microsoft Azure",
      "account": {
        "name": "My Azure Account"
      }
    }
  ]
}
```

```

    },
    "storageAccount": "mystorageaccount",
    "region": "Central US"
  }
]
}

```

## Nimbula

Default builder type: Nimbula ESX or Nimbula KVM

Require Cloud Account: Yes

The Nimbula builder provides information for building and publishing the machine image to the Nimbula cloud platform. This builder supports KVM (Nimbula KVM) or VMware (Nimbula ESX) based images for Nimbula. These builder types are the default names provided by UForge AppCenter.

---

**Note:** These builder type names can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The Nimbula builder requires cloud account information to upload and register the machine image to the Nimbula platform. The Nimbula builder section has the following definition:

```

{
  "builders": [
    {
      "type": "Nimbula KVM",
      ...the rest of the definition goes here.
    }
  ]
}

```

## Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Nimbula: Nimbula ESX` or, ``Nimbula KVMK. To get the available builder type, please refer to *format*
- **hardwareSettings** (mandatory): an object providing hardware settings to be used for the machine image. If an OVF is used, the hardware settings are mandatory.
  - **memory** (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation options defined in the stack.
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Publishing a Machine Image

To publish an image, the valid keys are:

- `type` (mandatory): a string providing the machine image type to build. Default builder type for Nimbula: `Nimbula ESX`` or, ``Nimbula KVMK. To get the available builder type, please refer to [format](#)
- `account` (mandatory): an object providing the Nimbula cloud account information required to publish the built machine image.
- `description` (mandatory): a string providing the description that will be displayed for the machine image.
- `imageListName` (mandatory): a string providing the list name where to register the machine image. Note that this is the full pathname, for example `/usharesoft/administrator/myimages`. Machine images can be added to an image list to create a versioned selection of related machine images recording the versions of the image over its lifetime. An image maintainer can add newer versions of a machine image to the image list and can set the default version to be used when this image list is invoked in a launch plan to deploy VM instances
- `imageVersion` (mandatory): a string providing the version of the machine image being registered.

## Nimbula Cloud Account

Key: `account`

Used to authenticate the Nimbula platform. The Nimbula cloud account has the following valid keys:

- `type` (mandatory): a string providing the cloud account type. Default platform type for Nimbula is `Nimbula`. To get the available platform type, please refer to [platform](#)
- `file` (optional): a string providing the location of the account information. This can be a pathname (relative or absolute) or an URL.
- `endpoint` (mandatory): URL endpoint of the Nimbula cloud
- `name` (mandatory): a string providing the name of the cloud account. This name can be used in a builder section to reference the rest of the cloud account information.
- `password` (mandatory): a string providing the password used to to authenticate to Nimbula Director
- `username` (mandatory): a string providing the user used to authenticate to Nimbula Director. This is in the form of a URI, for example `/root/root`

---

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

---

## Example

The following example shows an Nimbula builder with all the information to build and publish a machine image to Nimbula.

```
{
  "builders": [
    {
      "type": "Nimbula KVM",
      "account": {
        "type": "Nimbula",
```

```
    "name": "My Nimbula Account",
    "endpoint": "http://20.20.20.201",
    "username": "myLogin",
    "password": "myPassWD"
  },
  "hardwareSettings": {
    "memory": 1024
  },
  "installation": {
    "diskSize": 2000
  },
  "imageListName": "/usharesoft/administrator/myimages",
  "imageVersion": "1",
  "description": "CentOS Core Image"
}
]
```

## Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `nimbula-account.json`.

```
{
  "accounts": [
    {
      "type": "Nimbula",
      "name": "My Nimbula Account",
      "endpoint": "http://20.20.20.201",
      "username": "myLogin",
      "password": "myPassWD"
    }
  ]
}
```

The builder section can either reference by using file or name.

Reference by file:

```
{
  "builders": [
    {
      "type": "Nimbula KVM",
      "account": {
        "file": "/home/joris/accounts/nimbula-account.json"
      },
      "hardwareSettings": {
        "memory": 1024
      },
      "installation": {
        "diskSize": 2000
      },
      "imageListName": "/usharesoft/administrator/myimages",
      "imageVersion": "1",
      "description": "CentOS Core Image"
    }
  ]
}
```

```

    }
  ]
}

```

Reference by name, note the cloud account must already be created by using `account create`.

```

{
  "builders": [
    {
      "type": "Nimbula KVM",
      "account": {
        "name": "My Nimbula Account"
      },
      "hardwareSettings": {
        "memory": 1024
      },
      "installation": {
        "diskSize": 2000
      },
      "imageListName": "/usharesoft/administrator/myimages",
      "imageVersion": "1",
      "description": "CentOS Core Image"
    }
  ]
}

```

## OpenStack

Default builder type: OpenStack QCOW2, OpenStack VMDK, OpenStack VHD or OpenStack VDI

Require Cloud Account: Yes

[www.openstack.org](http://www.openstack.org)

The OpenStack builder provides information for building and publishing the machine image to the OpenStack cloud platform. This builder supports KVM (OpenStack QCOW2), VMware (OpenStack VMDK), Microsoft (OpenStack VHD) or VirtualBox (OpenStack VDI) based images for Openstack. These builder types are the default names provided by UForge AppCenter.

**Note:** These builder type names can be changed by your UForge administrator. To get the available builder types, please refer to *format*

The OpenStack builder requires cloud account information to upload and register the machine image to the OpenStack platform.

The OpenStack builder section has the following definition:

```

{
  "builders": [
    {
      "type": "OpenStack QCOW2",
      ...the rest of the definition goes here.
    }
  ]
}

```

## Building a Machine Image

For building an image, the valid keys are:

- `type` (mandatory): a string providing the machine image type to build. Default builder type for OpenStack: `OpenStack QCOW2`, `OpenStack VMDK`, `OpenStack VDI` or `OpenStack VHD`. To get the available builder type, please refer to *format*
- `installation` (optional): an object providing low-level installation or first boot options. These override any installation options in the *Stack* section. The following valid keys for installation are:
- `diskSize` (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Publishing a Machine Image

To publish an image, the valid keys are:

- `type` (mandatory): a string providing the machine image type to build. Default builder type for OpenStack: `OpenStack QCOW2`, `OpenStack VMDK`, `OpenStack VDI` or `OpenStack VHD`. To get the available builder type, please refer to *format*
- `account` (mandatory): an object providing the OpenStack cloud account information required to publish the built machine image.
- `displayName` (mandatory): a string providing the name of the image that will be displayed.
- `tenantName` (mandatory for keystone v2.0): a string providing the name of the tenant to register the machine image to. This value is only required if the cloud account's `keystoneVersion` is `v2.0`
- `keystoneDomain` (mandatory for keystone v3.0): a string providing the keystone domain to publish this machine image to.
- `keystoneProject` (mandatory for keystone v3.0): a string providing the keystone project to publish this machine image to.
- `publicImage` (optional): a boolean to determine if the machine image is public (for other users to use for provisioning).

## OpenStack Cloud Account

Key: `account`

Used to authenticate the OpenStack platform.

The OpenStack cloud account has the following valid keys:

- `type` (mandatory): a string providing the cloud account type. Default platform type for Openstack is `OpenStack`. To get the available platform type, please refer to *platform*
- `name` (mandatory): a string providing the name of the cloud account. This name can be used in a builder section to reference the rest of the cloud account information.
- `glanceUrl` (mandatory): a string providing the API URL endpoint of the OpenStack glance service. For example: <http://www.example.com/v1/>
- `keystoneUrl` (mandatory): a string providing the URL endpoint for the OpenStack keystone service to authenticate with. For example: <http://www.example.com:5000>

- `keystoneVersion` (mandatory): a string providing the keystone version of the OpenStack platform. Refer to [Valid Keystone Versions](#) for the valid keystone versions.
- `login` (mandatory): a string providing the user for authenticating to keystone for publishing images
- `password` (mandatory): a string providing the password for authenticating to keystone for publishing images
- `file` (optional): a string providing the location of the account information. This can be a pathname (relative or absolute) or an URL.

---

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

---

### Valid Keystone Versions

- `v2.0`: Keystone version 2.0
- `3.0`: Keystone version 3.0

### Example

The following example shows an OpenStack builder with all the information to build and publish a machine image to OpenStack.

```
{
  "builders": [
    {
      "type": "OpenStack QCOW2",
      "account": {
        "type": "OpenStack",
        "name": "My OpenStack Account",
        "glanceUrl": "http://myglanceurl/v1/",
        "keystoneUrl": "http://mykeystoneurl:9292/v1",
        "keystoneVersion": "v2.0",
        "login": "mylogin",
        "password": "mypassword"
      },
      "displayName": "OpenStack_testHammr",
      "tenantName": "mytenant"
    }
  ]
}
```

### Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `openstack-account.json`.

```
{
  "accounts": [
    {
      "type": "OpenStack",
```

```
"name": "My OpenStack Account",
"glanceUrl": "http://myglanceurl/v1/",
"keystoneUrl": "http://mykeystoneurl:9292/v1",
"keystoneVersion": "http://mykeystoneversion:5000/v2.0",
"login": "mylogin",
"password": "mypassword"
}
]
```

The builder section can either reference by using file or name.

Reference by file:

```
{
  "builders": [
    {
      "type": "OpenStack QCOW2",
      "account": {
        "file": "/path/to/openstack-account.json"
      },
      "displayName": "OpenStack_testHammr",
      "tenantName": "mytenant"
    }
  ]
}
```

Reference by name, note the cloud account must already be created by using `account create`.

```
{
  "builders": [
    {
      "type": "OpenStack QCOW2",
      "account": {
        "name": "My OpenStack Account"
      },
      "displayName": "OpenStack_testHammr",
      "tenantName": "mytenant"
    }
  ]
}
```

## Outscale

Default builder type: Outscale

Require Cloud Account: Yes

[outscale.com](https://outscale.com)

The Outscale builder provides information for building and publishing the machine image for Outscale cloud platform. The Outscale builder requires cloud account information to upload and register the machine image to Outscale cloud. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---



The Outscale builder section has the following definition:

```
{
  "builders": [
    {
      "type": "Outscale",
      ...the rest of the definition goes here.
    }
  ]
}
```

## Building a Machine Image

For building an image, the valid keys are:

- **type (mandatory):** a string providing the machine image type to build. Default builder type for Outscale: Outscale. To get the available builder type, please refer to *format*
- **installation (optional):** an object providing low-level installation or first boot options. These override any installation
  - **diskSize (mandatory):** an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. If the machine image is to be stored in Amazon S3, the maximum disk size is 10GB, otherwise if this is an EBS-backed machine image the maximum disk size is 1TB.

## Publishing a Machine Image

To publish an image, the valid keys are:

- **type (mandatory):** a string providing the machine image type to build. Default builder type for Outscale: Outscale. To get the available builder type, please refer to *format*
- **account (mandatory):** an object providing the AWS cloud account information required to publish the built machine image.
- **zone (mandatory):** a string providing the region where to publish the machine image. See below for valid regions.

## Valid Regions

The following regions are supported:

- **ap-northeast-1:** Asia Pacific (Tokyo) Region
- **ap-southeast-1:** Asia Pacific (Singapore) Region
- **eu-west-1:** EU (Ireland) Region
- **sa-east-1:** South America (Sao Paulo) Region
- **us-east-1:** US East (North Virginia) Region
- **us-west-1:** US West (North california) Region
- **us-west-2:** US West (Oregon) Region

## Outscale Cloud Account

Key: `account` Used to authenticate to Outscale cloud platform.

The Outscale cloud account has the following valid keys:

- `type` (mandatory): a string providing the cloud account type. Default platform type for Outscale: `Outscale`. To get the available platform type, please refer to [platform](#)
- `name` (mandatory): a string providing the name of the cloud account. This name can be used in a `builder` section to reference the rest of the cloud account information.
- `secretAccessKey` (mandatory): A string providing your Outscale secret access key
- `accessKey` (mandatory): A string providing your Outscale access key id

---

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

---

## Example

The following example shows an amazon builder with all the information to build and publish a machine image to Amazon EC2.

```
{
  "builders": [
    {
      "type": "Outscale",
      "account": {
        "type": "Outscale",
        "name": "My Outscale Account",
        "accessKey": "789456123ajdiewjd",
        "secretAccessKey": "ks30hPeH1xWqilJ04"
      },
      "installation": {
        "diskSize": 10240
      },
      "zone": "eu-west-2",
      "description": "centos-template"
    }
  ]
}
```

## Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `outscale-account.json`.

```
{
  "accounts": [
    {
      "type": "Outscale",
      "name": "My Outscale Account",
```

```

    "accessKey": "789456123ajdiewjd",
    "secretAccessKey": "ks30hPeHlxWqilJ04"
  }
]
}

```

The builder section can either reference by using file or name.

Reference by file:

```

{
  "builders": [
    {
      "type": "Outscale",
      "account": {
        "file": "/home/joris/accounts/outscale-account.json"
      },
      "installation": {
        "diskSize": 10240
      },
      "region": "eu-west-2",
      "s3bucket": "centos-template"
    }
  ]
}

```

Reference by name, note the cloud account must already be created by using `account create`.

```

{
  "builders": [
    {
      "type": "Outscale",
      "account": {
        "name": "My Outscale Account"
      },
      "installation": {
        "diskSize": 10240
      },
      "region": "eu-west-2",
      "s3bucket": "centos-template"
    }
  ]
}

```

## Suse Cloud

Default builder type: SUSE Cloud

Require Cloud Account: Yes

### SuseCloud

The SuseCloud builder provides information for building and publishing the machine image to the SuseCloud cloud platform. The SuseCloud builder requires cloud account information to upload and register the machine image to the SuseCloud platform. This builder type is the default name provided by UForge AppCenter.

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please

refer to *format*

---

The SuseCloud builder section has the following definition:

```
{
  "builders": [
    {
      "type": "SUSE Cloud",
      ...the rest of the definition goes here.
    }
  ]
}
```

### Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Suse Cloud: SUSE Cloud. To get the available builder type, please refer to *format*
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

### Publishing a Machine Image

To publish an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Suse Cloud: SUSE Cloud. To get the available builder type, please refer to *format*
- **account** (mandatory): an object providing the SuseCloud cloud account information required to publish the built machine image.
- **description** (optional): an object providing the description of the machine image.
- **imageName** (mandatory): a string providing the name of the image that will be displayed.
- **keystoneDomain** (mandatory for keystone v3.0): a string providing the keystone domain to publish this machine image to.
- **keystoneProject** (mandatory for keystone v3.0): a string providing the keystone project to publish this machine image to.
- **paraVirtMode** (optional) a boolean to determine if the machine should be provisioned in para-virtualised mode. By default, machine images are provisioned in full-virtualised mode
- **publicImage** (optional): a boolean to determine if the machine image is public (for other users to use for provisioning).
- **tenant** (mandatory for keystone v2.0): a string providing the name of the tenant to register the machine image to. This value is only required if the cloud account's `keystoneVersion` is `v2.0`

## SuseCloud Cloud Account

Key: `account` Used to authenticate the SuseCloud platform.

The SuseCloud cloud account has the following valid keys:

- `type` (mandatory): a string providing the machine image type to build. Default builder type for Suse Cloud, `Suse Cloud`. To get the available builder type, please refer to *format*
- `file` (optional): a string providing the location of the account information. This can be a pathname (relative or absolute) or an URL.
- `endpoint` (mandatory): a string providing the API URL endpoint of the SuseCloud glance service. For example: `http://www.example.com:9292`
- `keystoneEndpoint` (mandatory): a string providing the URL endpoint for the SuseCloud keystone service to authenticate with. For example: `http://www.example.com:5000`
- `keystoneVersion` (mandatory): a string providing the keystone version of the SuseCloud platform. Refer to *Valid Keystone Versions* for the valid keystone versions.
- `name` (mandatory): a string providing the name of the cloud account. This name can be used in a builder section to reference the rest of the cloud account information.
- `password` (mandatory): a string providing the password for authenticating to keystone for publishing images
- `username` (mandatory): a string providing the user for authenticating to keystone for publishing images

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

## Valid Keystone Versions

- `v2.0`: Keystone version 2.0
- `3.0`: Keystone version 3.0

## Example

The following example shows a SuseCloud builder with all the information to build and publish a machine image to SuseCloud.

```
{
  "builders": [
    {
      "type": "Suse Cloud",
      "account": {
        "type": "Suse Cloud",
        "name": "My SuseCloud Account",
        "endpoint": "http://ow2-04.xsalto.net:9292/v1",
        "keystoneEndpoint": "http://ow2-04.xsalto.net:5000/v2.0",
        "username": "test",
        "password": "password"
      },
      "tenant": "opencloudware",
      "imageName": "joris-test",
    }
  ]
}
```

```
    "description": "CentOS Core template."
  }
]
}
```

## Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `susecloud-account.json`.

```
{
  "accounts": [
    {
      "type": "Suse Cloud",
      "name": "My SuseCloud Account",
      "endpoint": "http://ow2-04.xsalto.net:9292/v1",
      "keystoneEndpoint": "http://ow2-04.xsalto.net:5000/v2.0",
      "username": "test",
      "password": "password"
    }
  ]
}
```

The builder section can either reference by using file or name.

Reference by file:

```
{
  "builders": [
    {
      "type": "Suse Cloud",
      "account": {
        "file": "/home/joris/accounts/susecloud-account.json"
      },
      "tenant": "opencloudware",
      "imageName": "joris-test",
      "description": "CentOS Core template."
    }
  ]
}
```

Reference by name, note the cloud account must already be created by using `account create`.

```
{
  "builders": [
    {
      "type": "Suse Cloud",
      "account": {
        "name": "My SuseCloud Account"
      },
      "tenant": "opencloudware",
      "imageName": "joris-test",
      "description": "CentOS Core template."
    }
  ]
}
```

```
]
}
```

## VMware vCloud Director

Default builder type: VMware vCloud Director

Require Cloud Account: Yes

The VMware vCloud Director builder provides information for building VMware vCloud Director compatible machine images. The VMware VCD builder section has the following definition:

```
{
  "builders": [
    {
      "type": "VMware vCloud Director",
      ...the rest of the definition goes here.
    }
  ]
}
```

## Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for VMware vCloud Director: VMware vCloud Director. To get the available builder type, please refer to [format](#)
- **hardwareSettings** (mandatory): an object providing hardware settings to be used for the machine image. The following keys are valid:
  - **memory** (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
  - **hwType** (optional): an integer providing the hardware type for the machine image. This is the VMware hardware type: 4 (ESXi>3.x), 7 (ESXi>4.x) or 9 (ESXi>5.x)
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation options in the [Stack](#) section. The following valid keys for installation are:
- **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Publishing a Machine Image

To publish an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for VMware vCloud Director: VMware vCloud Director. To get the available builder type, please refer to [format](#)
- **account** (mandatory): an object providing the vCloud Director cloud account information required to publish the built machine image.
- **catalogName** (mandatory): a string providing the name of the catalog to register the machine image. Catalogs contain references to virtual systems and media images.

- `imageName` (mandatory): a string providing the name of the machine image to display in VCD.
- `orgName` (mandatory): a string providing the name of the vCloud organization to register the machine image.

### vCloud Director Cloud Account

Key: `account` Used to authenticate to VMware vCloud Director.

The VCD cloud account has the following valid keys:

- `type` (mandatory): a string providing the cloud account type. Default platform type for VMware vCloud Director: VMware vCloud Director. To get the available platform type, please refer to [platform](#)
- `hostname` (mandatory): a string providing the fully-qualified hostname or IP address of the vCloud Directory platform.
- `password` (mandatory): a string providing the password to use to authenticate to the vCloud Director platform
- `port` (optional): an integer providing the vCloud Director platform port number (by default: 443 is used).
- `proxyHostname` (optional): a string providing the fully qualified hostname or IP address of the proxy to reach the vCloud Director platform.
- `proxyPort` (optional): an integer providing the proxy port number to use to reach the vCloud Director platform.
- `username` (mandatory): a string providing the user name to use to authenticate to the vCloud Director platform

---

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

---

### Example

The following example shows a VCD builder with all the information to build and publish a machine image to VMware vCloud Director.

```
{
  "builders": [
    {
      "type": "VMware vCloud Director",
      "account": {
        "type": "VMware vCloud Director",
        "name": "My VCD Account",
        "hostname": "10.1.1.2",
        "username": "joris",
        "password": "mypassword"
      },
      "hardwareSettings": {
        "memory": 1024,
        "hwType": 7
      },
      "installation": {
        "diskSize": 10240
      },
      "orgName": "HQProd",
      "catalogName": "myCatalog",
      "imageName": "CentOS Core"
    }
  ]
}
```



```

    }
  ]
}
```

## Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `vcd-account.json`.

```

{
  "accounts": [
    {
      "type": "VMware vCloud Director",
      "name": "My VCD Account",
      "hostname": "10.1.1.2",
      "username": "joris",
      "password": "mypassword"
    }
  ]
}
```

The builder section can either reference by using file or name.

Reference by file:

```

{
  "builders": [
    {
      "type": "VMware vCloud Director",
      "account": {
        "file": "/home/joris/accounts/vcd-account.json"
      },
      "hardwareSettings": {
        "memory": 1024,
        "hwType": 7
      },
      "installation": {
        "diskSize": 10240
      },
      "orgName": "HQProd",
      "catalogName": "myCatalog",
      "imageName": "CentOS Core"
    }
  ]
}
```

Reference by name, note the cloud account must already be created by using `account create`.

```

{
  "builders": [
    {
      "type": "VMware vCloud Director",
      "account": {
        "name": "My VCD Account"
      },
      "hardwareSettings": {
```

```
    "memory": 1024,  
    "hwType": 7  
  },  
  "installation": {  
    "diskSize": 10240  
  },  
  "orgName": "HQProd",  
  "catalogName": "myCatalog",  
  "imageName": "CentOS Core"  
}  
]  
}
```

## 10.2.2 Virtual Targets

### citrix-xen

Default builder type: Citrix Xen Server

Require Cloud Account: No

This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The Citrix XenServer builder provides information for building XenServer compatible machine images.

The Citrix XenServer builder section has the following definition:

```
{  
  "builders": [  
    {  
      "type": "Citrix Xen Server",  
      ...the rest of the definition goes here.  
    }  
  ]  
}
```

### Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Citrix Xen Server: Citrix Xen Server. To get the available builder type, please refer to *format*
- **hardwareSettings** (mandatory): an object providing hardware settings to be used for the machine image. The following
  - **memory** (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation options in the *Stack* section. The following valid keys for installation are:

- `diskSize` (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Example

The following example shows a Citrix XenServer builder.

```
{
  "builders": [
    {
      "type": "Citrix Xen Server",
      "hardwareSettings": {
        "memory": 1024
      }
    }
  ]
}
```

## Hyper-V

Default builder type: Hyper-V

Require Cloud Account: No

This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The Hyper-V builder provides information for building Hyper-V compatible machine images. The Hyper-V builder section has the following definition:

```
{
  "builders": [
    {
      "type": "Hyper-V",
      ...the rest of the definition goes here.
    }
  ]
}
```

## Building a Machine Image

For building an image, the valid keys are:

- `type` (mandatory): a string providing the machine image type to build. Default builder type for Hyper-V: Hyper-V. To get the available builder type, please refer to *format*
- `hardwareSettings` (mandatory): an object providing hardware settings to be used for the machine image. The following
  - `memory` (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).

- **installation (optional):** an object providing low-level installation or first boot options. These override any installation options.
  - **diskSize (mandatory):** an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

### Example

The following example shows a Hyper-V builder.

```
{
  "builders": [
    {
      "type": "Hyper-V",
      "hardwareSettings": {
        "memory": 1024
      }
    }
  ]
}
```

### KVM

Default builder type: KVM

Require Cloud Account: No

This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The KVM builder provides information for building KVM (Kernel-based Virtual Machine) compatible machine images. The KVM builder section has the following definition:

```
{
  "builders": [
    {
      "type": "KVM",
      ...the rest of the definition goes here.
    }
  ]
}
```

### Building a Machine Image

For building an image, the valid keys are:

- **type (mandatory):** a string providing the machine image type to build. Default builder type for KVM: KVM. To get the available builder type, please refer to *format*
- **hardwareSettings (mandatory):** an object providing hardware settings to be used for the machine image. The following

- `memory` (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
- **installation (optional): an object providing low-level installation or first boot options. These override any installation options.**
- `diskSize` (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Example

The following example shows a KVM builder.

```
{
  "builders": [
    {
      "type": "KVM",
      "hardwareSettings": {
        "memory": 1024
      }
    }
  ]
}
```

## OVF

Default builder type: OVF or OVA

Require Cloud Account: No

The OVF builder provides information for building OVF (Open Virtualization Format) compatible machine images. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The OVF builder section has the following definition:

```
{
  "builders": [
    {
      "type": "OVF or OVA",
      ...the rest of the definition goes here.
    }
  ]
}
```

The OVF builder has the following valid keys:

- `type` (mandatory): a string providing the machine image type to build. Default builder type for OVF: OVF or OVA. To get the available builder type, please refer to *format*
- **hardwareSettings (mandatory): an object providing hardware settings to be used for the machine image. The following**

- `memory` (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
- `hwType` (optional): an integer providing the hardware type for the machine image. This is the VMware hardware type: 4 (ESXi>3.x), 7 (ESXi>4.x) or 9 (ESXi>5.x)
- **installation (optional): an object providing low-level installation or first boot options. These override any installation**
- `diskSize` (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

### Example

The following example shows an OVF builder.

```
{
  "builders": [
    {
      "type": "OVF or OVA",
      "hardwareSettings": {
        "memory": 1024,
        "hwType": 7
      }
    }
  ]
}
```

### QCOW2

Default builder type: QCOW2

Require Cloud Account: No

The QCOW2 builder provides information for building a QCOW2 compatible machine images. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The QCOW2 builder section has the following definition:

```
{
  "builders": [
    {
      "type": "QCOW2",
      ...the rest of the definition goes here.
    }
  ]
}
```

## Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for QCOW2: QCOW2. To get the available builder type, please refer to [format](#)
- **hardwareSettings** (mandatory): an object providing hardware settings to be used for the machine image. The following keys are valid:
  - **memory** (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation options defined in the stack.
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Example

The following example shows a QCOW2 builder.

```
{
  "builders": [
    {
      "type": "QCOW2",
      "hardwareSettings": {
        "memory": 1024
      }
    }
  ]
}
```

## Raw

Default builder type: Raw Virtual Disk

Require Cloud Account: No

The Raw builder provides information for building a Raw Virtual Disk compatible machine images. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to [format](#)

---

The Raw builder section has the following definition:

```
{
  "builders": [
    {
      "type": "Raw Virtual Disk",
      ...the rest of the definition goes here.
    }
  ]
}
```

```
]
}
```

### Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for RAW: Raw Virtual Disk. To get the available builder type, please refer to [format](#)
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation options defined in the stack.
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

### Example

The following example shows a Raw builder.

```
{
  "builders": [
    {
      "type": "Raw Virtual Disk",
      "hardwareSettings": {
        "memory": 1024
      }
    }
  ]
}
```

### Vagrant Base Box

Default builder type: Vagrant Base Box

Require Cloud Account: No

The Vagrant builder provides information for building Vagrant base-box machine images. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to [format](#)

---

The Vagrant builder section has the following definition:

```
{
  "builders": [
    {
      "type": "Vagrant Base Box",
      ...the rest of the definition goes here.
    }
  ]
}
```



```
]
}
```

## Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Vagrant: `Vagrant Base Box`. To get the available builder type, please refer to [format](#)
- **hardwareSettings** (mandatory): an object providing hardware settings to be used for the machine image. The following keys are valid:
  - **memory** (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation options defined in the stack.
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.
- **osUser** (optional): a string providing the user used to authenticate to the vagrant base box. This is mandatory if the base box is private, otherwise this value is ignored and the user `vagrant` is used.
- **publicBaseBox** (optional): a boolean determining if the base box to be created is a public base box or not. When public, the os user is `vagrant` and uses the public (insecure) public key as described in the vagrant documentation
- **sshKey** (optional): an object providing the public SSH key information to add to the base box. The object contains:
  - **name** (mandatory): a string providing the name of the public ssh key
  - **publicKey** (mandatory): a string providing the public ssh key. A public key must begin with string `ssh-rsa` or `ssh-dss`. This is mandatory if the base box is private, otherwise this value is ignored and the [default public ssh key](#) is used.

---

**Note:** You can get copies of the SSH keypairs for public base boxes [here](#).

---

## Examples

### Basic Example: Public Base Box

The following example shows a Vagrant builder creating a public base box.

```
{
  "builders": [
    {
      "type": "Vagrant Base Box",
      "hardwareSettings": {
        "memory": 1024
      },
      "publicBaseBox": true
    }
  ]
}
```

```
}  
]  
}
```

## Private Base Box Example

The following example shows a Vagrant builder for a private base box (note, that the values used is the same for building a public base box)

```
{  
  "builders": [  
    {  
      "type": "Vagrant Base Box",  
      "hardwareSettings": {  
        "memory": 1024  
      },  
      "publicBaseBox": false,  
      "osUser": "vagrant",  
      "sshKey": {  
        "name": "myVagrantPublicKey",  
        "publicKey": "ssh-rsa_  
→AAAAB3NzaC1yc2EAAAABIwAAAQEA6NF8iallvQVp22WDkTkyrtvp9eWW6A8YVr+kz4TjGYe7gHzIw+niNltGEFHxD8+v1I2YJ6  
→vagrant insecure public key"  
      }  
    }  
  ]  
}
```

## VirtualBox

Default builder type: VirtualBox

Require Cloud Account: No

### Oracle VirtualBox

The VirtualBox builder provides information for building Oracle VM VirtualBox compatible machine images. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The VirtualBox builder section has the following definition:

```
{  
  "builders": [  
    {  
      "type": "VirtualBox",  
      ...the rest of the definition goes here.  
    }  
  ]  
}
```

## Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for VirtualBox: `VirtualBox`. To get the available builder type, please refer to [format](#)
- **hardwareSettings** (mandatory): an object providing hardware settings to be used for the machine image. The following keys are valid:
  - **memory** (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation options defined in the stack.
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Example

The following example shows a VirtualBox builder.

```
{
  "builders": [
    {
      "type": "VirtualBox",
      "hardwareSettings": {
        "memory": 1024
      }
    }
  ]
}
```

## VHD

Default builder type: VHD

Require Cloud Account: No

The VHD builder provides information for building VHD (Virtual Hard Disk) compatible machine images. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to [format](#)

---

The VHD builder section has the following definition:

```
{
  "builders": [
    {
      "type": "VHD",
      ...the rest of the definition goes here.
    }
  ]
}
```

```
]
}
```

## Building a Machine Image

For building an image, the valid keys are:

- `type` (mandatory): a string providing the machine image type to build. Default builder type for VHD: `VHD`. To get the available builder type, please refer to [format](#)
- **`hardwareSettings` (mandatory): an object providing hardware settings to be used for the machine image. The following keys are valid:**
  - `memory` (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
- **`installation` (optional): an object providing low-level installation or first boot options. These override any installation options defined in the stack.**
  - `diskSize` (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Example

The following example shows a VHD builder.

```
{
  "builders": [
    {
      "type": "VHD",
      "hardwareSettings": {
        "memory": 1024
      }
    }
  ]
}
```

## VMware Workstation

Default builder type: `VMware Server`

Require Cloud Account: No

The VMware Workstation builder provides information for building VMware Workstation compatible machine images. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to [format](#)

---

The VMware Workstation builder section has the following definition:

```
{
  "builders": [
    {
      "type": "VMware Server",
      ...the rest of the definition goes here.
    }
  ]
}
```

The VMware Workstation builder has the following valid keys:

- **type (mandatory):** a string providing the machine image type to build. Default builder type for VMware Workstation: `VMware Server`. To get the available builder type, please refer to [format](#)
- **hardwareSettings (mandatory):** an object providing hardware settings to be used for the machine image. The following keys are valid:
  - **memory (mandatory):** an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
  - **hwType (optional):** an integer providing the hardware type for the machine image. This is the VMware hardware type: 4 (ESXi>3.x), 7 (ESXi>4.x) or 9 (ESXi>5.x)
- **installation (optional):** an object providing low-level installation or first boot options. These override any installation options defined in the stack.
  - **diskSize (mandatory):** an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Example

The following example shows an VMware Workstation builder.

```
{
  "builders": [
    {
      "type": "VMware Server",
      "hardwareSettings": {
        "memory": 1024,
        "hwType": 7
      }
    }
  ]
}
```

## VMware vSphere vCenter

Builder type: `VMware vCenter`

Require Cloud Account: Yes

The VMware vCenter builder provides information for building VMware vSphere vCenter compatible machine images. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The VMware vCenter builder section has the following definition:

```
{
  "builders": [
    {
      "type": "VMware vCenter",
      ...the rest of the definition goes here.
    }
  ]
}
```

## Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for VMware vCenter: `VMware vCenter`. To get the available builder type, please refer to *format*
- **hardwareSettings** (mandatory): an object providing hardware settings to be used for the machine image. The following keys are valid:
  - **memory** (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
  - **hwType** (optional): an integer providing the hardware type for the machine image. This is the VMware hardware type: 4 (ESXi>3.x), 7 (ESXi>4.x) or 9 (ESXi>5.x)
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation options defined in the stack.
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

## Publishing a Machine Image

To publish an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for VMware vCenter: `VMware vCenter`. To get the available builder type, please refer to *format*
- **account** (mandatory): an object providing the VMware vSphere vCenter cloud account information required to publish the built machine image.
- **clusterName** (mandatory): a string providing the name of the cluster to register the machine image.
- **datacenterName** (mandatory): a string providing the name of the datacenter to register the machine image.
- **datastore** (mandatory): a string providing the name of the datastore where to store the machine image.
- **displayName** (mandatory): a string providing the name of the machine image to display in VMware vSphere vCenter.
- **network** (optional): a string providing the virtual network name.

## vSphere vCenter Cloud Account

Key: `account` Used to authenticate to VMware vSphere vCenter.

The vCenter cloud account has the following valid keys:

- `type` (mandatory): a string providing the cloud account type. Default platform type for VMware vCenter: `VMware vCenter`. To get the available platform type, please refer to [platform](#)
- `name` (mandatory): a string providing the name of the cloud account. This name can be used in a builder section to reference the rest of the cloud account information.
- `login` (mandatory): a string providing the user name to use to authenticate to the VMware vSphere vCenter platform
- `password` (mandatory): a string providing the password to use to authenticate to the VMware vSphere vCenter platform
- `hostname` (mandatory): a string providing the fully-qualified hostname or IP address of the VMware vSphere vCenter platform.
- `proxyHostname` (optional): a string providing the fully qualified hostname or IP address of the proxy to reach the VMware vSphere vCenter platform.
- `port` (optional): an integer providing the VMware vSphere vCenter platform port number (by default: 443 is used).
- `proxyPort` (optional): an integer providing the proxy port number to use to reach the VMware vSphere vCenter platform.

**Note:** In the case where `name` or `file` is used to reference a cloud account, all the other keys are no longer required in the account definition for the builder.

## Example

The following example shows an vCenter builder with all the information to build and publish a machine image to VMware vSphere vCenter.

```
{
  "builders": [
    {
      "type": "VMware vCenter",
      "account": {
        "type": "VMware vCenter",
        "name": "My VCenter account",
        "login": "mylogin",
        "password": "mypassword",
        "hostname": "myhostname",
        "proxyHostname": "myproxyHostname",
        "proxyPort": "6354",
        "port": "443"
      },
      "hardwareSettings": {
        "memory": 1024,
        "hwType": 7
      },
      "installation": {
```

```
    "diskSize": 10240
  },
  "clusterName": "cluster",
  "datacenterName": "datacentername",
  "datastore": "esx2esx_datastore",
  "displayName": "test_Hammr",
  "network": "VM_Network"
}
]
```

## Referencing the Cloud Account

To help with security, the cloud account information can be referenced by the builder section. This example is the same as the previous example but with the account information in another file. Create a json file `vcenter-account.json`.

```
{
  "accounts": [
    {
      "type": "VMware vCenter",
      "name": "My VCenter account",
      "login": "mylogin",
      "password": "mypassword",
      "hostname": "myhostname",
      "proxyHostname": "myproxyHostname",
      "proxyPort": "6354",
      "port": "443"
    }
  ]
}
```

The builder section can either reference by using file or name.

Reference by file:

```
{
  "builders": [
    {
      "type": "VMware vCenter",
      "account": {
        "file": "/home/joris/accounts/vcenter-account.json"
      },
      "hardwareSettings": {
        "memory": 1024,
        "hwType": 7
      },
      "installation": {
        "diskSize": 10240
      },
      "clusterName": "cluster",
      "datacenterName": "datacentername",
      "datastore": "esx2esx_datastore",
      "displayName": "test_Hammr",
      "network": "VM_Network"
    }
  ]
}
```



```
]
}
```

Reference by name, note the cloud account must already be created by using `account create`.

```
{
  "builders": [
    {
      "type": "VMware vCenter",
      "account": {
        "name": "My vCenter Account"
      },
      "hardwareSettings": {
        "memory": 1024,
        "hwType": 7
      },
      "installation": {
        "diskSize": 10240
      },
      "clusterName": "cluster",
      "datacenterName": "datacentername",
      "datastore": "esx2esx_datastore",
      "displayName": "test_Hammr",
      "network": "VM_Network"
    }
  ]
}
```

## Xen

Default builder type: Xen

Require Cloud Account: No

The Xen builder provides information for building a Xen.org compatible machine images. This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to *format*

---

The Xen builder section has the following definition:

```
{
  "builders": [
    {
      "type": "Xen",
      ...the rest of the definition goes here.
    }
  ]
}
```

## Building a Machine Image

For building an image, the valid keys are:

- **type** (mandatory): a string providing the machine image type to build. Default builder type for Xen: `Xen`. To get the available builder type, please refer to [format](#)
- **hardwareSettings** (mandatory): an object providing hardware settings to be used for the machine image. The following
  - **memory** (mandatory): an integer providing the amount of RAM to provide to an instance provisioned from the machine image (in MB).
- **installation** (optional): an object providing low-level installation or first boot options. These override any installation
  - **diskSize** (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

### Example

The following example shows a Xen builder.

```
{
  "builders": [
    {
      "type": "Xen",
      "hardwareSettings": {
        "memory": 1024
      }
    }
  ]
}
```

## 10.2.3 Physical Targets

### ISO

Default builder type: `ISO`

Require Cloud Account: No

This builder type is the default name provided by UForge AppCenter.

---

**Note:** This builder type name can be changed by your UForge administrator. To get the available builder types, please refer to [format](#)

---

The ISO builder provides information for building ISO images.

The ISO builder section has the following definition:

```
{
  "builders": [
    {
      "type": "ISO",
      ...the rest of the definition goes here.
    }
  ]
}
```

---

## Building a Machine Image

For building an image, the valid keys are:

- `type` (mandatory): a string providing the machine image type to build. Default builder type for ISO: `ISO`. To get the available builder type, please refer to [format](#)
- **`installation` (optional): an object providing low-level installation or first boot options. These override any installation**
  - `diskSize` (mandatory): an integer providing the disk size of the machine image to create. Note, this overrides any disk size information in the stack. This cannot be used if an advanced partitioning table is defined in the stack.

### Example

The following example shows an ISO builder.

```
{
  "builders": [
    {
      "type": "ISO"
    }
  ]
}
```



## Migrating a Live System

Hammr allows you to migrate a live system. The key steps in migrating your system are:

1. Scan your system, this sends a scan report back to your UForge account
2. From the scan report, build and publish a machine image
3. Finally provision an instance from the published machine image (effectively migrating the system)

Optionally, at step #2, you can import the scan report to create a template. This allows you to change the content prior to building a machine image.

First, scan the system you wish to migrate by running `scan run`. This “deep scans” the live system, reporting back the meta-data of every file and package that makes up the running workload. The following is an example of a scan of a live system:

[illegible]

Once you have run the scan of your system, a scan report is saved to your account. You can list your scans by running `scan list`. The output will be similar to the following. As you can see below, the “scanExample” is the group name. The actual scan appears below it with “Scan #1“ added to the name. If you run the scan on the same machine again, the scan number will increase. This allows you to compare scans.

```
$ hammr scan list
Getting scans for [root] ...

+-----+-----+-----+-----+
| Id | Name | Status | Distribution |
+-----+-----+-----+-----+
| 133 | scanExample | | Debian 6 x86_64 |
+-----+-----+-----+-----+
| 149 | scanExample Scan #1 | Done | |
+-----+-----+-----+-----+

Found 1 scans
```

If you are simply moving your system from one cloud provider to another, you can then simply build a machine image from this scan by running `scan build`. The following is an example which builds a machine image from a scan:

[illegible]

In the example above, you will need to have a JSON file which defines the `builder` parameters for the type of machine image you want to create. This is NOT a full template configuration file, but just the builders parameters. For example:

```
{
  "builders": [
    {
      "type": "openstack",
      "hardwareSettings": {
        "memory": 1024
      },
      "installation": {
        "diskSize": 2000
      },
      "account": "Openstack OW2",
      "tenant": "opencloudware",
      "imageName": "scan-test",
      "publicImage": "no"
    }
  ]
}
```

## 11.1 Updating a Template Before Migrating

Hammr also allows you to modify or update packages that are part of the system you want to migrate. To do this, you first need to transform the scan report to a template. You can then modify any part of this new template prior to building the final machine image used for migration.

To create a template from your scan you will need to run `scan import`. The following is an example that shows a scan conversion to a template within UForge.







### 12.1 hammr-3.6 1.1 (2016-16-12)

#### Evolutions:

- Improve project setup.py clean command
- Add travis CI build for the project
- Add an optional parameter to allow to change the ssh port used to connect on the running machine
- Ability to use a directory as source for bundle

#### Bug fixes:

- Scan build method generate exception
- Fix typo in os help message
- Some fixes on documentation
- A name including a space cannot be specified with hammr template clone
- Account list gives the class name instead of the account type
- The usage of the pkg parameter of hammr os search is not correct

### 12.2 hammr-3.6 0.1 (2016-07-01)

#### Evolutions:

- **Compatibility with UForge AppCenter 3.6**
  - Target formats and target platforms support
  - Builder part has been updated
- Hammr documentation now inside github repository

- Improve setup.py clean command
- Hammr uses a new download utility

Bug fixes:

- Ability to specify a timezone inside “updateTo” field for “stack”

Known issues:

- Amazon AWS format is not working
- Bootscript order is mandatory (incompatibility with Hammr on UForge AppCenter 3.5.1)
- Not possible to use both hammr 0.2.x and hammr-3.6 on the same system

### 12.3 0.2.5.10 (2016-04-29)

Evolutions:

- Added hammr documentation to the github project
- Add support for uforge-python-sdk 3.5.1.4: ability to do streaming download

Bug fixes:

- `hammr scan run` fails when searching scan on uforge
- Using a relative path to the json file seems to invoke an error
- hammr image publish returns exception if there is no cloud account

### 12.4 0.2.5.9 (2015-12-18)

Evolutions:

- Add compatibility with Outscale format

### 12.5 0.2.5.8 (2015-11-20)

Evolutions:

- Increase timeout value

Bug fixes:

- Cannot install hammr because of a dependency error (issue #45)

### 12.6 0.2.5.7 (2015-09-21)

Evolutions:

- Reuse existing bundles option while importing templates (issue #26)
- Template export directory clean up (issue #43)

## 12.7 0.2.5.6 (2015-08-29)

Bug fixes:

- Fix issue #38 - Could be nice to have a way to specify credentials file from command line
- Fix issue #31 - “hammr scan delete” deletes every scan if scan id and scan instance id is the same.

## 12.8 0.2.5.5 (2015-08-04)

Evolutions:

- Add support for lxc and targz for Hammr

Bug fixes:

- Fix issue #34 - Exit status of Hammr command
- Enhance the error message if an issue occurs when trying to download a machine image