
kncloudevents Documentation

Release 0.1.0

The Elegant Monkeys

Jun 16, 2019

Contents

1	kncloudevents	1
2	Installation	3
3	Usage	5
4	Reference	7
5	Contributing	9
6	Indices and tables	13
	Index	15

kncloudevents is a HTTP server for listening to Knative Eventing messages

- Documentation: <https://kncloudevents.readthedocs.io>.
- Source code: <https://github.com/elegantmonkeys/python-kncloudevents>
- Bug reports: <https://github.com/elegantmonkeys/python-kncloudevents/issues>

1.1 Description

A lightweight package for doing the heavy lifting of setting up a `cloudevents` server for you! Just provide your function and it will be called on every new event with the event data.

1.2 Notes

- Uses the [official cloudevents sdk for Python](#) for parsing the incoming data
- Inspired by the [Knative Golang project](#)

1.3 Credits

This package was created with [Cookiecutter](#) and the [audreyr/cookiecutter-pypackage](#) project template.

2.1 Stable release

To install kncloudevents, run this command in your terminal:

```
$ pip install kncloudevents
```

This is the preferred method to install kncloudevents, as it will always install the most recent stable release.

If you don't have `pip` installed, this [Python installation guide](#) can guide you through the process.

2.2 From sources

The sources for knative-python can be downloaded from the [Github repo](#).

You can either clone the public repository:

```
$ git clone git@github.com:elegantmonkeys/python-kncloudevents.git
```

Or download the [tarball](#):

```
$ curl -OL https://github.com/elegantmonkeys/python-kncloudevents/tarball/master
```

Once you have a copy of the source, you can install it with:

```
$ python setup.py install
```


To use kncloudevents in a project:

```
import os
from kncloudevents import CloudeventsServer
import logging

logging.basicConfig(stream=sys.stdout, level=logging.INFO)

def run_event(event):
    try:
        logging.info(event.Data())
    except Exception as e:
        logging.error(f"Unexpected error: {e}")
        raise

client = CloudeventsServer()
client.start_receiver(run_event)
```


4.1 CloudeventsServer

class `kncloudevents.CloudeventsServer` (*port=8080*)

Listen for incoming HTTP cloudevents requests.

cloudevents request is simply a HTTP Post request following a well-defined of how to pass the event data.

start_receiver (*func*)

Start listening to HTTP requests

Parameters **func** (*cloudevent -> none*) – the callback to call upon a cloudevents request

Contributions are welcome, and they are greatly appreciated! Every little bit helps, and credit will always be given. You can contribute in many ways:

5.1 Types of Contributions

5.1.1 Report Bugs

Report bugs at <https://github.com/elegantmonkeys/python-kncloudevents/issues>.

If you are reporting a bug, please include:

- Your operating system name and version.
- Any details about your local setup that might be helpful in troubleshooting.
- Detailed steps to reproduce the bug.

5.1.2 Fix Bugs

Look through the GitHub issues for bugs. Anything tagged with “bug” and “help wanted” is open to whoever wants to implement it.

5.1.3 Implement Features

Look through the GitHub issues for features. Anything tagged with “enhancement” and “help wanted” is open to whoever wants to implement it.

5.1.4 Write Documentation

kncloudevents could always use more documentation, whether as part of the official kncloudevents docs, in docstrings, or even on the web in blog posts, articles, and such.

5.1.5 Submit Feedback

The best way to send feedback is to file an issue at <https://github.com/elegantmonkeys/python-kncloudevents/issues>.

If you are proposing a feature:

- Explain in detail how it would work.
- Keep the scope as narrow as possible, to make it easier to implement.
- Remember that this is a volunteer-driven project, and that contributions are welcome :)

5.2 Get Started!

Ready to contribute? Here's how to set up *kncloudevents* for local development.

1. Fork the *kncloudevents* repo on GitHub.
2. Clone your fork locally:

```
$ git clone git@github.com:elegantmonkeys/python-kncloudevents.git
```

3. Install your local copy into a virtualenv. Assuming you have virtualenvwrapper installed, this is how you set up your fork for local development:

```
$ mkvirtualenv python-kncloudevents
$ cd python-kncloudevents/
$ python setup.py develop
```

4. Create a branch for local development:

```
$ git checkout -b name-of-your-bugfix-or-feature
```

Now you can make your changes locally.

5. When you're done making changes, check that your changes pass flake8 and the tests, including testing other Python versions with tox:

```
$ flake8 kncloudevents tests
$ python setup.py test or py.test
$ tox
```

To get flake8 and tox, just pip install them into your virtualenv.

6. Commit your changes and push your branch to GitHub:

```
$ git add .
$ git commit -m "Your detailed description of your changes."
$ git push origin name-of-your-bugfix-or-feature
```

7. Submit a pull request through the GitHub website.

5.3 Pull Request Guidelines

Before you submit a pull request, check that it meets these guidelines:

1. The pull request should include tests.
2. If the pull request adds functionality, the docs should be updated. Put your new functionality into a function with a docstring, and add the feature to the list in README.rst.
3. The pull request should work for Python 3.5 and 3.6, and for PyPy. Check https://travis-ci.org/elegantmonkeys/python-kncloudevents/pull_requests and make sure that the tests pass for all supported Python versions.

5.4 Tips

To run a subset of tests:

```
$ python -m unittest tests.test_kncloudevents
```

5.5 Deploying

A reminder for the maintainers on how to deploy. Make sure all your changes are committed (including an entry in HISTORY.rst). Then run:

```
$ bumpversion patch # possible: major / minor / patch
$ git push
$ git push --tags
```

Travis will then deploy to PyPI if tests pass.

CHAPTER 6

Indices and tables

- `genindex`
- `modindex`
- `search`

C

CloudeventsServer (*class in knloudevents*), 7

S

start_receiver() (*knloudevents.CloudeventsServer method*), 7