

---

# **libgithub Documentation**

***Release 1.0***

**Matt Sparks**

October 05, 2014



<b>1 Requirements and Installation</b>	<b>3</b>
<b>2 Usage</b>	<b>5</b>
<b>3 API</b>	<b>7</b>
3.1 libgithub.Badge . . . . .	7



libgithub is a JavaScript library for displaying GitHub data on websites. It uses the [GitHub API v2](#).

Currently libgithub only generates ‘badges’, which look something like this:

😊 [msparks/alphasign](#)



Matt Sparks committed **3d3b96e078** about 8 months ago

📦 "Changing setup.py version to 1.0"

(0 added, 0 removed, 1 modified) [Show files](#)

😊 [msparks/alphasign](#)



Matt Sparks committed **155b779d73** about 8 months ago

📦 "Adding a much-needed complete example"

(0 added, 0 removed, 3 modified) [Hide files](#)

**Modified:**

- alphasign/\_\_init\_\_.py
- alphasign/string.py
- docs/index.rst

😊 [msparks/alphasign](#)



Matt Sparks committed **82f40a10e1** about 8 months ago

📦 "Documenting speeds"

(0 added, 0 removed, 1 modified) [Show files](#)

libgithub is available from [GitHub](#) as a single JavaScript file. A ‘minified’ version of the library is available as well. CSS styles are also included with the distribution and can be customized.



---

## Requirements and Installation

---

libgithub relies on several other JavaScript libraries to function properly, all of which are conveniently included in the libgithub distribution:

- [jQuery](#)
- [humane.js](#)
- [date.js](#)
- [md5.js](#)

These libraries must be loaded along with `libgithub.min.js` in the HTML files which use libgithub.

Thus, to load libgithub for use, simply include in your HTML file:

```
<script type="text/javascript" src="jquery.js"></script>
<script type="text/javascript" src="humane.js"></script>
<script type="text/javascript" src="date.js"></script>
<script type="text/javascript" src="md5.js"></script>
<script type="text/javascript" src="libgithub.min.js"></script>
```

You may need to modify the file paths as appropriate, depending on your installation. To get a style similar to the screenshot above, you will also need to include the CSS stylesheet, using something like:

```
<link type="text/css" rel="stylesheet" href="css/libgithub.css" />
```

Again, modify the path as appropriate. This stylesheet references images also included with the libgithub distribution that are expected to be in a directory called ‘img’ by default.



---

## Usage

---

Here is a simple example for creating a badge:

```
<script type="text/javascript">
$(window).load(function () {
  var b = new libgithub.Badge('msparks', 'alphasign');
  b.targetIs('#commit');
});
</script>

<div id="commit"></div>
```

This example uses jQuery to create a badge when the window loads. The output is displayed in the element selected by '#commit', which is the `<div id="commit">`.

To display multiple commits or change other various settings, see the [libgithub.Badge API](#).



## 3.1 libgithub.Badge

This class is used to create and display GitHub commit badges.

### 3.1.1 Reference

**class libgithub.Badge (username, repo[, commitId])**  
Construct a new badge object.

#### Parameters

- **username** – GitHub username
- **repo** – Repository name
- **commitId** – ref name or commit ID (default: ‘master’)

**gravatarSize ()**  
Get the Gravatar size. Defaults to 60 pixels.

**gravatarSizeIs (size)**  
Set the Gravatar size.

**Parameters** **size** – width of Gravatar in pixels

**startHidden ()**  
Current startHidden setting. If true, the file list is hidden when the badge is created. Defaults to true.

**startHiddenIs (setting)**  
Set the startHidden setting.

**Parameters** **setting** – new setting. True = hide file list, False = show file list

**target ()**  
Get the current target.

**targetIs (selector)**  
Set the target HTML element via a jQuery selector.

This issues a request to GitHub for commit data and creates a callback to display the badge.

The badge is appended to the inside of the element selected by the selector.

**Parameters** **selector** – string selector to find the target HTML element. See the [jQuery documentation](#) for more information about valid selectors.

### 3.1.2 Examples

Here is a simple example for creating a badge:

```
<script type="text/javascript">
$(window).load(function () {
  var b = new libgithub.Badge('msparks', 'alphasign');
  b.targetIs('#commit');
});
</script>

<div id="commit"></div>
```

To show the file list by default, simply toggle the `startHidden` setting like so:

```
var b = new libgithub.Badge('msparks', 'alphasign');
b.startHiddenIs(false);
b.targetIs('#commit');
```

The `commitId` parameter in the badge constructor can be a ref of any kind: a specific commit ID, partial or complete; a branch name; or a tag name. Creating a badge for a specific commit is easy:

```
var b = new libgithub.Badge('msparks', 'alphasign', 'c5f6c7a2');
b.targetIs('#commit');
```

## G

gravatarSize() (libgithub.Badge method), [7](#)  
gravatarSizeIs() (libgithub.Badge method), [7](#)

## L

libgithub.Badge (built-in class), [7](#)

## S

startHidden() (libgithub.Badge method), [7](#)  
startHiddenIs() (libgithub.Badge method), [7](#)

## T

target() (libgithub.Badge method), [7](#)  
targetIs() (libgithub.Badge method), [7](#)