
MyCapytains Documentation

Release 0.0.1

Thibault Clérice

Aug 21, 2017

Contents

1 Simple Example of what it does	3
2 Installation and Requirements	5
3 Contents	7
3.1 MyCapytain's Main Objects Explained	7
3.2 Project using MyCapytain	20
3.3 Working with Local CapiTainS XML File	20
3.4 Known issues and recommendations	22
3.5 MyCapytain API Documentation	22
3.6 Benchmarks	146
Python Module Index	149

MyCapytain is a python library which provides a large set of methods to interact with Text Services API such as the Canonical Text Services, the Distributed Text Services. It also provides a programming interface to exploit local textual resources developed according to the Capitains Guidelines.

CHAPTER 1

Simple Example of what it does

The following code and example is badly displayed at the moment on Github. We recommend you to go to <http://mycapytain.readthedocs.org>

On Leipzig DH Chair's Canonical Text Services API, we can find the Epigrammata of Martial. This texts are identified by the identifier "urn:cts:latinLit:phi1294.phi002.perseus-lat2". We want to have some information about this text so we are gonna ask the API to give its metadata to us :

Listing 1.1: example.py from the Github Repository

```
1  from MyCapytain.resolvers.cts.api import HttpCtsResolver
2  from MyCapytain.retrievers.cts5 import CTS
3  from MyCapytain.common.constants import Mimetypes
4
5  # We set up a resolver which communicates with an API available in Leipzig
6  resolver = HttpCtsResolver(CTS("http://cts.dh.uni-leipzig.de/api/cts/"))
7  # We require some metadata information
8  textMetadata = resolver.getMetadata("urn:cts:latinLit:phi1294.phi002.perseus-lat2")
9  # Texts in CTS Metadata have one interesting property : its citation scheme.
10 # XmlCtsCitation are embedded objects that carries information about how a text can_
11 # be quoted, what depth it has
11 print(type(textMetadata), [citation.name for citation in textMetadata.citation])
```

This query will return the following information :

```
<class 'MyCapytain.resources.collections.cts.Text'> ['book', 'poem', 'line']
```

```
12 # Now, we want to retrieve the first line of poem seventy two of the second book
13 passage = resolver.getTextualNode("urn:cts:latinLit:phi1294.phi002.perseus-lat2",
14 # subreference="2.72.1")
14 # And we want to have its content exported to plain text and have the siblings of_
15 # this passage (previous and next line)
15 print(passage.export(Mimetypes.PLAINTEXT), passage.siblingsId)
```

And we will get

```
Hesterna factum narratur, Postume, cena
```

If you want to play more with this, like having a list of what can be found in book three, you could go and do

```
16 poemsInBook3 = resolver.getReffs("urn:cts:latinLit:phi1294.phi002.perseus-lat2",  
17     ↪subreference="3")  
print(poemsInBook3)
```

Which would be equal to :

```
['3.1', '3.2', '3.3', '3.4', '3.5', '3.6', '3.7', '3.8', '3.9', '3.10', '3.11', '3.12  
↪', '3.13', ...]
```

Now, it's your time to work with the resource ! See the CapiTainS Classes page on ReadTheDocs to have a general introduction to MyCapytain objects !

CHAPTER 2

Installation and Requirements

The best way to install MyCapytain is to use pip. MyCapytain tries to support Python over 3.4.

The work needed for supporting Python 2.7 is mostly done, however, since 2.0.0, we are giving up on ensuring that MyCapytain will be compatible with Python < 3 while accepting PR which would help doing so.

```
pip install MyCapytain
```

If you prefer to use setup.py, you should clone and use the following

```
git clone https://github.com/Capitains/MyCapytain.git
cd MyCapytain
python setup.py install
```


CHAPTER 3

Contents

MyCapytain's Main Objects Explained

Exportable Parent Classes

Description

`MyCapytain.common.base.Exportable`

The Exportable class is visible all across the library. It provides a common, standardized way to retrieve in an API fashion to what can an object be exported and to exports it. Any exportable object should have an EXPORT_TO constant variable and include a `__export__(output, **kwargs)` methods if it provides an export type.

Example

The following code block is a mere example of how to implement Exportable and what are its responsibilities. Exportable typically loops over all the parents class of the current class until it find one exportable system matching the required one.

```
1 from MyCapytain.common.constants import Mimetypes
2 from MyCapytain.common.base import Exportable
3
4
5 class Sentence(Exportable):
6     """ This class represent a Sentence
7
8         :param content: Content of the sentence
9         """
10
11     # EXPORT_TO is a list of Mimetype the object is capable to export to
12     EXPORT_TO = [
13         Mimetypes.PLAINTEXT, Mimetypes.XML.Std
14     ]
14     DEFAULT_EXPORT = Mimetypes.PLAINTEXT
```

```

15
16     def __init__(self, content):
17         self.content = content
18
19     def __export__(self, output=None, **kwargs):
20         """ Export the collection item in the Mimetype required.
21
22         :param output: Mimetype to export to (Uses MyCapytain.common.utils.Mimetypes)
23         :type output: str
24         :return: Object using a different representation
25         """
26
27         if output == Mimetypes.PLAINTEXT:
28             return self.content
29         elif output == Mimetypes.XML.Std:
30             return "<sentence>{}</sentence>".format(self.content)
31
32     class TEISentence(Sentence):
33         """ This class represent a Sentence but adds some exportable accepted output
34
35         :param content: Content of the sentence
36         """
37
38         EXPORT_TO = [
39             Mimetypes.JSON.Std
40         ]
41
42     def __export__(self, output=None, **kwargs):
43         """ Export the collection item in the Mimetype required.
44
45         :param output: Mimetype to export to (Uses MyCapytain.common.utils.Mimetypes)
46         :type output: str
47         :return: Object using a different representation
48         """
49
50         if output == Mimetypes.JSON.Std:
51             return {"http://www.tei-c.org/ns/1.0/sentence": self.content}
52         elif output == Mimetypes.XML.Std:
53             return "<sentence xmlns=\"http://www.tei-c.org/ns/1.0\">{}</sentence>".format(self.content)
54
55     s = Sentence("I love Martial's Epigrammata")
56     print(s.export(Mimetypes.PLAINTEXT))
57     # I love Martial's Epigrammata
58     print(s.export()) # Defaults to PLAINTEXT
59     # I love Martial's Epigrammata
60     print(s.export(Mimetypes.XML.Std))
61     # <sentence>I love Martial's Epigrammata</sentence>
62
63     tei = TEISentence("I love Martial's Epigrammata")
64     print(tei.export(Mimetypes.PLAINTEXT))
65     # I love Martial's Epigrammata
66     print(tei.export()) # Defaults to PLAINTEXT
67     # I love Martial's Epigrammata
68     print(tei.export(Mimetypes.JSON.Std))
69     # {"http://www.tei-c.org/ns/1.0/sentence": I love Martial's Epigrammata}
70     print(tei.export(Mimetypes.XML.Std)) # Has been rewritten by TEISentence
71     # <sentence xmlns="http://www.tei-c.org/ns/1.0">I love Martial's Epigrammata</
72     # <sentence>
```

```

71 try:
72     print(tei.export(Mimetypes.XML.RDF))
73 except NotImplementedError as error:
74     print(error)
75 # Raise the error and prints "Mimetype application/rdf+xml has not been implemented"
# for this resource"

```

Retrievers

MyCapytain.retrievers.prototypes.API

Description

Retrievers are classes that help build requests to API and return standardized responses from them. There is no real perfect prototypes. The only requirements for a Retriever is that its query function should returns string only. It is not the role of the retrievers to parse response. It is merely to facilitate the communication to remote API most of the time.

Recommendations

For Textual API, it is recommended to implement the following requests

- getTextNode(textId[str], subreference[str], prevnext[bool], metadata[bool])
- getMetadata(objectId[str], **kwargs)
- getSiblings(textId[str], subreference[str])
- getReffs(textId[str], subreference[str], depth[int])

Example of implementation : CTS 5

MyCapytain.retrievers.cts5.HttpCtsRetriever

```

1 from MyCapytain.retrievers.cts5 import HttpCtsRetriever
2
3 # We set up a retriever which communicates with an API available in Leipzig
4 retriever = HttpCtsRetriever("http://cts.dh.uni-leipzig.de/api/cts/")
5 # We require a passage : passage is now a Passage object
6 passage = retriever.getPassage("urn:cts:latinLit:phi1294.phi002.perseus-lat2:1.1")
7 # Passage is now equal to the string content of http://cts.dh.uni-leipzig.de/api/cts/
# request=GetPassage&urn=urn:cts:latinLit:phi1294.phi002.perseus-lat2:1.1
8 print(passage)
9
10 """
11 <GetPassage><request><requestName>GetPassage</requestName><requestUrn>
# urn:cts:latinLit:phi1294.phi002.perseus-lat2:1.1</requestUrn></request>
12 <reply><urn>urn:cts:latinLit:phi1294.phi002.perseus-lat2:1.1</urn><passage><TEI>
13 <text n="urn:cts:latinLit:phi1294.phi002.perseus-lat2" xml:id="stoa0045.stoa0"><body>
14 <div type="edition" n="urn:cts:latinLit:phi1294.phi002.perseus-lat2" xml:lang="lat">
15 <div type="textpart" subtype="book" n="1"><div type="textpart" subtype="poem" n="1">
16 <head>I</head>
17 <l n="1">Hic est quem legis ille, quem requiris, </l>
18 <l n="2">Toto notus in orbe Martialis </l>
19 <l n="3">Argutis epigrammaton libellis: <pb/></l>

```

```
20 <l n="4">Cui, lector studiose, quod dedisti </l>
21 <l n="5">Viventi decus atque sentienti, </l>
22 <l n="6">Rari post cineres habent poetae. </l>
23 </div></div></div></body></text></TEI></passage></reply>
24   "" "
```

Text and Passages

Description

Hierarchy

The generic idea of both Text and Passage's classes is that they inherit from a longer trail of text bearing object that complexified over different features. The basic is

- *TextualElement* is an object which can bear Metadata and Collection information. It has a `.text` property and is exportable
- *TextualNode* inherits from `NodeId` and unlike `TextualElement`, `TextualNode` is part of a graph of `CitableObject`. It bears informations about its siblings, parents, children.
- *TextualGraph* is a bit interactive : you can query for children nodes and get descendant references of the object.
- *InteractiveTextualNode* is completely interactive . You can browse the graph by accessing the `.next` property for example : it should then return an `InteractiveTextualNode` as well
- *CtsNode* has two unique methods more as well as a `urn` property.
- From *CtsNode* we find *CitableText* and *Passage*, which represents complete and portion of a Text. The main difference is that *CitableText* has no parents, no siblings.

Fig. 3.1: Prototype of Texts from `:module:'MyCapytain.resources.prototypes.text'`. `NodeId` and `Exportable` are respectively from `:module:'MyCapytain.common.reference'` and `:module:'MyCapytain.common.base'`.

Objectives

Text and Passages object have been built around `InteractiveTextualNode` which fills the main purpose of MyCapytain : being able to interact with citable, in-graph texts that are retrieve through web API or local files. Any implementation should make sure that the whole set of navigation tool are covered. Those are :

Tree Identifiers(Returns str Identifiers)	Tree Navigations (Returns InteractiveTextualNode or children class)	Retrieval Methods	Other
prevId	prev	.getTextualNode(subreference)	id : TextualNode Identifier [str]
nextId	nextId	.getReffs(subreference[optional])	metadata : Metadata [Metadata]
siblingsId [tuple[str]]	siblings [tuple[InteractiveTextualNode]]		
parentId	parent		citation : Citation Information [Citation]
childIds [list[str]]	children [list[InteractiveTextualNode]]		text : String Representation of the text without annotation
firstId	first		.export()
lastId	last		

The base module

The base module contains special implementations : they technically do not support interactive methods but provides generic parsing and export methods for specific type of contents such as TEI XML object or other formats such as json, csv, treebank objects in the future.

The TEIResource for example requires the object to be set up with a resource parameters that will be furtherparsed using lxml. From there, it provides export such as plain/text, TEI XML, nested dictionaries or even anlxml etree interface.

Implementation example : HTTP API Passage work

```

1  from MyCapytain.retrievers.cts5 import HttpCtsRetriever
2  from MyCapytain.resources.texts.remote.cts import CtsText
3
4  # We set up a retriever which communicates with an API available in Leipzig
5  retriever = HttpCtsRetriever("http://cts.dh.uni-leipzig.de/api/cts/")
6
7  # Given that we have other examples that shows how to work with text,
8  # we will focus here on playing with the graph functionality of texts implementations.
9  # We are gonna retrieve a text passage and the retrieve all its siblings in different
10 # fashion#
11 # The main point is to find all children of the same parent.
12 # The use case could be the following : some one want to retrieve the full text_
13 # around a citation
14 # To enhance the display a little.
15
16 # We will work with the line 7 of poem 39 of book 4 of Martial's Epigrammata
17 # The text is urn:cts:latinLit:phi1294.phi002.perseus-lat2
18 text = CtsText(retriever=retriever, urn="urn:cts:latinLit:phi1294.phi002.perseus-lat2
19
20 # We retrieve up the passage
21 target = text.getTextualNode(subreference="4.39.7")
22 print(target.text)
23 """
24 Nec quae Callaico linuntur auro,
```

```
23 """
24
25 # The parent way :
26 # - get to the parent,
27 # - retrieve each node,
28 # - print only the one which are not target
29
30 parent = target.parent
31 for node in parent.children:
32     if node.id != target.id:
33         print("{}\t{}".format(node.id, node.text))
34     else:
35         print("-----Original Node-----")
36
37 """
38 4.39.1      Argenti genus omne comparasti,
39 4.39.2      Et solus veteres Myronos artes,
40 4.39.3      Solus Praxitelus manum Scopaeque,
41 4.39.4      Solus Phidiaci toreuma caeli,
42 4.39.5      Solus Mentoreos habes labores.
43 4.39.6      Nec desunt tibi vera Gratiana,
44 -----Original Node-----
45 4.39.8      Nec mensis anaglypta de paternis.
46 4.39.9      Argentum tamen inter omne miror
47 4.39.10     Quare non habeas, Charine, purum.
48 """
49
50 print("\n\nSecond Method\n\n")
51
52 # We are gonna do another way this time :
53 # - get the previous until we change parent
54 # - get the next until we change parent
55
56 parentId = node.parentId
57 # Deal with the previous ones
58 current = target.prev
59 while current.parentId == parentId:
60     print("{}\t{}".format(current.id, current.text))
61     current = current.prev
62
63 print("-----Original Node-----")
64
65 # Deal with the next ones
66 current = target.next
67 while current.parentId == parentId:
68     print("{}\t{}".format(current.id, current.text))
69     current = current.next
70 """
71 4.39.6      Nec desunt tibi vera Gratiana,
72 4.39.5      Solus Mentoreos habes labores.
73 4.39.4      Solus Phidiaci toreuma caeli,
74 4.39.3      Solus Praxitelus manum Scopaeque,
75 4.39.2      Et solus veteres Myronos artes,
76 4.39.1      Argenti genus omne comparasti,
77 -----Original Node-----
78 4.39.8      Nec mensis anaglypta de paternis.
79 4.39.9      Argentum tamen inter omne miror
80 4.39.10     Quare non habeas, Charine, purum.
```

81
82 " " "

Other Example

See MyCapytain.resources.texts.local

Collection

Description

Collections are the metadata containers object in MyCapytain. Unlike other object, they will never contain textual content such as Texts and Passages but will in return help you browse through the catalog of one APIs collection and identify manually or automatically texts that are of relevant interests to you.

The main information that you should be interested in are :

- Collections are children from Exportable. As of 2.0.0, any collection can be exported to JSON DTS.
- Collections are built on a hierarchy. They have children and descendants
- Collections have identifiers and title (Main name of what the collection represents : if it's an author, it's her name, a title for a book, a volume label for a specific edition, etc.)
- Collections can inform the machine if it represents a readable object : if it is readable, it means that using its identifier, you can query for passages or references on the same API.

Main Properties

- Collection().id : Identifier of the object
- Collection().get_label(lang[Optional]) : Title of the object
- Collection().readable : If True, means that the Collection().id can be used in GetReffs or GetTextualNode queries
- Collection().members : Direct children of the object
- Collection().descendants : Direct and Indirect children of the objects
- Collection().readableDescendants : Descendants that have .readable as True
- Collection().export() : Export Method
- Collection().metadata : Metadata object that contain flat descriptive localized information about the object.

Implementation : CTS Collections

Note: For a recap on what Textgroup means or any CTS jargon, go to <http://capitains.github.io/pages/vocabulary>

CTS Collections are divided in 4 kinds : TextInventory, TextGroup, Work, Text. Their specificity is that the hierarchy of these objects are predefined and always follow the same order. They implement a special export (MyCapytain.common.constants.Mimetypes.XML.CTS) which basically exports to the XML Text Inventory Format that one would find making a GetCapabilities request.

CapiTainS CTS Collections implement a parents property which represent a list of parents where .parents' order is equal to `Text.parents = [Work(), TextGroup(), TextInventory()]`.

Their finale implementation accepts to parse resources through the `resource=` named argument.

Example

```
1 from MyCapytain.retrievers.cts5 import HttpCtsRetriever
2 from MyCapytain.resources.collections.cts import XmlCtsTextInventoryMetadata,_
3     XmlCtsWorkMetadata
4 from MyCapytain.common.constants import Mimetypes
5 from pprint import pprint
6
7 """
8 In order to have a real life example,
9 we are gonna query for data in the Leipzig CTS API
10 We are gonna query for metadata about Seneca who
11 is represented by urn:cts:latinLit:stoa0255
12
13 To retrieve data, we are gonna make a GetMetadata query
14 to the CTS Retriever.
15 """
16 retriever = HttpCtsRetriever("http://cts.dh.uni-leipzig.de/api/cts/")
17 # We store the response (Pure XML String)
18 response = retriever.getMetadata(objectId="urn:cts:latinLit:stoa0255")
19
20 """
21 From here, we actually have the necessary data, we can now
22 play with collections. TextInventory is the main collection type that is needed to
23 parse the whole response.
24 """
25 inventory = XmlCtsTextInventoryMetadata.parse(resource=response)
26 # What we are gonna do is print the title of each descendant :
27 for descendant in inventory.descendants:
28     # Metadatum resolve any non-existing language ("eng", "lat") to a default one
29     # Putting default is just making that clear
30     print(descendant.get_label())
31
32 """
33 You should see in there things such as
34 - "Seneca, Lucius Annaeus" (The TextGroup or main object)
35 - "de Ira" (The Work object)
36 - "de Ira, Moral essays Vol 2" (The Edition specific Title)
37
38 We can now see other functions, such as the export to JSON DTS.
39 Collections have a unique feature built in : they allow for
40 accessing an item using its key as if it were a dictionary :
41 The identifier of a De Ira is urn:cts:latinLit:stoa0255.stoa0110
42 """
43 deIra = inventory["urn:cts:latinLit:stoa0255.stoa010"]
44 assert isinstance(deIra, XmlCtsWorkMetadata)
45 pprint(deIra.export(output=Mimetypes.JSON.DTS.Std))
46 # you should see a DTS representation of the work
47
48 """
49 What we might want to do is to browse metadata about seneca's De Ira
50 Remember that CtsCollections have a parents attribute !
```

```

50 """
51 for descAsc in deIra.descendants + [deIra] + deIra.parents:
52     # We filter out Textgroup which has an empty Metadata value
53     if not isinstance(descAsc, HttpCtsRetriever):
54         print(
55             descAsc.metadata.export(output=Mimetypes.JSON.Std)
56         )
57 """
58 And of course, we can simply export deIra to CTS XML format
59 """
60 print(deIra.export(Mimetypes.XML.CTS))

```

Dispatchers

Description

Dispatcher are tools to be used to organize semi-automatically resources, most likely in the context of a resolver retrieving data from local directories.

Dispatcher has following properties :

- methods -> [tuple(Callable()->Bool, str)]
- add(func[Callable()], inventory_name[str])
- inventory(inventory_name[str]) -> @decorator
- dispatch(collection[Collection], **kwargs)

Implementation

```
class MyCapytain.resolvers.utils.CollectionDispatcher(collection,           de-
                                                     default_inventory_name=None)
```

Collection Dispatcher provides a utility to divide automatically texts and collections into different collections

Parameters

- **collection** – The root collection
- **default_inventory_name** – The default name of the default collection

add(func, inventory_name)

Register given function as a filter.

If this function “func” returns True when given an object, said object will be dispatched to Collection(inventory_name)

Parameters

- **func** – Callable
- **inventory_name** – Identifier of the collection to dispatch to

dispatch(collection, **kwargs)

Dispatch a collection using internal filters

Parameters

- **collection** – Collection object
- **kwargs** – Additional keyword arguments that could be used by internal filters

Returns None

Raises

inventory (*inventory_name*)

Decorator to register filters for given inventory. For a function “abc”, it has the same effect

Parameters *inventory_name* –

Returns

```
tic = CtsTextInventoryCollection()
latin = CtsTextInventoryMetadata("urn:perseus:latinLit", parent=tic)
latin.set_label("Classical Latin", "eng")
dispatcher = CollectionDispatcher(tic)

@dispatcher.inventory("urn:perseus:latinLit")
def dispatchLatinLit(collection, path=None, **kwargs):
    if collection.id.startswith("urn:cts:latinLit:"):
        return True
    return False
```

methods

List of methods to dispatch resources.

Each element is a tuple with two elements :

- First one is the inventory identifier to dispatch to
- Second one is a function which, if returns true, will activate dispatching to given

Return type List

Example

```
1 from MyCapytain.resolvers.cts.local import CtsCapitainsLocalResolver
2 from MyCapytain.resolvers.utils import CollectionDispatcher
3 from MyCapytain.common.constants import Mimetypes
4 from MyCapytain.resources.collections.cts import XmlCtsTextInventoryMetadata
5 from MyCapytain.resources.prototypes.cts.inventory import CtsTextInventoryCollection
6
7 # We set up a main collection
8 tic = CtsTextInventoryCollection()
9 # We register sub collection we want to dispatch to
10 latin = XmlCtsTextInventoryMetadata("urn:perseus:latinLit", parent=tic)
11 latin.set_label("Classical Latin", "eng")
12 farsi = XmlCtsTextInventoryMetadata("urn:perseus:farsiLit", parent=tic)
13 farsi.set_label("Farsi", "eng")
14 gc = XmlCtsTextInventoryMetadata("urn:perseus:greekLit", parent=tic)
15 gc.set_label("Ancient Greek", "eng")
16 gc.set_label("Grec Ancien", "fre")
17
18 # We create the dispatcher with the root collection
19 dispatcher = CollectionDispatcher(tic)
20
21 # And we record function for each given repository
22 # We could have two function dispatching for the same repository !
23 @dispatcher.inventory("urn:perseus:latinLit")
24 def dispatchLatinLit(collection, path=None, **kwargs):
```

```

25     if collection.id.startswith("urn:cts:latinLit:"):
26         return True
27     return False
28
29 @dispatcher.inventory("urn:perseus:farsiLit")
30 def dispatchfFarsiLit(collection, path=None, **kwargs):
31     if collection.id.startswith("urn:cts:farsiLit:"):
32         return True
33     return False
34
35 @dispatcher.inventory("urn:perseus:greekLit")
36 def dispatchGreekLit(collection, path=None, **kwargs):
37     if collection.id.startswith("urn:cts:greekLit:"):
38         return True
39     return False
40
41 # We set up a resolver which parses local file
42 NautilusDummy = CtsCapitainsLocalResolver(
43     resource=[
44         "./tests/testing_data/latinLit2"
45     ],
46     # We give it the dispatcher
47     dispatcher=dispatcher
48 )
49
50 # If we want to read the main repository, we will have all children
51 all = NautilusDummy.getMetadata()
52
53 print(len(all.readableDescendants)) # 25 is the number of edition and translation
54 print([m.id for m in all.members]) # Direct members are dispatched-in collections
55 print(
56     all["urn:cts:latinLit:phi1294"] == all["urn:perseus:latinLit"][
57     "urn:cts:latinLit:phi1294"]
58 ) # Is true because they are dispatched this way
59
60 try:
61     all["urn:perseus:greekLit"]["urn:cts:latinLit:phi1294"]
62 except KeyError:
63     print("But this won't work because the object has been dispatched to latinLit !")
64
65 print(len(all["urn:perseus:greekLit"].readableDescendants)) # Is 6 because there is
66     ↪ 6 recorded texts in __cts__
67 print(len(all["urn:perseus:latinLit"].readableDescendants)) # Is 19 because there is
68     ↪ 6 recorded texts in __cts__

```

Resolvers

Description

Resolvers were introduced in 2.0.0b0 and came as a solution to build tools around Text Services APIs where you can seamlessly switch a resolver for another and not changing your code, join together multiple resolvers, etc. The principle behind resolver is to provide native python object based on API-Like methods which are restricted to four simple commands :

- getTextualNode(textId[str], subreference[str], prevnext[bool], metadata[bool]) -> Passage

- `getMetadata(objectId[str], **kwargs) -> Collection`
- `getSiblings(textId[str], subreference[str]) -> tuple([str, str])`
- `getReffs(textId[str], subreference[str], depth[int]) -> list([str])`

These function will always return objects derived from the major classes, *i.e.* Passage and Collection for the two firsts and simple collections of strings for the two others. Resolvers fills the hole between these base objects and the original retriever objects that were designed to return plain strings from remote or local APIs.

The base functions are represented in the prototype, and only `getMetadata` might be expanded in terms of arguments depending on what filtering can be offered. Though, any additional filter has not necessarily effects with other resolvers.

Historical Perspective

The original incentive to build resolvers was the situation with retrievers, in the context of the Nautilus API and Nemo UI : Nemo took a retriever as object, which means that, based on the prototype, Nemo was retrieving string objects. That made sense as long as Nemo was running with HTTP remote API because it was actually receiving string objects which were not even (pre-)processed by the Retriever object. But since Nautilus was developed (a fully native python CTS API), we had the situation where Nemo was parsing strings that were exported from python etree objects by Nautilus which parsed strings. Introducing Resolvers, we managed to avoid this double parsing effect in any situation : MyCapytain now provides a default class to provide access to querying text no matter what kind of transactions there is behind the Python object. At the same time, Resolvers provide a now unified system to retrieve texts independently from the retriever standard type (CTS, DTS, Proprietary, etc.).

Prototype

```
class MyCapytain.resolvers.prototypes.Resolver
    Resolver provide a native python API which returns python objects.
```

Initiation of resolvers are dependent on the implementation of the prototype

```
getMetadata (objectId=None, **filters)
    Request metadata about a text or a collection
```

Parameters

- `objectId (str)` – Object Identifier to filter on
- `filters (dict)` – Kwarg parameters.

Returns Collection

```
getReffs (textId, level=1, subreference=None)
```

Retrieve the siblings of a textual node

Parameters

- `textId (str)` – CtsTextMetadata Identifier
- `level (int)` – Depth for retrieval
- `subreference (str)` – CapitainsCtsPassage Reference

Returns List of references

Return type [str]

```
getSiblings (textId, subreference)
```

Retrieve the siblings of a textual node

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **subreference** (*str*) – CapitainsCtsPassage Reference

Returns Tuple of references**Return type** (*str, str*)**getTextualNode** (*textId, subreference=None, prevnext=False, metadata=False*)

Retrieve a text node from the API

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **subreference** (*str*) – CapitainsCtsPassage Reference
- **prevnext** (*boolean*) – Retrieve graph representing previous and next passage
- **metadata** (*boolean*) – Retrieve metadata about the passage and the text

Returns CapitainsCtsPassage**Return type** *CapitainsCtsPassage***Example**

```

1  from MyCapytain.resolvers.cts.api import HttpCtsResolver
2  from MyCapytain.retrievers.cts5 import HttpCtsRetriever
3  from MyCapytain.common.constants import Mimetypes, XPATH_NAMESPACES
4
5  # We set up a resolver which communicates with an API available in Leipzig
6  resolver = HttpCtsResolver(HttpCtsRetriever("http://cts.dh.uni-leipzig.de/api/cts"))
7  # We require a passage : passage is now a Passage object
8  # This is an entry from the Smith Myth Dictionary
9  # The inner methods will resolve to the URI http://cts.dh.uni-leipzig.de/api/cts?
10 #→request=GetPassage&urn=urn:cts:pdlrefwk:viaf88890045.003.perseus-eng1:A.abaeus_1
11 # And parse it into interactive objects
12 passage = resolver.getTextualNode("urn:cts:pdlrefwk:viaf88890045.003.perseus-eng1",
13 #→"A.abaeus_1")
14 # We need an export as plaintext
15 print(passage.export(
16     output=Mimetypes.PLAINTEXT
17 ))
18 """
19     Abaeus ( Ἀβαῖος ), a surname of Apollo
20     derived from the town of Abae in Phocis, where the god had a rich temple. ↴
21     (Hesych. s. v.
22     βαῖος ; Hdt. 8.33 ; Paus. 10.35.1 , &c.) [ L.S. ]
23 """
24 # We want to find bibliographic information in the passage of this dictionary
25 # We need an export as LXML ETREE object to perform XPath
26 print(
27     passage.export(
28         output=Mimetypes.PYTHON.ETREE
29         ).xpath("./tei:bibl/text()", namespaces=XPATH_NAMESPACES, magic_string=False)
30 )
31 [ "Hdt. 8.33", "Paus. 10.35.1" ]

```

Project using MyCapytain

If you are using MyCapytain and wish to appear here, please feel free to open an [issue](#)

Extensions

Nautilus

Nautilus provides a local retriever to build inventory based on a set of folders available locally.

Flask Capitains Nemo

Flask Capitains Nemo is an extension for Flask to build a browsing interface using both retrievers and resources modules. You will find example of use in a web based environment.

HookTest

HookTest is a library and command line tools for checking resources against the Capitains Guidelines You'll find uses mainly in `units.py`

CLTK Corpora Converter

Capitains Corpora Converter Converts CapiTainS-based Repository (<http://capitains.github.io>) to JSON for CLTK

Working with Local CapiTainS XML File

Introduction

The class `MyCapytain.resources.texts.locals.tei.Text` requires the guidelines of Capitains to be implemented in your file.

Example

```
1 # We import the correct classes from the local module
2 from MyCapytain.resources.texts.local.capitains.cts import CapitainsCtsText
3 from MyCapytain.common.constants import Mimetypes, XPATH_NAMESPACES
4 from lxml.etree import tostring
5
6 # We open a file
7 with open("./tests/testing_data/examples/text.martial.xml") as f:
8     # We initiate a Text object giving the IO instance to resource argument
9     text = CapitainsCtsText(resource=f)
10
11 # Text objects have a citation property
12 # len(Citation(...)) gives the depth of the citation scheme
13 # in the case of this sample, this would be 3 (Book, Poem, Line)
14 for ref in text.getReffs(level=len(text.citation)):
15     # We retrieve a Passage object for each reference that we find
```

```

16     # We can pass the reference many way, including in the form of a list of strings
17     # We use the _simple parameter to get a fairly simple object
18     # Simple makes a straight object that has only the targeted node inside of it
19     psg = text.getTextualNode(subreference=ref, simple=True)
20     # We print the passage from which we retrieve <note> nodes
21     print("\t".join([ref, psg.export(Mimetypes.PLAINTEXT, exclude=["tei:note"])]))

22
23 """
24 You'll print something like the following :
25
26     1.pr.1      Spero me secutum in libellis meis tale temperamen-
27     1.pr.2      tum, ut de illis queri non possit quisquis de se bene
28     1.pr.3      senserit, cum salva infimarum quoque personarum re-
29     1.pr.4      verentia ludant; quae adeo antiquis auctoribus defuit, ut
30     1.pr.5      nominibus non tantum veris abusi sint, sed et magnis.
31     1.pr.6      Mihi fama vilius constet et probetur in me novissimum

32 """
33
34
35 # It is possible that what you're interested in is a little more complex
36 # Like for example, getting a specific text sample with a specific reference
37 # In TEI !
38
39 # We open another such as Cicero's texts !
40 with open("./tests/testing_data/examples/text.cicero.xml") as f:
41     # We initiate a Text object giving the IO instance to resource argument
42     text = CapitainsCtsText(resource=f)
43     # We are specifically interest in the portion 28-30
44     # Note that we won't use 28-30 as cross passage reference won't work properly
45     p28_29 = text.getTextualNode("28-29")

46
47     # And we want to be able to work with the xml
48     # To be injected in a third party API for lemmatization purposes
49     xml = p28_29.export(Mimetypes.XML.Std)
50     print("XML of 28-29")
51     print(xml)
52     print("-----")

53
54     # But what we really want to do, is suppress the note from the XML.
55     # So we export to an LXML Object
56     document = p28_29.export(Mimetypes.PYTHON.ETREE)
57     # We remove some XML
58     for element in document.xpath("//tei:note", namespaces=XPATH_NAMESPACES):
59         element.getparent().remove(element)
60     # And we print using LXML constants
61     print("Clean XML of 28-29")
62     print(tostring(document, encoding=str))
63     print("-----")
64

```

Known issues and recommendations

XPath Issues

`lxml`, which is the package powering xml support here, does not accept XPath notations such as `/div/(a or b)[@n]`. Solution for this edge case is `/div/*[self::a or self::b][@n]`

MyCapytain API Documentation

Utilities, metadata and references

Module common contains tools such as a namespace dictionary as well as cross-implementation objects, like URN, Citations...

Base

```
class MyCapytain.common.base.Exportable(*args, **kwargs)
    Objects that supports Export

    Variables EXPORT_TO – List of Mimetypes the resource can export to
    export(output=None, **kwargs)
        Export the collection item in the Mimetype required.

        Parameters output (str) – Mimetype to export to (Uses MyCapytain.common.utils.Mimetypes)

        Returns Object using a different representation

    export_capacities
        List Mimetypes that current object can export to
```

Constants

```
class MyCapytain.common.constants.Mimetypes
    Mimetypes constants that are used to provide export functionality to base MyCapytain object.
```

Variables

- **JSON** – JSON Resource mimetype
- **XML** – XML Resource mimetype
- **PYTHON** – Python Native Object
- **PLAINTEXT** – Plain string format

```
class JSON
```

Json Mimetype

Variables

- **Std** – Standard JSON Export
- **CTS** – CTS Json Export

```
class DTS
    JSON DTS Expression
    Variables
        • Std – Standard DTS Json-LD Expression
        • NoParents – DTS Json-LD Expression without parents expression

class Mimetypes.PYTHON
    Python Native Objects
    Variables
        • NestedDict – Nested Dictionary Object
        • ETREE – Python LXML Etree Object

class MyCapytain
    MyCapytain Objects
    Variables ReadableText – MyCapytain.resources.prototypes.text.CitableText

class Mimetypes.XML
    XML Mimetype
    Variables
        • Std – Standard XML Export
        • RDF – RDF XML Expression Export
        • CTS – CTS API XML Expression Export
        • TEI – TEI XML Expression Export

class CapiTainS
    CapiTainS Guideline XML Structured metadata

class MyCapytain.common.constants.RDF_NAMESPACES
    Namespaces Constants used to provide Namespace capacities across the library
    Variables
        • CTS – CTS Namespace
        • TEI – TEI Namespace
        • DC – DC Elements
        • CAPITAINS – CapiTainS Ontology

MyCapytain.common.constants.XPATH_NAMESPACES = {'tei': 'http://www.tei-c.org/ns/1.0', 'xsd': 'http://www.w3.org/2001/XMLSchema'}
```

List of XPath Namespaces used in guidelines

URN, References and Citations

```
class MyCapytain.common.reference.NodeId(identifier=None, children=None, parent=None, siblings=(None, None), depth=None)
```

Collection of directional references for a Tree

Parameters

- **identifier** (*str*) – Current object identifier
- **children** (*[str]*) – Current node Children's Identifier
- **parent** (*str*) – Parent of the current node

- **siblings** (*str*) – Previous and next node of the current node
- **depth** (*int*) – Depth of the node in the global hierarchy of the text tree

childIds

Children Node

Return type [*str*]

depth

Depth of the node in the global hierarchy of the text tree

Return type *int*

firstId

First child Node

Return type *str*

id

Current object identifier

Return type *str*

lastId

Last child Node

Return type *str*

nextId

Next Node (Sibling)

Return type *str*

parentId

Parent Node

Return type *str*

prevId

Previous Node (Sibling)

Return type *str*

siblingsId

Siblings Node

Return type (*str*, *str*)

class MyCapytain.common.reference.URN (*urn*)

A URN object giving all useful sections

Parameters *urn* (*str*) – A CTS URN

Variables

- **NAMESPACE** – Constant representing the URN until its namespace
- **TEXTGROUP** – Constant representing the URN until its textgroup
- **WORK** – Constant representing the URN until its work
- **VERSION** – Constant representing the URN until its version
- **PASSAGE** – Constant representing the URN until its full passage
- **PASSAGE_START** – Constant representing the URN until its passage (end excluded)

- **PASSAGE_END** – Constant representing the URN until its passage (start excluded)
- **NO_PASSAGE** – Constant representing the URN until its passage excluding its passage
- **COMPLETE** – Constant representing the complete URN

Example

```
>>> a = URN(urn="urn:cts:latinLit:phi1294.phi002.perseus-lat2:1.1")
```

URN object supports the following magic methods : len(), str() and eq(), gt() and lt().

Example

```
>>> b = URN("urn:cts:latinLit:phi1294.phi002")
>>> a != b
>>> a > b # It has more member. Only member count is compared
>>> b < a
>>> len(a) == 5 # Reference is not counted to not induce count_
↪equivalencies with the optional version
>>> len(b) == 4
```

static model()

Generate a standard dictionary model for URN inside function

Returns Dictionary of CTS elements

namespace

CTS Namespace element of the URN

Return type str

Returns Namespace part of the URN

reference

Reference element of the URN

Return type Reference

Returns Reference part of the URN

textgroup

Textgroup element of the URN

Return type str

Returns Textgroup part of the URN

upTo(key)

Returns the urn up to given level using URN Constants

Parameters key (int) – Identifier of the wished resource using URN constants

Returns String representation of the partial URN requested

Return type str

Example

```
>>> a = URN(urn="urn:cts:latinLit:phi1294.phi002.perseus-lat2:1.1
↪")
>>> a.upTo(URN.TEXTGROUP) == "urn:cts:latinLit:phi1294"
```

urn_namespace

General Namespace element of the URN

Return type str

Returns Namespace part of the URN

version

Version element of the URN

Return type str

Returns Version part of the URN

work

CtsWorkMetadata element of the URN

Return type str

Returns CtsWorkMetadata part of the URN

class MyCapytain.common.reference.Reference (*reference*=‘‘)

A reference object giving information

Parameters **reference** (*basestring*) – CapitainsCtsPassage Reference part of a Urn

Example

```
>>> a = Reference(reference="1.1@Achilles[1]-1.2@Zeus[1]")
>>> b = Reference(reference="1.1")
>>> Reference("1.1-2.2.2").highest == ["1", "1"]
```

Reference object supports the following magic methods : len(), str() and eq().

Example

```
>>> len(a) == 2 && len(b) == 1
>>> str(a) == "1.1@Achilles[1]-1.2@Zeus[1]"
>>> b == Reference("1.1") && b != a
```

Note: While Reference(...).subreference and .list are not available for range, Reference(..).start.subreference and Reference(..).end.subreference as well as .list are available

static convert_subreference (*word, counter*)

Convert a word and a counter into a standard tuple representation

Parameters

- **word** – Word Element of the subreference
- **counter** – Index of the Word

Returns Tuple representing the element

Return type (str, int)

end

Quick access property for reference end list

Return type Reference

highest

Return highest reference level

For references such as 1.1-1.2.8, with different level, it can be useful to access to the highest node in the hierarchy. In this case, the highest level would be 1.1. The function would return [“1”, “1”]

Note: By default, this property returns the start level

Return type *Reference*

list

Return a list version of the object if it is a single passage

Note: Access to start list and end list should be done through obj.start.list and obj.end.list

Return type [str]

parent

Parent of the actual URN, for example, 1.1 for 1.1.1

Return type *Reference*

start

Quick access property for start list

Return type *Reference*

subreference

Return the subreference of a single node reference

Note: Access to start and end subreference should be done through obj.start.subreference and obj.end.subreference

Return type (str, int)

class MyCapytain.common.reference.Citation(*name=None*, *xpath=None*, *scope=None*, *refsDecl=None*, *child=None*)

A citation object gives informations about the scheme

Parameters

- **name** (*basestring*) – Name of the citation (e.g. “book”)
- **xpath** (*basestring*) – Xpath of the citation (As described by CTS norm)
- **scope** – Scope of the citation (As described by CTS norm)
- **refsDecl** (*basestring*) – refsDecl version
- **child** (*Citation*) – A citation

Variables

- **name** – Name of the citation (e.g. “book”)
- **xpath** – Xpath of the citation (As described by CTS norm)
- **scope** – Scope of the citation (As described by CTS norm)
- **refsDecl** – refsDecl version
- **child** – A citation

__iter__()
Iteration method
Loop over the citation childs

Example

```
>>> c = XmlCtsCitation(name="line")
>>> b = XmlCtsCitation(name="poem", child=c)
>>> a = XmlCtsCitation(name="book", child=b)
>>> [e for e in a] == [a, b, c]
```

__len__()
Length method

Return type int

Returns Number of nested citations

fill(passage=None, xpath=None)
Fill the xpath with given informations

Parameters

- **passage** (*Reference or list or None. Can be list of None and not None*) – CapitainsCtsPassage reference
- **xpath** (*Boolean*) – If set to True, will return the replaced self.xpath value and not the whole self.refsDecl

Return type basestring

Returns Xpath to find the passage

```
citation = XmlCtsCitation(name="line", scope="/TEI/text/body/div/div[@n='?']",
                           xpath="//l[@n='?']")
print(citation.fill(["1", None]))
# /TEI/text/body/div/div[@n='1']//l[@n]
print(citation.fill(None))
# /TEI/text/body/div/div[@n]//l[@n]
print(citation.fill(Reference("1.1")))
# /TEI/text/body/div/div[@n='1']//l[@n='1']
print(citation.fill("1", xpath=True))
# //l[@n='1']
```

Metadata containers

class MyCapytain.common.metadata.Metadata(node=None, *args, **kwargs)
A metadatum aggregation object provided to centralize metadata

Parameters keys ([text_type]) – A metadata field names list

Variables

- **EXPORT_TO** – List of exportable supported formats
- **DEFAULT_EXPORT** – Default export (CTS XML Inventory)
- **STORE** – RDF Store

add(key, value, lang=None)
Add a triple to the graph related to this node

Parameters

- **key** – Predicate of the triple
- **value** – Object of the triple
- **lang** – Language of the triple if applicable

export (*output=None*, ***kwargs*)

Export the collection item in the MimETYPE required.

Parameters **output** (*str*) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)**Returns** Object using a different representation**export_capacities**

List MimETYPES that current object can export to

get (*key, lang=None*)

Returns triple related to this node. Can filter on lang

Parameters

- **key** – Predicate of the triple
- **lang** – Language of the triple if applicable

Return type Literal or BNode or URIRef**static getOr** (*subject, predicate, *args, **kwargs*)

Retrieve a metadata node or generate a new one

Parameters

- **subject** – Subject to which the metadata node should be connected
- **predicate** – Predicate by which the metadata node should be connected

Returns Metadata for given node**Return type** Metadata**get_single** (*key, lang=None*)

Returns a single triple related to this node.

Parameters

- **key** – Predicate of the triple
- **lang** – Language of the triple if applicable

Return type Literal or BNode or URIRef**graph**

Quick access to the graph this node is connected to

Return type Graph**predicate_object** (*predicate=None, obj=None*)

Retrieve predicate and object around this object

Parameters

- **predicate** – Predicate to match, None to match all
- **obj** – Object to match, None to match all

Returns List of resources

remove (*predicate=None, obj=None*)
Remove triple matching the predicate or the object

Parameters

- **predicate** – Predicate to match, None to match all
- **obj** – Object to match, None to match all

unlink (*subj=None, predicate=None*)
Remove triple where Metadata is the object

Parameters

- **subj** – Subject to match, None to match all
- **predicate** – Predicate to match, None to match all

Utilities

`MyCapytain.common.utils.LiteralToDict (value)`
Transform an object value into a dict readable value

Parameters **value** (*Literal or URIRef*) – Object of a triple which is not a BNode

Returns dict or str or list

`class MyCapytain.common.utils.OrderedDefaultDict (default_factory=None, *args, **kwargs)`

Extension of Default Dict that makes an OrderedDefaultDict

Parameters **default_factory** – Default class to initiate

`class MyCapytain.common.utils.Subgraph (namespace_manager)`

Utility class to generate subgraph around one or more items

:param

graphiter (*graph, target, ascendants=0, descendants=1*)
Iter on a graph to finds object connected

Parameters

- **graph** (*Graph*) – Graph to serialize
- **target** (*Node*) – Node to iterate over
- **ascendants** – Number of level to iter over upwards (-1 = No Limit)
- **descendants** – Number of level to iter over downwards (-1 = No limit)

Returns

`MyCapytain.common.utils.copyNode (node, children=False, parent=False)`
Copy an XML Node

Parameters

- **node** – Etree Node
- **children** – Copy children nodes is set to True
- **parent** – Append copied node to parent if given

Returns

New Element

MyCapytain.common.utils.**expand_namespace** (*nsmap*, *string*)

If the string starts with a known prefix in nsmap, replace it by full URI

Parameters

- **nsmap** – Dictionary of prefix -> uri of namespace
- **string** – String in which to replace the namespace

Returns Expanded string with no namespace

MyCapytain.common.utils.**make_xml_node** (*graph*, *name*, *close=False*, *attributes=None*, *text=''*,
complete=False, *innerXML=''*)

Create an XML Node

Parameters

- **graph** – Graph used to geneates prefixes
- **name** – Name of the tag
- **close** – Produce closing tag (close=False -> “<tag>”, close=True -> “</tag>”)
- **attributes** – Dictionary of attributes
- **text** – CapitainsCtsText to put inside the node
- **complete** – Complete node (node with opening and closing tag)
- **innerXML** – XML to append to the node

Returns String representation of the node

Return type str

MyCapytain.common.utils.**nested_get** (*dictionary*, *keys*)

Get value in dictionary for dictionary[keys[0]][keys[1]][keys[..n]]

Parameters

- **dictionary** – An input dictionary
- **keys** – Keys where to store data

Returns

MyCapytain.common.utils.**nested_ordered_dictionary** ()

Helper to create a nested ordered default dictionary

Rtype OrderedDefaultDict

Returns Nested Ordered Default Dictionary instance

MyCapytain.common.utils.**nested_set** (*dictionary*, *keys*, *value*)

Set value in dictionary for dictionary[keys[0]][keys[1]][keys[..n]]

Parameters

- **dictionary** – An input dictionary
- **keys** – Keys where to store data
- **value** – Value to set at keys** target

Returns None

MyCapytain.common.utils.**normalize** (*string*)

Remove double-or-more spaces in a string

Parameters **string** (*text_type*) – A string to change

Return type text_type

Returns Clean string

MyCapytain.common.utils.normalizeXpath(xpath)

Normalize XPATH split around slashes

Parameters xpath ([str]) – List of xpath elements

Returns List of refined xpath

Return type [str]

MyCapytain.common.utils.passageLoop(parent, new_tree, xpath1, xpath2=None, preceding_siblings=False, following_siblings=False)

Loop over passages to construct and increment new tree given a parent and XPaths

Parameters

- **parent** – Parent on which to perform xpath
- **new_tree** – Parent on which to add nodes
- **xpath1** ([str]) – List of xpath elements
- **xpath2** ([str]) – List of xpath elements
- **preceding_siblings** – Append preceding siblings of XPath 1/2 match to the tree
- **following_siblings** – Append following siblings of XPath 1/2 match to the tree

Returns Newly incremented tree

MyCapytain.common.utils.performXPath(parent, xpath)

Perform an XPath on an element and indicate if we need to loop over it to find something

Parameters

- **parent** – XML Node on which to perform XPath
- **xpath** – XPath to run

Returns (Result, Need to loop Indicator)

MyCapytain.common.utils.xmliter(node)

Provides a simple XML Iter method which complies with either _Element or _ObjectifiedElement

Parameters node – XML Node

Returns Iterator for iterating over children of said node.

MyCapytain.common.utils.xmlparser(xml, objectify=True)

Parse xml

Parameters xml (Union[text_type, lxml.etree._Element]) – XML element

Return type lxml.etree._Element

Returns An element object

Raises TypeError if element is not in accepted type

API Retrievers

Module endpoints contains prototypes and implementation of retrievers in MyCapytain

CTS 5 API

class MyCapytain.retrievers.cts5.HttpCtsRetriever (*endpoint, inventory=None*)
Bases: MyCapytain.retrievers.prototypes.CtsRetriever

Basic integration of the MyCapytain.retrievers.proto.CTS abstraction

call (*parameters*)

Call an endpoint given the parameters

Parameters **parameters** (*dict*) – Dictionary of parameters

Return type *text*

getCapabilities (*inventory=None, urn=None*)

Retrieve the inventory information of an API

Parameters

- **inventory** (*text*) – Name of the inventory
- **urn** (*str*) – URN to filter with

Return type *str*

getFirstUrn (*urn, inventory=None*)

Retrieve the first passage urn of a text

Parameters

- **urn** (*text*) – URN identifying the text
- **inventory** (*text*) – Name of the inventory

Return type *str*

getLabel (*urn, inventory=None*)

Retrieve informations about a CTS Urn

Parameters

- **urn** (*text*) – URN identifying the text's passage (Minimum depth : 1)
- **inventory** (*text*) – Name of the inventory

Return type *str*

getMetadata (*objectId=None, **filters*)

Request metadata about a text or a collection

Parameters

- **objectId** – Filter for some object identifier
- **filters** – Kwargs parameters. URN and Inv are available

Returns GetCapabilities CTS API request response

getPassage (*urn, inventory=None, context=None*)

Retrieve a passage

Parameters

- **urn** (*text*) – URN identifying the text's passage (Minimum depth : 1)
- **inventory** (*text*) – Name of the inventory

- **context** (`int`) – Number of citation units at the same level of the citation hierarchy as the requested urn, immediately preceding and immediately following the requested urn to include in the reply

Return type `str`

getPassagePlus (`urn, inventory=None, context=None`)

Retrieve a passage and information about it

Parameters

- **urn** (`text`) – URN identifying the text's passage (Minimum depth : 1)
- **inventory** (`text`) – Name of the inventory
- **context** (`int`) – Number of citation units at the same level of the citation hierarchy as the requested urn, immediately preceding and immediately following the requested urn to include in the reply

Return type `str`

getPrevNextUrn (`urn, inventory=None`)

Retrieve the previous and next passage urn of one passage

Parameters

- **urn** (`text`) – URN identifying the text's passage (Minimum depth : 1)
- **inventory** (`text`) – Name of the inventory

Return type `str`

getReffs (`textId, level=1, subreference=None`)

Retrieve the siblings of a textual node

Parameters

- **textId** (`str`) – CtsTextMetadata Identifier
- **level** (`int`) – Depth for retrieval
- **subreference** (`str`) – CapitainsCtsPassage Reference

Returns List of references

Return type `[str]`

getsiblings (`textId, subreference`)

Retrieve the siblings of a textual node

Parameters

- **textId** – CtsTextMetadata Identifier
- **reference** – CapitainsCtsPassage Reference

Returns GetPrevNextUrn request response from the endpoint

getTextualNode (`textId, subreference=None, prevnext=False, metadata=False`)

Retrieve a text node from the API

Parameters

- **textId** – CtsTextMetadata Identifier
- **subreference** – CapitainsCtsPassage Reference
- **prevnext** – Retrieve graph representing previous and next passage

- **metadata** – Retrieve metadata about the passage and the text

Returns GetPassage or GetPassagePlus CTS API request response

getValidReff (*urn*, *inventory=None*, *level=None*)

Retrieve valid urn-references for a text

Parameters

- **urn** (*text*) – URN identifying the text
- **inventory** (*text*) – Name of the inventory
- **level** (*int*) – Depth of references expected

Returns XML Response from the API as string

Return type *str*

Prototypes

class MyCapytain.retrievers.prototypes.**API** (*endpoint*)

Bases: *object*

API Prototype object

Parameters

- **self** (*API*) – Object
- **endpoint** (*text*) – URL of the API

Variables *endpoint* – Url of the endpoint

class MyCapytain.retrievers.prototypes.**CitableTextServiceRetriever** (*endpoint*)

Bases: MyCapytain.retrievers.prototypes.API

Citable CtsTextMetadata Service retrievers should have at least have some of the following properties

getMetadata (*objectId=None*, ***filters*)

Request metadata about a text or a collection

Parameters

- **objectId** – CtsTextMetadata Identifier
- **filters** – Kwargs parameters. URN and Inv are available

Returns Metadata of text from an API or the likes as bytes

getReffs (*textId*, *level=1*, *subreference=None*)

Retrieve the siblings of a textual node

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **level** (*int*) – Depth for retrieval
- **subreference** (*str*) – CapitainsCtsPassage Reference

Returns List of references

Return type [*str*]

getsiblings (*textId*, *subreference*)

Retrieve the siblings of a textual node

Parameters

- **textId** – CtsTextMetadata Identifier
- **subreference** – CapitainsCtsPassage Reference

Returns Siblings references from an API or the likes as bytes

getTextualNode (*textId*, *subreference=None*, *prevnext=False*, *metadata=False*)

Retrieve a text node from the API

Parameters

- **textId** – CtsTextMetadata Identifier
- **subreference** – CapitainsCtsPassage Reference
- **prevnext** – Retrieve graph representing previous and next passage
- **metadata** – Retrieve metadata about the passage and the text

Returns CtsTextMetadata of a CapitainsCtsPassage from an API or the likes as bytes

class MyCapytain.retrievers.prototypes.CtsRetriever (*endpoint*)

Bases: MyCapytain.retrievers.prototypes.CitableTextServiceRetriever

CTS API Endpoint Prototype

getCapabilities (*inventory*)

Retrieve the inventory information of an API

Parameters **inventory** (*text*) – Name of the inventory

Return type str

getFirstUrn (*urn*, *inventory*)

Retrieve the first passage urn of a text

Parameters

- **urn** (*text*) – URN identifying the text
- **inventory** (*text*) – Name of the inventory

Return type str

getLabel (*urn*, *inventory*)

Retrieve informations about a CTS Urn

Parameters

- **urn** (*text*) – URN identifying the text's passage (Minimum depth : 1)
- **inventory** (*text*) – Name of the inventory

Return type str

getMetadata (*objectId=None*, ***filters*)

Request metadata about a text or a collection

Parameters

- **objectId** – CtsTextMetadata Identifier
- **filters** – Kwargs parameters. URN and Inv are available

Returns Metadata of text from an API or the likes as bytes

getPassage (*urn, inventory, context=None*)

Retrieve a passage

Parameters

- **urn** (`text`) – URN identifying the text's passage (Minimum depth : 1)
- **inventory** (`text`) – Name of the inventory
- **context** (`int`) – Number of citation units at the same level of the citation hierarchy as the requested urn, immediately preceding and immediately following the requested urn to include in the reply

Return type `str`**getPassagePlus** (*urn, inventory, context=None*)

Retrieve a passage and informations about it

Parameters

- **urn** (`text`) – URN identifying the text's passage (Minimum depth : 1)
- **inventory** (`text`) – Name of the inventory
- **context** (`int`) – Number of citation units at the same level of the citation hierarchy as the requested urn, immediately preceding and immediately following the requested urn to include in the reply

Return type `str`**getPrevNextUrn** (*urn, inventory*)

Retrieve the previous and next passage urn of one passage

Parameters

- **urn** (`text`) – URN identifying the text's passage (Minimum depth : 1)
- **inventory** (`text`) – Name of the inventory

Return type `str`**getReffs** (*textId, level=1, subreference=None*)

Retrieve the siblings of a textual node

Parameters

- **textId** (`str`) – CtsTextMetadata Identifier
- **level** (`int`) – Depth for retrieval
- **subreference** (`str`) – CapitainsCtsPassage Reference

Returns List of references**Return type** `[str]`**getsiblings** (*textId, subreference*)

Retrieve the siblings of a textual node

Parameters

- **textId** – CtsTextMetadata Identifier
- **subreference** – CapitainsCtsPassage Reference

Returns Siblings references from an API or the likes as bytes

getTextualNode (*textId*, *subreference=None*, *prevnext=False*, *metadata=False*)

Retrieve a text node from the API

Parameters

- **textId** – CtsTextMetadata Identifier
- **subreference** – CapitainsCtsPassage Reference
- **prevnext** – Retrieve graph representing previous and next passage
- **metadata** – Retrieve metadata about the passage and the text

Returns CtsTextMetadata of a CapitainsCtsPassage from an API or the likes as bytes

getValidReff (*urn*, *inventory*, *level=1*)

Retrieve valid urn-references for a text

Parameters

- **urn** (*text*) – URN identifying the text
- **inventory** (*text*) – Name of the inventory
- **level** (*int*) – Depth of references expected

Return type str

Resolvers

Remote CTS API

class MyCapytain.resolvers.cts.api.HttpCtsResolver (*endpoint*)

HttpCtsResolver provide a resolver for CTS API http endpoint.

Parameters **endpoint** (*HttpCtsRetriever*) – CTS API Retriever

Variables **endpoint** – CTS API Retriever

endpoint

CTS Endpoint of the resolver

Returns CTS Endpoint

Return type HttpCtsRetriever

getMetadata (*objectId=None*, ***filters*)

Request metadata about a text or a collection

Parameters

- **objectId** (*str*) – Object Identifier to filter on
- **filters** (*dict*) – Kwargs parameters.

Returns Collection

getReffs (*textId*, *level=1*, *subreference=None*)

Retrieve the siblings of a textual node

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **level** (*int*) – Depth for retrieval

- **subreference** (*str*) – CapitainsCtsPassage Reference

Returns List of references

Return type [*str*]

getSiblings (*textId*, *subreference*)

Retrieve the siblings of a textual node

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **subreference** (*str*) – CapitainsCtsPassage Reference

Returns Tuple of references

Return type (*str*, *str*)

getTextualNode (*textId*, *subreference=None*, *prevnext=False*, *metadata=False*)

Retrieve a text node from the API

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **subreference** (*str*) – CapitainsCtsPassage Reference
- **prevnext** (*boolean*) – Retrieve graph representing previous and next passage
- **metadata** (*boolean*) – Retrieve metadata about the passage and the text

Returns CapitainsCtsPassage

Return type *CapitainsCtsPassage*

Local CapiTainS Guidelines CTS Resolver

```
class MyCapytain.resolvers.cts.local.CtsCapitainsLocalResolver(resource,
                                                               name=None,
                                                               logger=None,
                                                               dispatcher=None)
```

XML Folder Based resolver. CtsTextMetadata and metadata resolver based on local directories

Parameters

- **resource** (*[str]*) – Resource should be a list of folders retaining data as Capitains Guidelines Repositories
- **name** (*str*) – Key used to differentiate Repository and thus enabling different repo to be used
- **logger** (*logging*) – Logging object

Variables

- **TEXT_CLASS** – CtsTextMetadata Class [not instantiated] to be used to parse Texts. Can be changed to support Cache for example
- **DEFAULT_PAGE** – Default Page to show
- **PER_PAGE** – Tuple representing the minimal number of texts returned, the default number and the maximum number of texts returned

TEXT_CLASS

alias of CapitainsCtsText

getMetadata (*objectId=None, **filters*)

Request metadata about a text or a collection

Parameters

- **objectId** (*str*) – Object Identifier to filter on
- **filters** (*dict*) – Kwargs parameters.

Returns Collection

getReffs (*textId, level=1, subreference=None*)

Retrieve the siblings of a textual node

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **level** (*int*) – Depth for retrieval
- **subreference** (*str*) – CapitainsCtsPassage Reference

Returns List of references

Return type [*str*]

getsiblings (*textId, subreference*)

Retrieve the siblings of a textual node

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **subreference** (*str*) – CapitainsCtsPassage Reference

Returns Tuple of references

Return type (*str, str*)

getTextualNode (*textId, subreference=None, prevnext=False, metadata=False*)

Retrieve a text node from the API

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **subreference** (*str*) – CapitainsCtsPassage Reference
- **prevnext** (*boolean*) – Retrieve graph representing previous and next passage
- **metadata** (*boolean*) – Retrieve metadata about the passage and the text

Returns CapitainsCtsPassage

Return type *CapitainsCtsPassage*

static pagination (*page, limit, length*)

Help for pagination :param page: Provided Page :param limit: Number of item to show :param length: Length of the list to paginate :return: (Start Index, End Index, Page Number, Item Count)

parse (*resource*)

Parse a list of directories and reads it into a collection

Parameters **resource** – List of folders

Returns An inventory resource and a list of CtsTextMetadata metadata-objects

xmlparse (*file*)

Parse a XML file :param file: Opened File :return: Tree

Dispatcher

```
class MyCapytain.resolvers.utils.CollectionDispatcher(collection,          de-
                                                     default_inventory_name=None)
```

Collection Dispatcher provides a utility to divide automatically texts and collections into different collections

Parameters

- **collection** – The root collection
- **default_inventory_name** – The default name of the default collection

add (*func, inventory_name*)

Register given function as a filter.

If this function “*func*” returns True when given an object, said object will be dispatched to Collection(*inventory_name*)

Parameters

- **func** – Callable
- **inventory_name** – Identifier of the collection to dispatch to

dispatch (*collection, **kwargs*)

Dispatch a collection using internal filters

Parameters

- **collection** – Collection object
- **kwargs** – Additional keyword arguments that could be used by internal filters

Returns None

Raises

inventory (*inventory_name*)

Decorator to register filters for given inventory. For a function “abc”, it has the same effect

Parameters **inventory_name** –

Returns

```
tic = CtsTextInventoryCollection()
latin = CtsTextInventoryMetadata("urn:perseus:latinLit", parent=tic)
latin.set_label("Classical Latin", "eng")
dispatcher = CollectionDispatcher(tic)

@dispatcher.inventory("urn:perseus:latinLit")
def dispatchLatinLit(collection, path=None, **kwargs):
    if collection.id.startswith("urn:cts:latinLit:"):
        return True
    return False
```

methods

List of methods to dispatch resources.

Each element is a tuple with two elements :

- First one is the inventory identifier to dispatch to
- Second one is a function which, if returns true, will activate dispatching to given

Return type List

Prototypes

class MyCapytain.resolvers.prototypes.Resolver

Resolver provide a native python API which returns python objects.

Initiation of resolvers are dependent on the implementation of the prototype

getMetadata (*objectId=None*, ***filters*)

Request metadata about a text or a collection

Parameters

- **objectId** (*str*) – Object Identifier to filter on
- **filters** (*dict*) – Kwarg parameters.

Returns Collection

getRefs (*textId*, *level=1*, *subreference=None*)

Retrieve the siblings of a textual node

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **level** (*int*) – Depth for retrieval
- **subreference** (*str*) – CapitainsCtsPassage Reference

Returns List of references

Return type [*str*]

getsiblings (*textId*, *subreference*)

Retrieve the siblings of a textual node

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **subreference** (*str*) – CapitainsCtsPassage Reference

Returns Tuple of references

Return type (*str*, *str*)

getTextualNode (*textId*, *subreference=None*, *prevnext=False*, *metadata=False*)

Retrieve a text node from the API

Parameters

- **textId** (*str*) – CtsTextMetadata Identifier
- **subreference** (*str*) – CapitainsCtsPassage Reference
- **prevnext** (*boolean*) – Retrieve graph representing previous and next passage
- **metadata** (*boolean*) – Retrieve metadata about the passage and the text

Returns CapitainsCtsPassage

Return type *CapitainsCtsPassage*

Texts and inventories

Text

TEI based texts

```
class MyCapytain.resources.texts.base.tei.TEIResource(resource, **kwargs)
Bases: MyCapytain.resources.prototypes.text.InteractiveTextualNode

TEI Encoded Resource

Parameters resource (Union[str, _Element]) – XML Resource that needs to be parsed
into a CapitainsCtsPassage/CtsTextMetadata

Variables

    • EXPORT_TO – List of exportable supported formats
    • DEFAULT_EXPORT – Default export (Plain/CtsTextMetadata)

DEFAULT_EXPORT = ‘text/plain’

EXPORT_TO = [‘python/lxml’, ‘text/xml’, ‘python/NestedDict’, ‘text/plain’, ‘text/xml:tei’]

asNode()

childIds
Identifiers of children

    Returns Identifiers of children

    Return type [str]

children
Children Passages

    Return type iterator(CapitainsCtsPassage)

citation
XmlCtsCitation Object of the CtsTextMetadata

    Returns XmlCtsCitation Object of the CtsTextMetadata

    Return type Citation

default_exclude = []

depth
Depth of the node in the global hierarchy of the text tree

    Return type int

export (output=None, exclude=None, **kwargs)
Export the collection item in the MimETYPE required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

    • output (str) – MimETYPE to export to (Uses MyCapytain.common.constants.Mimetypes)

    • exclude ([str]) – Information to exclude. Specific to implementations

    Returns Object using a different representation
```

export_capacities

List Mimetypes that current object can export to

first

First CapitainsCtsPassage

Return type Passage

firstId

First child of current CapitainsCtsPassage

Return type str

Returns First passage node Information

getReffs (*level=1, subreference=None*)

Reference available at a given level

Parameters

- **level** (Int) – Depth required. If not set, should retrieve first encountered level (1 based)
- **passage** (Reference) – Subreference (optional)

Return type [text_type]

Returns List of levels

getTextualNode (*subreference*)

Retrieve a passage and store it in the object

Parameters **subreference** (str or Node or Reference) – Reference of the passage to retrieve

Return type TextualNode

Returns Object representing the passage

Raises TypeError when reference is not a list or a Reference

get_creator (*lang=None*)

Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_description (*lang=None*)

Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (*lang=None*)

Get the subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)
Get the title of the object

Parameters `lang` – Lang to retrieve

Returns Title string representation

Return type Literal

graph

id
Identifier of the text

Returns Identifier of the text

Return type text_type

last
Last CapitainsCtsPassage

Return type Passage

lastId
Last child of current CapitainsCtsPassage

Return type str

Returns Last passage Node representation

metadata
Metadata information about the text

Returns Collection object with metadata about the text

Return type Metadata

next
Get Next CapitainsCtsPassage

Return type Passage

nextId
Next Node (Sibling)

Return type str

parent
Parent CapitainsCtsPassage

Return type Passage

parentId
Parent Node

Return type str

prev
Get Previous CapitainsCtsPassage

Return type Passage

prevId
Previous Node (Sibling)

Return type str

```
set_creator(value, lang)
Set the DC Creator literal value

    Parameters lang – Language in which the value is

set_description(value, lang=None)
Set the DC Description literal value

    Parameters lang – Language in which the value is

set_subject(value, lang=None)
Set the DC Subject literal value

    Parameters lang – Language in which the value is

set_title(value, lang=None)
Set the DC Title literal value

    Parameters lang – Language in which the value is

siblingsId
Siblings Node

    Return type (str, str)

text
String representation of the text

    Returns String representation of the text

    Return type text\_type

xml
XML Representation of the CapitainsCtsPassage

    Return type lxml.etree.\_Element

    Returns XML element representing the passage
```

Locally read text

```
class MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText(urn=None,
                                                                     citation=None,
                                                                     re-
                                                                     source=None)
Bases:      MyCapytain.resources.texts.local.capitains.cts.__SharedMethods__,
MyCapytain.resources.texts.base.tei.TEIResource,      MyCapytain.resources.
prototypes.text.CitableText
```

Implementation of CTS tools for local files

Parameters

- **urn** ([MyCapytain.common.reference.URN](#)) – A URN identifier
- **resource** ([lxml.etree._Element](#)) – A resource
- **citation** ([Citation](#)) – Highest XmlCtsCitation level
- **autoreffs** ([bool](#)) – Parse references on load (default : True)

Variables **resource** – [lxml](#)

DEFAULT_EXPORT = ‘text/plain’

```
EXPORT_TO = ['python/lxml', 'text/xml', 'python/NestedDict', 'text/plain', 'text/xml:tei']
```

asNode()

childIds

Identifiers of children

Returns Identifiers of children

Return type [str]

children

Children Passages

Return type iterator(*CapitainsCtsPassage*)

citation

XmlCtsCitation Object of the CtsTextMetadata

Returns XmlCtsCitation Object of the CtsTextMetadata

Return type Citation

default_exclude = []

depth

Depth of the node in the global hierarchy of the text tree

Return type int

export (*output=None, exclude=None, **kwargs*)

Export the collection item in the MimETYPE required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

- **output** (str) – Mimetype to export to (Uses MyCapytain.common.constants.Mimetypes)
- **exclude** ([str]) – Information to exclude. Specific to implementations

Returns Object using a different representation

export_capacities

List MIMETYPES that current object can export to

first

First CapitainsCtsPassage

Return type Passage

firstId

First child of current CapitainsCtsPassage

Return type str

Returns First passage node information

getLabel()

Retrieve metadata about the text

Return type Collection

Returns Retrieve Label informations in a Collection format

getReffs (*level=1, subreference=None*)

Reference available at a given level

Parameters

- **level** (*Int*) – Depth required. If not set, should retrieve first encountered level (1 based)
- **subreference** (*str*) – Subreference (optional)

Return type List`.basestring`

Returns List of levels

getTextualNode (*subreference=None, simple=False*)

Finds a passage in the current text

Parameters

- **subreference** (*Union[list, Reference]*) – Identifier of the subreference / passages
- **simple** (*boolean*) – If set to true, retrieves nodes up to the given one, cleaning non required siblings.

Return type *CapitainsCtsPassage, ContextPassage*

Returns Asked passage

getValidReff (*level=None, reference=None, _debug=False*)

Retrieve valid passages directly

Parameters

- **level** (*int*) – Depth required. If not set, should retrieve first encountered level (1 based)
- **reference** (*Reference*) – CapitainsCtsPassage Reference
- **_debug** (*bool*) – Check on passages duplicates

Returns List of levels

Return type *list(basestring, str)*

Note: GetValidReff works for now as a loop using CapitainsCtsPassage, subinstances of CtsTextMetadata, to retrieve the valid informations. Maybe something is more powerfull ?

get_creator (*lang=None*)

Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_metadata (*key, lang=None*)

get_description (*lang=None*)

Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (*lang=None*)

Get the subject of the object

Parameters `lang` – Lang to retrieve
Returns Subject string representation
Return type Literal

get_title (`lang=None`)
Get the title of the object

Parameters `lang` – Lang to retrieve
Returns Title string representation
Return type Literal

graph

id
Identifier of the text

Returns Identifier of the text
Return type text_type

last
Last CapitainsCtsPassage

Return type Passage

lastId
Last child of current CapitainsCtsPassage

Return type str
Returns Last passage Node representation

metadata
Metadata information about the text

Returns Collection object with metadata about the text
Return type Metadata

next
Get Next CapitainsCtsPassage

Return type Passage

nextId
Next Node (Sibling)

Return type str

parent
Parent CapitainsCtsPassage

Return type Passage

parentId
Parent Node

Return type str

prev
Get Previous CapitainsCtsPassage

Return type Passage

prevId

Previous Node (Sibling)

Return type str

reffs

Get all valid reffs for every part of the CitableText

Return type [str]

set_creator(value, lang)

Set the DC Creator literal value

Parameters lang – Language in which the value is

set_description(value, lang=None)

Set the DC Description literal value

Parameters lang – Language in which the value is

set_metadata_from_collection(text_metadata)

Set the object metadata using its collections recursively

Parameters text_metadata

(CtsEditionMetadata or

CtsTranslationMetadata) – Object representing the current text as a collection

set_subject(value, lang=None)

Set the DC Subject literal value

Parameters lang – Language in which the value is

set_title(value, lang=None)

Set the DC Title literal value

Parameters lang – Language in which the value is

siblingsId

Siblings Node

Return type (str, str)

test()

Parse the object and generate the children

text

String representation of the text

Returns String representation of the text

Return type text_type

textObject

Textual Object with full capacities (Unlike Simple CapitainsCtsPassage)

Return type CtsTextMetadata, CapitainsCtsPassage

Returns Textual Object with full capacities (Unlike Simple CapitainsCtsPassage)

tostring(*args, **kwargs)

Transform the CapitainsCtsPassage in XML string

Parameters

- args – Ordered arguments for etree.tostring() (except the first one)

- kwargs – Named arguments

Returns**urn**

URN Identifier of the object

Return type [URN](#)**xml**

XML Representation of the CapitainsCtsPassage

Return type `lxml.etree._Element`**Returns** XML element representing the passage**xpath** (*args, **kwargs)

Perform XPath on the passage XML

Parameters

- **args** – Ordered arguments for `etree._Element().xpath()`
- **kwargs** – Named arguments

Returns Result list**Return type** `list(etree._Element)`

```
class MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsPassage(reference,
    urn=None,
    cita-
    tion=None,
    re-
    source=None,
    text=None)
Bases:      MyCapytain.resources.texts.local.capitains.cts.__SharedMethods__,
    MyCapytain.resources.texts.base.tei.TEIResource,      MyCapytain.resources.
prototypes.text.Passage
```

CaptainsCtsPassage class for local texts which rebuilds the tree up to the passage.

For design purposes, some people would prefer the output of GetPassage to be consistent. ContextPassage rebuilds the tree of the text up to the passage, keeping attributes of original nodes

Example : for a text with a citation scheme with following refsDecl : `/TEI/text/body/div[@type='edition']/div[@n='$1']/div[@n='$2']/l[@n='$3']` and a passage 1.1.1-1.2.3, this class will build an XML tree looking like the following

```
<TEI ...>
  <text ...>
    <body ...>
      <div type='edition' ...>
        <div n='1' ...>
          <div n='1' ...>
            <l n='1'>...</l>
            ...
          </div>
          <div n='2' ...>
            <l n='3'>...</l>
          </div>
        </div>
      </body>
    </text>
  </TEI>
```

```
</text>
</TEI>
```

Parameters

- **reference** ([Reference](#)) – CapitainsCtsPassage reference
- **urn** ([URN](#)) – URN of the source text or of the passage
- **citation** ([XmlCtsCitation](#)) – XmlCtsCitation scheme of the text
- **resource** ([etree._Element](#)) – Element representing the passage
- **text** ([CtsTextMetadata](#)) – CtsTextMetadata containing the passage

Note: .prev, .next, .first and .last won't run on passage with a range made of two different level, such as 1.1-1.2.3 or 1-a.b. Those will raise *InvalidSiblingRequest*

DEFAULT_EXPORT = ‘text/plain’

EXPORT_TO = [‘python/lxml’, ‘text/xml’, ‘python/NestedDict’, ‘text/plain’, ‘text/xml:tei’]

asNode()

childIds

Children of the passage

Return type [None, Reference](#)

Returns Dictionary of children, where key are subreferences

children

Children Passages

Return type iterator([CapitainsCtsPassage](#))

citation

XmlCtsCitation Object of the CtsTextMetadata

Returns XmlCtsCitation Object of the CtsTextMetadata

Return type [Citation](#)

default_exclude = []

depth

Depth of the node in the global hierarchy of the text tree

Return type [int](#)

export (*output=None, exclude=None, **kwargs*)

Export the collection item in the MimETYPE required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

- **output** ([str](#)) – Mimetype to export to (Uses [MyCapytain.common.constants.Mimetypes](#))
- **exclude** ([\[str\]](#)) – Information to exclude. Specific to implementations

Returns Object using a different representation

export_capacities

List Mimetypes that current object can export to

first

First CapitainsCtsPassage

Return type Passage

firstId

First child of current CapitainsCtsPassage

Return type str

Returns First passage node Information

getLabel()

Retrieve metadata about the text

Return type Collection

Returns Retrieve Label informations in a Collection format

getReffs(level=1, subreference=None)

Reference available at a given level

Parameters

- **level** (Int) – Depth required. If not set, should retrieve first encountered level (1 based)
- **subreference** (str) – Subreference (optional)

Return type List[basestring]

Returns List of levels

getTextualNode(subreference=None, *args, **kwargs)**getValidReff(level=None, reference=None, _debug=False)**

Retrieve valid passages directly

Parameters

- **level** (int) – Depth required. If not set, should retrieve first encountered level (1 based)
- **reference** (Reference) – CapitainsCtsPassage Reference
- **_debug** (bool) – Check on passages duplicates

Returns List of levels

Return type list(basestring, str)

Note: GetValidReff works for now as a loop using CapitainsCtsPassage, subinstances of CtsTextMetadata, to retrieve the valid informations. Maybe something is more powerfull ?

get_creator(lang=None)

Get the DC Creator literal value

Parameters lang – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_metadata(key, lang=None)

get_description (*lang=None*)

Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (*lang=None*)

Get the subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)

Get the title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph

id

Identifier of the text

Returns Identifier of the text

Return type text_type

last

Last CapitainsCtsPassage

Return type Passage

lastId

Last child of current CapitainsCtsPassage

Return type str

Returns Last passage Node representation

metadata

Metadata information about the text

Returns Collection object with metadata about the text

Return type Metadata

next

Next CapitainsCtsPassage (Interactive CapitainsCtsPassage)

nextId

Next passage

Returns Next passage at same level

Return type None, Reference

parent

Parent CapitainsCtsPassage

Return type Passage

parentId

Parent Node

Return type str

prev

Previous CapitainsCtsPassage (Interactive CapitainsCtsPassage)

prevId

Get the Previous passage reference

Returns Previous passage reference at the same level

Return type None, Reference

reference

Reference of the object

set_creator(value, lang)

Set the DC Creator literal value

Parameters lang – Language in which the value is

set_description(value, lang=None)

Set the DC Description literal value

Parameters lang – Language in which the value is

set_metadata_from_collection(text_metadata)

Set the object metadata using its collections recursively

Parameters text_metadata

(CtsEditionMetadata or

CtsTranslationMetadata) – Object representing the current text as a collection

set_subject(value, lang=None)

Set the DC Subject literal value

Parameters lang – Language in which the value is

set_title(value, lang=None)

Set the DC Title literal value

Parameters lang – Language in which the value is

siblingsId

Siblings Identifiers of the passage

Return type (str, str)

text

String representation of the text

Returns String representation of the text

Return type text_type

textObject

CtsTextMetadata Object. Required for NextPrev

Return type CapitainsCtsText

tostring(*args, **kwargs)

Transform the CapitainsCtsPassage in XML string

Parameters

- **args** – Ordered arguments for etree.tostring() (except the first one)
- **kwargs** – Named arguments

Returns

urn

URN Identifier of the object

Return type [URN](#)

xml

XML Representation of the CapitainsCtsPassage

Return type [lxml.etree._Element](#)

Returns XML element representing the passage

xpath(*args, **kwargs)

Perform XPath on the passage XML

Parameters

- **args** – Ordered arguments for etree._Element().xpath()
- **kwargs** – Named arguments

Returns

Result list

Return type [list\(etree._Element\)](#)

```
class MyCapytain.resources.texts.local.capitains.cts.__SimplePassage__(resource,
    reference,
    citation,
    text,
    urn=None)
Bases:      MyCapytain.resources.texts.local.capitains.cts.__SharedMethods__,
MyCapytain.resources.texts.base.tei.TEIResource,      MyCapytain.resources.prototypes.text.Passage
```

CapitainsCtsPassage for simple and quick parsing of texts

Parameters

- **resource** ([etree._Element](#)) – Element representing the passage
- **reference** ([Reference](#)) – CapitainsCtsPassage reference
- **urn** ([URN](#)) – URN of the source text or of the passage
- **citation** ([Citation](#)) – XmlCtsCitation scheme of the text
- **text** ([CapitainsCtsText](#)) – CtsTextMetadata containing the passage

childIds

Children of the passage

Return type [None, Reference](#)

Returns Dictionary of children, where key are subreferences

children

Children Passages

Return type iterator([CapitainsCtsPassage](#))

citation

XmlCtsCitation Object of the CtsTextMetadata

Returns XmlCtsCitation Object of the CtsTextMetadata

Return type *Citation*

depth

Depth of the node in the global hierarchy of the text tree

Return type *int*

export (*output=None, exclude=None, **kwargs*)

Export the collection item in the Mimetype required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

- **output** (*str*) – MimETYPE to export to (Uses MyCapytain.common.constants.Mimetypes)
- **exclude** ([*str*]) – Information to exclude. Specific to implementations

Returns Object using a different representation

export_capacities

List MIMETYPES that current object can export to

first

First CapitainsCtsPassage

Return type Passage

firstId

First child of current CapitainsCtsPassage

Return type str

Returns First passage node information

getLabel()

Retrieve metadata about the text

Return type Collection

Returns Retrieve Label informations in a Collection format

getRefs (*level=1, subreference=None*)

Reference available at a given level

Parameters

- **level** (*Int*) – Depth required. If not set, should retrieve first encountered level (1 based)
- **subreference** (*Reference*) – Subreference (optional)

Return type List.basestring

Returns List of levels

getTextualNode (*subreference=None*)

Special GetPassage implementation for SimplePassage (Simple is True by default)

Parameters **subreference** –

Returns

getValidReff (*level=None*, *reference=None*, *_debug=False*)

Retrieve valid passages directly

Parameters

- **level** (*int*) – Depth required. If not set, should retrieve first encountered level (1 based)
- **reference** ([Reference](#)) – CapitainsCtsPassage Reference
- **_debug** (*bool*) – Check on passages duplicates

Returns List of levels

Return type *list*(*basestring*, *str*)

Note: GetValidReff works for now as a loop using CapitainsCtsPassage, subinstances of CtsTextMetadata, to retrieve the valid informations. Maybe something is more powerfull ?

get_creator (*lang=None*)

Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_description (*lang=None*)

Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (*lang=None*)

Get the subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)

Get the title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

id

Identifier of the text

Returns Identifier of the text

Return type *text_type*

last

Last CapitainsCtsPassage

Return type Passage

lastId

Last child of current CapitainsCtsPassage

Return type str

Returns Last passage Node representation

metadata

Metadata information about the text

Returns Collection object with metadata about the text

Return type Metadata

next

Get Next CapitainsCtsPassage

Return type Passage

nextId

Next passage

Returns Next passage at same level

Return type None, Reference

parent

Parent CapitainsCtsPassage

Return type Passage

parentId

Parent Node

Return type str

prev

Get Previous CapitainsCtsPassage

Return type Passage

prevId

Get the Previous passage reference

Returns Previous passage reference at the same level

Return type None, Reference

reference

URN CapitainsCtsPassage Reference

Returns Reference

Return type Reference

set_creator(value, lang)

Set the DC Creator literal value

Parameters lang – Language in which the value is

set_description(value, lang=None)

Set the DC Description literal value

Parameters lang – Language in which the value is

set_metadata_from_collection(text_metadata)

Set the object metadata using its collections recursively

Parameters `text_metadata` (*CtsEditionMetadata or CtsTranslationMetadata*) – Object representing the current text as a collection

set_subject (*value, lang=None*)
Set the DC Subject literal value

Parameters `lang` – Language in which the value is

set_title (*value, lang=None*)
Set the DC Title literal value

Parameters `lang` – Language in which the value is

siblingsId
Siblings Identifiers of the passage

Return type (`str, str`)

text
String representation of the text

Returns String representation of the text

Return type `text_type`

textObject
CtsTextMetadata Object. Required for NextPrev

Return type `CapitainsCtsText`

tostring (*args, **kwargs)
Transform the CapitainsCtsPassage in XML string

Parameters

- **args** – Ordered arguments for etree.tostring() (except the first one)
- **kwargs** – Named arguments

Returns

urn
URN Identifier of the object

Return type `URN`

xml
XML Representation of the CapitainsCtsPassage

Return type `lxml.etree._Element`

Returns XML element representing the passage

xpath (*args, **kwargs)
Perform XPath on the passage XML

Parameters

- **args** – Ordered arguments for etree._Element().xpath()
- **kwargs** – Named arguments

Returns Result list

Return type `list(etree._Element)`

CTS API Texts

Formerly MyCapytain.resources.texts.api (< 2.0.0)

```
class MyCapytain.resources.texts.remote.cts.CtsText(urn, retriever, citation=None,
                                                    **kwargs)
Bases: MyCapytain.resources.texts.remote.cts.__SharedMethod__, MyCapytain.
resources.prototypes.text.CitableText
API CtsTextMetadata object
```

Parameters

- **urn** (*Union[URN, str, unicode]*) – A URN identifier
- **resource** (*CitableTextServiceRetriever*) – An API endpoint
- **citation** (*XmlCtsCitation*) – XmlCtsCitation for children level
- **id** (*List*) – Identifier of the subreference without URN informations

DEFAULT_EXPORT = `None`

DEFAULT_LANG = ‘eng’

EXPORT_TO = []

asNode ()

childIds

Identifiers of children

Returns Identifiers of children

Return type [str]

children

Children Passages

Return type iterator(*CapitainsCtsPassage*)

citation

XmlCtsCitation Object of the CtsTextMetadata

Returns XmlCtsCitation Object of the CtsTextMetadata

Return type Citation

default_exclude = []

depth

Depth of the current opbject

Returns Int representation of the depth based on URN information

Return type int

export (*output='text/plain'*, *exclude=None*, ***kwargs*)

Export the collection item in the MimETYPE required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

- **output** (*str*) – Mimetype to export to (Uses MIMETYPES)
- **exclude** (*[str]*) – Informations to exclude. Specific to implementations

Returns Object using a different representation

export_capacities
List Mimetypes that current object can export to

first
First CapitainsCtsPassage

Return type Passage

firstId
Children passage

Return type str

Returns First children of the graph. Shortcut to self.graph.children[0]

firstUrn (resource)
Parse a resource to get the first URN

Parameters resource (etree._Element) – XML Resource

Returns Tuple representing previous and next urn

Return type str

getFirstUrn (reference=None)
Get the first children URN for a given resource

Parameters reference (Reference, str) – Reference from which to find child (If None, find first reference)

Returns Children URN

Return type URN

getLabel ()
Retrieve metadata about the text

Return type Metadata

Returns Dictionary with label informations

getPassagePlus (reference=None)
Retrieve a passage and informations around it and store it in the object

Parameters reference (Reference or List of text_type) – Reference of the passage

Return type CtsPassage

Returns Object representing the passage

Raises TypeError when reference is not a list or a Reference

getPrevNextUrn (reference)
Get the previous URN of a reference of the text

Parameters reference (Union[Reference, str]) – Reference from which to find siblings

Returns (Previous CapitainsCtsPassage Reference, Next CapitainsCtsPassage Reference)

getRefs (level=1, subreference=None)
Reference available at a given level

Parameters

- **level** (*Int*) – Depth required. If not set, should retrieve first encountered level (1 based)
- **subreference** (*Reference*) – Subreference (optional)

Return type [text_type]

Returns List of levels

getTextualNode (*subreference=None*)

Retrieve a passage and store it in the object

Parameters **subreference** (*Union[Reference, URN, str, list]*) – Reference of the passage (Note : if given a list, this should be a list of string that compose the reference)

Return type *CtsPassage*

Returns Object representing the passage

Raises *TypeError* when reference is not a list or a Reference

getValidReff (*level=1, reference=None*)

Given a resource, CitableText will compute valid reffs

Parameters

- **level** (*Int*) – Depth required. If not set, should retrieve first encountered level (1 based)
- **reference** (*Reference*) – CapitainsCtsPassage reference

Return type *list(str)*

Returns List of levels

get_creator (*lang=None*)

Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_metadata (*key, lang=None*)

get_description (*lang=None*)

Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (*lang=None*)

Get the subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)

Get the title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph

id
Identifier of the text

Returns Identifier of the text

Return type text_type

last
Last CapitainsCtsPassage

Return type Passage

lastId
Children passage

Return type str

Returns First children of the graph. Shortcut to self.graph.children[0]

metadata
Metadata information about the text

Returns Collection object with metadata about the text

Return type Metadata

next

nextId

parent
Parent CapitainsCtsPassage

Return type Passage

parentId
Parent Node

Return type str

prev

prevId

prevnext (resource)
Parse a resource to get the prev and next urn

Parameters **resource** (etree._Element) – XML Resource

Returns Tuple representing previous and next urn

Return type (str, str)

reffs
Get all valid reffs for every part of the CitableText

Return type MyCapytain.resources.texts.tei.XmlCtsCitation

retriever
Retriever object used to query for more data

Return type CitableTextServiceRetriever

set_creator(*value, lang*)

Set the DC Creator literal value

Parameters **lang** – Language in which the value is

set_description(*value, lang=None*)

Set the DC Description literal value

Parameters **lang** – Language in which the value is

set_metadata_from_collection(*text_metadata*)

Set the object metadata using its collections recursively

Parameters **text_metadata**

(*CtsEditionMetadata* or

CtsTranslationMetadata) – Object representing the current text as a collection

set_subject(*value, lang=None*)

Set the DC Subject literal value

Parameters **lang** – Language in which the value is

set_title(*value, lang=None*)

Set the DC Title literal value

Parameters **lang** – Language in which the value is

siblingsId

text

String representation of the text

Returns String representation of the text

Return type *text_type*

urn

URN Identifier of the object

Return type *URN*

```
class MyCapytain.resources.texts.remote.cts.CtsPassage(urn,      resource,      *args,
                                                       **kwargs)
Bases:  MyCapytain.resources.texts.remote.cts.__SharedMethod__,  MyCapytain.
        resources.prototypes.text.Passage,      MyCapytain.resources.texts.base.tei.
        TEIResource
```

CapitainsCtsPassage representing

Parameters

- **urn** –
- **resource** –
- **retriever** –
- **args** –
- **kwargs** –

DEFAULT_EXPORT = ‘text/plain’

EXPORT_TO = [‘python/lxml’, ‘text/xml’, ‘python/NestedDict’, ‘text/plain’, ‘text/xml:tei’]

asNode()

childIds

Identifiers of children

Returns Identifiers of children

Return type [str]

children

Children Passages

Return type iterator(*CapitainsCtsPassage*)

citation

XmlCtsCitation Object of the CtsTextMetadata

Returns XmlCtsCitation Object of the CtsTextMetadata

Return type *Citation*

default_exclude = []

depth

Depth of the current opbject

Returns Int representation of the depth based on URN information

Return type int

export (*output=None, exclude=None, **kwargs*)

Export the collection item in the Mimetype required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

- **output** (str) – Mimetype to export to (Uses MyCapytain.common.constants.Mimetypes)
- **exclude** ([str]) – Information to exclude. Specific to implementations

Returns Object using a different representation

export_capacities

List Mimetypes that current object can export to

first

First CapitainsCtsPassage

Return type Passage

firstId

Children passage

Return type str

Returns First children of the graph. Shortcut to self.graph.children[0]

firstUrn (*resource*)

Parse a resource to get the first URN

Parameters **resource** (etree._Element) – XML Resource

Returns Tuple representing previous and next urn

Return type str

getFirstUrn (*reference=None*)

Get the first children URN for a given resource

Parameters **reference** (Reference, str) – Reference from which to find child (If None, find first reference)

Returns Children URN

Return type *URN*

getLabel()

Retrieve metadata about the text

Return type Metadata

Returns Dictionary with label informations

getPassagePlus (*reference=None*)

Retrieve a passage and informations around it and store it in the object

Parameters **reference** (*Reference* or *List of text_type*) – Reference of the passage

Return type *CtsPassage*

Returns Object representing the passage

Raises *TypeError* when reference is not a list or a Reference

getPrevNextUrn (*reference*)

Get the previous URN of a reference of the text

Parameters **reference** (*Union[Reference, str]*) – Reference from which to find siblings

Returns (Previous CapitainsCtsPassage Reference, Next CapitainsCtsPassage Reference)

getReffs (*level=1, subreference=None*)

Reference available at a given level

Parameters

- **level** (*Int*) – Depth required. If not set, should retrieve first encountered level (1 based)
- **subreference** (*Reference*) – Subreference (optional)

Return type [text_type]

Returns List of levels

getTextualNode (*subreference=None*)

Retrieve a passage and store it in the object

Parameters **subreference** (*Union[Reference, URN, str, list]*) – Reference of the passage (Note : if given a list, this should be a list of string that compose the reference)

Return type *CtsPassage*

Returns Object representing the passage

Raises *TypeError* when reference is not a list or a Reference

getValidReff (*level=1, reference=None*)

Given a resource, CitableText will compute valid reffs

Parameters

- **level** (*Int*) – Depth required. If not set, should retrieve first encountered level (1 based)
- **reference** (*Reference*) – CapitainsCtsPassage reference

Return type *list(str)*

Returns List of levels

get_creator (*lang=None*)
Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_metadata (*key, lang=None*)

get_description (*lang=None*)
Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (*lang=None*)
Get the subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)
Get the title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph

id

last
Last CapytainsCtsPassage

Return type Passage

lastId
Children passage

Return type str

Returns First children of the graph. Shortcut to self.graph.children[0]

metadata
Metadata information about the text

Returns Collection object with metadata about the text

Return type Metadata

next
Get Next CapytainsCtsPassage

Return type Passage

nextId

Shortcut for getting the following passage identifier

Return type *Reference*

Returns Following passage reference

parent

Parent CapitainsCtsPassage

Return type Passage

parentId

Shortcut for getting the parent passage identifier

Return type *Reference*

Returns Following passage reference

prev

Get Previous CapitainsCtsPassage

Return type Passage

prevId

Previous passage Identifier

Return type *CtsPassage*

Returns Previous passage at same level

prevnext (resource)

Parse a resource to get the prev and next urn

Parameters **resource** (*etree._Element*) – XML Resource

Returns Tuple representing previous and next urn

Return type (str, str)

reference**retriever**

Retriever object used to query for more data

Return type CitableTextServiceRetriever

set_creator (value, lang)

Set the DC Creator literal value

Parameters **lang** – Language in which the value is

set_description (value, lang=None)

Set the DC Description literal value

Parameters **lang** – Language in which the value is

set_metadata_from_collection (text_metadata)

Set the object metadata using its collections recursively

Parameters **text_metadata** (*CtsEditionMetadata* or
CtsTranslationMetadata) – Object representing the current text as a collection

set_subject (value, lang=None)

Set the DC Subject literal value

Parameters **lang** – Language in which the value is

set_title (*value*, *lang=None*)

Set the DC Title literal value

Parameters **lang** – Language in which the value is

siblingsId

Shortcut for getting the previous and next passage identifier

Return type *Reference*

Returns Following passage reference

text

String representation of the text

Returns String representation of the text

Return type *text_type*

urn

URN Identifier of the object

Return type *URN*

xml

XML Representation of the CapitainsCtsPassage

Return type *lxml.etree._Element*

Returns XML element representing the passage

Collections

Metadata

```
class MyCapytain.resources.prototypes.metadata.Collection(identifier='', *args, **kwargs)
```

Bases: MyCapytain.common.base.Exportable

Collection represents any resource's metadata. It has members and parents

Variables

- **properties** – Properties of the collection
- **parents** – Parent of the node from the direct parent to the highest ascendant
- **metadata** – Metadata

DEFAULT_EXPORT = None

EXPORT_TO = ['application/ld+json', 'application/ld+json:DTS', 'application/rdf+xml']

MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')

TYPE_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')

asNode()

Node representation of the collection in the graph

Return type *URIRef*

capabilities

children

Dictionary of childrens {Identifier: Collection}

Return type `dict`

descendants
Any descendant (no max level) of the collection's item

Return type [Collection]

export (`output=None`, `**kwargs`)
Export the collection item in the MimETYPE required.

Parameters `output` (`str`) – MimETYPE to export to (Uses `MyCapytain.common.utils.Mimetypes`)

Returns Object using a different representation

export_capacities
List MimETYPES that current object can export to

get_label (`lang=None`)
Return label for given lang or any default

Parameters `lang` – Language to request

Returns Label value

Return type Literal

graph
RDFLib Graph space

Return type Graph

id

members
Children of the collection's item

Return type [Collection]

metadata

model

parent
Parent of current object

Return type Collection

parents
Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

readable
Readable property should return elements where the element can be queried for `getPassage` / `getReffs`

readableDescendants
List of element available which are readable

Return type [Collection]

set_label (`label, lang`)
Add the label of the collection in given lang

Parameters

- `label` – Label Value

- **lang** – Language code

size

type

version

```
class MyCapytain.resources.prototypes.metadata.ResourceCollection(identifier='',
                                                               *args,
                                                               **kwargs)
```

Bases: MyCapytain.resources.prototypes.metadata.Collection

DEFAULT_EXPORT = None

EXPORT_TO = ['application/ld+json', 'application/ld+json:DTS', 'application/rdf+xml']

MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')

TYPE_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')

asNode()

 Node representation of the collection in the graph

Return type URIRef

capabilities

children

 Dictionary of childrens {Identifier: Collection}

Return type dict

descendants

 Any descendant (no max level) of the collection's item

Return type [Collection]

export(output=None, **kwargs)

 Export the collection item in the Mimetype required.

Parameters **output** (str) – Mimetype to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

export_capacities

 List Mimetype that current object can export to

get_creator(lang=None)

 Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_description(lang=None)

 Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_label (*lang=None*)

Return label for given lang or any default

Parameters **lang** – Language to request

Returns Label value

Return type Literal

get_subject (*lang=None*)

Get the subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)

Get the title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph

RDFLib Graph space

Return type Graph

id**lang**

Languages this text is in

Returns List of available languages

members

Children of the collection's item

Return type [Collection]

metadata**model****parent**

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

readable

Readable property should return elements where the element can be queried for getPassage / getReffs

readableDescendants

List of element available which are readable

Return type [Collection]

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

size

type

version

CTS inventory

```
class MyCapytain.resources.collections.cts.XmlCtsCitation(name=None, xpath=None,  
scope=None, refs-  
Decl=None, child=None)
```

Bases: *MyCapytain.common.reference.Citation*

XmlCtsCitation XML implementation for CtsTextInventoryMetadata

DEFAULT_EXPORT = ‘text/xml:CTS’

EXPORT_TO = [‘text/xml:CTS’, ‘text/xml:tei’]

attribute

Attribute that serves as a reference getter

child

Child of a citation

Type XmlCtsCitation or None

Example XmlCtsCitation.name==poem would have a child XmlCtsCitation.name==line

escape = re.compile(‘(?)’)

export (output=None, **kwargs)

Export the collection item in the Mimetype required.

Parameters **output** (str) – Mimetype to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

export_capacities

List Mimetypes that current object can export to

fill (passage=None, xpath=None)

Fill the xpath with given informations

Parameters

- **passage** (*Reference or list or None. Can be list of None and not None*) – CapitainsCtsPassage reference
- **xpath** (Boolean) – If set to True, will return the replaced self.xpath value and not the whole self.refsDecl

Return type basestring

Returns Xpath to find the passage

```

citation = XmlCtsCitation(name="line", scope="/TEI/text/body/div/div[@n='?"]",
                           xpath="//l[@n='?']")
print(citation.fill(["1", None]))
# /TEI/text/body/div/div[@n='1']//l[@n]
print(citation.fill(None))
# /TEI/text/body/div/div[@n]//l[@n]
print(citation.fill(Reference("1.1")))
# /TEI/text/body/div/div[@n='1']//l[@n='1']
print(citation.fill("1", xpath=True))
# //l[@n='1']

```

static ingest (resource, element=None, xpath='ti:citation')

Ingest xml to create a citation

Parameters

- **resource** – XML on which to do xpath
- **element** – Element where the citation should be stored
- **xpath** – XPath to use to retrieve citation

Returns XmlCtsCitation**isEmpty ()**

Check if the citation has not been set

Returns True if nothing was setup**Return type** bool**name**

Type of the citation represented

Type text_type**Example** Book, Chapter, Textpart, Section, Poem...**refsDecl**

ResfDecl expression of the citation scheme

Return type str**Example** /tei:TEI/tei:text/tei:body/tei:div//tei:l[@n='1']**scope**

CtsTextInventoryMetadata scope property of a citation (ie. identifier of all element but the last of the citation)

Type basestring**Example** /tei:TEI/tei:text/tei:body/tei:div**xpath**

CtsTextInventoryMetadata xpath property of a citation (ie. identifier of the last element of the citation)

Type basestring**Example** //tei:l[@n='?']

```

class MyCapytain.resources.collections.cts.XmlCtsCommentaryMetadata (urn='',
                                                               parent=None,
                                                               lang=None)

```

Bases: MyCapytain.resources.prototypes.cts.inventory.CtsCommentaryMetadata,
 MyCapytain.resources.collections.cts.XmlCtsTextMetadata

Create a commentary subtyped PrototypeText object

`CTS_LINKS = [rdfs.term.URIRef('http://chs.harvard.edu/xmlns/cts/about')]`

`CTS_MODEL = 'CtsCollection'`

`CTS_PROPERTIES = [rdfs.term.URIRef('http://chs.harvard.edu/xmlns/cts/label'), rdfs.term.URIRef('http://chs.harva`

`DC_TITLE_KEY = rdfs.term.URIRef('http://chs.harvard.edu/xmlns/cts/label')`

`DEFAULT_EXPORT = 'python/lxml'`

`EXPORT_TO = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']`

`MODEL_URI = rdfs.term.URIRef('http://w3id.org/dts-ontology/resource')`

`SUBTYPE = 'commentary'`

`TYPE_URI = rdfs.term.URIRef('http://chs.harvard.edu/xmlns/cts/commentary')`

`asNode()`

Node representation of the collection in the graph

Return type `URIRef`

`capabilities`

`children`

Dictionary of childrens {Identifier: Collection}

Return type `dict`

`descendants`

Descendants of the collection's item

Warning: CapitainsCtsText has no Descendants

Return type `list`

`editions()`

Get all editions of the texts

Returns List of editions

Return type `[CtsTextMetadata]`

`export(output=None, **kwargs)`

Export the collection item in the MimETYPE required.

Parameters `output` (`str`) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

`export_capacities`

List Mimetypes that current object can export to

`get_creator(lang=None)`

Get the DC Creator literal value

Parameters `lang` – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_property (*prop, lang=None*)
Set given property in CTS Namespace

Parameters

- **prop** – Property to get (Without namespace)
- **lang** – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type `dict` or Literal

get_description (*lang=None*)
Get the DC description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_label (*lang=None*)
Return label for given lang or any default

Parameters **lang** – Language to request

Returns Label value

Return type Literal

get_link (*prop*)
Get given link in CTS Namespace

Parameters **prop** – Property to get (Without namespace)

Returns whole set of values

Return type `list`

get_subject (*lang=None*)
Get the DC subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)
Get the DC Title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph
RDFLib Graph space

Return type Graph

id

lang

Languages this text is in

Returns List of available languages

members

Children of the collection's item

Warning: CapitainsCtsText has no children

Return type *list*

metadata

model

parent

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

static parse (*resource, parent=None*)

parse_metadata (*obj, xml*)

Parse a resource to feed the object

Parameters

- **obj** (*XmLCtsTextMetadata*) – Obj to set metadata of
- **xml** (*lxml.etree._Element*) – An xml representation object

readable

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (*prop, value, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)

- **value** – Value to set for given property

size**subtype**

Subtype of the object

Returns string representation of subtype

translations (*key=None*)

Get translations in given language

Parameters **key** – Language ISO Code to filter on

Returns

type**urn****version**

```
class MyCapytain.resources.collections.cts.XmlCtsEditionMetadata(urn='', parent=None, lang=None)
Bases: MyCapytain.resources.prototypes.cts.inventory.CtsEditionMetadata, MyCapytain.resources.collections.cts.XmlCtsTextMetadata
Create an edition subtyped CtsTextMetadata object
CTS_LINKS = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/about')]
CTS_MODEL = 'CtsCollection'
CTS_PROPERTIES = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label'), rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/resource')]
DC_TITLE_KEY = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label')
DEFAULT_EXPORT = 'python/lxml'
EXPORT_TO = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']
MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/resource')
SUBTYPE = 'edition'
TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts.edition')
```

asNode()

Node representation of the collection in the graph

Return type URIRef

capabilities**children**

Dictionary of childrens {Identifier: Collection}

Return type dict

descendants

Descendants of the collection's item

Warning: CapytainsCtsText has no Descendants

Return type list

editions()

Get all editions of the texts

Returns List of editions

Return type [CtsTextMetadata]

export (*output=None*, ***kwargs*)

Export the collection item in the MimETYPE required.

Parameters **output** (*str*) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

export_capacities

List MimETYPES that current object can export to

get_creator (*lang=None*)

Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_property (*prop*, *lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to get (Without namespace)
- **lang** – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type dict or Literal

get_description (*lang=None*)

Get the DC description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_label (*lang=None*)

Return label for given lang or any default

Parameters **lang** – Language to request

Returns Label value

Return type Literal

get_link (*prop*)

Get given link in CTS Namespace

Parameters **prop** – Property to get (Without namespace)

Returns whole set of values

Return type list

get_subject (*lang=None*)

Get the DC subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)

Get the DC Title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph

RDFLib Graph space

Return type Graph

id**lang**

Languages this text is in

Returns List of available languages

members

Children of the collection's item

Warning: CapitainsCtsText has no children

Return type *list*

metadata**model****parent**

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

static parse (*resource, parent=None*)**parse_metadata** (*obj, xml*)

Parse a resource to feed the object

Parameters

- **obj** (*XmLCtsTextMetadata*) – Obj to set metadata of

- **xml** (*lxml.etree._Element*) – An xml representation object

readable

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (*prop, value, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size**subtype**

Subtype of the object

Returns string representation of subtype

translations (*key=None*)

Get translations in given language

Parameters **key** – Language ISO Code to filter on

Returns

type**urn****version**

```
class MyCapytain.resources.collections.cts.XmlCtsTextInventoryMetadata (name='defaultInventory',
                                                               parent=None)
Bases: MyCapytain.resources.prototypes.cts.inventory.CtsTextInventoryMetadata
Represents a CTS Inventory file
CTS_LINKS = []
CTS_MODEL = 'CtsCollection'
CTS_PROPERTIES = []
DC_TITLE_KEY = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/name')
```

```
DEFAULT_EXPORT = 'python/lxml'
EXPORT_TO = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']
MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')
TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/TextInventory')

asNode ()
    Node representation of the collection in the graph

    Return type URIRef

capabilities

children
    Dictionary of childrens {Identifier: Collection}

    Return type dict

descendants
    Any descendant (no max level) of the collection's item

    Return type [Collection]

export (output=None, **kwargs)
    Export the collection item in the Mimetype required.

    Parameters output (str) – Mimetype to export to (Uses MyCapytain.common.utils.Mimetypes)

    Returns Object using a different representation

export_capacities
    List Mimetype that current object can export to

get_cts_property (prop, lang=None)
    Set given property in CTS Namespace

    Parameters
        • prop – Property to get (Without namespace)
        • lang – Language to get for given value

    Returns Value or default if lang is set, else whole set of values

    Return type dict or Literal

get_label (lang=None)
    Return label for given lang or any default

    Parameters lang – Language to request

    Returns Label value

    Return type Literal

get_link (prop)
    Get given link in CTS Namespace

    Parameters prop – Property to get (Without namespace)

    Returns whole set of values

    Return type list
```

graph

RDFLib Graph space

Return type Graph

id

members

Children of the collection's item

Return type [Collection]

metadata

model

parent

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

static parse (resource)

Parse a resource

Parameters

- **resource** – Element representing the text inventory
- **type** – basestring, etree._Element

readable

Readable property should return elements where the element can be queried for getPassage / getReffs

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (prop, value, lang=None)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (label, lang)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (prop, value)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size**textgroups**

Textgroups

Returns Dictionary of textgroups**Return type** defaultdict(CtsTextgroupMetadata)**type****urn****version**

```
class MyCapytain.resources.collections.cts.XmlCtsTextMetadata(urn='',
                                                               parent=None,
                                                               lang=None)
```

Bases: MyCapytain.resources.prototypes.cts.inventory.CtsTextMetadata

Represents a CTS CtsTextMetadata

CTS_LINKS = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/about')]

CTS_MODEL = 'CtsCollection'

CTS_PROPERTIES = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label'), rdflib.term.URIRef('http://chs.harva')]

DC_TITLE_KEY = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label')

DEFAULT_EXPORT = 'python/lxml'

EXPORT_TO = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']

MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/resource')

SUBTYPE = 'unknown'

TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/text')

asNode()

Node representation of the collection in the graph

Return type URIRef**capabilities****children**

Dictionary of childrens {Identifier: Collection}

Return type dict**descendants**

Descendants of the collection's item

Warning: CapitainsCtsText has no Descendants

Return type list**editions()**

Get all editions of the texts

Returns List of editions

Return type [CtsTextMetadata]

export (*output=None*, ***kwargs*)

Export the collection item in the MimETYPE required.

Parameters **output** (*str*) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

export_capacities

List Mimetypes that current object can export to

get_creator (*lang=None*)

Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_property (*prop, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to get (Without namespace)
- **lang** – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type dict or Literal

get_description (*lang=None*)

Get the DC description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_label (*lang=None*)

Return label for given lang or any default

Parameters **lang** – Language to request

Returns Label value

Return type Literal

get_link (*prop*)

Get given link in CTS Namespace

Parameters **prop** – Property to get (Without namespace)

Returns whole set of values

Return type list

get_subject (*lang=None*)

Get the DC subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation
Return type Literal

get_title (*lang=None*)
Get the DC Title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph
RDFLib Graph space

Return type Graph

id

lang
Languages this text is in

Returns List of available languages

members

Children of the collection's item

Warning: CapitainsCtsText has no children

Return type *list*

metadata

model

parent

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

static parse_metadata (*obj, xml*)

Parse a resource to feed the object

Parameters

- **obj** (*XmLCtsTextMetadata*) – Obj to set metadata of
- **xml** (*lxml.etree._Element*) – An xml representation object

readable

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (*prop, value, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size

subtype

Subtype of the object

Returns string representation of subtype

translations (*key=None*)

Get translations in given language

Parameters **key** – Language ISO Code to filter on

Returns

type

urn

version

```
class MyCapytain.resources.collections.cts.XmlCtsTextgroupMetadata(urn='', parent=None)
Bases: MyCapytain.resources.prototypes.cts.inventory.CtsTextgroupMetadata
Represents a CTS Textgroup in XML

CTS_LINKS = []
CTS_MODEL = 'CtsCollection'

CTS_PROPERTIES = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/groupname')]

DC_TITLE_KEY = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/groupname')

DEFAULT_EXPORT = 'python/lxml'

EXPORT_TO = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']

MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')

TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/textgroup')

asNode()
Node representation of the collection in the graph
```

Return type URIRef

capabilities

children
Dictionary of childrens {Identifier: Collection}

Return type dict

descendants
Any descendant (no max level) of the collection's item

Return type [Collection]

export (*output=None*, ***kwargs*)
Export the collection item in the Mimetype required.

Parameters `output` (*str*) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

export_capacities
List Mimetypes that current object can export to

get_cts_property (*prop*, *lang=None*)
Set given property in CTS Namespace

Parameters

- `prop` – Property to get (Without namespace)
- `lang` – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type dict or Literal

get_label (*lang=None*)
Return label for given lang or any default

Parameters `lang` – Language to request

Returns Label value

Return type Literal

get_link (*prop*)
Get given link in CTS Namespace

Parameters `prop` – Property to get (Without namespace)

Returns whole set of values

Return type list

graph
RDFLib Graph space

Return type Graph

id

members
Children of the collection's item

Return type [Collection]

metadata

model

parent

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

static parse (*resource*, *parent*=None)

Parse a textgroup resource

Parameters

- **resource** – Element representing the textgroup
- **parent** – Parent of the textgroup

readable

Readable property should return elements where the element can be queried for getPassage / getReffs

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (*prop*, *value*, *lang*=None)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label*, *lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop*, *value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size

type

update (*other*)

Merge two Textgroup Objects.

•Original (left Object) keeps his parent.

- Added document merges with work if it already exists

Parameters `other` (`CtsTextgroupMetadata`) – Textgroup object

Returns Textgroup Object

Return type `CtsTextgroupMetadata`

urn

version

works

Works

Returns Dictionary of works

Return type `defaultdict(PrototypeWorks)`

```
class MyCapytain.resources.collections.cts.XmlCtsTranslationMetadata (urn='',
    par-
    ent=None,
    lang=None)
Bases: MyCapytain.resources.prototypes.cts.inventory.CtsTranslationMetadata,
MyCapytain.resources.collections.cts.XmlCtsTextMetadata

Create a translation subtyped CtsTextMetadata object
CTS_LINKS = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/about')]
CTS_MODEL = 'CtsCollection'
CTS_PROPERTIES = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label'), rdflib.term.URIRef('http://chs.harva
DC_TITLE_KEY = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label')
DEFAULT_EXPORT = 'python/lxml'
EXPORT_TO = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']
MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/resource')
SUBTYPE = 'translation'
TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/translation')
asNode()
Node representation of the collection in the graph
```

Return type `URIRef`

capabilities

children

Dictionary of childrens {Identifier: Collection}

Return type `dict`

descendants

Descendants of the collection's item

Warning: CapitainsCtsText has no Descendants

Return type `list`

editions()

Get all editions of the texts

Returns List of editions

Return type [CtsTextMetadata]

export (*output=None*, ***kwargs*)

Export the collection item in the MimETYPE required.

Parameters **output** (*str*) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

export_capacities

List Mimetypes that current object can export to

get_creator (*lang=None*)

Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_property (*prop*, *lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to get (Without namespace)
- **lang** – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type dict or Literal

get_description (*lang=None*)

Get the DC description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_label (*lang=None*)

Return label for given lang or any default

Parameters **lang** – Language to request

Returns Label value

Return type Literal

get_link (*prop*)

Get given link in CTS Namespace

Parameters **prop** – Property to get (Without namespace)

Returns whole set of values

Return type list

get_subject (*lang=None*)

Get the DC subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)

Get the DC Title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph

RDFLib Graph space

Return type Graph

id**lang**

Languages this text is in

Returns List of available languages

members

Children of the collection's item

Warning: CapitainsCtsText has no children

Return type *list*

metadata**model****parent**

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

static parse (*resource, parent=None*)**parse_metadata** (*obj, xml*)

Parse a resource to feed the object

Parameters

- **obj** (*XmLCtsTextMetadata*) – Obj to set metadata of

- **xml** (*lxml.etree._Element*) – An xml representation object

readable

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (*prop, value, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size

subtype

Subtype of the object

Returns string representation of subtype

translations (*key=None*)

Get translations in given language

Parameters **key** – Language ISO Code to filter on

Returns

type

urn

version

```
class MyCapytain.resources.collections.cts.XmlCtsWorkMetadata(urn=None, parent=None)
```

Bases: MyCapytain.resources.prototypes.cts.inventory.CtsWorkMetadata

Represents a CTS Textgroup in XML

CTS_LINKS = []

CTS_MODEL = ‘CtsCollection’

CTS_PROPERTIES = [rdflib.term.URIRef(‘http://chs.harvard.edu/xmlns/cts/title’)]

DC_TITLE_KEY = rdflib.term.URIRef(‘http://chs.harvard.edu/xmlns/cts/title’)

DEFAULT_EXPORT = ‘python/lxml’

```
EXPORT_TO = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']
MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')
TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/work')

asNode()
    Node representation of the collection in the graph
    Return type URIRef

capabilities
children
    Dictionary of childrens {Identifier: Collection}
    Return type dict
descendants
    Any descendant (no max level) of the collection's item
    Return type [Collection]
export (output=None, **kwargs)
    Export the collection item in the MimETYPE required.
    Parameters output (str) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)
    Returns Object using a different representation
export_capacities
    List MimETYPES that current object can export to
get_cts_property (prop, lang=None)
    Set given property in CTS Namespace
    Parameters
        • prop – Property to get (Without namespace)
        • lang – Language to get for given value
    Returns Value or default if lang is set, else whole set of values
    Return type dict or Literal
get_label (lang=None)
    Return label for given lang or any default
    Parameters lang – Language to request
    Returns Label value
    Return type Literal
get_link (prop)
    Get given link in CTS Namespace
    Parameters prop – Property to get (Without namespace)
    Returns whole set of values
    Return type list
get_translation_in (key=None)
    Find a translation with given language
```

Parameters **key** (*text_type*) – Language to find

Return type [CtsTextMetadata]

Returns List of available translations

graph

RDFLib Graph space

Return type Graph

id

lang

Languages this text is in

Returns List of available languages

members

Children of the collection's item

Return type [Collection]

metadata

model

parent

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

static parse (*resource*, *parent=None*)

Parse a resource

Parameters

- **resource** – Element representing a work
- **type** – basestring, etree._Element
- **parent** (XmlCtsTextgroupMetadata) – Parent of the object

readable

Readable property should return elements where the element can be queried for getPassage / getReffs

readableDescendants

List of elements available which are readable

Return type [Collection]

set_cts_property (*prop*, *value*, *lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size**texts**

Texts

Returns Dictionary of texts

Return type defaultdict(PrototypeTexts)

type**update** (*other*)

Merge two XmlCtsWorkMetadata Objects.

- Original (left Object) keeps his parent.
- Added document overwrite text if it already exists

Parameters **other** (*CtsWorkMetadata*) – XmlCtsWorkMetadata object

Returns XmlCtsWorkMetadata Object

Rtype XmlCtsWorkMetadata

urn**version**

MyCapytain.resources.collections.cts.**xpathDict** (*xml, xpath, cls, parent, **kwargs*)

Returns a default Dict given certain information

Parameters

- **xml** (*etree*) – An xml tree
- **xpath** (*str*) – XPath to find children
- **cls** (*inventory.Resource*) – Class identifying children
- **parent** (*CtsCollection*) – Parent of object

Return type collections.defaultdict.<basestring, inventory.Resource>

Returns Dictionary of children

CTS Inventory Prototypes

```
class MyCapytain.resources.prototypes.cts.inventory.CtsCommentaryMetadata(urn='',
    parent=None,
    lang=None)
```

Bases: MyCapytain.resources.prototypes.cts.inventory.CtsTextMetadata

Represents a CTS Commentary

Parameters

- **urn** (*str*) – Identifier of the PrototypeText
- **parent** (*PrototypeWork*) – Parent of current item
- **lang** (*Lang*) – Language of the commentary

```
CTS_LINKS = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/about')]
```

CTS_MODEL = ‘CtsCollection’

```
CTS_PROPERTIES = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label'), rdflib.term.URIRef('http://chs.harva
```

DC_TITLE_KEY = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label')

DEFAULT_EXPORT = ‘python/lxml’

EXPORT_TO = [‘text/xml:CTS’, ‘text/xml:CapiTainS’]

MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/resource')

SUBTYPE = ‘commentary’

TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/commentary')

asNode()

Node representation of the collection in the graph

Return type *URIRef*

capabilities

children

Dictionary of childrens {Identifier: Collection}

Return type *dict*

descendants

Descendants of the collection’s item

Warning: CapitainsCtsText has no Descendants

Return type *list*

editions()

Get all editions of the texts

Returns List of editions

Return type [CtsTextMetadata]

export (*output=None*, ***kwargs*)

Export the collection item in the Mimetype required.

Parameters `output` (`str`) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

export_capacities

List Mimetypes that current object can export to

get_creator (`lang=None`)

Get the DC Creator literal value

Parameters `lang` – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_property (`prop, lang=None`)

Set given property in CTS Namespace

Parameters

- `prop` – Property to get (Without namespace)
- `lang` – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type dict or Literal

get_description (`lang=None`)

Get the DC description of the object

Parameters `lang` – Lang to retrieve

Returns Description string representation

Return type Literal

get_label (`lang=None`)

Return label for given lang or any default

Parameters `lang` – Language to request

Returns Label value

Return type Literal

get_link (`prop`)

Get given link in CTS Namespace

Parameters `prop` – Property to get (Without namespace)

Returns whole set of values

Return type list

get_subject (`lang=None`)

Get the DC subject of the object

Parameters `lang` – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (`lang=None`)

Get the DC Title of the object

Parameters `lang` – Lang to retrieve

Returns Title string representation

Return type Literal

graph

RDFLib Graph space

Return type Graph

id

lang

Languages this text is in

Returns List of available languages

members

Children of the collection's item

Warning: CapitainsCtsText has no children

Return type `list`

metadata

model

parent

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

readable

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (`prop, value, lang=None`)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (`label, lang`)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link(*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size**subtype**

Subtype of the object

Returns string representation of subtype**translations**(*key=None*)

Get translations in given language

Parameters **key** – Language ISO Code to filter on**Returns****type****urn****version**

```
class MyCapytain.resources.prototypes.cts.inventory.CtsEditionMetadata(urn='',  
                                         par-  
                                         ent=None,  
                                         lang=None)
```

Bases: MyCapytain.resources.prototypes.cts.inventory.CtsTextMetadata

Represents a CTS XmlCtsEditionMetadata

Parameters

- **urn** (*str*) – Identifier of the CtsTextMetadata
- **parent** (*CtsWorkMetadata*) – Parent of current item

CTS_LINKS = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/about')]**CTS_MODEL** = 'CtsCollection'**CTS_PROPERTIES** = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label'), rdflib.term.URIRef('http://chs.harva**DC_TITLE_KEY** = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label')**DEFAULT_EXPORT** = 'python/lxml'**EXPORT_TO** = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']**MODEL_URI** = rdflib.term.URIRef('http://w3id.org/dts-ontology/resource')**SUBTYPE** = 'edition'**TYPE_URI** = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/edition')**asNode**()

Node representation of the collection in the graph

Return type URIRef**capabilities**

children

Dictionary of childrens {Identifier: Collection}

Return type `dict`

descendants

Descendants of the collection's item

Warning: CapitainsCtsText has no Descendants

Return type `list`

editions()

Get all editions of the texts

Returns List of editions

Return type [CtsTextMetadata]

export (*output=None*, ***kwargs*)

Export the collection item in the MimETYPE required.

Parameters `output` – Mimetype to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

export_capacities

List MIMETYPES that current object can export to

get_creator (*lang=None*)

Get the DC Creator literal value

Parameters `lang` – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_property (*prop*, *lang=None*)

Set given property in CTS Namespace

Parameters

- `prop` – Property to get (Without namespace)

- `lang` – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type `dict` or Literal

get_description (*lang=None*)

Get the DC description of the object

Parameters `lang` – Lang to retrieve

Returns Description string representation

Return type Literal

get_label (*lang=None*)

Return label for given lang or any default

Parameters `lang` – Language to request

Returns Label value

Return type Literal

get_link (*prop*)
Get given link in CTS Namespace

Parameters **prop** – Property to get (Without namespace)

Returns whole set of values

Return type *list*

get_subject (*lang=None*)
Get the DC subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)
Get the DC Title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph
RDFLib Graph space

Return type Graph

id

lang
Languages this text is in

Returns List of available languages

members
Children of the collection's item

Warning: CapitainsCtsText has no children

Return type *list*

metadata

model

parent
Parent of current object

Return type Collection

parents
Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

readable

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (*prop, value, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size

subtype

Subtype of the object

Returns string representation of subtype

translations (*key=None*)

Get translations in given language

Parameters **key** – Language ISO Code to filter on

Returns

type

urn

version

class MyCapytain.resources.prototypes.cts.inventory.**CtsTextInventoryCollection** (*identifier='default'*)
Bases: MyCapytain.resources.prototypes.cts.inventory.PrototypeCtsCollection

Initiate a CtsTextInventoryMetadata resource

Parameters

- **resource** (*Any*) – Resource representing the CtsTextInventoryMetadata
- **name** (*str*) – Identifier of the CtsTextInventoryMetadata

CTS_LINKS = []

CTS_MODEL = ‘CtsCollection’

```
CTS_PROPERTIES = []
DC_TITLE_KEY = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/name')
DEFAULT_EXPORT = 'python/lxml'
EXPORT_TO = ['text/xml:CTS', 'application/ld+json:DTS', 'text/xml:CTS_CapiTainS']
MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')
TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/CtsTextInventoryCollection')

asNode()
    Node representation of the collection in the graph
    Return type URIRef

capabilities

children
    Dictionary of childrens {Identifier: Collection}
    Return type dict

descendants
    Any descendant (no max level) of the collection's item
    Return type [Collection]

export (output=None, **kwargs)
    Export the collection item in the Mimetype required.
    Parameters output – Mimetype to export to (Uses MyCapytain.common.utils.Mimetypes)
    Returns Object using a different representation

export_capacities
    List Mimetype that current object can export to

get_cts_property (prop, lang=None)
    Set given property in CTS Namespace
    Parameters
        • prop – Property to get (Without namespace)
        • lang – Language to get for given value
    Returns Value or default if lang is set, else whole set of values
    Return type dict or Literal

get_label (lang=None)
    Return label for given lang or any default
    Parameters lang – Language to request
    Returns Label value
    Return type Literal

get_link (prop)
    Get given link in CTS Namespace
    Parameters prop – Property to get (Without namespace)
    Returns whole set of values
```

Return type *list*

graph

RDFLib Graph space

Return type Graph

id

members

Children of the collection's item

Return type [Collection]

metadata

model

parent

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

readable

Readable property should return elements where the element can be queried for getPassage / getReffs

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (*prop, value, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size

type

```
urn
version

class MyCapytain.resources.prototypes.cts.inventory.CtsTextInventoryMetadata(name='defaultInventory',
                                                                           parent=None)
Bases: MyCapytain.resources.prototypes.cts.inventory.PrototypeCtsCollection

Initiate a CtsTextInventoryMetadata resource

Parameters
    • resource (Any) – Resource representing the CtsTextInventoryMetadata
    • name (str) – Identifier of the CtsTextInventoryMetadata

CTS_LINKS = []
CTS_MODEL = 'CtsCollection'
CTS_PROPERTIES = []
DC_TITLE_KEY = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/name')
DEFAULT_EXPORT = 'python/lxml'
EXPORT_TO = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']
MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')
TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/TextInventory')

asNode()
    Node representation of the collection in the graph
    Return type URIRef

capabilities

children
    Dictionary of childrens {Identifier: Collection}
    Return type dict

descendants
    Any descendant (no max level) of the collection's item
    Return type [Collection]

export (output=None, **kwargs)
    Export the collection item in the MimETYPE required.
    Parameters output (str) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)
    Returns Object using a different representation

export_capacities
    List MIMETYPES that current object can export to

get_cts_property (prop, lang=None)
    Set given property in CTS Namespace

Parameters
    • prop – Property to get (Without namespace)
    • lang – Language to get for given value
```

Returns Value or default if lang is set, else whole set of values

Return type `dict` or Literal

get_label (`lang=None`)

Return label for given lang or any default

Parameters `lang` – Language to request

Returns Label value

Return type Literal

get_link (`prop`)

Get given link in CTS Namespace

Parameters `prop` – Property to get (Without namespace)

Returns whole set of values

Return type `list`

graph

RDFLib Graph space

Return type Graph

id

members

Children of the collection's item

Return type [Collection]

metadata

model

parent

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

readable

Readable property should return elements where the element can be queried for `getPassage` / `getReffs`

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (`prop, value, lang=None`)

Set given property in CTS Namespace

Parameters

- `prop` – Property to set (Without namespace)

- `value` – Value to set for given property

- `lang` – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size**textgroups**

Textgroups

Returns Dictionary of textgroups

Return type defaultdict(CtsTextgroupMetadata)

type**urn****version**

class MyCapytain.resources.prototypes.cts.inventory.CtsTextMetadata (*urn=None, parent=None, lang=None*)

Bases: MyCapytain.resources.prototypes.metadata.ResourceCollection, MyCapytain.resources.prototypes.cts.inventory.PrototypeCtsCollection

Represents a CTS CtsTextMetadata

Parameters

- **urn** (URN) – Identifier of the CtsTextMetadata
- **parent** ([PrototypeCtsCollection]) – Item parents of the current collection

Variables **urn** – URN Identifier

CTS_LINKS = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/about')]

CTS_MODEL = 'CtsCollection'

CTS_PROPERTIES = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label'), rdflib.term.URIRef('http://chs.harva

DC_TITLE_KEY = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label')

DEFAULT_EXPORT = 'python/lxml'

EXPORT_TO = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']

MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/resource')

SUBTYPE = 'unknown'

TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/text')

asNode()

Node representation of the collection in the graph

Return type URIRef

capabilities

children

Dictionary of childrens {Identifier: Collection}

Return type dict

descendants

Descendants of the collection's item

Warning: CapitainsCtsText has no Descendants

Return type list

editions ()

Get all editions of the texts

Returns List of editions

Return type [CtsTextMetadata]

export (output=None, **kwargs)

Export the collection item in the MimETYPE required.

Parameters output (str) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

export_capacities

List Mimetypes that current object can export to

get_creator (lang=None)

Get the DC Creator literal value

Parameters lang – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_property (prop, lang=None)

Set given property in CTS Namespace

Parameters

- prop – Property to get (Without namespace)

- lang – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type dict or Literal

get_description (lang=None)

Get the DC description of the object

Parameters lang – Lang to retrieve

Returns Description string representation

Return type Literal

get_label (*lang=None*)

Return label for given lang or any default

Parameters **lang** – Language to request

Returns Label value

Return type Literal

get_link (*prop*)

Get given link in CTS Namespace

Parameters **prop** – Property to get (Without namespace)

Returns whole set of values

Return type *list*

get_subject (*lang=None*)

Get the DC subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)

Get the DC Title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph

RDFLib Graph space

Return type Graph

id**lang**

Languages this text is in

Returns List of available languages

members

Children of the collection's item

Warning: CapitainsCtsText has no children

Return type *list*

metadata**model****parent**

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

readable**readableDescendants**

List of element available which are readable

Return type [Collection]

set_cts_property(*prop, value, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label(*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link(*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size**subtype**

Subtype of the object

Returns string representation of subtype

translations(*key=None*)

Get translations in given language

Parameters **key** – Language ISO Code to filter on

Returns

type**urn****version**

```
class MyCapytain.resources.prototypes.cts.inventory.CtsTextgroupMetadata(urn='',
    parent=None)
Bases: MyCapytain.resources.prototypes.cts.inventory.PrototypeCtsCollection
Represents a CTS Textgroup
```

CTS CtsTextgroupMetadata can be added to each other which would most likely happen if you take your data from multiple API or Textual repository. This works close to dictionary update in Python. See update

Parameters

- **urn** ([URN](#)) – Identifier of the CtsTextgroupMetadata
- **parent** (*CtsTextInventoryMetadata*) – Parent of the current object

Variables `urn` – URN Identifier

`CTS_LINKS = []`

`CTS_MODEL = 'CtsCollection'`

`CTS_PROPERTIES = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/groupname')]`

`DC_TITLE_KEY = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/groupname')`

`DEFAULT_EXPORT = 'python/lxml'`

`EXPORT_TO = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']`

`MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')`

`TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/textgroup')`

asNode()

Node representation of the collection in the graph

Return type `URIRef`

capabilities

children

Dictionary of childrens {Identifier: Collection}

Return type `dict`

descendants

Any descendant (no max level) of the collection's item

Return type `[Collection]`

export (`output=None, **kwargs`)

Export the collection item in the Mimetype required.

Parameters `output` (`str`) – Mimetype to export to (Uses `MyCapytain.common.utils.Mimetypes`)

Returns Object using a different representation

export_capacities

List Mimetypes that current object can export to

get_cts_property (`prop, lang=None`)

Set given property in CTS Namespace

Parameters

- **prop** – Property to get (Without namespace)
- **lang** – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type `dict` or Literal

get_label (*lang=None*)

Return label for given lang or any default

Parameters **lang** – Language to request

Returns Label value

Return type Literal

get_link (*prop*)

Get given link in CTS Namespace

Parameters **prop** – Property to get (Without namespace)

Returns whole set of values

Return type *list*

graph

RDFLib Graph space

Return type Graph

id

members

Children of the collection's item

Return type [Collection]

metadata

model

parent

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

readable

Readable property should return elements where the element can be queried for getPassage / getReffs

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (*prop, value, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link(*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size**type****update**(*other*)

Merge two Textgroup Objects.

- Original (left Object) keeps his parent.
- Added document merges with work if it already exists

Parameters **other** (*CtsTextgroupMetadata*) – Textgroup object**Returns** Textgroup Object**Return type** *CtsTextgroupMetadata***urn****version****works**

Works

Returns Dictionary of works**Return type** defaultdict(*PrototypeWorks*)

```
class MyCapytain.resources.prototypes.cts.inventory.CtsTranslationMetadata(urn='',
    parent=None,
    lang=None)
```

Bases: *MyCapytain.resources.prototypes.cts.inventory.CtsTextMetadata*

Represents a CTS XMLCtsTranslationMetadata

Parameters

- **urn** (*str*) – Identifier of the CtsTextMetadata
- **parent** (*CtsWorkMetadata*) – Parent of current item
- **lang** (*Lang*) – Language of the translation

CTS_LINKS = [r_dflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/about')]**CTS_MODEL** = 'CtsCollection'**CTS_PROPERTIES** = [r_dflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label'), r_dflib.term.URIRef('http://chs.harva**DC_TITLE_KEY** = r_dflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/label')**DEFAULT_EXPORT** = 'python/lxml'**EXPORT_TO** = ['text/xml:CTS', 'text/xml:CTS_CapiTainS']

```
MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/resource')
SUBTYPE = 'translation'
TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/translation')
```

asNode()
Node representation of the collection in the graph

Return type URIRef

capabilities

children
Dictionary of childrens {Identifier: Collection}

Return type dict

descendants

Descendants of the collection's item

Warning: CapitainsCtsText has no Descendants

Return type list

editions()
Get all editions of the texts

Returns List of editions

Return type [CtsTextMetadata]

export (output=None, **kwargs)
Export the collection item in the MimETYPE required.

Parameters output (str) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

export_capacities
List Mimetypes that current object can export to

get_creator (lang=None)
Get the DC Creator literal value

Parameters lang – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_property (prop, lang=None)
Set given property in CTS Namespace

Parameters

- prop – Property to get (Without namespace)
- lang – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type dict or Literal

get_description (*lang=None*)
Get the DC description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_label (*lang=None*)
Return label for given lang or any default

Parameters **lang** – Language to request

Returns Label value

Return type Literal

get_link (*prop*)
Get given link in CTS Namespace

Parameters **prop** – Property to get (Without namespace)

Returns whole set of values

Return type *list*

get_subject (*lang=None*)
Get the DC subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)
Get the DC Title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph
RDFLib Graph space

Return type Graph

id

lang

Languages this text is in

Returns List of available languages

members

Children of the collection's item

Warning: CapitainsCtsText has no children

Return type *list*

metadata

model

parent

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

readable

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (*prop, value, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size

subtype

Subtype of the object

Returns string representation of subtype

translations (*key=None*)

Get translations in given language

Parameters **key** – Language ISO Code to filter on

Returns

type

urn

version

```
class MyCapytain.resources.prototypes.cts.inventory.CtsWorkMetadata (urn=None,
par-
ent=None)
```

Bases: MyCapytain.resources.prototypes.cts.inventory.PrototypeCtsCollection

Represents a CTS CtsWorkMetadata

CTS CtsWorkMetadata can be added to each other which would most likely happen if you take your data from multiple API or Textual repository. This works close to dictionary update in Python. See update

Parameters

- **urn** ([URN](#)) – Identifier of the CtsWorkMetadata
- **parent** (*CtsTextgroupMetadata*) – Parent of current object

Variables **urn** – URN Identifier

```
CTS_LINKS = []
CTS_MODEL = 'CtsCollection'
CTS_PROPERTIES = [rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/title')]
DC_TITLE_KEY = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/title')
DEFAULT_EXPORT = 'python/lxml'
EXPORT_TO = ['text/xml:CTS', 'text/xml:CtsCapiTainS']
MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')
TYPE_URI = rdflib.term.URIRef('http://chs.harvard.edu/xmlns/cts/work')
asNode()
```

Node representation of the collection in the graph

Return type URIRef**capabilities****children**

Dictionary of childrens {Identifier: Collection}

Return type dict**descendants**

Any descendant (no max level) of the collection's item

Return type [Collection]**export** (*output=None, **kwargs*)

Export the collection item in the Mimetype required.

Parameters **output** (*str*) – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

export_capacities

List MimetypeS that current object can export to

get_cts_property (*prop, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to get (Without namespace)

- **lang** – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type `dict` or Literal

get_label (`lang=None`)

Return label for given lang or any default

Parameters `lang` – Language to request

Returns Label value

Return type Literal

get_link (`prop`)

Get given link in CTS Namespace

Parameters `prop` – Property to get (Without namespace)

Returns whole set of values

Return type `list`

get_translation_in (`key=None`)

Find a translation with given language

Parameters `key` (`text_type`) – Language to find

Return type [CtsTextMetadata]

Returns List of available translations

graph

RDFLib Graph space

Return type Graph

id

lang

Languages this text is in

Returns List of available languages

members

Children of the collection's item

Return type [Collection]

metadata

model

parent

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

readable

Readable property should return elements where the element can be queried for `getPassage` / `getReffs`

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (*prop, value, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size**texts**

Texts

Returns Dictionary of texts

Return type defaultdict(PrototypeTexts)

type**update** (*other*)

Merge two XmlCtsWorkMetadata Objects.

- Original (left Object) keeps his parent.
- Added document overwrite text if it already exists

Parameters **other** (*CtsWorkMetadata*) – XmlCtsWorkMetadata object

Returns XmlCtsWorkMetadata Object

Rtype XmlCtsWorkMetadata

urn**version**

class MyCapytain.resources.prototypes.cts.inventory.**PrototypeCtsCollection** (*identifier=''*)
Bases: MyCapytain.resources.prototypes.metadata.Collection

Resource represents any resource from the inventory

Parameters **identifier** (*str, URN*) – Identifier representing the CtsTextInventoryMetadata

Variables `CTS_MODEL` – String Representation of the type of collection

`CTS_LINKS = []`

`CTS_MODEL = 'CtsCollection'`

`CTS_PROPERTIES = []`

`DC_TITLE_KEY = None`

`DEFAULT_EXPORT = 'python/lxml'`

`EXPORT_TO = ['python/lxml']`

`MODEL_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')`

`TYPE_URI = rdflib.term.URIRef('http://w3id.org/dts-ontology/collection')`

`asNode()`

Node representation of the collection in the graph

Return type `URIRef`

`capabilities`

`children`

Dictionary of childrens {Identifier: Collection}

Return type `dict`

`descendants`

Any descendant (no max level) of the collection's item

Return type `[Collection]`

`export(output=None, **kwargs)`

Export the collection item in the MimETYPE required.

Parameters `output (str)` – MimETYPE to export to (Uses MyCapytain.common.utils.Mimetypes)

Returns Object using a different representation

`export_capacities`

List Mimetypes that current object can export to

`get_cts_property(prop, lang=None)`

Set given property in CTS Namespace

Parameters

- `prop` – Property to get (Without namespace)
- `lang` – Language to get for given value

Returns Value or default if lang is set, else whole set of values

Return type `dict` or Literal

`get_label(lang=None)`

Return label for given lang or any default

Parameters `lang` – Language to request

Returns Label value

Return type Literal

get_link (*prop*)

Get given link in CTS Namespace

Parameters **prop** – Property to get (Without namespace)

Returns whole set of values

Return type *list*

graph

RDFLib Graph space

Return type Graph

id**members**

Children of the collection's item

Return type [Collection]

metadata**model****parent**

Parent of current object

Return type Collection

parents

Iterator to find parents of current collection, from closest to furthest

Return type Generator[Collection]

readable

Readable property should return elements where the element can be queried for getPassage / getReffs

readableDescendants

List of element available which are readable

Return type [Collection]

set_cts_property (*prop, value, lang=None*)

Set given property in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property
- **lang** – Language to set for given value

set_label (*label, lang*)

Add the label of the collection in given lang

Parameters

- **label** – Label Value
- **lang** – Language code

set_link (*prop, value*)

Set given link in CTS Namespace

Parameters

- **prop** – Property to set (Without namespace)
- **value** – Value to set for given property

size

type

urn

version

Text Prototypes

```
class MyCapytain.resources.prototypes.text.CitableText(citation=None,          meta-
                                                       data=None, **kwargs)
Bases: MyCapytain.resources.prototypes.text.CtsNode
A CTS CitableText

DEFAULT_EXPORT = None

EXPORT_TO = []

asNode()
childIds
Identifiers of children

    Returns Identifiers of children

    Return type [str]

children
Children Passages

    Return type iterator(CapitainsCtsPassage)

citation
XmlCtsCitation Object of the CtsTextMetadata

    Returns XmlCtsCitation Object of the CtsTextMetadata

    Return type Citation

default_exclude = []

depth
Depth of the node in the global hierarchy of the text tree

    Return type int

export (output=None, exclude=None, **kwargs)
Export the collection item in the MimETYPE required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters
    • output (str) – MimETYPE to export to (Uses MyCapytain.common.constants.Mimetypes)

    • exclude ([str]) – Information to exclude. Specific to implementations

Returns Object using a different representation
```

export_capacities

List Mimetype that current object can export to

first

First CapitainsCtsPassage

Return type Passage

firstId

First child of current CapitainsCtsPassage

Return type str

Returns First passage node Information

getLabel()

Retrieve metadata about the text

Return type Collection

Returns Retrieve Label informations in a Collection format

getReffs(*level=1, subreference=None*)

Reference available at a given level

Parameters

- **level** (Int) – Depth required. If not set, should retrieve first encountered level (1 based)
- **passage** (Reference) – Subreference (optional)

Return type [text_type]

Returns List of levels

getTextualNode(*subreference*)

Retrieve a passage and store it in the object

Parameters **subreference** (str or Node or Reference) – Reference of the passage to retrieve

Return type TextualNode

Returns Object representing the passage

Raises TypeError when reference is not a list or a Reference

getValidReff(*level=1, reference=None*)

Given a resource, CitableText will compute valid reffs

Parameters

- **level** (Int) – Depth required. If not set, should retrieve first encountered level (1 based)
- **passage** (Reference) – Subreference (optional)

Return type List.text_type

Returns List of levels

get_creator(*lang=None*)

Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

```
get_cts_metadata (key, lang=None)
get_description (lang=None)
    Get the description of the object

    Parameters lang – Lang to retrieve
    Returns Description string representation
    Return type Literal

get_subject (lang=None)
    Get the subject of the object

    Parameters lang – Lang to retrieve
    Returns Subject string representation
    Return type Literal

get_title (lang=None)
    Get the title of the object

    Parameters lang – Lang to retrieve
    Returns Title string representation
    Return type Literal

graph

id
    Identifier of the text
    Returns Identifier of the text
    Return type text_type

last
    Last CapitainsCtsPassage
    Return type Passage

lastId
    Last child of current CapitainsCtsPassage
    Return type str
    Returns Last passage Node representation

metadata
    Metadata information about the text
    Returns Collection object with metadata about the text
    Return type Metadata

next
    Get Next CapitainsCtsPassage
    Return type Passage

nextId
    Next Node (Sibling)
    Return type str
```

parent
Parent CapitainsCtsPassage
Return type Passage

parentId
Parent Node
Return type str

prev
Get Previous CapitainsCtsPassage
Return type Passage

prevId
Previous Node (Sibling)
Return type str

reffs
Get all valid reffs for every part of the CitableText
Return type [str]

set_creator(value, lang)
Set the DC Creator literal value
Parameters lang – Language in which the value is

set_description(value, lang=None)
Set the DC Description literal value
Parameters lang – Language in which the value is

set_metadata_from_collection(text_metadata)
Set the object metadata using its collections recursively
Parameters text_metadata
(CtsEditionMetadata or CtsTranslationMetadata) – Object representing the current text as a collection

set_subject(value, lang=None)
Set the DC Subject literal value
Parameters lang – Language in which the value is

set_title(value, lang=None)
Set the DC Title literal value
Parameters lang – Language in which the value is

siblingsId
Siblings Node
Return type (str, str)

text
String representation of the text
Returns String representation of the text
Return type text_type

urn
URN Identifier of the object
Return type URN

```
class MyCapytain.resources.prototypes.text.CtsNode (urn=None, **kwargs)
```

```
Bases: MyCapytain.resources.prototypes.text.InteractiveTextualNode
```

Initiate a Resource object

Parameters

- **urn** ([URN](#)) – A URN identifier
- **metadata** ([Collection](#)) – Collection Information about the Item
- **citation** ([Citation](#)) – XmlCtsCitation system of the text
- **children** ([\[str\]](#)) – Current node Children's Identifier
- **parent** ([str](#)) – Parent of the current node
- **siblings** ([str](#)) – Previous and next node of the current node
- **depth** ([int](#)) – Depth of the node in the global hierarchy of the text tree
- **resource** – Resource used to navigate through the textual graph

Variables **default_exclude** – Default exclude for exports

```
DEFAULT_EXPORT = None
```

```
EXPORT_TO = []
```

```
asNode()
```

childIds

Identifiers of children

Returns Identifiers of children

Return type [\[str\]](#)

children

Children Passages

Return type iterator([CapitainsCtsPassage](#))

citation

XmlCtsCitation Object of the CtsTextMetadata

Returns XmlCtsCitation Object of the CtsTextMetadata

Return type [Citation](#)

```
default_exclude = []
```

depth

Depth of the node in the global hierarchy of the text tree

Return type [int](#)

```
export (output=None, exclude=None, **kwargs)
```

Export the collection item in the MimETYPE required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

- **output** ([str](#)) – MimETYPE to export to (Uses [MyCapytain.common.constants.Mimetypes](#))
- **exclude** ([\[str\]](#)) – Information to exclude. Specific to implementations

Returns Object using a different representation

export_capacities

List Mimetypes that current object can export to

first

First CapitainsCtsPassage

Return type Passage

firstId

First child of current CapitainsCtsPassage

Return type str

Returns First passage node Information

getLabel()

Retrieve metadata about the text

Return type Collection

Returns Retrieve Label informations in a Collection format

getReffs (level=1, subreference=None)

Reference available at a given level

Parameters

- **level** (Int) – Depth required. If not set, should retrieve first encountered level (1 based)
- **passage** (Reference) – Subreference (optional)

Return type [text_type]

Returns List of levels

getTextualNode (subreference)

Retrieve a passage and store it in the object

Parameters **subreference** (str or Node or Reference) – Reference of the passage to retrieve

Return type TextualNode

Returns Object representing the passage

Raises TypeError when reference is not a list or a Reference

getValidReff (level=1, reference=None)

Given a resource, CitableText will compute valid reffs

Parameters

- **level** (Int) – Depth required. If not set, should retrieve first encountered level (1 based)
- **passage** (Reference) – Subreference (optional)

Return type List.text_type

Returns List of levels

get_creator (lang=None)

Get the DC Creator literal value

Parameters lang – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_metadata (*key*, *lang=None*)

get_description (*lang=None*)
Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (*lang=None*)
Get the subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)
Get the title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph

id
Identifier of the text

Returns Identifier of the text

Return type text_type

last
Last CapytainsCtsPassage

Return type Passage

lastId
Last child of current CapytainsCtsPassage

Return type str

Returns Last passage Node representation

metadata
Metadata information about the text

Returns Collection object with metadata about the text

Return type Metadata

next
Get Next CapytainsCtsPassage

Return type Passage

nextId
Next Node (Sibling)

Return type str

parent
Parent CapitainsCtsPassage

Return type Passage

parentId
Parent Node

Return type str

prev
Get Previous CapitainsCtsPassage

Return type Passage

prevId
Previous Node (Sibling)

Return type str

set_creator(value, lang)
Set the DC Creator literal value

Parameters lang – Language in which the value is

set_description(value, lang=None)
Set the DC Description literal value

Parameters lang – Language in which the value is

set_metadata_from_collection(text_metadata)
Set the object metadata using its collections recursively

Parameters text_metadata
(*CtsEditionMetadata* or
CtsTranslationMetadata) – Object representing the current text as a collection

set_subject(value, lang=None)
Set the DC Subject literal value

Parameters lang – Language in which the value is

set_title(value, lang=None)
Set the DC Title literal value

Parameters lang – Language in which the value is

siblingsId
Siblings Node

Return type (str, str)

text
String representation of the text

Returns String representation of the text

Return type text_type

urn
URN Identifier of the object

Return type URN

class MyCapytain.resources.prototypes.text.**InteractiveTextualNode**(identifier=None,
**kwargs)
Bases: MyCapytain.resources.prototypes.text.TextualGraph

Node representing a text passage.

Parameters

- **identifier** (*str*) – Identifier of the text
- **metadata** (*Collection*) – Collection Information about the Item
- **citation** (*Citation*) – XmlCtsCitation system of the text
- **children** (*[str]*) – Current node Children's Identifier
- **parent** (*str*) – Parent of the current node
- **siblings** (*str*) – Previous and next node of the current node
- **depth** (*int*) – Depth of the node in the global hierarchy of the text tree
- **resource** – Resource used to navigate through the textual graph

Variables `default_exclude` – Default exclude for exports

`DEFAULT_EXPORT = None`

`EXPORT_TO = []`

`asNode()`

`childIds`

Identifiers of children

Returns Identifiers of children

Return type `[str]`

`children`

Children Passages

Return type iterator(*Capytains.CtsPassage*)

`citation`

XmlCtsCitation Object of the CtsTextMetadata

Returns XmlCtsCitation Object of the CtsTextMetadata

Return type *Citation*

`default_exclude = []`

`depth`

Depth of the node in the global hierarchy of the text tree

Return type `int`

`export` (*output=None, exclude=None, **kwargs*)

Export the collection item in the Mimetype required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

- **output** (*str*) – Mimetype to export to (Uses `MyCapytain.common.constants.Mimetypes`)
- **exclude** (*[str]*) – Information to exclude. Specific to implementations

Returns Object using a different representation

export_capacities

List Mimetypes that current object can export to

first

First CapitainsCtsPassage

Return type Passage

firstId

First child of current CapitainsCtsPassage

Return type str

Returns First passage node Information

getReffs (level=1, subreference=None)

Reference available at a given level

Parameters

- **level** (Int) – Depth required. If not set, should retrieve first encountered level (1 based)
- **passage** (Reference) – Subreference (optional)

Return type [text_type]

Returns List of levels

getTextualNode (subreference)

Retrieve a passage and store it in the object

Parameters **subreference** (str or Node or Reference) – Reference of the passage to retrieve

Return type TextualNode

Returns Object representing the passage

Raises TypeError when reference is not a list or a Reference

get_creator (lang=None)

Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_description (lang=None)

Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (lang=None)

Get the subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)

Get the title of the object

Parameters `lang` – Lang to retrieve

Returns Title string representation

Return type Literal

graph

id

Identifier of the text

Returns Identifier of the text

Return type text_type

last

Last CapitainsCtsPassage

Return type Passage

lastId

Last child of current CapitainsCtsPassage

Return type str

Returns Last passage Node representation

metadata

Metadata information about the text

Returns Collection object with metadata about the text

Return type Metadata

next

Get Next CapitainsCtsPassage

Return type Passage

nextId

Next Node (Sibling)

Return type str

parent

Parent CapitainsCtsPassage

Return type Passage

parentId

Parent Node

Return type str

prev

Get Previous CapitainsCtsPassage

Return type Passage

prevId

Previous Node (Sibling)

Return type str

set_creator (*value, lang*)

Set the DC Creator literal value

Parameters **lang** – Language in which the value is

set_description (*value, lang=None*)

Set the DC Description literal value

Parameters **lang** – Language in which the value is

set_subject (*value, lang=None*)

Set the DC Subject literal value

Parameters **lang** – Language in which the value is

set_title (*value, lang=None*)

Set the DC Title literal value

Parameters **lang** – Language in which the value is

siblingsId

Siblings Node

Return type (*str, str*)

text

String representation of the text

Returns String representation of the text

Return type *text_type*

class MyCapytain.resources.prototypes.text.**Passage** (**kwargs)

Bases: MyCapytain.resources.prototypes.text.CtsNode

CapitainsCtsPassage objects possess metadata informations

Parameters

- **urn** ([URN](#)) – A URN identifier
- **metadata** (*Collection*) – Collection Information about the Item
- **citation** ([Citation](#)) – XmlCtsCitation system of the text
- **children** (*[str]*) – Current node Children's Identifier
- **parent** (*str*) – Parent of the current node
- **siblings** (*str*) – Previous and next node of the current node
- **depth** (*int*) – Depth of the node in the global hierarchy of the text tree
- **resource** – Resource used to navigate through the textual graph

Variables **default_exclude** – Default exclude for exports

DEFAULT_EXPORT = None

EXPORT_TO = []

asNode ()

childIds

Identifiers of children

Returns Identifiers of children

Return type [*str*]

children

Children Passages

Return type iterator(*CapitainsCtsPassage*)

citation

XmlCtsCitation Object of the CtsTextMetadata

Returns XmlCtsCitation Object of the CtsTextMetadata

Return type *Citation*

default_exclude = []

depth

Depth of the node in the global hierarchy of the text tree

Return type int

export (*output=None, exclude=None, **kwargs*)

Export the collection item in the MimETYPE required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

- **output** (str) – MimETYPE to export to (Uses `MyCapytain.common.constants.Mimetypes`)
- **exclude** ([str]) – Information to exclude. Specific to implementations

Returns Object using a different representation

export_capacities

List Mimetypes that current object can export to

first

First CapitainsCtsPassage

Return type Passage

firstId

First child of current CapitainsCtsPassage

Return type str

Returns First passage node Information

getLabel()

Retrieve metadata about the text

Return type Collection

Returns Retrieve Label informations in a Collection format

getReffs (*level=1, subreference=None*)

Reference available at a given level

Parameters

- **level** (Int) – Depth required. If not set, should retrieve first encountered level (1 based)
- **passage** (Reference) – Subreference (optional)

Return type [text_type]

Returns List of levels

getTextualNode (*subreference*)
Retrieve a passage and store it in the object

Parameters **subreference** (*str or Node or Reference*) – Reference of the passage to retrieve

Return type TextualNode

Returns Object representing the passage

Raises *TypeError* when reference is not a list or a Reference

getValidReff (*level=1, reference=None*)
Given a resource, CitableText will compute valid reffs

Parameters

- **level** (*Int*) – Depth required. If not set, should retrieve first encountered level (1 based)
- **passage** (*Reference*) – Subreference (optional)

Return type List.text_type

Returns List of levels

get_creator (*lang=None*)
Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_cts_metadata (*key, lang=None*)

get_description (*lang=None*)
Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (*lang=None*)
Get the subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)
Get the title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph

id
Identifier of the text

Returns Identifier of the text

Return type text_type

last
Last CapitainsCtsPassage

Return type Passage

lastId
Last child of current CapitainsCtsPassage

Return type str

Returns Last passage Node representation

metadata
Metadata information about the text

Returns Collection object with metadata about the text

Return type Metadata

next
Get Next CapitainsCtsPassage

Return type Passage

nextId
Next Node (Sibling)

Return type str

parent
Parent CapitainsCtsPassage

Return type Passage

parentId
Parent Node

Return type str

prev
Get Previous CapitainsCtsPassage

Return type Passage

prevId
Previous Node (Sibling)

Return type str

reference

set_creator(value, lang)
Set the DC Creator literal value

Parameters lang – Language in which the value is

set_description(value, lang=None)
Set the DC Description literal value

Parameters lang – Language in which the value is

set_metadata_from_collection(text_metadata)
Set the object metadata using its collections recursively

Parameters `text_metadata` (*CtsEditionMetadata or CtsTranslationMetadata*) – Object representing the current text as a collection

set_subject (*value, lang=None*)
Set the DC Subject literal value

Parameters `lang` – Language in which the value is

set_title (*value, lang=None*)
Set the DC Title literal value

Parameters `lang` – Language in which the value is

siblingsId
Siblings Node

Return type (*str, str*)

text
String representation of the text

Returns String representation of the text

Return type `text_type`

urn
URN Identifier of the object

Return type *URN*

class `MyCapytain.resources.prototypes.text.TextualElement` (*identifier=None, metadata=None*)
Bases: `MyCapytain.common.base.Exportable`

Node representing a text passage.

Parameters

- **identifier** (*str*) – Identifier of the text
- **metadata** (*Collection*) – Collection Information about the Item

Variables `default_exclude` – Default exclude for exports

DEFAULT_EXPORT = None

EXPORT_TO = []

asNode()

default_exclude = []

export (*output=None, exclude=None, **kwargs*)
Export the collection item in the MimETYPE required.
..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

- **output** (*str*) – Mimetype to export to (Uses `MyCapytain.common.constants.Mimetypes`)
- **exclude** (*[str]*) – Information to exclude. Specific to implementations

Returns Object using a different representation

export_capacities
List MIMETYPES that current object can export to

get_creator (*lang=None*)

Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_description (*lang=None*)

Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (*lang=None*)

Get the subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)

Get the title of the object

Parameters **lang** – Lang to retrieve

Returns Title string representation

Return type Literal

graph

id

Identifier of the text

Returns Identifier of the text

Return type text_type

metadata

Metadata information about the text

Returns Collection object with metadata about the text

Return type Metadata

set_creator (*value, lang*)

Set the DC Creator literal value

Parameters **lang** – Language in which the value is

set_description (*value, lang=None*)

Set the DC Description literal value

Parameters **lang** – Language in which the value is

set_subject (*value, lang=None*)

Set the DC Subject literal value

Parameters **lang** – Language in which the value is

set_title (*value*, *lang=None*)

Set the DC Title literal value

Parameters **lang** – Language in which the value is

text

String representation of the text

Returns String representation of the text

Return type *text_type*

class MyCapytain.resources.prototypes.text.**TextualGraph** (*identifier=None*, ***kwargs*)

Bases: MyCapytain.resources.prototypes.text.TextualNode

Node representing a text passage.

Parameters

- **identifier** (*str*) – Identifier of the text
- **metadata** (*Collection*) – Collection Information about the Item
- **citation** (*Citation*) – XmlCtsCitation system of the text
- **children** (*[str]*) – Current node Children's Identifier
- **parent** (*str*) – Parent of the current node
- **siblings** (*str*) – Previous and next node of the current node
- **depth** (*int*) – Depth of the node in the global hierarchy of the text tree
- **resource** – Resource used to navigate through the textual graph

Variables **default_exclude** – Default exclude for exports

DEFAULT_EXPORT = None

EXPORT_TO = []

asNode()

childIds

Children Node

Return type *[str]*

citation

XmlCtsCitation Object of the CtsTextMetadata

Returns XmlCtsCitation Object of the CtsTextMetadata

Return type *Citation*

default_exclude = []

depth

Depth of the node in the global hierarchy of the text tree

Return type *int*

export (*output=None*, *exclude=None*, ***kwargs*)

Export the collection item in the Mimetype required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

- **output** (*str*) – Mimetype to export to (Uses `MyCapytain.common.constants.Mimetypes`)

- **exclude** ([*str*]) – Information to exclude. Specific to implementations

Returns Object using a different representation

export_capacities

List Mimetype that current object can export to

firstId

First child Node

Return type *str*

getReffs (*level*=1, *subreference*=None)

Reference available at a given level

Parameters

- **level** (*Int*) – Depth required. If not set, should retrieve first encountered level (1 based)
- **passage** ([Reference](#)) – Subreference (optional)

Return type [text_type]

Returns List of levels

getTextualNode (*subreference*)

Retrieve a passage and store it in the object

Parameters **subreference** (*str* or *Node* or [Reference](#)) – Reference of the passage to retrieve

Return type TextualNode

Returns Object representing the passage

Raises *TypeError* when reference is not a list or a Reference

get_creator (*lang*=None)

Get the DC Creator literal value

Parameters **lang** – Language to retrieve

Returns Creator string representation

Return type Literal

get_description (*lang*=None)

Get the description of the object

Parameters **lang** – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (*lang*=None)

Get the subject of the object

Parameters **lang** – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)

Get the title of the object

Parameters `lang` – Lang to retrieve

Returns Title string representation

Return type Literal

graph**id**

Identifier of the text

Returns Identifier of the text

Return type text_type

lastId

Last child Node

Return type str

metadata

Metadata information about the text

Returns Collection object with metadata about the text

Return type Metadata

nextId

Next Node (Sibling)

Return type str

parentId

Parent Node

Return type str

prevId

Previous Node (Sibling)

Return type str

set_creator (*value, lang*)

Set the DC Creator literal value

Parameters `lang` – Language in which the value is

set_description (*value, lang=None*)

Set the DC Description literal value

Parameters `lang` – Language in which the value is

set_subject (*value, lang=None*)

Set the DC Subject literal value

Parameters `lang` – Language in which the value is

set_title (*value, lang=None*)

Set the DC Title literal value

Parameters `lang` – Language in which the value is

siblingsId

Siblings Node

Return type (`str`, `str`)

text

String representation of the text

Returns String representation of the text

Return type `text_type`

```
class MyCapytain.resources.prototypes.text.TextualNode(identifier=None, citation=None, **kwargs)
Bases: MyCapytain.resources.prototypes.text.TextualElement, MyCapytain.common.reference.NodeId
```

Node representing a text passage.

Parameters

- **identifier** (`str`) – Identifier of the text
- **metadata** (`Collection`) – Collection Information about the Item
- **citation** (`Citation`) – XmlCtsCitation system of the text
- **children** (`[str]`) – Current node Children's Identifier
- **parent** (`str`) – Parent of the current node
- **siblings** (`str`) – Previous and next node of the current node
- **depth** (`int`) – Depth of the node in the global hierarchy of the text tree

Variables `default_exclude` – Default exclude for exports

`DEFAULT_EXPORT = None`

`EXPORT_TO = []`

`asNode()`

childIds

Children Node

Return type [`str`]

citation

XmlCtsCitation Object of the CtsTextMetadata

Returns XmlCtsCitation Object of the CtsTextMetadata

Return type `Citation`

`default_exclude = []`

depth

Depth of the node in the global hierarchy of the text tree

Return type `int`

`export(output=None, exclude=None, **kwargs)`

Export the collection item in the Mimetype required.

..note:: If current implementation does not have special mimetypes, reuses default_export method

Parameters

- **output** (`str`) – Mimetype to export to (Uses `MyCapytain.common.constants.Mimetypes`)

- **exclude** ([*str*]) – Information to exclude. Specific to implementations

Returns Object using a different representation

export_capacities
List Mimetypes that current object can export to

firstId
First child Node

Return type *str*

get_creator (*lang=None*)
Get the DC Creator literal value

Parameters *lang* – Language to retrieve

Returns Creator string representation

Return type Literal

get_description (*lang=None*)
Get the description of the object

Parameters *lang* – Lang to retrieve

Returns Description string representation

Return type Literal

get_subject (*lang=None*)
Get the subject of the object

Parameters *lang* – Lang to retrieve

Returns Subject string representation

Return type Literal

get_title (*lang=None*)
Get the title of the object

Parameters *lang* – Lang to retrieve

Returns Title string representation

Return type Literal

graph

id
Identifier of the text

Returns Identifier of the text

Return type *text_type*

lastId
Last child Node

Return type *str*

metadata
Metadata information about the text

Returns Collection object with metadata about the text

Return type Metadata

nextId

Next Node (Sibling)

Return type str

parentId

Parent Node

Return type str

prevId

Previous Node (Sibling)

Return type str

set_creator(value, lang)

Set the DC Creator literal value

Parameters lang – Language in which the value is

set_description(value, lang=None)

Set the DC Description literal value

Parameters lang – Language in which the value is

set_subject(value, lang=None)

Set the DC Subject literal value

Parameters lang – Language in which the value is

set_title(value, lang=None)

Set the DC Title literal value

Parameters lang – Language in which the value is

siblingsId

Siblings Node

Return type (str, str)

text

String representation of the text

Returns String representation of the text

Return type text_type

Benchmarks

In the recent attempt to boost our system, we had a look on the performance of MyCapytain with different parser. Even if as 1.0.1 xmlparser() is the recommended tool, we highly recommend to switch to lxml.objectify.parse() parser for performance. In the following benchmark run with timeit.sh on the main repo (You need PerseusDL/canonical-latinLit somewhere), the first line is run with lxml.etree, the second with objectify and the third with a pickled object.

Testing on Seneca, Single Simple Passage

- 100 loops, best of 3: 4.45 msec per loop
- 100 loops, best of 3: 4.15 msec per loop
- 100 loops, best of 3: 3.75 msec per loop

Testing range

- 100 loops, best of 3: 7.63 msec per loop
- 100 loops, best of 3: 7.72 msec per loop
- 100 loops, best of 3: 6.66 msec per loop

Testing with a deeper architecture

- 100 loops, best of 3: 18.2 msec per loop
- 100 loops, best of 3: 14.3 msec per loop
- 100 loops, best of 3: 9.31 msec per loop

Testing with a deeper architecture at the end

- 100 loops, best of 3: 18.2 msec per loop
- 100 loops, best of 3: 14.2 msec per loop
- 100 loops, best of 3: 9.34 msec per loop

Testing with a deeper architecture with range

- 100 loops, best of 3: 19.3 msec per loop
- 100 loops, best of 3: 14.3 msec per loop
- 100 loops, best of 3: 9.9 msec per loop

Testing with complicated XPATH

- 100 loops, best of 3: 751 usec per loop
- 100 loops, best of 3: 770 usec per loop
- 100 loops, best of 3: 617 usec per loop

Python Module Index

m

`MyCapytain.common.metadata`, 28
`MyCapytain.common.reference`, 30
`MyCapytain.resources.proto.text`, 124
`MyCapytain.resources.prototypes.cts.inventory`,
 98
`MyCapytain.resources.prototypes.metadata`,
 70
`MyCapytain.resources.xml`, 74
`MyCapytain.retrievers.cts5`, 33
`MyCapytain.retrievers.protoypes`, 35

Symbols

`_SimplePassage_` (class in `MyCapytain.resources.texts.local.capitains.cts`), 56
`_iter_()` (`MyCapytain.common.reference.Citation` method), 27
`_len_()` (`MyCapytain.common.reference.Citation` method), 28

A

`add()` (`MyCapytain.resolvers.utils.CollectionDispatcher` method), 15
`asNode()` (`MyCapytain.resources.texts.base.tei.TEIResource` method), 43
`asNode()` (`MyCapytain.resources.texts.local.capitains.cts.CapitainsCtsText` method), 52
`asNode()` (`MyCapytain.resources.texts.local.capitains.cts.CapitainsCtsText` method), 47
`asNode()` (`MyCapytain.resources.texts.remote.cts.CtsPassage` method), 65
`asNode()` (`MyCapytain.resources.texts.remote.cts.CtsText` method), 61

C

`CapitainsCtsPassage` (class in `MyCapytain.resources.texts.local.capitains.cts`), 51
`CapitainsCtsText` (class in `MyCapytain.resources.texts.local.capitains.cts`), 46
`childIds` (`MyCapytain.common.reference.NodeId` attribute), 24
`childIds` (`MyCapytain.resources.texts.base.tei.TEIResource` attribute), 43
`childIds` (`MyCapytain.resources.texts.local.capitains.cts._SimplePassage` attribute), 56
`childIds` (`MyCapytain.resources.texts.local.capitains.cts.CapitainsCtsText` attribute), 52
`childIds` (`MyCapytain.resources.texts.local.capitains.cts.CapitainsCtsText` attribute), 47
`childIds` (`MyCapytain.resources.texts.remote.cts.CtsPassage` attribute), 65

`childIds` (`MyCapytain.resources.texts.remote.cts.CtsText` attribute), 61
`children` (`MyCapytain.resources.texts.base.tei.TEIResource` attribute), 43
`children` (`MyCapytain.resources.texts.local.capitains.cts._SimplePassage` attribute), 56
`children` (`MyCapytain.resources.texts.local.capitains.cts.CapitainsCtsPassage` attribute), 52
`children` (`MyCapytain.resources.texts.local.capitains.cts.CapitainsCtsText` attribute), 47
`children` (`MyCapytain.resources.texts.remote.cts.CtsPassage` attribute), 66
`children` (`MyCapytain.resources.texts.remote.cts.CtsText` attribute), 61
`Citation` (class in `MyCapytain.common.reference`), 27
`citation` (`MyCapytain.resources.texts.base.tei.TEIResource` attribute), 43
`citation` (`MyCapytain.resources.texts.local.capitains.cts._SimplePassage` attribute), 56
`citation` (`MyCapytain.resources.texts.local.capitains.cts.CapitainsCtsPassage` attribute), 52
`citation` (`MyCapytain.resources.texts.local.capitains.cts.CapitainsCtsText` attribute), 47
`citation` (`MyCapytain.resources.texts.remote.cts.CtsPassage` attribute), 66
`citation` (`MyCapytain.resources.texts.remote.cts.CtsText` attribute), 61
`CollectionDispatcher` (class in `MyCapytain.resolvers.utils`), 15
`convert_subreference()` (`MyCapytain.common.reference.Reference` method), 26
`CtsCapitainsLocalResolver` (class in `MyCapytain.resolvers.cts.local`), 39
`CtsPassage` (class in `MyCapytain.resources.texts.remote.cts`), 65
`CtsText` (class in `MyCapytain.resources.texts.remote.cts`), 61

D

```

default_exclude           (MyCapy-
                         tain.resources.texts.base.tei.TEIResource
                         attribute), 43
default_exclude           (MyCapy-
                         tain.resources.texts.local.capitains.cts.CaptainsCtsPassage
                         attribute), 52
default_exclude           (MyCapy-
                         tain.resources.texts.local.capitains.cts.CaptainsCtsText
                         attribute), 47
default_exclude           (MyCapy-
                         tain.resources.texts.remote.cts.CtsPassage
                         attribute), 66
default_exclude           (MyCapy-
                         tain.resources.texts.remote.cts.CtsText
                         attribute), 61
DEFAULT_EXPORT            (MyCapy-
                           tain.resources.texts.base.tei.TEIResource
                           attribute), 43
DEFAULT_EXPORT            (MyCapy-
                           tain.resources.texts.local.capitains.cts.CaptainsCtsPassage
                           attribute), 52
DEFAULT_EXPORT            (MyCapy-
                           tain.resources.texts.local.capitains.cts.CaptainsCtsText
                           attribute), 46
DEFAULT_EXPORT            (MyCapy-
                           tain.resources.texts.remote.cts.CtsPassage
                           attribute), 65
DEFAULT_EXPORT            (MyCapy-
                           tain.resources.texts.remote.cts.CtsText
                           attribute), 61
DEFAULT_LANG              (MyCapy-
                           tain.resources.texts.remote.cts.CtsText
                           attribute), 61
depth (MyCapytain.common.reference.NodeId attribute),
      24
depth (MyCapytain.resources.texts.base.tei.TEIResource
      attribute), 43
depth (MyCapytain.resources.texts.local.capitains.cts.__SimplePassage_
      attribute), 57
depth (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsPassage
      attribute), 52
depth (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText
      attribute), 47
depth (MyCapytain.resources.texts.remote.cts.CtsPassage
      attribute), 66
depth (MyCapytain.resources.texts.remote.cts.CtsText
      attribute), 61
dispatch() (MyCapytain.resolvers.utils.CollectionDispatcher
            method), 15

```

E

```

end   (MyCapytain.common.reference.Reference
       attribute), 26

```

```

endpoint (MyCapytain.resolvers.cts.api.HttpCtsResolver
          attribute), 38
export() (MyCapytain.resources.texts.base.tei.TEIResource
          method), 43
export() (MyCapytain.resources.texts.local.capitains.cts.__SimplePassage_
          method), 57
export() (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsPassage
          method), 52
export() (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText
          method), 47
export() (MyCapytain.resources.texts.remote.cts.CtsPassage
          method), 66
export() (MyCapytain.resources.texts.remote.cts.CtsText
          method), 61
export_capacities         (MyCapy-
                           tain.resources.texts.base.tei.TEIResource
                           attribute), 43
export_capacities         (MyCapy-
                           tain.resources.texts.local.capitains.cts.__SimplePassage_
                           attribute), 57
export_capacities         (MyCapy-
                           tain.resources.texts.local.capitains.cts.CaptainsCtsPassage
                           attribute), 52
export_capacities         (MyCapy-
                           tain.resources.texts.local.capitains.cts.CaptainsCtsText
                           attribute), 47
export_capacities         (MyCapy-
                           tain.resources.texts.remote.cts.CtsPassage
                           attribute), 66
export_capacities         (MyCapy-
                           tain.resources.texts.remote.cts.CtsText
                           attribute), 62
EXPORT_TO                 (MyCapy-
                           tain.resources.texts.base.tei.TEIResource
                           attribute), 43
EXPORT_TO                 (MyCapy-
                           tain.resources.texts.local.capitains.cts.CaptainsCtsPassage
                           attribute), 52
EXPORT_TO                 (MyCapy-
                           tain.resources.texts.local.capitains.cts.CaptainsCtsText
                           attribute), 47
EXPORT_TO                 (MyCapy-
                           tain.resources.texts.remote.cts.CtsPassage
                           attribute), 65
EXPORT_TO                 (MyCapy-
                           tain.resources.texts.remote.cts.CtsText
                           attribute), 61

```

F

```

fill() (MyCapytain.common.reference.Citation
        method), 28
first  (MyCapytain.resources.texts.base.tei.TEIResource
        attribute), 44

```

```

first (MyCapytain.resources.texts.local.captains.cts.__SimplePassage_metadata()
      attribute), 57                                         (MyCapy-
                                                               tain.resources.texts.remote.cts.CtsPassage
first (MyCapytain.resources.texts.local.captains.cts.CaptainsCtsPassage.get_cts_metadata()
      attribute), 53                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsText
first (MyCapytain.resources.texts.local.captains.cts.CaptainsCtsText.get_cts_metadata()
      attribute), 47                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsText
first (MyCapytain.resources.texts.remote.cts.CtsPassage.get_description()
      attribute), 66                                         (MyCapy-
                                                               tain.resources.texts.base.tei.TEIResource
first (MyCapytain.resources.texts.remote.cts.CtsText.get_description()
      attribute), 62                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsText
firstId (MyCapytain.common.reference.NodeId attribute),
       24                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.__SimplePassage_
                                                               method), 58
firstId (MyCapytain.resources.texts.base.tei.TEIResource.get_description()
      attribute), 44                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsPassage
firstId (MyCapytain.resources.texts.local.captains.cts.__SimplePassage.get_description()
      attribute), 57                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsText
firstId (MyCapytain.resources.texts.local.captains.cts.CaptainsCtsPassage.get_cts_description()
      attribute), 53                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsText
firstId (MyCapytain.resources.texts.local.captains.cts.CaptainsCtsText.get_cts_description()
      attribute), 47                                         (MyCapy-
                                                               tain.resources.texts.remote.cts.CtsPassage
firstId (MyCapytain.resources.texts.remote.cts.CtsPassage.get_cts_description()
      attribute), 66                                         (MyCapy-
                                                               tain.resources.texts.remote.cts.CtsText
firstId (MyCapytain.resources.texts.remote.cts.CtsText.get_cts_description()
      attribute), 62                                         (MyCapy-
                                                               tain.resources.texts.remote.cts.CtsText
firstUrn() (MyCapytain.resources.texts.remote.cts.CtsPassage.get_subject()
            method), 66                                         (MyCapy-
                                                               tain.resources.texts.base.tei.TEIResource
firstUrn() (MyCapytain.resources.texts.remote.cts.CtsText.get_subject()
            method), 62                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.__SimplePassage_
                                                               method), 58

```

G

```

get_creator()                                         (MyCapy-
                                                               tain.resources.texts.base.tei.TEIResource
                                                               method), 44                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsPassage
                                                               method), 54
get_creator()                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.__SimplePassage_
                                                               method), 58                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsText
                                                               method), 48
get_creator()                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsPassage
                                                               method), 53                                         (MyCapy-
                                                               tain.resources.texts.remote.cts.CtsPassage
                                                               method), 68
get_creator()                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsText
                                                               method), 48                                         (MyCapy-
                                                               tain.resources.texts.remote.cts.CtsText
                                                               method), 63
get_creator()                                         (MyCapy-
                                                               tain.resources.texts.remote.cts.CtsPassage
                                                               method), 68                                         (MyCapy-
                                                               tain.resources.texts.base.tei.TEIResource
                                                               method), 44
get_creator()                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.__SimplePassage_
                                                               method), 58                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsPassage
                                                               method), 54
get_creator()                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsText
                                                               method), 63                                         (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsText
                                                               method), 49
get_cts_metadata() (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsPassage
                                                               method), 53                                         (MyCapy-
                                                               tain.resources.texts.remote.cts.CtsPassage
                                                               method), 68
get_cts_metadata() (MyCapy-
                                                               tain.resources.texts.local.captains.cts.CaptainsCtsText
                                                               method), 48                                         (MyCapy-
                                                               tain.resources.texts.remote.cts.CtsText
                                                               method), 63

```

```

getFirstUrn() (MyCapy- method), 62
    tain.resources.texts.remote.cts.CtsPassage
        method), 66
getFirstUrn() (MyCapy- getSiblings() (MyCapy-
    tain.resources.texts.remote.cts.CtsText
        method), 62
            tain.resolvers.cts.api.HttpCtsResolver
getLabel() (MyCapytain.resources.texts.local.capitains.cts._SimplePassage_ 39
    method), 57
getLabel() (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsPassage 39
    method), 53
getLabel() (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText 39
    method), 47
getLabel() (MyCapytain.resources.texts.remote.cts.CtsPassage) getTextualNode() (MyCapy-
    method), 67
    tain.resolvers.cts.local.CtsCapitainsLocalResolver
getLabel() (MyCapytain.resources.texts.remote.cts.CtsText) getTextualNode() (MyCapy-
    method), 62
    tain.resolvers.prototypes.Resolver
getMetadata() (MyCapy- getTextualNode() (MyCapy-
    tain.resolvers.cts.api.HttpCtsResolver
        method), 38
    tain.resolvers.cts.local.CtsCapitainsLocalResolver
getMetadata() (MyCapy- getTextualNode() (MyCapy-
    tain.resolvers.prototypes.Resolver
        method), 39
    tain.resources.texts.base.tei.TEIResource
getMetadata() (MyCapy- getTextualNode() (MyCapy-
    tain.resolvers.prototypes.Resolver
        method), 18
    tain.resources.texts.local.capitains.cts._SimplePassage_
getPassagePlus() (MyCapy- getTextualNode() (MyCapy-
    tain.resources.texts.remote.cts.CtsPassage
        method), 67
    tain.resources.texts.local.capitains.cts.CaptainsCtsPassage
getPassagePlus() (MyCapy- getTextualNode() (MyCapy-
    tain.resources.texts.remote.cts.CtsText
        method), 62
    tain.resources.texts.local.capitains.cts.CaptainsCtsText
getPrevNextUrn() (MyCapy- getTextualNode() (MyCapy-
    tain.resources.texts.remote.cts.CtsPassage
        method), 67
    tain.resources.texts.remote.cts.CtsText
getPrevNextUrn() (MyCapy- getTextualNode() (MyCapy-
    tain.resources.texts.remote.cts.CtsText
        method), 62
    tain.resources.texts.local.capitains.cts.CaptainsCtsText
getReffs() (MyCapytain.resolvers.cts.api.HttpCtsResolver getValidReff() (MyCapy-
    method), 38
    tain.resources.texts.local.capitains.cts._SimplePassage_
getReffs() (MyCapytain.resolvers.cts.local.CtsCapitainsLocalResol- getValidReff() (MyCapy-
    ler) getValidReff() (MyCapy-
    tain.resources.texts.local.capitains.cts.CaptainsCtsPassage
    method), 40
    tain.resources.local.capitains.cts.CaptainsCtsText
getReffs() (MyCapytain.resolvers.prototypes.Resolver getValidReff() (MyCapy-
    method), 18
    tain.resources.texts.local.capitains.cts.CaptainsCtsText
getReffs() (MyCapytain.resources.texts.base.tei.TEIResource getValidReff() (MyCapy-
    method), 44
    tain.resources.texts.local.capitains.cts.CaptainsCtsText
getReffs() (MyCapytain.resources.texts.local.capitains.cts._SimpleReff_ 67
    method), 57
    tain.resources.texts.remote.cts.CtsPassage
getReffs() (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsPassage 67
    method), 53
    tain.resources.local.capitains.cts.CaptainsCtsText
getReffs() (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText 63
    method), 47
    tain.resources.texts.remote.cts.CtsText
getReffs() (MyCapytain.resources.texts.remote.cts.CtsPassage) graph (MyCapytain.resources.texts.base.tei.TEIResource
    method), 67
    attribute), 45
getReffs() (MyCapytain.resources.texts.remote.cts.CtsText graph (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsPassage
    method), 62
    tain.resources.local.capitains.cts.CaptainsCtsText

```

attribute), 54
graph (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 49
graph (MyCapytains.resources.texts.remote.cts.CtsPassage attribute), 68
graph (MyCapytains.resources.texts.remote.cts.CtsText attribute), 64

H

highest (MyCapytains.common.reference.Reference attribute), 26
HttpCtsResolver (class in MyCapytains.resolvers.cts.api), 38

I

id (MyCapytains.common.reference.NodeId attribute), 24
id (MyCapytains.resources.texts.base.tei.TEIResource attribute), 45
id (MyCapytains.resources.texts.local.capitains.cts.__SimplePassage attribute), 58
id (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsPassage attribute), 54
id (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 49
id (MyCapytains.resources.texts.remote.cts.CtsPassage attribute), 68
id (MyCapytains.resources.texts.remote.cts.CtsText attribute), 64
inventory() (MyCapytains.resolvers.utils.CollectionDispatcher method), 16

L

last (MyCapytains.resources.texts.base.tei.TEIResource attribute), 45
last (MyCapytains.resources.texts.local.capitains.cts.__SimplePassage attribute), 58
last (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsPassage attribute), 54
last (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 49
last (MyCapytains.resources.texts.remote.cts.CtsPassage attribute), 68
last (MyCapytains.resources.texts.remote.cts.CtsText attribute), 64
lastId (MyCapytains.common.reference.NodeId attribute), 24
lastId (MyCapytains.resources.texts.base.tei.TEIResource attribute), 45
lastId (MyCapytains.resources.texts.local.capitains.cts.__SimplePassage attribute), 58
lastId (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsPassage attribute), 54
lastId (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 24
lastId (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 49

lastId (MyCapytains.resources.texts.remote.cts.CtsPassage attribute), 68
list (MyCapytains.common.reference.Reference attribute), 27

M

metadata (MyCapytains.resources.texts.base.tei.TEIResource attribute), 45
metadata (MyCapytains.resources.texts.local.capitains.cts.__SimplePassage attribute), 59
metadata (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsPassage attribute), 54
metadata (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 49
metadata (MyCapytains.resources.texts.remote.cts.CtsPassage attribute), 68
metadata (MyCapytains.resources.texts.remote.cts.CtsText attribute), 64
methods (MyCapytains.resolvers.utils.CollectionDispatcher attribute), 16
model () (MyCapytains.common.referenceURN static method), 25

MyCapytains.common.metadata (module), 28
MyCapytains.common.reference (module), 30
MyCapytains.resources.proto.text (module), 124
MyCapytains.resources.prototypes.cts.inventory (module), 98
MyCapytains.resources.prototypes.metadata (module), 70
MyCapytains.resources.xml (module), 74
MyCapytains.retrievers.cts5 (module), 33
MyCapytains.retrievers.prototypes (module), 35

N

namespace (MyCapytains.common.referenceURN attribute), 25
next (MyCapytains.resources.texts.base.tei.TEIResource attribute), 45
next (MyCapytains.resources.texts.local.capitains.cts.__SimplePassage attribute), 59
next (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsPassage attribute), 54
next (MyCapytains.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 49
next (MyCapytains.resources.texts.remote.cts.CtsPassage attribute), 68
next (MyCapytains.resources.texts.remote.cts.CtsText attribute), 64
nextId (MyCapytains.common.reference.NodeId attribute), 24
nextId (MyCapytains.resources.texts.base.tei.TEIResource attribute), 45

nextId (MyCapytain.resources.texts.local.capitains.cts.__SimplePassage attribute), 59
nextId (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 64
nextId (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 49
nextId (MyCapytain.resources.texts.remote.cts.CtsPassage attribute), 68
nextId (MyCapytain.resources.texts.remote.cts.CtsText attribute), 64
NodeId (class in MyCapytain.common.reference), 23

P

pagination() (MyCapytain.resolvers.cts.local.CtsCapitainsLocalResolver static method), 40
parent (MyCapytain.common.reference.Reference attribute), 27
parent (MyCapytain.resources.texts.base.tei.TEIResource attribute), 45
parent (MyCapytain.resources.texts.local.capitains.cts.__SimplePassage attribute), 59
parent (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 54
parent (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 49
parent (MyCapytain.resources.texts.remote.cts.CtsPassage attribute), 69
parent (MyCapytain.resources.texts.remote.cts.CtsText attribute), 64
parentId (MyCapytain.common.reference.NodeId attribute), 24
parentId (MyCapytain.resources.texts.base.tei.TEIResource attribute), 45
parentId (MyCapytain.resources.texts.local.capitains.cts.__SimplePassage attribute), 59
parentId (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 55
parentId (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 55
parentId (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 49
parentId (MyCapytain.resources.texts.remote.cts.CtsPassage attribute), 69
parentId (MyCapytain.resources.texts.remote.cts.CtsText attribute), 64
parse() (MyCapytain.resolvers.cts.local.CtsCapitainsLocalResolver method), 40
prev (MyCapytain.resources.texts.base.tei.TEIResource attribute), 45
prev (MyCapytain.resources.texts.local.capitains.cts.__SimplePassage attribute), 59
prev (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 55
prev (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 49

R

Reference (class in MyCapytain.common.reference), 26
reference (MyCapytain.common.reference.URN attribute), 25
reference (MyCapytain.resources.texts.local.capitains.cts.__SimplePassage attribute), 59
reference (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 55
reference (MyCapytain.resources.texts.remote.cts.CtsPassage attribute), 69
reference (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 50
reference (MyCapytain.resources.texts.remote.cts.CtsText attribute), 64
RankerCtsText (class in MyCapytain.resolvers.prototypes), 18
retriever (MyCapytain.resources.texts.remote.cts.CtsPassage attribute), 69
retriever (MyCapytain.resources.texts.remote.cts.CtsText attribute), 64

S

set_creator() (MyCapytain.resources.texts.base.tei.TEIResource method), 45
set_creator() (MyCapytain.resources.texts.local.capitains.cts.__SimplePassage method), 59
set_creator() (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText method), 55

set_creator()	(MyCapy-	tain.resources.texts.local.capitains.cts.CaptainsCtsText	set_subject()	(MyCapy-	tain.resources.texts.remote.cts.CtsPassage
method), 50			method), 69		method), 69
set_creator()	(MyCapy-	tain.resources.texts.remote.cts.CtsPassage	set_subject()	(MyCapy-	tain.resources.texts.remote.cts.CtsText
method), 69			method), 65		method), 65
set_creator()	(MyCapy-	tain.resources.texts.remote.cts.CtsText	set_title()	(MyCapytian.resources.texts.base.tei.TEIResource	
method), 64			method), 46		
set_description()	(MyCapy-	tain.resources.texts.base.tei.TEIResource	set_title()	(MyCapytian.resources.texts.local.capitains.cts.__SimplePassage_	
method), 46			method), 60		method), 55
set_description()	(MyCapy-	tain.resources.texts.local.capitains.cts.__SimplePassage_	set_title()	(MyCapytian.resources.texts.local.capitains.cts.CaptainsCtsPassa	
method), 59		method), 50	method), 50		
set_description()	(MyCapy-	tain.resources.texts.local.capitains.cts.CaptainsCtsText	set_title()	(MyCapytian.resources.texts.remote.cts.CtsPassage	
method), 55			method), 69		method), 65
set_description()	(MyCapy-	tain.resources.texts.local.capitains.cts.CaptainsCtsText	siblingsId	(MyCapytian.common.reference.NodeId at-	
method), 50			tribute), 24		
set_description()	(MyCapy-	tain.resources.texts.remote.cts.CtsPassage	siblingsId	(MyCapytian.resources.texts.base.tei.TEIResource	
method), 69			attribute), 46		
set_description()	(MyCapy-	tain.resources.texts.remote.cts.CtsText	siblingsId	(MyCapytian.resources.texts.local.capitains.cts.__SimplePassage_	
method), 65			attribute), 60		attribute), 55
set_metadata_from_collection()	(MyCapy-	tain.resources.texts.local.capitains.cts.__SimplePassage_	siblingsId	(MyCapytian.resources.texts.local.capitains.cts.CaptainsCtsPassa	
method), 59		method), 50			
set_metadata_from_collection()	(MyCapy-	tain.resources.texts.local.capitains.cts.CaptainsCtsText	siblingsId	(MyCapytian.resources.texts.remote.cts.CtsPassage	
method), 55			attribute), 65		attribute), 70
set_metadata_from_collection()	(MyCapy-	tain.resources.texts.local.capitains.cts.CaptainsCtsPassage	start	(MyCapytian.common.reference.Reference at-	
method), 50			tribute), 27		
set_metadata_from_collection()	(MyCapy-	tain.resources.texts.local.capitains.cts.CaptainsCtsText	text	(MyCapytian.common.reference.Reference attribute), 27	
method), 55					
set_metadata_from_collection()	(MyCapy-	tain.resources.texts.remote.cts.CtsPassage	T		
method), 69					
set_metadata_from_collection()	(MyCapy-	tain.resources.texts.remote.cts.CtsText	TEIResource	(class	in
method), 65			tain.resources.texts.base.tei), 43		MyCapy-
set_subject()	(MyCapy-	tain.resources.texts.base.tei.TEIResource	test()	(MyCapytian.resources.texts.local.capitains.cts.CaptainsCtsText	
method), 46			method), 50		
set_subject()	(MyCapy-	tain.resources.texts.local.capitains.cts.__SimplePassage_	text	(MyCapytian.resources.texts.base.tei.TEIResource	
method), 60		method), 60	attribute), 46		
set_subject()	(MyCapy-	tain.resources.texts.local.capitains.cts.CaptainsCtsText	text	(MyCapytian.resources.texts.local.capitains.cts.__SimplePassage_	
method), 55			attribute), 60		attribute), 55
set_subject()	(MyCapy-	tain.resources.texts.local.capitains.cts.CaptainsCtsPassage	text	(MyCapytian.resources.texts.local.capitains.cts.CaptainsCtsText	
method), 50			attribute), 50		attribute), 50
set_subject()	(MyCapy-	tain.resources.texts.local.capitains.cts.CaptainsCtsText	text	(MyCapytian.resources.texts.remote.cts.CtsPassage	
method), 50			attribute), 70		attribute), 65
set_subject()	(MyCapy-	tain.resources.texts.local.capitains.cts.CaptainsCtsText	text	(MyCapytian.resources.texts.remote.cts.CtsText	
method), 50			attribute), 65		attribute), 65

TEXT_CLASS (MyCapytain.resolvers.cts.local.CtsCapitainsLocalResolver attribute), 39
textgroup (MyCapytain.common.reference.URN attribute), 25
textObject (MyCapytain.resources.texts.local.capitains.cts._SimplePassaged) 56
textObject (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 60
textObject (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 55
textObject (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 50
tostring() (MyCapytain.resources.texts.local.capitains.cts._SimplePassage method), 60
tostring() (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsPassage method), 55
tostring() (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText method), 50

U

upTo() (MyCapytain.common.reference.URN method), 25
URN (class in MyCapytain.common.reference), 24
urn (MyCapytain.resources.texts.local.capitains.cts._SimplePassage attribute), 60
urn (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsPassage attribute), 56
urn (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 51
urn (MyCapytain.resources.texts.remote.cts.CtsPassage attribute), 70
urn (MyCapytain.resources.texts.remote.cts.CtsText attribute), 65
urn_namespace (MyCapytain.common.reference.URN attribute), 25

V

version (MyCapytain.common.reference.URN attribute), 26

W

work (MyCapytain.common.reference.URN attribute), 26

X

xml (MyCapytain.resources.texts.base.tei.TEIResource attribute), 46
xml (MyCapytain.resources.texts.local.capitains.cts._SimplePassage attribute), 60
xml (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsPassage attribute), 56
xml (MyCapytain.resources.texts.local.capitains.cts.CaptainsCtsText attribute), 51
xml (MyCapytain.resources.texts.remote.cts.CtsPassage attribute), 70