



n98-magerun Documentation

Release 1.0.0

netz98 new media GmbH

April 17, 2015

1	Overview	3
1.1	Compatibility	3
2	Installation/Update	5
2.1	Installation	5
2.2	Update	5
3	Standalone Commands	7
3.1	help	7
3.2	install	10
3.3	list	14
3.4	open-browser	15
3.5	script	17
3.6	shell	19
3.7	uninstall	21
4	Admin Commands	25
4.1	admin:notifications	25
4.2	admin:user:change-password	27
4.3	admin:user:create	29
4.4	admin:user:list	32
5	Cache Commands	35
5.1	cache:clean	35
5.2	cache:disable	37
5.3	cache:enable	39
5.4	cache:flush	41
5.5	cache:list	42
6	Composer Commands	45
6.1	composer:diagnose	45
6.2	composer:init	47
6.3	composer:install	50
6.4	composer:require	54
6.5	composer:search	57
6.6	composer:update	59
6.7	composer:validate	64
7	Config Commands	67

7.1	config:delete	67
7.2	config:dump	69
7.3	config:get	72
7.4	config:search	75
7.5	config:set	77
8	Customer Commands	81
8.1	customer:change-password	81
8.2	customer:create	83
8.3	customer:create:dummy	86
8.4	customer:info	89
8.5	customer:list	91
9	Db Commands	95
9.1	db:console	95
9.2	db:create	97
9.3	db:drop	99
9.4	db:dump	101
9.5	db:import	105
9.6	db:info	108
9.7	db:query	110
10	Design Commands	113
10.1	design:demo-notice	113
11	Dev Commands	117
11.1	dev:class:lookup	117
11.2	dev:console	119
11.3	dev:ide:phpstorm:meta	121
11.4	dev:log	123
11.5	dev:log:db	125
11.6	dev:log:size	128
11.7	dev:module:create	130
11.8	dev:module:dependencies:from	134
11.9	dev:module:dependencies:on	136
11.10	dev:module:list	138
11.11	dev:module:observer:list	141
11.12	dev:module:rewrite:conflicts	143
11.13	dev:module:rewrite:list	145
11.14	dev:profiler	147
11.15	dev:report:count	149
11.16	dev:setup:script:attribute	151
11.17	dev:symlinks	153
11.18	dev:template-hints	156
11.19	dev:template-hints-blocks	158
11.20	dev:theme:duplicates	161
11.21	dev:theme:list	163
11.22	dev:translate:admin	165
11.23	dev:translate:shop	167
12	Extension Commands	171
12.1	extension:download	171
12.2	extension:install	173
12.3	extension:list	175
12.4	extension:upgrade	177

13	Index Commands	181
13.1	index:list	181
13.2	index:reindex	183
13.3	index:reindex:all	185
14	Local-config Commands	189
14.1	local-config:generate	189
15	Script Commands	193
15.1	script:repo:list	193
15.2	script:repo:run	195
16	Standalone Commands	199
16.1	help	199
16.2	install	202
16.3	list	206
16.4	open-browser	207
16.5	script	209
16.6	shell	212
16.7	uninstall	214
17	Sys Commands	217
17.1	sys:check	217
17.2	sys:cron:history	219
17.3	sys:cron:list	221
17.4	sys:cron:run	222
17.5	sys:info	224
17.6	sys:maintenance	226
17.7	sys:setup:compare-versions	228
17.8	sys:setup:run	230
17.9	sys:store:config:base-url:list	232
17.10	sys:store:list	234
17.11	sys:url:list	236
17.12	sys:website:list	239
18	Uml Commands	243
18.1	uml:generate	243
19	Copyrights	247
20	Command Reference	249
21	Indices and tables	251

Contents:

Overview

The n98 magerun cli tools provides some handy tools to work with Magento from command line.

1.1 Compatibility

The tools will automatically be tested for multiple PHP versions (5.3, 5.4, 5.5). It's currently currently running in various Linux distributions and Mac OS X. Microsoft Windows is not fully supported (some Commands like *db:dump* or *install* are excluded).

The tool partially works with Magento 2 development branch.

Installation/Update

2.1 Installation

There are two ways to install the tools:

2.1.1 Download phar file

```
wget https://raw.githubusercontent.com/netz98/n98-magerun/master/n98-magerun.phar
```

or if you have problems with SSL certificate:

```
curl -o n98-magerun.phar https://raw.githubusercontent.com/netz98/n98-magerun/master/n98-magerun.phar
```

You can make the .phar file executable.

```
chmod +x ./n98-magerun.phar
```

If you want to use command system wide you can copy it to */usr/local/bin*.

```
sudo cp ./n98-magerun.phar /usr/local/bin/
```

Debian / suhosin:

On some debian systems with compiled in suhosin the phar extension must be added to a whitelist.

Add this to your php.ini file:

```
suhosin.executor.include.whitelist="phar"
```

You don't like the filename?

Just rename it to whatever you want.

2.1.2 Install with Composer

<https://github.com/netz98/n98-magerun/wiki/Install-from-source-with-Composer>

2.2 Update

Since version 1.1.0 we deliver a self-update script within the phar file:

```
$ n98-magerun.phar self-update
```

If file was installed system wide do not forget “sudo”.

See it in action: <http://youtu.be/wMHpfKD9vjM>

Standalone Commands

3.1 help

Displays help for a command

The `<info>help</info>` command displays help for a given command:

```
&lt;info&gt;php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
help list&lt;/info&gt;
```

You can also output the help in other formats by using the `<comment>-format</comment>` option:

```
&lt;info&gt;php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
help --format=xml list&lt;/info&gt;
```

To display the list of available commands, please use the `<info>list</info>` command.

Usage:

```
$ n98-magerun.phar help [--xml] [--format='...'] [--raw] [command_name]
```

3.1.1 Arguments

command_name

Is required: No

Is array: No

Description: The command name

Default: help

3.1.2 Options

-xml

Description: To output help as XML

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-format

Description: To output help in other formats

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-raw

Description: To output raw command help

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

3.2 install

Install magento

Usage:

```
$ n98-magerun.phar install [--magentoVersion[='&quot;...&quot;']] [--magentoVersionByName[='&quot;...&quot;']]
```

3.2.1 Options

--magentoVersion

Description: Magento version

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--magentoVersionByName

Description: Magento version name instead of order number

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--installationFolder

Description: Installation folder

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--dbHost

Description: Database host

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-dbUser

Description: Database user

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-dbPass

Description: Database password

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-dbName

Description: Database name

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-installSampleData

Description: Install sample data

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-useDefaultConfigParams

Description: Use default installation parameters defined in the yaml file

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-baseUrl

Description: Installation base url

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-replaceHtaccessFile

Description: Generate htaccess file (for non vhost environment)

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

3.3 list

Lists commands

The `list` command lists all commands:

```
&lt;pre>php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
list
```

You can also display the commands for a specific namespace:

```
&lt;pre>php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
list test
```

You can also output the information in other formats by using the `--format=` option:

```
&lt;pre>php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
list --format=xml
```

It's also possible to get raw list of commands (useful for embedding command runner):

```
&lt;pre>php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
list --raw
```

Usage:

```
$ n98-magerun.phar list [--xml] [--raw] [--format='...'] [namespace]
```

3.3.1 Arguments

namespace

Is required: No

Is array: No

Description: The namespace name

Default: n/a

3.3.2 Options

-xml

Description: To output list as XML

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-raw

Description: To output raw command list

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-format

Description: To output list in other formats

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

3.4 open-browser

Open current project in browser `<comment>(experimental)</comment>`

Usage:

```
$ n98-magerun.phar open-browser [store]
```

3.4.1 Arguments

store

Is required: No

Is array: No

Description: Store code or ID

Default: n/a

3.4.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

3.5 script

Runs multiple n98-magerun commands

Usage:

```
$ n98-magerun.phar script [-d|--define[='&quot;...&quot;']] [filename]
```

3.5.1 Arguments

filename

Is required: No

Is array: No

Description: Script file

Default: n/a

3.5.2 Options

-define

Description: Defines a variable

Shortcut: -d

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

3.6 shell

Runs n98-magerun as shell

Usage:

```
$ n98-magerun.phar shell
```

3.6.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

3.7 uninstall

Uninstall magento (drops database and empties current folder)

Usage:

```
$ n98-magerun.phar uninstall [-f|--force]
```

3.7.1 Options

-force

Description: Force

Shortcut: -f

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Admin Commands

4.1 admin:notifications

Toggles admin notifications

Usage:

```
$ n98-magerun.phar admin:notifications [--on] [--off]
```

4.1.1 Options

-on

Description: Switch on

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-off

Description: Switch off

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

4.2 admin:user:change-password

Changes the password of a adminhtml user.

Usage:

```
$ n98-magerun.phar admin:user:change-password [username] [password]
```

4.2.1 Arguments

username

Is required: No

Is array: No

Description: Username

Default: n/a

password

Is required: No

Is array: No

Description: Password

Default: n/a

4.2.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

4.3 admin:user:create

Create admin user.

Usage:

```
$ n98-magerun.phar admin:user:create [username] [email] [password] [firstname] [lastname] [role]
```

4.3.1 Arguments

username

Is required: No

Is array: No

Description: Username

Default: n/a

email

Is required: No

Is array: No

Description: Email, empty string = generate

Default: n/a

password

Is required: No

Is array: No

Description: Password

Default: n/a

firstname

Is required: No

Is array: No

Description: Firstname

Default: n/a

lastname

Is required: No

Is array: No

Description: Lastname

Default: n/a

role

Is required: No

Is array: No

Description: Role

Default: n/a

4.3.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

4.4 admin:user:list

List admin users.

Usage:

```
$ n98-magerun.phar admin:user:list
```

4.4.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Cache Commands

5.1 cache:clean

Clean magento cache

Cleans expired cache entries. If you like to remove all entries use *cache:flush* Or only one cache type like i.e. *full_page* cache:

```
$ n98-magerun.phar cache:clean full_page
```

Usage:

```
$ n98-magerun.phar cache:clean [type]
```

5.1.1 Arguments

type

Is required: No

Is array: No

Description: Cache type code like `"config"`;

Default: n/a

5.1.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

5.2 cache:disable

Disables magento caches

Usage:

```
$ n98-magerun.phar cache:disable
```

5.2.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

5.3 cache:enable

Enables magento caches

Usage:

```
$ n98-magerun.phar cache:enable
```

5.3.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

5.4 cache:flush

Flush magento cache storage

Usage:

```
$ n98-magerun.phar cache:flush
```

5.4.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

5.5 cache:list

Lists all magento caches

Usage:

```
$ n98-magerun.phar cache:list
```


5.5.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Composer Commands

6.1 composer:diagnose

Diagnoses the system to identify common errors.

The `composer:diagnose` command checks common errors to help debugging problems.

Usage:

```
$ n98-magerun.phar composer:diagnose
```

6.1.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

6.2 composer:init

Creates a basic composer.json file in current directory.

The `<info>init</info>` command creates a basic composer.json file in the current directory.

`<info>php composer.phar init</info>`

Usage:

```
$ n98-magerun.phar composer:init [--name='&quot;...&quot;'] [--description='&quot;...&quot;']
```

6.2.1 Options

-name

Description: Name of the package

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-description

Description: Description of package

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-author

Description: Author name of package

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-homepage

Description: Homepage of package

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-require

Description: Package to require with a version constraint, e.g. `foo/bar:1.0.0` or `foo/bar=1.0.0` or `"foo/bar 1.0.0"`;

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-require-dev

Description: Package to require for development with a version constraint, e.g. `foo/bar:1.0.0` or `foo/bar=1.0.0` or `"foo/bar 1.0.0"`;

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-stability

Description: Minimum stability (empty or one of: stable, RC, beta, alpha, dev)

Shortcut: -s

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-license

Description: License of package

Shortcut: -l

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

6.3 composer:install

Installs the project dependencies from the composer.lock file if present, or falls back on the composer.json.

The `<info>install</info>` command reads the composer.lock file from the current directory, processes it, and downloads and installs all the libraries and dependencies outlined in that file. If the file does not exist it will look for composer.json and do the same.

`<info>php composer.phar install</info>`

Usage:

```
$ n98-magerun.phar composer:install [--prefer-source] [--prefer-dist] [--dry-run] [--dev] [--no-dev]
```

6.3.1 Options

--prefer-source

Description: Forces installation from package sources when possible, including VCS information.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-prefer-dist

Description: Forces installation from package dist even for dev versions.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-dry-run

Description: Outputs the operations but will not execute anything (implicitly enables `-verbose`).

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-dev

Description: Enables installation of require-dev packages (enabled by default, only present for BC).

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-dev

Description: Disables installation of require-dev packages.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-plugins

Description: Disables all plugins.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-custom-installers

Description: DEPRECATED: Use no-plugins instead.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-scripts

Description: Skips the execution of all scripts defined in composer.json file.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-progress

Description: Do not output download progress.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-optimize-autoloader

Description: Optimize autoloader during autoloader dump

Shortcut: -o

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

6.4 composer:require

Adds required packages to your composer.json and installs them

The require command adds required packages to your composer.json and installs them

If you do not want to install the new dependencies immediately you can call it with `-no-update`

Usage:

```
$ n98-magerun.phar composer:require [--dev] [--prefer-source] [--prefer-dist] [--no-progress] [--no-u
```

6.4.1 Arguments

packages

Is required: No

Is array: Yes

Description: Required package with a version constraint, e.g. `foo/bar:1.0.0` or `foo/bar=1.0.0` or `"foo/bar 1.0.0"`;

Default: n/a

6.4.2 Options

-dev

Description: Add requirement to require-dev.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-prefer-source

Description: Forces installation from package sources when possible, including VCS information.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-prefer-dist

Description: Forces installation from package dist even for dev versions.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-progress

Description: Do not output download progress.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-update

Description: Disables the automatic update of the dependencies.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

6.5 composer:search

Search for packages

The search command searches for packages by its name <info>php composer.phar search symfony composer</info>;

Usage:

```
$ n98-magerun.phar composer:search [-N|--only-name] tokens1 ... [tokensN]
```

6.5.1 Arguments

tokens

Is required: Yes

Is array: Yes

Description: tokens to search for

Default: n/a

6.5.2 Options

-only-name

Description: Search only in name

Shortcut: -N

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

6.6 composer:update

Updates your dependencies to the latest version according to composer.json, and updates the composer.lock file.

The `<info>update</info>` command reads the composer.json file from the current directory, processes it, and updates, removes or installs all the dependencies.

`<info>php composer.phar update</info>`

To limit the update operation to a few packages, you can list the package(s) you want to update as such:

<info>php composer.phar update vendor/package1 foo/mypackage [...]</info>

Usage:

```
$ n98-magerun.phar composer:update [--prefer-source] [--prefer-dist] [--dry-run] [--dev] [--no-dev]
```

6.6.1 Arguments

packages

Is required: No

Is array: Yes

Description: Packages that should be updated, if not provided all packages are.

Default: n/a

6.6.2 Options

--prefer-source

Description: Forces installation from package sources when possible, including VCS information.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--prefer-dist

Description: Forces installation from package dist even for dev versions.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--dry-run

Description: Outputs the operations but will not execute anything (implicitly enables *--verbose*).

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--dev

Description: Enables installation of require-dev packages (enabled by default, only present for BC).

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-dev

Description: Disables installation of require-dev packages.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-lock

Description: Only updates the lock file hash to suppress warning about the lock file being out of date.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-plugins

Description: Disables all plugins.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-custom-installers

Description: DEPRECATED: Use no-plugins instead.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-scripts

Description: Skips the execution of all scripts defined in composer.json file.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-progress

Description: Do not output download progress.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-optimize-autoloader

Description: Optimize autoloader during autoloader dump

Shortcut: -o

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

6.7 composer:validate

Validates a composer.json

The validate command validates a given composer.json

Usage:

```
$ n98-magerun.phar composer:validate [file]
```

6.7.1 Arguments

file

Is required: No

Is array: No

Description: path to composer.json file

Default: ./composer.json

6.7.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Config Commands

7.1 config:delete

Deletes a store config item

To delete all entries if a path you can set the option `-all`.

Usage:

```
$ n98-magerun.phar config:delete [--scope[='&quot;...&quot;']] [--scope-id[='&quot;...&quot;']]
```

7.1.1 Arguments

path

Is required: Yes

Is array: No

Description: The config path

Default: n/a

7.1.2 Options

-scope

Description: The config value's scope (default, websites, stores)

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: default

-scope-id

Description: The config value's scope ID

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-all

Description: Delete all entries by path

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

7.2 config:dump

Dump merged xml config

Dumps merged XML configuration to stdout. Useful to see all the XML. You can filter the XML with first argument.

Examples:

Config of catalog module

```
$ n98-magerun.phar config:dump global/catalog
```

See module order in XML

```
$ n98-magerun.phar config:dump modules
```

Write output to file

```
$ n98-magerun.phar config:dump &gt; extern_file.xml
```

Usage:

```
$ n98-magerun.phar config:dump [xpath]
```

7.2.1 Arguments

xpath

Is required: No

Is array: No

Description: XPath to filter XML output

Default: n/a

7.2.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

7.3 config:get

Get a core config item

If `<info>path</info>` is not set, all available config items will be listed. The `<info>path</info>` may contain wildcards (*). If `<info>path</info>` ends with a trailing slash, all child items will be listed. E.g.

```
config:get web/
```

is the same as `config:get web/*`

Usage:

```
$ n98-magerun.phar config:get [--scope='...&quot;'] [--scope-id='...&quot;']
```

7.3.1 Arguments

path

Is required: No

Is array: No

Description: The config path

Default: n/a

7.3.2 Options

-scope

Description: The config value's scope

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-scope-id

Description: The config value's scope ID

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-decrypt

Description: Decrypt the config value using local.xml's crypt key

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-update-script

Description: Output as update script lines

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-magerun-script

Description: Output for usage with config:set

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

7.4 config:search

Search system configuration descriptions.

Searches the merged system.xml configuration tree <labels/> and <comments/> for the indicated text.

Usage:

```
$ n98-magerun.phar config:search text
```

7.4.1 Arguments

text

Is required: Yes

Is array: No

Description: The text to search for

Default: n/a

7.4.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

7.5 config:set

Set a core config item

Set a store config value by path. To set a value of a specify store view you must set the `"scope"` and `"scope-id"` option.

Usage:

```
$ n98-magerun.phar config:set [--scope [=&quot;...&quot;]] [--scope-id [=&quot;...&quot;]]
```

7.5.1 Arguments

path

Is required: Yes

Is array: No

Description: The config path

Default: n/a

value

Is required: Yes

Is array: No

Description: The config value

Default: n/a

7.5.2 Options

-scope

Description: The config value's scope (default, websites, stores)

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: default

-scope-id

Description: The config value's scope ID

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-encrypt

Description: The config value should be encrypted using local.xml's crypt key

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Customer Commands

8.1 customer:change-password

Changes the password of a customer.

- Website parameter must only be given if more than one websites are available.

Usage:

```
$ n98-magerun.phar customer:change-password [email] [password] [website]
```

8.1.1 Arguments

email

Is required: No

Is array: No

Description: Email

Default: n/a

password

Is required: No

Is array: No

Description: Password

Default: n/a

website

Is required: No

Is array: No

Description: Website of the customer

Default: n/a

8.1.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

8.2 customer:create

Creates a new customer/user for shop frontend.

Usage:

```
$ n98-magerun.phar customer:create [email] [password] [firstname] [lastname] [website]
```

8.2.1 Arguments

email

Is required: No

Is array: No

Description: Email

Default: n/a

password

Is required: No

Is array: No

Description: Password

Default: n/a

firstname

Is required: No

Is array: No

Description: Firstname

Default: n/a

lastname

Is required: No

Is array: No

Description: Lastname

Default: n/a

website

Is required: No

Is array: No

Description: Website

Default: n/a

8.2.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

8.3 customer:create:dummy

Generate dummy customers. You can specify a count and a locale.

Supported Locales:

- cs_CZ
- ru_RU
- bg_BG
- en_US
- it_IT
- sr_RS
- sr_Cyrl_RS
- sr_Latn_RS
- pl_PL
- en_GB
- de_DE
- sk_SK
- fr_FR
- es_AR
- de_AT

Usage:

```
$ n98-magerun.phar customer:create:dummy count locale [website]
```

8.3.1 Arguments

count

Is required: Yes

Is array: No

Description: Count

Default: n/a

locale

Is required: Yes

Is array: No

Description: Locale

Default: n/a

website

Is required: No

Is array: No

Description: Website

Default: n/a

8.3.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

8.4 customer:info

Loads basic customer info by email address.

Usage:

```
$ n98-magerun.phar customer:info [email] [website]
```

8.4.1 Arguments

email

Is required: No

Is array: No

Description: Email

Default: n/a

website

Is required: No

Is array: No

Description: Website of the customer

Default: n/a

8.4.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

8.5 customer:list

Lists customers

List customers. The output is limited to 1000 (can be changed by overriding config). If search parameter is given the customers are filtered (searchs in firstname, lastname and email).

Usage:

```
$ n98-magerun.phar customer:list [search]
```

8.5.1 Arguments

search

Is required: No

Is array: No

Description: Search query

Default: n/a

8.5.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Db Commands

9.1 db:console

Opens mysql client by database config from local.xml

Usage:

```
$ n98-magerun.phar db:console
```

9.1.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

9.2 db:create

Create currently configured database

The command tries to create the configured database according to your settings in `app/etc/local.xml`. The configured user must have `'CREATE DATABASE'` privileges on MySQL Server.

Usage:

```
$ n98-magerun.phar db:create
```

9.2.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

9.3 db:drop

Drop current database

The command prompts before dropping the database. If `-force` option is specified it directly drops the database. The configured user in `app/etc/local.xml` must have `'DROP'` privileges.

Usage:

```
$ n98-magerun.phar db:drop [-f|--force]
```

9.3.1 Options

-force

Description: Force

Shortcut: -f

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

9.4 db:dump

Dumps database with `mysqldump` cli client according to informations from `local.xml`

Dumps configured magento database with `mysqldump`. You must have installed the MySQL client tools.

On debian systems run `apt-get install mysql-client` to do that.

The command reads `app/etc/local.xml` to find the correct settings. If you like to skip data of some tables you can use the `--strip` option. The strip option creates only the structure of the defined tables and forces `mysqldump` to skip the data.

Dumps your database and excludes some tables. This is useful i.e. for development.

Separate each table to strip by a space. You can use wildcards like `*` and `?` in the table names to strip multiple tables. In addition you can specify pre-defined table groups, that start with an `@` Example: `"dataflow_batch_export unimportant_module_* @log`

```
$ n98-magerun.phar db:dump --strip=&quot;@stripped&quot;
```

Available Table Groups:

- `@log` Log tables
- `@dataflowtemp` Temporary tables of the dataflow import/export tool
- `@stripped` Standard definition for a stripped dump (logs and dataflow)
- `@sales` Sales data (orders, invoices, creditmemos etc)
- `@customers` Customer data
- `@trade` Current trade data (customers and orders). You usually do not want those in developer systems.
- `@development` Removes logs and trade data so developers do not have to work with real customer data

Extended: <https://github.com/netz98/n98-magerun/wiki/Stripped-Database-Dumps>

See it in action: <http://youtu.be/tjZHY6vThs>

- If you like to prepend a timestamp to the dump name the `--add-time` option can be used.
- The command comes with a compression function. Add i.e. `--compress=gz` to dump directly in gzip compressed file.

<comment>Compression option</comment> Supported compression: `gzip`
The `gzip` cli tool has to be installed. Additionally, for `data-to-csv` option `tar` cli tool has to be installed too.

<comment>Strip option</comment> Separate each table to strip by a space. You can use wildcards like `*` and `?` in the table names to strip multiple tables. In addition you can specify pre-defined table groups, that start with an `@` Example: `"dataflow_batch_export unimportant_module_* @log`

<comment>Available Table Groups</comment>

`@log`; Log tables
`@dataflowtemp`; Temporary tables of the dataflow import/export tool
`@stripped`; Standard definition for a stripped dump (logs and dataflow)
`@sales`; Sales data (orders, invoices, creditmemos etc)
`@customers`; Customer data - Should not be used without `@sales`
`@trade`; Current trade data (customers and orders). You usually do not want those in developer systems.

<info>@development</info> Removes logs and trade data so developers do not have to work with real customer data <info>@ee_changelog</info> Changelog tables of new indexer since EE 1.13 <info>@idx</info> Tables with _idx suffix

Usage:

```
$ n98-magerun.phar db:dump [-t|--add-time[=&quot;...&quot;]] [-c|--compression=&quot;...&quot;]
```

9.4.1 Arguments

filename

Is required: No

Is array: No

Description: Dump filename

Default: n/a

9.4.2 Options

-add-time

Description: Adds time to filename (only if filename was not provided)

Shortcut: -t

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-compression

Description: Compress the dump file using one of the supported algorithms

Shortcut: -c

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-only-command

Description: Print only mysqldump command. Do not execute

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-print-only-filename

Description: Execute and prints no output except the dump filename

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-single-transaction

Description: Do not use single-transaction (not recommended, this is blocking)

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-human-readable

Description: Use a single insert with column names per row. Useful to track database differences, but significantly slows down a later import

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-stdout

Description: Dump to stdout

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-strip

Description: Tables to strip (dump only structure of those tables)

Shortcut: -s

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-force

Description: Do not prompt if all options are defined

Shortcut: -f

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

9.5 db:import

Imports database with mysql cli client according to database defined in local.xml

Usage:

```
$ n98-magerun.phar db:import [-c|--compression='&quot;...&quot;'] [--only-command] [--only-if-e
```

9.5.1 Arguments

filename

Is required: No

Is array: No

Description: Dump filename

Default: n/a

9.5.2 Options

-compression

Description: The compression of the specified file

Shortcut: -c

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-only-command

Description: Print only mysql command. Do not execute

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-only-if-empty

Description: Imports only if database is empty

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

9.6 db:info

Dumps database informations

This command is useful to print all informations about the current configured database in app/etc/local.xml. It can print connection string for JDBC, PDO connections.

Usage:

```
$ n98-magerun.phar db:info
```

9.6.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

9.7 db:query

Executes an SQL query on the database defined in local.xml

Executes an SQL query on the current configured database. Wrap your SQL in single or double quotes.

If your query produces a result (e.g. a SELECT statement), the output of the mysql cli tool will be returned.

- Requires MySQL CLI tools installed on your system.

Usage:

```
$ n98-magerun.phar db:query [--only-command] [query]
```

9.7.1 Arguments

query

Is required: No

Is array: No

Description: SQL query

Default: n/a

9.7.2 Options

-only-command

Description: Print only mysql command. Do not execute

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Design Commands

10.1 design:demo-notice

Toggles demo store notice for a store view

Usage:

```
$ n98-magerun.phar design:demo-notice [--on] [--off] [--global] [store]
```

10.1.1 Arguments

store

Is required: No

Is array: No

Description: Store code or ID

Default: n/a

10.1.2 Options

-on

Description: Switch on

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-off

Description: Switch off

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-global

Description: Set value on default scope

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Dev Commands

11.1 dev:class:lookup

Resolves a grouped class name

Usage:

```
$ n98-magerun.phar dev:class:lookup type name
```

11.1.1 Arguments

type

Is required: Yes

Is array: No

Description: The type of the class (helper/block/model)

Default: n/a

name

Is required: Yes

Is array: No

Description: The grouped class name

Default: n/a

11.1.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.2 dev:console

Opens PHP interactive shell with initialized Mage::app() <comment>(Experimental)</comment>

Usage:

```
$ n98-magerun.phar dev:console
```

11.2.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.3 dev:ide:phpstorm:meta

Generates meta data file for PhpStorm auto completion

Usage:

```
$ n98-magerun.phar dev:ide:phpstorm:meta [--stdout]
```

11.3.1 Options

-stdout

Description: Print to stdout instead of file .phpstorm.meta.php

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.4 dev:log

Toggle development log (system.log, exception.log)

Usage:

```
$ n98-magerun.phar dev:log [--on] [--off] [--global] [store]
```

11.4.1 Arguments

store

Is required: No

Is array: No

Description: Store code or ID

Default: n/a

11.4.2 Options

-on

Description: Switch on

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-off

Description: Switch off

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-global

Description: Set value on default scope

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.5 dev:log:db

Turn on/off database query logging

Usage:

```
$ n98-magerun.phar dev:log:db [--on] [--off]
```

11.5.1 Options

-on

Description: Force logging

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-off

Description: Disable logging

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.6 dev:log:size

Get size of log file

Usage:

```
$ n98-magerun.phar dev:log:size [log_filename]
```

11.6.1 Arguments

log_filename

Is required: No

Is array: No

Description: Name of log file.

Default: n/a

11.6.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.7 dev:module:create

Create and register a new magento module.

Usage:

```
$ n98-magerun.phar dev:module:create [--add-blocks] [--add-helpers] [--add-models] [--add-setup] [--add-views]
```

11.7.1 Arguments

vendorNamespace

Is required: Yes

Is array: No

Description: Namespace (your company prefix)

Default: n/a

moduleName

Is required: Yes

Is array: No

Description: Name of your module.

Default: n/a

codePool

Is required: No

Is array: No

Description: Codepool (local,community)

Default: local

11.7.2 Options

-add-blocks

Description: Adds blocks

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-add-helpers

Description: Adds helpers

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-add-models

Description: Adds models

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-add-setup

Description: Adds SQL setup

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-add-all

Description: Adds blocks, helpers and models

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-modman

Description: Create all files in folder with a modman file.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-add-readme

Description: Adds a readme.md file to generated module

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-add-composer

Description: Adds a composer.json file to generated module

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-author-name

Description: Author for readme.md or composer.json

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-author-email

Description: Author for readme.md or composer.json

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-description

Description: Description for readme.md or composer.json

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.8 dev:module:dependencies:from

Show list of modules which depend on %s module

Usage:

```
$ n98-magerun.phar dev:module:dependencies:from [-a|--all] moduleName
```

11.8.1 Arguments

moduleName

Is required: Yes

Is array: No

Description: Module to show dependencies

Default: n/a

11.8.2 Options

-all

Description: Show all dependencies (dependencies of dependencies)

Shortcut: -a

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.9 dev:module:dependencies:on

Show list of modules which given module depends on

Usage:

```
$ n98-magerun.phar dev:module:dependencies:on [-a|--all] moduleName
```

11.9.1 Arguments

moduleName

Is required: Yes

Is array: No

Description: Module to show dependencies

Default: n/a

11.9.2 Options

-all

Description: Show all dependencies (dependencies of dependencies)

Shortcut: -a

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.10 dev:module:list

List all installed modules

Usage:

```
$ n98-magerun.phar dev:module:list [--codepool[='&quot;...&quot;']] [--status[='&quot;...&quot;']]
```


11.10.1 Options

-codepool

Description: Show modules in a specific codepool

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-status

Description: Show modules with a specific status

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-vendor

Description: Show modules of a specified vendor

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.11 dev:module:observer:list

Lists all registered observers

Usage:

```
$ n98-magerun.phar dev:module:observer:list [type]
```

11.11.1 Arguments

type

Is required: No

Is array: No

Description: Observer type (global, admin, frontend)

Default: n/a

11.11.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.12 dev:module:rewrite:conflicts

Lists all magento rewrite conflicts

Lists all duplicated rewrites and tells you which class is loaded by Magento. The command checks class inheritance in order of your module dependencies.

- If a filename with *-log-junit* option is set the tool generates an XML file and no output to *stdout*.

Usage:

```
$ n98-magerun.phar dev:module:rewrite:conflicts [--log-junit=&quot;...&quot;]
```

11.12.1 Options

-log-junit

Description: Log conflicts in JUnit XML format to defined file.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.13 dev:module:rewrite:list

Lists all magento rewrites

Usage:

```
$ n98-magerun.phar dev:module:rewrite:list
```

11.13.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.14 dev:profiler

Toggles profiler for debugging

Usage:

```
$ n98-magerun.phar dev:profiler [--on] [--off] [--global] [store]
```

11.14.1 Arguments

store

Is required: No

Is array: No

Description: Store code or ID

Default: n/a

11.14.2 Options

-on

Description: Switch on

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-off

Description: Switch off

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-global

Description: Set value on default scope

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.15 dev:report:count

Get count of report files

Usage:

```
$ n98-magerun.phar dev:report:count
```

11.15.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.16 dev:setup:script:attribute

Creates attribute script for a given attribute code

Usage:

```
$ n98-magerun.phar dev:setup:script:attribute entityType attributeCode
```

11.16.1 Arguments

entityType

Is required: Yes

Is array: No

Description: Entity Type Code like catalog_product

Default: n/a

attributeCode

Is required: Yes

Is array: No

Description: Attribute Code

Default: n/a

11.16.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.17 dev:symlinks

Toggle allow symlinks setting

Usage:

```
$ n98-magerun.phar dev:symlinks [--on] [--off] [--global] [store]
```

11.17.1 Arguments

store

Is required: No

Is array: No

Description: Store code or ID

Default: n/a

11.17.2 Options

-on

Description: Switch on

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-off

Description: Switch off

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-global

Description: Set value on default scope

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.18 dev:template-hints

Toggles template hints

Usage:

```
$ n98-magerun.phar dev:template-hints [--on] [--off] [store]
```

11.18.1 Arguments

store

Is required: No

Is array: No

Description: Store code or ID

Default: n/a

11.18.2 Options

-on

Description: Switch on

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-off

Description: Switch off

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.19 dev:template-hints-blocks

Toggles template hints block names

Usage:

```
$ n98-magerun.phar dev:template-hints-blocks [--on] [--off] [store]
```

11.19.1 Arguments

store

Is required: No

Is array: No

Description: Store code or ID

Default: n/a

11.19.2 Options

-on

Description: Switch on

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-off

Description: Switch off

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.20 dev:theme:duplicates

Find duplicate files (templates, layout, locale, etc.) between two themes.

- If a filename with `-log-junit` option is set the tool generates an XML file and no output to `stdout`.

Usage:

```
$ n98-magerun.phar dev:theme:duplicates [--log-junit=&quot;...&quot;] theme [originalTheme]
```

11.20.1 Arguments

theme

Is required: Yes

Is array: No

Description: Your theme

Default: n/a

originalTheme

Is required: No

Is array: No

Description: Original theme to compare. Default is `"base/default"`;

Default: base/default

11.20.2 Options

-log-junit

Description: Log duplicates in JUnit XML format to defined file.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.21 dev:theme:list

Lists all available themes

Usage:

```
$ n98-magerun.phar dev:theme:list
```

11.21.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.22 dev:translate:admin

Toggle inline translation tool for admin

Usage:

```
$ n98-magerun.phar dev:translate:admin [--on] [--off]
```

11.22.1 Options

-on

Description: Switch on

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-off

Description: Switch off

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

11.23 dev:translate:shop

Toggle inline translation tool for shop

Usage:

```
$ n98-magerun.phar dev:translate:shop [--on] [--off] [store]
```

11.23.1 Arguments

store

Is required: No

Is array: No

Description: Store code or ID

Default: n/a

11.23.2 Options

-on

Description: Switch on

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-off

Description: Switch off

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Extension Commands

12.1 extension:download

Download magento-connect package

- Requires Magento's *mage* shell script.
- Does not work with Windows as operating system.

Usage:

```
$ n98-magerun.phar extension:download package
```

12.1.1 Arguments

package

Is required: Yes

Is array: No

Description: Package to download

Default: n/a

12.1.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

12.2 extension:install

Install magento-connect package

If the package could not be found a search for alternatives will be done. If alternatives could be found you can select the package to install.

- Requires Magento's *mage* shell script.
- Does not work with Windows as operating system.

Usage:

```
$ n98-magerun.phar extension:install package
```

12.2.1 Arguments

package

Is required: Yes

Is array: No

Description: Package to install

Default: n/a

12.2.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

12.3 extension:list

List magento connection extensions

- Requires Magento's *mage* shell script.
- Does not work with Windows as operating system.

Usage:

```
$ n98-magerun.phar extension:list [search]
```

12.3.1 Arguments

search

Is required: No

Is array: No

Description: Search string

Default: n/a

12.3.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

12.4 extension:upgrade

Upgrade magento-connect package

- Requires Magento's *mage* shell script.
- Does not work with Windows as operating system.

Usage:

```
$ n98-magerun.phar extension:upgrade package
```

12.4.1 Arguments

package

Is required: Yes

Is array: No

Description: Package to upgrade

Default: n/a

12.4.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Index Commands

13.1 index:list

Lists all magento indexes

Usage:

```
$ n98-magerun.phar index:list
```

13.1.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

13.2 index:reindex

Reindex a magento index by code

Index by indexer code. Code is optional. If you don't specify a code you can pick a indexer from a list.

```
$ n98-magerun.phar index:reindex [code]
```

Since 1.75.0 it's possible to run mutiple indexers by seperating code with a comma.

i.e.

```
$ n98-magerun.phar index:reindex catalog_product_attribute,tag_summary
```

If no index is provided as argument you can select indexers from menu by `"number"` like `"1,3"` for first and third indexer.

Usage:

```
$ n98-magerun.phar index:reindex [index_code]
```

13.2.1 Arguments

index_code

Is required: No

Is array: No

Description: Code of indexer.

Default: n/a

13.2.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

13.3 index:reindex:all

Reindex all magento indexes

Loops all magento indexes and triggers reindex.

Usage:

```
$ n98-magerun.phar index:reindex:all
```

13.3.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Local-config Commands

14.1 local-config:generate

Generates local.xml config

Generates the app/etc/local.xml.

- The file `app/etc/local.xml.template` (bundles with Magento) must exist!
- Currently the command does not validate anything you enter.
- The command will not overwrite existing `app/etc/local.xml` files.

Usage:

```
$ n98-magerun.phar local-config:generate [db-host] [db-user] [db-pass] [db-name] [session-save] [adm
```

14.1.1 Arguments

db-host

Is required: No

Is array: No

Description: Database host

Default: n/a

db-user

Is required: No

Is array: No

Description: Database user

Default: n/a

db-pass

Is required: No

Is array: No

Description: Database password

Default: n/a

db-name

Is required: No

Is array: No

Description: Database name

Default: n/a

session-save

Is required: No

Is array: No

Description: Session storage adapter

Default: n/a

admin-frontname

Is required: No

Is array: No

Description: Admin front name

Default: n/a

14.1.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Script Commands

15.1 script:repo:list

Lists all scripts in repository

You can organize your scripts in a repository. Simply place a script in folder `/usr/local/share/n98-magerun/scripts` or in your home dir in folder `<HOME>/n98-magerun/scripts`.

Scripts must have the file extension `.magerun`.

After that you can list all scripts with the `script:repo:list` command. The first line of the script can contain a comment (line prefixed with `#`) which will be displayed as description.

```
$ n98-magerun.phar script:repo:list
```

Usage:

```
$ n98-magerun.phar script:repo:list
```

15.1.1 Options

`-help`

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

`-quiet`

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

15.2 script:repo:run

Run script from repository

Usage:

```
$ n98-magerun.phar script:repo:run [script]
```

15.2.1 Arguments

script

Is required: No

Is array: No

Description: Name of script in repository

Default: n/a

15.2.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Standalone Commands

16.1 help

Displays help for a command

The `help` command displays help for a given command:

```
&lt;pre>php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
help list
```

You can also output the help in other formats by using the `--format` option:

```
&lt;pre>php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
help --format=xml list
```

To display the list of available commands, please use the `list` command.

Usage:

```
$ n98-magerun.phar help [--xml] [--format='...'] [--raw] [command_name]
```

16.1.1 Arguments

command_name

Is required: No

Is array: No

Description: The command name

Default: help

16.1.2 Options

--xml

Description: To output help as XML

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-format

Description: To output help in other formats

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-raw

Description: To output raw command help

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

16.2 install

Install magento

- Download Magento by a list of git repos and zip files (mageplus, magelte, official community packages).
- Try to create database if it does not exist.
- Installs Magento sample data if available (since version 1.2.0).
- Starts Magento installer
- Sets rewrite base in .htaccess file

Example of an unattended Magento CE 1.7.0.2 installation:

```
$ n98-magerun.phar install --dbHost='localhost' --dbUser='mydbuser' --dbPass='mysecret' --dbName='magentodb' --installSampleData=yes --useDefaultConfigParams=yes --magentoVersionByName='magento-ce-1.7.0.2' --installationFolder='magento' --baseUrl='http://magento.localdomain/';
```

See it in action: <http://youtu.be/WU-CbJ86eQc>

Usage:

```
$ n98-magerun.phar install [--magentoVersion[='...']] [--magentoVersionByName[='...']]
```

16.2.1 Options

--magentoVersion

Description: Magento version

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--magentoVersionByName

Description: Magento version name instead of order number

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--installationFolder

Description: Installation folder

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-dbHost

Description: Database host

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-dbUser

Description: Database user

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-dbPass

Description: Database password

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-dbName

Description: Database name

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-installSampleData

Description: Install sample data

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-useDefaultConfigParams

Description: Use default installation parameters defined in the yaml file

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-baseUrl

Description: Installation base url

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-replaceHtaccessFile

Description: Generate htaccess file (for non vhost environment)

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

16.3 list

Lists commands

The `<info>list</info>` command lists all commands:

```
&lt;info>php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
list&lt;/info>
```

You can also display the commands for a specific namespace:

```
&lt;info>php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
list test&lt;/info>
```

You can also output the information in other formats by using the `<comment>-format</comment>` option:

```
&lt;info>php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
list --format=xml&lt;/info>
```

It's also possible to get raw list of commands (useful for embedding command runner):

```
&lt;info>php /home/cmuench/Workspaces/PHP/opensource/n98-magerun/bin/n98-magerun
list --raw&lt;/info>
```

Usage:

```
$ n98-magerun.phar list [--xml] [--raw] [--format='...'] [namespace]
```

16.3.1 Arguments

namespace

Is required: No

Is array: No

Description: The namespace name

Default: n/a

16.3.2 Options

-xml

Description: To output list as XML

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-raw

Description: To output raw command list

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-format

Description: To output list in other formats

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

16.4 open-browser

Open current project in browser `<comment>(experimental)</comment>`

Usage:

```
$ n98-magerun.phar open-browser [store]
```

16.4.1 Arguments

store

Is required: No

Is array: No

Description: Store code or ID

Default: n/a

16.4.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

16.5 script

Runs multiple n98-magerun commands

Example:

```
# Set multiple config config:set &quot;web/cookie/cookie_domain&quot; example.com
```

```
# Set with multiline values with &quot;
```

```
&quot; config:set &quot;general/store_information/address&quot; &quot;First line
```

```
Second line Third line&quot;
```

```
# This is a comment cache:flush
```

Optionally you can work with unix pipes.

```
$ echo &quot;cache:flush&quot; | n98-magerun-dev script
```

```
$ n98-magerun.phar script &lt; filename
```

It is even possible to create executable scripts:

Create file *test.magerun* and make it executable (*chmod +x test.magerun*):

```
#!/usr/bin/env n98-magerun.phar script
config:set &quot;web/cookie/cookie_domain&quot; example.com cache:flush
# Run a shell script with &quot;!&quot; as first char ! ls -l
# Register your own variable (only key = value currently supported) ${my.var}=bar
# Let magerun ask for variable value - add a question mark ${my.var}=?
! echo ${my.var}
# Use resolved variables from n98-magerun in shell commands ! ls -l ${magento.root}/code/local
```

Pre-defined variables:

- `${magento.root}` -> Magento Root-Folder
- `${magento.version}` -> Magento Version i.e. 1.7.0.2
- `${magento.edition}` -> Magento Edition -> Community or Enterprise
- `${magerun.version}` -> Magerun version i.e. 1.66.0
- `${php.version}` -> PHP Version
- `${script.file}` -> Current script file path
- `${script.dir}` -> Current script file dir

Variables can be passed to a script with `"--define (-d)"` option.

Example:

```
$ n98-magerun.phar script -d foo=bar filename
# This will register the variable ${foo} with value bar.
```

It's possible to define multiple values by passing more than one option.

Usage:

```
$ n98-magerun.phar script [-d|--define[=&quot;...&quot;]] [filename]
```

16.5.1 Arguments

filename

Is required: No

Is array: No

Description: Script file

Default: n/a

16.5.2 Options

-define

Description: Defines a variable

Shortcut: -d

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

16.6 shell

Runs n98-magerun as shell

Usage:

```
$ n98-magerun.phar shell
```

16.6.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

16.7 uninstall

Uninstall magento (drops database and empties current folder)

Please be careful: This removes all data from your installation.

Usage:

```
$ n98-magerun.phar uninstall [-f|--force]
```

16.7.1 Options

-force

Description: Force

Shortcut: -f

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Sys Commands

17.1 sys:check

Checks Magento System

- Checks missing files and folders
- Security
- PHP Extensions (Required and Bytecode Cache)
- MySQL InnoDB Engine

Usage:

```
$ n98-magerun.phar sys:check
```

17.1.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

17.2 sys:cron:history

Last executed cronjobs with status.

Usage:

```
$ n98-magerun.phar sys:cron:history
```

17.2.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

17.3 sys:cron:list

Lists all cronjobs

Usage:

```
$ n98-magerun.phar sys:cron:list
```

17.3.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

17.4 sys:cron:run

Runs a cronjob by job code

If no *job* argument is passed you can select a job from a list. See it in action:
<http://www.youtube.com/watch?v=QkzkLgrfNaM>

Usage:

```
$ n98-magerun.phar sys:cron:run [job]
```

17.4.1 Arguments

job

Is required: No

Is array: No

Description: Job code

Default: n/a

17.4.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -vl-vvl-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

17.5 sys:info

Prints infos about the current magento system.

Usage:

```
$ n98-magerun.phar sys:info
```

17.5.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

17.6 sys:maintenance

Toggles maintenance mode.

Usage:

```
$ n98-magerun.phar sys:maintenance [--on] [--off]
```

17.6.1 Options

-on

Description: Force maintenance mode

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-off

Description: Disable maintenance mode

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

17.7 sys:setup:compare-versions

Compare module version with core_resource table.

Compares module version with saved setup version in *core_resource* table and displays version mismatch.

Usage:

§ n98-magerun.phar sys:setup:compare-versions [--ignore-data]

17.7.1 Options

--ignore-data

Description: Ignore data updates

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

--version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

17.8 sys:setup:run

Runs all new setup scripts.

Runs all setup scripts (no need to call frontend). This command is useful if you update your system with enabled maintenance mode.

Usage:

```
$ n98-magerun.phar sys:setup:run
```

17.8.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

17.9 sys:store:config:base-url:list

Lists all base urls

Usage:

```
$ n98-magerun.phar sys:store:config:base-url:list
```

17.9.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

17.10 sys:store:list

Lists all installed store-views

Usage:

```
$ n98-magerun.phar sys:store:list
```

17.10.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

17.11 sys:url:list

Get all urls.

Examples:

- Create a list of product urls only:

```
$ n98-magerun.phar sys:url:list --add-products 4
```

- Create a list of all products, categories and cms pages of store 4 and 5 separating host and path (e.g. to feed a jmeter csv sampler):

```
$ n98-magerun.phar sys:url:list --add-all 4,5 &#039;{host},{path}&#039; &#039;&#039;
urls.csv
```

- The `'linetemplate'` can contain all parts `'parse_url'` return wrapped in `'{}'`. `'{url}'` always maps the complete url and is set by default

Usage:

```
$ n98-magerun.phar sys:url:list [--add-categories] [--add-products] [--add-cmspages] [--add-all] [st
```

17.11.1 Arguments

stores

Is required: No

Is array: No

Description: Stores (comma-separated list of store ids)

Default: n/a

linetemplate

Is required: No

Is array: No

Description: Line template

Default: {url}

17.11.2 Options

-add-categories

Description: Adds categories

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-add-products

Description: Adds products

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-add-cmspages

Description: Adds cms pages

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-add-all

Description: Adds categories, products and cms pages

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

17.12 sys:website:list

Lists all websites

Usage:

```
$ n98-magerun.phar sys:website:list
```

17.12.1 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Uml Commands

18.1 uml:generate

Generate UML diagramm

Usage:

```
$ n98-magerun.phar uml:generate classname
```

18.1.1 Arguments

classname

Is required: Yes

Is array: No

Description: PHP class name

Default: n/a

18.1.2 Options

-help

Description: Display this help message.

Shortcut: -h

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-quiet

Description: Do not output any message.

Shortcut: -q

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-verbose

Description: Increase the verbosity of messages: 1 for normal output, 2 for more verbose output and 3 for debug

Shortcut: -v|-vv|-vvv

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-version

Description: Display this application version.

Shortcut: -V

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-ansi

Description: Force ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-ansi

Description: Disable ANSI output.

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-no-interaction

Description: Do not ask any interactive question.

Shortcut: -n

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

-root-dir

Description: Force magento root dir. No auto detection

Shortcut:

Accept value: No

Is value required: No

Is multiple: No

Default: n/a

Copyrights

netz98 new media GmbH

info@netz98.de

Haifa Allee 2 55128 Mainz Germany

Command Reference

- *Standalone Commands*
- *Admin Commands*
- *Cache Commands*
- *Composer Commands*
- *Config Commands*
- *Customer Commands*
- *Db Commands*
- *Design Commands*
- *Dev Commands*
- *Extension Commands*
- *Index Commands*
- *Local-config Commands*
- *Script Commands*
- *Sys Commands*

Indices and tables

- *Welcome to n98-magerun documentation!*