# **NAPALM Documentation**

Release 1

**David Barroso** 

_		
Co	-1-	
( .A	nto	nte
		IILO

1	Documentation	3

YANG (RFC6020) is a data modelling language, it's a way of defining how data is supposed to look like. The napalmyang library provides a framework to use models defined with YANG in the context of network management. It provides mechanisms to transform native data/config into YANG and vice versa.

Contents 1

2 Contents

## CHAPTER 1

**Documentation** 

## 1.1 Quickstart

## 1.1.1 Tutorial

You can take a look to the following tutorial to see what this is about and how to get started.

#### 1.1.2 Installation

To install napalm-yang you can use pip as with any other driver:

pip install -U napalm-yang

## 1.2 YANG Basics

It's not really necessary to fully understand how YANG works to work with napalm-yang but understanding the language used by YANG can be beneficial to better understand the documentation and the benefits of it.

Here is a list or resources to start learning YANG:

· YANG for dummies

## 1.3 Supported Models

Below you can find all the YANG models supported and which profiles implements which ones. Note that all the implementations are not necessarily complete, in the next section you can find links to each individual profile so you can inspect them yourself.

## 1.4 Profiles

Profiles are responsible from mapping native data/configuration to a YANG model and vice versa. Below you can find links to all the profiles so you can inspect what each one does.

## 1.5 API

## **1.5.1 Models**

Models are generated by pyangbind so it's better to check it's documentation for up to date information: http://pynms.io/pyangbind/generic\_methods/

#### 1.5.2 Utils

```
napalm_yang.utils.model_to_dict (model, mode=", show_defaults=False) Given a model, return a representation of the model in a dict.
```

This is mostly useful to have a quick visual represenation of the model.

#### **Parameters**

- model (PybindBase) Model to transform.
- mode (string) Whether to print config, state or all elements ("" for all)

**Returns** A dictionary representing the model.

Return type dict

## **Examples**

```
>>> config = napalm_yang.base.Root()
>>> # Adding models to the object
>>> config.add_model(napalm_yang.models.openconfig_interfaces())
>>> config.add_model(napalm_yang.models.openconfig_vlan())
>>> # Printing the model in a human readable format
>>> pretty_print(napalm_yang.utils.model_to_dict(config))
>>> {
        "openconfig-interfaces:interfaces [rw]": {
>>>
            "interface [rw]": {
>>>
                "config [rw]": {
>>>
                    "description [rw]": "string",
>>>
                    "enabled [rw]": "boolean",
>>>
                    "mtu [rw]": "uint16",
                    "name [rw]": "string",
                     "type [rw]": "identityref"
>>>
                },
>>>
                "hold_time [rw]": {
>>>
                    "config [rw]": {
>>>
>>>
                        "down [rw]": "uint32",
                         "up [rw]": "uint32"
    (trimmed for clarity)
```

```
napalm_yang.utils.diff (f, s)
```

Given two models, return the difference between them.

#### **Parameters**

- **f** (Pybindbase) First element.
- **s** (Pybindbase) Second element.

**Returns** A dictionary highlighting the differences.

Return type dict

#### **Examples**

```
>>> diff = napalm_yang.utils.diff(candidate, running)
>>> pretty_print(diff)
>>> {
        "interfaces": {
>>>
            "interface": {
>>>
                 "both": {
>>>
>>>
                     "Port-Channell": {
>>>
                         "config": {
>>>
                              "mtu": {
>>>
                                  "first": "0",
>>>
                                  "second": "9000"
>>>
>>>
>>>
                     }
                 },
                 "first_only": [
>>>
                     "Loopback0"
>>>
>>>
                 ],
                 "second_only": [
>>>
                     "Loopback1"
>>>
>>>
                 ]
>>>
            }
>>>
>>> }
```

## 1.5.3 Root

```
class napalm_yang.base.Root
    Bases: object
```

This is a container you can use as root for your other models.

## **Examples**

```
>>> config = napalm_yang.base.Root()
>>>
>>> # Adding models to the object
>>> config.add_model(napalm_yang.models.openconfig_interfaces())
>>> config.add_model(napalm_yang.models.openconfig_vlan())
```

1.5. API 5

#### add\_model (model, force=False)

Add a model.

The model will be asssigned to a class attribute with the YANG name of the model.

#### **Parameters**

- model (PybindBase) Model to add.
- **force** (bool) If not set, verify the model is in SUPPORTED\_MODELS

#### **Examples**

```
>>> import napalm_yang
>>> config = napalm_yang.base.Root()
>>> config.add_model(napalm_yang.models.openconfig_interfaces)
>>> config.interfaces
<pyangbind.lib.yangtypes.YANGBaseClass object at 0x10bef6680>
```

#### compliance\_report (validation\_file='validate.yml')

Return a compliance report. Verify that the device complies with the given validation file and writes a compliance report file. See https://napalm.readthedocs.io/en/latest/validate.html.

#### elements()

```
get (filter=False)
```

Returns a dictionary with the values of the model. Note that the values of the leafs are YANG classes.

**Parameters filter** (bool) – If set to True, show only values that have been set.

**Returns** A dictionary with the values of the model.

Return type dict

### **Example**

```
>>> pretty_print(config.get(filter=True))
>>> {
         "interfaces": {
>>>
             "interface": {
>>>
                 "et1": {
>>>
>>>
                      "config": {
>>>
                          "description": "My description",
                          "mtu": 1500
>>>
>>>
                      },
                      "name": "et1"
>>>
                 },
>>>
                 "et2": {
>>>
                      "config": {
                          "description": "Another description",
>>>
                          "mtu": 9000
>>>
>>>
                      },
                      "name": "et2"
>>>
>>>
                 }
>>>
             }
>>>
        }
>>> }
```

load\_dict (data, overwrite=False, auto\_load\_model=True)
Load a dictionary into the model.

#### **Parameters**

- data (dict) Dictionary to locad
- **overwrite** (bool) Whether the data present in the model should be overwritten by the data in the dict or not.
- auto\_load\_model (bool) If set to true models will be loaded as they are needed

#### **Examples**

```
>>> vlans dict = {
        "vlans": { "vlan": { 100: {
>>>
                                 "config": {
>>>
                                     "vlan_id": 100, "name": "production"}},
>>>
>>>
                              200: {
>>>
                                 "config": {
>>>
                                     "vlan_id": 200, "name": "dev"}}}}
>>> config.load_dict(vlans_dict)
>>> print(config.vlans.vlan.keys())
... [200, 100]
>>> print(100, config.vlans.vlan[100].config.name)
... (100, u'production')
>>> print(200, config.vlans.vlan[200].config.name)
... (200, u'dev')
```

#### parse\_config (device=None, profile=None, native=None, attrs=None)

Parse native configuration and load it into the corresponding models. Only models that have been added to the root object will be parsed.

If native is passed to the method that's what we will parse, otherwise, we will use the device to retrieve it.

#### **Parameters**

- **device** (*NetworkDriver*) Device to load the configuration from.
- **profile** (*list*) Profiles that the device supports. If no profile is passed it will be read from device.
- native (list of strings) Native configuration to parse.

## **Examples**

```
>>> # Load from device
>>> running_config = napalm_yang.base.Root()
>>> running_config.add_model(napalm_yang.models.openconfig_interfaces)
>>> running_config.parse_config(device=d)
```

```
>>> # Load from file
>>> with open("junos.config", "r") as f:
>>> config = f.read()
>>>
>>> running_config = napalm_yang.base.Root()
```

(continues on next page)

1.5. API 7

```
>>> running_config.add_model(napalm_yang.models.openconfig_interfaces)
>>> running_config.parse_config(native=[config], profile="junos")
```

#### parse\_state (device=None, profile=None, native=None, attrs=None)

Parse native state and load it into the corresponding models. Only models that have been added to the root object will be parsed.

If native is passed to the method that's what we will parse, otherwise, we will use the device to retrieve it.

#### **Parameters**

- **device** (NetworkDriver) Device to load the configuration from.
- **profile** (*list*) Profiles that the device supports. If no profile is passed it will be read from device.
- native (list string) Native output to parse.

#### **Examples**

```
>>> # Load from device
>>> state = napalm_yang.base.Root()
>>> state.add_model(napalm_yang.models.openconfig_interfaces)
>>> state.parse_config(device=d)
```

```
>>> # Load from file
>>> with open("junos.state", "r") as f:
>>> state_data = f.read()
>>>
>>> state = napalm_yang.base.Root()
>>> state.add_model(napalm_yang.models.openconfig_interfaces)
>>> state.parse_config(native=[state_data], profile="junos")
```

#### to\_dict (filter=True)

Returns a dictionary with the values of the model. Note that the values of the leafs are evaluated to python types.

**Parameters filter** (bool) – If set to True, show only values that have been set.

**Returns** A dictionary with the values of the model.

Return type dict

#### **Example**

```
>>> pretty_print(config.to_dict(filter=True))
>>> {
        "interfaces": {
>>>
            "interface": {
>>>
>>>
                 "et1": {
>>>
                     "config": {
>>>
                          "description": "My description",
                         "mtu": 1500
>>>
>>>
                     },
```

```
>>>
                      "name": "et1"
>>>
                 },
                  "et2": {
>>>
                      "config": {
>>>
                          "description": "Another description",
>>>
                           "mtu": 9000
>>>
                      },
                      "name": "et2"
>>>
                 }
             }
>>>
>>>
         }
>>> }
```

#### translate\_config (profile, merge=None, replace=None)

Translate the object to native configuration.

In this context, merge and replace means the following:

- Merge Elements that exist in both self and merge will use by default the values in merge unless self specifies a new one. Elements that exist only in self will be translated as they are and elements present only in merge will be removed.
- Replace All the elements in replace will either be removed or replaced by elements in self.

You can specify one of merge, replace or none of them. If none of them are set we will just translate configuration.

#### **Parameters**

- **profile** (list) Which profiles to use.
- merge (Root) Object we want to merge with.
- replace (Root) Object we want to replace.

## 1.6 Developers Guide

WIP. Information here is a bit chaotic, sorry about that.

#### 1.6.1 Profiles

In order to correctly map YANG objects to native configuration and vice versa, napalm-yang uses the concept of **profiles**. Profiles, identify the type of device you are dealing with, which can vary depending on the OS, version and/or platform you are using.

If you are using a napalm driver and have access to your device, you will have access to the profile property which you can pass to any function that requires to know the profile. If you are not using a napalm driver or don't have access to the device, a profile is just a list of strings so you can just specify it directly. For example:

```
# Without access to the device
model.parse_config(profile=["junos"], config=my_configuration)

# With access
with driver(hostname, username, password) as d:
    model.parse_config(device=d)
```

```
# With access but overriding profile
with driver(hostname, username, password) as d:
    model.parse_config(device=d, profile=["junos13", "junos"])
```

**Note:** As you noticed a device may have multiple profiles. When that happens, each model that is parsed will loop through the profiles from left to right and use the first profile that implements that model (note that a YANG model is often comprised of multiple modules). This is useful as there might be small variances between different systems but not enough to justify reimplementing everything.

You can find the profiles here but what exactly is a profile? A profile is a bunch of YAML files that follows the structure of a YANG model and describes two things:

- 1. How to parse native configuration/state and map it into a model.
- 2. How to translate a model and map it into native configuration.

For example, here you can see how to map native configuration from an EOS device into the openconfig-interface model and here how to map the model to native configuration.

As you can see it's not extremely difficult to understand what they are doing, in the next section we will learn how to write our own profiles.

## 1.6.2 Writing Profiles

As it's been already mentioned, a profile consists of a bunch of YAML files that describe how to map native configuration and how to translate an object into native configuration. In order to read native configuration we will use **parsers**. To translate a YANG model into native configuration we will use **translators**.

Both parsers and translators follow three basic rules:

- 1. One directory per module.
- 2. One file per model.
- 3. Exact same representation of the model inside the file:

#### For example:

If we check the content of the file vlan.yaml we can clearly see two parts:

• metadata - This part specifies what parser or translator we want to use. There are several options available depending on the type of data we are parsing from or translating to. Additionally, we need to provide some options that the parser/translator might need. For example:

In this case we are using the XMLParser parser. In order to get the data we need from the device we have to call the method \_rpc with the args and kwargs parameters. This is, by the way, an RPC call for a junos device.

**Note:** If a model is called by other models, like openconfig-if-ethernet is called by openconfig-interfaces, there is no need to specify the execute section in the metadata, if the commands will be the same. Since the first model executes the commands, the data from the commands will be shared with the models that the first model calls. While it will work it to specify the same commands in the metadata section for the second model, it could cause the commands to be executed multiple times.

• vlan - This is the part that follows the model specification. In this case is vlan but in others it might be interfaces, addressess or something else, this will be model dependent but it's basically whatever it's not metadata. This part will follow the model specification and add rules on each attribute to tell the parser/translator what needs to be done. For example:

We have to specify the \_process attribute at each step, which can either be unnecessary, "not\_implemented" or a list of rules:

- not\_implemented means that we haven't added support to that field. In addition it will stop parsing that branch of the tree.
- unnecessary means that we don't need that field. This is common in containers as you usually don't need to process them at all.
- list of rules. See Parsers and Translators.

Something else worth noting is that each rule inside \_process is evaluated as a jinja2 template so you can do variable substitutions, evaluations, etc...

## 1.6.3 Parsers

Parsers are responsible for mapping native configuration/data to a YANG model.

#### **Processing data**

The first thing you have to know is what type of data you are dealing with and then select the appropriate parser. Each one initializes the data and makes it available in similar ways but you have to be aware of the particularities of each one.

You can select the parser with the metadata field:

```
metadata:
    processor: TextTree
    execute:
        - method: cli
        kwargs:
        commands: ["show running-config all"]
```

That block not only specifies which parser to use but how to retrieve the data necessary for the parser to operate for that particular model.

Available processors are:

#### **JSONParser**

TBD

#### **XMLParser**

**TBD** 

#### **TextParser**

**TBD** 

#### **Rule Directives**

## **Keys**

When a list is traversed you will always have available a key with name \$ (attribute)\_key. In addition, you will have parent\_key as the key of the immediate parent object. Example.

#### **Bookmarks**

Bookmarks are points of interest in the configuration. Usually, you will be gathering blocks of configurations and parsing on those as you progress. However, sometimes the data you need is somewhere else. For those cases you can use the bookmarks within the from field to pick the correct block of configuration.

Bookmarks are created automatically according to these rules:

- At the begining of each model a bookmark of name root\_\$first\_attribute\_name will point to the list of data that the parser requires. Example
- When a container is traversed, a bookmark will be created with name \$attribure\_name
- When a list is traveresed, each element of the list will have its own bookmark with name \$attribute\_name. \$key.

#### extra\_vars

The regexp directive lets you capture any arbitary amount of information you want. All captured groups will be avaible to you inside the extra\_vars.\$attribute (\$attribute is the attribute where the additional information was captured). Example.

#### **Examples**

## **Examples - Lists**

## Parsing interfaces in industry standard CLIs (simple case)

When TexTree parses industry standard CLIs it will generate a dictionary similar to:

This means that to parse the interfaces we only have to advance to the interface key and map the keys to the YANG model key and get the block for further processing.

## **Original data**

```
interface Port-Channel1
    shutdown
!
interface Port-Channel1.1
    shutdown
!
interface Ethernet1
    shutdown
!
interface Ethernet2
```

```
no shutdown
!
interface Ethernet2.1
  no shutdown
!
interface Ethernet2.2
  no shutdown
!
interface Loopback1
  no shutdown
!
interface Management1
  no shutdown
!
```

#### Parser rule

```
- from: root_interfaces.0
  path: interface
  regexp: ^(?P<value>(\w|-)*\d+(\/\d+)*)$
```

- regexp is useful to filter out data that we don't want to process. For example, in the example above we are basically filtering subinterfaces as they will be processed later. Note that the regular expression has to capture a value.
- path is simply telling the parser that the data is looking for is inside the interface key.
- from is just telling the parser where to get the data from. This is the first element processed by the profile so there is no information that can be inferred yet.

#### Result

Note that extra\_vars will be populated with anything you capture with the regular expression. This might be handier when parsing more complex keys like ip addresses which might include the prefix length.

Note as well that we didn't get any subinterface thanks to regexp.

## **Example 1**

```
extra_vars: {}
keys: {}
```

## Parsing subinterfaces in industry standard CLIs (variables)

When we were parsing interfaces we skipped the subinterfaces. In order to pass subinterfaces we can leverage on the interface\_key to build a dynamic regular expression.

## **Original data**

```
interface Port-Channel1
   shutdown
interface Port-Channell.1
   shutdown
interface Ethernet1
   shutdown
interface Ethernet2
  no shutdown
interface Ethernet2.1
  no shutdown
interface Ethernet2.2
  no shutdown
interface Loopback1
  no shutdown
interface Management1
  no shutdown
```

#### Parser rule

```
- path: interface
regexp: '{{interface_key}}\.(?P<value>\d+)'
```

Because we are parsing a *subinterface* which is a child of an *interface*, all the keys and extra\_vars that we previously collected in the current interface will be available. We will use { { interface\_key } } in our regular expression to match only our current parent interface.

#### Result

Note that thanks to the variable used in the regular expression we are only capturing the relevant subinterface for the current interface. In the second case it turns out there are no subinterfaces.

## **Example 1**

```
extra_vars: {}
keys:
interface_key: Ethernet2
```

## Example 2

```
extra_vars: {}
keys:
interface_key: Loopback1
```

## Parsing IP addresses in EOS (extracting extra information from a key)

IP addresses in EOS contain two pieces of information; the address and it's prefix-length. You can use regexp to select the relevant part for the key and any additional information you may need.

#### **Original data**

```
ip address 192.168.1.1/24
ip address 192.168.2.1/24 secondary
ip address 172.20.0.1/24 secondary
```

#### Parser rule

```
- path: ip.address
regexp: (?P<value>(?P<ip>.*))\/(?P<prefix>\d+)
```

The regular expression is doing two things; use the <value> to capture which part should be used for the key and then capture as well all the useful information so we have it available for later use in the extra\_vars field.

#### Result

Note that extra\_vars is populated with the information we captured with regexp..

#### **Example 1**

```
extra_vars: {}
keys: {}
```

## Parsing IP addresses in IOS (flattening dictionaries)

Sometimes the information is unnecessarily nested. This is the case for the ip address configuration in IOS. Let's see how that data might look like after processing it with the TextParser:

```
255.255.255.0:
    "#standalone": true

172.20.0.1:
    255.255.255.0:
    secondary":
    "#standalone": true
```

Luckily, we can solve this issue with the path resolver.

## **Original data**

```
ip address 192.168.1.1 255.255.255.0
ip address 192.168.2.1 255.255.255.0 secondary
ip address 172.20.0.1 255.255.255.0 secondary
```

#### Parser rule

```
- key: prefix
path: ip.address.?prefix.?mask
regexp: ^(?P<value>\d+\.\d+\.\d+\)
```

We specify a regexp here to make sure we don't parse lines like ip address dhcp.

When path contains ?identifier what it actually does is flatten that key and assign the value of that key to a new key named identifier. For example, with the nested structure and the path we have right now we would get the following:

```
- prefix: 192.168.1.1
   mask: 255.255.255.0
   '#standalone': true
- prefix: 192.168.2.1
   mask: 255.255.255.0
   secondary:
        '#standalone': true
- prefix: 172.20.0.1
   mask: 255.255.255.0
   prefix: 172.20.0.1
   secondary:
        '#standalone': true
```

#### Result

## **Example 1**

```
extra_vars: {}
keys: {}
```

## Parse BGP neighbors in Junos (nested lists)

XML often consists of lists of lists which sometimes makes it challenging to nest things in a sane manner. Hopefully, the path can solve this issue as well.

## **Original data**

```
<some_configuration_block>
   <group>
       <name>my_peers</name>
       <neighbor>
            <name>192.168.100.2</name>
            <description>adsasd</description>
            <peer-as>65100</peer-as>
       </neighbor>
        <neighbor>
            <name>192.168.100.3</name>
            <peer-as>65100</peer-as>
       </neighbor>
   </group>
   <group>
       <name>my_other_peers</name>
       <neighbor>
            <name>172.20.0.1</name>
            <peer-as>65200</peer-as>
       </neighbor>
   </group>
</some_configuration_block>
```

#### Parser rule

```
- key: ip path: group.?peer_group:name.neighbor.?ip:name
```

Note that this time the path contains a couple of ?identifier:field. That pattern is used to flatten lists and what it does is assign the contents of that sublist to the parent object and also assign the value of field to a new key called identifier. For example, the XML above will be converted to the following structure:

```
- name:
    '#text': my_peers
peer-as:
    '#text': 65100
neighbor: 192.168.100.3
peer_group: my_peers
- name:
    '#text': my_peers
description:
    '#text': adsasd
peer-as:
    '#text': 65100
neighbor: 192.168.100.2
peer_group: my_peers
- name:
```

```
'#text': my_other_peers
peer-as:
    '#text': 65200
neighbor: 172.20.0.1
peer_group: my_other_peers
```

#### Result

#### **Example 1**

```
extra_vars: {}
keys: {}
```

## Parsing protocols (down the rabbit hole)

Some parsing might require more complex rules. In this example we can see how to combine multiple rules ran under different circumstances.

## **Original data**

```
ip route 10.0.0.0/24 192.168.0.2 10 tag 0
ip route vrf devel 10.0.0.0/24 192.168.2.2 1 tag 0
!
router bgp 65001
  router-id 1.1.1.1
  address-family ipv4
       default neighbor 192.168.0.200 activate
!
  address-family ipv6
       default neighbor 192.168.0.200 activate
  vrf devel
       router-id 3.3.3.3
!
router pim sparse-mode
  vrf devel
       ip pim log-neighbor-changes
!
```

## Parser rule

```
- key: '{{ protocol }} {{ protocol }}'
  path: router.?protocol.?process_id
  regexp: (?P<value>bgp bgp)
  when: '{{ network_instance_key == ''global'' }}'
- from: root_network-instances.0
  key: '{{ protocol }} {{ protocol }}'
  path: router.?protocol.?process_id.vrf.{{ network_instance_key }}
  regexp: (?P<value>bgp bgp)
```

```
when: '{{ network_instance_key != ''global'' }}'
- from: root_network-instances.0
key: '{{ ''static static'' }}'
path: ip.route
```

When multiple rules are specified all of them will be executed and the results will be concatenated. You can combine this technique with when to specify how to parse the data under different circumstances (see rules #1 and #2) or just to add more ways of parsing data (see rule #3)

Note also that we are also dynamically building the key to follow the format that the YANG model requires, which in this case is as simple (and weird) as just specifying a name for our protocol (which in our case will be the same as the protocool).

It also worth noting that we are using a regular expression to match only on BGP. We are doing that to avoid processing protocols that we are not (yet) supporting in this profile.

#### Result

The results below might look intimidating but it's basically the relevant configuration for BGP and for the static routes for the current network instance.

## **Example 1**

```
extra_vars: {}
keys:
  network_instance_key: global
```

#### Example 2

```
extra_vars: {}
keys:
  network_instance_key: devel
```

#### Parsing json interfaces IOS-XE (jsonrpc)

IOS-XE groups interfaces by type.

#### **Original data**

```
}
    },
    "mop": {
     "enabled": false
    "Cisco-IOS-XE-ethernet:negotiation": {
     "auto": true
  },
   "name": "2",
   "description": "GbE 2",
    "ip": {
     "no-address": {
       "address": false
     }
    },
    "mop": {
     "enabled": false
    "Cisco-IOS-XE-ethernet:negotiation": {
     "auto": true
  },
   "name": "2.10",
   "description": "GbE 2.10",
    "encapsulation": {
     "dot1Q": {
       "vlan-id": 10
     }
    "vrf": {
     "forwarding": "internal"
    },
    "ip": {
     "address": {
       "primary": {
          "address": "172.16.10.1",
          "mask": "255.255.255.0"
      }
    }
  }
  ],
"Loopback": [
 {
   "name": 0,
    "description": "Loopback Zero",
    "ip": {
     "address": {
        "primary": {
          "address": "100.64.0.1",
          "mask": "255.255.255.255"
        }
      }
    },
```

```
"ipv6": {
        "address": {
          "prefix-list": [
               "prefix": "2001:DB8::1/64"
          ]
        }
      }
    },
      "name": 1,
      "description": "Loopback One",
      "vrf": {
        "forwarding": "mgmt"
      },
      "ip": {
        "no-address": {
          "address": false
  ]
}
```

#### Parser rule

```
- from: root_interfaces.0
key: '{{ type }}{{ name }}'
path: Cisco-IOS-XE-native:interface.?type
regexp: ^(?P<value>(\w|-)*\d+(\/\d+)*)$
```

## Result

## **Example 1**

```
extra_vars: {}
keys: {}
```

## Parsing ntp peers Junos

Junos groups ntp servers and peers by type and then lists them

## **Original data**

#### Parser rule

```
- key: '#text'
path: configuration.system.ntp.?type.name
```

#### Result

## **Example 1**

```
extra_vars: {}
keys: {}
```

#### **Examples - leaf**

## Parsing metric style for junos ISIS level

Junos sometimes indicates the value of something not by using an element with a specific value but by the presence of it. For instance, the metric style of an ISIS level can either be NARROW or WIDE but instead of indicating explicitly junos will do it with the presence or not of the element </wide-metrics-only>.

## **Original data**

```
</interface>
        <interface>
            <name>ge-0/0/1.0</name>
            <point-to-point/>
        </interface>
        <interface>
            < name > ge - 0/0/2.0 < / name >
            <point-to-point/>
        </interface>
        <interface>
            <name>ge-0/0/3.0</name>
            <point-to-point/>
        </interface>
        <interface>
            <name>100.0</name>
        </interface>
    </isis>
</configuration>
```

#### Parser rule

```
- default: NARROW_METRIC
path: wide-metrics-only
post: WIDE_METRIC
present: true
```

#### Result

#### **Example 1**

```
extra_vars: {}
keys: {}
```

## Parse EOS privilege:role

The role in eos is the combination of the privilege level and the role itself. In this example we should how to use a regular expression to capture data and postprocess it to set the correct role.

## **Original data**

```
username test1 privilege 1 nopassword
username test2 privilege 1 secret sha512 $6$WL/ibPpzPJ/C7c/E$.

→bVF08dYhlNpOrxER0P3SNdsA2wUtK2Ru1YuKkRRZQG1609DA1JvX.dSFgKXaq.

→LWjDR1ZoHudfk7hamod0Th/
username test3 privilege 15 role network-operator secret sha512 $6$Vd6.7k2FybfsTKKp$S.

→AHfdwicaWEoA41sPd6ZXOOdruJMrKJh70WNfiX/eZKH1oYBtFz9VbrPlYNDkhM/pi54gcYKH2hviy/xrUav.
username test4 privilege 1 secret 5 $1$NKhJ$PUfYNtJF2tIneEBZztchy.
username test5 privilege 15 secret sha512 $6$d3fdbbZBrhplknVB$FILKNelLURwd/

→xT74ktjxJ4XP1vTfJ53H7OWJHgAqeuY/1F3BDyP3SWpH/MeBRn171Li8hU2oy6hkbnB7jvtA.

(continues on next page)
```

#### Parser rule

```
- path: privilege
post: '{{ extra_vars.privilege }}:{{ extra_vars.role }}'
regexp: (?P<value>(?P<privilege>\d+).*role (?P<role>\S+)) secret
- path: privilege
post: '{{ value }}:network-operator'
regexp: (?P<value>\d+)
```

#### Result

#### **Example 1**

```
extra_vars: {}
keys: {}
```

## 1.6.4 Translators

Translators are responsible for transforming a model into native configuration.

## **Special actions**

Most actions depend on the parser you are using, however, some are common to all of them:

#### unnecessary

This makes the parser skip the field and continue processing the tree.

#### not implemented

This makes the parser stop processing the tree underneath this value. For example:

```
field_1:
    process: unnecessary
field_2:
    process: not_implemented
    subfield_1:
        process: ...
    subfield_2:
        process: ...
field_3:
    ...
```

The not\_implemented action will stop the parser from processing subfield\_1 and subfield\_2 and move directly onto field\_3.

#### gate

Works like not\_implemented but accepts a condition. For example:

```
protocols:
    protocol:
    bgp:
        _process:
        - mode: gate
        when: "{{ protocol_key != 'bgp bgp' }}"
        global:
        ...
```

The snippet above will only process the bgp subtree if the condition is **not** met.

## Special fields

When translating an object, some fields might depend on the translator you are using but some will available regardless. Some may be even be mandatory.

#### mode

- mandatory: yes
- description: which parsing/translation action to use for this particular field
- example: translate description attribute of an interface to native configuration:

```
description:
   _process:
        - mode: element
        value: "         description {{ model }}\n"
        negate: "         default description"
```

## when

- · mandatory: no
- **description**: the evaluation of this field will determine if the action is executed or skipped. This action is probably not very useful when parsing but it's available if you need it.
- example: configure switchport on IOS devices only if the interface is not a loopback or a management interface:

```
ipv4:
   _process: unnecessary
   config:
    _process: unnecessary
    enabled:
    _process:
```

```
- mode: element
    value: "    no switchport\n"
    negate: "    switchport\n"
    in: "interface.{{ interface_key }}"
    when: "{{ model and interface_key[0:4] not in ['mana', 'loop'] }

$\iff \}"
```

in

- · mandatory: no
- **description**: where to add the configuration. Sometimes the configuration might have to be installed on a different object from the one you are parsing. For example, when configuring a tagged subinterface on junos you will have to add also a vlan-tagging option on the parent interface. On IOS/EOS, when configuring interfaces, you have to also add the configuration in the root of the configuration and not as a child of the parent interface:

```
vlan:
    _process: unnecessary
    confiq:
        _process: unnecessary
        vlan id:
            _process:
                - mode: element
                  element: "vlan-tagging"
                  in: "interface.{{ interface_key }}" # <--- add element to_</pre>
→parent interface
                  when: "{{ model > 0 }}"
                  value: null
                - mode: element
                  element: "vlan-id"
                  when: "{{ model > 0 }}"
(...)
subinterface:
    _process:
       mode: container
        key_value: "interface {{ interface_key}}.{{ subinterface_key }}\n"
        negate: "no interface {{ interface_key}}.{{ subinterface_key }}\n"
        in: "interfaces"
                                                      # <--- add element to root of
→ configuration
```

**Note:** This field follows the same logic as the *Bookmarks* special field.

#### continue\_negating

- · mandatory: no
- **description**: this option, when added to a container, will make the framework to also negate children.
- example: we can use as an example the "network-instances" model. In the model, BGP is inside the network-instance container, however, in EOS and other platforms that BGP configuration is decoupled

from the VRF, so in order to tell the framework to delete also the direct children you will have to use this option. For example:

```
network-instance:
   _process:
       - mode: container
         key_value: "vrf definition {{ network_instance_key }}\n"
         negate: "no vrf definition {{ network_instance_key }}\n"
         continue_negating: true
         end: " exit\n"
         when: "{{ network_instance_key != 'global' }}"
   protocols:
       _process: unnecessary
       protocol:
           _process:
             - mode: container
               key_value: "router bgp {{ model.bgp.global_.config.as_ }}\n vrf {
→{ network_instance_key}}\n"
              negate: "router bgp {{ model.bgp.global_.config.as_ }}\n no vrf {
→{ network_instance_key}}\n"
               end: " exit\n"
               when: "{{ protocol_key == 'bgp bgp' and network_instance_key !=
replace: false
               in: "network-instances"
```

The example above will generate:

```
no vrf definition blah
router bgp ASN
no vrf blah
```

Without continue\_negating it would just generate:

```
no vrf definition blah
```

#### Special variables

#### keys

See Keys.

#### model

This is the current model/attribute being translated. You have the entire object at your disposal, not only it's value so you can do things like:

```
vlan_id:
    _process:
        - mode: element
        value: " encapsulation dot1q vlan {{ model }}\n"
```

Or:

## 1.6.5 XMLTranslator

XMLTranslator is responsible for translating a model into XML configuration.

#### Metadata

• xml root - Set this value on the root of the model to instantiate the XML object.

For example:

```
---
metadata:
   processor: XMLTranslator
   xml_root: configuration
```

This will instantiate the XML object <configuration/>.

#### **Container - container**

Creates a container.

Arguments:

- **container** (mandatory) Container name.
- **replace** (optional) True/Flase, depending Whether this element has to be replaced in case of merge/replace or it's not necessary (remember XML is hierarchical, which means you can unset things directly in the root).

Example:

Create the interfaces container:

```
_process:
. mode: container
container: interfaces
replace: true
```

#### List - container

For each element of the list, create a container.

Arguments:

• container (mandatory) - Name of container to create.

- **key\_element** (mandatory) Lists require a key element, this is the name of the element.
- key\_value (mandatory) Key element value.

## Example:

Create interfaces:

```
interface:
   _process:
        . mode: container
        container: interface
        key_element: name
        key_value: "{{ interface_key }}"
```

This will result elements such as:

#### Leaf - element

Adds an element to a container.

Arguments:

- **element** (mandatory): Element name.
- value (optional): Override value. Default is value of the object.

## Example 1:

Configure description:

#### Example 2:

Enable or disable an interface:

```
enabled:
   _process:
        - mode: element
        element: "disable"
        when: "{{ not model }}"
        value: null
```

We override the value and set it to null because to disable we just have to create the element, we don't have to set any value.

#### Example 3:

Configure an IP address borrowing values from other fields:

```
config:
    _process: unnecessary
    ip:
        _process: unnecessary
    prefix_length:
        _process:
        - mode: element
            element: name
            value: "{{ model._parent.ip }}/{{ model }}"
            when: "{{ model }}"
```

## 1.6.6 TextTranslator

TextTranslator is responsible of translating a model into text configuration.

#### Metadata

• root - Set to true if this is the root of the model.

#### List - container

Create/Removes each element of the list.

Arguments:

- key\_value (mandatory): How to create the element.
- negate (mandatory): How to eliminate/default the element.
- replace (optional): Whether the element has to be defaulted or not during the replace operation.
- end (optional): Closing command to signal end of element

## Example 1:

Create/Default interfaces:

### Example 2:

Configure IP addresses. As the parent interface is defaulted already, don't do it again:

```
negate: " default ip address {{ model.config.ip }} {{ model.
config.prefix_length|cidr_to_netmask }}{{ ' secondary' if model.config.
condary else '' }}\n"
replace: false
```

#### Leaf - element

Configures an attribute.

Arguments:

- value (mandatory): How to configure the attribute
- negate (mandatory): How to default the attribute

## Example 1:

Configure description:

#### Example 2:

Configure an IP address borrowing values from other fields:

## 1.6.7 Jinja2 Filters

#### IP address

```
napalm_yang.jinja_filters.ip_filters.cidr_to_netmask(value, *args, **kwargs)
Converts a CIDR prefix-length to a network mask.
```

## **Examples**

```
>>> "{{ '24'|cidr_to_netmask }}" -> "255.255.255.0"
```

napalm\_yang.jinja\_filters.ip\_filters.netmask\_to\_cidr(value, \*args, \*\*kwargs)
Converts a network mask to it's CIDR value.

## **Examples**

```
>>> "{{ '255.255.255.0'|netmask_to_cidr }}" -> "24"
```

napalm\_yang.jinja\_filters.ip\_filters.normalize\_address (value, \*args, \*\*kwargs)
Converts an IPv4 or IPv6 address writen in various formats to a standard textual representation.

This filter works only on addresses without network mask. Use normalize\_prefix to normalize networks.

## **Examples**

```
>>> "{{ '192.168.0.1'|normalize_address }}" -> "192.168.0.1"
>>> "{{ '192.168.1'|normalize_address }}" -> "192.168.0.1"
>>> "{{ '2001:DB8:0:0:1:0:0:1'|normalize_address }}" -> "2001:db8::1:0:0:1"
```

napalm\_yang.jinja\_filters.ip\_filters.normalize\_prefix (value, \*args, \*\*kwargs)
Converts an IPv4 or IPv6 prefix writen in various formats to its CIDR representation.

This filter works only on prefixes. Use normalize\_address if you wish to normalize an address without a network mask.

## **Examples**

```
>>> "{{ '192.168.0.0 255.255.255.0'|normalize_prefix }}" -> "192.168.0.0/24"
>>> "{{ '192.168/255.255.255.0'|normalize_prefix }}" -> "192.168.0.0/24"
>>> "{{ '2001:DB8:0:0:1:0:0:1/64'|normalize_prefix }}" -> "2001:db8::1:0:0:1/64"
```

napalm\_yang.jinja\_filters.ip\_filters.**prefix\_to\_addrmask** (*value*, \*args, \*\*kwargs)

Converts a CIDR formatted prefix into an address netmask representation. Argument sep specifies the separator between the address and netmask parts. By default it's a single space.

## **Examples**

```
>>> "{{ '192.168.0.1/24|prefix_to_addrmask }}" -> "192.168.0.1 255.255.255.0"
>>> "{{ '192.168.0.1/24|prefix_to_addrmask('/') }}" -> "192.168.0.1/255.255.255.0"
```

### 1.6.8 FAQ

#### Some YAML files are insanely large. Can I break them down into multiple files?

Yes, you can with the !include relative/path/to/file.yaml directive. For example:

```
# ./main.yaml
my_key:
    blah: asdasdasd
    bleh: !include includes/bleh.yaml

(continues on next page)
```

```
# ./includes/bleh.yaml qwe: 1 asd: 2
```

## Will result in the final object:

```
my_key:
   blah: asdasdasd
   bleh:
    qwe: 1
   asd: 2
```

# Python Module Index

## n

 $\begin{array}{c} \texttt{napalm\_yang.jinja\_filters.ip\_filters,} \\ 32 \end{array}$ 

36 Python Module Index

# Index

Α		R				
add_model() (napalm_yang.base.Root method), 5	Root (class in napalm_yang.base), 5					
C		Т				
cidr_to_netmask() (in module palm_yang.jinja_filters.ip_filters), 32 compliance_report() (napalm_yang.base.Root method	na- d), 6	to_dict() (napalm_yang.base.Root method), 8 translate_config() (napalm_yang.base.Root method), 9				
D						
diff() (in module napalm_yang.utils), 4						
E						
elements() (napalm_yang.base.Root method), 6						
G						
get() (napalm_yang.base.Root method), 6						
L						
load_dict() (napalm_yang.base.Root method), 6	load_dict() (napalm_yang.base.Root method), 6					
M						
model_to_dict() (in module napalm_yang.utils), 4						
N						
napalm_yang.jinja_filters.ip_filters (module), 32						
netmask_to_cidr() (in module palm_yang.jinja_filters.ip_filters), 32	na-					
normalize_address() (in module	na-					
palm_yang.jinja_filters.ip_filters), 33 normalize_prefix() (in module	na-					
palm_yang.jinja_filters.ip_filters), 33	na-					
Р						
parse_config() (napalm_yang.base.Root method), 7						
parse_state() (napalm_yang.base.Root method), 8 prefix_to_addrmask() (in module	no					
palm_yang.jinja_filters.ip_filters), 33	na-					