

---

# OfertoApp Documentation

*Release latest*

Sep 07, 2019



---

## Contents

---

<b>1</b>	<b>Requeriments</b>	<b>3</b>
<b>2</b>	<b>Prerequisites</b>	<b>5</b>
<b>3</b>	<b>Installation</b>	<b>7</b>



Maneja tus canales de referidos, publica y controla los chollos de tus tiendas online preferidas. Distribuye tus referidos a tus afiliados. Totalmente gratis y opensource.



# OfertoApp



# CHAPTER 1

---

## Requeriments

---

```
PHP 7.3.0 or higher ( php-xml, php-zip & php-mysql extensions are required)
MySQL or PostgreSQL
Web server
Composer
Google IAM Service Account Credentials API
```





## CHAPTER 2

---

### Prerequisites

---

- Ensure that you created a user for mysql before.

```
create database ofertoapp;  
create user user_ofertoapp@localhost;  
SET PASSWORD FOR 'user_ofertoapp'@'localhost' = PASSWORD('secure_password_here');  
GRANT ALL PRIVILEGES ON ofertoapp.* to 'user_ofertoapp'@'localhost' IDENTIFIED BY  
↪ 'secure_password_here';  
flush privileges;  
exit
```



## CHAPTER 3

---

### Installation

---

- Download the project from [Source Forge](#). or clone the project from github.
- Modify the line DATABASE\_URL & APP\_ENV and Google information with your data at the .env file.

```
APP_ENV=prod
GOOGLE_CLIENT_ID=
GOOGLE_CLIENT_SECRET=
DATABASE_URL=mysql://user_ofertoapp:secure_password_here@127.0.0.1:3306/ofertoapp
```

- Go to the file /config/packages/doctrine.yaml and add the following parameters in the beginning

```
parameters:
    database_driver: pdo_mysql
    database_host: 127.0.0.1
    database_port: 3306
    database_name: ofertaapp
    database_user: user_ofertoapp
    database_password: secure_password_here
```

- Inside the project folder execute composer install.

```
composer install --no-dev --optimize-autoloader
```

- Update the schema with doctrine

```
php bin/console doctrine:schema:update --force
```

- Migrate some required data

```
php bin/console doctrine:migrations:execute --up 01
```

- Configure permissions, virtualhost and logs

```
chown -R www-data. /var/www/OfertoApp
a2enmod rewrite
```

- Enable default vhost for apache2 example:

```
<VirtualHost *:80>
    ServerName your_domain_here.com
    ServerAlias your_domain_here.com www.your_domain_here.com
    DocumentRoot /var/www/OfertoApp/public
    <Directory /var/www/OfertoApp/public>
        Options Indexes FollowSymLinks MultiViews
        AllowOverride All
        Require all granted
        <IfModule mod_rewrite.c>
            Options -MultiViews
            RewriteEngine On
            RewriteCond %{REQUEST_FILENAME} !-f
            RewriteRule ^(.*)$ index.php [QSA,L]
        </IfModule>
    </Directory>
    <Directory /var/www/OfertoApp>
        Options FollowSymLinks
    </Directory>
    ErrorLog /var/log/apache2/OfertoApp/project_error.log
    CustomLog /var/log/apache2/OfertoApp/project_access.log combined
</VirtualHost>
```

- Clear the cache in the project directory for prod env

```
APP_ENV=prod APP_DEBUG=0 php bin/console cache:clear
```

- In order to create the admin user, first access with your google account and insert the following SQL in the database

```
UPDATE user SET roles = 'a:1:{i:0;s:10:"ROLE_ADMIN";}' where id = 1;
```

- Logout in the application and log in again.