
pydocstyle Documentation

Release 1.0.0

Amir Rachum

Oct 09, 2017

Contents

1	Quick Start	3
1.1	Usage	3
1.2	Error Codes	7
1.3	Release Notes	8
1.4	Older Versions	11
1.5	License	13
2	Credits	15

pydocstyle is a static analysis tool for checking compliance with Python docstring conventions.

pydocstyle supports most of [PEP 257](#) out of the box, but it should not be considered a reference implementation.

pydocstyle supports Python 2.7, 3.3, 3.4, 3.5 and pypy.

CHAPTER 1

Quick Start

1. Install

```
pip install pydocstyle
```

2. Run

```
$ pydocstyle test.py
test.py:18 in private nested class `meta`:
    D101: Docstring missing
test.py:27 in public function `get_user`:
    D300: Use """triple double quotes""" (found '''-quotes)
test.py:75 in public function `init_database`:
    D201: No blank lines allowed before function docstring (found 1)
...
```

3. Fix your code :)

Contents:

1.1 Usage

1.1.1 Installation

Use `pip` or `easy_install`:

```
pip install pydocstyle
```

Alternatively, you can use `pydocstyle.py` source file directly - it is self-contained.

1.1.2 Command Line Interface

Usage

```
Usage: pydocstyle [options] [<file|dir>...]
```

Options:

<code>--version</code>	show program's version number and exit
<code>-h, --help</code>	show this help message and exit
<code>-e, --explain</code>	show explanation of each error
<code>-s, --source</code>	show source for each error
<code>-d, --debug</code>	print debug information
<code>-v, --verbose</code>	print status information
<code>--count</code>	print total number of errors to stdout
<code>--config=<path></code>	use given config file and disable config discovery
<code>--match=<pattern></code>	check only files that exactly match <pattern> regular expression; default is <code>--match='(?!test_).*\.py'</code> which matches files that don't start with 'test_' but end with '.py'
<code>--match-dir=<pattern></code>	search only dirs that exactly match <pattern> regular expression; default is <code>--match-dir='^[\.].*'</code> , which matches all dirs that don't start with a dot
<code>--ignore-decorators=<decorators></code>	ignore any functions or methods that are decorated by a function with a name fitting the <decorators> regular expression; default is <code>--ignore-decorators=''</code> which does not ignore any decorated functions.

Error Check Options:

Only one of `--select`, `--ignore` or `--convention` can be specified. If none is specified, defaults to `--convention=pep257`. These three options select the "basic list" of error codes to check. If you wish to change that list (for example, if you selected a known convention but wish to ignore a specific error from it or add a new one) you can use `--add-[ignore/select]` in order to do so.

<code>--select=<codes></code>	choose the basic list of checked errors by specifying which errors to check for (with a list of comma-separated error codes or prefixes). for example: <code>--select=D101,D2</code>
<code>--ignore=<codes></code>	choose the basic list of checked errors by specifying which errors to ignore out of all of the available error codes (with a list of comma-separated error codes or prefixes). for example: <code>--ignore=D101,D2</code>
<code>--convention=<name></code>	choose the basic list of checked errors by specifying an existing convention. Possible conventions: pep257, numpy.
<code>--add-select=<codes></code>	add extra error codes to check to the basic list of errors previously set by <code>--select</code> , <code>--ignore</code> or <code>--convention</code> .
<code>--add-ignore=<codes></code>	ignore extra error codes by removing them from the basic list previously set by <code>--select</code> , <code>--ignore</code> or <code>--convention</code> .

Note: When using any of the `--select`, `--ignore`, `--add-select`, or `--add-ignore` command line flags, it is possible to pass a prefix for an error code. It will be expanded so that any code beginning with that prefix will match. For example, running the command `pydocstyle --ignore=D4` will ignore all docstring content issues as their error codes beginning with “D4” (i.e. D400, D401, D402, D403, and D404).

Return Code

0	Success - no violations
1	Some code violations were found
2	Illegal usage - see error message

Configuration Files

`pydocstyle` supports *ini*-like configuration files. In order for `pydocstyle` to use it, it must be named one of the following options, and have a `[pydocstyle]` section.

- `setup.cfg`
- `tox.ini`
- `.pydocstyle`
- `.pydocstyle.ini`
- `.pydocstylerc`
- `.pydocstylerc.ini`

When searching for a configuration file, `pydocstyle` looks for one of the file specified above *in that exact order*. If a configuration file was not found, it keeps looking for one up the directory tree until one is found or uses the default configuration.

Note: For backwards compatibility purposes, **pydocstyle** supports configuration files named `.pep257`, as well as section header `[pep257]`. However, these are considered deprecated and support will be removed in the next major version.

Available Options

Not all configuration options are available in the configuration files. Available options are:

- `convention`
- `select`
- `ignore`
- `add_select`
- `add_ignore`
- `match`
- `match_dir`

- `ignore_decorators`

See the *Usage* section for more information.

Inheritance

By default, when finding a configuration file, `pydocstyle` tries to inherit the parent directory's configuration and merge them to the local ones.

The merge process is as follows:

- If one of `select`, `ignore` or `convention` was specified in the child configuration - Ignores the parent configuration and set the new error codes to check. Otherwise, simply copies the parent checked error codes.
- If `add-ignore` or `add-select` were specified, adds or removes the specified error codes from the checked error codes list.
- If `match` or `match-dir` were specified - use them. Otherwise, use the parent's.

In order to disable this (useful for configuration files located in your repo's root), simply add `inherit=false` to your configuration file.

Note: If any of `select`, `ignore` or `convention` were specified in the CLI, the configuration files will take no part in choosing which error codes will be checked. `match` and `match-dir` will still take effect.

Example

```
[pydocstyle]
inherit = false
ignore = D100,D203,D405
match = *.py
```

In-file configuration

`pydocstyle` supports inline commenting to skip specific checks on specific functions or methods. The supported comments that can be added are:

1. `"# noqa"` skips all checks.
2. `"# noqa: D102,D203"` can be used to skip specific checks. Note that this is compatible with skips from `flake8`, e.g. `# noqa: D102,E501,D203`.

For example, this will skip the check for a period at the end of a function docstring:

```
>>> def bad_function(): # noqa: D400
...     """Omit a period in the docstring as an exception"""
...     pass
```

1.2 Error Codes

1.2.1 Grouping

Missing Docstrings	
D100	Missing docstring in public module
D101	Missing docstring in public class
D102	Missing docstring in public method
D103	Missing docstring in public function
D104	Missing docstring in public package
D105	Missing docstring in magic method
D106	Missing docstring in public nested class
D107	Missing docstring in <code>__init__</code>
Whitespace Issues	
D200	One-line docstring should fit on one line with quotes
D201	No blank lines allowed before function docstring
D202	No blank lines allowed after function docstring
D203	1 blank line required before class docstring
D204	1 blank line required after class docstring
D205	1 blank line required between summary line and description
D206	Docstring should be indented with spaces, not tabs
D207	Docstring is under-indented
D208	Docstring is over-indented
D209	Multi-line docstring closing quotes should be on a separate line
D210	No whitespaces allowed surrounding docstring text
D211	No blank lines allowed before class docstring
D212	Multi-line docstring summary should start at the first line
D213	Multi-line docstring summary should start at the second line
D214	Section is over-indented
D215	Section underline is over-indented
Quotes Issues	
D300	Use <code>"""triple double quotes"""</code>
D301	Use <code>r"""</code> if any backslashes in a docstring
D302	Use <code>u"""</code> for Unicode docstrings
Docstring Content Issues	
D400	First line should end with a period
D401	First line should be in imperative mood
D401	First line should be in imperative mood; try rephrasing
D402	First line should not be the function's "signature"
D403	First word of the first line should be properly capitalized
D404	First word of the docstring should not be <i>This</i>
D405	Section name should be properly capitalized
D406	Section name should end with a newline
D407	Missing dashed underline after section
D408	Section underline should be in the line following the section's name
D409	Section underline should match the length of its name
D410	Missing blank line after section
D411	Missing blank line before section
D412	No blank lines allowed between a section header and its content
D413	Missing blank line after last section

Continued on next page

Table 1.1 – continued from previous page

D414	Section has no content
------	------------------------

1.2.2 Default Checks

Not all error codes are checked for by default. The default behavior is to check only error codes that are part of the [PEP257](#) official convention.

All of the above error codes are checked for by default except for D203, D212, D213 and D404.

1.2.3 Publicity

The D1xx group of errors deals with missing docstring in public constructs: modules, classes, methods, etc. It is important to note how publicity is determined and what its effects are.

How publicity is determined

Publicity for all constructs is determined as follows: a construct is considered *public* if -

1. Its immediate parent is public *and*
2. Its name does not contain a single leading underscore.

A construct's immediate parent is the construct that contains it. For example, a method's parent is a class object. A class' parent is usually a module, but might also be a function, method, etc. A module can either have no parent, or it can have a parent that is a package.

In order for a construct to be considered public, its immediate parent must also be public. Since this definition is recursive, it means that *all* of its parents need to be public. The corollary is that if a construct is considered private, then all of its descendants are also considered private. For example, a class called `_Foo` is considered private. A method `bar` in `_Foo` is also considered private since its parent is a private class, even though its name does not begin with a single underscore.

Modules are parsed to look if `__all__` is defined. If so, only those top level constructs are considered public. The parser looks for `__all__` defined as a literal list or tuple. As the parser doesn't execute the module, any mutation of `__all__` will not be considered.

How publicity affects error reports

The immediate effect of a construct being determined as private is that no D1xx errors will be reported for it (or its children, as the previous section explains). A private method, for instance, will not generate a D102 error, even if it has no docstring.

However, it is important to note that while docstring are optional for private construct, they are still required to adhere to your style guide. So if a private module `_foo.py` does not have a docstring, it will not generate a D100 error, but if it *does* have a docstring, that docstring might generate other errors.

1.3 Release Notes

pydocstyle version numbers follow the [Semantic Versioning](#) specification.

1.3.1 2.1.1 - October 9th, 2017

Bug Fixes

- Changed wheel configuration to be NOT universal, as #281 added `configparser` as a dependency for Python 2.7.
- Updated usage documentation.

1.3.2 2.1.0 - October 8th, 2017

New Features

- Public nested classes missing a docstring are now reported as D106 instead of D101 (#198, #261).
- `__init__` methods missing a docstring are now reported as D107 instead of D102 (#273, #277).
- Added support for Python 3.6 (#270).
- Specifying an invalid error code prefix (e.g., `--select=D9`) will print a warning message to `stderr` (#253, #279).
- Configuration files now support multiple-lined entries (#250, #281).
- Improved description of how error selection works in the help section (#231, #283).

Bug Fixes

- Fixed an issue where the `--source` flag would result in improperly spaced output (#256, #257, #260).
- Fixed an issue where if a first word in a docstring had Unicode characters and the docstring was not a unicode string, an exception would be raised (#258, #264).
- Configuration files that were specified by CLI and don't contain a valid section name will now issue a warning to `stderr` (#276, #280).
- Removed D107 from the numpy convention (#288).

1.3.3 2.0.0 - April 18th, 2017

Major Updates

- Support for `numpy` conventions verification has been added (#129, #226).
- Support for Python 2.6 has been dropped (#206, #217).
- Support for PyPy3 has been temporarily dropped, until it will be equivalent to CPython 3.3+ and supported by `pip` (#223).
- Support for the `pep257` console script has been dropped. Only the `pydocstyle` console script should be used (#216, #218).
- Errors are now printed to `stdout` instead of `stderr` (#201, #210).

New Features

- Decorator-based skipping via `--ignore-decorators` has been added (#204).
- Support for using `pycodestyle` style wildcards has been added (#72, #209).
- Superfluous opening quotes are now reported as part of D300 (#166, #225).
- Fixed a false-positive recognition of *D410* and added *D412* (#230, #233).

- Added `--config=<path>` flag to override the normal config file discovery and choose a specific config file (#117, #247).
- Support for specifying error codes with partial prefix has been added, e.g., `--select=D101,D2` (#72, #209).
- All configuration file can now have the `.ini` extension (#237).
- Added better imperative mood checks using third party stemmer (#235, #68).

Bug Fixes

- Made parser more robust to bad source files (#168, #214)
- Modules are now considered private if their name starts with a single underscore. This is a bugfix where “public module” (D100) was reported regardless of module name (#199, #222).
- Removed error when `__all__` is a list (#62, #227).
- Fixed a bug where the `@` sign was used as a matrix multiplication operator in Python 3.5, but was considered a decorator by the parser (#246, #191).

1.3.4 1.1.1 - October 4th, 2016

Bug Fixes

- Fixed an issue where the `flake8-docstrings` failed when accessing some public API from `pydocstyle`.

1.3.5 1.1.0 - September 29th, 2016

Major Updates

- `pydocstyle` is no longer a single file. This might make it difficult for some users to just add it to their project, but the project has reached certain complexity where splitting it into modules was necessary (#200).

New Features

- Added the optional error codes D212 and D213, for checking whether the summary of a multi-line docstring starts at the first line, respectively at the second line (#174).
- Added D404 - First word of the docstring should not be “This”. It is turned off by default (#183).
- Added the ability to ignore specific function and method docstrings with inline comments:
 1. “`# noqa`” skips all checks.
 2. “`# noqa: D102,D203`” can be used to skip specific checks.

Bug Fixes

- Fixed an issue where file paths were printed in lower case (#179, #181).
- The error code D300 is now also being reported if a docstring has uppercase literals (R or U) as prefix (#176).
- Fixed a bug where an `__all__` error was reported when `__all__` was imported from another module with a different name (#182, #187).
- Fixed a bug where `raise X from Y` syntax caused `pydocstyle` to crash (#196, #200).

1.3.6 1.0.0 - January 30th, 2016

Major Updates

- The project was renamed to **pydocstyle** and the new release will be 1.0.0!

New Features

- Added support for Python 3.5 (#145).
- Classes nested inside classes are no longer considered private. Nested classes are considered public if their names are not prepended with an underscore and if their parent class is public, recursively (#13, #146).
- Added the D403 error code - “First word of the first line should be properly capitalized”. This new error is turned on by default (#164, #165, #170).
- Added support for `.pydocstyle` and `as` configuration file name (#140, #173).

Bug Fixes

- Fixed an issue where a `NameError` was raised when parsing complex definitions of `__all__` (#142, #143).
- Fixed a bug where D202 was falsely reported when a function with just a docstring and no content was followed by a comment (#165).
- Fixed wrong `__all__` definition in main module (#150, #156).
- Fixed a bug where an `AssertionError` could occur when parsing `__future__` imports (#154).

1.4 Older Versions

Note: Versions documented below are before renaming the project from **pep257** to **pydocstyle**.

1.4.1 0.7.0 - October 9th, 2015

New Features

- Added the D104 error code - “Missing docstring in public package”. This new error is turned on by default. Missing docstring in `__init__.py` files which previously resulted in D100 errors (“Missing docstring in public module”) will now result in D104 (#105, #127).
- Added the D105 error code - “Missing docstring in magic method”. This new error is turned on by default. Missing docstrings in magic method which previously resulted in D102 error (“Missing docstring in public method”) will now result in D105. Note that exceptions to this rule are variadic magic methods - specifically `__init__`, `__call__` and `__new__`, which will be considered non-magic and missing docstrings in them will result in D102 (#60, #139).
- Support the option to exclude all error codes. Running `pep257` with `--select=` (or `select=` in the configuration file) will exclude all errors which could then be added one by one using `add-select`. Useful for projects new to `pep257` (#132, #135).
- Added check D211: No blank lines allowed before class docstring. This change is a result of a change to the official PEP257 convention. Therefore, D211 will now be checked by default instead of D203, which required a single blank line before a class docstring (#137).
- Configuration files are now handled correctly. The closer a configuration file is to a checked file the more it matters. Configuration files no longer support `explain`, `source`, `debug`, `verbose` or `count` (#133).

Bug Fixes

- On Python 2.x, D302 (“Use u””” for Unicode docstrings”) is not reported if *unicode_literals* is imported from *__future__* (#113, #134).
- Fixed a bug where there was no executable for *pep257* on Windows (#73, #136).

1.4.2 0.6.0 - July 20th, 2015

New Features

- Added support for more flexible error selections using `--ignore`, `--select`, `--convention`, `--add-ignore` and `--add-select` (#96, #123).

Bug Fixes

- Property setter and deleter methods are now treated as private and do not require docstrings separate from the main property method (#69, #107).
- Fixed an issue where *pep257* did not accept docstrings that are both unicode and raw in Python 2.x (#116, #119).
- Fixed an issue where Python 3.x files with Unicode encodings were not read correctly (#118).

1.4.3 0.5.0 - March 14th, 2015

New Features

- Added check D210: No whitespaces allowed surrounding docstring text (#95).
- Added real documentation rendering using Sphinx (#100, #101).

Bug Fixes

- Removed log level configuration from module level (#98).
- D205 used to check that there was *a* blank line between the one line summary and the description. It now checks that there is *exactly* one blank line between them (#79).
- Fixed a bug where `--match-dir` was not properly respected (#108, #109).

1.4.4 0.4.1 - January 10th, 2015

Bug Fixes

- Getting `ImportError` when trying to run *pep257* as the installed script (#92, #93).

1.4.5 0.4.0 - January 4th, 2015

Warning: A fatal bug was discovered in this version (#92). Please use a newer version.

New Features

- Added configuration file support (#58, #87).
- Added a `--count` flag that prints the number of violations found (#86, #89).
- Added support for Python 3.4, PyPy and PyPy3 (#81).

Bug Fixes

- Fixed broken tests (#74).
- Fixed parsing various colon and parenthesis combinations in definitions (#82).
- Allow for greater flexibility in parsing `__all__` (#67).
- Fixed handling of one-liner definitions (#77).

1.4.6 0.3.2 - March 11th, 2014

First documented release!

1.5 License

Copyright (c) 2012 GreenSteam, <<http://greensteam.dk/>>

Copyright (c) 2014-2017 Amir Rachum, <<http://amir.rachum.com/>>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

CHAPTER 2

Credits

pydocstyle is a rename and continuation of pep257, a project created by Vladimir Keleshev.

Maintained by Amir Rachum.