
python-gerritclient

Feb 07, 2019

Contents

1	User Documentation	3
1.1	Gerrit Command Line Utility	3
1.1.1	Gerrit CLI Commands	3

This is a CLI tool and Python API wrapper for [Gerrit Code Review](#).

1.1 Gerrit Command Line Utility

python-gerritclient CLI is a command line utility for managing Gerrit Code Review environment. It allows to perform several types of operations.

For help on a specific **gerrit** command or subcommand, enter:

```
$ gerrit COMMAND [SUBCOMMAND [SUBCOMMAND ...]] --help
```

All **gerrit** commands support several options:

```
Usage: gerrit [--version] [-v | -q] [--log-file LOG_FILE] [-h] [--debug]
```

optional arguments:

- version** Show program's version number and exit.
- v, --verbose** Increase verbosity of output. Can be repeated.
- q, --quiet** Suppress output except warnings and errors.
- log-file LOG_FILE** Specify a file to log output. Disabled by default.
- h, --help** Show help message and exit.
- debug** Show tracebacks on errors.

1.1.1 Gerrit CLI Commands

gerrit account * commands

account create

Creates a new account in Gerrit Code Review.

```
gerrit account create
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [--file FILE]
  account-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

--file <FILE>
File with metadata to be uploaded.

account-identifier
Account identifier.

This command is provided by the python-gerritclient plugin.

account disable

Sets the account state in Gerrit to inactive.

```
gerrit account disable account-identifier
```

account-identifier
Account identifier.

This command is provided by the python-gerritclient plugin.

account email add

Registers a new email address for the user in Gerrit.


```
gerrit account email add
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  -e EMAIL
  [--preferred]
  [--no-confirmation]
  account-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

-e <EMAIL>, **--email** <EMAIL>
Account email.

--preferred
Set email address as preferred.

--no-confirmation
Email address confirmation. Only Gerrit administrators are allowed to add email addresses without confirmation.

account-identifier
Account identifier.

This command is provided by the python-gerritclient plugin.

account email delete

Deletes an email address of an account in Gerrit.

```
gerrit account email delete -e EMAIL account-identifier
```

-e <EMAIL>, **--email** <EMAIL>
Account email.

account-identifier

Account identifier.

This command is provided by the python-gerritclient plugin.

account email set-preferred

Sets an email address as preferred email address for an account.

```
gerrit account email set-preferred account-identifier email
```

account-identifier

Account identifier.

email

Account email.

This command is provided by the python-gerritclient plugin.

account enable

Sets the account state in Gerrit to active.

```
gerrit account enable account-identifier
```

account-identifier

Account identifier.

This command is provided by the python-gerritclient plugin.

account list

Lists all accounts in Gerrit visible to the caller.

```
gerrit account list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
  [--suggest]
  [-l LIMIT]
  [-S SKIP]
  [-a]
  [--all-emails]
  query
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- quote** <QUOTE_MODE>
when to include quotes, defaults to nonnumeric
- sort-column** SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated
- suggest**
Get account suggestions.
- l** <LIMIT>, **--limit** <LIMIT>
Limit the number of accounts to be included in the results.
- S** <SKIP>, **--skip** <SKIP>
Skip the given number of accounts from the beginning of the list.
- a**, **--all**
Includes full name, preferred email, username and avatars for each account.
- all-emails**
Includes all registered emails.
- query**
Query string.

This command is provided by the python-gerritclient plugin.

account membership list

Lists all groups that contain the specified user as a member.

```
gerrit account membership list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
  account-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- quote** <QUOTE_MODE>
when to include quotes, defaults to nonnumeric
- sort-column** SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated
- account-identifier**
Account identifier.

This command is provided by the python-gerritclient plugin.

account name set

Sets the full name of an account in Gerrit Code Review.

```
gerrit account name set account-identifier name
```

account-identifier
Account identifier.

name
Account name.

This command is provided by the python-gerritclient plugin.

account oauth show

Returns a previously obtained OAuth access token.

If there is no token available, or the token has already expired, “404 Not Found” is returned as response. Requests to obtain an access token of another user are rejected with “403 Forbidden”.

```
gerrit account oauth show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  account-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- account-identifier**
Account identifier.

This command is provided by the python-gerritclient plugin.

account password delete

Deletes the HTTP password of an account in Gerrit.

```
gerrit account password delete account-identifier
```

account-identifier
Account identifier.

This command is provided by the python-gerritclient plugin.

account password set

Sets/Generates the HTTP password of an account in Gerrit.

```
gerrit account password set
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  (--generate | -p PASSWORD)
  account-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **-max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- generate**
Generate HTTP password.
- p** <PASSWORD>, **--password** <PASSWORD>
HTTP password.
- account-identifier**
Account identifier.

This command is provided by the python-gerritclient plugin.

account show

Shows information about specific account in Gerrit.

```
gerrit account show
[-f {json,shell,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
[-a]
account-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **-max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

-a, --all
Show more details about account.

account-identifier
Account identifier.

This command is provided by the python-gerritclient plugin.

account ssh-key add

Adds an SSH key for a user in Gerrit.

```
gerrit account ssh-key add
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  (--ssh-key SSH_KEY | --file SSH_KEY_FILE)
  account-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable `CLIFF_FIT_WIDTH=1` to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

--ssh-key <SSH_KEY>
The SSH public key.

--file SSH_KEY_FILE
File with the SSH public key.

account-identifier

Account identifier.

This command is provided by the python-gerritclient plugin.

account ssh-key delete

Deletes an SSH key of a user in Gerrit.

```
gerrit account ssh-key delete
  --sequence-id SEQUENCE_ID
  account-identifier
```

--sequence-id <SEQUENCE_ID>

The sequence number of the SSH key.

account-identifier

Account identifier.

This command is provided by the python-gerritclient plugin.

account ssh-key list

Returns the SSH keys of an account in Gerrit.

```
gerrit account ssh-key list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
  account-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>

the output format, defaults to table

-c COLUMN, **--column** COLUMN

specify the column(s) to include, can be repeated

--max-width <integer>

Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width

Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable `CLIFF_FIT_WIDTH=1` to always enable

--print-empty

Print empty table if there is no data to show.

--noindent

whether to disable indenting the JSON

--quote <QUOTE_MODE>

when to include quotes, defaults to nonnumeric

--sort-column SORT_COLUMN
 specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated

account-identifier
 Account identifier.

This command is provided by the python-gerritclient plugin.

account ssh-key show

Retrieves an SSH key of a user in Gerrit.

```
gerrit account ssh-key show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  -s SEQUENCE_ID
  account-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
 the output format, defaults to table

-c COLUMN, **--column** COLUMN
 specify the column(s) to include, can be repeated

--max-width <integer>
 Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
 Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
 Print empty table if there is no data to show.

--noindent
 whether to disable indenting the JSON

--prefix <PREFIX>
 add a prefix to all variable names

-s <SEQUENCE_ID>, **--sequence-id** <SEQUENCE_ID>
 The sequence number of the SSH key.

account-identifier
 Account identifier.

This command is provided by the python-gerritclient plugin.

account state show

Fetches the state of an account in Gerrit.

```
gerrit account state show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  account-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

account-identifier
Account identifier.

This command is provided by the python-gerritclient plugin.

account status set

Sets the status of an account.

```
gerrit account status set account-identifier status
```

account-identifier
Account identifier.

status
Account status.

This command is provided by the python-gerritclient plugin.

account status show

Retrieves the status of an account.

```
gerrit account status show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  account-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

account-identifier
Account identifier.

This command is provided by the python-gerritclient plugin.

account username set

Sets the username of an account in Gerrit Code Review.

```
gerrit account username set account-identifier username
```

account-identifier
Account identifier.

username
Account username.

This command is provided by the python-gerritclient plugin.

gerrit change * commands

change abandon

Abandons a change.

```
gerrit change abandon
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

change-identifier
Change identifier.

This command is provided by the python-gerritclient plugin.

change assignee delete

Deletes the assignee of a change.

```
gerrit change assignee delete
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- change-identifier**
Change identifier.

This command is provided by the python-gerritclient plugin.

change assignee history show

Retrieve a list of every user ever assigned to a change.

```
gerrit change assignee history show
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
  change-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- quote** <QUOTE_MODE>
when to include quotes, defaults to nonnumeric

--sort-column SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated

change-identifier
Change identifier.

This command is provided by the python-gerritclient plugin.

change assignee set

Sets the assignee of a change.

```
gerrit change assignee set
[-f {json,shell,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
-a ACCOUNT
change-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

-a <ACCOUNT>, **--account** <ACCOUNT>
The ID of one account that should be added as assignee.

change-identifier
Change identifier.

This command is provided by the python-gerritclient plugin.

change assignee show

Retrieves the account of the user assigned to a change.

```

gerrit change assignee show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier

```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

change-identifier
Change identifier.

This command is provided by the python-gerritclient plugin.

change check

Performs consistency checks on the change.

Returns a ChangeInfo entity with the problems field.

```

gerrit change check
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier

```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- change-identifier**
Change identifier.

This command is provided by the python-gerritclient plugin.

change comment list

Lists the published comments of all revisions of the change.

```
gerrit change comment list
[-f {csv,json,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--quote {all,minimal,none,nonnumeric}]
[--sort-column SORT_COLUMN]
[-t {drafts,robotcomments}]
change-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- quote** <QUOTE_MODE>
when to include quotes, defaults to nonnumeric

- sort-column** SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated
- t** <TYPE>, **--type** <TYPE>
The type of comments. Defaults to published.
- change-identifier**
Change identifier.

This command is provided by the python-gerritclient plugin.

change create

Creates a new change.

```
gerrit change create
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  file
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable `CLIFF_FIT_WIDTH=1` to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- file**
File with metadata of a new change.

This command is provided by the python-gerritclient plugin.

change delete

Deletes a change.

```
gerrit change delete change-identifier
```

change-identifier

Change identifier.

This command is provided by the python-gerritclient plugin.

change draft publish

Publishes a draft change.

```
gerrit change draft publish change-identifier
```

change-identifier

Change identifier.

This command is provided by the python-gerritclient plugin.

change fix

Performs consistency checks on the change.

Additionally fixes any problems that can be fixed automatically. The returned field values reflect any fixes. Only the change owner, a project owner, or an administrator may fix changes.

```
gerrit change fix
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [--delete-patchset]
  [--expect-merged-as]
  change-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>

add a prefix to all variable names

--delete-patchset

Delete patch sets from the database if they refer to missing commit options.

--expect-merged-as

Check that the change is merged into the destination branch as this exact SHA-1. If not, insert a new patch set referring to this commit.

change-identifier

Change identifier.

This command is provided by the python-gerritclient plugin.

change included-in show

Retrieves the branches and tags in which a change is included.

```
gerrit change included-in show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>

the output format, defaults to table

-c COLUMN, **--column** COLUMN

specify the column(s) to include, can be repeated

--max-width <integer>

Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width

Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable `CLIFF_FIT_WIDTH=1` to always enable

--print-empty

Print empty table if there is no data to show.

--noindent

whether to disable indenting the JSON

--prefix <PREFIX>

add a prefix to all variable names

change-identifier

Change identifier.

This command is provided by the python-gerritclient plugin.

change index

Adds or updates the change in the secondary index.

```
gerrit change index change-identifier
```

change-identifier

Change identifier.

This command is provided by the python-gerritclient plugin.

change list

Queries changes visible to the caller.

```
gerrit change list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
  [-l LIMIT]
  [-S SKIP]
  [-o OPTION [OPTION ...]]
  query
  [query ...]
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--quote <QUOTE_MODE>
when to include quotes, defaults to nonnumeric

--sort-column SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated

-l <LIMIT>, **--limit** <LIMIT>
Limit the number of changes to be included in the results.

-S <SKIP>, **--skip** <SKIP>
Skip the given number of changes from the beginning of the list.

-o <OPTION>, **--option** <OPTION>
Fetch additional data about changes.

query
Query string.

This command is provided by the python-gerritclient plugin.

change move

Moves a change.

```
gerrit change move
[-f {json,shell,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
-b BRANCH
[-m MESSAGE]
change-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **-max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

-b <BRANCH>, **--branch** <BRANCH>
Destination branch.

-m <MESSAGE>, **--message** <MESSAGE>
A message to be posted in this change's comments.

change-identifier
Change identifier.

This command is provided by the python-gerritclient plugin.

change rebase

Rebases a change.

```
gerrit change rebase
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [-p PARENT]
  change-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

-p <PARENT>, **--parent** <PARENT>
The new parent revision.

change-identifier
Change identifier.

This command is provided by the python-gerritclient plugin.

change restore

Restores a change.

```
gerrit change restore
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- change-identifier**
Change identifier.

This command is provided by the python-gerritclient plugin.

change revert

Reverts a change.

```
gerrit change revert
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [-m MESSAGE]
  change-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.

--noindent

whether to disable indenting the JSON

--prefix <PREFIX>

add a prefix to all variable names

-m <MESSAGE>, **--message** <MESSAGE>

Message to be added as review comment when reverting the change.

change-identifier

Change identifier.

This command is provided by the python-gerritclient plugin.

change show

Retrieves a change.

```
gerrit change show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [-a]
  [-o OPTION [OPTION ...]]
  change-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>

the output format, defaults to table

-c COLUMN, **--column** COLUMN

specify the column(s) to include, can be repeated

--max-width <integer>

Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width

Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable `CLIFF_FIT_WIDTH=1` to always enable

--print-empty

Print empty table if there is no data to show.

--noindent

whether to disable indenting the JSON

--prefix <PREFIX>

add a prefix to all variable names

-a, **--all**

Retrieves a change with labels, detailed labels, detailed accounts, reviewer updates, and messages.

-o <OPTION>, **--option** <OPTION>

Fetch additional data about a change.

change-identifier

Change identifier.

This command is provided by the python-gerritclient plugin.

change submit

Submits a change.

```
gerrit change submit
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [--on-behalf-of ON_BEHALF_OF]
  [--notify {NONE,OWNER,OWNER_REVIEWERS,ALL}]
  change-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

--on-behalf-of <ON_BEHALF_OF>
Submit the change on behalf of the given user.

--notify <NOTIFY>
Notify handling that defines to whom email notifications should be sent after the change is submitted.

change-identifier
Change identifier.

This command is provided by the python-gerritclient plugin.

change topic delete

Deletes the topic of a change.

```
gerrit change topic delete
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  change-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

change-identifier
Change identifier.

This command is provided by the python-gerritclient plugin.

change topic set

Sets the topic of a change.

```
gerrit change topic set
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  -t TOPIC
  change-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- t** <TOPIC>, **--topic** <TOPIC>
Topic of a change.
- change-identifier**
Change identifier.

This command is provided by the python-gerritclient plugin.

change topic show

Retrieves the topic of a change.

```
gerrit change topic show
[-f {json,shell,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
change-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

change-identifier
Change identifier.

This command is provided by the python-gerritclient plugin.

gerrit group * commands

group create

Creates a new group in Gerrit Code Review.

```
gerrit group create
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [--file FILE]
  group-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

--file <FILE>
File with metadata to be uploaded.

group-identifier
Group identifier.

This command is provided by the python-gerritclient plugin.

group description delete

Deletes the description of a specified Gerrit internal group.

```
gerrit group description delete group-identifier
```

group-identifier

Group identifier.

This command is provided by the python-gerritclient plugin.

group description set

Sets the description of a specified Gerrit internal group.

```
gerrit group description set group-identifier description
```

group-identifier

Group identifier.

description

Group description.

This command is provided by the python-gerritclient plugin.

group exclude

Deletes one or several included groups from a Gerrit internal group.

```
gerrit group exclude
  --group group-identifier
  [group-identifier ...]
  group-identifier
```

--group group-identifier

Group(s) identifier(s).

group-identifier

Group identifier.

This command is provided by the python-gerritclient plugin.

group include

Includes one or several groups into a Gerrit internal group.

```
gerrit group include
  --group group-identifier
  [group-identifier ...]
  group-identifier
```

--group group-identifier

Group(s) identifier(s).

group-identifier

Group identifier.

This command is provided by the python-gerritclient plugin.

group list

Lists all groups in Gerrit Code Review.

```
gerrit group list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--quote <QUOTE_MODE>
when to include quotes, defaults to nonnumeric

--sort-column SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated

This command is provided by the python-gerritclient plugin.

group member add

Adds a user or several users as member(s) to a Gerrit internal group.

```
gerrit group member add
  --account account-identifier
  [account-identifier ...]
  group-identifier
```

--account account-identifier
Account(s) identifier(s).

group-identifier
Group identifier.

This command is provided by the python-gerritclient plugin.

group member delete

Removes a user or several users from a Gerrit internal group.

```
gerrit group member delete
  --account account-identifier
  [account-identifier ...]
  group-identifier
```

--account account-identifier
Account(s) identifier(s).

group-identifier
Group identifier.

This command is provided by the python-gerritclient plugin.

group member list

Lists all members of specific group in Gerrit Code Review.

```
gerrit group member list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
  [-a]
  group-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--quote <QUOTE_MODE>
when to include quotes, defaults to nonnumeric

--sort-column SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated

-a, --all
Show members from included groups.

group-identifier
Group identifier.

This command is provided by the python-gerritclient plugin.

group options set

Sets the options of a Gerrit internal group.

```
gerrit group options set
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  (--visible | --no-visible)
  group-identifier
```

-f <FORMATTER>, --format <FORMATTER>
the output format, defaults to table

-c COLUMN, --column COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

--visible
Set group visible to all registered users.

--no-visible
Set group not visible to all registered users.

group-identifier
Group identifier.

This command is provided by the python-gerritclient plugin.

group owner set

Sets the owner group of a Gerrit internal group.

```
gerrit group owner set group-identifier owner
```

group-identifier

Group identifier.

owner

Group owner.

This command is provided by the python-gerritclient plugin.

group rename

Renames a Gerrit internal group.

```
gerrit group rename group-identifier new_name
```

group-identifier

Group identifier.

new_name

New group name.

This command is provided by the python-gerritclient plugin.

group show

Shows information about specific group in Gerrit Code Review.

```
gerrit group show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [-a]
  group-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **-max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty

Print empty table if there is no data to show.

--noindent

whether to disable indenting the JSON

--prefix <PREFIX>

add a prefix to all variable names

-a, --all

Show more details about group.

group-identifier

Group identifier.

This command is provided by the python-gerritclient plugin.

gerrit plugin * commands

plugin disable

Disables a plugin on the Gerrit server.

```
gerrit plugin disable plugin-identifier
```

plugin-identifier

Plugin identifier.

This command is provided by the python-gerritclient plugin.

plugin enable

Enables a plugin on the Gerrit server.

```
gerrit plugin enable plugin-identifier
```

plugin-identifier

Plugin identifier.

This command is provided by the python-gerritclient plugin.

plugin install

Installs a new plugin on the Gerrit server.

```
gerrit plugin install
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  (--url URL | --file FILE)
  plugin-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- url** <URL>
URL to the plugin jar.
- file** <FILE>
File path to the plugin jar.
- plugin-identifier**
Plugin identifier.

This command is provided by the python-gerritclient plugin.

plugin list

Lists all installed plugins in Gerrit Code Review.

```
gerrit plugin list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
  [-a]
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width

Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable `CLIFF_FIT_WIDTH=1` to always enable

--print-empty

Print empty table if there is no data to show.

--noindent

whether to disable indenting the JSON

--quote <QUOTE_MODE>

when to include quotes, defaults to nonnumeric

--sort-column SORT_COLUMN

specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated

-a, --all

Show all plugins (including disabled).

This command is provided by the python-gerritclient plugin.

plugin reload

Reloads a plugin on the Gerrit server.

```
gerrit plugin reload
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  plugin-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>

the output format, defaults to table

-c COLUMN, **--column** COLUMN

specify the column(s) to include, can be repeated

--max-width <integer>

Maximum display width, <1 to disable. You can also use the `CLIFF_MAX_TERM_WIDTH` environment variable, but the parameter takes precedence.

--fit-width

Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable `CLIFF_FIT_WIDTH=1` to always enable

--print-empty

Print empty table if there is no data to show.

--noindent

whether to disable indenting the JSON

--prefix <PREFIX>

add a prefix to all variable names

plugin-identifier

Plugin identifier.

This command is provided by the python-gerritclient plugin.

plugin show

Shows information about specific plugin in Gerrit Code Review.

```
gerrit plugin show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  plugin-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

plugin-identifier

Plugin identifier.

This command is provided by the python-gerritclient plugin.

gerrit project * commands**project branch create**

Creates a new branch.

```
gerrit project branch create
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
```

(continues on next page)

```
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
-b BRANCH
[-r REVISION]
project-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

-b <BRANCH>, **--branch** <BRANCH>
The name of a branch or HEAD. The prefix refs/heads/ can be omitted.

-r <REVISION>, **--revision** <REVISION>
The base revision of the new branch. If not set, HEAD will be used as base revision.

project-identifier
Project identifier.

This command is provided by the python-gerritclient plugin.

project branch delete

Deletes one or more branches.

```
gerrit project branch delete -b BRANCH [BRANCH ...] name
```

-b <BRANCH>, **--branch** <BRANCH>
The branches that should be deleted.

name
Name of the project.

This command is provided by the python-gerritclient plugin.

project branch list

Lists the branches of a project.

```
gerrit project branch list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
  name
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--quote <QUOTE_MODE>
when to include quotes, defaults to nonnumeric

--sort-column SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated

name
Name of the project.

This command is provided by the python-gerritclient plugin.

project branch reflog show

Gets the reflog of a certain branch.

The caller must be project owner.

```
gerrit project branch reflog show
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
```

(continues on next page)

```

[--print-empty]
[--noindent]
[--quote {all,minimal,none,nonnumeric}]
[--sort-column SORT_COLUMN]
-b BRANCH
name

```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- quote** <QUOTE_MODE>
when to include quotes, defaults to nonnumeric
- sort-column** SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated
- b** <BRANCH>, **--branch** <BRANCH>
The name of a branch or HEAD. The prefix refs/heads/ can be omitted.
- name**
Name of the project.

This command is provided by the python-gerritclient plugin.

project branch show

Retrieves a branch of a project.

```

gerrit project branch show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  -b BRANCH
  project-identifier

```


- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- b** <BRANCH>, **--branch** <BRANCH>
The name of a branch or HEAD. The prefix refs/heads/ can be omitted.
- project-identifier**
Project identifier.

This command is provided by the python-gerritclient plugin.

project child list

Lists the direct child projects of a project.

Child projects that are not visible to the calling user are ignored and are not resolved further.

```
gerrit project child list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
  [-r]
  name
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width

Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable `CLIFF_FIT_WIDTH=1` to always enable

--print-empty

Print empty table if there is no data to show.

--noindent

whether to disable indenting the JSON

--quote <QUOTE_MODE>

when to include quotes, defaults to nonnumeric

--sort-column SORT_COLUMN

specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated

-r, --recursively

Resolve the child projects of a project recursively.

name

Name of the project.

This command is provided by the python-gerritclient plugin.

project commit file-content show

Gets the content of a file from a certain commit.

```
gerrit project commit file-content show
  --commit COMMIT
  --file-id FILE_ID
  name
```

--commit <COMMIT>

Commit ID.

--file-id <FILE_ID>

The path to the file.

name

Name of the project.

This command is provided by the python-gerritclient plugin.

project commit included-in

Retrieves the branches and tags in which a change is included.

```
gerrit project commit included-in
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
```

(continues on next page)

(continued from previous page)

```
--commit COMMIT
project-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- commit** <COMMIT>
Commit ID.
- project-identifier**
Project identifier.

This command is provided by the python-gerritclient plugin.

project commit show

Retrieves a commit of a project.

The commit must be visible to the caller.

```
gerrit project commit show
[-f {json,shell,table,value,yaml}]
[-c COLUMN]
[--max-width <integer>]
[--fit-width]
[--print-empty]
[--noindent]
[--prefix PREFIX]
--commit COMMIT
project-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

--commit <COMMIT>
Commit ID.

project-identifier
Project identifier.

This command is provided by the python-gerritclient plugin.

project configuration download

Gets some configuration information about a project.

Note that this config info is not simply the contents of `project.config`; it generally contains fields that may have been inherited from parent projects.

```
gerrit project configuration download
  [-f {json,yaml}]
  [-d DIRECTORY]
  name
```

-f <FORMAT>, **--format** <FORMAT>
Format of serialization.

-d <DIRECTORY>, **--directory** <DIRECTORY>
Destination directory. Defaults to the current directory.

name
Name of the project.

This command is provided by the python-gerritclient plugin.

project configuration set

Sets the configuration of a project.

```
gerrit project configuration set --file FILE name
```

--file <FILE>
File with metadata to be uploaded.

name
Name of the project.

This command is provided by the python-gerritclient plugin.

project create

Creates a new project in Gerrit Code Review.

```
gerrit project create
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [--file FILE]
  project-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

--file <FILE>
File with metadata to be uploaded.

project-identifier
Project identifier.

This command is provided by the python-gerritclient plugin.

project delete

Deletes specified project from Gerrit Code Review.

Note, 'deleteproject' plugin must be installed.

```
gerrit project delete [-f] [--preserve-git-repository] name
```

-f, **--force**
Delete project even if it has open changes.

python-gerritclient

--preserve-git-repository

Do not delete git repository directory.

name

Name of the project.

This command is provided by the python-gerritclient plugin.

project description set

Retrieves the description of a project.

```
gerrit project description set [-d DESCRIPTION] [-m MESSAGE] name
```

-d <DESCRIPTION>, **--description** <DESCRIPTION>

The project description. The project description will be deleted if not set.

-m <MESSAGE>, **--message** <MESSAGE>

Message that should be used to commit the change of the project description in the project.config file to the refs/meta/config branch.

name

Name of the project.

This command is provided by the python-gerritclient plugin.

project description show

Retrieves the description of a project.

```
gerrit project description show name
```

name

Name of the project.

This command is provided by the python-gerritclient plugin.

project gc-run

Runs the Git garbage collection for the repository of a project.

In case of asynchronous execution the `-show-progress` option is ignored.

```
gerrit project gc-run [--show-progress] [--aggressive] name
```

--show-progress

Show progress information.

--aggressive

Do aggressive garbage collection.

name

Name of the project.

This command is provided by the python-gerritclient plugin.

project head set

Sets HEAD for a project.

```
gerrit project head set -b BRANCH name
```

-b <BRANCH>, **--branch** <BRANCH>
The name of the branch to which HEAD should point.

name
Name of the project.

This command is provided by the python-gerritclient plugin.

project head show

Retrieves for a project the name of the branch to which HEAD points.

```
gerrit project head show name
```

name
Name of the project.

This command is provided by the python-gerritclient plugin.

project list

Lists all projects accessible by the caller.

```
gerrit project list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
  [-a]
  [-d]
  [-b BRANCHES [BRANCHES ...]]
  [-l LIMIT]
  [-S SKIP]
  [--type {code,permissions,all}]
  [-p PREFIX | -m MATCH | -r REGEX]
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

- fit-width**
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable `CLIFF_FIT_WIDTH=1` to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- quote** <QUOTE_MODE>
when to include quotes, defaults to nonnumeric
- sort-column** SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated
- a, --all**
Include hidden projects in the results.
- d, --description**
Include project description in the results.
- b** <BRANCHES>, **--branches** <BRANCHES>
Limit the results to the projects having the specified branches and include the sha1 of the branches in the results.
- l** <LIMIT>, **--limit** <LIMIT>
Limit the number of projects to be included in the results.
- S** <SKIP>, **--skip** <SKIP>
Skip the given number of projects from the beginning of the list.
- type** <TYPE>
Display only projects of the specified type.
- p** <PREFIX>, **--prefix** <PREFIX>
Limit the results to those projects that start with the specified prefix.
- m** <MATCH>, **--match** <MATCH>
Limit the results to those projects that match the specified substring.
- r** <REGEX>, **--regex** <REGEX>
Limit the results to those projects that match the specified regex.

This command is provided by the python-gerritclient plugin.

project parent set

Sets the parent project for a project.

```
gerrit project parent set -p PARENT [-m MESSAGE] name
```

- p** <PARENT>, **--parent** <PARENT>
The name of the parent project.
- m** <MESSAGE>, **--message** <MESSAGE>
Message that should be used to commit the change of the project parent in the project.config file to the refs/meta/config branch.

name
Name of the project.

This command is provided by the python-gerritclient plugin.

project parent show

Retrieves the name of a project's parent project.

```
gerrit project parent show name
```

name

Name of the project.

This command is provided by the python-gerritclient plugin.

project repo-statistics show

Return statistics for the repository of a project.

```
gerrit project repo-statistics show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  project-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

project-identifier
Project identifier.

This command is provided by the python-gerritclient plugin.

project show

Shows information about specific project in Gerrit Code Review.

```
gerrit project show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  project-identifier
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

project-identifier
Project identifier.

This command is provided by the python-gerritclient plugin.

project tag create

Creates a new tag on the project.

If a message is provided in the input, the tag is created as an annotated tag with the current user as tagger. Signed tags are not supported.

```
gerrit project tag create
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  -t TAG
```

(continues on next page)

(continued from previous page)

```
[-r REVISION]
[-m MESSAGE]
project-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- t** <TAG>, **--tag** <TAG>
The name of the tag. The leading refs/tags/ is optional.
- r** <REVISION>, **--revision** <REVISION>
The revision to which the tag should point. If not specified, the project's HEAD will be used.
- m** <MESSAGE>, **--message** <MESSAGE>
The tag message. When set, the tag will be created as an annotated tag.
- project-identifier**
Project identifier.

This command is provided by the python-gerritclient plugin.

project tag delete

Deletes one or more tags of the project.

```
gerrit project tag delete -t TAG [TAG ...] name
```

- t** <TAG>, **--tag** <TAG>
The tags to be deleted.

name
Name of the project.

This command is provided by the python-gerritclient plugin.

project tag list

Lists the tags of a project.

Only includes tags under the refs/tags/ namespace.

```
gerrit project tag list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
  [-l LIMIT]
  [-S SKIP]
  [-m MATCH | -r REGEX]
  name
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--quote <QUOTE_MODE>
when to include quotes, defaults to nonnumeric

--sort-column SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated

-l <LIMIT>, **--limit** <LIMIT>
Limit the number of tags to be included in the results.

-S <SKIP>, **--skip** <SKIP>
Skip the given number of tags from the beginning of the list.

-m <MATCH>, **--match** <MATCH>
Limit the results to those tags that match the specified substring. The match is case insensitive.

-r <REGEX>, **--regex** <REGEX>
Limit the results to those tags that match the specified regex. The match is case sensitive.

name
Name of the project.

This command is provided by the python-gerritclient plugin.

project tag show

Retrieves a tag of a project.

```

gerrit project tag show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  project-identifier
  tag

```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

project-identifier
Project identifier.

tag
Name of the tag.

This command is provided by the python-gerritclient plugin.

gerrit server * commands

server cache flush

Flushes a cache.

```

gerrit server cache flush (-a | -n NAME [NAME ...])

```

-a, **--all**
All available caches.

-n <NAME>, **--name** <NAME>
Caches names.

This command is provided by the python-gerritclient plugin.

server cache list

Show the cache names as a list.

```
gerrit server cache list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--quote <QUOTE_MODE>
when to include quotes, defaults to nonnumeric

--sort-column SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated

This command is provided by the python-gerritclient plugin.

server cache show

Retrieves information about a cache.

```
gerrit server cache show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
```

(continues on next page)

(continued from previous page)

```
[--prefix PREFIX]
name
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- name**
Cache name.

This command is provided by the python-gerritclient plugin.

server capabilities download

Downloads a list of the capabilities available in the system.

```
gerrit server capabilities download [-f {json,yaml}] [-d DIRECTORY]
```

- f** <FORMAT>, **--format** <FORMAT>
Format of serialization.
- d** <DIRECTORY>, **--directory** <DIRECTORY>
Destination directory. Defaults to the current directory.

This command is provided by the python-gerritclient plugin.

server configuration download

Downloads the information about the Gerrit server configuration.

```
gerrit server configuration download [-f {json,yaml}] [-d DIRECTORY]
```

- f** <FORMAT>, **--format** <FORMAT>
Format of serialization.
- d** <DIRECTORY>, **--directory** <DIRECTORY>
Destination directory. Defaults to the current directory.

This command is provided by the python-gerritclient plugin.

server state show

Retrieves a summary of the current server state.

```
gerrit server state show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--prefix PREFIX]
  [--jvm]
  [--gc]
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--prefix <PREFIX>
add a prefix to all variable names

--jvm
Includes a JVM summary.

--gc
Requests a Java garbage collection before computing the information about the Java memory heap.

This command is provided by the python-gerritclient plugin.

server task delete

Kills a task from the background work queue that the Gerrit daemon is currently performing, or will perform in the near future.

```
gerrit server task delete task-identifier
```

task-identifier
The ID of the task (hex string).

This command is provided by the python-gerritclient plugin.

server task list

Lists the tasks from the background work queues that the Gerrit daemons is currently performing, or will perform in the near future.

```
gerrit server task list
  [-f {csv,json,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
  [--quote {all,minimal,none,nonnumeric}]
  [--sort-column SORT_COLUMN]
```

-f <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table

-c COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated

--max-width <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.

--fit-width
Fit the table to the display width. Implied if **--max-width** greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable

--print-empty
Print empty table if there is no data to show.

--noindent
whether to disable indenting the JSON

--quote <QUOTE_MODE>
when to include quotes, defaults to nonnumeric

--sort-column SORT_COLUMN
specify the column(s) to sort the data (columns specified first have a priority, non-existing columns are ignored), can be repeated

This command is provided by the python-gerritclient plugin.

server task show

Retrieves a task from the background work queue that the Gerrit daemon is currently performing, or will perform in the near future.

```
gerrit server task show
  [-f {json,shell,table,value,yaml}]
  [-c COLUMN]
  [--max-width <integer>]
  [--fit-width]
  [--print-empty]
  [--noindent]
```

(continues on next page)

(continued from previous page)

```
[--prefix PREFIX]
task-identifier
```

- f** <FORMATTER>, **--format** <FORMATTER>
the output format, defaults to table
- c** COLUMN, **--column** COLUMN
specify the column(s) to include, can be repeated
- max-width** <integer>
Maximum display width, <1 to disable. You can also use the CLIFF_MAX_TERM_WIDTH environment variable, but the parameter takes precedence.
- fit-width**
Fit the table to the display width. Implied if `--max-width` greater than 0. Set the environment variable CLIFF_FIT_WIDTH=1 to always enable
- print-empty**
Print empty table if there is no data to show.
- noindent**
whether to disable indenting the JSON
- prefix** <PREFIX>
add a prefix to all variable names
- task-identifier**
The ID of the task (hex string).

This command is provided by the python-gerritclient plugin.

server version

Returns the version of the Gerrit server.

```
gerrit server version
```

This command is provided by the python-gerritclient plugin.

Symbols

- account account-identifier
 - gerrit-group-member-add command line option, 34
 - gerrit-group-member-delete command line option, 35
- aggressive
 - gerrit-project-gc-run command line option, 50
- all-emails
 - gerrit-account-list command line option, 7
- commit <COMMIT>
 - gerrit-project-commit-file-content-show command line option, 46
 - gerrit-project-commit-included-in command line option, 47
 - gerrit-project-commit-show command line option, 48
- delete-patchset
 - gerrit-change-fix command line option, 23
- expect-merged-as
 - gerrit-change-fix command line option, 23
- file SSH_KEY_FILE
 - gerrit-account-ssh-key-add command line option, 11
- file <FILE>
 - gerrit-account-create command line option, 4
 - gerrit-group-create command line option, 32
 - gerrit-plugin-install command line option, 39
 - gerrit-project-configuration-set command line option, 48
 - gerrit-project-create command line option, 49
- file-id <FILE_ID>
 - gerrit-project-commit-file-content-show command line option, 46
- fit-width
 - gerrit-account-create command line option, 4
 - gerrit-account-email-add command line option, 5
 - gerrit-account-list command line option, 7
 - gerrit-account-membership-list command line option, 8
 - gerrit-account-oauth-show command line option, 9
 - gerrit-account-password-set command line option, 10
 - gerrit-account-show command line option, 10
 - gerrit-account-ssh-key-add command line option, 11
 - gerrit-account-ssh-key-list command line option, 12
 - gerrit-account-ssh-key-show command line option, 13
 - gerrit-account-state-show command line option, 14
 - gerrit-account-status-show command line option, 15
 - gerrit-change-abandon command line option, 16
 - gerrit-change-assignee-delete command line option, 17
 - gerrit-change-assignee-history-show command line option, 17
 - gerrit-change-assignee-set command line option, 18
 - gerrit-change-assignee-show command line option, 19
 - gerrit-change-check command line option, 20
 - gerrit-change-comment-list command line option, 20
 - gerrit-change-create command line option, 21
 - gerrit-change-fix command line option, 22
 - gerrit-change-included-in-show command line option, 23
 - gerrit-change-list command line option, 24
 - gerrit-change-move command line option, 25
 - gerrit-change-rebase command line option, 26
 - gerrit-change-restore command line option, 27
 - gerrit-change-revert command line option, 27
 - gerrit-change-show command line option, 28
 - gerrit-change-submit command line option, 29
 - gerrit-change-topic-delete command line option, 30
 - gerrit-change-topic-set command line option, 31
 - gerrit-change-topic-show command line option, 31
 - gerrit-group-create command line option, 32
 - gerrit-group-list command line option, 34
 - gerrit-group-member-list command line option, 35
 - gerrit-group-options-set command line option, 36
 - gerrit-group-show command line option, 37
 - gerrit-plugin-install command line option, 39
 - gerrit-plugin-list command line option, 39

- gerrit-plugin-reload command line option, 40
- gerrit-plugin-show command line option, 41
- gerrit-project-branch-create command line option, 42
- gerrit-project-branch-list command line option, 43
- gerrit-project-branch-reflog-show command line option, 44
- gerrit-project-branch-show command line option, 45
- gerrit-project-child-list command line option, 45
- gerrit-project-commit-included-in command line option, 47
- gerrit-project-commit-show command line option, 48
- gerrit-project-create command line option, 49
- gerrit-project-list command line option, 51
- gerrit-project-repo-statistics-show command line option, 53
- gerrit-project-show command line option, 54
- gerrit-project-tag-create command line option, 55
- gerrit-project-tag-list command line option, 56
- gerrit-project-tag-show command line option, 57
- gerrit-server-cache-list command line option, 58
- gerrit-server-cache-show command line option, 59
- gerrit-server-state-show command line option, 60
- gerrit-server-task-list command line option, 61
- gerrit-server-task-show command line option, 62
- gc
 - gerrit-server-state-show command line option, 60
- generate
 - gerrit-account-password-set command line option, 10
- group group-identifier
 - gerrit-group-exclude command line option, 33
 - gerrit-group-include command line option, 33
- jvm
 - gerrit-server-state-show command line option, 60
- max-width <integer>
 - gerrit-account-create command line option, 4
 - gerrit-account-email-add command line option, 5
 - gerrit-account-list command line option, 6
 - gerrit-account-membership-list command line option, 8
 - gerrit-account-oauth-show command line option, 9
 - gerrit-account-password-set command line option, 10
 - gerrit-account-show command line option, 10
 - gerrit-account-ssh-key-add command line option, 11
 - gerrit-account-ssh-key-list command line option, 12
 - gerrit-account-ssh-key-show command line option, 13
 - gerrit-account-state-show command line option, 14
 - gerrit-account-status-show command line option, 15
 - gerrit-change-abandon command line option, 16
 - gerrit-change-assignee-delete command line option, 16
 - gerrit-change-assignee-history-show command line option, 17
 - gerrit-change-assignee-set command line option, 18
 - gerrit-change-assignee-show command line option, 19
 - gerrit-change-check command line option, 19
 - gerrit-change-comment-list command line option, 20
 - gerrit-change-create command line option, 21
 - gerrit-change-fix command line option, 22
 - gerrit-change-included-in-show command line option, 23
 - gerrit-change-list command line option, 24
 - gerrit-change-move command line option, 25
 - gerrit-change-rebase command line option, 26
 - gerrit-change-restore command line option, 27
 - gerrit-change-revert command line option, 27
 - gerrit-change-show command line option, 28
 - gerrit-change-submit command line option, 29
 - gerrit-change-topic-delete command line option, 30
 - gerrit-change-topic-set command line option, 30
 - gerrit-change-topic-show command line option, 31
 - gerrit-group-create command line option, 32
 - gerrit-group-list command line option, 34
 - gerrit-group-member-list command line option, 35
 - gerrit-group-options-set command line option, 36
 - gerrit-group-show command line option, 37
 - gerrit-plugin-install command line option, 39
 - gerrit-plugin-list command line option, 39
 - gerrit-plugin-reload command line option, 40
 - gerrit-plugin-show command line option, 41
 - gerrit-project-branch-create command line option, 42
 - gerrit-project-branch-list command line option, 43
 - gerrit-project-branch-reflog-show command line option, 44
 - gerrit-project-branch-show command line option, 45
 - gerrit-project-child-list command line option, 45
 - gerrit-project-commit-included-in command line option, 47
 - gerrit-project-commit-show command line option, 47
 - gerrit-project-create command line option, 49
 - gerrit-project-list command line option, 51
 - gerrit-project-repo-statistics-show command line option, 53
 - gerrit-project-show command line option, 54
 - gerrit-project-tag-create command line option, 55
 - gerrit-project-tag-list command line option, 56
 - gerrit-project-tag-show command line option, 57
 - gerrit-server-cache-list command line option, 58
 - gerrit-server-cache-show command line option, 59
 - gerrit-server-state-show command line option, 60

- gerrit-server-task-list command line option, 61
- gerrit-server-task-show command line option, 62
- no-confirmation
 - gerrit-account-email-add command line option, 5
- no-visible
 - gerrit-group-options-set command line option, 36
- noindent
 - gerrit-account-create command line option, 4
 - gerrit-account-email-add command line option, 5
 - gerrit-account-list command line option, 7
 - gerrit-account-membership-list command line option, 8
 - gerrit-account-oauth-show command line option, 9
 - gerrit-account-password-set command line option, 10
 - gerrit-account-show command line option, 11
 - gerrit-account-ssh-key-add command line option, 11
 - gerrit-account-ssh-key-list command line option, 12
 - gerrit-account-ssh-key-show command line option, 13
 - gerrit-account-state-show command line option, 14
 - gerrit-account-status-show command line option, 15
 - gerrit-change-abandon command line option, 16
 - gerrit-change-assignee-delete command line option, 17
 - gerrit-change-assignee-history-show command line option, 17
 - gerrit-change-assignee-set command line option, 18
 - gerrit-change-assignee-show command line option, 19
 - gerrit-change-check command line option, 20
 - gerrit-change-comment-list command line option, 20
 - gerrit-change-create command line option, 21
 - gerrit-change-fix command line option, 22
 - gerrit-change-included-in-show command line option, 23
 - gerrit-change-list command line option, 24
 - gerrit-change-move command line option, 25
 - gerrit-change-rebase command line option, 26
 - gerrit-change-restore command line option, 27
 - gerrit-change-revert command line option, 27
 - gerrit-change-show command line option, 28
 - gerrit-change-submit command line option, 29
 - gerrit-change-topic-delete command line option, 30
 - gerrit-change-topic-set command line option, 31
 - gerrit-change-topic-show command line option, 31
 - gerrit-group-create command line option, 32
 - gerrit-group-list command line option, 34
 - gerrit-group-member-list command line option, 35
 - gerrit-group-options-set command line option, 36
 - gerrit-group-show command line option, 38
 - gerrit-plugin-install command line option, 39
 - gerrit-plugin-list command line option, 40
 - gerrit-plugin-reload command line option, 40
 - gerrit-plugin-show command line option, 41
 - gerrit-project-branch-create command line option, 42
 - gerrit-project-branch-list command line option, 43
 - gerrit-project-branch-reflog-show command line option, 44
 - gerrit-project-branch-show command line option, 45
 - gerrit-project-child-list command line option, 46
 - gerrit-project-commit-included-in command line option, 47
 - gerrit-project-commit-show command line option, 48
 - gerrit-project-create command line option, 49
 - gerrit-project-list command line option, 52
 - gerrit-project-repo-statistics-show command line option, 53
 - gerrit-project-show command line option, 54
 - gerrit-project-tag-create command line option, 55
 - gerrit-project-tag-list command line option, 56
 - gerrit-project-tag-show command line option, 57
 - gerrit-server-cache-list command line option, 58
 - gerrit-server-cache-show command line option, 59
 - gerrit-server-state-show command line option, 60
 - gerrit-server-task-list command line option, 61
 - gerrit-server-task-show command line option, 62
 - notify <NOTIFY>
 - gerrit-change-submit command line option, 29
 - on-behalf-of <ON_BEHALF_OF>
 - gerrit-change-submit command line option, 29
 - preferred
 - gerrit-account-email-add command line option, 5
 - prefix <PREFIX>
 - gerrit-account-create command line option, 4
 - gerrit-account-email-add command line option, 5
 - gerrit-account-oauth-show command line option, 9
 - gerrit-account-password-set command line option, 10
 - gerrit-account-show command line option, 11
 - gerrit-account-ssh-key-add command line option, 11
 - gerrit-account-ssh-key-show command line option, 13
 - gerrit-account-state-show command line option, 14
 - gerrit-account-status-show command line option, 15
 - gerrit-change-abandon command line option, 16
 - gerrit-change-assignee-delete command line option, 17
 - gerrit-change-assignee-set command line option, 18
 - gerrit-change-assignee-show command line option, 19
 - gerrit-change-check command line option, 20
 - gerrit-change-create command line option, 21
 - gerrit-change-fix command line option, 22
 - gerrit-change-included-in-show command line option, 23

- gerrit-change-move command line option, 25
- gerrit-change-rebase command line option, 26
- gerrit-change-restore command line option, 27
- gerrit-change-revert command line option, 28
- gerrit-change-show command line option, 28
- gerrit-change-submit command line option, 29
- gerrit-change-topic-delete command line option, 30
- gerrit-change-topic-set command line option, 31
- gerrit-change-topic-show command line option, 31
- gerrit-group-create command line option, 32
- gerrit-group-options-set command line option, 36
- gerrit-group-show command line option, 38
- gerrit-plugin-install command line option, 39
- gerrit-plugin-reload command line option, 40
- gerrit-plugin-show command line option, 41
- gerrit-project-branch-create command line option, 42
- gerrit-project-branch-show command line option, 45
- gerrit-project-commit-included-in command line option, 47
- gerrit-project-commit-show command line option, 48
- gerrit-project-create command line option, 49
- gerrit-project-repo-statistics-show command line option, 53
- gerrit-project-show command line option, 54
- gerrit-project-tag-create command line option, 55
- gerrit-project-tag-show command line option, 57
- gerrit-server-cache-show command line option, 59
- gerrit-server-state-show command line option, 60
- gerrit-server-task-show command line option, 62
- preserve-git-repository
 - gerrit-project-delete command line option, 49
- print-empty
 - gerrit-account-create command line option, 4
 - gerrit-account-email-add command line option, 5
 - gerrit-account-list command line option, 7
 - gerrit-account-membership-list command line option, 8
 - gerrit-account-oauth-show command line option, 9
 - gerrit-account-password-set command line option, 10
 - gerrit-account-show command line option, 10
 - gerrit-account-ssh-key-add command line option, 11
 - gerrit-account-ssh-key-list command line option, 12
 - gerrit-account-ssh-key-show command line option, 13
 - gerrit-account-state-show command line option, 14
 - gerrit-account-status-show command line option, 15
 - gerrit-change-abandon command line option, 16
 - gerrit-change-assignee-delete command line option, 17
 - gerrit-change-assignee-history-show command line option, 17
 - gerrit-change-assignee-set command line option, 18
 - gerrit-change-assignee-show command line option, 19
 - gerrit-change-check command line option, 20
 - gerrit-change-comment-list command line option, 20
 - gerrit-change-create command line option, 21
 - gerrit-change-fix command line option, 22
 - gerrit-change-included-in-show command line option, 23
 - gerrit-change-list command line option, 24
 - gerrit-change-move command line option, 25
 - gerrit-change-rebase command line option, 26
 - gerrit-change-restore command line option, 27
 - gerrit-change-revert command line option, 27
 - gerrit-change-show command line option, 28
 - gerrit-change-submit command line option, 29
 - gerrit-change-topic-delete command line option, 30
 - gerrit-change-topic-set command line option, 31
 - gerrit-change-topic-show command line option, 31
 - gerrit-group-create command line option, 32
 - gerrit-group-list command line option, 34
 - gerrit-group-member-list command line option, 35
 - gerrit-group-options-set command line option, 36
 - gerrit-group-show command line option, 37
 - gerrit-plugin-install command line option, 39
 - gerrit-plugin-list command line option, 40
 - gerrit-plugin-reload command line option, 40
 - gerrit-plugin-show command line option, 41
 - gerrit-project-branch-create command line option, 42
 - gerrit-project-branch-list command line option, 43
 - gerrit-project-branch-reflog-show command line option, 44
 - gerrit-project-branch-show command line option, 45
 - gerrit-project-child-list command line option, 46
 - gerrit-project-commit-included-in command line option, 47
 - gerrit-project-commit-show command line option, 48
 - gerrit-project-create command line option, 49
 - gerrit-project-list command line option, 52
 - gerrit-project-repo-statistics-show command line option, 53
 - gerrit-project-show command line option, 54
 - gerrit-project-tag-create command line option, 55
 - gerrit-project-tag-list command line option, 56
 - gerrit-project-tag-show command line option, 57
 - gerrit-server-cache-list command line option, 58
 - gerrit-server-cache-show command line option, 59
 - gerrit-server-state-show command line option, 60
 - gerrit-server-task-list command line option, 61
 - gerrit-server-task-show command line option, 62
- quote <QUOTE_MODE>
 - gerrit-account-list command line option, 7

- gerrit-account-membership-list command line option, 8
- gerrit-account-ssh-key-list command line option, 12
- gerrit-change-assignee-history-show command line option, 17
- gerrit-change-comment-list command line option, 20
- gerrit-change-list command line option, 24
- gerrit-group-list command line option, 34
- gerrit-group-member-list command line option, 35
- gerrit-plugin-list command line option, 40
- gerrit-project-branch-list command line option, 43
- gerrit-project-branch-reflog-show command line option, 44
- gerrit-project-child-list command line option, 46
- gerrit-project-list command line option, 52
- gerrit-project-tag-list command line option, 56
- gerrit-server-cache-list command line option, 58
- gerrit-server-task-list command line option, 61
- sequence-id <SEQUENCE_ID>
 - gerrit-account-ssh-key-delete command line option, 12
- show-progress
 - gerrit-project-gc-run command line option, 50
- sort-column SORT_COLUMN
 - gerrit-account-list command line option, 7
 - gerrit-account-membership-list command line option, 8
 - gerrit-account-ssh-key-list command line option, 12
 - gerrit-change-assignee-history-show command line option, 17
 - gerrit-change-comment-list command line option, 20
 - gerrit-change-list command line option, 24
 - gerrit-group-list command line option, 34
 - gerrit-group-member-list command line option, 35
 - gerrit-plugin-list command line option, 40
 - gerrit-project-branch-list command line option, 43
 - gerrit-project-branch-reflog-show command line option, 44
 - gerrit-project-child-list command line option, 46
 - gerrit-project-list command line option, 52
 - gerrit-project-tag-list command line option, 56
 - gerrit-server-cache-list command line option, 58
 - gerrit-server-task-list command line option, 61
- ssh-key <SSH_KEY>
 - gerrit-account-ssh-key-add command line option, 11
- suggest
 - gerrit-account-list command line option, 7
- type <TYPE>
 - gerrit-project-list command line option, 52
- url <URL>
 - gerrit-plugin-install command line option, 39
- visible
 - gerrit-group-options-set command line option, 36
- S <SKIP>, -skip <SKIP>
 - gerrit-account-list command line option, 7
 - gerrit-change-list command line option, 24
 - gerrit-project-list command line option, 52
 - gerrit-project-tag-list command line option, 56
- a <ACCOUNT>, -account <ACCOUNT>
 - gerrit-change-assignee-set command line option, 18
- a, -all
 - gerrit-account-list command line option, 7
 - gerrit-account-show command line option, 11
 - gerrit-change-show command line option, 28
 - gerrit-group-member-list command line option, 35
 - gerrit-group-show command line option, 38
 - gerrit-plugin-list command line option, 40
 - gerrit-project-list command line option, 52
 - gerrit-server-cache-flush command line option, 57
- b <BRANCHES>, -branches <BRANCHES>
 - gerrit-project-list command line option, 52
- b <BRANCH>, -branch <BRANCH>
 - gerrit-change-move command line option, 25
 - gerrit-project-branch-create command line option, 42
 - gerrit-project-branch-delete command line option, 42
 - gerrit-project-branch-reflog-show command line option, 44
 - gerrit-project-branch-show command line option, 45
 - gerrit-project-head-set command line option, 51
- c COLUMN, -column COLUMN
 - gerrit-account-create command line option, 4
 - gerrit-account-email-add command line option, 5
 - gerrit-account-list command line option, 6
 - gerrit-account-membership-list command line option, 7
 - gerrit-account-oauth-show command line option, 9
 - gerrit-account-password-set command line option, 9
 - gerrit-account-show command line option, 10
 - gerrit-account-ssh-key-add command line option, 11
 - gerrit-account-ssh-key-list command line option, 12
 - gerrit-account-ssh-key-show command line option, 13
 - gerrit-account-state-show command line option, 14
 - gerrit-account-status-show command line option, 15
 - gerrit-change-abandon command line option, 16
 - gerrit-change-assignee-delete command line option, 16
 - gerrit-change-assignee-history-show command line option, 17
 - gerrit-change-assignee-set command line option, 18
 - gerrit-change-assignee-show command line option, 19
 - gerrit-change-check command line option, 19
 - gerrit-change-comment-list command line option, 20
 - gerrit-change-create command line option, 21
 - gerrit-change-fix command line option, 22

- gerrit-change-included-in-show command line option, 23
- gerrit-change-list command line option, 24
- gerrit-change-move command line option, 25
- gerrit-change-rebase command line option, 26
- gerrit-change-restore command line option, 27
- gerrit-change-revert command line option, 27
- gerrit-change-show command line option, 28
- gerrit-change-submit command line option, 29
- gerrit-change-topic-delete command line option, 30
- gerrit-change-topic-set command line option, 30
- gerrit-change-topic-show command line option, 31
- gerrit-group-create command line option, 32
- gerrit-group-list command line option, 34
- gerrit-group-member-list command line option, 35
- gerrit-group-options-set command line option, 36
- gerrit-group-show command line option, 37
- gerrit-plugin-install command line option, 39
- gerrit-plugin-list command line option, 39
- gerrit-plugin-reload command line option, 40
- gerrit-plugin-show command line option, 41
- gerrit-project-branch-create command line option, 42
- gerrit-project-branch-list command line option, 43
- gerrit-project-branch-reflog-show command line option, 44
- gerrit-project-branch-show command line option, 45
- gerrit-project-child-list command line option, 45
- gerrit-project-commit-included-in command line option, 47
- gerrit-project-commit-show command line option, 47
- gerrit-project-create command line option, 49
- gerrit-project-list command line option, 51
- gerrit-project-repo-statistics-show command line option, 53
- gerrit-project-show command line option, 54
- gerrit-project-tag-create command line option, 55
- gerrit-project-tag-list command line option, 56
- gerrit-project-tag-show command line option, 57
- gerrit-server-cache-list command line option, 58
- gerrit-server-cache-show command line option, 59
- gerrit-server-state-show command line option, 60
- gerrit-server-task-list command line option, 61
- gerrit-server-task-show command line option, 62
- d <DESCRIPTION>, --description <DESCRIPTION>
 - gerrit-project-description-set command line option, 50
- d <DIRECTORY>, --directory <DIRECTORY>
 - gerrit-project-configuration-download command line option, 48
 - gerrit-server-capabilities-download command line option, 59
 - gerrit-server-configuration-download command line option, 59
- d, --description
 - gerrit-project-list command line option, 52
- e <EMAIL>, --email <EMAIL>
 - gerrit-account-email-add command line option, 5
 - gerrit-account-email-delete command line option, 5
- f <FORMATTER>, --format <FORMATTER>
 - gerrit-account-create command line option, 4
 - gerrit-account-email-add command line option, 5
 - gerrit-account-list command line option, 6
 - gerrit-account-membership-list command line option, 7
 - gerrit-account-oauth-show command line option, 8
 - gerrit-account-password-set command line option, 9
 - gerrit-account-show command line option, 10
 - gerrit-account-ssh-key-add command line option, 11
 - gerrit-account-ssh-key-list command line option, 12
 - gerrit-account-ssh-key-show command line option, 13
 - gerrit-account-state-show command line option, 14
 - gerrit-account-status-show command line option, 15
 - gerrit-change-abandon command line option, 16
 - gerrit-change-assignee-delete command line option, 16
 - gerrit-change-assignee-history-show command line option, 17
 - gerrit-change-assignee-set command line option, 18
 - gerrit-change-assignee-show command line option, 19
 - gerrit-change-check command line option, 19
 - gerrit-change-comment-list command line option, 20
 - gerrit-change-create command line option, 21
 - gerrit-change-fix command line option, 22
 - gerrit-change-included-in-show command line option, 23
 - gerrit-change-list command line option, 24
 - gerrit-change-move command line option, 25
 - gerrit-change-rebase command line option, 26
 - gerrit-change-restore command line option, 26
 - gerrit-change-revert command line option, 27
 - gerrit-change-show command line option, 28
 - gerrit-change-submit command line option, 29
 - gerrit-change-topic-delete command line option, 30
 - gerrit-change-topic-set command line option, 30
 - gerrit-change-topic-show command line option, 31
 - gerrit-group-create command line option, 32
 - gerrit-group-list command line option, 34
 - gerrit-group-member-list command line option, 35
 - gerrit-group-options-set command line option, 36
 - gerrit-group-show command line option, 37
 - gerrit-plugin-install command line option, 38
 - gerrit-plugin-list command line option, 39
 - gerrit-plugin-reload command line option, 40

- gerrit-plugin-show command line option, 41
 - gerrit-project-branch-create command line option, 42
 - gerrit-project-branch-list command line option, 43
 - gerrit-project-branch-reflog-show command line option, 44
 - gerrit-project-branch-show command line option, 44
 - gerrit-project-child-list command line option, 45
 - gerrit-project-commit-included-in command line option, 47
 - gerrit-project-commit-show command line option, 47
 - gerrit-project-create command line option, 49
 - gerrit-project-list command line option, 51
 - gerrit-project-repo-statistics-show command line option, 53
 - gerrit-project-show command line option, 54
 - gerrit-project-tag-create command line option, 55
 - gerrit-project-tag-list command line option, 56
 - gerrit-project-tag-show command line option, 57
 - gerrit-server-cache-list command line option, 58
 - gerrit-server-cache-show command line option, 59
 - gerrit-server-state-show command line option, 60
 - gerrit-server-task-list command line option, 61
 - gerrit-server-task-show command line option, 62
 - f <FORMAT>, --format <FORMAT>
 - gerrit-project-configuration-download command line option, 48
 - gerrit-server-capabilities-download command line option, 59
 - gerrit-server-configuration-download command line option, 59
 - f, --force
 - gerrit-project-delete command line option, 49
 - l <LIMIT>, --limit <LIMIT>
 - gerrit-account-list command line option, 7
 - gerrit-change-list command line option, 24
 - gerrit-project-list command line option, 52
 - gerrit-project-tag-list command line option, 56
 - m <MATCH>, --match <MATCH>
 - gerrit-project-list command line option, 52
 - gerrit-project-tag-list command line option, 56
 - m <MESSAGE>, --message <MESSAGE>
 - gerrit-change-move command line option, 25
 - gerrit-change-revert command line option, 28
 - gerrit-project-description-set command line option, 50
 - gerrit-project-parent-set command line option, 52
 - gerrit-project-tag-create command line option, 55
 - n <NAME>, --name <NAME>
 - gerrit-server-cache-flush command line option, 57
 - o <OPTION>, --option <OPTION>
 - gerrit-change-list command line option, 25
 - gerrit-change-show command line option, 28
 - p <PARENT>, --parent <PARENT>
 - gerrit-change-rebase command line option, 26
 - gerrit-project-parent-set command line option, 52
 - p <PASSWORD>, --password <PASSWORD>
 - gerrit-account-password-set command line option, 10
 - p <PREFIX>, --prefix <PREFIX>
 - gerrit-project-list command line option, 52
 - r <REGEX>, --regex <REGEX>
 - gerrit-project-list command line option, 52
 - gerrit-project-tag-list command line option, 56
 - r <REVISION>, --revision <REVISION>
 - gerrit-project-branch-create command line option, 42
 - gerrit-project-tag-create command line option, 55
 - r, --recursively
 - gerrit-project-child-list command line option, 46
 - s <SEQUENCE_ID>, --sequence-id <SEQUENCE_ID>
 - gerrit-account-ssh-key-show command line option, 13
 - t <TAG>, --tag <TAG>
 - gerrit-project-tag-create command line option, 55
 - gerrit-project-tag-delete command line option, 55
 - t <TOPIC>, --topic <TOPIC>
 - gerrit-change-topic-set command line option, 31
 - t <TYPE>, --type <TYPE>
 - gerrit-change-comment-list command line option, 21
- ## A
- account-identifier
 - gerrit-account-create command line option, 4
 - gerrit-account-disable command line option, 4
 - gerrit-account-email-add command line option, 5
 - gerrit-account-email-delete command line option, 5
 - gerrit-account-email-set-preferred command line option, 6
 - gerrit-account-enable command line option, 6
 - gerrit-account-membership-list command line option, 8
 - gerrit-account-name-set command line option, 8
 - gerrit-account-oauth-show command line option, 9
 - gerrit-account-password-delete command line option, 9
 - gerrit-account-password-set command line option, 10
 - gerrit-account-show command line option, 11
 - gerrit-account-ssh-key-add command line option, 11
 - gerrit-account-ssh-key-delete command line option, 12
 - gerrit-account-ssh-key-list command line option, 13
 - gerrit-account-ssh-key-show command line option, 13
 - gerrit-account-state-show command line option, 14
 - gerrit-account-status-set command line option, 14

gerrit-account-status-show command line option, 15
 gerrit-account-username-set command line option, 15

C

change-identifier

gerrit-change-abandon command line option, 16
 gerrit-change-assignee-delete command line option, 17
 gerrit-change-assignee-history-show command line option, 18
 gerrit-change-assignee-set command line option, 18
 gerrit-change-assignee-show command line option, 19
 gerrit-change-check command line option, 20
 gerrit-change-comment-list command line option, 21
 gerrit-change-delete command line option, 22
 gerrit-change-draft-publish command line option, 22
 gerrit-change-fix command line option, 23
 gerrit-change-included-in-show command line option, 23
 gerrit-change-index command line option, 24
 gerrit-change-move command line option, 25
 gerrit-change-rebase command line option, 26
 gerrit-change-restore command line option, 27
 gerrit-change-revert command line option, 28
 gerrit-change-show command line option, 28
 gerrit-change-submit command line option, 29
 gerrit-change-topic-delete command line option, 30
 gerrit-change-topic-set command line option, 31
 gerrit-change-topic-show command line option, 32

D

description

gerrit-group-description-set command line option, 33

E

email

gerrit-account-email-set-preferred command line option, 6

F

file

gerrit-change-create command line option, 21

G

gerrit-account-create command line option

-file <FILE>, 4
 -fit-width, 4
 -max-width <integer>, 4
 -noindent, 4
 -prefix <PREFIX>, 4
 -print-empty, 4

-c COLUMN, -column COLUMN, 4
 -f <FORMATTER>, -format <FORMATTER>, 4
 account-identifier, 4

gerrit-account-disable command line option
 account-identifier, 4

gerrit-account-email-add command line option

-fit-width, 5
 -max-width <integer>, 5
 -no-confirmation, 5
 -noindent, 5
 -preferred, 5
 -prefix <PREFIX>, 5
 -print-empty, 5
 -c COLUMN, -column COLUMN, 5
 -e <EMAIL>, -email <EMAIL>, 5
 -f <FORMATTER>, -format <FORMATTER>, 5
 account-identifier, 5

gerrit-account-email-delete command line option

-e <EMAIL>, -email <EMAIL>, 5
 account-identifier, 5

gerrit-account-email-set-preferred command line option

account-identifier, 6

email, 6

gerrit-account-enable command line option

account-identifier, 6

gerrit-account-list command line option

-all-emails, 7
 -fit-width, 7
 -max-width <integer>, 6
 -noindent, 7
 -print-empty, 7
 -quote <QUOTE_MODE>, 7
 -sort-column SORT_COLUMN, 7
 -suggest, 7
 -S <SKIP>, -skip <SKIP>, 7
 -a, -all, 7
 -c COLUMN, -column COLUMN, 6
 -f <FORMATTER>, -format <FORMATTER>, 6
 -l <LIMIT>, -limit <LIMIT>, 7
 query, 7

gerrit-account-membership-list command line option

-fit-width, 8
 -max-width <integer>, 8
 -noindent, 8
 -print-empty, 8
 -quote <QUOTE_MODE>, 8
 -sort-column SORT_COLUMN, 8
 -c COLUMN, -column COLUMN, 7
 -f <FORMATTER>, -format <FORMATTER>, 7
 account-identifier, 8

gerrit-account-name-set command line option

account-identifier, 8
 name, 8

gerrit-account-oauth-show command line option

- fit-width, 9
- max-width <integer>, 9
- noindent, 9
- prefix <PREFIX>, 9
- print-empty, 9
- c COLUMN, -column COLUMN, 9
- f <FORMATTER>, -format <FORMATTER>, 8
- account-identifier, 9
- gerrit-account-password-delete command line option
 - account-identifier, 9
- gerrit-account-password-set command line option
 - fit-width, 10
 - generate, 10
 - max-width <integer>, 10
 - noindent, 10
 - prefix <PREFIX>, 10
 - print-empty, 10
 - c COLUMN, -column COLUMN, 9
 - f <FORMATTER>, -format <FORMATTER>, 9
 - p <PASSWORD>, -password <PASSWORD>, 10
 - account-identifier, 10
- gerrit-account-show command line option
 - fit-width, 10
 - max-width <integer>, 10
 - noindent, 11
 - prefix <PREFIX>, 11
 - print-empty, 10
 - a, -all, 11
 - c COLUMN, -column COLUMN, 10
 - f <FORMATTER>, -format <FORMATTER>, 10
 - account-identifier, 11
- gerrit-account-ssh-key-add command line option
 - file SSH_KEY_FILE, 11
 - fit-width, 11
 - max-width <integer>, 11
 - noindent, 11
 - prefix <PREFIX>, 11
 - print-empty, 11
 - ssh-key <SSH_KEY>, 11
 - c COLUMN, -column COLUMN, 11
 - f <FORMATTER>, -format <FORMATTER>, 11
 - account-identifier, 11
- gerrit-account-ssh-key-delete command line option
 - sequence-id <SEQUENCE_ID>, 12
 - account-identifier, 12
- gerrit-account-ssh-key-list command line option
 - fit-width, 12
 - max-width <integer>, 12
 - noindent, 12
 - print-empty, 12
 - quote <QUOTE_MODE>, 12
 - sort-column SORT_COLUMN, 12
 - c COLUMN, -column COLUMN, 12
 - f <FORMATTER>, -format <FORMATTER>, 12
 - account-identifier, 13
- gerrit-account-ssh-key-show command line option
 - fit-width, 13
 - max-width <integer>, 13
 - noindent, 13
 - prefix <PREFIX>, 13
 - print-empty, 13
 - c COLUMN, -column COLUMN, 13
 - f <FORMATTER>, -format <FORMATTER>, 13
 - s <SEQUENCE_ID>, -sequence-id <SEQUENCE_ID>, 13
 - account-identifier, 13
- gerrit-account-state-show command line option
 - fit-width, 14
 - max-width <integer>, 14
 - noindent, 14
 - prefix <PREFIX>, 14
 - print-empty, 14
 - c COLUMN, -column COLUMN, 14
 - f <FORMATTER>, -format <FORMATTER>, 14
 - account-identifier, 14
- gerrit-account-status-set command line option
 - account-identifier, 14
 - status, 14
- gerrit-account-status-show command line option
 - fit-width, 15
 - max-width <integer>, 15
 - noindent, 15
 - prefix <PREFIX>, 15
 - print-empty, 15
 - c COLUMN, -column COLUMN, 15
 - f <FORMATTER>, -format <FORMATTER>, 15
 - account-identifier, 15
- gerrit-account-username-set command line option
 - account-identifier, 15
 - username, 15
- gerrit-change-abandon command line option
 - fit-width, 16
 - max-width <integer>, 16
 - noindent, 16
 - prefix <PREFIX>, 16
 - print-empty, 16
 - c COLUMN, -column COLUMN, 16
 - f <FORMATTER>, -format <FORMATTER>, 16
 - change-identifier, 16
- gerrit-change-assignee-delete command line option
 - fit-width, 17
 - max-width <integer>, 16
 - noindent, 17
 - prefix <PREFIX>, 17
 - print-empty, 17
 - c COLUMN, -column COLUMN, 16
 - f <FORMATTER>, -format <FORMATTER>, 16
 - change-identifier, 17

- gerrit-change-assignee-history-show command line option
- fit-width, 17
 - max-width <integer>, 17
 - noindent, 17
 - print-empty, 17
 - quote <QUOTE_MODE>, 17
 - sort-column SORT_COLUMN, 17
 - c COLUMN, -column COLUMN, 17
 - f <FORMATTER>, -format <FORMATTER>, 17
 - change-identifier, 18
- gerrit-change-assignee-set command line option
- fit-width, 18
 - max-width <integer>, 18
 - noindent, 18
 - prefix <PREFIX>, 18
 - print-empty, 18
 - a <ACCOUNT>, -account <ACCOUNT>, 18
 - c COLUMN, -column COLUMN, 18
 - f <FORMATTER>, -format <FORMATTER>, 18
 - change-identifier, 18
- gerrit-change-assignee-show command line option
- fit-width, 19
 - max-width <integer>, 19
 - noindent, 19
 - prefix <PREFIX>, 19
 - print-empty, 19
 - c COLUMN, -column COLUMN, 19
 - f <FORMATTER>, -format <FORMATTER>, 19
 - change-identifier, 19
- gerrit-change-check command line option
- fit-width, 20
 - max-width <integer>, 19
 - noindent, 20
 - prefix <PREFIX>, 20
 - print-empty, 20
 - c COLUMN, -column COLUMN, 19
 - f <FORMATTER>, -format <FORMATTER>, 19
 - change-identifier, 20
- gerrit-change-comment-list command line option
- fit-width, 20
 - max-width <integer>, 20
 - noindent, 20
 - print-empty, 20
 - quote <QUOTE_MODE>, 20
 - sort-column SORT_COLUMN, 20
 - c COLUMN, -column COLUMN, 20
 - f <FORMATTER>, -format <FORMATTER>, 20
 - t <TYPE>, -type <TYPE>, 21
 - change-identifier, 21
- gerrit-change-create command line option
- fit-width, 21
 - max-width <integer>, 21
 - noindent, 21
 - prefix <PREFIX>, 21
 - print-empty, 21
 - c COLUMN, -column COLUMN, 21
 - f <FORMATTER>, -format <FORMATTER>, 21
 - file, 21
- gerrit-change-delete command line option
- change-identifier, 22
- gerrit-change-draft-publish command line option
- change-identifier, 22
- gerrit-change-fix command line option
- delete-patchset, 23
 - expect-merged-as, 23
 - fit-width, 22
 - max-width <integer>, 22
 - noindent, 22
 - prefix <PREFIX>, 22
 - print-empty, 22
 - c COLUMN, -column COLUMN, 22
 - f <FORMATTER>, -format <FORMATTER>, 22
 - change-identifier, 23
- gerrit-change-included-in-show command line option
- fit-width, 23
 - max-width <integer>, 23
 - noindent, 23
 - prefix <PREFIX>, 23
 - print-empty, 23
 - c COLUMN, -column COLUMN, 23
 - f <FORMATTER>, -format <FORMATTER>, 23
 - change-identifier, 23
- gerrit-change-index command line option
- change-identifier, 24
- gerrit-change-list command line option
- fit-width, 24
 - max-width <integer>, 24
 - noindent, 24
 - print-empty, 24
 - quote <QUOTE_MODE>, 24
 - sort-column SORT_COLUMN, 24
 - S <SKIP>, -skip <SKIP>, 24
 - c COLUMN, -column COLUMN, 24
 - f <FORMATTER>, -format <FORMATTER>, 24
 - l <LIMIT>, -limit <LIMIT>, 24
 - o <OPTION>, -option <OPTION>, 25
 - query, 25
- gerrit-change-move command line option
- fit-width, 25
 - max-width <integer>, 25
 - noindent, 25
 - prefix <PREFIX>, 25
 - print-empty, 25
 - b <BRANCH>, -branch <BRANCH>, 25
 - c COLUMN, -column COLUMN, 25
 - f <FORMATTER>, -format <FORMATTER>, 25
 - m <MESSAGE>, -message <MESSAGE>, 25

- change-identifier, 25
- gerrit-change-rebase command line option
 - fit-width, 26
 - max-width <integer>, 26
 - noindent, 26
 - prefix <PREFIX>, 26
 - print-empty, 26
 - c COLUMN, -column COLUMN, 26
 - f <FORMATTER>, -format <FORMATTER>, 26
 - p <PARENT>, -parent <PARENT>, 26
 - change-identifier, 26
- gerrit-change-restore command line option
 - fit-width, 27
 - max-width <integer>, 27
 - noindent, 27
 - prefix <PREFIX>, 27
 - print-empty, 27
 - c COLUMN, -column COLUMN, 27
 - f <FORMATTER>, -format <FORMATTER>, 26
 - change-identifier, 27
- gerrit-change-revert command line option
 - fit-width, 27
 - max-width <integer>, 27
 - noindent, 27
 - prefix <PREFIX>, 28
 - print-empty, 27
 - c COLUMN, -column COLUMN, 27
 - f <FORMATTER>, -format <FORMATTER>, 27
 - m <MESSAGE>, -message <MESSAGE>, 28
 - change-identifier, 28
- gerrit-change-show command line option
 - fit-width, 28
 - max-width <integer>, 28
 - noindent, 28
 - prefix <PREFIX>, 28
 - print-empty, 28
 - a, -all, 28
 - c COLUMN, -column COLUMN, 28
 - f <FORMATTER>, -format <FORMATTER>, 28
 - o <OPTION>, -option <OPTION>, 28
 - change-identifier, 28
- gerrit-change-submit command line option
 - fit-width, 29
 - max-width <integer>, 29
 - noindent, 29
 - notify <NOTIFY>, 29
 - on-behalf-of <ON_BEHALF_OF>, 29
 - prefix <PREFIX>, 29
 - print-empty, 29
 - c COLUMN, -column COLUMN, 29
 - f <FORMATTER>, -format <FORMATTER>, 29
 - change-identifier, 29
- gerrit-change-topic-delete command line option
 - fit-width, 30
 - max-width <integer>, 30
 - noindent, 30
 - prefix <PREFIX>, 30
 - print-empty, 30
 - c COLUMN, -column COLUMN, 30
 - f <FORMATTER>, -format <FORMATTER>, 30
 - change-identifier, 30
- gerrit-change-topic-set command line option
 - fit-width, 31
 - max-width <integer>, 30
 - noindent, 31
 - prefix <PREFIX>, 31
 - print-empty, 31
 - c COLUMN, -column COLUMN, 30
 - f <FORMATTER>, -format <FORMATTER>, 30
 - t <TOPIC>, -topic <TOPIC>, 31
 - change-identifier, 31
- gerrit-change-topic-show command line option
 - fit-width, 31
 - max-width <integer>, 31
 - noindent, 31
 - prefix <PREFIX>, 31
 - print-empty, 31
 - c COLUMN, -column COLUMN, 31
 - f <FORMATTER>, -format <FORMATTER>, 31
 - change-identifier, 32
- gerrit-group-create command line option
 - file <FILE>, 32
 - fit-width, 32
 - max-width <integer>, 32
 - noindent, 32
 - prefix <PREFIX>, 32
 - print-empty, 32
 - c COLUMN, -column COLUMN, 32
 - f <FORMATTER>, -format <FORMATTER>, 32
 - group-identifier, 32
- gerrit-group-description-delete command line option
 - group-identifier, 33
- gerrit-group-description-set command line option
 - description, 33
 - group-identifier, 33
- gerrit-group-exclude command line option
 - group group-identifier, 33
 - group-identifier, 33
- gerrit-group-include command line option
 - group group-identifier, 33
 - group-identifier, 33
- gerrit-group-list command line option
 - fit-width, 34
 - max-width <integer>, 34
 - noindent, 34
 - print-empty, 34
 - quote <QUOTE_MODE>, 34
 - sort-column SORT_COLUMN, 34

- c COLUMN, --column COLUMN, 34
- f <FORMATTER>, --format <FORMATTER>, 34
- gerrit-group-member-add command line option
 - account account-identifier, 34
 - group-identifier, 34
- gerrit-group-member-delete command line option
 - account account-identifier, 35
 - group-identifier, 35
- gerrit-group-member-list command line option
 - fit-width, 35
 - max-width <integer>, 35
 - noindent, 35
 - print-empty, 35
 - quote <QUOTE_MODE>, 35
 - sort-column SORT_COLUMN, 35
 - a, --all, 35
 - c COLUMN, --column COLUMN, 35
 - f <FORMATTER>, --format <FORMATTER>, 35
 - group-identifier, 36
- gerrit-group-options-set command line option
 - fit-width, 36
 - max-width <integer>, 36
 - no-visible, 36
 - noindent, 36
 - prefix <PREFIX>, 36
 - print-empty, 36
 - visible, 36
 - c COLUMN, --column COLUMN, 36
 - f <FORMATTER>, --format <FORMATTER>, 36
 - group-identifier, 36
- gerrit-group-owner-set command line option
 - group-identifier, 37
 - owner, 37
- gerrit-group-rename command line option
 - group-identifier, 37
 - new_name, 37
- gerrit-group-show command line option
 - fit-width, 37
 - max-width <integer>, 37
 - noindent, 38
 - prefix <PREFIX>, 38
 - print-empty, 37
 - a, --all, 38
 - c COLUMN, --column COLUMN, 37
 - f <FORMATTER>, --format <FORMATTER>, 37
 - group-identifier, 38
- gerrit-plugin-disable command line option
 - plugin-identifier, 38
- gerrit-plugin-enable command line option
 - plugin-identifier, 38
- gerrit-plugin-install command line option
 - file <FILE>, 39
 - fit-width, 39
 - max-width <integer>, 39
 - noindent, 39
 - prefix <PREFIX>, 39
 - print-empty, 39
 - url <URL>, 39
 - c COLUMN, --column COLUMN, 39
 - f <FORMATTER>, --format <FORMATTER>, 38
 - plugin-identifier, 39
- gerrit-plugin-list command line option
 - fit-width, 39
 - max-width <integer>, 39
 - noindent, 40
 - print-empty, 40
 - quote <QUOTE_MODE>, 40
 - sort-column SORT_COLUMN, 40
 - a, --all, 40
 - c COLUMN, --column COLUMN, 39
 - f <FORMATTER>, --format <FORMATTER>, 39
- gerrit-plugin-reload command line option
 - fit-width, 40
 - max-width <integer>, 40
 - noindent, 40
 - prefix <PREFIX>, 40
 - print-empty, 40
 - c COLUMN, --column COLUMN, 40
 - f <FORMATTER>, --format <FORMATTER>, 40
 - plugin-identifier, 40
- gerrit-plugin-show command line option
 - fit-width, 41
 - max-width <integer>, 41
 - noindent, 41
 - prefix <PREFIX>, 41
 - print-empty, 41
 - c COLUMN, --column COLUMN, 41
 - f <FORMATTER>, --format <FORMATTER>, 41
 - plugin-identifier, 41
- gerrit-project-branch-create command line option
 - fit-width, 42
 - max-width <integer>, 42
 - noindent, 42
 - prefix <PREFIX>, 42
 - print-empty, 42
 - b <BRANCH>, --branch <BRANCH>, 42
 - c COLUMN, --column COLUMN, 42
 - f <FORMATTER>, --format <FORMATTER>, 42
 - r <REVISION>, --revision <REVISION>, 42
 - project-identifier, 42
- gerrit-project-branch-delete command line option
 - b <BRANCH>, --branch <BRANCH>, 42
 - name, 42
- gerrit-project-branch-list command line option
 - fit-width, 43
 - max-width <integer>, 43
 - noindent, 43
 - print-empty, 43

- quote <QUOTE_MODE>, 43
- sort-column SORT_COLUMN, 43
- c COLUMN, -column COLUMN, 43
- f <FORMATTER>, -format <FORMATTER>, 43
- name, 43
- gerrit-project-branch-reflog-show command line option
 - fit-width, 44
 - max-width <integer>, 44
 - noindent, 44
 - print-empty, 44
 - quote <QUOTE_MODE>, 44
 - sort-column SORT_COLUMN, 44
 - b <BRANCH>, -branch <BRANCH>, 44
 - c COLUMN, -column COLUMN, 44
 - f <FORMATTER>, -format <FORMATTER>, 44
 - name, 44
- gerrit-project-branch-show command line option
 - fit-width, 45
 - max-width <integer>, 45
 - noindent, 45
 - prefix <PREFIX>, 45
 - print-empty, 45
 - b <BRANCH>, -branch <BRANCH>, 45
 - c COLUMN, -column COLUMN, 45
 - f <FORMATTER>, -format <FORMATTER>, 44
 - project-identifier, 45
- gerrit-project-child-list command line option
 - fit-width, 45
 - max-width <integer>, 45
 - noindent, 46
 - print-empty, 46
 - quote <QUOTE_MODE>, 46
 - sort-column SORT_COLUMN, 46
 - c COLUMN, -column COLUMN, 45
 - f <FORMATTER>, -format <FORMATTER>, 45
 - r, -recursively, 46
 - name, 46
- gerrit-project-commit-file-content-show command line option
 - commit <COMMIT>, 46
 - file-id <FILE_ID>, 46
 - name, 46
- gerrit-project-commit-included-in command line option
 - commit <COMMIT>, 47
 - fit-width, 47
 - max-width <integer>, 47
 - noindent, 47
 - prefix <PREFIX>, 47
 - print-empty, 47
 - c COLUMN, -column COLUMN, 47
 - f <FORMATTER>, -format <FORMATTER>, 47
 - project-identifier, 47
- gerrit-project-commit-show command line option
 - commit <COMMIT>, 48
 - fit-width, 48
 - max-width <integer>, 47
 - noindent, 48
 - prefix <PREFIX>, 48
 - print-empty, 48
 - c COLUMN, -column COLUMN, 47
 - f <FORMATTER>, -format <FORMATTER>, 47
 - project-identifier, 48
- gerrit-project-configuration-download command line option
 - d <DIRECTORY>, -directory <DIRECTORY>, 48
 - f <FORMAT>, -format <FORMAT>, 48
 - name, 48
- gerrit-project-configuration-set command line option
 - file <FILE>, 48
 - name, 48
- gerrit-project-create command line option
 - file <FILE>, 49
 - fit-width, 49
 - max-width <integer>, 49
 - noindent, 49
 - prefix <PREFIX>, 49
 - print-empty, 49
 - c COLUMN, -column COLUMN, 49
 - f <FORMATTER>, -format <FORMATTER>, 49
 - project-identifier, 49
- gerrit-project-delete command line option
 - preserve-git-repository, 49
 - f, -force, 49
 - name, 50
- gerrit-project-description-set command line option
 - d <DESCRIPTION>, -description <DESCRIPTION>, 50
 - m <MESSAGE>, -message <MESSAGE>, 50
 - name, 50
- gerrit-project-description-show command line option
 - name, 50
- gerrit-project-gc-run command line option
 - aggressive, 50
 - show-progress, 50
 - name, 50
- gerrit-project-head-set command line option
 - b <BRANCH>, -branch <BRANCH>, 51
 - name, 51
- gerrit-project-head-show command line option
 - name, 51
- gerrit-project-list command line option
 - fit-width, 51
 - max-width <integer>, 51
 - noindent, 52
 - print-empty, 52
 - quote <QUOTE_MODE>, 52
 - sort-column SORT_COLUMN, 52
 - type <TYPE>, 52

- S <SKIP>, --skip <SKIP>, 52
- a, --all, 52
- b <BRANCHES>, --branches <BRANCHES>, 52
- c COLUMN, --column COLUMN, 51
- d, --description, 52
- f <FORMATTER>, --format <FORMATTER>, 51
- l <LIMIT>, --limit <LIMIT>, 52
- m <MATCH>, --match <MATCH>, 52
- p <PREFIX>, --prefix <PREFIX>, 52
- r <REGEX>, --regex <REGEX>, 52
- gerrit-project-parent-set command line option
 - m <MESSAGE>, --message <MESSAGE>, 52
 - p <PARENT>, --parent <PARENT>, 52
 - name, 52
- gerrit-project-parent-show command line option
 - name, 53
- gerrit-project-repo-statistics-show command line option
 - fit-width, 53
 - max-width <integer>, 53
 - noindent, 53
 - prefix <PREFIX>, 53
 - print-empty, 53
 - c COLUMN, --column COLUMN, 53
 - f <FORMATTER>, --format <FORMATTER>, 53
 - project-identifier, 53
- gerrit-project-show command line option
 - fit-width, 54
 - max-width <integer>, 54
 - noindent, 54
 - prefix <PREFIX>, 54
 - print-empty, 54
 - c COLUMN, --column COLUMN, 54
 - f <FORMATTER>, --format <FORMATTER>, 54
 - project-identifier, 54
- gerrit-project-tag-create command line option
 - fit-width, 55
 - max-width <integer>, 55
 - noindent, 55
 - prefix <PREFIX>, 55
 - print-empty, 55
 - c COLUMN, --column COLUMN, 55
 - f <FORMATTER>, --format <FORMATTER>, 55
 - m <MESSAGE>, --message <MESSAGE>, 55
 - r <REVISION>, --revision <REVISION>, 55
 - t <TAG>, --tag <TAG>, 55
 - project-identifier, 55
- gerrit-project-tag-delete command line option
 - t <TAG>, --tag <TAG>, 55
 - name, 55
- gerrit-project-tag-list command line option
 - fit-width, 56
 - max-width <integer>, 56
 - noindent, 56
 - print-empty, 56
 - quote <QUOTE_MODE>, 56
 - sort-column SORT_COLUMN, 56
 - S <SKIP>, --skip <SKIP>, 56
 - c COLUMN, --column COLUMN, 56
 - f <FORMATTER>, --format <FORMATTER>, 56
 - l <LIMIT>, --limit <LIMIT>, 56
 - m <MATCH>, --match <MATCH>, 56
 - r <REGEX>, --regex <REGEX>, 56
 - name, 56
- gerrit-project-tag-show command line option
 - fit-width, 57
 - max-width <integer>, 57
 - noindent, 57
 - prefix <PREFIX>, 57
 - print-empty, 57
 - c COLUMN, --column COLUMN, 57
 - f <FORMATTER>, --format <FORMATTER>, 57
 - project-identifier, 57
 - tag, 57
- gerrit-server-cache-flush command line option
 - a, --all, 57
 - n <NAME>, --name <NAME>, 57
- gerrit-server-cache-list command line option
 - fit-width, 58
 - max-width <integer>, 58
 - noindent, 58
 - print-empty, 58
 - quote <QUOTE_MODE>, 58
 - sort-column SORT_COLUMN, 58
 - c COLUMN, --column COLUMN, 58
 - f <FORMATTER>, --format <FORMATTER>, 58
- gerrit-server-cache-show command line option
 - fit-width, 59
 - max-width <integer>, 59
 - noindent, 59
 - prefix <PREFIX>, 59
 - print-empty, 59
 - c COLUMN, --column COLUMN, 59
 - f <FORMATTER>, --format <FORMATTER>, 59
 - name, 59
- gerrit-server-capabilities-download command line option
 - d <DIRECTORY>, --directory <DIRECTORY>, 59
 - f <FORMAT>, --format <FORMAT>, 59
- gerrit-server-configuration-download command line option
 - d <DIRECTORY>, --directory <DIRECTORY>, 59
 - f <FORMAT>, --format <FORMAT>, 59
- gerrit-server-state-show command line option
 - fit-width, 60
 - gc, 60
 - jvm, 60
 - max-width <integer>, 60
 - noindent, 60
 - prefix <PREFIX>, 60

- print-empty, 60
 - c COLUMN, -column COLUMN, 60
 - f <FORMATTER>, -format <FORMATTER>, 60
 - gerrit-server-task-delete command line option
 - task-identifier, 60
 - gerrit-server-task-list command line option
 - fit-width, 61
 - max-width <integer>, 61
 - noindent, 61
 - print-empty, 61
 - quote <QUOTE_MODE>, 61
 - sort-column SORT_COLUMN, 61
 - c COLUMN, -column COLUMN, 61
 - f <FORMATTER>, -format <FORMATTER>, 61
 - gerrit-server-task-show command line option
 - fit-width, 62
 - max-width <integer>, 62
 - noindent, 62
 - prefix <PREFIX>, 62
 - print-empty, 62
 - c COLUMN, -column COLUMN, 62
 - f <FORMATTER>, -format <FORMATTER>, 62
 - task-identifier, 62
 - group-identifier
 - gerrit-group-create command line option, 32
 - gerrit-group-description-delete command line option, 33
 - gerrit-group-description-set command line option, 33
 - gerrit-group-exclude command line option, 33
 - gerrit-group-include command line option, 33
 - gerrit-group-member-add command line option, 34
 - gerrit-group-member-delete command line option, 35
 - gerrit-group-member-list command line option, 36
 - gerrit-group-options-set command line option, 36
 - gerrit-group-owner-set command line option, 37
 - gerrit-group-rename command line option, 37
 - gerrit-group-show command line option, 38
- N**
- name
 - gerrit-account-name-set command line option, 8
 - gerrit-project-branch-delete command line option, 42
 - gerrit-project-branch-list command line option, 43
 - gerrit-project-branch-reflog-show command line option, 44
 - gerrit-project-child-list command line option, 46
 - gerrit-project-commit-file-content-show command line option, 46
 - gerrit-project-configuration-download command line option, 48
 - gerrit-project-configuration-set command line option, 48
 - gerrit-project-delete command line option, 50
 - gerrit-project-description-set command line option, 50
 - gerrit-project-description-show command line option, 50
 - gerrit-project-gc-run command line option, 50
 - gerrit-project-head-set command line option, 51
 - gerrit-project-head-show command line option, 51
 - gerrit-project-parent-set command line option, 52
 - gerrit-project-parent-show command line option, 53
 - gerrit-project-tag-delete command line option, 55
 - gerrit-project-tag-list command line option, 56
 - gerrit-server-cache-show command line option, 59
 - new_name
 - gerrit-group-rename command line option, 37
- O**
- owner
 - gerrit-group-owner-set command line option, 37
- P**
- plugin-identifier
 - gerrit-plugin-disable command line option, 38
 - gerrit-plugin-enable command line option, 38
 - gerrit-plugin-install command line option, 39
 - gerrit-plugin-reload command line option, 40
 - gerrit-plugin-show command line option, 41
 - project-identifier
 - gerrit-project-branch-create command line option, 42
 - gerrit-project-branch-show command line option, 45
 - gerrit-project-commit-included-in command line option, 47
 - gerrit-project-commit-show command line option, 48
 - gerrit-project-create command line option, 49
 - gerrit-project-repo-statistics-show command line option, 53
 - gerrit-project-show command line option, 54
 - gerrit-project-tag-create command line option, 55
 - gerrit-project-tag-show command line option, 57
- Q**
- query
 - gerrit-account-list command line option, 7
 - gerrit-change-list command line option, 25
- S**
- status
 - gerrit-account-status-set command line option, 14

T

tag

gerrit-project-tag-show command line option, [57](#)

task-identifier

gerrit-server-task-delete command line option, [60](#)

gerrit-server-task-show command line option, [62](#)

U

username

gerrit-account-username-set command line option,
[15](#)