

---

# PyTROLL AAPP runner Documentation

*Release develop*

Jun 21, 2022



---

## Contents

---

<b>1</b>	<b>Intended audience</b>	<b>1</b>
<b>2</b>	<b>Requirements</b>	<b>3</b>
<b>3</b>	<b>Running arguments:</b>	<b>5</b>
<b>4</b>	<b>Configuration</b>	<b>7</b>
4.1	Logging . . . . .	7
4.2	Static configuration . . . . .	7
4.3	aapp_processes . . . . .	7



# CHAPTER 1

---

## Intended audience

---

The PyTROLL AAPP runner processes with help of the AAPP, Direct Broadcast satellite data from POES and METOP. This is done within a PyTROLL context using posttroll passing information into the runner what data to process.

If you dont have AAPP and posttroll installed and don't have access to DB data (POES and METOP Eumet-sat/Eumetcast EARS HRPT and EPS can also be used) then this package is not for you.



## CHAPTER 2

---

### Requirements

---

You need to have latest version (7.XX) of AAPP installed. See [NWPSAF](#).





## CHAPTER 3

---

### Running arguments:

---

- c (–config\_file)** Valid yaml configuration file
- s (–station)** Name of the station doing the processing e.g. osl for Oslo, Norway
- e (–environment)** Name of the aapp\_processes section in the yaml file to read configuration from. The configuration file can contain several environments, e.g. dev, test oper.
- v (–verbose)** Override logging level given in the configuration file to level DEBUG.
- l (–log)** Specify the file to log to, else write to stdout



See this [aapp\\_config.yaml-template](#) for an example.

### 4.1 Logging

**log\_rotation\_days** How many days before rotation (if log\_file option is given)

**log\_rotation\_backup** How many rotations to keep ( if log\_file option is given)

**logging\_mode** Logging mode (if verbose is given logging\_mode is overridden)

### 4.2 Static configuration

This section contains a lot of information to the processes how to handle various names of platforms and sensors. An how to translate the in the processing. A platform can take many names, like: M01, Metop-B, METOP-B, metopb and so on. Depending of your source of the data adjust this section accordingly. The example listed above is used at Met Norway.

The point of having this configuration here is to avoid to edit the code to make adjustments like this.

### 4.3 aapp\_processes

**<environment>** Name of the environment, e.g. test, dev or oper

**description** A nice description of this enviroment

**name** A name of the environment

**subscribe\_topics** posttroll topics to subscribe to, must be a list

**tle\_indir** Basedir of your tle files.

**tle\_infile\_format** format of your tle files. Can contain sift encoding

**tle\_archive\_dir** Where to archive your TLEs

**tle\_file\_to\_data\_diff\_limit\_days** Search for the closest TLE file based on the TLE file format time stamp Maximum difference in days is the value configured here.

**tle\_download** List of TLE urls in a dictionary to download and append to a tle file. The order of the list matters. The first element is in top of the tle file and so on. A download is only triggered when a tle file of the data timestamp is not found and tle\_file\_to\_data\_diff\_limit\_days is not given or the search does not find any tle files. Only latest tle files are downloaded, so if you process old data this will not work. Valid keys in the dictionary is: url. For space-track additional keys are valid: timeout, user, passwd and catalogue. Catalogue is a comma separated string with internatinal satellite numbers.

**locktime\_before\_rerun** Minutes to lock for similar passes in minutes

**publish\_sift\_format** posttroll topic to be used when publishing the results. Can contain sift encoding

**aapp\_prefix** Base dir of your AAPP installation

**aapp\_environment\_file** Your AAPP environment file. This is typically ATOVS\_ENV7 in you aapp\_prefix dir.

**aapp\_workdir** The directory where AAPP writes all working files. This or working\_dir must be given.

**working\_dir** The directory where AAPP writes all working files. This or aapp\_workdir must be given.

**use\_dyn\_work\_dir** If aapp\_workdir is given and this variable is set to True, add a random named temporary directory below aapp\_workdir This is handy if more than one dataset are processed simultaneously

**aapp\_outdir\_base** AAPP base dir of all the final output data

**aapp\_outdir\_format** Name of the subdir under aapp\_outdir\_base where the output data is stored. Can contain sift encoding.

**passlength\_threshold** Minimums lenght of a dataset in minutes

**aapp\_log\_files\_archive\_dir** Base dir of an archive of the AAPP logs.

**aapp\_log\_files\_archive\_length** How many days to keep the AAPP logs before cleanup

**message\_providing\_server** If you use several servers with posttroll multicast, you can give this to specify which server you want to receive messages from.

**do\_ana\_correction** Do ANA correction. ANA is a separate software package not included in AAPP.

**do\_atovpp** Add AAPP processing of level 1c TOVS/ATOVS to level 1d.

**do\_avh2hirs** From the AAPP software documentation: applies the calibration coefficients (calculated by AVHRCL) to AVHRR counts and converts radiance into brightness temperature, maps AVHRR data in HIRS FOV, and makes the cloud mask MAIA\_2.1 for AAPP version 3 and later) in the HIRS ellipse for contaminated pixels discrimination. At the end of this procedure, a level 1d file exists (HIRS level 1d).

**instrument\_skipped\_in\_processing** This is a list of satellite names, each with a list of sensor to skip to process. Can be handy if you want to skip bad sensors on a specific platform.

**rename\_aapp\_compose** Tells the runner how to rename the processed data from AAPP to more meaningsfull names. This can be a simle file name, but then all sensors from each data level will be renamed to the same. So I would say you must use a sift formatted variable. See rename\_aapp\_files for details.

**rename\_aapp\_files** Is a list of dictionaries how to rename the various AAPP processed data. This dictionary is applied to rename\_aapp\_compose.

**monitor\_message:** Not implemented.