
signac-dashboard Documentation

Release 0.2.1

Bradley Dice

Apr 24, 2019

Contents

1	Contents	3
1.1	Installation	3
1.2	API Reference	4
1.3	Changes	10
1.4	Support and Development	13
2	Indices and tables	15
	Python Module Index	17

Note: This is documentation for the **signac-dashboard** package, which is part of the [signac](#) framework. See [here](#) for a comprehensive introduction to the **signac** framework.

CHAPTER 1

Contents

1.1 Installation

The recommended installation method for **signac-dashboard** is via [conda](#) or [pip](#). The software is tested for Python versions 3.4+. Its primary dependencies are [signac](#) and [flask](#).

1.1.1 Install with conda

You can install **signac-dashboard** via conda (available on the [conda-forge](#) channel), with:

```
$ conda install -c conda-forge signac-dashboard
```

All additional dependencies will be installed automatically. To upgrade the package, execute:

```
$ conda update signac-dashboard
```

1.1.2 Install with pip

To install the package with the package manager [pip](#), execute

```
$ pip install signac-dashboard --user
```

Note: It is highly recommended to install the package into the user space and not as superuser!

To upgrade the package, simply execute the same command with the `--upgrade` option.

```
$ pip install signac-dashboard --user --upgrade
```

1.1.3 Source Code Installation

Alternatively you can clone the `git` repository and execute the `setup.py` script to install the package.

```
git clone https://github.com/glotzerlab/signac-dashboard.git
cd signac-dashboard
git submodule update --init # This step is required!
python setup.py install --user
```

1.2 API Reference

This is the API for the **signac-dashboard** application.

1.2.1 The Dashboard

Attributes

<code>Dashboard.add_url(import_name[, url_rules, ...])</code>	Add a route to the dashboard.
<code>Dashboard.job_sorter(job)</code>	Override this method for custom job sorting.
<code>Dashboard.job_subtitle(job)</code>	Override this method for custom job subtitles.
<code>Dashboard.job_title(job)</code>	Override this method for custom job titles.
<code>Dashboard.main()</code>	Runs the command line interface.
<code>Dashboard.register_module_asset(asset)</code>	Register an asset required by a dashboard module.
<code>Dashboard.run(*args, **kwargs)</code>	Runs the dashboard webserver.

```
class signac_dashboard.Dashboard(config={}, project=None, modules=[])
A dashboard application to display a signac.Project.
```

The `Dashboard` class is designed to be used as a base class for a child class such as `MyDashboard` which can be customized and launched via its command line interface (CLI). The CLI is invoked by calling `main()` on an instance of this class.

Configuration options: The `config` dictionary recognizes the following options:

- **HOST**: Sets binding address (default: localhost).
- **PORT**: Sets port to listen on (default: 8888).
- **DEBUG**: Enables debug mode if True (default: False).
- **PROFILE**: Enables the profiler `werkzeug.middleware.profiler.ProfilerMiddleware` if True (default: False).
- **PER_PAGE**: Maximum number of jobs to show per page (default: 25).

Parameters

- **config** (`dict`) – Configuration dictionary (default: {}).
- **project** (`signac.Project`) – signac project (default: None, autodetected).
- **modules** (`list`) – List of `Module` instances to display.

`add_url(import_name, url_rules=[], import_file='signac_dashboard', **options)`

Add a route to the dashboard.

This method allows custom view functions to be triggered for specified routes. These view functions are imported lazily, when their route is triggered. For example, write a file `my_views.py`:

```
def my_custom_view(dashboard):
    return 'This is a custom message.'
```

Then, in `dashboard.py`:

```
from signac_dashboard import Dashboard

class MyDashboard(Dashboard):
    pass

if __name__ == '__main__':
    dashboard = MyDashboard()
    dashboard.add_url('my_custom_view', url_rules=['/custom-url'],
                      import_file='my_views')
    dashboard.main()
```

Finally, launching the dashboard with `python dashboard.py run` and navigating to `/custom-url` will show the custom message. This can be used in conjunction with user-provided jinja templates and the method `flask.render_template()` for extending dashboard functionality.

Parameters

- `import_name (str)` – The view function name to be imported.
- `url_rules (list)` – A list of URL rules, see `flask.Flask.add_url_rule()`.
- `import_file (str)` – The module from which to import (default: `'signac_dashboard'`).
- `**options` – Additional options to pass to `flask.Flask.add_url_rule()`.

`job_sorter(job)`

Override this method for custom job sorting.

This method returns a key that can be compared to sort jobs. By default, the sorting key is based on `Dashboard.job_title()`, with natural sorting of numbers. Good examples of such keys are strings or tuples of properties that should be used to sort.

Parameters `job (signac.contrib.job.Job)` – The job being sorted.

Returns Key for sorting.

Return type any comparable type

`job_subtitle(job)`

Override this method for custom job subtitles.

This method generates job subtitles. By default, the subtitle is a minimal unique substring of the job id.

Parameters `job (signac.contrib.job.Job)` – The job being subtitled.

Returns Subtitle to be displayed.

Return type str

`job_title(job)`

Override this method for custom job titles.

This method generates job titles. By default, the title is a pretty (but verbose) form of the job state point, based on the project schema.

Parameters `job` (`signac.contrib.job.Job`) – The job being titled.

Returns Title to be displayed.

Return type `str`

main()

Runs the command line interface.

Call this function to use signac-dashboard from its command line interface. For example, save this script as `dashboard.py`:

```
from signac_dashboard import Dashboard

class MyDashboard(Dashboard):
    pass

if __name__ == '__main__':
    MyDashboard().main()
```

Then the dashboard can be launched with:

```
python dashboard.py run
```

register_module_asset(asset)

Register an asset required by a dashboard module.

Some modules require special scripts or stylesheets, like the `signac_dashboard.modules.Notes` module. It is recommended to use a namespace for each module that matches the example below:

```
dashboard.register_module_asset({
    'file': 'templates/my-module/js/my-script.js',
    'url': '/module/my-module/js/my-script.js'
})
```

Parameters `asset` (`dict`) – A dictionary with keys '`file`' and '`url`'.

run(*args, **kwargs)

Runs the dashboard webserver.

Use `main()` instead of this method for the command-line interface. Arguments to this function are passed directly to `flask.Flask.run()`.

1.2.2 Dashboard Modules

<code>Module(name, context, template[, enabled])</code>	Base class for dashboard modules.
<code>modules.DocumentEditor([name, context, template])</code>	Provides an interface to edit the job document.
<code>modules.DocumentList([name, context, ...])</code>	Displays the job document.
<code>modules.FileList([name, context, template, ...])</code>	Lists files in the job workspace with download links.
<code>modules.FlowStatus([name, context, ...])</code>	Show job labels from a <code>flow.FlowProject</code> .
<code>modules.ImageViewer([name, context, ...])</code>	Displays images in the job workspace that match a glob.
<code>modules.Notes([name, context, template, key])</code>	Displays a text box that is synced to the job document.

Continued on next page

Table 2 – continued from previous page

<code>modules.StatepointList([name, context, template])</code>	Displays the job state point.
<code>modules.TextDisplay([name, message, markdown])</code>	Render custom text or Markdown in a card.
<code>modules.VideoViewer([name, context, ...])</code>	Displays videos in the job workspace that match a glob.

```
class signac_dashboard.Module(name, context, template, enabled=True)
    Base class for dashboard modules.
```

Modules provide *cards* of content, for a specific *context*. Each module must have a **name** which appears in its cards' titles, a **context** (such as 'JobContext') in which its contents will be displayed, and a **template** file (written in HTML/Jinja-compatible syntax) for rendering card content. Modules can be disabled by default, by setting `enabled=False` in the constructor.

Custom modules: User-defined module classes should be a subclass of `Module` and define the function `get_cards()`. See [this example](#).

Module assets: If a module requires scripts or stylesheets to be included for its content to be rendered, they must be handled by the callback `register()`. For example, a module inheriting from the base `signac_dashboard.Module` class may implement this by overriding the default method as follows:

```
def register(self, dashboard):
    assets = ['js/my-script.js', 'css/my-style.css']
    for asset in assets:
        dashboard.register_module_asset({
            'file': 'templates/my-module/{}'.format(asset),
            'url': '/module/my-module/{}'.format(asset)
        })
```

Then, when the module is active, its assets will be included and a route will be created that returns the asset file.

Module routes: The callback `register()` allows modules to implement custom routes, such as methods that should be triggered by POST requests or custom APIs. For example, a module inheriting from the base `signac_dashboard.Module` class may implement this by overriding the default method as follows:

```
def register(self, dashboard):
    @dashboard.app.route('/module/my-module/update', methods=['POST'])
    def my_module_update():
        # Perform update
        return "Saved."
```

Parameters

- **name** (`str`) – Name of this module (appears in card titles).
- **context** (`str`) – Context in which this module's cards should be displayed (e.g. 'JobContext').
- **template** (`str`) – Path to a template file for this module's cards (e.g. `cards/my_module.html`, without the template directory prefix `templates/`).

`disable()`

Disable this module.

`enable()`

Enable this module.

get_cards()

Returns this module's cards for rendering.

The cards are returned as a list of dictionaries with keys 'name' and 'content'.

Returns List of module cards.

Return type list

register(dashboard)

Callback to register this module with the dashboard.

This callback should register assets and routes, as well as any other initialization that accesses or modifies the dashboard.

Parameters **dashboard** (*signac_dashboard.Dashboard*) – The dashboard invoking this callback method.

toggle()

Toggle this module.

```
class signac_dashboard.modules.DocumentEditor(name='Document Editor', context='JobContext', template='cards/document_editor.html', **kwargs)
```

Provides an interface to edit the job document.

This module shows keys in the job document with a form that allows users to edit their contents. When saving, the edited strings are parsed into JSON-compatible Python data structures (e.g., `list` and `dict`). Job document keys beginning with an underscore _ are treated as private and are not displayed.

```
class signac_dashboard.modules.DocumentList(name='Job Document', context='JobContext', template='cards/document_list.html', max_chars=None, **kwargs)
```

Displays the job document.

Long values can be optionally truncated.

Parameters **max_chars** (*int*) – Truncation length for document values (default: None).

```
class signac_dashboard.modules.FileList(name='File List', context='JobContext', template='cards/file_list.html', prefix_jobid=True, **kwargs)
```

Lists files in the job workspace with download links.

Parameters **prefix_jobid** (*bool*) – Whether filenames should be prefixed with the job id when being downloaded (default: True).

```
class signac_dashboard.modules.FlowStatus(name='Flow Status', context='JobContext', template='cards/flow_status.html', project_module='project', project_class='Project', **kwargs)
```

Show job labels from a `flow.FlowProject`.

This module displays a card with labels from `flow.FlowProject.labels()`. The user must provide an instance of `flow.FlowProject` to the dashboard constructor. Example:

```
from project import Project # FlowProject subclass with labels
from signac_dashboard import Dashboard

if __name__ == '__main__':
    Dashboard(project=Project()).main()
```

```
class signac_dashboard.modules.ImageViewer(name='Image Viewer', context='JobContext',
                                           template='cards/image_viewer.html',
                                           img_globs=['*.png', '*.jpg', '*.gif'],
                                           **kwargs)
```

Displays images in the job workspace that match a glob.

This module can display images in any format that works with a standard tag. The module defaults to showing all images of PNG, JPG, or GIF types. A filename or glob can be defined to select specific filenames. Multiple ImageViewer modules can be defined with different filenames or globs to enable/disable cards for each image or image group. Examples:

```
from signac_dashboard.modules import ImageViewer
img_mod = ImageViewer() # Shows all PNG/JPG/GIF images
img_mod = ImageViewer(name='Bond Order Diagram', img_globs=['bod.png'])
```

Parameters `img_globs` (`list`) – A list of glob expressions or exact filenames to be displayed, one per card (default: ['*.png', '*.jpg', '*.gif']).

```
class signac_dashboard.modules.Notes(name='Notes', context='JobContext', template='cards/notes.html', key='notes', **kwargs)
```

Displays a text box that is synced to the job document.

The contents of the text box are saved to `job.document['notes']`. The Notes module can be used to annotate a large data space with tags or human-readable descriptions for post-processing, parsing, or searching.

Parameters `key` (`str`) – Document key to display and update (default: 'notes').

```
class signac_dashboard.modules.StatepointList(name='Statepoint Parameters',
                                              context='JobContext', template='cards/statepoint_list.html',
                                              **kwargs)
```

Displays the job state point.

```
class signac_dashboard.modules.TextDisplay(name='Text Display', message=<function TextDisplay.<lambda>>, markdown=False, **kwargs)
```

Render custom text or Markdown in a card.

This module calls a user-provided function to display text or Markdown content in a card. Rendering Markdown requires the `markdown` library to be installed. Example:

```
def my_text(job):
    return 'This job id is {}'.format(str(job))

modules = [TextDisplay(message=my_text)]
```

Parameters

- `message` (`callable`) – A callable accepting one argument of type `signac.contrib.job.Job` and returning text or Markdown content.
- `markdown` (`bool`) – Enables Markdown rendering if True (default: False).

```
class signac_dashboard.modules.VideoViewer(name='Video Viewer', context='JobContext', template='cards/video_viewer.html', video_globs=['*.mp4', '*.m4v'], preload='none', poster=None, **kwargs)
```

Displays videos in the job workspace that match a glob.

The `VideoViewer` module displays videos using an HTML <video> tag. The module defaults to showing all videos of MP4 or M4V types. A filename or glob can be defined to select specific filenames, which may be of any format supported by your browser with the <video> tag. A “poster” can be defined, which shows a thumbnail with that filename before the video is started. Videos do not preload by default, since file sizes can be large and there may be many videos on a page. To enable preloading, use the argument `preload='auto'` or `preload='metadata'`. Multiple VideoViewer modules can be defined with different filenames or globs to enable/disable cards individually. Examples:

```
from signac_dashboard.modules import VideoViewer
video_mod = VideoViewer()    # Shows all MP4/M4V videos
video_mod = VideoViewer(name='Cool Science Video',
                        video_globs=['cool_science.mp4'],
                        poster='cool_science_thumbnail.jpg',
                        preload='none')
```

Parameters

- **video_globs** (`list`) – A list of glob expressions or exact filenames to be displayed, one per card (default: `['*.mp4', '*.m4v']`).
- **preload** (`str`) – Option for preloading videos, one of `'auto'`, `'metadata'`, or `'none'` (default: `'none'`).
- **poster** (`str`) – A path in the job workspace for a poster image to be shown before a video begins playback (default: `None`).

1.3 Changes

The `signac-dashboard` package follows semantic versioning.

1.3.1 Version 0.2

[0.2.1] – 2019-04-24

Fixed

- Corrected PyPI deployment.

[0.2.0] – 2019-04-24

Added

- New modules: DocumentEditor, FlowStatus, TextDisplay.
- New examples: cli, custom-modules, document-editor, flow-status, plots.
- The default job sorter uses natural sorting for numbers via natsort.

Changed

- Improved API documentation, especially for modules.

- Unified module asset/route registration into one `register` method.
- The Notes module can be used with any job document key.

Fixed

- Corrected error in VideoViewer when no poster was provided.
- ImageViewer/VideoViewer match files in job workspace subdirectories.
- Files can now be retrieved from job workspace subdirectories.
- Corrected pagination error.

Removed

- The signac project document and user session are no longer used to store module settings. The dashboard user script is the single source for all configuration besides command line arguments.
- Job labels have been removed and replaced with the FlowStatus module.

1.3.2 Version 0.1

[0.1.6] – 2018-10-09

Changed

- Updated layouts for bulma 0.7.1.

Fixed

- PyPI upload was missing bulma and couldn't run.

Removed

- `cssmin` is no longer a dependency.

[0.1.5] – 2018-10-09

Added

- Example dashboards are in the `examples` folder.
- Console entry point, `signac-dashboard run` will launch a simple dashboard. This will be extended in a future release.
- Better support for custom module assets.

Changed

- Modules are now part of the user session and are saved to the project document. This requires all module arguments to be JSON-encodable.
- Restructured module design and how modules provide assets.
- Documentation has been updated, with instructions for port forwarding.
- Split views into a separate file.

Fixed

- Browsers will no longer cache dynamic content.
- Pagination rendering bug squashed.

[0.1.4] – 2018-07-23

Fixed

- Removed `flask_cache` and replaced with `lru_cache` to fix compatibility with Flask 1.0.

[0.1.3] – 2018-04-02

Added

- README documentation on searching.
- Added support for signac cache.
- Added LRU cache for job details.
- Added pagination support for much faster loading.
- Added VideoViewer module.

Changed

- Error handling is cleaner.
- Refactored job views.
- Job titles show statepoint booleans as True/False.
- Added job id prefix to downloaded filenames so they can be distinguished.

Fixed

- Heterogeneous schemas can generate job titles.

[0.1.2] – 2018-02-08

Added

- Search jobs with a document filter with `doc:{“key”:”value”}`.
- Unit tests for job search.
- README documentation is much more complete.
- flake8 checked in CI.
- Added CHANGELOG.

[0.1.1] – 2017-09-25

Added

- Continuous integration support.
- Added first unit test.
- Mobile support is significantly improved.

Fixed

- Flask package was incorrectly configured in the previous release.
- Corrected menu activation script to trigger on `turbolinks:load` event.

[0.1.0] – 2017-09-17

Added

- First release.

1.4 Support and Development

To get help using the **signac-dashboard** package, either send an email to signac-support@umich.edu or join the [signac gitter chatroom](#).

The **signac-dashboard** package is hosted on [GitHub](#) and licensed under the open-source BSD 3-Clause license. Please use the [repository’s issue tracker](#) to report bugs or request new features.

CHAPTER 2

Indices and tables

- genindex
- modindex
- search

Python Module Index

S

`signac_dashboard.modules`, 8

Index

A

`add_url()` (*signac_dashboard.Dashboard* method), 4

D

Dashboard (*class in signac_dashboard*), 4
disable () (*signac_dashboard.Module method*), 7
DocumentEditor (*class in signac_dashboard.modules*), 8
DocumentList (*class in signac_dashboard.modules*), 8

E

`enable()` (*signac_dashboard.Module* method), 7

F

FileList (class in `signac_dashboard.modules`), 8
FlowStatus (class in `signac_dashboard.modules`), 8

G

`get_cards()` (*signac dashboard.Module* method), 7

1

`ImageViewer` (*class in signac.dashboard.modules*), 8

1

```
job_sorter()      (signac_dashboard.Dashboard  
                  method), 5  
job_subtitle()    (signac_dashboard.Dashboard  
                  method), 5  
job_title()       (signac_dashboard.Dashboard method),  
                  5
```

M

`main()` (*signac_dashboard*.*Dashboard* method), 6
Module (class in *signac_dashboard*), 7

N

Notes (*class in signac dashboard.modules*), 9

R

`register()` (*signac_dashboard.Module* method), 8

```
register_module_asset()  
    (signac_dashboard.Dashboard      method),  
    6
```

ru

S
signac_dashboard.modules (*module*), 8
StatepointList (class in
signac_dashboard.modules), 9

T

`TextDisplay` (*class in `signac_dashboard.modules`*), 9
`toggle()` (*`signac_dashboard` *Module* method*) 8

V

VideoViewer (class in signac.dashboard modules) 9