
Slumber Documentation

Release 0.6.1.dev

Donald Stufft

Jul 24, 2018

Contents

1	Getting Started with Slumber	3
1.1	Installation	3
1.2	Using	3
1.3	Url Parameters	4
1.4	Nested Resources	4
2	Options	5
2.1	Authentication	5
2.2	File uploads	6
2.3	Serializer	6
2.4	Slashes	7
3	How Slumber Works Behind the Scenes	9
3.1	Python to Url Translation	9
3.2	(De)Serialization	10
4	Getting Help	11
5	QuickStart	13
6	Requirements	15
7	Indices and tables	17

Slumber is a python library that provides a convenient yet powerful object orientated interface to ReSTful APIs. It acts as a wrapper around the excellent [requests](#) library and abstracts away the handling of urls, serialization, and processing requests.

Getting Started with Slumber

1.1 Installation

Slumber is available on PyPi and the preferred method of install is using Pip.

1. Install Slumber:

```
$ pip install slumber
```

2. Install Optional Dependencies

[OPTIONAL] PyYaml (*Required for the yaml serializer*):

```
$ pip install pyyaml
```

[OPTIONAL] SimpleJson (*Required for the json serializer on Python2.5, or for speedups*):

```
$ pip install simplejson
```

1.2 Using

Using Slumber is easy. Using an example ReST API made with `django-tastypie` which you can see at <http://slumber.in/api/v1/>.

```
>>> import slumber
>>> ## Connect to http://slumber.in/api/v1/ with the Basic Auth user/password of demo/
    ↳demo
>>> api = slumber.API("http://slumber.in/api/v1/", auth=("demo", "demo"))
>>> ## GET http://slumber.in/api/v1/note/
>>> ## Note: Any kwargs passed to get(), post(), put(), delete() will be used as
    ↳url parameters
>>> api.note.get()
```

(continues on next page)

(continued from previous page)

```
>>> ## POST http://slumber.in/api/v1/note/
>>> new = api.note.post({"title": "My Test Note", "content": "This is the content of
↳my Test Note!"})
>>> ## PUT http://slumber.in/api/v1/note/{id}/
>>> api.note(new["id"]).put({"content": "I just changed the content of my Test Note!"}
↳)
>>> ## PATCH http://slumber.in/api/v1/note/{id}/
>>> api.note(new["id"]).patch({"content": "Wat!"})
>>> ## GET http://slumber.in/api/v1/note/{id}/
>>> api.note(new["id"]).get()
>>> ## DELETE http://slumber.in/api/v1/note/{id}/
>>> api.note(new["id"]).delete()
```

1.3 Url Parameters

Passing an url parameter to Slumber is easy. If you wanted to say, use Tastypie's ApiKey authentication, you could do so like:

```
>>> api.resource.get(username="example", api_key=
↳"1639eb74e86717f410c640d2712557aac0e989c8")
```

If you wanted to filter the Slumber demo api for notes that start with Bacon, you could do:

```
>>> import slumber
>>> api = slumber.API("http://slumber.in/api/v1/", auth=("demo", "demo"))
>>> ## GET http://slumber.in/api/v1/note/?title__startswith=Bacon
>>> api.note.get(title__startswith="Bacon")
```

1.4 Nested Resources

Nested resources are also easy and works just how a single level resource works:

```
>>> ## GET /resource1/resource2/
>>> api.resource1.resource2.get()

>>> ## GET /resource1/1/resource2/
>>> api.resource1(1).resource2.get()
```


Slumber comes with only a couple options.

2.1 Authentication

Out of the box Slumber should support any authentication method supported by requests. These include Basic, Digest, OAuth. However only Basic and Digest get tested currently.

2.1.1 Specify Authentication

Specifying authentication credentials is easy. When you create your slumber api instance, instead of doing:

```
api = slumber.API("http://path/to/my/api/")
```

You supply the username and password (for Basic Auth) like:

```
api = slumber.API("http://path/to/my/api/", auth=("myuser", "mypass"))
```

And slumber will attempt to use those credentials with each request.

With TastyPie ApikeyAuthentication you can use:

```
from requests.auth import AuthBase

class TastyPieApiKeyAuth(AuthBase):
    def __init__(self, username, apikey):
        self.username = username
        self.apikey = apikey

    def __call__(self, r):
        r.headers['Authorization'] = "ApiKey {0}:{1}".format(self.username, self.
↪apikey)
```

(continues on next page)

(continued from previous page)

```
        return r

api = slumber.API("http://path/to/my/api/", auth=TastypieApiKeyAuth("myuser", "mypass
↪"))
```

To Use Digest or OAuth please consult the requests documentation. The auth argument is passed directly to requests and thus works exactly the same way and accepts exactly the same arguments.

2.2 File uploads

You may upload files by supplying a dictionary in the form `{'key': file-like-object}` as the value of the `files` parameter in `post`, `patch` or `put` calls. E.g.:

```
with open('/home/philip/out.txt') as fp:
    api.file.post({'name': 'my file'}, files={'file': fp})
```

Will do a POST to `/api/file/` with a multipart-form-data request.

2.3 Serializer

Slumber allows you to use any serialization you want. It comes with json and yaml but creating your own is easy. By default it will attempt to use json. You can change the default by specifying a `format` argument to your api class.:

```
# Use Yaml instead of Json
api = slumber.API("http://path/to/my/api/", format="yaml")
```

If you want to override the serializer for a particular request, you can do that as well:

```
# Use Yaml instead of Json for just this request.
api = slumber.API("http://path/to/my/api/") # Serializer defaults to Json
api.resource_name(format="yaml").get() # Serializer will be Yaml
```

If you want to create your own serializer you can do so. A `Serialize` inherits from `slumber.serialize.BaseSerializer` and implements `loads`, `dumps`. It also must have a class member of `key` which will be the string key for this serialization (such as “json”). The final requirement is either a class member of `content_type` which is the content type to use for requests (such as “application/json”) or define a `get_content_type` method.

An example:

```
class PickleSerializer(slumber.serialize.BaseSerializer):
    key = "pickle"
    content_type = "x-application/pickle"

    def loads(self, data):
        return pickle.loads(data)

    def dumps(self, data):
        return pickle.dumps(data)
```

Once you have a custom serializer you can pass it to slumber like so:

```
from slumber import serialize
import slumber

s = serialize.Serializer(
    default="pickle",
    serializers=[
        serialize.JsonSerializer(),
        serialize.YamlSerializer(),
        PickleSerializer(),
    ]
)
api = slumber.API("http://example.com/api/v1/", format="pickle", serializer=s)
```

2.4 Slashes

Slumber assumes by default that all urls should end with a slash. If you do not want this behavior you can control it via the `append_slash` option which can be set by passing `append_slash` to the `slumber.API` kwargs.

How Slumber Works Behind the Scenes

Behind the scenes slumber is really 2 things. It is a translator from python code into urls, and it is a serializer/deserializer helper.

3.1 Python to Url Translation

The Url Translation portion of slumber is fairly simple but powerful. It is basically a list of url fragments that get joined together.

In the call:

```
>>> api.note.get()
```

Slumber translates this by adding the url value for `api` (say `http://slumber.in/api/v1/`) with the url value for `note`. The url value for an attribute is equal to it's name, so in this case slumber essentially does `"http://slumber.in/api/v1/" + "note"`,

The same holds true when you pass in an ID to a resource. It just adds another segment to the url list.

This means that in this call:

```
>>> api.note(1).get()
```

Slumber translates it to:

```
>>> "http://slumber.in/api/v1/" + "note" + "/" + str(1)
```

Nested Resources follow the same principle.

The other part of an url that Slumber translates is kwargs to `get()`, `post()`, `put()`, `delete()` into query string params. This again is a fairly simple operation which then gets added to the end of the url.

The Final portion of Slumber's Python to HTTP is that the first arg passed to each of the HTTP functions is serialized, and then passed into the HTTP request as the body of the request.

3.2 (De)Serialization

Slumber also has a built in Serialization framework. This is a fairly simple wrapper around (simple)json and/or pyyaml that controls setting the correct content-type on a request, and will automatically serialize or deserialize any incoming or outgoing request body.

CHAPTER 4

Getting Help

There are two primary ways of getting help. I have an IRC channel ([#slumber on irc.freenode.net](#)) to get help, want to bounce idea or generally shoot the breeze.

1. Install Slumber:

```
$ pip install slumber
```

2. Install Optional Requirement:

```
pip install pyyaml
```

3. Use Slumber!

CHAPTER 6

Requirements

Slumber requires the following modules:

- Python 2.6+
- requests
- pyyaml (If you are using the optional yaml serialization)

Testing Slumber requires the following modules:

- Mock

CHAPTER 7

Indices and tables

- `genindex`
- `modindex`
- `search`