
subliminal Documentation

Release 2.0.4

Antoine Bertin

September 03, 2016

1	Documentation	3
1.1	Usage	3
1.2	How it works	5
1.3	CLI	7
1.4	Provider Guide	8
2	API Documentation	11
2.1	Core	11
2.2	Video	15
2.3	Subtitle	18
2.4	Providers	19
2.5	Refiners	26
2.6	Extensions	27
2.7	Score	28
2.8	Utils	29
2.9	Cache	30
2.10	CLI	31
2.11	Exceptions	31
3	License	33
4	Indices and tables	35
	Python Module Index	37

Subliminal is a python 2.7+ library to search and download subtitles. It comes with an easy to use yet powerful CLI (command-line interface) suitable for direct use or cron jobs.

Documentation

1.1 Usage

1.1.1 CLI

Download English subtitles:

```
$ subliminal download -l en The.Big.Bang.Theory.S05E18.HDTV.x264-LOL.mp4
Collecting videos [#####] 100%
1 video collected / 0 video ignored
Downloading subtitles [#####] 100%
Downloaded 1 subtitle
```

Warning: For cron usage, make sure to specify a maximum age (with `--age`) so subtitles are searched for recent videos only. Otherwise you will get banned from the providers for abuse due to too many requests. If subliminal didn't find subtitles for an old video, it's unlikely it will find subtitles for that video ever anyway.

See [CLI](#) for more details on the available commands and options.

1.1.2 Nautilus/Nemo integration

See the dedicated [project page](#) for more information.

1.1.3 High level API

You can call subliminal in many different ways depending on how much control you want over the process. For most use cases, you can stick to the standard API.

Common

Let's start by importing subliminal:

```
>>> import os
>>> from babelfish import *
>>> from subliminal import *
```

Before going further, there are a few things to know about subliminal.

Video

The *Movie* and *Episode* classes represent a video, existing or not. You can create a video by name (or path) with *Video.fromname()*, use *scan_video()* on an existing file path to get even more information about the video or use *scan_videos()* on an existing directory path to scan a whole directory for videos.

```
>>> video = Video.fromname('The.Big.Bang.Theory.S05E18.HDTV.x264-LOL.mp4')
>>> video
<Episode ['The Big Bang Theory', 5x18]>
```

Here video information was guessed based on the name of the video, you can access some video attributes:

```
>>> video.video_codec
'h264'
>>> video.release_group
'LOL'
```

Configuration

Before proceeding to listing and downloading subtitles, you need to configure the cache. Subliminal uses a cache to reduce repeated queries to providers and improve overall performance with no impact on search quality. For the sake of this example, we're going to use a memory backend.

```
>>> my_region = region.configure('dogpile.cache.memory')
```

Warning: Choose a cache that fits your application and prefer persistent over volatile backends. The file backend is usually a good choice. See [dogpile.cache's documentation](#) for more details on backends.

Now that we're done with the basics, let's have some *real* fun.

Listing

To list subtitles, subliminal provides a *list_subtitles()* function that will return all found subtitles:

```
>>> subtitles = list_subtitles([video], {Language('hun')}, providers=['podnapisi'])
>>> subtitles[video]
[<PodnapisiSubtitle 'ZtAW' [hu]>, <PodnapisiSubtitle 'ONAW' [hu]>]
```

Note: As you noticed, all parameters are iterables but only contain one item which means you can deal with a lot of videos, languages and providers at the same time. For the sake of this example, we filter providers to use only one, pass *providers=None* (default) to search on all providers.

Scoring

It's usual you have multiple candidates for subtitles. To help you chose which one to download, subliminal can compare them to the video and tell you exactly what matches with *get_matches()*:

```
>>> for s in subtitles[video]:
...     sorted(s.get_matches(video))
['episode', 'format', 'release_group', 'season', 'series', 'video_codec', 'year']
['episode', 'format', 'season', 'series', 'year']
```

And then compute a score with those matches with `compute_score()`:

```
>>> for s in subtitles[video]:
...     {s: compute_score(s, video)}
{<PodnapisiSubtitle 'ZtAW' [hu]>: 354}
{<PodnapisiSubtitle 'ONAW' [hu]>: 337}
```

Now you should have a better idea about which one you should choose.

Downloading

We can settle on the first subtitle and download its content using `download_subtitles()`:

```
>>> subtitle = subtitles[video][0]
>>> subtitle.content is None
True
>>> download_subtitles([subtitle])
>>> subtitle.content.split(b'\n')[2]
b'Elszaladok a boltba'
```

If you want a string instead of bytes, you can access decoded content with the `text` property:

```
>>> subtitle.text.split('\n')[3]
'néhány apróságért.'
```

Downloading best subtitles

Downloading best subtitles is what you want to do in almost all cases, as a shortcut for listing, scoring and downloading you can use `download_best_subtitles()`:

```
>>> best_subtitles = download_best_subtitles([video], {Language('hun')}, providers=['podnapisi'])
>>> best_subtitles[video]
[<PodnapisiSubtitle 'ZtAW' [hu]>]
>>> best_subtitle = best_subtitles[video][0]
>>> best_subtitle.content.split(b'\n')[2]
b'Elszaladok a boltba'
```

We end up with the same subtitle but with one line of code. Neat.

Save

We got ourselves a nice subtitle, now we can save it on the file system using `save_subtitles()`:

```
>>> save_subtitles(video, [best_subtitle])
[<PodnapisiSubtitle 'ZtAW' [hu]>]
>>> os.listdir()
['The.Big.Bang.Theory.S05E18.HDTV.x264-LOL.hu.srt']
```

1.2 How it works

1.2.1 Providers

Subliminal uses multiple providers to give users a vast choice and have a better chance to find the best matching subtitles. Current supported providers are:

- Addic7ed
- LegendasTV
- NapiProjekt
- OpenSubtitles
- Podnapisi
- Shooter
- SubsCenter
- TheSubDB
- TvSubtitles

Providers all inherit the same `Provider` base class and thus share the same API. They are registered on the `subliminal.providers` entry point and are exposed through the `provider_manager` for easy access.

To work with multiple providers seamlessly, the `ProviderPool` exposes the same API but distributes it to its providers and `AsyncProviderPool` does it asynchronously.

1.2.2 Scoring

Rating subtitles and comparing them is probably the most difficult part and this is where subliminal excels with its powerful scoring algorithm.

Using `guessit` and `enzyme`, subliminal extracts properties of the video and match them with the properties of the subtitles found with the providers.

Equations in `subliminal.score` give a score to each property (called a match). The more matches the video and the subtitle have, the higher the score computed with `compute_score()` gets.

1.2.3 Libraries

Various libraries are used by subliminal and are key to its success:

- `guessit` to guess information from filenames
- `enzyme` to detect embedded subtitles in videos and read other video metadata
- `babelfish` to work with languages
- `requests` to make human readable HTTP requests
- `BeautifulSoup` to parse HTML and XML
- `dogpile.cache` to cache intermediate search results
- `stevedore` to manage the provider entry point
- `chardet` to detect subtitles' encoding
- `pysrt` to validate downloaded subtitles

1.3 CLI

1.3.1 subliminal

```
Usage: subliminal [OPTIONS] COMMAND [ARGS]...
```

Subtitles, faster than your thoughts.

Options:

```
--addic7ed USERNAME PASSWORD    Addic7ed configuration.
--legendastv USERNAME PASSWORD  Legendastv configuration.
--opensubtitles USERNAME PASSWORD
                                OpenSubtitles configuration.
--subscenter USERNAME PASSWORD  SubsCenter configuration.
--cache-dir DIRECTORY           Path to the cache directory. [default:
                                /home/docs/.cache/subliminal]
--debug                         Print useful information for debugging
                                subliminal and for reporting bugs.
--version                       Show the version and exit.
--help                          Show this message and exit.
```

Commands:

```
cache      Cache management.
download   Download best subtitles.
```

Suggestions and bug reports are greatly appreciated:
<https://github.com/Diaoul/subliminal/>

1.3.2 subliminal download

```
Usage: subliminal download [OPTIONS] PATH...
```

Download best subtitles.

PATH can be an directory containing videos, a video file path or a video file name. It can be used multiple times.

If an existing subtitle is detected (external or embedded) in the correct language, the download is skipped for the associated video.

Options:

```
-l, --language LANGUAGE          Language as IETF code, e.g. en, pt-BR (can
                                be used multiple times). [required]
-p, --provider [addic7ed|legendastv|opensubtitles|podnapisi|shooter|subscenter|thesubdb|tvsubtitles]
                                Provider to use (can be used multiple
                                times).
-r, --refiner [metadata|omdb|tvdb]
                                Refiner to use (can be used multiple times).
-a, --age AGE                    Filter videos newer than AGE, e.g. 12h,
                                1w2d.
-d, --directory DIR             Directory where to save subtitles, default
                                is next to the video file.
-e, --encoding ENC              Subtitle file encoding, default is to
                                preserve original encoding.
-s, --single                    Save subtitle without language code in the
```

	file name, i.e. use .srt extension. Do not use this unless your media player requires it.
<code>-f, --force</code>	Force download even if a subtitle already exist.
<code>-hi, --hearing-impaired</code>	Prefer hearing impaired subtitles.
<code>-m, --min-score INTEGER RANGE</code>	Minimum score for a subtitle to be downloaded (0 to 100).
<code>-w, --max-workers INTEGER RANGE</code>	Maximum number of threads to use.
<code>-z, --archives / -Z, --no-archives</code>	Scan archives for videos (supported extensions: .rar). [default: True]
<code>-v, --verbose</code>	Increase verbosity.
<code>--help</code>	Show this message and exit.

1.3.3 subliminal cache

Usage: subliminal cache [OPTIONS]

Cache management.

Options:

<code>--clear-subliminal</code>	Clear subliminal's cache. Use this ONLY if your cache is corrupted or if you experience issues.
<code>--help</code>	Show this message and exit.

1.4 Provider Guide

This guide is going to explain how to add a *Provider* to subliminal. You are encouraged to take a look at the existing providers, it can be a nice base to start your own provider.

1.4.1 Requirements

When starting a provider you should be able to answer to the following questions:

- What languages does my provider support?
- What are the language codes for the supported languages?
- Does my provider deliver subtitles for episodes? for movies?
- Does my provider require a video hash?

Each response of these questions will help you set the correct attributes for your *Provider*.

1.4.2 Video Validation

Not all providers deliver subtitles for *Episode*. Some may require a hash. The `check()` method does validation against a *Video* object and will return *False* if the given *Video* isn't suitable. If you're not happy with the default implementation, you can override it.

1.4.3 Configuration

API keys must not be configurable by the user and must remain linked to subliminal. Hence they must be written in the provider module.

Per-user authentication is allowed and must be configured at instantiation as keyword arguments. Configuration will be done by the user through the `provider_configs` argument of the `list_subtitles()` and `download_best_subtitles()` functions. No network operation must be done during instantiation, only configuration. Any error in the configuration must raise a `ConfigurationError`.

Beyond this point, if an error occurs, a generic `ProviderError` exception must be raised. You can also use more explicit exception classes `AuthenticationError` and `DownloadLimitExceeded`.

1.4.4 Initialization / Termination

Actual authentication operations must take place in the `initialize()` method. If you need anything to be executed when the provider isn't used anymore like logout, use `terminate()`.

1.4.5 Caching policy

To save bandwidth and improve querying time, intermediate data should be cached when possible. Typical use case is when a query to retrieve show ids is required prior to the query to actually search for subtitles. In that case the function that gets the show id from the show name must be cached. Expiration time should be `SHOW_EXPIRATION_TIME` for shows and `EPISODE_EXPIRATION_TIME` for episodes.

1.4.6 Language

To be able to handle various language codes, subliminal makes use of `babelfish` Language and converters. You must set the attribute `languages` with a set of supported `Language`.

If you cannot find a suitable converter for your provider, you can `make one of your own`.

1.4.7 Querying

The `query()` method parameters must include all aspects of provider's querying with primary types.

1.4.8 Subtitle

A custom `Subtitle` subclass must be created to represent a subtitle from the provider. It must have relevant attributes that can be used to compute the matches of the subtitle against a `Video` object.

1.4.9 Score computation

To be able to compare subtitles coming from different providers between them, the `get_matches()` method must be implemented.

1.4.10 Unittesting

All possible uses of `query()`, `list_subtitles()` and `download_subtitle()` methods must have integration tests. Use `vcrpy` for recording and playback of network activity. Other functions must be unittested. If necessary, you can use `unittest.mock` to mock some functions.

API Documentation

If you are looking for information on a specific function, class or method, this part of the documentation is for you.

2.1 Core

`subliminal.core.ARCHIVE_EXTENSIONS`

Supported archive extensions

class `subliminal.core.ProviderPool` (*providers=None, provider_configs=None*)

A pool of providers with the same API as a single *Provider*.

It has a few extra features:

- Lazy loads providers when needed and supports the *with* statement to *terminate()* the providers on exit.
- Automatically discard providers on failure.

Parameters

- **providers** (*list*) – name of providers to use, if not all.
- **provider_configs** (*dict*) – provider configuration as keyword arguments per provider name to pass when instanciating the *Provider*.

providers = None

Name of providers to use

provider_configs = None

Provider configuration

initialized_providers = None

Initialized providers

discarded_providers = None

Discarded providers

list_subtitles_provider (*provider, video, languages*)

List subtitles with a single provider.

The video and languages are checked against the provider.

Parameters

- **provider** (*str*) – name of the provider.

- **video** (*Video*) – video to list subtitles for.
- **languages** (set of *Language*) – languages to search for.

Returns found subtitles.

Return type list of *Subtitle* or None

list_subtitles (*video*, *languages*)

List subtitles.

Parameters

- **video** (*Video*) – video to list subtitles for.
- **languages** (set of *Language*) – languages to search for.

Returns found subtitles.

Return type list of *Subtitle*

download_subtitle (*subtitle*)

Download *subtitle*'s *content*.

Parameters **subtitle** (*Subtitle*) – subtitle to download.

Returns *True* if the subtitle has been successfully downloaded, *False* otherwise.

Return type *bool*

download_best_subtitles (*subtitles*, *video*, *languages*, *min_score=0*, *hearing_impaired=False*, *only_one=False*, *compute_score=None*)

Download the best matching subtitles.

Parameters

- **subtitles** (list of *Subtitle*) – the subtitles to use.
- **video** (*Video*) – video to download subtitles for.
- **languages** (set of *Language*) – languages to download.
- **min_score** (*int*) – minimum score for a subtitle to be downloaded.
- **hearing_impaired** (*bool*) – hearing impaired preference.
- **only_one** (*bool*) – download only one subtitle, not one per language.
- **compute_score** – function that takes *subtitle* and *video* as positional arguments, *hearing_impaired* as keyword argument and returns the score.

Returns downloaded subtitles.

Return type list of *Subtitle*

terminate ()

Terminate all the *initialized_providers*.

class `subliminal.core.AsyncProviderPool` (*max_workers=None*, **args*, ***kwargs*)

Subclass of *ProviderPool* with asynchronous support for *list_subtitles* ().

Parameters **max_workers** (*int*) – maximum number of threads to use. If *None*, *max_workers* will be set to the number of *providers*.

max_workers = None

Maximum number of threads to use

`subliminal.core.check_video` (*video*, *languages=None*, *age=None*, *undefined=False*)
 Perform some checks on the *video*.

All the checks are optional. Return *False* if any of this check fails:

- *languages* already exist in *video*'s *subtitle_languages*.
- *video* is older than *age*.
- *video* has an *undefined* language in *subtitle_languages*.

Parameters

- **video** (*Video*) – video to check.
- **languages** (set of *Language*) – desired languages.
- **age** (*datetime.timedelta*) – maximum age of the video.
- **undefined** (*bool*) – fail on existing undefined language.

Returns *True* if the video passes the checks, *False* otherwise.

Return type *bool*

`subliminal.core.search_external_subtitles` (*path*, *directory=None*)
 Search for external subtitles from a video *path* and their associated language.

Unless *directory* is provided, search will be made in the same directory as the video file.

Parameters

- **path** (*str*) – path to the video.
- **directory** (*str*) – directory to search for subtitles.

Returns found subtitles with their languages.

Return type *dict*

`subliminal.core.scan_video` (*path*)
 Scan a video from a *path*.

Parameters **path** (*str*) – existing path to the video.

Returns the scanned video.

Return type *Video*

`subliminal.core.scan_archive` (*path*)
 Scan an archive from a *path*.

Parameters **path** (*str*) – existing path to the archive.

Returns the scanned video.

Return type *Video*

`subliminal.core.scan_videos` (*path*, *age=None*, *archives=True*)
 Scan *path* for videos and their subtitles.

See `refine()` to find additional information for the video.

Parameters

- **path** (*str*) – existing directory path to scan.
- **age** (*datetime.timedelta*) – maximum age of the video or archive.

- **archives** (*bool*) – scan videos in archives.

Returns the scanned videos.

Return type list of *Video*

`subliminal.core.refine(video, episode_refiners=None, movie_refiners=None, **kwargs)`

Refine a video using *Refiners*.

Note: Exceptions raised in refiners are silently passed and logged.

Parameters

- **video** (*Video*) – the video to refine.
- **episode_refiners** (*tuple*) – refiners to use for episodes.
- **movie_refiners** (*tuple*) – refiners to use for movies.
- ****kwargs** – additional parameters for the *refine()* functions.

`subliminal.core.list_subtitles(videos, languages, pool_class=<class 'subliminal.core.ProviderPool'>, **kwargs)`

List subtitles.

The *videos* must pass the *languages* check of *check_video()*.

Parameters

- **videos** (set of *Video*) – videos to list subtitles for.
- **languages** (set of *Language*) – languages to search for.
- **pool_class** (*ProviderPool*, *AsyncProviderPool* or similar) – class to use as provider pool.
- ****kwargs** – additional parameters for the provided *pool_class* constructor.

Returns found subtitles per video.

Return type dict of *Video* to list of *Subtitle*

`subliminal.core.download_subtitles(subtitles, pool_class=<class 'subliminal.core.ProviderPool'>, **kwargs)`

Download *content* of *subtitles*.

Parameters

- **subtitles** (list of *Subtitle*) – subtitles to download.
- **pool_class** (*ProviderPool*, *AsyncProviderPool* or similar) – class to use as provider pool.
- ****kwargs** – additional parameters for the provided *pool_class* constructor.

`subliminal.core.download_best_subtitles(videos, languages, min_score=0, hearing_impaired=False, only_one=False, compute_score=None, pool_class=<class 'subliminal.core.ProviderPool'>, **kwargs)`

List and download the best matching subtitles.

The *videos* must pass the *languages* and *undefined (only_one)* checks of *check_video()*.

Parameters

- **videos** (set of *Video*) – videos to download subtitles for.
- **languages** (set of *Language*) – languages to download.
- **min_score** (*int*) – minimum score for a subtitle to be downloaded.
- **hearing_impaired** (*bool*) – hearing impaired preference.
- **only_one** (*bool*) – download only one subtitle, not one per language.
- **compute_score** – function that takes *subtitle* and *video* as positional arguments, *hearing_impaired* as keyword argument and returns the score.
- **pool_class** (*ProviderPool*, *AsyncProviderPool* or similar) – class to use as provider pool.
- ****kwargs** – additional parameters for the provided *pool_class* constructor.

Returns downloaded subtitles per video.

Return type dict of *Video* to list of *Subtitle*

```
subliminal.core.save_subtitles(video, subtitles, single=False, directory=None, encoding=None)
```

Save subtitles on filesystem.

Subtitles are saved in the order of the list. If a subtitle with a language has already been saved, other subtitles with the same language are silently ignored.

The extension used is *.lang.srt* by default or *.srt* if *single* is *True*, with *lang* being the IETF code for the *language* of the subtitle.

Parameters

- **video** (*Video*) – video of the subtitles.
- **subtitles** (list of *Subtitle*) – subtitles to save.
- **single** (*bool*) – save a single subtitle, default is to save one subtitle per language.
- **directory** (*str*) – path to directory where to save the subtitles, default is next to the video.
- **encoding** (*str*) – encoding in which to save the subtitles, default is to keep original encoding.

Returns the saved subtitles

Return type list of *Subtitle*

2.2 Video

```
subliminal.video.VIDEO_EXTENSIONS
```

Video extensions

```
class subliminal.video.Video(name, format=None, release_group=None, resolution=None,
                             video_codec=None, audio_codec=None, imdb_id=None,
                             hashes=None, size=None, subtitle_languages=None)
```

Base class for videos.

Represent a video, existing or not.

Parameters

- **name** (*str*) – name or path of the video.

- **format** (*str*) – format of the video (HDTV, WEB-DL, BluRay, ...).
- **release_group** (*str*) – release group of the video.
- **resolution** (*str*) – resolution of the video stream (480p, 720p, 1080p or 1080i).
- **video_codec** (*str*) – codec of the video stream.
- **audio_codec** (*str*) – codec of the main audio stream.
- **imdb_id** (*str*) – IMDb id of the video.
- **hashes** (*dict*) – hashes of the video file by provider names.
- **size** (*int*) – size of the video file in bytes.
- **subtitle_languages** (*set*) – existing subtitle languages.

name = None

Name or path of the video

format = None

Format of the video (HDTV, WEB-DL, BluRay, ...)

release_group = None

Release group of the video

resolution = None

Resolution of the video stream (480p, 720p, 1080p or 1080i)

video_codec = None

Codec of the video stream

audio_codec = None

Codec of the main audio stream

imdb_id = None

IMDb id of the video

hashes = None

Hashes of the video file by provider names

size = None

Size of the video file in bytes

subtitle_languages = None

Existing subtitle languages

exists

Test whether the video exists

age

Age of the video

classmethod fromguess (*name*, *guess*)

Create an *Episode* or a *Movie* with the given *name* based on the *guess*.

Parameters

- **name** (*str*) – name of the video.
- **guess** (*dict*) – guessed data.

Raise `ValueError` if the *type* of the *guess* is invalid

classmethod fromname (*name*)

Shortcut for `fromguess()` with a *guess* guessed from the *name*.

Parameters **name** (*str*) – name of the video.

```
class subliminal.video.Episode(name, series, season, episode, title=None, year=None, original_series=True, tvdb_id=None, series_tvdb_id=None, series_imdb_id=None, **kwargs)
```

Episode *Video*.

Parameters

- **series** (*str*) – series of the episode.
- **season** (*int*) – season number of the episode.
- **episode** (*int*) – episode number of the episode.
- **title** (*str*) – title of the episode.
- **year** (*int*) – year of the series.
- **original_series** (*bool*) – whether the series is the first with this name.
- **tvdb_id** (*int*) – TVDB id of the episode.
- ****kwargs** – additional parameters for the *Video* constructor.

series = None

Series of the episode

season = None

Season number of the episode

episode = None

Episode number of the episode

title = None

Title of the episode

year = None

Year of series

original_series = None

The series is the first with this name

tvdb_id = None

TVDB id of the episode

series_tvdb_id = None

TVDB id of the series

series_imdb_id = None

IMDb id of the series

```
class subliminal.video.Movie(name, title, year=None, **kwargs)
```

Movie *Video*.

Parameters

- **title** (*str*) – title of the movie.
- **year** (*int*) – year of the movie.
- ****kwargs** – additional parameters for the *Video* constructor.

title = None

Title of the movie

year = None
Year of the movie

2.3 Subtitle

subliminal.subtitle.**SUBTITLE_EXTENSIONS**
Subtitle extensions

class subliminal.subtitle.**Subtitle**(*language, hearing_impaired=False, page_link=None, encoding=None*)

Base class for subtitle.

Parameters

- **language** (*Language*) – language of the subtitle.
- **hearing_impaired** (*bool*) – whether or not the subtitle is hearing impaired.
- **page_link** (*str*) – URL of the web page from which the subtitle can be downloaded.
- **encoding** (*str*) – Text encoding of the subtitle.

provider_name = ''
Name of the provider that returns that class of subtitle

language = None
Language of the subtitle

hearing_impaired = None
Whether or not the subtitle is hearing impaired

page_link = None
URL of the web page from which the subtitle can be downloaded

content = None
Content as bytes

encoding = None
Encoding to decode with when accessing *text*

id
Unique identifier of the subtitle

text
Content as string
If *encoding* is None, the encoding is guessed with *guess_encoding()*

is_valid()
Check if a *text* is a valid SubRip format.

Returns whether or not the subtitle is valid.

Return type *bool*

guess_encoding()
Guess encoding using the language, falling back on chardet.

Returns the guessed encoding.

Return type *str*

get_matches (*video*)
Get the matches against the *video*.

Parameters `video` (*Video*) – the video to get the matches with.

Returns matches of the subtitle.

Return type `set`

`subliminal.subtitle.get_subtitle_path(video_path, language=None, extension='.srt')`

Get the subtitle path using the *video_path* and *language*.

Parameters

- **video_path** (*str*) – path to the video.
- **language** (*Language*) – language of the subtitle to put in the path.
- **extension** (*str*) – extension of the subtitle.

Returns path of the subtitle.

Return type `str`

`subliminal.subtitle.guess_matches(video, guess, partial=False)`

Get matches between a *video* and a *guess*.

If a *guess* is *partial*, the absence information won't be counted as a match.

Parameters

- **video** (*Video*) – the video.
- **guess** (*dict*) – the guess.
- **partial** (*bool*) – whether or not the guess is partial.

Returns matches between the *video* and the *guess*.

Return type `set`

`subliminal.subtitle.fix_line_ending(content)`

Fix line ending of *content* by changing it to .

param bytes content content of the subtitle.

return the content with fixed line endings.

rtype bytes

2.4 Providers

class `subliminal.providers.TimeoutSafeTransport` (*timeout*, **args*, ***kwargs*)

Timeout support for `xmlrpc.client.SafeTransport`.

class `subliminal.providers.ParserBeautifulSoup` (*markup*, *parsers*, ***kwargs*)

A `bs4.BeautifulSoup` that picks the first parser available in *parsers*.

Parameters

- **markup** – markup for the `bs4.BeautifulSoup`.
- **parsers** (*list*) – parser names, in order of preference.

class `subliminal.providers.Provider`

Base class for providers.

If any configuration is possible for the provider, like credentials, it must take place during instantiation.

Raise `ConfigurationError` if there is a configuration error

languages = `set()`

Supported set of `Language`

video_types = (`<class 'subliminal.video.Episode'>`, `<class 'subliminal.video.Movie'>`)

Supported video types

required_hash = `None`

Required hash, if any

initialize ()

Initialize the provider.

Must be called when starting to work with the provider. This is the place for network initialization or login operations.

Note: This is called automatically when entering the *with* statement

terminate ()

Terminate the provider.

Must be called when done with the provider. This is the place for network shutdown or logout operations.

Note: This is called automatically when exiting the *with* statement

classmethod check (*video*)

Check if the *video* can be processed.

The *video* is considered invalid if not an instance of `video_types` or if the `required_hash` is not present in `hashes` attribute of the *video*.

Parameters **video** (`Video`) – the video to check.

Returns `True` if the *video* is valid, `False` otherwise.

Return type `bool`

query (*args, **kwargs)

Query the provider for subtitles.

Arguments should match as much as possible the actual parameters for querying the provider

Returns found subtitles.

Return type list of `Subtitle`

Raise `ProviderError`

list_subtitles (*video*, *languages*)

List subtitles for the *video* with the given *languages*.

This will call the `query()` method internally. The parameters passed to the `query()` method may vary depending on the amount of information available in the *video*.

Parameters

- **video** (`Video`) – video to list subtitles for.
- **languages** (set of `Language`) – languages to search for.

Returns found subtitles.

Return type list of *Subtitle*

Raise *ProviderError*

download_subtitle (*subtitle*)

Download *subtitle*'s *content*.

Parameters **subtitle** (*Subtitle*) – subtitle to download.

Raise *ProviderError*

2.4.1 Addic7ed

subliminal.providers.addic7ed.**series_year_re** = <_sre.SRE_Pattern object>

Series header parsing regex

```
class subliminal.providers.addic7ed.Addic7edSubtitle (language,      hearing_impaired,
                                                    page_link,    series,    season,
                                                    episode,    title,    year,    version,
                                                    download_link)
```

Addic7ed Subtitle.

```
class subliminal.providers.addic7ed.Addic7edProvider (username=None,      pass-
                                                    word=None)
```

Addic7ed Provider.

_get_show_ids (*arg, **kw)

Get the dict of show ids per series by querying the *shows.php* page.

Returns show id per series, lower case and without quotes.

Return type dict

_search_show_id (*arg, **kw)

Search the show id from the *series* and *year*.

Parameters

- **series** (*str*) – series of the episode.
- **year** (*int*) – year of the series, if any.

Returns the show id, if found.

Return type int

get_show_id (*series*, *year*=None, *country_code*=None)

Get the best matching show id for *series*, *year* and *country_code*.

First search in the result of `_get_show_ids()` and fallback on a search with `_search_show_id()`.

Parameters

- **series** (*str*) – series of the episode.
- **year** (*int*) – year of the series, if any.
- **country_code** (*str*) – country code of the series, if any.

Returns the show id, if found.

Return type int

2.4.2 LegendasTv

```
subliminal.providers.legendastv.type_map = {'S': 'episode', 'M': 'movie', 'C': 'episode'}
    Conversion map for types

subliminal.providers.legendastv.season_re = <_sre.SRE_Pattern object at 0x2430b20>
    BR title season parsing regex

subliminal.providers.legendastv.downloads_re = <_sre.SRE_Pattern object>
    Downloads parsing regex

subliminal.providers.legendastv.rating_re = <_sre.SRE_Pattern object>
    Rating parsing regex

subliminal.providers.legendastv.timestamp_re = <_sre.SRE_Pattern object>
    Timestamp parsing regex

subliminal.providers.legendastv.releases_key = 'subliminal.providers.legendastv:releases|{archive_id}'
    Cache key for releases

class subliminal.providers.legendastv.LegendasTVArchive(id, name, pack, featured,
                                                         link, downloads=0, rating=0,
                                                         timestamp=None)
```

LegendasTV Archive.

Parameters

- **id** (*str*) – identifier.
- **name** (*str*) – name.
- **pack** (*bool*) – contains subtitles for multiple episodes.
- **pack** – featured.
- **link** (*str*) – link.
- **downloads** (*int*) – download count.
- **rating** (*int*) – rating (0-10).
- **timestamp** (*datetime.datetime*) – timestamp.

id = None
Identifier

name = None
Name

pack = None
Pack

featured = None
Featured

link = None
Link

downloads = None
Download count

rating = None
Rating (0-10)

timestamp = None
Timestamp

content = None

Compressed content as `rarfile.RarFile` or `zipfile.ZipFile`

```
class subliminal.providers.legendastv.LegendasTVSubtitle(language, type, title, year,  
imdb_id, season, archive,  
name)
```

LegendasTV Subtitle.

```
class subliminal.providers.legendastv.LegendasTVProvider(username=None, password=None)
```

LegendasTV Provider.

Parameters

- **username** (*str*) – username.
- **password** (*str*) – password.

```
search_titles(*arg, **kw)
```

Search for titles matching the *title*.

Parameters **title** (*str*) – the title to search for.

Returns found titles.

Return type `dict`

```
get_archives(*arg, **kw)
```

Get the archive list from a given *title_id* and *language_code*.

Parameters

- **title_id** (*int*) – title id.
- **language_code** (*int*) – language code.

Returns the archives.

Return type list of `LegendasTVArchive`

```
download_archive(archive)
```

Download an archive's *content*.

Parameters **archive** (`LegendasTVArchive`) – the archive to download *content* of.

2.4.3 NapiProjekt

```
subliminal.providers.napiprojekt.get_subhash(hash)
```

Get a second hash based on napiprojekt's hash.

Parameters **hash** (*str*) – napiprojekt's hash.

Returns the subhash.

Return type `str`

```
class subliminal.providers.napiprojekt.NapiProjektSubtitle(language, hash)
```

NapiProjekt Subtitle.

```
class subliminal.providers.napiprojekt.NapiProjektProvider
```

NapiProjekt Provider.

2.4.4 OpenSubtitles

```
class subliminal.providers.opensubtitles.OpenSubtitlesSubtitle (language,      hearing_impaired,
                                                                page_link,      subtitle_id, matched_by,
                                                                movie_kind,  hash,
                                                                movie_name,
                                                                movie_release_name,
                                                                movie_year,
                                                                movie_imdb_id,
                                                                series_season,
                                                                series_episode, file-
                                                                name, encoding)
```

OpenSubtitles Subtitle.

```
class subliminal.providers.opensubtitles.OpenSubtitlesProvider (username=None,
                                                                password=None)
```

OpenSubtitles Provider.

Parameters

- **username** (*str*) – username.
- **password** (*str*) – password.

```
exception subliminal.providers.opensubtitles.OpenSubtitlesError
```

Base class for non-generic *OpenSubtitlesProvider* exceptions.

```
exception subliminal.providers.opensubtitles.Unauthorized
```

Exception raised when status is ‘401 Unauthorized’.

```
exception subliminal.providers.opensubtitles.NoSession
```

Exception raised when status is ‘406 No session’.

```
exception subliminal.providers.opensubtitles.DownloadLimitReached
```

Exception raised when status is ‘407 Download limit reached’.

```
exception subliminal.providers.opensubtitles.InvalidImdbid
```

Exception raised when status is ‘413 Invalid ImdbID’.

```
exception subliminal.providers.opensubtitles.UnknownUserAgent
```

Exception raised when status is ‘414 Unknown User Agent’.

```
exception subliminal.providers.opensubtitles.DisabledUserAgent
```

Exception raised when status is ‘415 Disabled user agent’.

```
exception subliminal.providers.opensubtitles.ServiceUnavailable
```

Exception raised when status is ‘503 Service Unavailable’.

```
subliminal.providers.opensubtitles.checked (response)
```

Check a response status before returning it.

Parameters **response** – a response from a XMLRPC call to OpenSubtitles.

Returns the response.

Raise *OpenSubtitlesError*

2.4.5 Podnapisi

```
class subliminal.providers.podnapisi.PodnapisiSubtitle(language, hearing_impaired,  
                                                    page_link, pid, releases, title,  
                                                    season=None, episode=None,  
                                                    year=None)
```

Podnapisi Subtitle.

```
class subliminal.providers.podnapisi.PodnapisiProvider  
    Podnapisi Provider.
```

2.4.6 Shooter

```
class subliminal.providers.shooter.ShooterSubtitle(language, hash, download_link)  
    Shooter Subtitle.
```

```
class subliminal.providers.shooter.ShooterProvider  
    Shooter Provider.
```

2.4.7 SubsCenter

```
class subliminal.providers.subscenter.SubsCenterSubtitle(language, hearing_impaired,  
                                                         page_link, series, season,  
                                                         episode, title, subtitle_id,  
                                                         subtitle_key, downloaded,  
                                                         releases)
```

SubsCenter Subtitle.

```
class subliminal.providers.subscenter.SubsCenterProvider(username=None, password=None)  
    SubsCenter Provider.
```

```
__search_url_titles(*arg, **kw)  
    Search the URL titles by kind for the given title.
```

Parameters *title* (*str*) – title to search for.

Returns the URL titles by kind.

Return type `collections.defaultdict`

2.4.8 TheSubDB

```
class subliminal.providers.thesubdb.TheSubDBSubtitle(language, hash)  
    TheSubDB Subtitle.
```

```
class subliminal.providers.thesubdb.TheSubDBProvider  
    TheSubDB Provider.
```

2.4.9 TVsubtitles

```
class subliminal.providers.tvsubtitles.TVsubtitlesSubtitle(language, page_link, sub-  
                                                         title_id, series, season,  
                                                         episode, year, rip, re-  
                                                         lease)
```

TVsubtitles Subtitle.

class `subliminal.providers.tvsubtitles.TVsubtitlesProvider`
TVsubtitles Provider.

search_show_id (**arg, **kw*)
Search the show id from the *series* and *year*.

Parameters

- **series** (*str*) – series of the episode.
- **year** (*int*) – year of the series, if any.

Returns the show id, if any.

Return type `int`

get_episode_ids (**arg, **kw*)
Get episode ids from the show id and the season.

Parameters

- **show_id** (*int*) – show id.
- **season** (*int*) – season of the episode.

Returns episode ids per episode number.

Return type `dict`

2.5 Refiners

Refiners enrich a *Video* object by adding information to it.

A refiner is a simple function:

`subliminal.refiners.refine` (*video, **kwargs*)

Parameters

- **video** (*Video*) – the video to refine.
- ****kwargs** – additional parameters for refiners.

2.5.1 Metadata

`subliminal.refiners.metadata.refine` (*video, embedded_subtitles=True, **kwargs*)
Refine a video by searching its metadata.

Several *Video* attributes can be found:

- *resolution*
- *video_codec*
- *audio_codec*
- *subtitle_languages*

Parameters **embedded_subtitles** (*bool*) – search for embedded subtitles.

2.5.2 TVDB

`subliminal.refiners.tvdb.refine(video, **kwargs)`
 Refine a video by searching [TheTVDB](#).

Note: This refiner only work for instances of *Episode*.

Several attributes can be found:

- *series*
- *year*
- *series_imdb_id*
- *series_tvdb_id*
- *title*
- *imdb_id*
- *tvdb_id*

2.5.3 OMDb

`subliminal.refiners.omdb.refine(video, **kwargs)`
 Refine a video by searching [OMDb API](#).

Several *Episode* attributes can be found:

- *series*
- *year*
- *series_imdb_id*

Similarly, for a *Movie*:

- *title*
- *year*
- *imdb_id*

2.6 Extensions

class `subliminal.extensions.RegistrableExtensionManager(namespace, internal_extensions, **kwargs)`
 :class:`~stevedore.extensions.ExtensionManager` with support for registration.

It allows loading of internal extensions without setup and registering/unregistering additional extensions.

Loading is done in this order:

- Entry point extensions
- Internal extensions
- Registered extensions

Parameters

- **namespace** (*str*) – namespace argument for :class:`~stevedore.extensions.ExtensionManager`.
- **internal_extensions** (*list*) – internal extensions to use with entry point syntax.
- ****kwargs** – additional parameters for the :class:`~stevedore.extensions.ExtensionManager` constructor.

registered_extensions = None

Registered extensions with entry point syntax

internal_extensions = None

Internal extensions with entry point syntax

register (*entry_point*)

Register an extension

Parameters *entry_point* (*str*) – extension to register (entry point syntax).

Raise ValueError if already registered.

unregister (*entry_point*)

Unregister a provider

Parameters *entry_point* (*str*) – provider to unregister (entry point syntax).

`subliminal.extensions.provider_manager` = <subliminal.extensions.RegistrableExtensionManager object>
Provider manager

`subliminal.extensions.refiner_manager` = <subliminal.extensions.RegistrableExtensionManager object>
Refiner manager

2.7 Score

This module provides the default implementation of the `compute_score` parameter in `download_best_subtitles()` and `download_best_subtitles()`.

Note: To avoid unnecessary dependency on `sympy` and boost subliminal's import time, the resulting scores are hardcoded here and manually updated when the set of equations change.

Available matches:

- hash
- title
- year
- series
- season
- episode
- release_group
- format
- audio_codec
- resolution
- hearing_impaired

- `video_codec`
- `series_imdb_id`
- `imdb_id`
- `tvdb_id`

`subliminal.score.episode_scores = {'hash': 359, 'format': 7, 'series': 180, 'audio_codec': 3, 'year': 90, 'hearing_imp': 1}`
Scores for episodes

`subliminal.score.movie_scores = {'hash': 119, 'hearing_impaired': 1, 'audio_codec': 3, 'title': 60, 'video_codec': 2, 'year': 90}`
Scores for movies

`subliminal.score.get_scores(video)`
Get the scores dict for the given *video*.

This will return either *episode_scores* or *movie_scores* based on the type of the *video*.

Parameters `video` (*Video*) – the video to compute the score against.

Returns the scores dict.

Return type `dict`

`subliminal.score.compute_score(subtitle, video, hearing_impaired=None)`
Compute the score of the *subtitle* against the *video* with *hearing_impaired* preference.

compute_score() uses the *Subtitle.get_matches* method and applies the scores (either from *episode_scores* or *movie_scores*) after some processing.

Parameters

- **subtitle** (*Subtitle*) – the subtitle to compute the score of.
- **video** (*Video*) – the video to compute the score against.
- **hearing_impaired** (*bool*) – hearing impaired preference.

Returns score of the subtitle.

Return type `int`

2.8 Utils

`subliminal.utils.hash_opensubtitles(video_path)`
Compute a hash using OpenSubtitles' algorithm.

Parameters `video_path` (*str*) – path of the video.

Returns the hash.

Return type `str`

`subliminal.utils.hash_thesubdb(video_path)`
Compute a hash using TheSubDB's algorithm.

Parameters `video_path` (*str*) – path of the video.

Returns the hash.

Return type `str`

`subliminal.utils.hash_napiprojekt(video_path)`
Compute a hash using NapiProjekt's algorithm.

Parameters `video_path` (*str*) – path of the video.

Returns the hash.

Return type *str*

`subliminal.utils.hash_shooter` (*video_path*)

Compute a hash using Shooter’s algorithm

Parameters `video_path` (*string*) – path of the video

Returns the hash

Return type *string*

`subliminal.utils.sanitize` (*string*, *ignore_characters=None*)

Sanitize a string to strip special characters.

Parameters

- **string** (*str*) – the string to sanitize.
- **ignore_characters** (*set*) – characters to ignore.

Returns the sanitized string.

Return type *str*

`subliminal.utils.sanitize_release_group` (*string*)

Sanitize a *release_group* string to remove content in square brackets.

Parameters **string** (*str*) – the release group to sanitize.

Returns the sanitized release group.

Return type *str*

`subliminal.utils.timestamp` (*date*)

Get the timestamp of the *date*, python2/3 compatible

Parameters **date** (*datetime.datetime*) – the utc date.

Returns the timestamp of the date.

Return type *float*

2.9 Cache

`subliminal.cache.SHOW_EXPIRATION_TIME`

Expiration time for show caching

`subliminal.cache.EPISODE_EXPIRATION_TIME`

Expiration time for episode caching

`subliminal.cache.REFINER_EXPIRATION_TIME`

Expiration time for scraper searches

`subliminal.cache.region`

The *CacheRegion*

Refer to `dogpile.cache`’s [region configuration documentation](#) to see how to configure the region

2.10 CLI

Subliminal uses `click` to provide a powerful CLI.

class `subliminal.cli.MutexLock (filename)`

`MutexLock` is a thread-based rw lock based on `dogpile.core.ReadWriteMutex`.

class `subliminal.cli.Config (path)`

A `ConfigParser` wrapper to store configuration.

Interaction with the configuration is done with the properties.

Parameters `path (str)` – path to the configuration file.

path = None

Path to the configuration file

config = None

The underlying configuration object

read ()

Read the configuration from `path`

write ()

Write the configuration to `path`

class `subliminal.cli.LanguageParamType`

`ParamType` for languages that returns a `Language`

class `subliminal.cli.AgeParamType`

`ParamType` for age strings that returns a `timedelta`

An age string is in the form *number + identifier* with possible identifiers:

- w for weeks
- d for days
- h for hours

The form can be specified multiple times but only with that identifier ordering. For example:

- 1w2d4h for 1 week, 2 days and 4 hours
- 2w for 2 weeks
- 3w6h for 3 weeks and 6 hours

2.11 Exceptions

exception `subliminal.exceptions.Error`

Base class for exceptions in subliminal.

exception `subliminal.exceptions.ProviderError`

Exception raised by providers.

exception `subliminal.exceptions.ConfigurationError`

Exception raised by providers when badly configured.

exception `subliminal.exceptions.AuthenticationError`

Exception raised by providers when authentication failed.

exception `subliminal.exceptions.TooManyRequests`

Exception raised by providers when too many requests are made.

exception `subliminal.exceptions.DownloadLimitExceeded`

Exception raised by providers when download limit is exceeded.

License

MIT

Indices and tables

- `genindex`
- `modindex`
- `search`

S

- `subliminal.cache`, 30
- `subliminal.cli`, 31
- `subliminal.core`, 11
- `subliminal.exceptions`, 31
- `subliminal.extensions`, 27
- `subliminal.providers`, 19
 - `addic7ed`, 21
 - `legendastv`, 22
 - `napiprojekt`, 23
 - `opensubtitles`, 24
 - `podnapisi`, 25
 - `shooter`, 25
 - `subscenter`, 25
 - `thesubdb`, 25
 - `tvsubtitles`, 25
- `subliminal.refiners`, 26
- `subliminal.score`, 28
- `subliminal.subtitle`, 18
- `subliminal.utils`, 29
- `subliminal.video`, 15

Symbols

`_get_show_ids()` (subliminal.providers.addic7ed.Addic7edProvider method), 21

`_search_show_id()` (subliminal.providers.addic7ed.Addic7edProvider method), 21

`_search_url_titles()` (subliminal.providers.subscenter.SubsCenterProvider method), 25

A

`Addic7edProvider` (class in subliminal.providers.addic7ed), 21

`Addic7edSubtitle` (class in subliminal.providers.addic7ed), 21

`age` (subliminal.video.Video attribute), 16

`AgeParamType` (class in subliminal.cli), 31

`ARCHIVE_EXTENSIONS` (in module subliminal.core), 11

`AsyncProviderPool` (class in subliminal.core), 12

`audio_codec` (subliminal.video.Video attribute), 16

`AuthenticationError`, 31

C

`check()` (subliminal.providers.Provider class method), 20

`check_video()` (in module subliminal.core), 12

`checked()` (in module subliminal.providers.opensubtitles), 24

`compute_score()` (in module subliminal.score), 29

`Config` (class in subliminal.cli), 31

`config` (subliminal.cli.Config attribute), 31

`ConfigurationError`, 31

`content` (subliminal.providers.legendastv.LegendasTVArchive attribute), 23

`content` (subliminal.subtitle.Subtitle attribute), 18

D

`DisabledUserAgent`, 24

`discarded_providers` (subliminal.core.ProviderPool attribute), 11

`download_archive()` (subliminal.providers.legendastv.LegendasTVProvider method), 23

`download_best_subtitles()` (in module subliminal.core), 14

`download_best_subtitles()` (subliminal.core.ProviderPool method), 12

`download_subtitle()` (subliminal.core.ProviderPool method), 12

`download_subtitle()` (subliminal.providers.Provider method), 21

`download_subtitles()` (in module subliminal.core), 14

`DownloadLimitExceeded`, 32

`DownloadLimitReached`, 24

`downloads` (subliminal.providers.legendastv.LegendasTVArchive attribute), 22

`downloads_re` (in module subliminal.providers.legendastv), 22

E

`encoding` (subliminal.subtitle.Subtitle attribute), 18

`Episode` (class in subliminal.video), 17

`episode` (subliminal.video.Episode attribute), 17

`EPISODE_EXPIRATION_TIME` (in module subliminal.cache), 30

`episode_scores` (in module subliminal.score), 29

`Error`, 31

`exists` (subliminal.video.Video attribute), 16

F

`featured` (subliminal.providers.legendastv.LegendasTVArchive attribute), 22

`fix_line_ending()` (in module subliminal.subtitle), 19

`format` (subliminal.video.Video attribute), 16

`fromguess()` (subliminal.video.Video class method), 16

`fromname()` (subliminal.video.Video class method), 16

G

get_archives() (subliminal.providers.legendastv.LegendasTVProvider method), 23

get_episode_ids() (subliminal.providers.tvsubtitles.TVsubtitlesProvider method), 26

get_matches() (subliminal.subtitle.Subtitle method), 18

get_scores() (in module subliminal.score), 29

get_show_id() (subliminal.providers.addic7ed.Addic7edProvider method), 21

get_subhash() (in module subliminal.providers.napiprojekt), 23

get_subtitle_path() (in module subliminal.subtitle), 19

guess_encoding() (subliminal.subtitle.Subtitle method), 18

guess_matches() (in module subliminal.subtitle), 19

H

hash_napiprojekt() (in module subliminal.utils), 29

hash_opensubtitles() (in module subliminal.utils), 29

hash_shooter() (in module subliminal.utils), 30

hash_thesubdb() (in module subliminal.utils), 29

hashes (subliminal.video.Video attribute), 16

hearing_impaired (subliminal.subtitle.Subtitle attribute), 18

I

id (subliminal.providers.legendastv.LegendasTVArchive attribute), 22

id (subliminal.subtitle.Subtitle attribute), 18

imdb_id (subliminal.video.Video attribute), 16

initialize() (subliminal.providers.Provider method), 20

initialized_providers (subliminal.core.ProviderPool attribute), 11

internal_extensions (subliminal.extensions.RegistrableExtensionManager attribute), 28

InvalidImdbid, 24

is_valid() (subliminal.subtitle.Subtitle method), 18

L

language (subliminal.subtitle.Subtitle attribute), 18

LanguageParamType (class in subliminal.cli), 31

languages (subliminal.providers.Provider attribute), 20

LegendasTVArchive (class in subliminal.providers.legendastv), 22

LegendasTVProvider (class in subliminal.providers.legendastv), 23

LegendasTVSubtitle (class in subliminal.providers.legendastv), 23

link (subliminal.providers.legendastv.LegendasTVArchive attribute), 22

list_subtitles() (in module subliminal.core), 14

list_subtitles() (subliminal.core.ProviderPool method), 12

list_subtitles() (subliminal.providers.Provider method), 20

list_subtitles_provider() (subliminal.core.ProviderPool method), 11

M

max_workers (subliminal.core.AsyncProviderPool attribute), 12

Movie (class in subliminal.video), 17

movie_scores (in module subliminal.score), 29

MutexLock (class in subliminal.cli), 31

N

name (subliminal.providers.legendastv.LegendasTVArchive attribute), 22

name (subliminal.video.Video attribute), 16

NapiProjektProvider (class in subliminal.providers.napiprojekt), 23

NapiProjektSubtitle (class in subliminal.providers.napiprojekt), 23

NoSession, 24

O

OpenSubtitlesError, 24

OpenSubtitlesProvider (class in subliminal.providers.opensubtitles), 24

OpenSubtitlesSubtitle (class in subliminal.providers.opensubtitles), 24

original_series (subliminal.video.Episode attribute), 17

P

pack (subliminal.providers.legendastv.LegendasTVArchive attribute), 22

page_link (subliminal.subtitle.Subtitle attribute), 18

ParserBeautifulSoup (class in subliminal.providers), 19

path (subliminal.cli.Config attribute), 31

PodnapisiProvider (class in subliminal.providers.podnapisi), 25

PodnapisiSubtitle (class in subliminal.providers.podnapisi), 25

Provider (class in subliminal.providers), 19

provider_configs (subliminal.core.ProviderPool attribute), 11

provider_manager (in module subliminal.extensions), 28

provider_name (subliminal.subtitle.Subtitle attribute), 18

ProviderError, 31

ProviderPool (class in subliminal.core), 11

providers (subliminal.core.ProviderPool attribute), 11

Q

query() (subliminal.providers.Provider method), 20

R

rating (subliminal.providers.legendastv.LegendasTVArchive attribute), 22

rating_re (in module subliminal.providers.legendastv), 22

read() (subliminal.cli.Config method), 31

refine() (in module subliminal.core), 14

refine() (in module subliminal.refiners), 26

refine() (in module subliminal.refiners.metadata), 26

refine() (in module subliminal.refiners.omdb), 27

refine() (in module subliminal.refiners.tvdb), 27

REFINER_EXPIRATION_TIME (in module subliminal.cache), 30

refiner_manager (in module subliminal.extensions), 28

region (in module subliminal.cache), 30

register() (subliminal.extensions.RegistrableExtensionManager method), 28

registered_extensions (subliminal.extensions.RegistrableExtensionManager attribute), 28

RegistrableExtensionManager (class in subliminal.extensions), 27

release_group (subliminal.video.Video attribute), 16

releases_key (in module subliminal.providers.legendastv), 22

required_hash (subliminal.providers.Provider attribute), 20

resolution (subliminal.video.Video attribute), 16

S

sanitize() (in module subliminal.utils), 30

sanitize_release_group() (in module subliminal.utils), 30

save_subtitles() (in module subliminal.core), 15

scan_archive() (in module subliminal.core), 13

scan_video() (in module subliminal.core), 13

scan_videos() (in module subliminal.core), 13

search_external_subtitles() (in module subliminal.core), 13

search_show_id() (subliminal.providers.tvsubtitles.TVsubtitlesProvider method), 26

search_titles() (subliminal.providers.legendastv.LegendasTVProvider method), 23

season (subliminal.video.Episode attribute), 17

season_re (in module subliminal.providers.legendastv), 22

series (subliminal.video.Episode attribute), 17

series_imdb_id (subliminal.video.Episode attribute), 17

series_tvdb_id (subliminal.video.Episode attribute), 17

series_year_re (in module subliminal.providers.addic7ed), 21

ServiceUnavailable, 24

ShooterProvider (class in subliminal.providers.shooter), 25

ShooterSubtitle (class in subliminal.providers.shooter), 25

SHOW_EXPIRATION_TIME (in module subliminal.cache), 30

size (subliminal.video.Video attribute), 16

subliminal.cache (module), 30

subliminal.cli (module), 31

subliminal.core (module), 11

subliminal.exceptions (module), 31

subliminal.extensions (module), 27

subliminal.providers (module), 19

subliminal.providers.addic7ed (module), 21

subliminal.providers.legendastv (module), 22

subliminal.providers.napiprojekt (module), 23

subliminal.providers.opensubtitles (module), 24

subliminal.providers.podnapisi (module), 25

subliminal.providers.shooter (module), 25

subliminal.providers.subscenter (module), 25

subliminal.providers.thesubdb (module), 25

subliminal.providers.tvsubtitles (module), 25

subliminal.refiners (module), 26

subliminal.score (module), 28

subliminal.subtitle (module), 18

subliminal.utils (module), 29

subliminal.video (module), 15

SubsCenterProvider (class in subliminal.providers.subscenter), 25

SubsCenterSubtitle (class in subliminal.providers.subscenter), 25

Subtitle (class in subliminal.subtitle), 18

SUBTITLE_EXTENSIONS (in module subliminal.subtitle), 18

subtitle_languages (subliminal.video.Video attribute), 16

T

terminate() (subliminal.core.ProviderPool method), 12

terminate() (subliminal.providers.Provider method), 20

text (subliminal.subtitle.Subtitle attribute), 18

TheSubDBProvider (class in subliminal.providers.thesubdb), 25

TheSubDBSubtitle (class in subliminal.providers.thesubdb), 25

TimeoutSafeTransport (class in subliminal.providers), 19

timestamp (subliminal.providers.legendastv.LegendasTVArchive attribute), 22

timestamp() (in module subliminal.utils), 30

timestamp_re (in module subliminal.providers.legendastv), 22

title (subliminal.video.Episode attribute), 17

title (subliminal.video.Movie attribute), 17

TooManyRequests, 31

tvdb_id (subliminal.video.Episode attribute), 17

TVsubtitlesProvider (class in subliminal.providers.tvsubtitles), 26

TVsubtitlesSubtitle (class in subliminal.providers.tvsubtitles), 25
type_map (in module subliminal.providers.legendastv), 22

U

Unauthorized, 24
UnknownUserAgent, 24
unregister() (subliminal.extensions.RegistrableExtensionManager method), 28

V

Video (class in subliminal.video), 15
video_codec (subliminal.video.Video attribute), 16
VIDEO_EXTENSIONS (in module subliminal.video), 15
video_types (subliminal.providers.Provider attribute), 20

W

write() (subliminal.cli.Config method), 31

Y

year (subliminal.video.Episode attribute), 17
year (subliminal.video.Movie attribute), 17