
thorod

Release 2.1.0

thebigmunch

May 01, 2020

CONTENTS

1	Command-Line Interface	1
1.1	Options	1
1.2	Commands	1
1.3	Sub-commands:	1

COMMAND-LINE INTERFACE

Use `-h`, `--help` to display the help for any command.

Collection of torrent utilities.

1.1 Options

`-V, --version` Output version.

1.2 Commands

`<command>` Possible choices: abbrs, create, info, magnet, xseed

1.3 Sub-commands:

1.3.1 abbrs

List/Add/Remove tracker abbreviations.

Options

`-V, --version` Output version.

Commands

<subcommand> Possible choices: list, add, remove

Sub-commands:

list

List tracker abbreviations.

Options

-V, --version Output version.

add

Add tracker abbreviations.

```
thorod abbrs add [ABBREVIATION] [TRACKER]
```

Positional Arguments

ABBREVIATION Abbreviation to use for tracker.

TRACKER Tracker to abbreviate.

Options

-V, --version Output version.

remove

Remove tracker abbreviations.

```
thorod abbrs remove [ABBREVIATIONS]...
```

Positional Arguments

ABBREVIATIONS Abbreviations to remove.

Options

-V, --version Output version.

1.3.2 create

Create a torrent file.

```
thorod create [OPTIONS] [PATH] [TRACKERS]...
```

Options

-V, --version Output version.

Show

--show-progress Show hashing progress bar.
--hide-progress Hide hashing progress bar.
--show-files Show files in the summary.
--hide-files Don't show files in the summary.

Local

--no-recursion Disable recursion when scanning for local files. Recursion is enabled by default.
--max-depth Set maximum depth of recursion when scanning for local files. Default is infinite recursion.
-xp, --exclude-path Exclude filepaths. Can be specified multiple times.
-xr, --exclude-regex Exclude filepaths using regular expressions. Can be specified multiple times.
-xg, --exclude-glob Exclude filepaths using glob patterns. Can be specified multiple times. Absolute glob patterns not supported.

Filter

--created-in Include items created in year or year/month.
--created-on Include items created on date.
--created-before Include items created before datetime.
--created-after Include items created after datetime.
--modified-in Include items created in year or year/month.
--modified-on Include items created on date.

- | | |
|--------------------------|---|
| --modified-before | Include items modified before datetime. |
| --modified-after | Include items modified after datetime. |

Torrent

- | | |
|--------------------------|--|
| --piece-size | Set piece size. Defaults to automatic calculation. (16k, 32k, 64k, 128k, 256k, 512k, 1m, 2m, 4m, 8m, 16m, 32m, auto) |
| --piece-threshold | Set piece count threshold for automatic piece size calculation. Defaults to 2000. |
| --created-by | Set created by field. Defaults to 'thorod 2.1.0'. |
| -c, --comment | Set comment field. |
| -p, --private | Make torrent private. |
| -P, --public | Make torrent public. |
| -s, --source | Set source field. |
| --md5 | Add md5 hash to info dict. |

Output

- | | |
|---------------------|---|
| -o, --output | Set name of torrent file. Defaults to input file or directory name. |
|---------------------|---|

Input

- | | |
|-------------|--------------------|
| PATH | File or directory. |
|-------------|--------------------|

Trackers

- | | |
|-----------------|---|
| TRACKERS | Tracker tiers are separated by a space. Trackers on the same tier are separated with a carat (^)
Example: 'tracker1^tracker2' tracker3 |
|-----------------|---|

1.3.3 info

Output information about a torrent file.

```
thorod info [OPTIONS] [TORRENT]
```

Options

- | | |
|----------------------|-----------------|
| -V, --version | Output version. |
|----------------------|-----------------|

Show

- show-files** Show files in the summary.
- hide-files** Don't show files in the summary.

Input

- TORRENT** Torrent file.

1.3.4 magnet

Generate a magnet link from a torrent file.

```
thorod magnet [OPTIONS] [TORRENT]
```

Options

- V, --version** Output version.

Input

- TORRENT** Torrent file.

1.3.5 xseed

Copy a torrent for cross-seeding.

```
thorod xseed [OPTIONS] [TORRENT]
```

Options

- V, --version** Output version.

Torrent

- piece-size** Set piece size. Defaults to automatic calculation. (16k, 32k, 64k, 128k, 256k, 512k, 1m, 2m, 4m, 8m, 16m, 32m, auto)
- piece-threshold** Set piece count threshold for automatic piece size calculation. Defaults to 2000.
- created-by** Set created by field. Defaults to 'thorod 2.1.0'.
- c, --comment** Set comment field.
- p, --private** Make torrent private.
- P, --public** Make torrent public.
- s, --source** Set source field.
- md5** Add md5 hash to info dict.

Output

-o, --output Set name of torrent file. Defaults to input file or directory name.

Input

TORRENT Torrent file.

Trackers

TRACKERS Tracker tiers are separated by a space. Trackers on the same tier are separated with a carat (^)
Example: 'tracker1^tracker2' tracker3