
tsuru Documentation

Release 0.1

timeredbull

June 25, 2014

1	Using Tsuru	1
1.1	Application Deployment	1
1.2	CLI	1
1.3	Services	1
2	Running Tsuru	3
2.1	Deploy Tsuru	3
2.2	Services	3
3	Get Involved	5
3.1	API reference	5
3.2	Build your own PaaS	17
3.3	community	20
3.4	Configuring tsuru	20
3.5	contribute	29
3.6	Build your own PaaS with tsuru and Docker	30
3.7	Build your own PaaS with tsuru and Docker on Centos	33
3.8	Download	36
3.9	Tsuru Frequently Asked Questions	37
3.10	Tsuru Overview	39
3.11	Why Tsuru?	41
3.12	Deployment hooks	43
3.13	Application Deployment	44
3.14	Building your app in tsuru	45
3.15	Coding style	46
3.16	Setting up you tsuru development environment	47
3.17	Installing tsuru clients	49
3.18	Howto install a dns forwarder	51
3.19	Backing up tsuru database	53
3.20	Server installation guide	54
3.21	api workflow	54
3.22	Building your service	57
3.23	HOWTO Install a MySQL service	60
3.24	Crane usage	62
3.25	Services	63
3.26	Client usage	64
3.27	Deploying PHP applications in tsuru	66
3.28	Deploying Python applications in tsuru	71

3.29	Deploying Ruby applications in tsuru	80
3.30	Docker Provisioner Architecture	87

Using Tsuru

- *Why Tsuru?*.
- *Overview*
- *FAQ*.

1.1 Application Deployment

- *building your application*
- *python/django*
- *ruby/rails*
- *php*
- *understanding deployment hooks*

1.2 CLI

- *clients installation guide*
- *Tsuru client usage guide*

1.3 Services

- *using services*

Running Tsuru

2.1 Deploy Tsuru

- *Tsuru and juju*
- *docker provisioner architecture*
- *Tsuru and docker on ubuntu*
- *Tsuru and docker on centos*
- *configuration*
- *backing up Tsuru*
- *api reference*

2.2 Services

- *building your service*
- *crane usage guide*
- *services api workflow*

Get Involved

- *how to contribute*
- *coding style*
- *setting up your development environment*
- *community*

3.1 API reference

3.1.1 1. Endpoints

1.1 Apps

List apps

- Method: GET
- URI: /apps
- Format: json

Returns 200 in case of success, and json in the body of the response containing the app list.

Example:

```
GET /apps HTTP/1.1
Content-Length: 82
[{"Ip": "10.10.10.10", "Name": "app1", "Units": [{"Name": "app1/0", "State": "started"}]}
```

Info about an app

- Method: GET
- URI: /apps/:appname
- Format: json

Returns 200 in case of success, and a json in the body of the response containing the app content.

Example:

```
GET /apps/myapp HTTP/1.1
Content-Length: 284
{"Name": "app1", "Framework": "php", "Repository": "git@git.com:php.git", "State": "dead", "Units": [{"Ip": "192.168.1.1"}]}
```

Remove an app

- Method: DELETE
- URI: /apps/:appname

Returns 200 in case of success.

Example:

```
DELETE /apps/myapp HTTP/1.1
```

Create an app

- Method: POST
- URI: /apps
- Format: json

Returns 200 in case of success, and json in the body of the response containing the status and the url for git repository.

Example:

```
POST /apps HTTP/1.1
{"status": "success", "repository_url": "git@tsuru.plataformas.glb.com:ble.git"}
```

Restart an app

- Method: GET
- URI: /apps/<appname>/restart

Returns 200 in case of success.

Example:

```
GET /apps/myapp/restart HTTP/1.1
```

Get app environment variables

- Method: GET
- URI: /apps/<appname>/env

Returns 200 in case of success, and json in the body returning a dictionary with environment names and values..

Example:

```
GET /apps/myapp/env HTTP/1.1
{"DATABASE_HOST": "localhost"}
```

Set an app enviroment

- Method: POST
- URI: /apps/<appname>/env

Returns 200 in case of success.

Example:

```
POST /apps/myapp/env HTTP/1.1
```

Delete an app enviroment

- Method: DELETE
- URI: /apps/<appname>/env

Returns 200 in case of success.

Example:

```
DELETE /apps/myapp/env HTTP/1.1
```

Swapping two apps

- Method: PUT
- URI: /swap?app1=appname&app2=anotherapp

Returns 200 in case of success.

Example:

```
PUT /swap?app1=myapp&app2=anotherapp
```

1.2 Services

List services

- Method: GET
- URI: /services
- Format: json

Returns 200 in case of success.

Example:

```
GET /services HTTP/1.1
Content-Length: 67
{"service": "mongodb", "instances": ["my_nosql", "other-instance"]}
```

Create a new service

- Method: POST
- URI: /services
- Format: yaml
- Body: a yaml with the service metadata.

Returns 200 in case of success. Returns 403 if the user is not a member of a team. Returns 500 if the yaml is invalid. Returns 500 if the service name already exists.

Example:

```
POST /services HTTP/1.1
Body:
  `id: some_service
endpoint:
  production: someservice.com`
```

Remove a service

- Method: DELETE
- URI: /services/<servicename>

Returns 204 in case of success. Returns 403 if user has not access to the server. Returns 403 if service has instances. Returns 404 if service is not found.

Example:

```
DELETE /services/mongodb HTTP/1.1
```

Update a service

- Method: PUT
- URI: /services
- Format: yaml
- Body: a yaml with the service metadata.

Returns 200 in case of success. Returns 403 if the user is not a member of a team. Returns 500 if the yaml is invalid. Returns 500 if the service name already exists.

Example:

```
PUT /services HTTP/1.1
Body:
  `id: some_service
endpoint:
  production: someservice.com`
```

Get info about a service

- Method: GET

- URI: /services/<servicename>
- Format: json

Returns 200 in case of success. Returns 404 if the service does not exists.

Example:

```
GET /services/mongodb HTTP/1.1
[{"Name": "my-mongo", "Teams": ["myteam"], "Apps": ["myapp"], "ServiceName": "mongodb"}]
```

Get service documentation

- Method: GET
- URI: /services/<servicename>/doc
- Format: text

Returns 200 in case of success. Returns 404 if the service does not exists.

Example:

```
GET /services/mongodb/doc HTTP/1.1
Mongodb exports the ...
```

Update service documentation

- Method: PUT
- URI: /services/<servicename>/doc
- Format: text
- Body: text with the documentation

Returns 200 in case of success. Returns 404 if the service does not exists.

Example:

```
PUT /services/mongodb/doc HTTP/1.1
Body: Mongodb exports the ...
```

Grant access to a service

- Method: PUT
- URI: /services/<servicename>/<teamname>

Returns 200 in case of success. Returns 404 if the service does not exists.

Example:

```
PUT /services/mongodb/cobrateam HTTP/1.1
```

Revoke access from a service

- Method: DELETE
- URI: /services/<servicename>/<teamname>

Returns 200 in case of success. Returns 404 if the service does not exists.

Example:

```
DELETE /services/mongodb/cobrateam HTTP/1.1
```

1.3 Service instances

Add a new service instance

- Method: POST
- URI: /services/instances
- Body: `{"name": "mymysql": "service_name": "mysql"}`

Returns 200 in case of success. Returns 404 if the service does not exists.

Example:

```
POST /services/instances HTTP/1.1
{"name": "mymysql": "service_name": "mysql"}
```

Remove a service instance

- Method: DELETE
- URI: /services/instances/<serviceinstancename>

Returns 200 in case of success. Returns 404 if the service does not exists.

Example:

```
DELETE /services/instances/mymysql HTTP/1.1
```

Bind a service instance with an app

- Method: PUT
- URI: /services/instances/<serviceinstancename>/<appname>
- Format: json

Returns 200 in case of success, and json with the enviroment variables to be exported in the app environ. Returns 403 if the user has not access to the app. Returns 404 if the application does not exists. Returns 404 if the service instance does not exists.

Example:

```
PUT /services/instances/mymysql/myapp HTTP/1.1
Content-Length: 29
{"DATABASE_HOST": "localhost"}
```

Unbind a service instance with an app

- Method: DELETE
- URI: /services/instances/<serviceinstancename>/<appname>

Returns 200 in case of success. Returns 403 if the user has not access to the app. Returns 404 if the application does not exists. Returns 404 if the service instance does not exists.

Example:

```
DELETE /services/instances/mymysql/myapp HTTP/1.1
```

List all services and your instances

- Method: GET
- URI: /services/instances
- Format: json

Returns 200 in case of success and a json with the service list.

Example:

```
GET /services/instances HTTP/1.1
Content-Length: 52
[{"service": "redis", "instances": ["redis-globo"]}]
```

Get an info about a service instance

- Method: GET
- URI: /services/instances/<serviceinstancename>
- Format: json

Returns 200 in case of success and a json with the service instance data. Returns 404 if the service instance does not exists.

Example:

```
GET /services/instances/mymysql HTTP/1.1
Content-Length: 71
{"name": "mongo-1", "servicename": "mongodb", "teams": [], "apps": []}
```

service instance status

- Method: GET
- URI: /services/instances/<serviceinstancename>/status

Returns 200 in case of success.

Example:

```
GET /services/instances/mymysql/status HTTP/1.1
```

1.4 Quotas

Get quota info of an user

- Method: GET
- URI: /quota/<user>
- Format: json

Returns 200 in case of success, and json with the quota info.

Example:

```
GET /quota/wolverine HTTP/1.1
Content-Length: 29
{"items": 10, "available": 2}
```

1.5 Healers

List healers

- Method: GET
- URI: /healers
- Format: json

Returns 200 in case of success, and json in the body with a list of healers.

Example:

```
GET /healers HTTP/1.1
Content-Length: 35
[{"app-heal": "http://healer.com"}]
```

Execute healer

- Method: GET
- URI: /healers/<healer>

Returns 200 in case of success.

Example:

```
GET /healers/app-heal HTTP/1.1
```

1.6 Platforms

List platforms

- Method: GET
- URI: /platforms
- Format: json

Returns 200 in case of success, and json in the body with a list of platforms.

Example:

```
GET /platforms HTTP/1.1
Content-Length: 67
[{Name: "python"}, {Name: "java"}, {Name: "ruby20"}, {Name: "static"}]
```

1.7 Users

Create an user

- Method: POST
- URI: /users
- Body: `{"email": "nobody@globo.com", "password": "123456"}`

Returns 200 in case of success. Returns 400 if the json is invalid. Returns 400 if the email is invalid. Returns 400 if the password characters length is less than 6 and greater than 50. Returns 409 if the email already exists.

Example:

```
POST /users HTTP/1.1
Body: `{"email": "nobody@globo.com", "password": "123456"}`
```

Reset password

- Method: POST
- URI: /users/<email>/password?token=token

Returns 200 in case of success. Returns 404 if the user is not found.

The token parameter is optional.

Example:

```
POST /users/user@email.com/password?token=1234 HTTP/1.1
```

Login

- Method: POST
- URI: /users/<email>/tokens
- Body: `{"password": "123456"}`

Returns 200 in case of success. Returns 400 if the json is invalid. Returns 400 if the password is empty or nil. Returns 404 if the user is not found.

Example:

```
POST /users/user@email.com/tokens HTTP/1.1
```

Logout

- Method: DELETE
- URI: /users/tokens

Returns 200 in case of success.

Example:

```
DELETE /users/tokens HTTP/1.1
```

Change password

- Method: PUT
- URI: /users/password
- Body: `{ "old": "123456", "new": "654321" }`

Returns 200 in case of success. Returns 400 if the json is invalid. Returns 400 if the old or new password is empty or nil. Returns 400 if the new password characters length is less than 6 and greater than 50. Returns 403 if the old password does not match with the current password.

Example:

```
PUT /users/password HTTP/1.1
Body: `{"old": "123456", "new": "654321"}`
```

Remove an user

- Method: DELETE
- URI: /users

Returns 200 in case of success.

Example:

```
DELETE /users HTTP/1.1
```

Add public key to user

- Method: POST
- URI: /users/keys
- Body: `{ "key": "my-key" }`

Returns 200 in case of success.

Example:

```
POST /users/keys HTTP/1.1
Body: `{"key": "my-key"}`
```

Remove public key from user

- Method: DELETE
- URI: /users/keys
- Body: `{ "key": "my-key" }`

Returns 200 in case of success.

Example:

```
DELETE /users/keys HTTP/1.1
Body:  `{"key":"my-key"}`
```

1.8 Teams

List teams

- Method: GET
- URI: /teams
- Format: json

Returns 200 in case of success, and json in the body with a list of teams.

Example:

```
GET /teams HTTP/1.1
Content-Length: 22
[{"name": "teamname"}]
```

Info about a team

- Method: GET
- URI: /teams/<teamname>
- Format: json

Returns 200 in case of success, and json in the body with the info about a team.

Example:

```
GET /teams/teamname HTTP/1.1
{"name": "teamname", "users": ["user@email.com"]}
```

Add a team

- Method: POST
- URI: /teams

Returns 200 in case of success.

Example:

```
POST /teams HTTP/1.1
```

Remove a team

- Method: DELETE
- URI: /teams/<teamname>

Returns 200 in case of success.

Example:

```
DELETE /teams/myteam HTTP/1.1
```

Add user to team

- Method: PUT
- URI: /teams/<teamname>/<username>

Returns 200 in case of success.

Example:

```
PUT /teams/myteam/myuser HTTP/1.1
```

Remove user from team

- Method: DELETE
- URI: /teams/<teamname>/<username>

Returns 200 in case of success.

Example:

```
DELETE /teams/myteam/myuser HTTP/1.1
```

1.9 Tokens

Generate app token

- Method: POST
- URI: /tokens
- Format: json

Returns 200 in case of success, with the token in the body.

Example:

```
POST /tokens HTTP/1.1
{
    "Token": "sometoken",
    "Creation": "2001/01/01",
    "Expires": 1000,
```

```
    "AppName": "appname",  
}
```

3.2 Build your own PaaS

This document describes how to create a private PaaS service using tsuru. It contains instructions on how to build tsuru and some of its components from source.

This document assumes that tsuru is being installed on a Ubuntu machine. You can use equivalent packages for beanstalkd, git, MongoDB and other tsuru dependencies. Please make sure you satisfy minimal version requirements.

There's also a contributed [Vagrant](https://github.com/hfeeki/vagrant-tsuru) box, that setups a PaaS using [Chef](#). You can check this out: <https://github.com/hfeeki/vagrant-tsuru>.

3.2.1 Overview

The Tsuru PaaS is composed by multiple components:

- tsuru server
- tsuru collector
- gandalf
- charms

And these components have their own dependencies, like:

- mongodb ($\geq 2.2.0$)
- beanstalkd ($\geq 1.4.6$)
- git-daemon (git ≥ 1.7)
- juju (python version, ≥ 0.5)
- libyaml ($\geq 0.1.4$)

3.2.2 Requirements

1. Operating System

The steps below will guide you through the install process on Ubuntu Server 12.04.

If you try to build tsuru server on most Linux systems, you should have few problems and if there are problems, we are able to help you. Just ask on #tsuru channel on irc.freenode.net.

- *Have you tried tsuru server on other systems? Let us know and [contribute](#) to the project.*

2. Hardware

Tsuru server is a lightweight framework and can be run in a single small machine along with all the deps.

3. Software

3.1 MongoDB

Tsuru needs MongoDB stable, distributed by 10gen. It's pretty easy to get it running on Ubuntu

3.2 Juju

Tsuru uses juju to orchestrates your “apps”. To install juju follow the [juju install guide](#). Please make sure that you [configure Juju](#) properly. Then run:

```
$ juju bootstrap
```

Juju Charms define how platforms will be installed. You may take a look at [juju charms collection](#) or use the [charms provided by tsuru](#)

Put it somewhere and define the setting `juju:charms-path` in the configuration file:

```
$ git clone git://github.com/globocom/charms.git /home/me/charms
$ cat /etc/tsuru/tsuru.conf
# ...
juju:
    charms-path: /home/me/charms
```

3.3 Beanstalkd

Tsuru uses [Beanstalkd](#) as a work queue. Install the latest version, by doing this:

```
$ sudo apt-get install -y beanstalkd
```

3.4 Gandalf

Tsuru uses [Gandalf](#) to manage git repositories, to get it installed [follow this steps](#)

3.2.3 Installing from PPA

You can use `apt-get` to install Gandalf using [Tsuru's ppa](#):

```
$ sudo apt-add-repository ppa:tsuru/ppa -y
$ sudo apt-get update
$ sudo apt-get install tsuru-server
```

Then you will need to edit the file `/etc/default/tsuru-server` and enable the API and the collector:

```
TSR_API_ENABLED=yes
TSR_COLLECTOR_ENABLED=yes
```

Make sure you edit the configuration file (see [Configuring tsuru](#)) and then start API and collector using `upstart`:

```
$ sudo start tsuru-server-api
$ sudo start tsuru-server-collector
```

3.2.4 Installing pre-built binaries

You can download pre-built binaries of tsuru and collector. There are binaries available only for Linux 64 bits, so make sure that `uname -m` prints `x86_64`:

```
$ uname -m
x86_64
```

Then download and install the `tsr` binary:

```
$ curl -sL https://s3.amazonaws.com/tsuru/dist-server/tsr-master.tar.gz | sudo tar -xz -C /usr/bin
```

These commands will install `tsr` in `/usr/bin` (you will need to be a sudoer and provide your password). You may install this command in your `PATH`.

3.2.5 Installing from source

0. Build dependencies

To build `tsuru` from source you will need to install the following packages

```
$ sudo apt-get install -y golang-go git mercurial bzr gcc
```

1. Install the `tsuru tsr`

Add the following lines to your `~/.bashrc`:

```
$ export GOPATH=/home/ubuntu/.go
$ export PATH=${GOPATH}/bin:${PATH}
```

Then execute:

```
$ source ~/.bashrc
$ go get github.com/globocom/tsuru/tsr
```

3.2.6 Configuring `tsuru`

Before running `tsuru`, you must configure it. By default, `tsuru` will look for the configuration file in the `/etc/tsuru/tsuru.conf` path. You can check a sample configuration file and documentation for each `tsuru` setting in the “*Configuring `tsuru`*” page.

You can download the sample configuration file from Github:

```
$ [sudo] mkdir /etc/tsuru
$ [sudo] curl -sL https://raw.githubusercontent.com/globocom/tsuru/master/etc/tsuru.conf -o /etc/tsuru/tsuru.conf
```

Make sure you define the required settings (database connection, authentication configuration, AWS credentials, etc.) before running `tsuru`.

3.2.7 Running `tsuru`

Now that you have `tsr` properly installed, and you *configured `tsuru`*, you’re three steps away from running it.

1. Start `mongodb`

```
$ sudo service mongodb start
```

2. Start `beanstalkd`

```
$ sudo service beanstalkd start
```

3. Start `api` and `collector`

```
$ tsr api &
$ tsr collector &
```

One can see the logs in:

```
$ tail -f /var/log/syslog
```

3.2.8 Using *tsuru*

Congratulations! At this point you should have a working *tsuru* server running on your machine, follow the *tsuru client usage guide* to start build your apps.

3.3 community

3.3.1 irc channel

#tsuru channel on irc.freenode.net - chat with other *tsuru* users and developers

3.3.2 ticket system

ticket system - report bugs and make feature requests

3.4 Configuring *tsuru*

Tsuru uses a configuration file in *YAML* format. This document describes what each option means, and how it should look like.

3.4.1 Notation

Tsuru uses a colon to represent nesting in *YAML*. So, whenever this document say something like `key1:key2`, it refers to the value of the `key2` that is nested in the block that is the value of `key1`. For example, `database:url` means:

```
database:
  url: <value>
```

3.4.2 *Tsuru* configuration

This section describes *tsuru*'s core configuration. Other sections will include configuration of optional components, and finally, a full sample file.

HTTP server

Tsuru provides a REST API, that supports HTTP and HTTP/TLS (a.k.a. HTTPS). Here are the options that affect how *tsuru*'s API behaves:

listen

`listen` defines in which address tsuru webserver will listen. It has the form `<host>:<port>`. You may omit the host (example: `:8080`). This setting has no default value.

use-tls

`use-tls` indicates whether tsuru should use TLS or not. This setting is optional, and defaults to “false”.

tls:cert-file

`tls:cert-file` is the path to the X.509 certificate file configured to serve the domain. This setting is optional, unless `use-tls` is true.

tls:key-file

`tls:key-file` is the path to private key file configured to serve the domain. This setting is optional, unless `use-tls` is true.

Database access

Tsuru uses MongoDB as database manager, to store information about users, VM's, and its components. Regarding database control, you're able to define to which database server tsuru will connect (providing a [MongoDB connection string](#)). The database related options are listed below:

database:url

`database:url` is the database connection string. It is a mandatory setting and has no default value. Examples of strings include the basic “127.0.0.1” and the more advanced “mongodb://user@password:127.0.0.1:27017/database”. Please refer to [MongoDB documentation](#) for more details and examples of connection strings.

database:name

`database:name` is the name of the database that tsuru uses. It is a mandatory setting and has no default value. An example of value is “tsuru”.

Collector

Collector is a tsuru agent responsible for collecting information about app units, interacting with the provisioner. This agent runs a loop in configurable interval.

collector:ticker-time

`collector:ticker-time` is interval for running the loop, specified in seconds. Default value: 60 seconds.

Email configuration

Tsuru sends email to users when they request password recovery. In order to send those emails, Tsuru needs to be configured with some SMTP settings. Omitting these settings won't break Tsuru, but users would not be able to reset their password automatically.

smtp:server

The SMTP server to connect to. It must be in the form <host>:<port>. Example: "smtp.gmail.com:587".

smtp:user

The user to authenticate with the SMTP sever. Currently, Tsuru requires authenticated sessions.

smtp:password

The password for authentication within the SMTP server.

Git configuration

Tsuru uses [Gandalf](#) to manage git repositories. Gandalf exposes a REST API for repositories management, and tsuru uses it. So tsuru requires information about the Gandalf HTTP server, and also its git-daemon and SSH service.

Tsuru also needs to know where the git repository will be cloned and stored in units storage. Here are all options related to git repositories:

git:unit-repo

`git:unit-repo` is the path where tsuru will clone and manage the git repository in all units of an application. This is where the code of the applications will be stored in their units. Example of value: `/home/application/current`.

git:api-server

`git:api-server` is the address of the Gandalf API. It should define the entire address, including protocol and port. Examples of value: `http://localhost:9090` and `https://gandalf.tsuru.io:9595`.

git:rw-host

`git:rw-host` is the host that will be used to build the push URL. For example, when the value is "tsuruhost.com", the push URL will be something like `git@tsuruhost.com:<app-name>.git`.

git:ro-host

`git:ro-host` is the host that units will use to clone code from users applications. It's used to build the read only URL of the repository. For example, when the value is "tsuruhost.com", the read-only URL will be something like `git://tsuruhost.com/<app-name>.git`.

Authentication configuration

Tsuru has its own authentication mechanism, that hashes passwords bcrypt. Tokens are generated during authentication, and are hashed using SHA512.

This mechanism requires two settings to operate: `auth:hash-cost` and `auth:token-expire-days`. Each setting is described below.

The `auth` section also controls whether user registration is on or off. When user registration is off, the user creation URL is not registered in the server.

`auth:user-registration`

This flag indicates whether user registration is enabled. This setting is optional, and defaults to false.

`auth:hash-cost`

This number indicates how many CPU time you're willing to give to hashing calculation. It is an absolute number, between 4 and 31, where 4 is faster and less secure, while 31 is very secure and *very* slow.

`auth:token-expire-days`

Whenever a user logs in, tsuru generates a token for him/her, and the user may store the token. `auth:token-expire-days` setting defines the amount of days that the token will be valid. This setting is optional, and defaults to "7".

`auth:max-simultaneous-sessions`

Tsuru can limit the number of simultaneous sessions per user. This setting is optional, and defaults to "unlimited".

Amazon Web Services (AWS) configuration

Tsuru is able to use Amazon Web Services (AWS) Simple Storage Service (S3) to provide static storage for apps. Whenever `bucket-support` is true, Tsuru will create a S3 bucket and AWS Identity and Access Management (IAM) credentials to access this bucket during the app creation process. In order to be able to communicate with AWS API's, tsuru needs some settings, listed below.

For more details on AWS authentication, AWS AIM and AWS S3, check AWS docs: <https://aws.amazon.com/documentation/>.

`bucket-support`

`bucket-support` is a boolean flag, that turns on the bucket per app feature. This field is optional, and defaults to false.

`aws:access-key-id`

`aws:access-key-id` is the access key ID used by tsuru to authenticate with AWS API. Given that `bucket-support` is true, this setting is required and has no default value.

aws:secret-access-key

`aws:secret-access-key` is the secret access key used by tsuru to authenticate with AWS API. Given that `bucket-support` is true, this setting is required and has no default value.

aws:ec2:endpoint

`aws:ec2:endpoint` is the EC2 endpoint that tsuru will call to communicate with ec2. It's only used for *juju* healers.

aws:iam:endpoint

`aws:iam:endpoint` is the IAM endpoint that tsuru will call to create credentials for its applications. This setting is optional, and defaults to `https://iam.amazonaws.com/`. You should change this setting only when using another service that also implements IAM's API.

aws:s3:region-name

`aws:s3:region-name` is the name of the region that tsuru will use to create S3 buckets. Given that `bucket-support` is true, this setting is required and has no default value.

aws:s3:endpoint

`aws:s3:endpoint` is the S3 endpoint that tsuru will call to create buckets for its applications. Given that `bucket-support` is true, this setting is required and has no default value.

aws:s3:location-constraint

`aws:s3:location-constraint` indicates whether buckets should be stored in the selected region. Given that `bucket-support` is true, this setting is required and has no default value.

For more details, check the documentation for buckets and regions: <http://docs.aws.amazon.com/AmazonS3/latest/dev/LocationSelection>

aws:s3:lowercase-bucket

`aws:s3:lowercase-bucket` will be true if the region requires bucket names to be lowercase. Given that `bucket-support` is true, this setting is required and has no default value.

queue configuration

Tsuru uses a work queue for asynchronous tasks. By default it will use [beanstalkd](#). You can customize the used queue, and settings related to the queue (like the address where beanstalkd is listening).

Creating a new queue provider is as easy as implementing [an interface](#).

queue

`queue` is the name of the queue implementation that `tsuru` will use. This setting is optional and defaults to “`beanstalkd`”.

queue-server

`queue-server` is the TCP address where `beanstalkd` is listening. This setting is optional and defaults to “`localhost:11300`”.

Admin users

Tsuru has a very simple way to identify admin users: an admin user is a user that is the member of the admin team, and the admin team is defined in the configuration file, using the `admin-team` setting.

admin-team

`admin-team` is the name of the administration team for the current `tsuru` installation. All members of the administration team is able to use the `tsuru-admin` command.

Quota management

Tsuru can, optionally, manage quotas. Currently, there are two available quotas: apps per user and units per app.

Tsuru administrators can control the default quota for new users and new apps in the configuration file, and use `tsuru-admin` command to change quotas for users or apps. Quota management is disabled by default, to enable it, just set the desired quota to a positive integer.

quota:units-per-app

`quota:units-per-app` is the default value for units per-app quota. All new apps will have at most the number of units specified by this setting. This setting is optional, and defaults to “unlimited”.

quota:apps-per-user

`quota:apps-per-user` is the default value for apps per-user quota. All new users will have at most the number of apps specified by this setting. This setting is optional, and defaults to “unlimited”.

Log level

debug

`false` is the default value, so you won't see any noises on logs, to turn it on set it to `true`, e.g.: `debug: true`

Defining the provisioner

Tsuru supports multiple provisioners. A provisioner is a Go type that satisfies an interface. By default, tsuru will use `JujuProvisioner` (identified by the string “juju”). To use other provisioner, that has been already registered with tsuru, one must define the setting `provisioner`.

`provisioner`

`provisioner` is the string the name of the provisioner that will be used by tsuru. This setting is optional and defaults to “juju”.

You can also configure the provisioner (check the next section for details on Juju configuration).

3.4.3 Juju provisioner configuration

“juju” is the default provisioner used by Tsuru. It’s named after the [tool used by tsuru to provision and manage instances](#). It’s a extended version of Juju, supporting Amazon’s [Virtual Private Cloud \(VPC\)](#) and [Elastic Load Balancing \(ELB\)](#).

Charms path

Juju describe services as [Charms](#). Each tsuru platform is a Juju charm. The tsuru team provides a collection of charms with customized hooks: <https://github.com/globocom/charms>. In order (for more details, refer to [build documentation](#)).

`juju:charms-path`

`charms-path` is the path where tsuru should look for charms when creating new apps. If you specify the value “`/etc/juju/charms`”, your charms tree should look something like this:

```
.
-- centos
|   -- ...
-- precise
|   -- go
|       -- config.yaml
|       -- hooks
|       ...
|   -- metadata.yaml
-- nodejs
|   -- config.yaml
|   -- hooks
|   ...
|   -- metadata.yaml
-- python
|   -- config.yaml
|   -- hooks
|   ...
|   -- metadata.yaml
|   -- utils
|       -- circus.ini
|       -- nginx.conf
-- rack
|   -- config.yaml
```

```
|   -- hooks
|   ...
|   -- metadata.yaml
-- ruby
|   -- config.yaml
|   -- hooks
|   ...
|   -- metadata.yaml
-- static
|   -- config.yaml
|   -- hooks
|   ...
|   -- metadata.yaml
```

Given that you're using juju, this setting is mandatory and has no default value.

Storing units in the database

Juju provisioner uses the database to store information about units. It uses a MongoDB collection that will be located in the same database used by tsuru. One can set the name of this collection using the setting described below:

juju:units-collection

`juju:units-collection` defines the name of the collection that Juju provisioner should use to store information about units. This setting is required by the provisioner and has no default value.

Elastic Load Balancing support

Juju provisioner can manage load balancers per app using Elastic Load Balancing (ELB) API, provided by Amazon. In order to enable Elastic Load Balancing support, one must set `juju:use-elb` to true and define other settings described below:

juju:use-elb

`juju:use-elb` is a boolean flag that indicates whether Juju provisioner will use ELB. When enabled, it will create a load balancer per app, registering and deregistering units as they come and go, and deleting the load balancer when the app is removed. This setting is optional and defaults to false.

Whenever `juju:use-elb` is defined to be true, other settings related to load balancing become mandatory: `juju:elb-endpoint`, `juju:elb-collection`, `juju:elb-avail-zones` (or `juju:elb-vpc-subnets` and `juju:elb-vpc-secgroups`, see `juju:elb-use-vpc` for more details).

juju:elb-endpoint

`juju:elb-endpoint` is the ELB endpoint that tsuru will use to manage load balancers. This setting has no default value, and is mandatory once `juju:use-elb` is true. When `juju:use-elb` is false, the value of this setting is irrelevant.

juju:elb-collection

`juju:elb-collection` is the name of the collection that Juju provisioner will use to store information about load balancers.

This setting has no default value, and is mandatory once `juju:use-elb` is true. When `juju:use-elb` is false, the value of this setting is irrelevant.

juju:elb-use-vpc

`juju:elb-use-vpc` is another boolean flag. It indicates whether load balancers should be created using an Amazon Virtual Private Cloud. When this setting is true, one must also define `juju:elb-vpc-subnets` and `juju:elb-vpc-secgroups`.

This setting is optional, defaults to false and has no effect when `juju:use-elb` is false.

juju:elb-vpc-subnets

`juju:elb-vpc-subnets` contains a list of subnets that will be attached to the load balancer. This setting must be defined whenever `juju:elb-use-vpc` is true. It has no default value.

juju:elb-vpc-secgroups

`juju:elb-vpc-secgroups` contains a list of security groups from which the load balancer will inherit rules. This setting must be defined whenever `juju:elb-use-vpc` is true. It has no default value.

juju:elb-avail-zones

`juju:elb-avail-zones` contains a list of availability zones that the load balancer will communicate with. This setting has no effect when `juju:elb-use-vpc` is true, has no default value and must be defined whenever `juju:elb-use-vpc` is false.

3.4.4 Sample file

Here is a complete example, with S3, VPC, HTTP/TLS and load balacing enabled:

```
listen: ":8080"
use-tls: true
tls:
  cert-file: /etc/tsuru/tls/cert.pem
  key-file: /etc/tsuru/tls/key.pem
host: http://10.19.2.238:8080
database:
  url: 127.0.0.1:27017
  name: tsuru
git:
  unit-repo: /home/application/current
  host: gandalf.tsuru.io
  port: 8000
  protocol: http
auth:
  token-expire-days: 14
```



```
bucket-support: true
aws:
  access-key-id: access-key
  secret-access-key: s3cr3t
  iam:
    endpoint: https://iam.amazonaws.com/
  s3:
    region-name: sa-east-1
    endpoint: https://s3.amazonaws.com
    location-constraint: true
    lowercase-bucket: true
provisioner: juju
queue-server: "127.0.0.1:11300"
admin-team: admin
juju:
  charms-path: /etc/juju/charms
  units-collection: j_units
  use-elb: true
  elb-endpoint: https://elasticloadbalancing.amazonaws.com
  elb-collection: j_lbs
  elb-use-vpc: true
  elb-vpc-subnets:
    - subnet-alala1
  elb-vpc-secgroups:
    - sg-alala1
```

3.5 contribute

- Source hosted at [GitHub](#)
- Report issues on [GitHub Issues](#)

Pull requests are very welcome! Make sure your patches are well tested and documented :)

3.5.1 development environment

See this guide to *setting up your tsuru development environment*.

And follow our *coding style guide*.

3.5.2 running the tests

You can use *make* to install all tsuru dependencies and run tests. It will also check if everything is ok with your *GOPATH* setup:

```
$ make
```

3.5.3 writing docs

Tsuru documentation is written using [Sphinx](#), which uses [RST](#). Check these tools docs to learn how to write docs for Tsuru.

3.5.4 building docs

In order to build the HTML docs, just run on terminal:

```
$ make doc
```

3.6 Build your own PaaS with tsuru and Docker

This document describes how to create a private PaaS service using tsuru and docker.

This document assumes that tsuru is being installed on a Ubuntu 13.04 64-bit machine. If you want to use Ubuntu LTS version see [docker documentation](#) on how to install it. You can use equivalent packages for beanstalkd, git, MongoDB and other tsuru dependencies. Please make sure you satisfy minimal version requirements.

You can use the scripts bellow to quick install tsuru with docker:

```
$ curl -O https://raw.githubusercontent.com/globocom/tsuru/master/misc/docker-setup.bash; bash docker-setup.bash
```

Or follow this steps:

3.6.1 DNS server

You can integrate any DNS server with tsuru. Here: <http://docs.tsuru.io/en/latest/misc/dns-forwarders.html> you can find a example of how to install a DNS server integrated with tsuru

3.6.2 docker

Install docker:

```
$ wget -qO- https://get.docker.io/gpg | sudo apt-key add -
$ echo 'deb http://get.docker.io/ubuntu docker main' | sudo tee /etc/apt/sources.list.d/docker.list
$ sudo apt-get update
$ sudo apt-get install lxc-docker
```

Then edit `/etc/init/docker.conf` to start docker on `tcp://127.0.0.1:4243`:

```
$ cat > /etc/init/docker.conf <<EOF
description      "Docker daemon"

start on filesystem and started lxc-net
stop on runlevel [!2345]

respawn

script
    /usr/bin/docker -H tcp://127.0.0.1:4243 -d
end script

EOF
```

3.6.3 MongoDB

Tsuru needs MongoDB stable, distributed by 10gen. It's pretty easy to get it running on Ubuntu

3.6.4 Redis

Tsuru uses Redis to communicate new routes. By default it points to a locally installed Redis server. Install on Ubuntu via *apt-get*:

```
$ sudo apt-get install redis-server
```

If you will use a remote Redis server, skip this and point your server on */etc/tsuru/tsuru.conf*

3.6.5 Beanstalkd

Tsuru uses [Beanstalkd](#) as a work queue. Install the latest version, by doing this:

```
$ sudo apt-get install beanstalkd
```

Configuring beanstalkd to start, edit the */etc/default/beanstalkd* and uncomment this line:

```
START=yes
```

Then start beanstalkd:

```
$ sudo service beanstalkd start
```

3.6.6 Gandalf

Tsuru uses [Gandalf](#) to manage Git repositories, you can install it from [Tsuru PPA](#):

```
$ sudo apt-add-repository ppa:tsuru/ppa
$ sudo apt-get update
$ sudo apt-get install gandalf-server
```

Creating directory for bare template

Tsuru depends on some Git hooks, you will need to create the bare template directory, and download the hook from Tsuru repository:

```
$ sudo mkdir -p /home/git/bare-template/hooks
$ curl https://raw.githubusercontent.com/globocom/tsuru/master/misc/git-hooks/post-receive | sudo tee /home/git/bare-template/post-receive
$ sudo chown -R git:git /home/git/bare-template
```

Configuring gandalf

```
$ cat > /etc/gandalf.conf <<EOF
bin-path: /usr/bin/gandalf-ssh
database:
  url: 127.0.0.1:27017
  name: gandalf
git:
  bare:
    location: /var/lib/gandalf/repositories
    template: /home/git/bare-template
host: localhost
bind: 127.0.0.1:8000
EOF
```

Change the host : `localhost` to your base domain.

Starting Gandalf and git-daemon

This one is easy:

```
$ sudo start git-daemon
$ sudo start gandalf-server
```

3.6.7 Tsuru API and collector

You can also install Tsuru API and Collector from Tsuru PPA:

```
$ sudo apt-get install tsuru-server gandalf-server
```

Configuring

Before running `tsuru`, you must configure it. By default, `tsuru` will look for the configuration file in the `/etc/tsuru/tsuru.conf` path. You can check a sample configuration file and documentation for each `tsuru` setting in the “*Configuring tsuru*” page.

The debian package will create the file, you may open it and customize some settings, or you can download the sample configuration file from Github:

```
$ sudo curl -sL https://raw.githubusercontent.com/globocom/tsuru/master/etc/tsuru-docker.conf -o /etc/tsuru/tsuru.conf
```

By default, this configuration will use the `tsuru` image namespace, so if you try to create an application using `python` platform, `tsuru` will search for an image named `tsuru/python`. You can change this default behavior by changing the `docker:repository-namespace` config field.

You’ll also need to enable Tsuru API, Collector and SSH agent on `/etc/default/tsuru-server`:

```
$ cat > /etc/default/tsuru-server <<EOF
TSR_API_ENABLED=yes
TSR_COLLECTOR_ENABLED=yes

TSR_SSH_AGENT_ENABLED=yes
TSR_SSH_AGENT_USER=ubuntu
TSR_SSH_AGENT_LISTEN=127.0.0.1:4545
TSR_SSH_AGENT_PRIVATE_KEY=/var/lib/tsuru/.ssh/id_rsa
EOF
```

Running

Now that you have `tsr` properly installed, and you *configured tsuru*, you’re three steps away from running it.

Start `api`, `collector` and `docker-ssh-agent`

```
$ sudo start tsuru-server-collector
$ sudo start tsuru-server-api
$ sudo start tsuru-ssh-agent
```

You can see the logs in:

```
$ sudo tail -f /var/log/syslog
```

Creating Docker Images

Now it's time to import the Docker images for your platforms. You can build your own docker image, or you can use our images as following:

```
# Add an alias for docker to make your life easier (add it to your .bash_profile)
$ alias docker='docker -H 127.0.0.1:4243'
# Build the wanted platform, here we are adding the static platform(webserver)
$ docker build -t tsuru/static https://raw.githubusercontent.com/flaviamissi/basebuilder/master/static/Dockerfile
# Now you can see if your image is ready - you should see the tsuru/static as an repository
$ docker images
# If you want all the other platforms, just run the command bellow
$ for image in nodejs php python ruby; do docker build -t tsuru/$image https://raw.githubusercontent.com/flaviamissi/basebuilder/master/$image/Dockerfile; done
# To see if everything went well - just take a look in the repository column
$ docker images
# Now create your apps!
```

Using tsuru

Congratulations! At this point you should have a working tsuru server running on your machine, follow the *tsuru client usage guide* to start build your apps.

Adding Services

Here you will find a complete step-by-step example of how to install a mysql service with tsuru: <http://docs.tsuru.io/en/latest/services/mysql-example.html>

3.7 Build your own PaaS with tsuru and Docker on Centos

This document describes how to create a private PaaS service using tsuru and docker on Centos.

This document assumes that tsuru is being installed on a Centos (6.4+) machine. You can use equivalent packages for beanstalkd, git, MongoDB and other tsuru dependencies. Please make sure you satisfy minimal version requirements.

Just follow this steps:

3.7.1 DNS server

You can integrate any DNS server with tsuru. Here: <http://docs.tsuru.io/en/latest/misc/dns-forwarders.html> you can find a example of how to install a DNS server integrated with tsuru

3.7.2 Docker

To make docker working on a RHEL/Centos distro, you will need to use the [EPEL repository](#), build a kernel with AUFS support, and install all dependencies as following:

```
# Installing the EPEL repository
$ rpm -iUvh http://dl.fedoraproject.org/pub/epel/6/x86_64/epel-release-6-8.noarch.rpm
$ yum update -y
```

Here you can install our own kernel+lxc+docker or compile them To install our RPM package ready to go:

```
# Installing the EPEL repository
# rpm -iUvh http://tsuru.s3.amazonaws.com/centos/docker-0.6.0-1.el6.x86_64.rpm \
http://tsuru.s3.amazonaws.com/centos/lxc-0.8.0-3.el6.x86_64.rpm \
http://tsuru.s3.amazonaws.com/centos/lxc-libs-0.8.0-3.el6.x86_64.rpm \
http://tsuru.s3.amazonaws.com/centos/kernel-ml-aufs-3.10.11-1.el6.x86_64.rpm
```

To Compile, just follow these steps

```
# Download the kernel + dependencies for docker
$ yum install fedora-packager -y
# you will need to perform these steps bellow with a unprivileged user, ex: su - tsuru
$ git clone https://github.com/sciurus/docker-rhel-rpm
$ cd docker-rhel-rpm
# Remove auto restart of docker, as it will be managed by circus
$ sed -i 's|^%{_sysconfdir}/init/docker.conf||; s/.*source1.*//i' docker/docker.spec
```

Now, just follow the steps to build the kernel + lxc + docker from here: <https://github.com/sciurus/docker-rhel-rpm/blob/master/README.md>

```
# In order to use docker, you will need to allow the ip forward
$ grep ^net.ipv4.ip_forward /etc/sysctl.conf > /dev/null 2>&1 && \
    sed -i 's/^net.ipv4.ip_forward.*/net.ipv4.ip_forward = 1/' /etc/sysctl.conf || \
    echo 'net.ipv4.ip_forward = 1' >> /etc/sysctl.conf
$ sysctl -p
# You also need to disable selinux, adding the parameter "selinux=0" in your new kernel 3.10 (/boot/grub/menu.lst)
$ grep selinux=0 /boot/grub/menu.lst
# Turn off your default firewall rules for now
$ service iptables stop
$ chkconfig iptables off
```

After build, install and reboot the server with the new kernel(it will take some time), you will need to install the tsuru's dependencies

3.7.3 Tsuru's Dependencies

Tsuru needs MongoDB stable, distributed by 10genr, [Beanstalkd](#) as work queue, git-daemon(necessary for Gandalf) and Redis for [hipache](#) pt-ge Install the latest EPEL version, by doing this:

```
$ yum install mongodb-server beanstalkd git-daemon redis python-pip python-devel gcc gcc-c++ -y
$ service mongod start
$ service beanstalkd start
$ service redis start
$ chkconfig mongod on
$ chkconfig beanstalkd on
$ chkconfig redis on
```

3.7.4 Tsuru Setup

Tsuru uses [Gandalf](#) to manage [git repositories](#), and [hipache](#) as router To setup Tsuru, just follow this steps. Obs: It can be used to upgrade this services as needed

```
$ curl https://raw.githubusercontent.com/globocom/tsuru/master/misc/functions-docker-centos.sh -o functions-docker-centos.sh
$ source functions-docker-centos.sh
# Install Tsuru Server(tsr), Gandalf, Hipache and Circus for monitoring
$ install_services
```

Configuring

Before running tsuru, you must configure it. By default, tsuru will look for the configuration file in the `/etc/tsuru/tsuru.conf` path. You can check a sample configuration file and documentation for each tsuru setting in the “*Configuring tsuru*” page.

You can download the sample configuration file from [Github](#)

By default, this configuration will use the tsuru image namespace, so if you try to create an application using python platform, tsuru will search for an image named `tsuru/python`. You can change this default behavior by changing the `docker:repository-namespace` config field.

To automatically configure tsuru and all other services, just run the function presented in `functions-docker-centos.sh` file, as following

```
# It will configure tsuru, gandalf, hipache and circus. If you had already done that before, your pr
$ source functions-docker-centos.sh #you already did it above
$ configure_services_for_first_time
# start circus
$ initctl start circusd
```

At that time, circus should be running and started all the tsuru services

Running

Now that you have `tsr` properly installed, and you *configured tsuru* Verify api, collector and docker-ssh-agent

```
$ ps -ef|grep ts[r]
```

Creating Docker Images

Now it's time to install the docker images for your neededs platform. You can build your own docker image, or you can use ours own images as following

```
# Add an alias for docker to make your life easier (add it to your .bash_profile)
$ alias docker='docker -H 127.0.0.1:4243'
# Build the wanted platform, here we are adding the static platform(webserver)
$ docker build -t tsuru/static https://raw.githubusercontent.com/flaviamissi/basebuilder/master/static/Dockerfile
# Now you can see if your image is ready - you should see the tsuru/static as an repository
$ docker images
# If you want all the other platforms, just run the command bellow
$ for image in nodejs php python ruby; do docker build -t tsuru/$image https://raw.githubusercontent.com/flavian
# To see if everything went well - just take a look in the repository column
$ docker images
# Now try to create your apps!
```

Using tsuru

Congratulations! At this point you should have a working tsuru server running on your machine, follow the *tsuru client usage guide* to start build your apps.

Adding Services

Here you will find a complete step-by-step example of how to install a mysql service with tsuru: <http://docs.tsuru.io/en/latest/services/mysql-example.html>

3.8 Download

3.8.1 Client binaries

tsuru clients are also distributed in binary version, so you can just download an executable and put them somewhere in your PATH.

It's important to note that all binaries are platform dependent. Currently, we provide each of them in three flavors:

1. **darwin_amd64**: This is Mac OS X, 64 bits. Make sure the command `uname -ms` prints "Darwin x86_64", otherwise this binary will not work in your system;
2. **linux_386**: This is Linux, 32 bits. Make sure the command `uname -ms` prints "Linux x86", otherwise this binary will not work in your system;
3. **linux_amd64**: This is Linux, 64 bits. Make sure the command `uname -ms` prints "Linux x86_64", otherwise this binary will not work in your system.

Below are the links to the binaries, you can just download, extract the archive and put the binary somewhere in your PATH:

darwin_amd64

- tsuru: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-darwin-amd64.tar.gz>
- tsuru-admin: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-admin-darwin-amd64.tar.gz>
- crane: <https://s3.amazonaws.com/tsuru/dist-cmd/crane-darwin-amd64.tar.gz>

linux_386

- tsuru: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-linux-386.tar.gz>
- tsuru-admin: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-admin-linux-386.tar.gz>
- crane: <https://s3.amazonaws.com/tsuru/dist-cmd/crane-linux-386.tar.gz>

linux_amd64

- tsuru: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-linux-amd64.tar.gz>
- tsuru-admin: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-admin-linux-amd64.tar.gz>
- crane: <https://s3.amazonaws.com/tsuru/dist-cmd/crane-linux-amd64.tar.gz>

3.9 Tsuru Frequently Asked Questions

- What is Tsuru?
- What is an application?
- What is a unit?
- What is a platform?
- What is a service?
- How does environment variables work?
- How does the quota system works?
- How routing works?
- How are Git repositories managed?

This document is an attempt to explain concepts you'll face when deploying and managing applications using Tsuru. To request additional explanations you can open an issue on our issue tracker, talk to us at #tsuru @ freenode.net or open a thread on our mailing list.

3.9.1 What is Tsuru?

Tsuru is an open source polyglot cloud application platform (PaaS). With tsuru, you don't need to think about servers at all. You can write apps in the programming language of your choice, back it with add-on resources such as SQL and NoSQL databases, memcached, redis, and many others. You manage your app using the tsuru command-line tool and you deploy code using the Git revision control system, all running on the tsuru infrastructure.

3.9.2 What is an application?

An application, in Tsuru, is a program's source code, dependencies list - on operational system and language level - and a Procfile with instructions on how to run that program. An application has a name, a unique address, a Platform, associated development teams, a repository and a set of units.

3.9.3 What is a unit?

A unit is an isolated Unix container or a virtual machine - depending on the configured provisioner. A unit has everything an application needs to run, the fetched operational system and language level dependencies, the application's source code, the language runtime, and the applications processes defined on the Procfile.

3.9.4 What is a platform?

A platform is a well defined pack with installed dependencies for a language or framework that a group of applications will need. A platform might be a container template, or a virtual machine image.

For instance, Tsuru has a container image for python applications, with virtualenv installed and other required things needed for Tsuru to deploy applications on top of that platform. Platforms are easily extendable in Tsuru, but currently not managed by it, all Tsuru does (by now) is to keep database records for each existent platform. Every application runs on top of a platform.

3.9.5 What is a service?

A service is a well defined API that Tsuru communicates with to provide extra functionality for applications. Examples of services are MySQL, Redis, MongoDB, etc. Tsuru has built-in services, but it is easy to create and add new services to Tsuru. Services aren't managed by Tsuru, but by its creators.

Check the [service usage documentation](#) for more on using services and the [building your own service tutorial](#) for a quick start on how to extend Tsuru by creating new services.

3.9.6 How does environment variables work?

All configurations in Tsuru are handled by the use of environment variables. If you need to connect with a third party service, e.g. twitter's api, you are probably going to need some extra configurations, like `client_id`. In Tsuru, you can export those as environment variables, visible only by your application's processes.

When you bind your application into a service, most likely you'll need to communicate with that service in some way. Services can export environment variables by telling Tsuru what they need, so whenever you bind your application with a service, its api can return environment variables for Tsuru to export on your application's units.

3.9.7 How does the quota system works?

Quotas are handled per application and user. Every user has a quota number for applications. For example, users may have a default quota of 2 applications, so whenever a user tries to create more than two applications, he/she will receive a quota exceeded error. There are also per applications quota. This one limits the maximum number of units that an application may have.

3.9.8 How routing works?

Tsuru has a router interface, which makes extremely easy to change the way routing works with any provisioner. There are two ready-to-go routers: one using [hipache](#) and another with [elb](#).

3.9.9 How are Git repositories managed?

Tsuru uses [Gandalf](#) to manage git repositories. Every time you create an application, Tsuru will ask Gandalf to create a related git bare repository for you to push in.

This is the remote Tsuru gives you when you create a new app. Everytime you perform a git push, Gandalf intercepts it, check if you have the required authorization to write into the application's repository, and then lets the push proceeds or returns an error message.

3.9.10 Client installation fails with “undefined: bufio.Scanner”. What does it mean?

Tsuru clients require Go 1.1 or later. The message `undefined: bufio.Scanner` means that you're using an old version of Go. You'll have to [install](#) the last version.

If you're using Homebrew on Mac OS, just run:

```
% brew update
% brew upgrade go
```

3.10 Tsuru Overview

This document is in alpha state, to suggest improvements check out the [related github issue](#).

Tsuru is an open source PaaS. If you don't know what a PaaS is and what it does, see [wikipedia's description](#).

It follows the principles described in the [The Twelve-Factor App](#) methodology.

3.10.1 Fast and easy deployment

Deploying an app is simple and easy. No special tools needed, just a plain git push. The entire process is very simple, especially from the second deployment, whether your app is big or small.

Tsuru uses git as the means of deploying an application. You don't need master git in order to deploy an app to Tsuru, although you will need to know the very basic workflow, add/commit/push and remote managing. Git allows really fast deploys, and Tsuru makes the best possible use of it by not cloning the whole repository history of your application, there's no need to have that information in the application webserver.

Tsuru will also take care of all the applications dependencies in the deployment process. You can specify operating system and language specific dependencies. For example, if you have a Python application, tsuru will search for the requirements.txt file, but first it will search for OS dependencies (a list of deb packages in a file named requirements.apt, in the case of Ubuntu).

Tsuru also has *hooks* that can trigger commands before and after some events that happen during the deployment process, like restart (represented by `restart:before`, `restart:before-each`, `restart:after` and `restart:after-each` hooks).

3.10.2 Continuous Deployment

Easily create testing, staging, and production versions of your app and deploy to them instantly.

3.10.3 Add-on Resources

Instantly provision and integrate third party services with one command. Tsuru provides the basic services your application will need, like searching, caching, storage and frontend; you can get all of that in a fashionable and really easy way using Tsuru's command line.

3.10.4 Per-Environment Config Variables

Configuration for an application should be stored in environment variables - and we know that. Tsuru lets you define your environment variables using the command line, so you can have the configuration flexibility your application need.

Tsuru also makes use of environment variables. When you bind a service with your application, Tsuru gives the service the ability to inject environment variables in your application environment. For instance, if you use the default MySQL service, it will inject variables for you to establish a connection with your application database.

3.10.5 Custom Services

Tsuru already has services for you to use, but you don't need to use them at all if you don't want to. If you already have, let's say, a MySQL server running on your infrastructure, all you need to do in order to use it is simply configure environment variables and use them in your application config.

You can also create your own services and make them available for you and others to use it on Tsuru. It's so easy to do so that you'll want to sell your own services. Tsuru talks with services using a well defined [API](#), all you have to do is implement four endpoints that knows how to provision instances of your services and bind them to tsuru applications (like creating VMs, authorizing security groups, creating ACLs, etc), and register your service in Tsuru with a really simple [yaml manifest](#).

3.10.6 Logging and Visibility

Full visibility into your app's operations with real-time logging, process status inspection, and an audit trail of all releases. Tsuru will capture standard streams (output and error) from your application and expose them via the `tsuru log` command. You can also filter logs, for example, if you don't want to see the logs of developers activity (e.g.: a deploy action), you can specify the source as "app" and you'll get only the application webserver logs.

3.10.7 Process Management

Tsuru manages all processes from an application, so you don't have to worry about it. But it does not know to start it. You'll have to teach Tsuru how to start your application using a Procfile. Tsuru reads the Procfile and uses [Circus](#) to start and manage the running process. You can even enable a web console for Circus to manage your application process and to watch CPU and memory usage in real-time through a web interface.

Tsuru also allows you to easily restart your application process via command line. Although Tsuru will do all the hard work of managing and fixing eventual problems with your process, you might need to restart your application manually, so we give you an easy way to do it.

3.10.8 Control Surfaces

Tsuru exposes its features through a solid, stable REST API. You can write clients for this API, or you can use one of the clients maintained by tsuru developers.

Tsuru ships with two API clients: the command line interface (CLI), which is pretty stable and ready for day-to-day usage; and the [web interface](#), which is under development, but is also a great tool to manage, check logs and monitor applications and services resources.

3.10.9 Scaling

The [Juju](#) provisioner allows you to easily add and remove units, enabling one to scale an application painlessly. It will take care of the application code replication, and services binding. There's nothing required to the developer to do in order to scale an application, just add a new unit and Tsuru will do the trick.

You may also want to scale using the Front end as a Service, powered by [Varnish](#). One single application might have a whole farm of Varnish VMs in front of it handling all the traffic.

3.10.10 Built-in Database Services

Tsuru already has a variety of database services available for setup on your cloud. It allows you to easily create a service instance for your application usage and bind them together. The service setup for your application is transparent by the use of environment variables, which are exported in all instances of the application, allowing your configuration to fit several environments (like development, staging, production, etc.)

3.10.11 Extensible Service and Platform Support

Tsuru allows you to easily add support for new services and new platforms. For application platforms, it uses [Juju Charms](#), for services, it has an [API](#) that it uses to communicate with them.

3.10.12 Collaboration

Manage sharing and deployment of your application. Tsuru uses teams to control access to resources. A developer may create a team, grant/revoke app access to/from a team or add/remove new users to/from a team. One can be a member of multiple teams and control which applications each team has access to.

3.10.13 Easy Server Deployment

Tsuru itself is really easy to deploy and manage, you can get it done by following [these simple steps](#).

3.10.14 Distributed and Extensible

Tsuru server is easily extensible, distributed and customizable. It has the concept of `Provisioner`: a provisioner is a component that takes care of the orchestration (VM/container management) and provisioning. By default, it will deploy applications using the [Juju](#) provisioner, but you can easily implement your own provisioner and use whatever backend you wish.

When you extend Tsuru, you are able to practically build a new PaaS in terms of behavior of provision and orchestration, making use of the great Tsuru structure. You change the whole Tsuru workflow by implementing a new provisioner.

3.10.15 Dev/Ops Perspective

Tsuru's components are distributed, it is composed by many pieces of software, each one made to be easily deployable and maintainable. #TODO link architecture overview.

3.10.16 Application Developer Perspective

We aim to make developers life easier. #TODO link development workflow.

3.11 Why Tsuru?

This document aims to show Tsuru's most killing features. Additionally, provides a comparison of Tsuru with others PaaS's on the market.

3.11.1 Easy Server Installation

It's really easy to have a running PaaS with Tsuru. We provide a serie of scripts, each one built to install and configure the required components for each Tsuru provisioner, you can check our scripts on [Tsuru repository](#), there are separeted scripts to install each component, so it's easy to create your own script to configure a new provisioner or to change the configuration of an existing one.

But it's okay if you want more control and do not want to use our scripts, or want to better understand the interaction between Tsuru components, we built [a guide](#) only for you.

3.11.2 Platforms Extensibility

One of Tsuru main goals is to be easily extensible. The platform is one great example of accomplishment on that. Tsuru platforms works slightly different for each provisioner. Juju use *charms* for platform provisioning you can find the scripts on our [charms repository](#). The Docker provisioner is a bit different, it has an specific image for each platform, if one wants to create a new platform, just extend tsuru/base image and follow the directory tree structure, the scripts and Dockerfile for our existing platforms images can be found on our [images repository](#)

3.11.3 Services Creation and Extension

Most applications need a service to work properly, like a database service. Tsuru provides an interface API to communicate with services APIs, but it doesn't manage services directly, this provides more control over the service and its management.

In order to create a new service you simply write an API implementing the predefined endpoints. Tsuru will call when a user performs an action using the client, read more on the [building your service tutorial](#).

You can either create a new service or modify an existing one, if its source is open. All services APIs made by Tsuru team are open and contributions are very welcome. For example, the mongoDB api shares one database installation with everyone that is using it, if you don't like it and want to change it, you can do it and create a new service on Tsuru with your own implementation.

3.11.4 IaaS's and Provisioners

Tsuru provides an easy way to change the application unit provisioning system and it already has two working provisioners, Juju, Docker. But the main advantage is the ease of extending the provisioning system. One can simply implement the Provision interface Tsuru provides, configure it on your installation and start using it.

3.11.5 Routers

Tsuru also provides an abstraction for routing control and load balancing in application units. It provides a routing interface, that you can combine on many ways: you can plug any router with any provisioner, you can also create your own routing backend and plug it with any existing provisioner, this can be done only changing Tsuru's configuration file.

3.11.6 Comparing Tsuru With Other PaaS's

The following table compares Tsuru with OpenShift and Stackato PaaS's.

If you have anything to consider, or want to ask us to add another PaaS on the list contact us in [#tsuru @ freenode.net](#) or at our [mailing list](#)

	Tsuru	OpenShift	Stackato
Built-in Platforms	Node.js, PHP, HTML, Python, Ruby, Go, Java	Java, PHP, Ruby, Node.js, Python	Java, Node.js, Perl, PHP, Python, Ruby
End-user web UI	Yes (Abyss)	Yes	Yes
CLI	Yes	Yes	Yes
Deployment hooks	Yes	No	Yes
SSH Access	Yes (management-only)	Yes	Yes
Run Commands	Yes	No	No
Remotely			
Application	Yes	Yes	Yes
Monitoring			
SQL Databases	MySQL	MySQL, PostgreSQL	MySQL, PostgreSQL
NoSQL Databases	MongoDB, Cassandra Memcached, Redis	MongoDB	MongoDB, Redis
Log Streaming	Yes	Yes (not built-in)	Yes
Metering/Billing	No (issue 466)	No	Yes
API			
Quota System	Yes	Yes	Yes
Container Based	Yes	Yes	Yes
Apps			
VMs Based Apps	Yes	No	No
Open Source	Yes	Yes	No
Free	Yes	Yes	Yes
Paid/Closed	No	Yes	Yes
Version			
PaaS Healing	Yes	No	No
App Healing	Yes	No	No
App Fault	Yes	Yes (by cartridge)	Yes
Tolerance			
Auto Scaling	No (issue 154)	Yes	Yes (for some IaaS's)
Manual Scaling	Yes	No	Yes

3.12 Deployment hooks

Tsuru provides some deployment hooks, like `restart:before`, `restart:after` and `build`. Deployment hooks allow developers to run commands before and after some commands.

Hooks are listed in a special file located in the root of the application. The name of the file may be `app.yaml` or `app.yml`. Here is an example of the file:

```
hooks:
  restart:
    before:
      - python manage.py migrate
    before-each:
      - python manage.py generate_local_file
    after-each:
      - python manage.py clear_local_cache
    after:
      - python manage.py clear_redis_cache
  build:
    - python manage.py collectstatic --noinput
    - python manage.py compress
```

Tsuru supports the following hooks:

- `restart:before`: this hook lists commands that will run before the app is restarted. Commands listed in this hook will run once per app.
- `restart:before-each`: this hook lists commands that will run before the unit is restarted. Commands listed in this hook will run once per unit. For instance, imagine there's an app with two units and the `app.yaml` file listed above. The command `python manage.py generate_local_file` would run two times, once per unit.
- `restart:after-each`: this hook is like before-each, but runs after restarting a unit.
- `restart:after`: this hook is like before, but runs after restarting an app.
- `build`: this hook lists commands that will be run during deploy, when the image is being generated. (only for docker provisioner)

3.13 Application Deployment

This document provides a high-level description on how application deployment works on Tsuru.

3.13.1 Preparing Your Application

If you follow the [12 Factor](#) app principles you shouldn't have to change your application in order to deploy it on Tsuru. Here is what an application need to go on a Tsuru cloud:

1. Well defined requirements, both, on language level and operational system level
2. Configuration of external resources using environment variables
3. A Procfile to tell how your process should be run

Let's go a little deeper through each of those topics.

1. Requirements

Every well written application nowadays has well defined dependencies. In Python, everything is on a `requirements.txt` or like file, in Ruby, they go on Gemfile, Node.js has the `package.json`, and so on. Some of those dependencies also have operational system level dependencies, like the Nokogiri Ruby gem or MySQL-Python package, Tsuru bootstraps units as clean as possible, so you also have to declare those operational system requirements you need on a file called `requirements.apr`. This files should have the packages declared one per-line and look like that:

```
python-dev
libmysqlclient-dev
```

2. Configuration With Environment Variables

Everything that vary between deploys (on different environments, like development or production) should be managed by environment variables. Tsuru takes this principle very seriously, so all services available for usage in Tsuru that requires some sort of configuration does it via environment variables so you have no pain while deploying on different environments using Tsuru.

For instance, if you are going to use a database service on Tsuru, like MySQL, when you bind your application into the service, Tsuru will receive from the service API everything you need to connect with MySQL, e.g: user name, password, url and database name. Having this information, Tsuru will export on every unit your application has the equivalent environment variables with their values. The names of those variables are defined by the service providing them, in this case, the MySQL service.

Let's take a look at the settings of Tsuru hosted application built with Django:

```
import os

DATABASES = {
    "default": {
        "ENGINE": "django.db.backends.mysql",
        "NAME": os.environ.get("MYSQLAPI_DB_NAME"),
        "USER": os.environ.get("MYSQLAPI_DB_USER"),
        "PASSWORD": os.environ.get("MYSQLAPI_DB_PASSWORD"),
        "HOST": os.environ.get("MYSQLAPI_HOST"),
        "PORT": "",
        "TEST_NAME": "test",
    }
}
```

You might be asking yourself “How am I going to know those variables names?”, but don't fear! When you bind your application with Tsuru, it'll return all variables the service asked Tsuru to export on your application's units (without the values, since you are not gonna need them), if you lost the environments on your terminal history, again, don't fear! You can always check which service made what variables available to your application using the `<insert command here>`.

3.14 Building your app in tsuru

Tsuru is an open source polyglot cloud application platform. With Tsuru, you don't need to think about servers at all. You can write apps in the programming language of your choice, back it with add-on resources such as SQL and NoSQL databases, memcached, redis, and many others. You manage your app using the Tsuru command-line tool and you deploy code using the Git revision control system, all running on the Tsuru infrastructure.

3.14.1 Install the tsuru client

Install the Tsuru client for your development platform.

The the Tsuru client is a command-line tool for creating and managing apps. Check out the [CLI usage guide](#) to learn more.

3.14.2 Sign up

To create an account, you use the `user-create` command:

```
$ tsuru user-create youremail@domain.com
```

`user-create` will ask for your password twice.

3.14.3 Login

To login in tsuru, you use the `login` command, you will be asked for your password:

```
$ tsuru login youremail@domain.com
```

3.14.4 Deploy an application

Choose from the following getting started tutorials to learn how to deploy your first application using a supported language or framework:

- *Deploying Python applications in tsuru*
- *Deploying Ruby/Rails applications in tsuru*
- *Deploying PHP applications in tsuru*

3.15 Coding style

Please follow these coding standards when writing code for inclusion in Tsuru.

3.15.1 Formatting

- Follow the [go formatting style](#)

3.15.2 Naming standards

New<Something>

is used by the <Something> *constructor*:

```
NewApp(name string) (*App, error)
```

Add<Something>

is a *method* of a type that has a collection of <Something>'s. Should receive an instance of <Something>:

```
func (a *App) AddUnit(u *Unit) error
```

Add

is a collection *method* that adds one or more elements:

```
func (a *AppList) Add( apps ...*App) error
```

Create<Something>

it's a *function* that's save an instance of <Something> in the database. Should receives an instance of <Something>.

```
func CreateApp(a *App) error
```

Delete<Something>

it's a *function* that's delete an instance of <Something> from database.

Remove<Something>

it's opposite of Add<Something>.

3.16 Setting up you tsuru development environment

To install tsuru from source, you need to have Go installed and configured. This file will guide you through the necessary steps to get tsuru's development environment.

3.16.1 Installing Go

You need to install the last version of Go to compile tsuru. You can download binaries distribution from [Go website](#) or use your preferred package installer (like Homebrew on Mac OS and apt-get on Ubuntu):

```
$ [sudo] apt-get install golang
$ brew install go
```

3.16.2 Installing MongoDB

tsuru uses MongoDB (+2.2), so you need to install it. For that, you can follow instructions on MongoDB website and download binary distributions (<http://www.mongodb.org/downloads>). You can also use your preferred package installer:

```
$ sudo apt-key adv --keyserver keyserver.ubuntu.com --recv 7F0CEB10
$ sudo bash -c 'echo "deb http://downloads-distro.mongodb.org/repo/ubuntu-upstart dist 10gen" > /etc
$ sudo apt-get update
$ sudo apt-get install mongodb-10gen -y
$ brew install mongodb
```

3.16.3 Installing Beanstalkd

Tsuru uses [Beanstalkd](#) as a work queue. Install the latest version, by doing this:

```
$ sudo apt-get install -y beanstalkd
$ brew install beanstalkd
```

3.16.4 Installing Redis

One of Tsuru routing providers uses [Redis](#) to store information about frontends and backends. You will also need to install it:

```
$ sudo apt-get install -y redis-server
$ brew install redis
```

3.16.5 Installing git, bazaar and mercurial

tsuru depends on go libs that use git, bazaar and mercurial, so you need to install these two version control systems to get and compile tsuru from source.

To install git, you can use your package installer:

```
$ sudo apt-get install git
$ brew install git
```

To install bazaar, follow the instructions in bazaar's website (<http://wiki.bazaar.canonical.com/Download>), or use your package installer:

```
$ sudo apt-get install bazaar
$ brew install bazaar
```

To install mercurial, you can also follow instructions on its website (<http://mercurial.selenic.com/downloads/>) or use your package installer:

```
$ sudo apt-get install mercurial
$ brew install mercurial
```

3.16.6 Setting up GOPATH and cloning the project

Go uses an environment variable called GOPATH to allow users to develop using the go build tool (<http://golang.org/cmd/go>). So you need to setup this variable before cloning and installing tsuru. You can set this variable to your \$HOME directory, or something like *\$HOME/gocode*.

Once you have defined the GOPATH variable, then run the following commands:

```
$ mkdir -p $GOPATH/src/github.com/globocom
$ cd $GOPATH/src/github.com/globocom
$ git clone git://github.com/globocom/tsuru
```

If you have already cloned the repository, just move the cloned directory to *\$GOPATH/src/github.com/globocom*.

For more details on GOPATH, please check this url: http://golang.org/cmd/go/#GOPATH_environment_variable

3.16.7 Starting Redis, Beanstalkd and MongoDB

Before building the code and running the tests, execute the following commands to start Redis, Beanstalkd and MongoDB processes.

```
$ redis-server
$ mongod
$ beanstalkd -l 127.0.0.1
```

3.16.8 Installing tsuru dependencies and running tests

You can use *make* to install all tsuru dependencies and run tests. It will also check if everything is ok with your GOPATH setup:

```
$ make
```

3.17 Installing tsuru clients

tsuru contains three clients: `tsuru`, `tsuru-admin` and `crane`.

- **tsuru** is the command line utility used by application developers, that will allow users to create, list, bind and manage apps. For more details, check [tsuru usage](#);
- **crane** is used by service administrators. For more detail, check [crane usage](#);
- **tsuru-admin** is used by cloud administrators. Whoever is allowed to use it has gotten super powers :-)

This document describes how you can install those clients, using pre-compiled binaries or building them from source.

Using homebrew (Mac OS X only)

Using the PPA (Ubuntu only)

Pre-built binaries (Linux and Mac OS X)

Build from source (Linux and Mac OS X)

3.17.1 Using homebrew (Mac OS X only)

Mavericks note: Go 1.1 fails to compile with clang. In order to install Tsuru on Mavericks, you will need to install Go 1.2rc, running `brew install go --devel`.

If you use Mac OS X and [homebrew](#), you may use a custom tap to install `tsuru`, `crane` and `tsuru-admin`. First you need to add the tap:

```
$ brew tap globocom/homebrew-tsuru
```

Now you can install `tsuru`, `tsuru-admin` and `crane`:

```
$ brew install tsuru
$ brew install tsuru-admin
$ brew install crane
```

Whenever a new version of any of tsuru's clients is out, you can just run:

```
$ brew update
$ brew upgrade <formula> # tsuru/tsuru-admin/crane
```

For more details on taps, check [homebrew documentation](#).

NOTE: Tsuru requires Go 1.1 or higher. Make sure you have the last version of Go installed in your system.

3.17.2 Using the PPA (Ubuntu only)

Ubuntu users can install Tsuru clients using `apt-get` and the [Tsuru PPA](#). You'll need to add the PPA repository locally and run an `apt-get update`:

```
$ sudo apt-add-repository ppa:tsuru/ppa
$ sudo apt-get update
```

Now you can install Tsuru's clients:

```
$ sudo apt-get install tsuru
$ sudo apt-get install crane
$ sudo apt-get install tsuru-admin
```

3.17.3 Pre-built binaries (Linux and Mac OS X)

tsuru clients are also distributed in binary version, so you can just download an executable and put them somewhere in your `PATH`.

It's important to note that all binaries are platform dependent. Currently, we provide each of them in three flavors:

1. **darwin_amd64**: This is Mac OS X, 64 bits. Make sure the command `uname -ms` prints "Darwin x86_64", otherwise this binary will not work in your system;
2. **linux_386**: This is Linux, 32 bits. Make sure the command `uname -ms` prints "Linux x86", otherwise this binary will not work in your system;
3. **linux_amd64**: This is Linux, 64 bits. Make sure the command `uname -ms` prints "Linux x86_64", otherwise this binary will not work in your system.

Below are the links to the binaries, you can just download, extract the archive and put the binary somewhere in your `PATH`:

darwin_amd64

- tsuru: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-darwin-amd64.tar.gz>
- tsuru-admin: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-admin-darwin-amd64.tar.gz>
- crane: <https://s3.amazonaws.com/tsuru/dist-cmd/crane-darwin-amd64.tar.gz>

linux_386

- tsuru: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-linux-386.tar.gz>
- tsuru-admin: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-admin-linux-386.tar.gz>
- crane: <https://s3.amazonaws.com/tsuru/dist-cmd/crane-linux-386.tar.gz>

linux_amd64

- tsuru: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-linux-amd64.tar.gz>
- tsuru-admin: <https://s3.amazonaws.com/tsuru/dist-cmd/tsuru-admin-linux-amd64.tar.gz>
- crane: <https://s3.amazonaws.com/tsuru/dist-cmd/crane-linux-amd64.tar.gz>

3.17.4 Build from source (Linux and Mac OS X)

Tsuru's source is written in Go, so before installing tsuru from source, please make sure you have installed and configured Go.

With Go installed and configured, you can use `go get` to install any of tsuru's clients:

```
$ go get github.com/globocom/tsuru/cmd/tsuru
$ go get github.com/globocom/tsuru/cmd/tsuru-admin
$ go get github.com/globocom/tsuru/cmd/crane
```

3.18 Howto install a dns forwarder

This document describes how to create a dns forwarder and set a base domain for tsuru.

3.18.1 Overview

The recommended way to use tsuru is integrated with a DNS server. The easiest way to do that is configuring it as a cache forwarder, and configuring a DNS zone to be used for tsuru as required.

3.18.2 Installing Bind

Here you will see how easy is to install a DNS server. Bellow you will see a howto for Ubuntu and Centos

Ubuntu

```
$ apt-get install bind9 bind9utils -y
```

Centos

```
$ yum install bind bind-utils -y
$ chkconfig named on
$ service named start
```

3.18.3 Configuring Bind

Forwarder

First we will show how to configure your DNS as a forwarder. Into the config file, insert the forwarders directive inside the “options” main directive. You can use the google’s public DNS(8.8.8.8/8.8.4.4) as forwarder or your company’s DNS. It should look like that:

Ubuntu

```
$ egrep -v '//$|^$' /etc/bind/named.conf.options
options {
    directory "/var/cache/bind";
    forwarders {
        8.8.8.8;
        8.8.4.4;
    };
    dnssec-validation auto;
    auth-nxdomain no;      # conform to RFC1035
    listen-on-v6 { any; };
};
```

Centos

```
$ egrep -v '///|^$' /etc/named.conf |head
options {
    forwarders { 8.8.8.8; 8.8.4.4; };
    listen-on port 53 { any; };
    listen-on-v6 port 53 { ::1; };
    directory      "/var/named";
    dump-file       "/var/named/data/cache_dump.db";
    statistics-file "/var/named/data/named_stats.txt";
    memstatistics-file "/var/named/data/named_mem_stats.txt";
    allow-query     { any; };
    recursion yes;
```

DNS Zone

Now we will set a DNS Zone to be used by tsuru. In this example we are using the domain cloud.company.com. Create a entrance for that into /etc/bind/named.conf.local(for ubuntu) or /etc/named.conf(for centos) as following:

Ubuntu

```
zone "cloud.company.com" {
    type master;
    file "/etc/bind/db.cloud.company.com";
};
```

Centos

```
zone "cloud.company.com" {
    type master;
    file "db.cloud.company.com";
};
```

And create a db.cloud.company.com file(considering the your external IP for tsuru, hipache and git is 192.168.123.131) the way below:

```
$ cat db.cloud.company.com
;
$TTL      604800
@         IN      SOA      cloud.company.com. tsuru.cloud.company.com. (
                                3             ; Serial
                                604800        ; Refresh
                                86400         ; Retry
                                2419200       ; Expire
                                604800 )     ; Negative Cache TTL
;
@         IN      NS       cloud.company.com.
@         IN      A        192.168.123.131
git       IN      A        192.168.123.131 ; here we can set a better exhibition for the git remote prov
*         IN      A        192.168.123.131
```

Ps: If you have problems, it could be related with the date of your machine. We recommend you to install a ntpd service.

Now just reload your DNS server, point it to your `resolv.conf`, and use Tsuru! To test, just execute the command below, and see if all responses resolve to 192.168.123.131:

```
$ ping cloud.company.com
$ ping git.cloud.company.com
$ ping zzzzz.cloud.company.com
$ ping anydomain.cloud.company.com
```

3.19 Backing up tsuru database

In the tsuru repository, you will find two useful scripts in the directory `misc/mongodb`: `backup.bash` and `healer.bash`. In this page you will learn the purpose of these scripts and how to use them.

3.19.1 Dependencies

The script `backup.bash` uses S3 to store archives, and `healer.bash` downloads archives from S3 buckets. In order to communicate with S3 API, both scripts use `s3cmd`.

So, before running those scripts, make sure you have installed `s3cmd`. You can install it using your preferred package manager. For more details, refer to its [download documentation](#).

After installing `s3cmd`, you will need to configure it, by running the command:

```
$ s3cmd --configure
```

3.19.2 Saving data

The script `backup.bash` runs `mongodump`, creates a tar archive and send the archive to S3. Here is how you use it:

```
$ ./misc/mongodb/backup.bash s3://mybucket localhost database
```

The first parameter is the S3 bucket. The second parameter is the database host. You can provide just the hostname, or the host:port (for example, 127.0.0.1:27018). The third parameter is the name of the database.

3.19.3 Automatically restoring on data loss

The other script in the `misc/mongodb` directory is `healer.bash`. This script checks a list of collections and if any of them is gone, download the last three backup archives and fix all gone collections.

This is how you should use it:

```
$ ./misc/mongodb/healer.bash s3://mybucket localhost mongodb repositories users
```

The first three parameters mean the same as in the backup script. From the fourth parameter onwards, you should list the collections. In the example above, we provided two collections: “repositories” and “users”.

3.20 Server installation guide

3.20.1 Dependencies

Tsuru depends on [Go](#) and [libyaml](#).

To install Go, follow the official instructions in the language website: <http://golang.org/doc/install>.

To install libyaml, you can use one package manager, or download it and install it from source. To install from source, follow the instructions on PyYAML wiki: <http://pyyaml.org/wiki/LibYAML>.

The following instructions are system specific:

FreeBSD

```
$ cd /usr/ports/textproc/libyaml
$ make install clean
```

Mac OS X (homebrew)

```
$ brew install libyaml
```

Ubuntu

```
$ [sudo] apt-get install libyaml-dev
```

CentOS

```
$ [sudo] yum install libyaml-devel
```

3.20.2 Installation

After installing and configuring go, and installing libyaml, just run in your terminal:

```
$ go get github.com/globocom/tsuru/...
```

3.20.3 Server configuration

TODO!

3.21 api workflow

Tsuru sends requests to your service to:

- create a new instance of your service
- bind an app with your service

- unbind an app
- destroy an instance

3.21.1 Creating a new instance

This process begins when a Tsuru customer creates an instance of your service via command line tool:

```
$ tsuru service-add mysql mysql_instance
```

Tsuru calls your service to create a new instance of your service via POST on `/resources` (please notice that tsuru does not include a trailing slash) with the “name” that represents the app name in the request body. Example of request:

```
POST /resources HTTP/1.0
Content-Length: 19
```

```
name=mysql_instance
```

Your API should return the following HTTP response code with the respective response body:

- 201: when the instance is successfully created. You don’t need to include any content in the response body.
- 500: in case of any failure in the creation process. Make sure you include an explanation for the failure in the response body.

3.21.2 Binding an app to a service instance

This process begins when a Tsuru customer binds an app to an instance of your service via command line tool:

```
$ tsuru bind mysql_instance --app my_app
```

Tsuru calls your service to bind an app with a service instance via POST on `/resources/<service-name>` (please notice that tsuru does not include a trailing slash) with the “hostname” that represents the app hostname in the request body. Example of request:

```
POST /resources/mysql_instance HTTP/1.0
Content-Length: 25
```

```
hostname=myapp.myhost.com
```

Your API should return the following HTTP response code with the respective response body:

- 201: if the app is successfully binded to the instance. The response body must be a JSON containing the environment variables from this instance that should be exported in the app in order to connect to the instance. If your service does not export any environment variable, write `null` or `{ }` in the response body. Example of response:

```
HTTP/1.1 201 CREATED
Content-Type: application/json; charset=UTF-8
```

```
{"MYSQL_HOST": "10.10.10.10", "MYSQL_PORT": 3306, "MYSQL_USER": "ROOT", "MYSQL_PASSWORD": "s3cr3t", "MYSQL_D"
```

Status codes for errors in the process:

- 404: if the service instance does not exist. You don’t need to include any content in the response body.
- 412: if the service instance is still being provisioned, and not ready for binding yet. You can optionally include an explanation in the response body.

- 500: in case of any failure in the bind process. Make sure you include an explanation for the failure in the response body.

3.21.3 Unbind an app from a service instance

This process begins when a Tsuru customer unbinds an app from an instance of your service via command line tool:

```
$ tsuru unbind mysql_instance --app my_app
```

Tsuru calls your service to unbind an app with a service instance via DELETE on `/resources/<service-name>/hostname/<app-hostname>` (please notice that tsuru does not include a trailing slash). Example of request:

```
DELETE /resources/mysql_instance/hostname/myapp.myhost.com HTTP/1.0
Content-Length: 0
```

Your API should return the following HTTP response code with the respective response body:

- 200: if the app is successfully unbinded from the instance. You don't need to include any content in the response body.
- 404: if the service instance does not exist. You don't need to include any content in the response body.
- 500: in case of any failure in the unbind process. Make sure you include an explanation for the failure in the response body.

3.21.4 Destroying an instance

This process begins when a Tsuru customer removes an instance of your service via command line tool:

```
$ tsuru service-remove mysql_instance
```

Tsuru calls your service to remove an instance of your service via DELETE on `/resources/<service-name>` (please notice that tsuru does not include a trailing slash). Example of request:

```
DELETE /resources/mysql_instance HTTP/1.0
Content-Length: 0
```

Your API should return the following HTTP response code with the respective response body:

- 200: if the service is successfully destroyed. You don't need to include any content in the response body.
- 404: if the service instance does not exist. You don't need to include any content in the response body.
- 500: in case of any failure in the destroy process. Make sure you include an explanation for the failure in the response body.

3.21.5 Checking the status of an instance

This process begins when a Tsuru customer wants to check the status of an instance via command line tool:

```
$ tsuru service-status mysql_instance
```

Tsuru calls your service to check the status of the instance via GET on `/resources/mysql_instance/status` (please notice that tsuru does not include a trailing slash). Example of request:

```
GET /resources/mysql_instance/status HTTP/1.0
```

Your API should return the following HTTP response code, with the respective response body:

- 202: the instance is still being provisioned (pending). You don't need to include any content in the response body.
- 204: the instance is running and ready for connections (running). You don't need to include any content in the response body.
- 500: the instance is not running, nor ready for connections. Make sure you include the reason why the instance is not running.

3.21.6 Additional info about an instance

You can add additional info about instances of your service. To do it it's needed to implement the resource below:

```
GET /resources/mysql_instance HTTP/1.0
```

Your API should return the following HTTP response code, with the respective body:

- 404: when your api doesn't have extra info about the service instance. You don't need to include any content in the response body.
- 200: when your app has an extra info about the service instance. The response body must be a JSON containing a list of fields. A field is composed by two key/value's *label* and *value*:

```
HTTP/1.1 200 OK
```

```
Content-Type: application/json; charset=UTF-8
```

```
[{"label": "my label", "value": "my value"}, {"label": "myLabel2.0", "value": "my value 2.0"}]
```

3.22 Building your service

3.22.1 Overview

This document is a hands-on guide to turning your existing cloud service into a Tsuru service.

In order to create a service you need to implement a provisioning API for your service, which Tsuru will call using [HTTP protocol](#) when a customer creates a new instance or binds a service instance with an app.

You will also need to create a YAML document that will serve as the service manifest. We provide a command-line tool to help you to create this manifest and manage your service.

3.22.2 Creating your service api

To create your service api you can use any programming language or framework. In this tutorial we will use [flask](#).

Prerequisites

First, let's be sure that Python and pip are already installed:

```
$ python --version
Python 2.7.2
```

```
$ pip
```

Usage: pip COMMAND [OPTIONS]

pip: error: You must give a `command` (use `"pip help"` to see a list of commands)

For more information about how to install python you can see the [Python download documentation](#) and about how to install pip you can see the [pip installation instructions](#).

Now, with python and pip installed, you can use pip to install flask:

```
$ pip install flask
```

With flask installed let's create a file called `api.py` and add the code to create a minimal flask app:

```
from flask import Flask
app = Flask(__name__)

@app.route("/")
def hello():
    return "Hello World!"

if __name__ == "__main__":
    app.run()
```

For run this app you can do:

```
$ python api.py
* Running on http://127.0.0.1:5000/
```

If you open your web browser and access the url `"http://127.0.0.1:5000/"` you will see the "Hello World!".

Then, you need to implement the resources expected by the *Tsuru api workflow*.

Provisioning the resource for new instances

For new instances tsuru sends a POST to `/resources` with the "name" that represents the service instance name in the request body. If the service instance is successfully created, your API should return 201 in status code.

Let's create a method for this action:

```
@app.route("/resources", methods=["POST"])
def add_instance():
    return "", 201
```

Implementing the bind

In the bind action, tsuru calls your service via POST on `/resources/<service_name>/` with the "app-hostname" that represents the app hostname and the "unit-hostname" that represents the unit hostname on body.

If the app is successfully binded to the instance, you should return 201 as status code with the variables to be exported in the app environment on body with the json format.

As an example, let's create a method that returns a json with a fake variable called "SOMEVAR" to be injected in the app environment. To do it in flask you need to import the `jsonify` method.

```
from flask import jsonify

@app.route("/resources/<name>", methods=["POST"])
def bind(name):
```

```
out = jsonify(SOMEVAR="somevalue")
return out, 201
```

Implementing the unbinding

In the unbind action, tsuru calls your service via DELETE on `/resources/<service_name>/hostname/<unit_hostname>/`.

If the app is successfully unbinded from the instance you should return 200 as status code.

Let's create a method for this action:

```
@app.route("/resources/<name>/hostname/<host>", methods=["DELETE"])
def unbind(name, host):
    return "", 200
```

Implementing the destroy service instance

In the destroy action, tsuru calls your service via DELETE on `/resources/<service_name>/`.

If the service instance is successfully removed you should return 200 as status code.

Let's create a method for this action:

```
@app.route("/resources/<name>", methods=["DELETE"])
def remove_instance(name):
    return "", 200
```

Implementing the url for status checking

To check the status of an instance, tsuru uses the url `/resources/<service_name>/status`. If the instance is ok, this URL should return 204.

Let's create a function for this action:

```
@app.route("/resources/<name>/status", methods=["GET"])
def status(name):
    return "", 204
```

The final code for our “fake api” developed in flask is:

```
from flask import Flask
from flask import jsonify

app = Flask(__name__)

@app.route("/resources/<name>", methods=["POST"])
def bind(name):
    out = jsonify(SOMEVAR="somevalue")
    return out, 201

@app.route("/resources/<name>/hostname/<host>", methods=["DELETE"])
def unbind(name, host):
    return "", 200
```

```
@app.route("/resources", methods=["POST"])
def add_instance():
    return "", 201

@app.route("/resources/<name>", methods=["DELETE"])
def remove_instance(name, host):
    return "", 200

@app.route("/resources/<name>/status", methods=["GET"])
def status(name):
    return "", 204

if __name__ == "__main__":
    app.run()
```

3.22.3 Creating a service manifest

Using crane you can create a manifest template:

```
$ crane template
```

This will create a manifest.yaml in your current path with this content:

```
id: servicename
endpoint:
  production: production-endpoint.com
  test: test-endpoint.com:8080
```

The manifest.yaml is used by crane to defined an id and an endpoint to your service.

Change the id and the endpoint values with the information of your service:

```
id: fakeserviceid1
endpoint:
  production: fakeserviceid1.com
```

3.22.4 Submitting your service

To submit your service, you can run:

```
$ crane create manifest.yaml
```

3.23 HOWTO Install a MySQL service

First, you must have a [MariaDB server](#), the best “mysql” server in the market. You can also use the standard mysql-server.

```
# Ubuntu 13.04
$ sudo apt-get install software-properties-common
$ sudo gpg --keyserver hkp://keyserver.ubuntu.com:80 --recv-keys CBCB082A1BB943DB
$ sudo gpg -a --export CBCB082A1BB943DB | apt-key add -
```



```
$ sudo add-apt-repository 'deb http://mirror.aarnet.edu.au/pub/MariaDB/repo/10.0/ubuntu raring main'
$ sudo apt-get update
$ sudo apt-get install mariadb-server

# Centos - creating the mariadb repository
$ cat > /etc/yum.repos.d/MariaDB.repo <<END
# MariaDB 10.0 CentOS repository list - created 2013-09-13 13:25 UTC
# http://mariadb.org/mariadb/repositories/
[mariadb]
name = MariaDB
baseurl = http://yum.mariadb.org/10.0/centos6-amd64
gpgkey=https://yum.mariadb.org/RPM-GPG-KEY-MariaDB
gpgcheck=1
END
$ rpm --import https://yum.mariadb.org/RPM-GPG-KEY-MariaDB
$ yum install MariaDB-server MariaDB-client
$ service mysql start
$ chkconfig mysql on
```

After that, all you need is to create a database admin user for this service, with all necessary grants

```
# Creating a database user(log into the database with the root user)
> GRANT ALL PRIVILEGES ON *.* TO 'tsuru'@'%' IDENTIFIED BY 'password' with GRANT OPTION;
> FLUSH PRIVILEGES;
```

Now, you will install our mysql-api service example. Just create an application that will be responsible for this service

```
# Create a database for this service (change the 192.168.123.131 for your mysql server host)
$ echo "CREATE DATABASE mysqlapi" | mysql -h 192.168.123.131 -u tsuru -ppassword
# In a machine with tsuru client and crane installed
$ git clone https://github.com/globocom/mysqlapi
# Create the mysqlapi application using python as its platform.
$ tsuru app-create mysql-api python
```

In order to have mysql API ready to receive requests, we need some bootstrap stuff.

```
#First export the django settings variable:
$ tsuru env-set --app mysql-api DJANGO_SETTINGS_MODULE=mysqlapi.settings
# Inject the right environment for that service
$ tsuru env-set -a mysql-api MYSQLAPI_DB_NAME=mysqlapi
$ tsuru env-set -a mysql-api MYSQLAPI_DB_USER=tsuru
$ tsuru env-set -a mysql-api MYSQLAPI_DB_PASSWORD=password
$ tsuru env-set -a mysql-api MYSQLAPI_DB_HOST=192.168.123.131
# To show the application's repository
$ tsuru app-info -a mysql-api|grep Repository
Repository: git@192.168.123.131:mysql-api.git
$ git push git@192.168.123.131:mysql-api.git master
#Now gunicorn is able to run with our wsgi.py configuration. After that, we need to run syncdb:
$ tsuru run --app mysql-api -- python manage.py syncdb --noinput
```

To run the API in shared mode, follow this steps

```
# First export the needed variables:
# If the shared mysql database is installed in the same vm that the app is, you can use localhost for
$ tsuru env-set --app mysql-api MYSQLAPI_SHARED_SERVER=192.168.123.131
# Here you'll also need to set up a externally accessible endpoint to be used by the apps that are u
$ tsuru env-set --app mysql-api MYSQLAPI_SHARED_SERVER_PUBLIC_HOST=192.168.123.131
# Here the mysql user to manage the shared databases
$ tsuru env-set -a mysql-api MYSQLAPI_SHARED_USER=tsuru
$ tsuru env-set -a mysql-api MYSQLAPI_SHARED_PASSWORD=password
```

More information about the ways you can work with that api you can found [here](#).

Now you should have your application working. You just need to submit the mysqlapi service via crane. The manifest.yaml is used by crane to define an id and an endpoint to your service. For more details, see the text “Services API Workflow”: <http://docs.tsuru.io/en/latest/services/api.html> To submit your new service, you can run:

```
# Configure the service template and point it to the application service (considering that your domain is example.com)
$ cat manifest.yaml
id: mysqlapi
  endpoint:
    production: mysql-api.cloud.company.com
$ crane create manifest.yaml
```

To list your services:

```
$ crane list
#OR
$ tsuru service-list
```

This will return something like:

```
+-----+-----+
| Services | Instances |
+-----+-----+
| mysqlapi |           |
+-----+-----+
```

It would be nice if your service had some documentation. To add a documentation to you service you can use:

```
$ crane doc-add mysqlapi doc.txt
```

Crane will read the content of the file and save it.

To show the current documentation of your service:

```
$ crane doc-get mysqlapi
```

doc-get will retrieve the current documentation of the service.

3.23.1 Further instructions

Now you can add this service for your applications using the [bind](#) command

For a complete reference, check the documentation for [crane](#) command: <http://godoc.org/github.com/globocom/tsuru/cmd/crane>.

3.24 Crane usage

First, you must set the target with your server url, like:

```
$ crane target tsuru.myhost.com
```

After that, all you need is to create a user and authenticate:

```
$ crane user-create youremail@gmail.com
$ crane login youremail@gmail.com
```

To generate a service template:

```
$ crane template
```

This will create a manifest.yaml in your current path with this content:

```
id: servicename
endpoint:
  production: production-endpoint.com
  test: test-endpoint.com:8080
```

The manifest.yaml is used by crane to define an id and an endpoint to your service.

To submit your new service, you can run:

```
$ crane create path/to/your/manifest.yaml
```

To list your services:

```
$ crane list
```

This will return something like:

```
+-----+-----+
| Services | Instances |
+-----+-----+
| mysql    | my_db     |
+-----+-----+
```

To update a service manifest:

```
$ crane create path/to/your/manifest.yaml
```

To remove a service:

```
$ crane remove service_name
```

It would be nice if your service had some documentation. To add a documentation to you service you can use:

```
$ crane doc-add service_name path/to/your/docfile
```

Crane will read the content of the file and save it.

To show the current documentation of your service:

```
$ crane doc-get service_name
```

3.24.1 Further instructions

For a complete reference, check the documentation for crane command: <http://godoc.org/github.com/globocom/tsuru/cmd/crane>.

3.25 Services

You can manage your services using the tsuru command-line interface.

To list all services available you can use, you can use the `service-list` command:

```
$ tsuru service-list
```

To add a new instance of a service, use the `service-add` command:

```
$ tsuru service-add <service_name> <service_instance_name>
```

To remove an instance of a service, use the `service-remove` command:

```
$ tsuru service-remove <service_instance_name>
```

To bind a service instance with an app you can use the `bind` command. If this service has any variable to be used by your app, tsuru will inject this variables in the app's environment.

```
$ tsuru bind <service_instance_name> [--app appname]
```

And to unbind, use `unbind` command:

```
$ tsuru unbind <service_instance_name> [--app appname]
```

For more details on the `--app` flag, see “[Guessing app names](#)” section of tsuru command documentation.

3.26 Client usage

After installing the server, build the `cmd/main.go` file with the name you wish, and add it to your `$PATH`. Here we'll call it *tsuru*. Then you must set the target with your server url, like:

3.26.1 Setting a target

```
$ tsuru target-add default tsuru.myhost.com:8080
$ tsuru target-set default
```

3.26.2 Authentication

After that, all you need is to create a user and authenticate to start creating apps and pushing code to them. Use `create-user` and `login`:

```
$ tsuru user-create youremail@gmail.com
$ tsuru login youremail@gmail.com
```

3.26.3 Apps

Associating your user to a team

You need to be member of a team to create an app. To create a new team, use `create-team`:

```
$ tsuru team-create teamname
```

Creating an app

To create an app, use `app-create`:

```
$ tsuru app-create myblog <platform>
```

This will return your app's remote url, you should add it to your git repository:

```
$ git remote add tsuru git@tsuru.myhost.com:myblog.git
```

Listing your apps

When your app is ready, you can push to it. To check whether it is ready or not, you can use `app-list`:

```
$ tsuru app-list
```

This will return something like:

```
+-----+-----+-----+-----+
| Application | Units State Summary | Ip |
+-----+-----+-----+-----+
| myblog      | 1 of 1 units in-service | myblog-838381.us-east-1-elb.amazonaws.com |
+-----+-----+-----+-----+
```

Showing app info

You can also use the `app-info` command to view information of an app. Including the status of the app:

```
$ tsuru app-info
```

This will return something like:

```
Application: myblog
Platform: gunicorn
Repository: git@githost.com:myblog.git
Teams: team1, team2
Units:
+-----+-----+
| Unit    | State  |
+-----+-----+
| myblog/0 | started |
| myblog/1 | started |
+-----+-----+
```

Tsuru uses information from git configuration to guess the name of the app, for more details, see “Guessing app names” section of tsuru command documentation.

3.26.4 Public Keys

You can try to push now, but you'll get a permission error, because you haven't pushed your key yet.

```
$ tsuru key-add
```

This will search for a `id_rsa.pub` file in `~/.ssh/`, if you don't have a generated key yet, you should generate one before running this command.

If you have a public key in other format (for example, DSA), you can also give the public key file to `key-add`:

```
$ tsuru key-add $HOME/.ssh/id_dsa.pub
```

After your key is added, you can push your application to your cloud:

```
$ git push tsuru master
```

3.26.5 Running commands

After that, you can check your app's url in the browser and see your app there. You'll probably need to run migrations or other deploy related commands. To run a single command, you should use the command `run`:

```
$ tsuru run "python manage.py syncdb && python manage.py migrate"
```

3.26.6 Further instructions

For a complete reference, check the documentation for tsuru command: <http://godoc.org/github.com/globocom/tsuru/cmd/tsuru>.

3.27 Deploying PHP applications in tsuru

3.27.1 Overview

This document is a hands-on guide to deploying a simple PHP application in Tsuru. The example application will be a very simple Wordpress project associated to a MySQL service. It's applicable to any php over apache application.

3.27.2 Creating the app within tsuru

To create an app, you use `app-create` command:

```
$ tsuru app-create <app-name> <app-platform>
```

For PHP, the app platform is, guess what, php! Let's be over creative and develop a never-developed tutorial-app: a blog, and its name will also be very creative, let's call it "blog":

```
$ tsuru app-create blog php
```

To list all available platforms, use `platform-list` command.

You can see all your applications using `app-list` command:

```
$ tsuru app-list
+-----+-----+-----+-----+-----+
| Application | Units State Summary | Address | Ready? |
+-----+-----+-----+-----+-----+
| blog       | 0 of 0 units in-service |         | No      |
+-----+-----+-----+-----+-----+
```

Once your app is ready, you will be able to deploy your code, e.g.:

```
$ tsuru app-list
+-----+-----+-----+-----+-----+
| Application | Units State Summary | Address | Ready? |
+-----+-----+-----+-----+-----+
```

```
+-----+-----+-----+-----+
| blog      | 0 of 1 units in-service |           | Yes      |
+-----+-----+-----+-----+
```

3.27.3 Application code

This document will not focus on how to write a php blog, you can download the entire source direct from wordpress: <http://wordpress.org/latest.zip>. Here is all you need to do with your project:

```
# Download and unpack wordpress
$ wget http://wordpress.org/latest.zip
$ unzip latest.zip
# Preparing wordpress for tsuru
$ cd wordpress
# Notify tsuru about the necessary packages
$ echo php5-mysql > requirements.apt
# Preparing the application to receive the tsuru environment related to the mysql service
$ sed "s/'database_name_here'/getenv('MYSQL_DATABASE_NAME')/; \
      s/'username_here'/getenv('MYSQL_USER')/; \
      s/'localhost'/getenv('MYSQL_HOST')/; \
      s/'password_here'/getenv('MYSQL_PASSWORD')/" \
      wp-config-sample.php > wp-config.php
# Creating a local git repository
$ git init
$ git add .
$ git commit -m 'initial project version'
```

3.27.4 Git deployment

When you create a new app, tsuru will display the Git remote that you should use. You can always get it using `app-info` command:

```
$ tsuru app-info --app blog
Application: blog
Repository: git@git.tsuru.io:blog.git
Platform: php
Teams: tsuruteam
Address:
```

The git remote will be used to deploy your application using git. You can just push to tsuru remote and your project will be deployed:

```
$ git push git@git.tsuru.io:blog.git master
Counting objects: 119, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (53/53), done.
Writing objects: 100% (119/119), 16.24 KiB, done.
Total 119 (delta 55), reused 119 (delta 55)
remote:
remote: ---> Tsuru receiving push
remote:
remote: From git://cloud.tsuru.io/blog.git
remote: * branch                master      -> FETCH_HEAD
remote:
remote: ---> Installing dependencies
#####
```

```
#          OMIT (see below)          #
#####
remote: ---> Restarting your app
remote:
remote: ---> Deploy done!
remote:
To git@git.tsuru.io:blog.git
    a211fba..bbf5b53  master -> master
```

If you get a “Permission denied (publickey).”, make sure you’re member of a team and have a public key added to tsuru. To add a key, use `key-add` command:

```
$ tsuru key-add ~/.ssh/id_dsa.pub
```

You can use `git remote add` to avoid typing the entire remote url every time you want to push:

```
$ git remote add tsuru git@git.tsuru.io:blog.git
```

Then you can run:

```
$ git push tsuru master
Everything up-to-date
```

And you will be also able to omit the `--app` flag from now on:

```
$ tsuru app-info
Application: blog
Repository: git@git.tsuru.io:blog.git
Platform: php
Teams: tsuruteam
Address: blog.cloud.tsuru.io
Units:
+-----+-----+
| Unit           | State   |
+-----+-----+
| 9e70748f4f25  | started |
+-----+-----+
```

For more details on the `--app` flag, see “Guessing app names” section of tsuru command documentation.

3.27.5 Listing dependencies

In the last section we omitted the dependencies step of deploy. In tsuru, an application can have two kinds of dependencies:

- **Operating system dependencies**, represented by packages in the package manager of the underlying operating system (e.g.: `yum` and `apt-get`);
- **Platform dependencies**, represented by packages in the package manager of the platform/language (e.g. in Python, `pip`).

All `apt-get` dependencies must be specified in a `requirements.apt` file, located in the root of your application, and `pip` dependencies must be located in a file called `requirements.txt`, also in the root of the application. Since we will use MySQL with PHP, we need to install the package depends on just one `apt-get` package: `php5-mysql`, so here is how `requirements.apt` looks like:

```
php5-mysql
```

You can see the complete output of installing these dependencies bellow:


```
% git push tsuru master
#####
#                               #
#####
Counting objects: 1155, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (1124/1124), done.
Writing objects: 100% (1155/1155), 4.01 MiB | 327 KiB/s, done.
Total 1155 (delta 65), reused 0 (delta 0)
remote: Cloning into '/home/application/current'...
remote: Reading package lists...
remote: Building dependency tree...
remote: Reading state information...
remote: The following extra packages will be installed:
remote:  libmysqlclient18 mysql-common
remote: The following NEW packages will be installed:
remote:  libmysqlclient18 mysql-common php5-mysql
remote: 0 upgraded, 3 newly installed, 0 to remove and 0 not upgraded.
remote: Need to get 1042 kB of archives.
remote: After this operation, 3928 kB of additional disk space will be used.
remote: Get:1 http://archive.ubuntu.com/ubuntu/ quantal/main mysql-common all 5.5.27-0ubuntu2 [13.7 kB]
remote: Get:2 http://archive.ubuntu.com/ubuntu/ quantal/main libmysqlclient18 amd64 5.5.27-0ubuntu2 [13.7 kB]
remote: Get:3 http://archive.ubuntu.com/ubuntu/ quantal/main php5-mysql amd64 5.4.6-1ubuntu1 [79.0 kB]
remote: Fetched 1042 kB in 1s (739 kB/s)
remote: Selecting previously unselected package mysql-common.
remote: (Reading database ... 23874 files and directories currently installed.)
remote: Unpacking mysql-common (from ../mysql-common_5.5.27-0ubuntu2_all.deb) ...
remote: Selecting previously unselected package libmysqlclient18:amd64.
remote: Unpacking libmysqlclient18:amd64 (from ../libmysqlclient18_5.5.27-0ubuntu2_amd64.deb) ...
remote: Selecting previously unselected package php5-mysql.
remote: Unpacking php5-mysql (from ../php5-mysql_5.4.6-1ubuntu1_amd64.deb) ...
remote: Processing triggers for libapache2-mod-php5 ...
remote:  * Reloading web server config
remote:  ...done.
remote: Setting up mysql-common (5.5.27-0ubuntu2) ...
remote: Setting up libmysqlclient18:amd64 (5.5.27-0ubuntu2) ...
remote: Setting up php5-mysql (5.4.6-1ubuntu1) ...
remote: Processing triggers for libc-bin ...
remote: ldconfig deferred processing now taking place
remote: Processing triggers for libapache2-mod-php5 ...
remote:  * Reloading web server config
remote:  ...done.
remote: sudo: unable to resolve host 8cf20f4da877
remote: sudo: unable to resolve host 8cf20f4da877
remote: debconf: unable to initialize frontend: Dialog
remote: debconf: (Dialog frontend will not work on a dumb terminal, an emacs shell buffer, or without a tty)
remote: debconf: falling back to frontend: Readline
remote: debconf: unable to initialize frontend: Dialog
remote: debconf: (Dialog frontend will not work on a dumb terminal, an emacs shell buffer, or without a tty)
remote: debconf: falling back to frontend: Readline
remote:
remote: Creating config file /etc/php5/mods-available/mysql.ini with new version
remote: debconf: unable to initialize frontend: Dialog
remote: debconf: (Dialog frontend will not work on a dumb terminal, an emacs shell buffer, or without a tty)
remote: debconf: falling back to frontend: Readline
remote:
remote: Creating config file /etc/php5/mods-available/mysqlcli.ini with new version
remote: debconf: unable to initialize frontend: Dialog
```

```
remote: debconf: (Dialog frontend will not work on a dumb terminal, an emacs shell buffer, or without
remote: debconf: falling back to frontend: Readline
remote:
remote: Creating config file /etc/php5/mods-available/pdo_mysql.ini with new version
remote:
remote: ---> App will be restarted, please check its log for more details...
remote:
To git@git.tsuru.io:ingress.git
* [new branch]      master -> master
```

3.27.6 Running the application

As you can see, in the deploy output there is a step described as “App will be restarted”. In this step, tsuru will restart your app if it’s running, or start it if it’s not. Now that the app is deployed, you can access it from your browser, getting the IP or host listed in `app-list` and opening it. For example, in the list below:

```
$ tsuru app-list
+-----+-----+-----+-----+
| Application | Units State Summary | Address | Ready? |
+-----+-----+-----+-----+
| blog        | 1 of 1 units in-service | blog.cloud.tsuru.io | Yes    |
+-----+-----+-----+-----+
```

3.27.7 Using services

Now that php is running, we can access the application in the browser, but we get a database connection error: “*Error establishing a database connection*”. This error means that we can’t connect to MySQL. That’s because we should not connect to MySQL on localhost, we must use a service. The service workflow can be resumed to two steps:

1. Create a service instance
2. Bind the service instance to the app

But how can I see what services are available? Easy! Use `service-list` command:

```
$ tsuru service-list
+-----+-----+
| Services | Instances |
+-----+-----+
| mongodb  |           |
| mysql     |           |
+-----+-----+
```

The output from `service-list` above says that there are two available services: “elastic-search” and “mysql”, and no instances. To create our MySQL instance, we should run the `service-add` command:

```
$ tsuru service-add mysql blogsql
Service successfully added.
```

Now, if we run `service-list` again, we will see our new service instance in the list:

```
$ tsuru service-list
+-----+-----+
| Services | Instances |
+-----+-----+
| elastic-search |           |
+-----+-----+
```

```
| mysql          | blogsql      |
+-----+-----+
```

To bind the service instance to the application, we use the `bind` command:

```
$ tsuru bind blogsql
Instance blogsql is now bound to the app blog.
```

The following environment variables are now available **for** use in your app:

```
- MYSQL_PORT
- MYSQL_PASSWORD
- MYSQL_USER
- MYSQL_HOST
- MYSQL_DATABASE_NAME
```

For more details, please check the documentation **for** the service, using `service-doc` command.

As you can see from `bind` output, we use environment variables to connect to the MySQL server. Next step would be update the `wp-config.php` to use these variables to connect in the database:

```
$ grep getenv wp-config.php
define('DB_NAME', getenv('MYSQL_DATABASE_NAME'));
define('DB_USER', getenv('MYSQL_USER'));
define('DB_PASSWORD', getenv('MYSQL_PASSWORD'));
define('DB_HOST', getenv('MYSQL_HOST'));
```

You can extend your wordpress installing plugins into your repository. In the example bellow, we are installing the W3 Total Cache, adding the Amazon S3 capability to wordpress

```
$ cd wp-content/plugins/
$ wget http://downloads.wordpress.org/plugin/w3-total-cache.0.9.3.zip
$ unzip w3-total-cache.0.9.3.zip
$ rm w3-total-cache.0.9.3.zip
$ git add w3-total-cache/
$ git commit -m 'adding plugin for caching and S3'
$ git push tsuru master
```

It's done! Now we have a PHP project deployed on tsuru, using a MySQL service.

3.27.8 Going further

For more information, you can dig into [tsuru docs](#), or read [complete instructions of use for the tsuru command](#).

3.28 Deploying Python applications in tsuru

3.28.1 Overview

This document is a hands-on guide to deploying a simple Python application in Tsuru. The example application will be a very simple Django project associated to a MySQL service. It's applicable to any WSGI application.

3.28.2 Creating the app within tsuru

To create an app, you use `app-create` command:

```
$ tsuru app-create <app-name> <app-platform>
```

For Python, the app platform is, guess what, python! Let's be over creative and develop a never-developed tutorial-app: a blog, and its name will also be very creative, let's call it "blog":

```
$ tsuru app-create blog python
```

To list all available platforms, use `platform-list` command.

You can see all your applications using `app-list` command:

```
$ tsuru app-list
+-----+-----+-----+-----+
| Application | Units State Summary | Address | Ready? |
+-----+-----+-----+-----+
| blog        | 0 of 0 units in-service |         | No      |
+-----+-----+-----+-----+
```

Once your app is ready, you will be able to deploy your code, e.g.:

```
$ tsuru app-list
+-----+-----+-----+-----+
| Application | Units State Summary | Address | Ready? |
+-----+-----+-----+-----+
| blog        | 0 of 1 units in-service |         | Yes     |
+-----+-----+-----+-----+
```

3.28.3 Application code

This document will not focus on how to write a Django blog, you can clone the entire source direct from GitHub: <https://github.com/globocom/tsuru-django-sample>. Here is what we did for the project:

1. Create the project (`django-admin.py startproject`)
2. Enable django-admin
3. Install South
4. Create a "posts" app (`django-admin.py startapp posts`)
5. Add a "Post" model to the app
6. Register the model in django-admin
7. Generate the migration using South

3.28.4 Git deployment

When you create a new app, tsuru will display the Git remote that you should use. You can always get it using `app-info` command:

```
$ tsuru app-info --app blog
Application: blog
Repository: git@git.tsuru.io:blog.git
Platform: python
Teams: tsuruteam
Address:
```

The git remote will be used to deploy your application using git. You can just push to tsuru remote and your project will be deployed:

```
$ git push git@git.tsuru.io:blog.git master
Counting objects: 119, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (53/53), done.
Writing objects: 100% (119/119), 16.24 KiB, done.
Total 119 (delta 55), reused 119 (delta 55)
remote:
remote: ---> Tsuru receiving push
remote:
remote: From git://cloud.tsuru.io/blog.git
remote: * branch                master      -> FETCH_HEAD
remote:
remote: ---> Installing dependencies
#####
#          OMIT (see below)          #
#####
remote: ---> Restarting your app
remote:
remote: ---> Deploy done!
remote:
To git@git.tsuru.io:blog.git
    a211fba..bbf5b53  master -> master
```

If you get a “Permission denied (publickey).”, make sure you’re member of a team and have a public key added to tsuru. To add a key, use `key-add` command:

```
$ tsuru key-add ~/.ssh/id_rsa.pub
```

You can use `git remote add` to avoid typing the entire remote url every time you want to push:

```
$ git remote add tsuru git@git.tsuru.io:blog.git
```

Then you can run:

```
$ git push tsuru master
Everything up-to-date
```

And you will be also able to omit the `--app` flag from now on:

```
$ tsuru app-info
Application: blog
Repository: git@git.tsuru.io:blog.git
Platform: python
Teams: tsuruteam
Address: blog.cloud.tsuru.io
Units:
+-----+-----+
| Unit           | State   |
+-----+-----+
| 9e70748f4f25  | started |
+-----+-----+
```

For more details on the `--app` flag, see “Guessing app names” section of tsuru command documentation.

3.28.5 Listing dependencies

In the last section we omitted the dependencies step of deploy. In tsuru, an application can have two kinds of dependencies:

- **Operating system dependencies**, represented by packages in the package manager of the underlying operating system (e.g.: `yum` and `apt-get`);
- **Platform dependencies**, represented by packages in the package manager of the platform/language (in Python, `pip`).

All `apt-get` dependencies must be specified in a `requirements.apt` file, located in the root of your application, and `pip` dependencies must be located in a file called `requirements.txt`, also in the root of the application. Since we will use MySQL with Django, we need to install `mysql-python` package using `pip`, and this package depends on two `apt-get` packages: `python-dev` and `libmysqlclient-dev`, so here is how `requirements.apt` looks like:

```
libmysqlclient-dev
python-dev
```

And here is `requirements.txt`:

```
Django==1.4.1
MySQL-python==1.2.3
South==0.7.6
```

Please notice that we've included `South` too, for database migrations, and `Django`, off-course.

You can see the complete output of installing these dependencies bellow:

```
% git push tsuru master
#####
#                               #
#####
remote: Reading package lists...
remote: Building dependency tree...
remote: Reading state information...
remote: python-dev is already the newest version.
remote: The following extra packages will be installed:
remote:  libmysqlclient18 mysql-common
remote: The following NEW packages will be installed:
remote:  libmysqlclient-dev libmysqlclient18 mysql-common
remote: 0 upgraded, 3 newly installed, 0 to remove and 0 not upgraded.
remote: Need to get 2360 kB of archives.
remote: After this operation, 9289 kB of additional disk space will be used.
remote: Get:1 http://archive.ubuntu.com/ubuntu/ quantal/main mysql-common all 5.5.27-0ubuntu2 [13.7 K]
remote: Get:2 http://archive.ubuntu.com/ubuntu/ quantal/main libmysqlclient18 amd64 5.5.27-0ubuntu2 [13.7 K]
remote: Get:3 http://archive.ubuntu.com/ubuntu/ quantal/main libmysqlclient-dev amd64 5.5.27-0ubuntu2 [2332 K]
remote: debconf: unable to initialize frontend: Dialog
remote: debconf: (Dialog frontend will not work on a dumb terminal, an emacs shell buffer, or without a controlling tty.)
remote: debconf: falling back to frontend: Readline
remote: debconf: unable to initialize frontend: Readline
remote: debconf: (This frontend requires a controlling tty.)
remote: debconf: falling back to frontend: Teletype
remote: dpkg-preconfigure: unable to re-open stdin:
remote: Fetched 2360 kB in 1s (1285 kB/s)
remote: Selecting previously unselected package mysql-common.
remote: (Reading database ... 23143 files and directories currently installed.)
remote: Unpacking mysql-common (from .../mysql-common_5.5.27-0ubuntu2_all.deb) ...
remote: Selecting previously unselected package libmysqlclient18:amd64.
```

```

remote: Unpacking libmysqlclient18:amd64 (from ../libmysqlclient18_5.5.27-0ubuntu2_amd64.deb) ...
remote: Selecting previously unselected package libmysqlclient-dev.
remote: Unpacking libmysqlclient-dev (from ../libmysqlclient-dev_5.5.27-0ubuntu2_amd64.deb) ...
remote: Setting up mysql-common (5.5.27-0ubuntu2) ...
remote: Setting up libmysqlclient18:amd64 (5.5.27-0ubuntu2) ...
remote: Setting up libmysqlclient-dev (5.5.27-0ubuntu2) ...
remote: Processing triggers for libc-bin ...
remote: ldconfig deferred processing now taking place
remote: sudo: Downloading/unpacking Django==1.4.1 (from -r /home/application/current/requirements.txt)
remote:   Running setup.py egg_info for package Django
remote:
remote: Downloading/unpacking MySQL-python==1.2.3 (from -r /home/application/current/requirements.txt)
remote:   Running setup.py egg_info for package MySQL-python
remote:
remote:   warning: no files found matching 'MANIFEST'
remote:   warning: no files found matching 'ChangeLog'
remote:   warning: no files found matching 'GPL'
remote: Downloading/unpacking South==0.7.6 (from -r /home/application/current/requirements.txt (line
remote:   Running setup.py egg_info for package South
remote:
remote: Installing collected packages: Django, MySQL-python, South
remote:   Running setup.py install for Django
remote:     changing mode of build/scripts-2.7/django-admin.py from 644 to 755
remote:
remote:     changing mode of /usr/local/bin/django-admin.py to 755
remote: Running setup.py install for MySQL-python
remote:   building '_mysql' extension
remote:   gcc -pthread -fno-strict-aliasing -DNDEBUG -g -fwrapv -O2 -Wall -Wstrict-prototypes -fPI
remote:   In file included from _mysql.c:36:0:
remote:   /usr/include/mysql/my_config.h:422:0: warning: "HAVE_WCSCOLL" redefined [enabled by default]
remote:   In file included from /usr/include/python2.7/Python.h:8:0,
remote:   from pymemcompat.h:10,
remote:   from _mysql.c:29:
remote:   /usr/include/python2.7/pyconfig.h:890:0: note: this is the location of the previous definition
remote:   gcc -pthread -shared -Wl,-O1 -Wl,-Bsymbolic-functions -Wl,-Bsymbolic-functions -Wl,-z,relro
remote:
remote:   warning: no files found matching 'MANIFEST'
remote:   warning: no files found matching 'ChangeLog'
remote:   warning: no files found matching 'GPL'
remote:   Running setup.py install for South
remote:
remote: Successfully installed Django MySQL-python South
remote: Cleaning up...
#####
#               OMIT               #
#####
To git@git.tsuru.io:blog.git
a211fba..bbf5b53  master -> master

```

3.28.6 Running the application

As you can see, in the deploy output there is a step described as “Restarting your app”. In this step, tsuru will restart your app if it’s running, or start it if it’s not. But how does tsuru start an application? That’s very simple, it uses a Procfile (a concept stolen from Foreman). In this Procfile, you describe how your application should be started. We can use [gunicorn](#), for example, to start our Django application. Here is how the Procfile should look like:

```
web: gunicorn -b 0.0.0.0:$PORT blog.wsgi
```

Now we commit the file and push the changes to tsuru git server, running another deploy:

```
$ git add Procfile
$ git commit -m "Procfile: added file"
$ git push tsuru master
Counting objects: 5, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 326 bytes, done.
Total 3 (delta 1), reused 0 (delta 0)
remote:
remote: ---> Tsuru receiving push
remote:
remote: ---> Installing dependencies
remote: Reading package lists...
remote: Building dependency tree...
remote: Reading state information...
remote: python-dev is already the newest version.
remote: libmysqlclient-dev is already the newest version.
remote: 0 upgraded, 0 newly installed, 0 to remove and 1 not upgraded.
remote: Requirement already satisfied (use --upgrade to upgrade): Django==1.4.1 in /usr/local/lib/python2.7/site-packages
remote: Requirement already satisfied (use --upgrade to upgrade): MySQL-python==1.2.3 in /usr/local/lib/python2.7/site-packages
remote: Requirement already satisfied (use --upgrade to upgrade): South==0.7.6 in /usr/local/lib/python2.7/site-packages
remote: Cleaning up...
remote:
remote: ---> Restarting your app
remote: /var/lib/tsuru/hooks/start: line 13: gunicorn: command not found
remote:
remote: ---> Deploy done!
remote:
To git@git.tsuru.io:blog.git
 81e884e..530c528 master -> master
```

Now we get an error: `gunicorn: command not found`. It means that we need to add gunicorn to `requirements.txt` file:

```
$ cat >> requirements.txt
gunicorn==0.14.6
^D
```

Now we commit the changes and run another deploy:

```
$ git add requirements.txt
$ git commit -m "requirements.txt: added gunicorn"
$ git push tsuru master
Counting objects: 5, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (3/3), done.
Writing objects: 100% (3/3), 325 bytes, done.
Total 3 (delta 1), reused 0 (delta 0)
remote:
remote: ---> Tsuru receiving push
remote:
remote: [...]
remote: ---> Restarting your app
remote:
remote: ---> Deploy done!
```



```
remote:
To git@git.tsuru.io:blog.git
    530c528..542403a  master -> master
```

Now that the app is deployed, you can access it from your browser, getting the IP or host listed in `app-list` and opening it. For example, in the list below:

```
$ tsuru app-list
+-----+-----+-----+-----+
| Application | Units State Summary | Address | Ready? |
+-----+-----+-----+-----+
| blog        | 1 of 1 units in-service | blog.cloud.tsuru.io | Yes    |
+-----+-----+-----+-----+
```

We can access the admin of the app in the URL <http://blog.cloud.tsuru.io/admin/>.

3.28.7 Using services

Now that gunicorn is running, we can access the application in the browser, but we get a Django error: “*Can’t connect to local MySQL server through socket ‘/var/run/mysqld/mysqld.sock’ (2)*”. This error means that we can’t connect to MySQL on localhost. That’s because we should not connect to MySQL on localhost, we must use a service. The service workflow can be resumed to two steps:

1. Create a service instance
2. Bind the service instance to the app

But how can I see what services are available? Easy! Use `service-list` command:

```
$ tsuru service-list
+-----+-----+
| Services | Instances |
+-----+-----+
| elastic-search | |
| mysql          | |
+-----+-----+
```

The output from `service-list` above says that there are two available services: “elastic-search” and “mysql”, and no instances. To create our MySQL instance, we should run the `service-add` command:

```
$ tsuru service-add mysql blogsql
Service successfully added.
```

Now, if we run `service-list` again, we will see our new service instance in the list:

```
$ tsuru service-list
+-----+-----+
| Services | Instances |
+-----+-----+
| elastic-search | |
| mysql          | blogsql   |
+-----+-----+
```

To bind the service instance to the application, we use the `bind` command:

```
$ tsuru bind blogsql
Instance blogsql is now bound to the app blog.
```

The following environment variables are now available **for** use in your app:

```
- MYSQL_PORT
- MYSQL_PASSWORD
- MYSQL_USER
- MYSQL_HOST
- MYSQL_DATABASE_NAME
```

For more details, please check the documentation [for](#) the service, using `service-doc` command.

As you can see from bind output, we use environment variables to connect to the MySQL server. Next step is update `settings.py` to use these variables to connect in the database:

```
import os

DATABASES = {
    'default': {
        'ENGINE': 'django.db.backends.mysql',
        'NAME': os.environ.get('MYSQL_DATABASE_NAME', 'blog'),
        'USER': os.environ.get('MYSQL_USER', 'root'),
        'PASSWORD': os.environ.get('MYSQL_PASSWORD', ''),
        'HOST': os.environ.get('MYSQL_HOST', ''),
        'PORT': os.environ.get('MYSQL_PORT', ''),
    }
}
```

Now let's commit it and run another deploy:

```
$ git add blog/settings.py
$ git commit -m "settings: using environment variables to connect to MySQL"
$ git push tsuru master
Counting objects: 7, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (4/4), done.
Writing objects: 100% (4/4), 535 bytes, done.
Total 4 (delta 3), reused 0 (delta 0)
remote:
remote: ---> Tsuru receiving push
remote:
remote: ---> Installing dependencies
#####
#                               #
#####
remote:
remote: ---> Restarting your app
remote:
remote: ---> Deploy done!
remote:
To git@git.tsuru.io:blog.git
ab4e706..a780de9 master -> master
```

Now if we try to access the admin again, we will get another error: *“Table ‘blogsqli.django_session’ doesn’t exist”*. Well, that means that we have access to the database, so bind worked, but we did not set up the database yet. We need to run `syncdb` and `migrate` (if we’re using South) in the remote server. We can use `run` command to execute commands in the machine, so for running `syncdb` we could write:

```
$ tsuru run -- python manage.py syncdb --noinput
Syncing...
Creating tables ...
Creating table auth_permission
```

```

Creating table auth_group_permissions
Creating table auth_group
Creating table auth_user_user_permissions
Creating table auth_user_groups
Creating table auth_user
Creating table django_content_type
Creating table django_session
Creating table django_site
Creating table django_admin_log
Creating table south_migrationhistory
Installing custom SQL ...
Installing indexes ...
Installed 0 object(s) from 0 fixture(s)

```

Synced:

```

> django.contrib.auth
> django.contrib.contenttypes
> django.contrib.sessions
> django.contrib.sites
> django.contrib.messages
> django.contrib.staticfiles
> django.contrib.admin
> south

```

Not synced (use migrations):

```
- blog.posts
```

(use ./manage.py migrate to migrate these)

The same applies for migrate.

3.28.8 Deployment hooks

It would be boring to manually run `syncdb` and/or `migrate` after every deployment. So we can configure an automatic hook to always run before or after the app restarts.

Tsuru parses a file called `app.yaml` and runs restart hooks. As the extension suggests, this is a YAML file, that contains a list of commands that should run before and after the restart. Here is our example of `app.yaml`:

```

hooks:
  restart:
    after:
      - python manage.py syncdb --noinput
      - python manage.py migrate

```

For more details, check the [hooks documentation](#).

Tsuru will look for the file in the root of the project. Let's commit and deploy it:

```

$ git add app.yaml
$ git commit -m "app.yaml: added file"
$ git push tsuru master
Counting objects: 4, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (3/3), done.
Writing objects: 100% (3/3), 338 bytes, done.
Total 3 (delta 1), reused 0 (delta 0)
remote:
remote: ---> Tsuru receiving push

```

```
remote:
remote: ---> Installing dependencies
remote: Reading package lists...
remote: Building dependency tree...
remote: Reading state information...
remote: python-dev is already the newest version.
remote: libmysqlclient-dev is already the newest version.
remote: 0 upgraded, 0 newly installed, 0 to remove and 15 not upgraded.
remote: Requirement already satisfied (use --upgrade to upgrade): Django==1.4.1 in /usr/local/lib/python2.7/dist-packages
remote: Requirement already satisfied (use --upgrade to upgrade): MySQL-python==1.2.3 in /usr/local/lib/python2.7/dist-packages
remote: Requirement already satisfied (use --upgrade to upgrade): South==0.7.6 in /usr/local/lib/python2.7/dist-packages
remote: Requirement already satisfied (use --upgrade to upgrade): gunicorn==0.14.6 in /usr/local/lib/python2.7/dist-packages
remote: Cleaning up...
remote:
remote: ---> Restarting your app
remote:
remote: ---> Running restart:after
remote:
remote: ---> Deploy done!
remote:
To git@git.tsuru.io:blog.git
    a780de9..1b675b8  master -> master
```

It's done! Now we have a Django project deployed on tsuru, using a MySQL service.

3.28.9 Going further

For more information, you can dig into [tsuru docs](#), or read [complete instructions of use for the tsuru command](#).

3.29 Deploying Ruby applications in tsuru

3.29.1 Overview

This document is a hands-on guide to deploying a simple Ruby application in Tsuru. The example application will be a very simple Rails project associated to a MySQL service.

3.29.2 Creating the app within tsuru

To create an app, you use `app-create` command:

```
$ tsuru app-create <app-name> <app-platform>
```

For Ruby, the app platform is, guess what, ruby! Let's be over creative and develop a never-developed tutorial-app: a blog, and its name will also be very creative, let's call it "blog":

```
$ tsuru app-create blog ruby
```

To list all available platforms, use `platform-list` command.

You can see all your applications using `app-list` command:

```
$ tsuru app-list
+-----+-----+-----+-----+
| Application | Units State Summary | Address | Ready? |
```

```
+-----+-----+-----+-----+
| blog      | 0 of 0 units in-service |      | No      |
+-----+-----+-----+-----+
```

Once your app is ready, you will be able to deploy your code, e.g.:

```
$ tsuru app-list
+-----+-----+-----+-----+
| Application | Units State Summary      | Address      | Ready? |
+-----+-----+-----+-----+
| blog        | 0 of 0 units in-service |              | Yes    |
+-----+-----+-----+-----+
```

3.29.3 Application code

This document will not focus on how to write a blog with Rails, you can clone the entire source direct from GitHub: <https://github.com/globocom/tsuru-ruby-sample>. Here is what we did for the project:

1. Create the project (`rails new blog`)
2. Generate the scaffold for Post (`rails generate scaffold Post title:string body:text`)

3.29.4 Git deployment

When you create a new app, tsuru will display the Git remote that you should use. You can always get it using `app-info` command:

```
$ tsuru app-info --app blog
Application: blog
Repository: git@cloud.tsuru.io:blog.git
Platform: ruby
Teams: tsuruteam
Address:
```

The git remote will be used to deploy your application using git. You can just push to tsuru remote and your project will be deployed:

```
$ git push git@cloud.tsuru.io:blog.git master
Counting objects: 86, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (75/75), done.
Writing objects: 100% (86/86), 29.75 KiB, done.
Total 86 (delta 2), reused 0 (delta 0)
remote: Cloning into '/home/application/current'...
remote: requirements.txt not found.
remote: Skipping...
remote: /home/application/current /
remote: Fetching gem metadata from https://rubygems.org/.....
remote: Fetching gem metadata from https://rubygems.org/..
#####
#          OMIT (see below)          #
#####
remote: --> App will be restarted, please check its log for more details...
remote:
To git@cloud.tsuru.io:blog.git
* [new branch]      master -> master
```

If you get a “Permission denied (publickey).”, make sure you’re member of a team and have a public key added to tsuru. To add a key, use `key-add` command:

```
$ tsuru key-add ~/.ssh/id_rsa.pub
```

You can use `git remote add` to avoid typing the entire remote url every time you want to push:

```
$ git remote add tsuru git@cloud.tsuru.io:blog.git
```

Then you can run:

```
$ git push tsuru master
Everything up-to-date
```

And you will be also able to omit the `--app` flag from now on:

```
$ tsuru app-info
Application: blog
Repository: git@cloud.tsuru.io:blog.git
Platform: ruby
Teams: tsuruteam
Address: blog.cloud.tsuru.io
Units:
+-----+-----+
| Unit           | State   |
+-----+-----+
| 9e70748f4f25   | started |
+-----+-----+
```

For more details on the `--app` flag, see “[Guessing app names](#)” section of tsuru command documentation.

3.29.5 Listing dependencies

In the last section we omitted the dependencies step of deploy. In tsuru, an application can have two kinds of dependencies:

- **Operating system dependencies**, represented by packages in the package manager of the underlying operating system (e.g.: `yum` and `apt-get`);
- **Platform dependencies**, represented by packages in the package manager of the platform/language (in Ruby, `bundler`).

All `apt-get` dependencies must be specified in a `requirements.apt` file, located in the root of your application, and ruby dependencies must be located in a file called `Gemfile`, also in the root of the application. Since we will use MySQL with Rails, we need to install `mysql` package using `gem`, and this package depends on an `apt-get` package: `libmysqlclient-dev`, so here is how `requirements.apt` looks like:

```
libmysqlclient-dev
```

And here is `Gemfile`:

```
source 'https://rubygems.org'

gem 'rails', '3.2.13'
gem 'mysql'
gem 'sass-rails', '~> 3.2.3'
gem 'coffee-rails', '~> 3.2.1'
gem 'therubyracer', :platforms => :ruby
gem 'uglifier', '>= 1.0.3'
gem 'jquery-rails'
```

You can see the complete output of installing these dependencies below:

```
$ git push tsuru master
#####
#                OMIT                #
#####
remote: Reading package lists...
remote: Building dependency tree...
remote: Reading state information...
remote: The following extra packages will be installed:
remote:   libmysqlclient18 mysql-common
remote: The following NEW packages will be installed:
remote:   libmysqlclient-dev libmysqlclient18 mysql-common
remote: 0 upgraded, 3 newly installed, 0 to remove and 0 not upgraded.
remote: Need to get 2360 kB of archives.
remote: After this operation, 9289 kB of additional disk space will be used.
remote: Get:1 http://archive.ubuntu.com/ubuntu/ quantal/main mysql-common all 5.5.27-0ubuntu2 [13.7 kB]
remote: Get:2 http://archive.ubuntu.com/ubuntu/ quantal/main libmysqlclient18 amd64 5.5.27-0ubuntu2 [13.7 kB]
remote: Get:3 http://archive.ubuntu.com/ubuntu/ quantal/main libmysqlclient-dev amd64 5.5.27-0ubuntu2 [2360 kB]
remote: Fetched 2360 kB in 2s (1112 kB/s)
remote: Selecting previously unselected package mysql-common.
remote: (Reading database ... 41063 files and directories currently installed.)
remote: Unpacking mysql-common (from .../mysql-common_5.5.27-0ubuntu2_all.deb) ...
remote: Selecting previously unselected package libmysqlclient18:amd64.
remote: Unpacking libmysqlclient18:amd64 (from .../libmysqlclient18_5.5.27-0ubuntu2_amd64.deb) ...
remote: Selecting previously unselected package libmysqlclient-dev.
remote: Unpacking libmysqlclient-dev (from .../libmysqlclient-dev_5.5.27-0ubuntu2_amd64.deb) ...
remote: Setting up mysql-common (5.5.27-0ubuntu2) ...
remote: Setting up libmysqlclient18:amd64 (5.5.27-0ubuntu2) ...
remote: Setting up libmysqlclient-dev (5.5.27-0ubuntu2) ...
remote: Processing triggers for libc-bin ...
remote: ldconfig deferred processing now taking place
remote: /home/application/current /
remote: Fetching gem metadata from https://rubygems.org/.....
remote: Fetching gem metadata from https://rubygems.org/..
remote: Using rake (10.1.0)
remote: Using i18n (0.6.1)
remote: Using multi_json (1.7.8)
remote: Using activesupport (3.2.13)
remote: Using builder (3.0.4)
remote: Using activemodel (3.2.13)
remote: Using erubis (2.7.0)
remote: Using journey (1.0.4)
remote: Using rack (1.4.5)
remote: Using rack-cache (1.2)
remote: Using rack-test (0.6.2)
remote: Using hike (1.2.3)
remote: Using tilt (1.4.1)
remote: Using sprockets (2.2.2)
remote: Using actionpack (3.2.13)
remote: Using mime-types (1.23)
remote: Using polyglot (0.3.3)
remote: Using treetop (1.4.14)
remote: Using mail (2.5.4)
remote: Using actionmailer (3.2.13)
remote: Using arel (3.0.2)
remote: Using tzinfo (0.3.37)
remote: Using activerecord (3.2.13)
remote: Using activerecord (3.2.13)
```

```
remote: Using coffee-script-source (1.6.3)
remote: Using execjs (1.4.0)
remote: Using coffee-script (2.2.0)
remote: Using rack-ssl (1.3.3)
remote: Using json (1.8.0)
remote: Using rdoc (3.12.2)
remote: Using thor (0.18.1)
remote: Using railties (3.2.13)
remote: Using coffee-rails (3.2.2)
remote: Using jquery-rails (3.0.4)
remote: Installing libv8 (3.11.8.17)
remote: Installing mysql (2.9.1)
remote: Using bundler (1.3.5)
remote: Using rails (3.2.13)
remote: Installing ref (1.0.5)
remote: Using sass (3.2.10)
remote: Using sass-rails (3.2.6)
remote: Installing therubyracer (0.11.4)
remote: Installing uglifier (2.1.2)
remote: Your bundle is complete!
remote: Gems in the groups test and development were not installed.
remote: It was installed into ./vendor/bundle
#####
#                OMIT                #
#####
To git@cloud.tsuru.io:blog.git
    9515685..d67c3cd  master -> master
```

3.29.6 Running the application

As you can see, in the deploy output there is a step described as “Restarting your app”. In this step, tsuru will restart your app if it’s running, or start it if it’s not. But how does tsuru start an application? That’s very simple, it uses a Procfile (a concept stolen from Foreman). In this Procfile, you describe how your application should be started. Here is how the Procfile should look like:

```
web: bundle exec rails server -p $PORT -e production
```

Now we commit the file and push the changes to tsuru git server, running another deploy:

```
$ git add Procfile
$ git commit -m "Procfile: added file"
$ git push tsuru master
#####
#                OMIT                #
#####
remote: ---> App will be restarted, please check its log for more details...
remote:
To git@cloud.tsuru.io:blog.git
    d67c3cd..f2a5d2d  master -> master
```

Now that the app is deployed, you can access it from your browser, getting the IP or host listed in `app-list` and opening it. For example, in the list below:

```
$ tsuru app-list
+-----+-----+-----+-----+
| Application | Units State Summary | Address | Ready? |
+-----+-----+-----+-----+
```



```
| blog          | 1 of 1 units in-service | blog.cloud.tsuru.io | Yes      |
+-----+-----+-----+-----+
```

3.29.7 Using services

Now that your app is not running with success because the rails can't connect to MySQL. That's because we add a relation between your rails app and a mysql instance. To do it we must use a service. The service workflow can be resumed to two steps:

1. Create a service instance
2. Bind the service instance to the app

But how can I see what services are available? Easy! Use `service-list` command:

```
$ tsuru service-list
+-----+-----+
| Services      | Instances |
+-----+-----+
| elastic-search |           |
| mysql         |           |
+-----+-----+
```

The output from `service-list` above says that there are two available services: “elastic-search” and “mysql”, and no instances. To create our MySQL instance, we should run the `service-add` command:

```
$ tsuru service-add mysql blogsql
Service successfully added.
```

Now, if we run `service-list` again, we will see our new service instance in the list:

```
$ tsuru service-list
+-----+-----+
| Services      | Instances |
+-----+-----+
| elastic-search |           |
| mysql         | blogsql   |
+-----+-----+
```

To bind the service instance to the application, we use the `bind` command:

```
$ tsuru bind blogsql
Instance blogsql is now bound to the app blog.
```

The following environment variables are now available **for** use in your app:

```
- MYSQL_PORT
- MYSQL_PASSWORD
- MYSQL_USER
- MYSQL_HOST
- MYSQL_DATABASE_NAME
```

For more details, please check the documentation **for** the service, using `service-doc` command.

As you can see from `bind` output, we use environment variables to connect to the MySQL server. Next step is update `conf/database.yml` to use these variables to connect in the database:

```
production:
  adapter: mysql
```

```
encoding: utf8
database: <%= ENV["MYSQL_DATABASE_NAME"] %>
pool: 5
username: <%= ENV["MYSQL_USER"] %>
password: <%= ENV["MYSQL_PASSWORD"] %>
host: <%= ENV["MYSQL_HOST"] %>
```

Now let's commit it and run another deploy:

```
$ git add conf/database.yml
$ git commit -m "database.yml: using environment variables to connect to MySQL"
$ git push tsuru master
Counting objects: 7, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (4/4), done.
Writing objects: 100% (4/4), 535 bytes, done.
Total 4 (delta 3), reused 0 (delta 0)
remote:
remote: ---> Tsuru receiving push
remote:
remote: ---> Installing dependencies
#####
#                OMIT                #
#####
remote:
remote: ---> Restarting your app
remote:
remote: ---> Deploy done!
remote:
To git@cloud.tsuru.io:blog.git
ab4e706..a780de9 master -> master
```

Now if we try to access the admin again, we will get another error: “*Table ‘blogsql.django_session’ doesn’t exist*”. Well, that means that we have access to the database, so bind worked, but we did not set up the database yet. We need to run `rake db:migrate` in the remote server. We can use `run` command to execute commands in the machine, so for running `rake db:migrate` we could write:

```
$ tsuru run -- RAILS_ENV=production bundle exec rake db:migrate
== CreatePosts: migrating =====
-- create_table(:posts)
-> 0.1126s
== CreatePosts: migrated (0.1128s) =====
```

3.29.8 Deployment hooks

It would be boring to manually run `rake db:migrate` after every deployment. So we can configure an automatic hook to always run before or after the app restarts.

Tsuru parses a file called `app.yaml` and runs restart hooks. As the extension suggests, this is a YAML file, that contains a list of commands that should run before and after the restart. Here is our example of `app.yaml`:

```
hooks:
  restart:
    before-each:
      - RAILS_ENV=production bundle exec rake db:migrate
```

For more details, check the [hooks documentation](#).

Tsuru will look for the file in the root of the project. Let's commit and deploy it:

```
$ git add app.yaml
$ git commit -m "app.yaml: added file"
$ git push tsuru master
#####
#                OMIT                #
#####
To git@cloud.tsuru.io:blog.git
a780de9..1b675b8  master -> master
```

It is necessary to compile the assets before the app restart. To do it we can use the `rake assets:precompile` command. Then let's add the command to compile the assets in `app.yaml`:

```
hooks:
  restart:
    before:
      - RAILS_ENV=production bundle exec rake assets:precompile

$ git add app.yaml
$ git commit -m "app.yaml: added file"
$ git push tsuru master
#####
#                OMIT                #
#####
To git@cloud.tsuru.io:blog.git
a780de9..1b675b8  master -> master
```

It's done! Now we have a Rails project deployed on tsuru, using a MySQL service.

Now we can access your *blog app* in the URL <http://blog.cloud.tsuru.io/posts/>.

3.29.9 Going further

For more information, you can dig into [tsuru docs](#), or read [complete instructions of use for the tsuru command](#).

3.30 Docker Provisioner Architecture

This document describes how tsuru works when configured with docker provisioner. [Docker](#)

The docker provisioner is responsible for provisioning your application units. Everytime you perform an action in your application Tsuru repasses the request with specific parameters to the configured provisioner. In this document you will learn how the docker provisioner reacts facing those actions.

Given the app creation -> deploy workflow.

3.30.1 App Provisioning

When you create an application Tsuru asks the provisioner to provision the application, the docker provisioner will do nothing in this action, the only change is that Tsuru creates the application on the database. Docker provisioner will wait until you perform a deploy, so it can create a base image to your application.

3.30.2 Deployment

When you perform a git push into your application repository on Tsuru the custom `pre-receive git hook` is triggered, this hook will ask Tsuru to deploy your application, Tsuru will then repass the action to docker. Docker will run a container, clone your application code to it and install all dependencies specified by your application, then it will generate an image of that container and store its id on the database, this container is then destroyed and a new one is run starting your application. This allows an easy and fast scalability for your application, whenever you need a new unit Tsuru can deploy one in a few seconds.

Every deploy will trigger this process, resulting in a new image with the deployed version and new dependencies if any.

3.30.3 HTTP Routing

Because containers are ephemeral their routes changes everytime a deploy is performed. So we need an easy and fast way to manage routes to containers, by default the docker provisioner uses `Hipache` router. Routes to containers are managed transparently by the docker provisioner. The hipache router also acts as a load balancer to the containers, distributing traffic using a round robin algorithm.