
WebDispatch Documentation

Release 1.0b1

Atsushi Odagiri

November 18, 2014

| | |
|----------------------------------------------------------------|-----------|
| 1 Basic Usage | 3 |
| 1.1 Install | 3 |
| 1.2 URL Dispatch | 3 |
| 1.3 Method Dispatch | 3 |
| 1.4 Action Dispatch | 3 |
| 2 Tips and Tricks | 5 |
| 2.1 integrate with WebOb | 5 |
| 2.2 generate absolute url on backend of reverse proxy. | 5 |
| 3 Reference | 7 |
| 4 Indices and tables | 9 |
| Python Module Index | 11 |


```
 1 from webob import Request
 2 from webob.dec import wsgify
 3 from webdispatch import URLDispatcher
 4 from webdispatch.mixins import URLMapperMixin
 5
 6 class MyRequest(Request, URLMapperMixin):
 7     pass
 8
 9 app = URLDispatcher()
10
11 @wsgify(RequestClass=MyRequest)
12 def index(request):
13     url = request.generate_url("hello", xname="webdispatch")
14     return '<a href="%s">Hello</a>' % (url,)
15
16 @wsgify(RequestClass=MyRequest)
17 def hello(request):
18     return "Hello %s" % request.urlvars['xname']
19
20 app.add_url('home', '/', index)
21 app.add_url('hello', '/hello/{xname}', hello)
22
23 if __name__ == '__main__':
24     from wsgiref.simple_server import make_server
25
26     httpd = make_server('0.0.0.0', 8080, app)
27     httpd.serve_forever()
```

Contents:

Basic Usage

1.1 Install

```
$ pip install WebDispatch
```

1.2 URL Dispatch

```
webdispatch.urldispatcher.URLDispatcher

def hello(environ, start_response):
    start_response("200 OK",
                  [('Content-type', 'text/plain')])
    return ["hello"]

def goodbye(environ, start_response):
    start_response("200 OK",
                  [('Content-type', 'text/plain')])
    return ["goodby %s" % environ['wsgiorg.routing_args'][1]['name']]

from webdispatch import URLDispatcher
application = URLDispatcher()
application.add_url('hello', '/hello', hello)
application.add_url('goodbye', '/good-bye', goodbye)

from wsgiref.simple_server import make_server

httpd = make_server('0.0.0.0', 8080, application)
httpd.serve_forever()
```

this is very primitive wsgi application.

1.3 Method Dispatch

```
webdispatch.methoddispatcher.MethodDispatcher
```

1.4 Action Dispatch

Tips and Tricks

2.1 integrate with WebOb

WebOb has wsgify decorator that makes callable wsgi application.

WebDispatch provides `webdispatch.mixins.URLMapperMixin` to add `generate_url` method to Request class.
use generator mixin:

```
class MyRequest(Request, URLMapperMixin):
    pass

@wsgify(RequestClass=MyRequest)
def view(request):
    return "Hello"
```

2.2 generate absolute url on backend of reverse proxy.

When application is forwarded by reverse proxy, below headers are given.

- `HTTP_X_FORWARDED_SERVER`
- `HTTP_X_FORWARDED_HOST`
- `HTTP_X_FORWARDED_FOR`
- `HTTP_X_FORWARDED_SCHEME`
- `HTTP_X_FORWARDED_PROTO`

use `paste.deploy.config.PrefixMiddleware`.

```
[pipeline:main]
pipeline =
    prefix
        app

[filter:prefix]
use = egg:PasteDeploy#prefix
scheme = https
```

Reference

urldispatcher

```
class webdispatch.urldispatcher.URLDispatcher(applications=None,      extra_environ=None,
                                                **kwargs)
```

dispatch applications with url patterns.

add_subroute (*pattern*)

create new URLDispatcher routed by pattern

add_url (*name, pattern, application*)

add url pattern dispatching to application

detect_view_name (*environ*)

detect view name from environ

on_view_not_found (*environ, start_response*)

called when views not found

```
class webdispatch.urldispatcher.URLGenerator(environ, urlmapper)
```

generate url form parameters and url patterns.

generate (*name, **kwargs*)

generate full qualified url for named url pattern with kwargs

make_full_qualified_url (*path*)

append application url to path

```
class webdispatch.urldispatcher.URLMapper(converters=None)
```

find application matched url pattern.

add (*name, pattern*)

add url pattern for name

generate (*name, **kwargs*)

generate url for named url pattern with kwargs

lookup (*path_info*)

lookup url match for path_info

method dispatcher

```
class webdispatch.method dispatcher.ActionDispatcher(action_var_name='action')
```

wsgi application dispatching actions to registered classes

detect_view_name (*environ*)

get view name from routing args

```
on_view_not_found(environ, start_response)
    called when action is not found

register_actionhandler(action_handler)
    register class as action handler

class webdispatch.methoddispatcher.MethodDispatcher(**kwargs)
    dispatch applications with request method.

detect_view_name(environ)
    convert request method to view name

on_view_not_found(_, start_response)
    called when valid view is not found

webdispatch.methoddispatcher.action_handler_adapter(handler_cls, action_name)
    wraps class to wsgi application dispatching action

useful mixin classes

class webdispatch.mixins.URLMapperMixin
    mixin to add generate_url() method.

generate_url(name, **kwargs)
    generate url with urlgenerator used by urldispatch

urlmapper
    get urlmapper object from wsgi environ
```

Indices and tables

- *genindex*
- *modindex*
- *search*

W

`webdispatch.methoddispatcher`, [7](#)
`webdispatch.mixins`, [8](#)
`webdispatch.urldispatcher`, [7](#)

A

action_handler_adapter() (in module webdispatch.methoddispatcher), 8
ActionDispatcher (class in webdispatch.methoddispatcher), 7
add() (webdispatch.urldispatcher.URLMapper method), 7
add_subroute() (webdispatch.urldispatcher.URLDispatcher method), 7
add_url() (webdispatch.urldispatcher.URLDispatcher method), 7

D

detect_view_name() (webdispatch.methoddispatcher.ActionDispatcher method), 7
detect_view_name() (webdispatch.methoddispatcher.MethodDispatcher method), 8
detect_view_name() (webdispatch.urldispatcher.URLDispatcher method), 7

G

generate() (webdispatch.urldispatcher.URLGenerator method), 7
generate() (webdispatch.urldispatcher.URLMapper method), 7
generate_url() (webdispatch.mixins.URLMapperMixin method), 8

L

lookup() (webdispatch.urldispatcher.URLMapper method), 7

M

make_full_qualified_url() (webdispatch.urldispatcher.URLGenerator method), 7

MethodDispatcher (class in webdispatch.methoddispatcher), 8

O

on_view_not_found() (webdispatch.methoddispatcher.ActionDispatcher method), 7
on_view_not_found() (webdispatch.methoddispatcher.MethodDispatcher method), 8
on_view_not_found() (webdispatch.urldispatcher.URLDispatcher method), 7

R

register_actionhandler() (webdispatch.methoddispatcher.ActionDispatcher method), 8

U

URLDispatcher (class in webdispatch.urldispatcher), 7
URLGenerator (class in webdispatch.urldispatcher), 7
URLMapper (class in webdispatch.urldispatcher), 7
urlmapper (webdispatch.mixins.URLMapperMixin attribute), 8

URLMapperMixin (class in webdispatch.mixins), 8

W

webdispatch.methoddispatcher (module), 7
webdispatch.mixins (module), 8
webdispatch.urldispatcher (module), 7